Subject Index

A	C
Acetoxy systems, 299 Acid-base interactions, 87 Acrylic, 29, 144 polymers, 268 Adhesion, coatings D 4541: 1 Adhesion-in-peel C 794: 1, 29, 87, 126 Adhesion, sealant, 105, 201, 238 aluminum, coated, 144 C 719: 1 cleaning and, 74 gloss level and, 117 highway joint seals, 213 tensile, 45 tests for, 87 Aging, accelerated, 45, 64 Aging, heat C 792: 1 Alkoxy systems, 299	Calcium peroxide, 292 Caulk, 29 Channel movement, 29 Cleaning solvents, 74 Climate driven durability tester, 29 Coatings acrylic, 144 D 4541: 1 elastomeric, 245, 260 fluorinated, 144 organic, aluminum, 144 powder, 117 silicone emulsion, 260 Concrete joint sealer D 1190: 201 D 3405: 201 masonry walls, 245 Condensation, 64
C 792: 1	Condensation, 64 Constrained blister test, 105 Cracking, sealant, 10, 299
ASTM standards C 661: 1 C 719: 1 C 792: 1	Crack width, 245 Cure, 64, 299 rates, 292 Curtain wall, 1, 179
C 794: 1, 29, 87, 126 C 920: 292	D
D 1190: 201 D 3405: 201 D 4541: 1 E 330: 1	Deformation, continuous, 299 Degradation, sealant, 10, 45, 311 Deutsches Institut fur Normung DIN 52455, 87 Durability, 64
В	durometer, 1, 45 C 661: 1 climate-driven tester, 29 glass units, dual-sealed, 222
Barium peroxide, 292 Benzamide, 299	E
Blister test, constrained, 105 Blue sky radiation, 311 Building movement, 160 model, 245 Butadience-styrene, 260	Elasticity, 201, 222 viscoelasticity, 213 Elastomeric materials, 213 Elastomeric sealants, 201
=, 200	Liastomeric scarants, 201

Elastomeric wall coatings, 245 Elastomers, 260

F

Failure prevention, sealant, 189 Fillet, 179, 189 Finite element analysis, 213 Fluorinated coatings, 144 Foam bond-breaking tape, 179

G

Glass channel, 29 Glass, insulating, 222, 238, 268 Glazing compounds, solvent-based, 268 Gloss level, 117 Gunning equipment, 268

H

Hardness, 201 indentation, 1 Heat aging, 1 Highrise buildings leakage, 179 sealants for, 160 Highway joint seals, 213

I

International Organization for Standardization ISO/DIS 9047, 87

J

Joints, sealant
design, 179
failure, 189
movement, 299
pavement
D 3405: 201
performance, 74
strength, sealant, 1
stress distributions, 213

L

Lap-shear tests, 87, 105 Latex rubber, 280 Lead dioxide, 292

M

Manganese dioxide, 292
Masonry, 260
Mortar block, 126
Movement, building, 160
profile, 245
Movement, channel, 29
Movement, joint, 299
Mullion cover, 179

O

Oxime cure, 299

P

Peel tests, 87, 105 C 794: 1, 29, 87, 126 Photometer, 311 Phthalate, 292 Pigments, 117 Polarity, 87 Polybutadiene, hydroxylated, 238 Polyester coatings, powder, 117, 144 coatings, wet, 144 resins, 117 Poly(dimethylsiloxane), 280 Polyisobutene, 222 Polysulfide, 238, 292 Polyurethane, 238 Pressure difference, air E 330: 1 Pressure, rate of, 105 Primer, organic solvent based, 74

Q

QUV, 10, 45

R

Reversion, 45 Rubber latex, silicone, 280 Silicone cleaning/priming solution, 74 Silicone emulsion elastomers, 260 Silicone rubber latex, 280 Silicone sealants, 29 adhesion, 87, 117, 144 gloss level, 117 heat stability, 45 oxime, 299 rubber latex, 280 tests for, 1 weathering, artificial, 201 Solvents, surface cleaning, 74 Spectral power distribution, 10 Standards (See also ASTM standards) building construction, 160 Stress analysis, 213 Stress relaxation, 213 Stress concentration, 87 Sunlight, 311 Surface energy, 87, 117, 144 Surface preparation, 126 Surface profile, sealant, 189

T

Tape, foam bond-breaking, 179 Tensile strength, 1, 87 Tensile stress, 222 Tin catalyst, 280 U

Ultraviolet radiation, 10, 45, 64 absorption, 311 aging effect, 238 resistance, 268 Urethane, 45

V

Vinyl acetate polymer, 260 Viscoelasticity, 213 Volatile organic compounds, 268

W

Wall panels, exterior, 160
Wall surface temperature
building movement model, 245
Water-based acrylic sealants, 268
Water permeability, 222, 238, 260
Waterproofing, 245
Weathering, sealant, 10
accelerated, 45
artificial, 29, 64, 201
Weatherometer, 1
Weathersealing, 74

X

Xenon arc, 10