

Subject Index

1

exterior climate,332-351

1-D numerical model,19-44

A

aging,126-143

air transport,369-408

asphalt shingle roof,306-331

B

building envelope,261-305, 213-233

building system,369-408

C

calibration,352-368

closure,144-159

concrete,56-82

construction materials,45-55

corrections,3-18

cup test,3-18

D

data acquisition,194-209

design,213-233

drying,369-408, 352-368

DSC,234-260

E

electrical resistance sensors,179-193

energy rating,109-125

entrapped air,83-105

envelope,369-408, 352-368

experiment,109-125

experimental testing,409-423

F

fiber optic sensors,179-193

field monitoring and

measurements,261-305

G

gypsum,19-44

H

heat transfer,369-408, 352-368,
409-423

heat transfer model,234-260

HVAC,409-423

hygrothermal,194-209

hygrothermal property,56-82

hygrothermal simulation,213-233

I

indoor environment,261-305

indoor relative humidity,409-423

insulation,109-125

L

laboratory,109-125

long-term thermal resistance,126-143

LTTR,126-143

M

mass transfer,369-408, 352-368

mass transfer coefficient,19-44

measurement and absorption

experiment,56-82

micro-environment, 179-193
 modeling, 109-125, 369-408
 modified inverted cup test, 45-55
 moisture, 369-408, 352-368, 306-331,
 179-193, 144-159, 213-233
 moisture pins, 352-368
 moisture transfer, 409-423
 moisture transport, 179-193, 45-55
 monitoring, 179-193

O

OSB, 352-368

P

PCM, 234-260
 permeance, 144-159
 polyurethane, 109-125
 porous material, 19-44
 porous membrane, 409-423

R

radiant ceiling panel, 409-423
 rainfall, 213-233
 residential buildings, 261-305
 retarder, 144-159
 rigid closed-cell plastic foams, 126-
 143
 roof tile, 83-105
 ruggedness study, 45-55

S

saturation, 83-105
 scaling factors, 126-143
 seam, 144-159

sensor, 194-209
 simulation, 234-260
 spray-foam insulation, 306-331
 stone decay, 179-193

T

temperature, 179-193
 testing, 109-125
 thermal insulation, 126-143
 thermal resistance, 126-143
 time-averaged thermal
 resistance, 126-143
 tools, 261-305

U

uncertainty, 194-209, 213-233
 unvented, 306-331

V

vapor barrier, 332-351
 vapor permeability, 3-18
 variability, 56-82
 vented, 306-331
 ventilation drying, 194-209

W

water permeability, 83-105
 water vapor permeance, 332-351
 water vapor transmission, 144-159,
 45-55
 weather data, 213-233
 wood, 19-44
 wood product, 369-408, 352-368
 wood-frame stucco wall, 332-351
 WUFI® computer model, 306-331