Subject Index

A	Compressed gas cables, 112 Cone calorimeter, 160 Cooling liquid, 18
Acid gas, 160 Aging, accelerated, 136	Corrosivity, 160 Coulometric titration
Antimony oxide, 151	D 1533, 59
ASTM Committee D-9 on	Cycloaliphatic chlorinated
Electrical and Electronic	compound, 151
Insulating Materials, 3, 13, 30	·D
ASTM Committee D-11 on Rubber, 3	ď
ASTM Committee D-20 on	Dechlorane Plus, 151
Plastics, 3	Diagnostics, transformers, 47
ASTM Committee D-27 on	Dielectrics, 3, 13, 18
Insulating Liquids and	Discharge pattern recognition
Gases, 3, 18 ASTM standards, 82, 112	112 Disruptive discharge, 99
D 69 3	Dissolved gas analysis, 47, 70
D 69, 3 D 115, 3	
D 149, 3 D 150, 3	E
D 150, 3	Electronics 3
D 202, 3 D 229, 3	Electronics, 3 Energy, breakdown, 99
D 257, 3	Bheigi, ordandown, 33
D 295, 3 D 748, 3	F
D 748 3	
D 170, 3	5 ''1 151
D 1533, 59	Ferric oxide, 151
D 1533, 59 D 1744, 59	Fiber, 13
D 1533, 59 D 1744, 59 D 3487, 37	Fiber, 13 Fire hazard testing, 24, 151,
D 1533, 59 D 1744, 59	Fiber, 13 Fire hazard testing, 24, 151, 160, 168 Flame spread, 168
D 1533, 59 D 1744, 59 D 3487, 37 D 5222, 37 D 6006, 37 ASTM collaborative water in	Fiber, 13 Fire hazard testing, 24, 151, 160, 168 Flame spread, 168 Flammability
D 1533, 59 D 1744, 59 D 3487, 37 D 5222, 37 D 6006, 37	Fiber, 13 Fire hazard testing, 24, 151, 160, 168 Flame spread, 168 Flammability flame-retardant nylon, 151
D 1533, 59 D 1744, 59 D 3487, 37 D 5222, 37 D 6006, 37 ASTM collaborative water in oil study, 59	Fiber, 13 Fire hazard testing, 24, 151, 160, 168 Flame spread, 168 Flammability
D 1533, 59 D 1744, 59 D 3487, 37 D 5222, 37 D 6006, 37 ASTM collaborative water in	Fiber, 13 Fire hazard testing, 24, 151, 160, 168 Flame spread, 168 Flammability flame-retardant nylon, 151 polybutylene terephthalate
D 1533, 59 D 1744, 59 D 3487, 37 D 5222, 37 D 6006, 37 ASTM collaborative water in oil study, 59	Fiber, 13 Fire hazard testing, 24, 151, 160, 168 Flame spread, 168 Flammability flame-retardant nylon, 151 polybutylene terephthalate
D 1533, 59 D 1744, 59 D 3487, 37 D 5222, 37 D 6006, 37 ASTM collaborative water in oil study, 59 B Biodegradable dielectric fluid, 37 Breakdown testing/recognition,	Fiber, 13 Fire hazard testing, 24, 151, 160, 168 Flame spread, 168 Flammability flame-retardant nylon, 151 polybutylene terephthalate 151 G
D 1533, 59 D 1744, 59 D 3487, 37 D 5222, 37 D 6006, 37 ASTM collaborative water in oil study, 59 B Biodegradable dielectric fluid, 37	Fiber, 13 Fire hazard testing, 24, 151, 160, 168 Flame spread, 168 Flammability flame-retardant nylon, 151 polybutylene terephthalate 151 G Gas analysis, dissolved, 47
D 1533, 59 D 1744, 59 D 3487, 37 D 5222, 37 D 6006, 37 ASTM collaborative water in oil study, 59 B Biodegradable dielectric fluid, 37 Breakdown testing/recognition, 99	Fiber, 13 Fire hazard testing, 24, 151, 160, 168 Flame spread, 168 Flammability flame-retardant nylon, 151 polybutylene terephthalate 151 G Gas analysis, dissolved, 47 Gas cables, compressed, 112
D 1533, 59 D 1744, 59 D 3487, 37 D 5222, 37 D 6006, 37 ASTM collaborative water in oil study, 59 B Biodegradable dielectric fluid, 37 Breakdown testing/recognition,	Fiber, 13 Fire hazard testing, 24, 151, 160, 168 Flame spread, 168 Flammability flame-retardant nylon, 151 polybutylene terephthalate 151 G Gas analysis, dissolved, 47 Gas cables, compressed, 112 Gassing tendency, 70
D 1533, 59 D 1744, 59 D 3487, 37 D 5222, 37 D 6006, 37 ASTM collaborative water in oil study, 59 B Biodegradable dielectric fluid, 37 Breakdown testing/recognition, 99 C Cable, 13, 160, 168	Fiber, 13 Fire hazard testing, 24, 151, 160, 168 Flame spread, 168 Flammability flame-retardant nylon, 151 polybutylene terephthalate 151 G Gas analysis, dissolved, 47 Gas cables, compressed, 112 Gassing tendency, 70 Glass, 13
D 1533, 59 D 1744, 59 D 3487, 37 D 5222, 37 D 6006, 37 ASTM collaborative water in oil study, 59 B Biodegradable dielectric fluid, 37 Breakdown testing/recognition, 99 C Cable, 13, 160, 168 Charge transfer, apparent, 112	Fiber, 13 Fire hazard testing, 24, 151, 160, 168 Flame spread, 168 Flammability flame-retardant nylon, 151 polybutylene terephthalate 151 G Gas analysis, dissolved, 47 Gas cables, compressed, 112 Gassing tendency, 70
D 1533, 59 D 1744, 59 D 3487, 37 D 5222, 37 D 6006, 37 ASTM collaborative water in oil study, 59 B Biodegradable dielectric fluid, 37 Breakdown testing/recognition, 99 C Cable, 13, 160, 168	Fiber, 13 Fire hazard testing, 24, 151, 160, 168 Flame spread, 168 Flammability flame-retardant nylon, 151 polybutylene terephthalate 151 G Gas analysis, dissolved, 47 Gas cables, compressed, 112 Gassing tendency, 70 Glass, 13

209

Hydraulic fluids, 37 Hydrocarbons, 37, 70

I

Ignition resistance, 160, 168 Institute of Electrical and Electronic Engineers, 3, Insulating oil, 18, 82 Insulation, 13 testing devices, 99 International Commission on Rules for the Approval of Electrical Equipment, 24 International Electrotechnical Commission, 3, 24, 82, 112 International Organization for Standardization, 24 International standards, fire hazard testing, 24 Iron oxide, 151 Isothermal DSC measurements,

K

Karl Fischer method, 59 D 1533, 59

M

Mica, 13
Military specifications, 30
Mineral insulating oils
electrochemical stability, 70
oxidation stability, 82
Model, chemical kinetic, 136

N

National Electrical
Manufacturers
Association, 30
National Fire Protection
Association, 168
National Institute of Standards
and Technology, 34
Nylon, flame-retardant, 151

0

Oils, 18, 37, 70 mineral, 82 silicone, 99 water content in, 59 Oliec acid vegetable oil, 37 Optical sensors, 99 Outboard engine oils, 37 Oxidation, 70 stability, 82, 136

P

Paper, 13 Partial discharge, 99, 112 Pattern recognition, discharge, 112 Physical stability, 70 Plastics, 3, 13, 24 Polybutylene terephthalates, 151 Pulse-height analysis, 112

R

Railway, 160 Resin, 13 Risk reduction, fire hazard, 24 Rolling stock, 160 Rubber, 13

S

Sensors, optical, 99 Service life recommendations, transformer, 47 Silicones, 37 oil. 99 Site location techniques, discharge, 112 Smoke, 160, 168 Stability, mineral insulating oils, 70, 82 Stability testing, 136 Standards (See also ASTM standards), 37 industry, 30 international, fire hazard testing, 24 partial discharge measurement, 112 Steiner tunnel, 168

Switchoff characteristics, 99 Synthetic fluid, 18

T

Testing devices, insulation, 99 Thermal aging, 136 Titration, 59 Transformers, 37 condition evaluation, 47 outage, 47 Transport systems, 160

U

U.S. Department of Defense, 30 U.S. Navy, 3

V

Varnishes, 13, 18 Vegetable oil, 37

 \mathbf{W}

Water content in oil, 59 Waxes, 13 Wire, thin wall insulated, 160

 \mathbf{Z}

Zinc, 151