

Subject Index

A

Accelerators

Cockroft-Walton, 7

Van de Graaff, 7

AC impedance (*See also* Impedance)

computer-controlled measurements

for water penetration of anti-corrosion coatings, 374-385

methods, current needs, 216-217

mild steel corrosion induced by sulfate-reducing bacteria, 428-429

polarizing techniques in corrosion monitoring, 207-208

Acoustic emission

aluminum and steel alloys, high-strength, 35-36

active path corrosion and hydrogen embrittlement, fig., 52

amplitude distribution (*See* Amplitude distribution)

corrosion

304 austenitic stainless steel, 48

2024 aluminum alloys, 48

D16AT aluminum alloy, 47

detection in aluminum, 6

signals produced by, 82

corrosion fatigue

304 austenitic stainless steel, 61-62

A533B in simulated boiling water reactor environment, 68

carbon/manganese steel, 60

D6aC steel, 60

sources and relative energies in

Ti-6Al-4V, fig., 61

Ti-6Al-4V alloys, 60

TTStE36 steel, 61

corrosion processes

detectability, 31-36

principle, table, 34

crack growth processes and, 36

amplitude distribution function for, 36-37

hydrogen-assisted, 166, 174-178

crack growth rate and, 68

during cracking, factors affecting, 45

electric currents and, 33-34

factors affecting, 33

field application, 40-41

film formation and cracking, 34

gas evolution, 34-35

hydrogen absorption and desorption, 47

hydrogen cracking, 35

hydrogen embrittlement in 4340 steel, 53-54

hydrogen migration/microcracking, 35

metal dissolution and, 34

monitoring in

during periodic proof testing, 41

high-strength aluminum and steel alloys, 35-36

stainless steel, 36

titanium alloys, 36

practical limitations, 45-46, 72

Acoustic emission (*cont.*)

- results of corrosion, 37–40
 - corrosion products, 38–39
 - cracks, 39
 - effect of transducer and filter on, table, 80
 - Kaiser effect and, 37–38
 - rough surfaces, 38
 - thinning of metal, 38
- sources of, 69–71
- stress application, 40
- stress-corrosion cracking
 - 817M40 steel, 53
 - 897M39 steel, 53
 - Admiralty metal, 57
 - AISI 4340 steel, 53
 - aluminum alloys 7075-T651 and 2024-T351, 77–83
 - aluminum and magnesium alloys, 57
 - Al-Zn-Mg alloys, 55
 - brass, 57
 - continuous monitoring of, 67
 - copper and copper alloys, 57
 - D6aC steel, 53
 - detectability, 35
 - detection in industry, 84–87
 - high-amplitude signals, 84–86
 - low-amplitude signals, 86–87
 - high-strength steels, 52
 - mild steels, 52, 57
 - nickel maraging steel, 250 grade, 54
 - signal differentiation, 82–87
 - signals produced by, 82
 - stainless steels
 - type 304, 50–51, 67
 - type 316, 65
 - structural steel for blast furnace domes, 68
 - titanium-zirconium alloys, 58–60
 - uranium alloys, 57–58
- less steel during polarization scan, 49
- Activated carbon, corrosion potential, table, 294
- Admiralty metal, acoustic emission during stress-corrosion cracking, 57
- Aircraft
 - aluminum corrosion, neutron radiographic detection, 10–11
 - fuselage, corrosion monitoring with portable ultrasonic imaging system, 92, 94
- Aluminum
 - aircraft, corrosion detection
 - acoustic emission, 6
 - neutron radiography for, 10–11
 - half-value-layer for thermal neutrons, 13
 - structure and composite honeycomb, acoustic emission, 47
 - wire in salt water, acoustic emission, 46
- Aluminum alloys
 - 2024, acoustic emission during corrosion, 48
 - 7075-T6
 - acoustic emission during corrosion fatigue, 60
 - thermal neutron radiograph of HCL-treated beam, 10
 - D16AT, acoustic emission during corrosion, 47
- Aluminum-magnesium alloys, acoustic emissions
 - hydrogen embrittlement, 57
 - stress-growth cracking, 54–57
 - transgranular cracking, 55
- Ammeters, zero-resistance, in corrosion troubleshooting, 302
- Amplitude distribution, acoustic emission
 - during stress-corrosion cracking in 304 stainless steel, fig., 51
 - sources during stress-corrosion

- cracking or corrosion fatigue, fig., 66
- Anaerobic corrosion
 - cathodic depolarization theory, 460-461
 - corrosion metabolite theory, 461-462
 - electrochemical noise and, 462-468
- Anode-cathode potential difference, in occluded cell corrosion monitoring, 481
- Apparent activation energy, carbon steel corrosion in NaOH solutions, table, 411
- Armco iron, hydrogen-assisted crack growth, detection by modulus changes, 165-174
- ASME Code Section XI, requirements for nuclear reactors, 113
- ASTM Committee E-7, 1, 2
- ASTM Committee G-1, 1, 2
- ASTM Standards
 - A 53-78: 295
 - D 807: 210
 - D 993: 421
 - D 2776: 203
 - E 399: 53
 - G 1: 202
 - G 3: 290
 - G 4: 200, 202, 217
 - G 9: 375, 376, 377, 382, 383
 - G 30: 201
 - G 46: 201
 - G 59: 290
 - G 61: 290

B

- Bacteria, sulfate-reducing (*See* Sulfate-reducing bacteria-induced corrosion)

- Batch circulation treatments, efficiency, tracer studies, 253-255
- Blast furnace domes, acoustic emission monitoring of stress-corrosion cracking, 68
- Boilers, utility
 - 2400-psig cycle, 340-341
 - analytical and monitoring methods, 349-354
 - boilerwater chemistry, 347-348
 - boilerwater limits, table, 348
 - caustic damage in, 343-345
 - embrittlement detector for, 210-211
 - feedwater chemical control, 346-347
 - feedwater limits, table, 348
 - frequency of water analysis for, table, 354
 - hydrogen damage in, 343-345
 - inspection of, 355
 - nondestructive testing methods, table, 356
 - operation criteria tables
 - 1001-1800 psig, 350
 - 1801-2350 psig, 351
 - 2351-2600 psig, 352
 - 2601-2900 psig, 353
 - preboiler design, 341-342
 - tubing, ultrasonic detection of hydrogen damage, 27-28
 - waterside corrosion problems, 342-345
- Boiling water reactor environments
 - acoustic emission from A533B corrosion fatigue in, 68
 - discrimination of acoustic emission signals in, 69
- Boremag system, 103-105
 - Boresonic data acquisition system, 105-110
 - hardware and software, 105-106
 - mechanics, 108-110
 - ultrasonic evaluation, 107-108

Brass, acoustic emission during stress-corrosion cracking, 57

Bubbles

gas, bursting as source of acoustic emission energy, 34-35

hydrogen

acoustic emissions, 69-70

evolution, acoustic emission energy, 48-49

C

Calcium phosphates, cooling water and scale inhibition with, 307-313

Californium-252, in neutron radiography, 7, 10, 13

Capacitance of anticorrosion coatings, water penetration, 378-383

Carbon dioxide absorption tower, hydrogen probe for corrosion potential and hydrogen content, 230-231

Carbon steel (*See under Steel*)

Cast iron

ductile, chemical composition, table, 362

pipe, corrosion rate by drinkable water, 358-373

Cathode ray tube

ultrasonic thickness measurement,

conventional, 18

direct digital conversion, 19-20

Cathode-to-anode area ratio, in occluded cell corrosion monitoring, 481-484

Cathodic charging of Armco iron, changes in elastic modulus during, 167-174

Cathodic depolarization theory, 460-461

Cathodic protection

CuNi alloys, corrosion rate determination with harmonic impedance spectroscopy, 443-455

current response of electrode to voltage perturbation, 436-443

Caustic embrittlement, in utility boilers, 343

Caustic gouging

in tube metal, fig., 345

in utility boilers, 343-345

Choke valve erosion, monitoring with portable ultrasonic imaging system, 94

Coal tar enamel, computer-controlled AC impedance measurements, 377-383

Coatings, pipeline (*See Coal tar enamel; Fusion bonded epoxy; Polyethylene*)

Computer-controlled AC impedance measurements (*See AC impedance, computer-controlled measurements*)

Computer data acquisition (*See Data acquisition, computer-assisted*)

Computer data processing (*See Data processing, computer-assisted*)

Computer methods for corrosion monitoring, 217

Contaminants, crevice (*See Crevice contaminants*)

Cooling systems, corrosion control, 329-333

Cooling towers, uniform and pitting corrosion, inhibitor evaluation, 307-313

Copper

acoustic emission during stress-corrosion cracking, 57

ductile, chemical composition, table, 362

- pipe, corrosion rate by drinkable water, 358-373
- Copper alloys, acoustic emission during stress-corrosion cracking, 57
- Copper-nickel alloy corrosion rate determination with harmonic impedance spectroscopy, 443-455
 - mass loss and harmonic current analysis, table, 455, 456
 - mass loss determination in seawater, table, 454
- Corrosion
 - acoustic emissions
 - 304 austenitic stainless steel, 48
 - 2024 aluminum alloy, 48
 - active path corrosion in steels, fig., 52
 - aluminum structure and composite honeycomb, 47
 - aluminum wire in salt water, 46
 - D16AT aluminum alloy, 47
 - electrode, 46-47
 - low- and high-frequency signals during, fig., 84
 - sources, fig., 45
 - anaerobic (*See* Anaerobic corrosion; Sulfate-reducing bacteria-induced corrosion)
 - anticorrosion coatings, AC impedance for water penetration, 374-385
 - bacterial (*See* Anaerobic corrosion)
 - carbon steel
 - in kraft white liquors, 270-273
 - in NaOH solutions, LiOH effect, 404-411
 - economic costs of, 5, 179, 237
 - frequency spectra for acoustic emission signals with broadband pass transducer filters, fig., 85
 - localized, current needs, 217
 - microbiological (*See* Anaerobic corrosion; Sulfate-reducing bacteria-induced corrosion)
 - occluded cell (*See* Occluded cell corrosion)
 - pipelines, economic costs, 459
 - pits (*See under* Crevice corrosion)
 - portable ultrasonic imaging system for, 89-101
 - potentials
 - 304 stainless steel and activated carbon, table, 294
 - weld materials, table, 297
 - recirculating water, composition, table, 310
 - results of
 - and acoustic emissive behavior, table, 38
 - detection by acoustic emission, 37-40
 - Dunegan strategy, 37-38
 - sulfate-reducing bacteria-induced (*See* Sulfate-reducing bacteria-induced corrosion)
 - underwater steel structures, ultrasonic techniques, 179-189
 - focused transducer for thickness measurements, 181-184
 - system operation, 184-187
 - tests in harbor environment, 187
 - uniform, in cooling towers, 307-313
 - waterbox, rate determination with harmonic impedance spectroscopy, 433-436
 - water pipe, economic costs, 358
 - weld (*See* Welds)
- Corrosion detection
 - advanced ultrasonic systems for, 19-27
 - neutron radiography in industrial environments, 13
- Corrosion fatigue
 - acoustic emission during
 - 304 austenitic steel, effects of

Corrosion fatigue (*cont.*)304 austenitic steel (*cont.*)

environmental and mechanical conditions, fig., 64

A533B in simulated boiling water reactor environment, 68

sources and energy levels drawn on amplitude distribution, fig., 66

sources during, fig., 45

detectability by acoustic emission, 35

in utility boilers, 345

Corrosion inhibition during oil production

corrosion monitoring loop, 253

electrical resistance probes, 260–261

film life of inhibitors, 258

film persistency wheel tests, 252

inhibitor concentration and percent protection, 255–258

linear polarization measurements, 252–253

linear polarization probes, 258–259

test procedure for, 263–265

tracer studies, 253–255, 261–263

Corrosion inhibitors

effective film life, 258

polyphosphates, in cooling towers, 307–313

Corrosion monitoring

AC impedance, 207–208, 216–217

computer methods for, 217

coupons, 201–203

current needs in, 216–217

dye penetrant examination, 205

eddy current techniques, 205

electrical resistance probe, 203–204

electrochemical methods, 197–218

electrical resistance probes, 241–245, 247–248

harmonic impedance spectroscopy in cathodically protected systems, 433–456

hydrogen probe, 208–209

linear polarization resistance probe, 238–241, 243–245, 248–249

oil production corrosion inhibitor optimization, 251–265

in power plant steam condensers and circuits, 214–337

for production-support corrosion engineering, 292, 297–298

rates in simulated Kraft white liquors, 266–287

leaks, problem of, 216

localized corrosion, 217

magnetic methods, 205

motivation for, 198–199

occluded cell (*See under* Occluded cell corrosion)

oil wellhead loop, devices, 253

packing glands on pressure vessels and, 216

polarization diagrams, 207

polarization resistance, 205–207

product stream analysis, 209–210

radiographic methods, 205

selection of method for, 199–201

sentinel holes, 210

standards for, 217

strategies in, 211–216

monitoring location, 211–213

redundancy, 214–215

ultrasonic thickness data analysis, 214

stress-corrosion cracking, 210, 216

ultrasonic thickness measurements, 204–205

utility boilers, water and steam side, 339–357

weep holes, 210

wiring system problems, 215–216

- Corrosion probes
 - CISE high-temperature, schematic, 320
 - design problems of, 315-317
- Corrosion products
 - carbon steels in kraft white liquors, 280-281
 - detectability by acoustic emission, 38-39
 - hydrogen in, 9
 - neutron radiographic sensitivity to, 14
 - product stream analysis, 209-210
- Corrosion rates
 - carbon steels in kraft white liquors
 - actual and predicted, table, 277
 - actual, comparison with electrical resistance-determined rates, table, 279
 - composition of anodic and cathodic Tafel slopes, table, 279
 - corrosion characteristics, 270-273
 - corrosion products, 280-281
 - electrical resistance, 269-270, 278, 287
 - linear polarization, 269, 273-278, 287
 - reference electrode for potential measurements, 270
 - weight loss exposures, 270
 - cast iron pipe by drinkable water, 358-373
 - in cathodically protected systems, harmonic impedance spectroscopy, 433-456
 - copper pipe by drinkable water, 358-373
 - steam condensers, on-line monitoring, 214-337
- Corrosive metabolite theory, 461-462
- Coupling current in steam condenser, characteristics, 322, 324-325
- Coupons, corrosion monitoring with, 201-203
- Crack growth
 - in high-strength steel and aluminum alloys, 36
 - hydrogen-assisted, 165-178
 - acoustic emission measurements, 174-178
 - detection procedure, 167-168
 - modulus measurements, 168-174, 177
 - process and terminology, fig., 55
 - processes, emission amplitudes, 36
 - rate
 - and acoustic emission energy, relationship, 68
 - in high-strength low-alloy line pipe steel, table, 399
 - secondary, in high-strength low-alloy line pipe steel, kinetics, 395-399
- Cracking
 - acoustic emission during, factors affecting, 45
 - hydrogen embrittlement, detectability by acoustic emission, 35
 - intergranular, detected acoustic emission event counts and fig., 54
 - stress-corrosion (*See* Stress-corrosion cracking)
 - transgranular, acoustic emission during propagation in Mg-Al alloy, fig., 55
- Crack jump, acoustic emission and, 70
- Crack nucleation, hydrogen-assisted, 165-174
- Cracks
 - detectability by acoustic emission, 39
 - microcracks in hydrogen-attacked steel, 162
- Crack tip, dissolution kinetics in

- high-strength low-alloy line pipe steel, 399-401
- Crevice contaminants, sensor for, 138-154
 - design and manufacture, 139-140
 - field evaluation, 144-151
 - laboratory testing, 140-144
- Crevice corrosion
 - eddy current technique for pits, 124-136
 - amplitude-distance parameter, 128
 - approach, 126-127
 - calculated and experimental results, comparison, 131-135
 - experimental data, 130-131
 - field-strength pattern, 127-128
 - field width determination, 131
 - influence function, 131
 - inverse problem, 136
 - lift-off parameter determination, 131
 - model testing, 130
 - response derivation, 128-129
 - factors affecting, fig., 474
 - mathematical modeling of, 484
 - occluded cell monitors, design, 472-489
- C-scan, and Ultra Image III, comparison, 99-100

D

- Data acquisition, computer-assisted
 - boresonic system, 105-110
 - hardware and software for, 105-106
 - inspection system methodology, table, 105
 - mechanics, 108-110
 - ultrasonic evaluation, 107-108
 - ultrasonic thickness measurements, 20-24

- Data processing, computer-assisted
 - ultrasonic thickness measurements, 24-27
 - calibration of, 26-27
 - coverage maps, 25-26
 - recording data on magnetic tape, 26
 - tables, 26
- Decarburization, hydrogen-attacked steel, 162
- Decontamination processes, corrosion rates, 333-336
- Desulfovibrio desulfuricans*, 418, 423, 427, 460-461
- Dunegan strategy, 37-38

E

- Eddy current technique
 - for corrosion pits, 124-136
 - amplitude-distance parameter, 128
 - approach, 126-127
 - calculated and experimental results in, 131-135
 - experimental data, 130-131
 - field strength patterns, 127-128
 - field width determination, 131
 - influence function, 131
 - inverse problem, 136
 - lift-off parameter determination, 131
 - model testing, 130
 - nuclear reactors and, 125-126
 - response derivation, 128-129
 - sensitivity to thickness changes, 6
- Electrical resistance, carbon steel in kraft white liquors
 - accuracy of corrosion rate measurement, 286-287
 - corrosion rate determination, 278
 - measurement procedure, 269-270
- Electrical resistance probes
 - advantages of, 243-245

- comparison with linear polarization resistance probes, 245
- corrosion monitoring with, 203-204
- data plot from, fig., 203
- instrumentation for, 245-247
- oil production, comparison with corrosion coupon results, table, 260
- principles, 241-243
- probe selection, 247-249
- Electric current, detectability by acoustic emission, 33-34
- Electric power plant crevice contaminants, sensor for, 138-154
- Electrochemical methods for corrosion monitoring (*See specific methods*)
- Electrode
 - corrosion, acoustic emission, 46-47
 - potential, hydrogen content as function of, 226-229
- Embrittlement detector, for cracking of boiler steels, 210-211
- Enzyme-linked immunosorbent assay, for sulfate-reducing bacteria detection, 419
- Erosion, portable ultrasonic imaging system for
 - in seawater pipeline, 91-93
 - inside a choke valve, 94

F

- Film
 - formation and cracking detectability by acoustic emission, 34
 - for neutron radiography
 - fluorescent screens of gadolinium oxysulfide, 7
 - images, thermal neutron exposures for, 8
 - metal screens of gadolinium, 7

- Film persistency wheel tests, inhibitor performance, 263
- Fluorescence antibody technique, for sulfate-reducing bacteria detection, 418-419
- Fractography, high-strength low-alloy line pipe steel, 392-393
- Fusion bonded epoxy, computer-controlled AC impedance measurements, 377-383

G

- Gadolinium metal screens, 7-8
- Gadolinium oxysulfide fluorescent screens, 7
- Galvanic current, density for A 53 pipe and E6010 weld deposit
 - agitation effect, fig., 299
 - pipe-to-weld area ratio effect, fig., 299
 - weld materials coupled to A 53 steel pipe, fig., 299
- Gas
 - bubbles (*See Bubbles*)
 - evolution, detectability by acoustic emission, 34
- Gouging, caustic, in utility boilers, 342-345

H

- Half-value-layer for thermal neutrons
 - aluminum, 13
 - stainless steel, 13
 - water, 9
- Harmonic impedance spectroscopy, corrosion rates in cathodically protected systems, 433-456
- Hydrogen
 - absorption and desorption, acoustic emission during, 47

Hydrogen (cont.)

- attack (*See* Hydrogen attack in steels)
- attenuation of slow neutrons, 6, 9
- content, K_{ISCC} as function of, measurement with hydrogen probe, 229–230
- content of mild steel, measurement with hydrogen probe, 226–229
- in corrosion products, 9, 12
- cracking
 - in 4340 steel, acoustic emission, 36
 - detectability by acoustic emission, 35
- Hydrogen attack in steels
 - attacked wall thickness and wave ratio, fig., 161
 - effect on wave velocity, 154
 - quantitative evaluation with ultrasonic velocity technique, 153–164
 - thickness evaluation, longitudinal wave velocity and, 155–158
 - ultrasonic wave velocity method, experimental results, table, 159
- Hydrogen damage
 - brittle corrosion failure, fig., 343
 - in boiler tubing
 - progress of, 27–28
 - ultrasonic detection, 27–28
 - in utility boilers, 343–345
- Hydrogen embrittlement in steels, acoustic emission during, 52–54
- Hydrogen/methane process in boiler tubing, ultrasonic detection, 27–28
- Hydrogen probe
 - apparatus description, 222–223
 - CO₂ absorption tower in ammonia synthesis, 230–231
 - detection limits, 233–234
 - hydrogen content as function of electrode potential, 226–229
 - hydrogen monitoring of line pipe, 231–234
 - K_{ISCC} as function of hydrogen content, 229–230
 - measurement procedure, 223–226
 - use in corrosion monitoring, 208–209

I**Imaging**

- physical and ultrasonic, comparison, table, 122
- ultrasonic, automated technique for intergranular stress-corrosion cracking detection, 112

Impedance (*See also* AC impedance)

- measurements for sulfate-reducing bacteria detection, 419–420

Industrial environments

- acoustic emission detection of stress-corrosion cracking in, 84–87
- corrosion control, main methods for, 238
- neutron radiography applicability, 13
- standards for corrosion monitoring in, 217

Inspection, automated, nuclear power plant piping/weld systems, 112**Intergranular stress-corrosion cracking**

- 304 stainless steel, acoustic emission response during, 65–67
- automated ultrasonic detection technique, 112
- imaging technique, 117–122
- search head design, 114–117

- boiling water reactor environment,
 - acoustic emission response discrimination, 69
- nuclear power plants, acoustic emission monitoring, 65
- simulated boiling water reactor environments, acoustic emission monitoring for, 44
- Iron phosphide, anaerobic corrosion and, 462
- Iron sulfide, anaerobic corrosion and, 461

K

- Kaiser effect, 37-38
- Kraft white liquors, carbon steel corrosion rates in, 266-287
 - electrical resistance measurements, 269-270, 278, 286-287
 - linear polarization measurements, 269, 273-278, 287

L

- Leaks, in corrosion monitoring systems, 216
- Linear polarization
 - AISI 1020 steel, inhibitor performance, 252-253
 - carbon steel in Kraft white liquors corrosion rates determination, 273-278
 - errors due to liquor oxidation effects, 286
 - measurement procedure, 269
 - resistance, 315
 - resistance ratio, 316, 319
 - uniform and pitting corrosion rates in cooling towers, 307-313
- Linear polarization resistance probes
 - advantages of, 243-245

- comparison with electrical resistance probes, 245
- instrumentation for, 245-247
- oil production corrosion, 258
- principles, 238-241
- proper probe selection, 247-248
- Lithium hydroxide, effect on carbon steel corrosion in NaOH solution, 404-411

M

- Magnesium-aluminum alloys (*See* Aluminum-magnesium alloys)
- Magnetic particle examination (*See* Boremag system)
- Metal dissolution, detectability by acoustic emission, 34
- Microcalorimetry, sulfate-reducing bacteria detection with, 420
- Moderator, neutron, 7
- Moderator-collimator approach, to neutron radiography, 7
- Monitoring devices, location of, 211-213

N

- Neutron radiography
 - corrosion detection methods, 7-12
 - neutron-sensitive intensifying screens, 7
 - sensitivity of, 12
 - film for, 7-9
 - in industrial environments, 13
 - moderator-collimator approach, 7
 - neutron-attenuating materials and, 13
 - real-time, screens for, 7-8
 - sensitivity to corrosion products, 9-12

- sources, 7
 - accelerator, 7
 - CF-252, 7, 10, 13
 - television-type detection methods, 14
 - thermal
 - HCL-treated aluminum beam, fig., 10
 - typical geometry for, fig., 9
 - Neutrons
 - classification according to energy, table, 8
 - cold, for neutron radiography, 7, 13
 - slow, attenuation by hydrogen, 6, 9
 - thermal
 - half-value-layer (*See* Half-value layer for thermal neutrons)
 - for neutron radiography, 7
 - Nickel oxyhydroxide, hydrogen probe plating with, 222
 - Noise
 - anaerobic corrosion and, 465-468
 - electrochemical, 462-463
 - sources, in acoustic emission field applications, 40
 - Nondestructive testing methods (*See specific methods*)
 - Nuclear power plants
 - acoustic emission and stress-corrosion cracking in, 65
 - eddy current technique for crevice corrosion pits, 124-136
 - pipng system, automated ultrasonic detection of intergranular stress-corrosion cracking in, 112
 - Nuclear reactors (*See* Nuclear power plants)
- O**
- Occluded cell corrosion
 - design criteria for monitoring
 - anode-cathode potential difference, 481
 - cathode-to-anode area ratio, 481-484
 - gap dimensions, 479-481
 - mathematical modeling of crevices, 484
 - rate process in, 478
 - thermodynamic factors affecting, 474-478
 - monitoring device, 210
 - in-plant monitors, 486-487
 - laboratory devices, 485-486
 - Oil production, corrosion inhibitor optimization, 251-265
 - electrical resistance probes, 260-261
 - field measurements
 - corrosion monitoring loop, 253
 - tracer studies, 253-255
 - film life of inhibitors, 258
 - film persistency wheel tests, 252
 - inhibitor concentration and percent protection, 255-258
 - linear polarization measurements, 252-253
 - linear polarization probes, 258
 - test procedure for, 263-265
 - tracer studies, 261-263
 - Open-circuit potentials, for sulfate-reducing bacteria-induced corrosion, 422-423
 - Operator skill
 - in acoustic emission field applications, 40
 - in computer-assisted ultrasonic data-processing, 26-27
- P**
- Phosphonate dispersants, 310-313
 - Piezoelectric sensors, acoustic emission amplitudes measured by, 69

Pipe

A 53 steel, weld corrosion-induced failure, 295-302

copper-nickel, corrosion monitoring with portable ultrasonic imaging system, 94

line, hydrogen monitoring with hydrogen probe, 231-234

in nuclear reactors, automated ultrasonic detection of intergranular stress-corrosion cracking, 112

seawater, corrosion monitoring with portable ultrasonic imaging system, 91, 93

water

cast iron and copper, corrosion rate by drinkable water, 358-373

corrosion costs, 358

Pipeline coatings (*See* Coal tar enamel; Fusion bonded epoxy; Polyethylene)

Pipelines (*See* Pipe)

Pitting

acoustic emission during, 47

corrosion

eddy current technique for, 124-136

in utility boilers, 343-345

failure of stainless steel tank, troubleshooting, 291-295

potentials, sulfate-reducing bacteria and, 425-426

rates in cooling towers, calcium phosphate effects, 307-313

underwater

focused transducer technique of thickness measurements, 181-187

traditional inspection methods, 180

Plastic strain effects

hydrogen absorption, 228-229

K_{ISCC} and hydrogen content, 229-230

Poisson's ratio, hydrogen-attacked steel, estimation by ultrasonic wave velocity ratio, 162-163

Polarization

curve and acoustic emission count rate, in 304 austenitic stainless steel, fig., 49

galvanostatic and potentiostatic, for sulfate-reducing bacteria detection, 423-425

Polarization diagrams, in corrosion monitoring, 207

Polarization resistance

corrosion monitoring with, 205-207

mild steel corrosion induced by sulfate-reducing bacteria, 426-429

Polyethylene pipeline coating, computer-controlled AC impedance measurements, 377-383

Polymers, synthetic, 310-313

Potentiodynamic polarization

curves for stress-corrosion cracking in high-strength low-alloy line pipe steel, 390

for pitting corrosion rates

cooling water towers, 308-309

oil fields, 258

pulp and paper plants, 269, 273-278

uniform and pitting corrosion rates in cooling towers, 307-313

Potentiostatic polarization, AISI 1020 steel in seawater contaminated by sulfate-reducing bacteria, fig., 426

Power plants

cycles, construction materials, table, 342

true corrosion rate, on-linear monitoring, 314-337

wall thinning in, 28

Pressure vessels, packing glands on, 216

Probes

- electrical resistance (*See* Electrical resistance probes)
- electrochemical (*See* Linear polarization resistance probes)
- hydrogen (*See* Hydrogen probe)

R

Radiography

- conventional, 6
- neutron (*See* Neutron, radiography)

Radioisotopic techniques, for sulfate-reducing bacteria detection, 420-421

Redundancy, in corrosion monitoring programs, 214-215

Resistive thermal device, calibration
field tests, 147
laboratory, 143

Rough surfaces, detectability by acoustic emission, 38

S

Scanning electron microscopy

- stress-corrosion cracking in high-strength low-alloy line pipe steel, 392-393
- sulfate-reducing bacteria detection, 416

Sensor for real-time crevice contaminant detection, 138-154

calibration of conductivity electrodes, 148

calibration procedures, 147

design and manufacture, 139-140

field equipment development, 144-147

field evaluation, 144-151

field installation, 149

flowing steam tests, 143-144

integrity tests, 148-149

mechanical testing, 143

probe evaluation and data analysis, 149-151

resistive thermal device calibration, 143, 147

room temperature calibration, 141-142

steam environment calibration and testing, 142-143

test bed for, 144

Sensor placement, in acoustic emission field applications, 40

Sentinel holes (*See* Weep holes)

Shear modulus, hydrogen-attacked steel, estimation by ultrasonic wave velocity ratio, 162

Slow-strain rate technique, for stress-corrosion cracking of line pipe steel, 387, 389-390

Sodium hydroxide, carbon steel corrosion in, 404-411

Stainless steel

304

acoustic emission

during corrosion, 48

during corrosion fatigue, 61-62

effects of environmental and mechanical conditions during corrosion fatigue, fig., 64

hydrogen-assisted growth detection by, 174-178

monitoring, 36

during polarization scan, 49

during stress-corrosion cracking, 50-51, 65-67

corrosion potential, table, 294

pitting failure troubleshooting, 291-295

316, acoustic emission during stress-corrosion cracking, 65

- 410 (martensitic), hydrogen assisted growth detection by acoustic emission, 174-178
- 430 (austenitic), hydrogen assisted growth detection by acoustic emission, 174-178
- half-value-layer for thermal neutrons, 13
- Standards, for corrosion monitoring in industrial plants, 217
- Steam condensers, on-line corrosion measurements, 318-329
- Steam turbine crevice contaminants, sensor for real-time detection of, 138-154
- Steels
 - 414 high-strength low-alloy line pipe, stress-corrosion cracking, 386-402
 - 483 high-strength low-alloy line pipe, stress-corrosion cracking, 386-402
 - 817M40, acoustic emission during stress-corrosion cracking, 53
 - 897M39, acoustic emission during stress-corrosion cracking, 53
 - A 53 pipe (*See* Pipe)
 - AISI 1020, linear polarization measurements, 252-253
 - AISI 4135, K_{ISCC} as function of hydrogen content, measurement with hydrogen probe, 229-230
 - AISI 4340, acoustic emission during hydrogen embrittlement, 53-54
- carbon
 - A515, corrosion potential and hydrogen content measurement with hydrogen probe, 231
 - corrosion in NaOH solution, LiOH effect, 404-411
 - corrosion rate as function of corrosion potential, fig., 326
 - corrosion rates in Kraft white liquors, 270-281
 - hydrogen-attack evaluation, 153-164
 - Poisson's ratio, 162-163
 - shear modulus, 162-163
 - Young's modulus of, 162-163
- carbon/manganese, acoustic emission during corrosion fatigue, 60
- D6aC, acoustic emission
 - during corrosion fatigue, 60
 - during stress-corrosion cracking, 53
- hydrogen-damaged, detection, 27-28
- low alloy, hydrogen-attack evaluation, 153-164
- mild
 - acoustic emission during stress-corrosion cracking, 57
 - hydrogen content measurement with hydrogen probe, 226-229
- nickel maraging (250 grade), acoustic emission during stress-corrosion cracking, 54
- plate in heavy water, corrosion monitoring with portable ultrasonic imaging system, 94
- stainless (*See* Stainless steel)
- TTS36, acoustic emission during corrosion fatigue, 61
- Steel structures, underwater, ultrasonic corrosion monitoring technique, 179-189
- Stress, thermal, in acoustic emission monitoring, 40
- Stress-corrosion cracking
 - 304 stainless steel, acoustic emission during, 50-51, 67
 - 316 stainless steel, acoustic emission during, 65
 - 817M40 steel, acoustic emission during, 53

Stress-corrosion cracking (*cont.*)

897M39 steel, acoustic emission during, 53

2024-T351 aluminum alloy

acoustic emission monitoring, 81-82

and corrosion acoustic emission signals, differentiation, 82-87

7075-T651 aluminum alloy

effect of transducer and filter on acoustic emission results, table, 80

velocity measurements, acoustic emission monitoring, 77-78

acoustic emission

low and high frequency signals during, fig., 84

sources and energy levels drawn on amplitude distribution, fig., 66

sources during, fig., 45

active path, detectability by acoustic emission, 35

Admiralty metal, acoustic emission during, 57

AISI 4340 steel, acoustic emission during, 53

aluminum and magnesium alloys, acoustic emission during, 57

Al-Zn-Mg alloy, acoustic emission during, 55

amplitudes distribution function for, 36-37

brass, acoustic emission during, 57

caused by crevice contaminants, sensor for real-time detection, 138-154

continuous-monitoring of acoustic emission, 67

copper and copper alloys, acoustic emission during, 57

current monitoring needs, 216

D6aC steel, acoustic emission during, 53

detection in industry, 84-87

discontinuous, detectability by acoustic emission, 35

frequency spectra for acoustic emission signals with broadband pass transducer filters, fig., 85

high-strength low-alloy line pipe steel, 386-402

intergranular (*See* Intergranular stress-corrosion cracking)

metals, acoustic emission during, 47

mild steels, acoustic emission during, 57

nickel maraging steel (250 grade), acoustic emission during, 54

process streams, device for, 210

structural steel for blast furnace domes, acoustic emission during, 68

uranium alloys, acoustic emission during, 57-58

utility boilers, 343

velocity, acoustic emission rate and, 76

Sulfate-reducing bacteria-induced corrosion

cathodic depolarization theory and, 460-461

cellular components unique to, 421-422

corrosive metabolite theory of, 461

counting, 414-416

detection by impedance measurements, 419-420

enumeration, 414-416

galvanostatic methods, 423-425

immunological detection, 418-419

microcalorimetric detection, 420

microscopic detection, 416-417

open circuit potential measurements, 422-423

pitting potentials, 425-426

polarization resistance measurements, 426-429
 potentiostatic polarization methods, 423-425
 radioisotope techniques for, 420-421
 sulfide determination, 421
 Sulfide ion, detection for bacterial sulfate reduction, 421

T

Television-type detection systems, 14
 Thermodynamics, occluded cell corrosion, 474-478
 Thickness (*See also* Thinning)
 computer-assisted data acquisition system, 20-22
 computer-assisted measurement system, 22-27
 data acquisition subsystem, 23-24
 data processing subsystem, 24-27
 hydrogen damage in boiler tubing, 27-28
 conventional examination methods, shortcomings, 28-29
 conventional ultrasonic measurements of, 17-18
 printer for measurement of, 19-20
 ultrasonic measurements
 corrosion monitoring with, 204-205
 data analysis, 214
 underwater, focused transducer technique for, 181-187
 Thinning
 detectability by acoustic emission, 38
 wall, measurement of, 28-29
 Titanium alloys, acoustic emission monitoring, 36

Titanium-aluminum-vanadium alloy, acoustic emission during corrosion fatigue, 60-62
 Titanium-zirconium alloys, acoustic emission during stress-corrosion cracking, 58-60
 Tomography, Ultra Image III image formation and, 100
 Tracer studies, oil wellhead, corrosion inhibitor program, 253-255, 261-263
 Turbine rotors
 boremag system, 103-105
 boresonic data acquisition system, 105-110
 mechanics, 108-110
 ultrasonic evaluation, 107-108

U

Ultra Image III (*See* Ultrasonics, portable imaging system)
 Ultrasonics
 advanced systems, 19-27
 data acquisition subsystem, 23-24
 data processing subsystem, 24-27
 thickness data acquisition system, 20-22
 thickness measurement system, 22-23
 thickness printer, 19-20
 automated data acquisition and evaluation system
 boremag system, 103-105
 boresonic mechanics, 108-110
 boresonic system, 105-108
 implementation, 107-108
 inspection system methodology, table, 105
 automated technique for intergranular stress-corrosion cracking detection, 112

Ultrasonics (*cont.*)

- conventional, 17-18, 28-29
- with focused transducer, for underwater corrosion of steel structures, 179-189
- system operation, 184-187
- technique for thickness measurements, 181-184
- tests in harbor environment, 187
- imaging, and physical imaging, comparison, table, 122
- portable imaging system
 - accuracy of image, 100
 - in airplane fuselage, 92, 94
 - analyzing power of, 93
 - applications for, 91-93
 - corrosion/erosion in seawater pipeline, 93
 - corrosion in airplane fuselage, 92, 94
 - corrosion in seawater pipeline, 91-92
 - C-scan comparison with, 99-100
 - description and calibration, 90-91
 - equipment and calibration, 90-91
 - erosion inside choke valve, 94
 - for large areas, 92-93
 - in seawater pipeline, 91-93
 - steel plate in heavy water processing plant, 94
 - tomographic image formation, 100
 - welded region of copper nickel pipe, 94
- pulse-echo methods, 6
- resonance methods, 6
- thickness measurements, corrosion monitoring with, 204-205
- wave velocity ratio method for hydrogen attack in steels, 153-164

- Uranium alloys, acoustic emission during stress-corrosion cracking, 57-58

V

- Voltammogram, cyclic, carbon steel corrosion in NaOH solutions, 406-409
- Voltmeters, high-impedance, in corrosion troubleshooting, 302

W

Water

- analysis frequency for utility boilers, table, 354
- chemistry in power plants, 319-333
- chemistry monitoring in utility boilers, 349-355
- drinkable, effect on corrosion rate of cast iron and copper pipe, 358-373
- half-value-layer for thermal neutron radiographic beam, 9
- penetration of anticorrosion coatings, 374-385
- pipe (*See under* Pipe)

Wave velocity

- ratio method for hydrogen-attacked steels, 153-164
- shear and longitudinal, in hydrogen-attacked steel, fig., 157

- Weep holes, in corrosion monitoring, 210

Weld

- corrosion, troubleshooting techniques, 295-302
- inspection, automated ultrasonic technique for, 112
- materials, corrosion potentials, table, 297

Wheel tests, inhibitor performance,
263

Wiring systems, corrosion monitoring systems and, 215-216

X-Z

X-rays and slow neutrons, attenuation characteristics, fig., 7

Young's modulus

changes in, detection of hydrogen-assisted crack growth by,
165-178

hydrogen-attacked steel, estimation by ultrasonic wave
velocity ratio, 162

Zirconium-aluminum alloys (*See*
Aluminum-zirconium alloys)