# Subject Index

## A

AASHTO Charpy V-notch requirements, 356-357 AASHTO fatigue-design curve welded beams, 260-270 welded bridge components, 265-267 AASHTO Fracture Control Plan for Steel Bridges, 414 adequacy, Bryte Bend Bridge, 423-427 Bryte Bend Bridge design, 418-423 AASHTO fracture toughness requirement, verification, 357 AASHTO Guide Specification for Steel Bridge Members, 354 AASHTO Guide Specifications for Fracture Critical Non-Redundant Members, 419 AASHTO Standard Specifications for Highway Bridges, 419 AASHTO Standard Specifications for Welding Structural Highway Bridges, 355 Aircraft, failures, 5-6 Aluminum, fatigue-crack propagation, constant amplitude load fluctuation, 202-203 ANSI/AASHTO/AWS D1.5-96 Welding Code, Section 12, 355

API 579, 402 API specifications, J–55 and K-55 casing, 482-483, 487 Arc welding, 273-274 maximum temperature of weld metal, 274 ASME Code Section III, 265, 354 ASME Section XI Rules, 338, 396, 401-402 A508 steel, K -CVN-CTOD-I correlations, 129 A516 steel, K.-CVN-CTOD-I correlations, 128 A517 steel, K<sub>c</sub>-CVN-CTOD-J correlations, 130 A533 steel, K<sub>c</sub>-CVN-CTOD-J correlations, 129 ASTM A-328, 457 ASTM E-23, 119 ASTM E-399, 77, 95, 98, 102, 106, 405, 416 ASTM E-561, 78 ASTM E-813, 78 ASTM E-1152, 78 ASTM E-1221, 78 ASTM E-1290, 78 ASTM E-1737, 78 ASTM E-1820-96, 78-79, 91 ASTM E-1921, 79, 81, 93-94 As-welded components, fatigue behavior, 253-264composition effect, 258, 260 geometry effect, 256-258 postweld heat treatment effect, 263-264 residual stress effect, 260-263 superposition of applied

compressive stress on residual stress, 262–263 tensile stress on residual stress, 262 Austenitic stainless steels, fatigue-crack propagation, constant amplitude load fluctuation, 201–202

## B

Barge, see Ingram Barge Beam in bending, stressintensity factors equation, 41-42 Bridge components, welded, AASHTO fatigue design curves, 265-269 Bridges, see Steel bridges Brittle failure aircraft, 5 bridges, 5-8 characteristics, 9, 11 vs. ductile, 9-11 minor, 16-17 history, 3-9 ships, 4-8 Brittle fracture, 3 Bryte Bend Bridge, 414-418 failure by, analyzing structure, 136-137 possibility, factors to be controlled, 139-140 prevention, 338 Bryte Bend Bridge, 413-427 **AASHTO Fracture Control** Plan for Steel Bridges, 414 adequacy of AASHTO Fracture Control Plan, 423-427

## 507

effect of details on fatigue life, 424-426 implied versus guaranteed notch toughness, 423–424 brittle fracture, 414-418 critical detail at, 421 design aspects related to AASHTO Fracture Control Plan, 418-423 layout, 417 superstructure, 414-415 BS5500, 265 BS7608, 265 Burst tests, steel casings, 468-487 failure analysis, 472–480 flaw geometry, 469, 471 fracture mechanics equation, 474 material and experimental procedures, 468-469 metallographic analysis, 476, 478, 481-483

# С

Cantilever-beam specimen  $K_{\rm Iscc}$  tests, 287, 289 stress-corrosion cracking, 284-286 Case studies, 26 see also Bryte Bend Bridge; Ingram Barge; Lockand-dam sheet piling; Trans Alaska Pipeline Service oil tankers Charpy V-notch AASHTO requirements, 356-357 effect of temperature and loading rate, 97, 99-100 energy absorption, correlation with planestrain impact fracture toughness, 119-120 temperature shift, 109-110 upper-shelf, correlation with KIc, 120-124 Charpy V-notch energy absorption, structural steel, 12-13 Charpy V-notch fracture toughness, lock-anddam sheet piling, 461 Charpy V-notch impact criterion, ship steels, 370-373

Charpy V-notch impact energy, versus temperature behavior, 11–12 Charpy V-notch impact energy absorption curve, steels, 472-473 Charpy V-notch impact test predicted dynamic fracture toughness, 477–478 steel casings, 468-470 temperature shift, 114–116 Charpy V-notch- $K_{Id}$ - $K_c$ correlation, two-stage, 119-122 Charpy V-notch specimens, fracture toughness, weldments, 277-279 Circular crack, embedded, in infinite plate, stressintensity factors equation, 37-39 Cofferdam, 455 critical fracture toughness, 462-463 nonpropagating crack, 462– 463 Column instability, 19–20, 142-143 Compact-specimen test, setup, 83 Constant-amplitude loading, 165-166 Constraint affecting fracture toughness, 71–76 effect fitness for service analysis, 389–394 fracture toughness, 101-109 structural behavior, Ingram Barge, 428–431 Corrosion-fatigue-crackgrowth, rate as function of RMS stress-intensity factor, 311-312, 316-319 Corrosion-fatigue-crack initiation, 296-305 behavior, steels, 298-305 cyclic-load frequency effect, 301-302 equation for predicting, 303-305 long-life behavior, 303 stress ratio of effects, 302 test specimens and experimental procedures, 296-298

Corrosion-fatigue-crack propagation, 305-307, 309-324 behavior below  $K_{Isccr}$  313– 320 cyclic frequency effect, 311 cyclic-stress waveform effect, 319-321 environmental effects during transient loading, 320-323 generalized behavior, 323-324near-threshold rate, 309-310 reduced cyclic crackopening displacement, 310 threshold, 306-307, 309-313 Corrosion-fatigue failures, prevention, 324-326 Crack growing from round holes, stress-intensity factors equation, 40-41 inclined, stress-intensity factors, 44-45 instability, 19-20, 142-143 irregularly shaped, estimating stressintensity factors, 45–47 probability of detection, 444-445 sharp, constraint ahead of, 105 - 107subjected to point or pressure loading, stress-intensity factors equation, 42–43 see also Fatigue cracks Crack arrest designing for, 388 fitness for service analysis, 404 - 408Crack arresters, 352 Crack blunting, 107–109 Crack closure, mechanisms, 196 - 197Crack-closure model, 221 Crack extension energy-balance approach, 60 under loading conditions, 222 Crack front, constant K, 177 Crack growth, 22 effect of cyclic-stress range, 172– 173 initial crack length, 174

local residual stresses effect, 343 phases, 255 ship steel behavior, 449 stress-corrosion, fatigue and, 19-23 Crack-growth rate as function of RMS stressintensity-factor range, 223-225 subcritical, relation to stress-intensity factor, 295 Crack-growth-rate tests, stress-corrosion cracking, 284, 294-296 Crack initiation, 21-22 fitness for service analysis, 404 - 408Crack length, critical, 463 Crack propagation, 21-22 fitness for service analysis, 404 - 408stages, weldments, 248-249 unstable, 334 Crack-shape parameter, 152– 153 Crack size critical, 138 for critical details, Trans Alaska Pipeline Service oil tankers, 443-444 as function of yield strength and fracture toughness, 144-145 initial, inspection capability, Trans Alaska Pipeline Service oil tankers, 444-445 Crack surface displacements, modes, 31-32 Crack tip coordinate system and stress components, 34 deformation modes, stress and displacement fields, 32-33 of "infinite" sharpness, limiting constraint, 107 opening mode stresses near, short- vs. deepcrack specimens, 391 Crack-tip-blunting model, 220 Crack-tip deformation, 50-52 Crack-tip opening displacement, 55--56, 88 - 89calculation, 93 critical value, 62 Dugdale Model, 60-63

fracture toughness tests, 461 stress-intensity factors relationship, 126-127 temperature-transition curve, 128, 130-131 Crack-tip opening displacement parameter, relation to *I*-integral, 63 Crack-tip plasticity model, 61 Critical member, nonfracture impact test requirements, 359 Cyclic-load frequency, effect on corrosion-fatigue-crack initiation, 301-302 fatigue-crack propagation, 206-209 Cyclic-stress waveform, effect on corrosion-fatiguecrack propagation,

## D

318-321

Delayed retardation, 220 Design definitions, 133-134 effect of lowering stress, fracture-control plan, 347 fatigue-crack propagation example, 212-216 fatigue curves, 182 high-strength steel selection for pressure vessel, 150 - 158fracture-mechanics design, 151-157 general analysis, 157-158 tradition approach, 150-151 see also Fracture-mechanics design Direct current electric potential probes, 469, 471 Discontinuities, weld, their effects, 243, 245-250 Distortion, weldments, 240-241 Distribution curves, unimodal, fatiguecrack growth, 227-228, 230-232 Distribution functions, 218

Double cantilever clip-in displacement gage, 84-85 Driving force, 14-15 definition, xv Drop weight NDT test, 123 Ductile failure vs. brittle behavior, 9–10 characteristics, 9, 11 Ductile plastic fracture, 368 Dugdale Model, CTOD, 60-63 Dynamic loading fracture-toughness transition behavior, steels, 476, 481 impact transition curve, 368, 373

## Ε

Edge crack, stress-flaw-size relation, 418, 420, 422 Elastic-plastic behavior, as fracture criterion, 364 Elastic-plastic conditions, 405-406 Elastic-stress-field distribution, ahead of crack, 73–74 Elliptical crack, embedded in infinite plate, stressintensity factors equation, 37-39 Environment-material system, corrosionfatigue-crack growth rate dependence on, 313, 315-316 Euler column instability, 142-143

## F

Fail-safe design, 135
Failure

assessment diagram, 397–399
at component connections, 237–238
consequences, 368–370
elapsed cycles to, 20–21
modes, 333

Fatigue, 163–181
definition, 163
effect of stress

concentration, 184–187
history, 3–9
loading, 164–167

constant-amplitude, 165-166 variable-amplitude, 166-167 performance, factors affecting, 164 stress-corrosion crack growth and, 19-23 testing, 167-176 fatigue-crack-initiation tests, 168-172 fatigue-crack-propagation tests, 172-174 strain-life tests, 170, 172 stress-life test, 168-171 tests of actual or simulated structural components, 174-176 Fatigue control, 23–24 Fatigue crack characteristics, 175-181 marks, schematic representation, 176-177 multiple, initiation, 176-177 originating from internal discontinuities, 247-248 propagation, 177 striations, 177, 180 Fatigue crack behavior, weldments smooth welded components, 250-253 as welded components, 253-264 Fatigue-crack growth calculations, 215 controlling, 352-353 effects of stress concentration, 207, 209 - 210retardation, 220 steels, 225-229 under unimodal distribution curves, 227-228, 230-232 under variable-amplitude loading, 218 Fatigue-crack initiation, 182-192 behavior of steels, 187, 299 dependence on nominalstress fluctuations, 185 - 186life, 163 predicting from notches, 189-192 sites, weldments, 246-250

tests, 168-172 threshold dependence on yield strength, 189, 260-262 independence from stress ratio, 188 predicting, 187-189 Fatigue-crack propagation, 194-232 analysis, 254–255 background, 194-196 bottom shell plates, Trans Alaska Pipeline Service oil tankers, 447–450 constant amplitude load fluctuation, 199-203 aluminum and titanium alloys, 202-203 austenitic stainless steels, 201 - 202ferrite-pearlite steels, 200-201 martensitic steels, 199-200 design example, 212–216 effect of cyclic frequency and waveform, 206–209 mean stress, 203-206 stress ratio, 205 life, 163 dependence, 254 regions, 194-195 in shadow of notch, 207 steel weldments, 210-212 tests, 172-174 threshold, 196-199 effect of factors, 197 variable-amplitude load fluctuation, 216-221 fatigue-crack growth, 218 ordered-sequence cyclic load, 225 probability-density distribution, 216-219 random-sequence, 223 root-mean-square model, 221-225 single and multiple highload fluctuations, 218, 220-221 Fatigue life determination, calculations, 271 - 272effect of details, Bryte Bend Bridge, 424-426 stages, 182 storm avoidance and, 438

Fatigue loading histogram, Trans Alaska Pipeline Service oil tankers, 445-447 reduced, effect, Trans Alaska Pipeline Service oil tankers, 450-453 Fatigue-strength-reduction factor, 182 Ferrite-pearlite steels, 177, 179 fatigue-crack propagation, constant amplitude load fluctuation, 200-201 Fitness for service, 25-26, 384 - 408definition, 25, 384-385 evaluations, 388 existing procedures, 396-402 API 579, 402 ASME Section XI, 396, 401-402 PD 6493, 396-400 proof or hydro-test to establish continued service fitness, 402-404 Fitness-for-service analysis difference between initiation and arrest fracture toughness behavior, 404-408 fracture mechanics use, 385-396 constraint effect, 389-394 effect of many factors, 394-396 loading rate effect, 386-389 Fixtures, test, 82-85 Flaw size critical relation with stress and material fracture toughness, 336 service temperature effect, 343-344 effect on life under fatigue loading, 349–350 initial, effect of reducing, 347 - 348maximum, 136 relationship with critical stress-intensity factor, 136, 141 stress and material toughness, 18

Fracture behavior, regions, 79-80 factors controlling susceptibility to, 346-347 history, 3-9 identification, fracturecontrol plan, 340-342 weldments, primary cause, 335 Fracture control, 23-24 guidelines, historical, 337-339 Fracture-control plan, 23-24, 348-350 comprehensive, 360-363 design consideration recommendations, 353-354 design methods, 351-353 developing, 336-337 effect of lowering design stress, 347 reducing the initial flaw size, 347-348 using material with better fracture toughness, 348-349 elements, 339-340 fracture identification, 340-342 historical background, 337-339  $K_{\rm Iscc}$ , design use, 343, 345 relative contribution establishment, 342-346 relative efficiency determination, 346-353 steel bridges, 354-360 AASHTO Charpy V-notch requirements, 356-359 design, 354-355 fabrication, 355 high-performance steels, 357 material, 355-356 verification of AASHTO fracture toughness requirement, 357 Fracture criteria, 24-25, 364-382 consequences of failure, 368-370 elastic-plastic behavior, 364 general levels of performance, 366-368

leak-before-break criterion, 378-381 original 15-ft-lb CVN impact criterion, ship steels, 370-373 parts, 366 selection, 364-365 steel bridges, 381-382 through-thickness yielding criterion, 374-378 transition-temperature criterion, 373-374 varying for different structure types, 369 Fracture instability, prediction with critical planestrain stress-intensity factors, 60 Fracture mechanics, 14-16 driving force, 14-15 fatigue crack propagation analysis, 254-255 fundamental principle, 31 resistance force, 15-16 Fracture-mechanics approach, stress-corrosion cracking, 283 Fracture-mechanics design, 16-19, 133-158 analysis of failure of 260in.-diameter motor case, 146-150 basic information, 135 discontinuities in, 135 factors controlling susceptibility to fracture, 335 fail-safe, 135 high-strength steel selection for pressure vessel, 151 - 157assumption that a flaw is present, 151–152 crack-shape parameter, 152 - 153design stress, 153 magnification factor, 154-155 materials selection, 142, 144-146  $K_{\rm Ic}/\sigma_{\rm vs}$  ratio, 144 procedure, 17-18 for terminal failure, 136-142 safe-life, 135 specifying more fracture toughness than required, 367

Fracture mechanics equation, 474 Fracture mechanics methodology, see Trans Alaska Pipeline Service oil tankers Fracture paths, multiple-load, 351-352 Fracture toughness behavior, weldments, 272-279 bridge steel requirements, 355-356 crack blunting, 107-109 crack depth effect, 390-393 crack size effect, 480 criterion critical stress intensity factor, 381 through-thickness vielding before fracture, 377-378 definition, 68 difference between initiation and arrest behavior, 404-408 effect of constraint, 101–109 loading rate, 98-101 temperature and loading rate, 114 temperature and strain rate, 16, 71, 73 effect on life under fatigue loading, 349-350 elastic-plastic behavior, 69-70, 72 fracture criterion, 366–367 fully plastic behavior, 69, 71-72 as function of a/W ratio, 391-395 loading rate effect on behavior of structures, 387-388 slow, initiation at, 408 lowest value, 68-69, 72 materials with low values, use, 346 microstructure effect, 273 plane-strain impact, correlation with CVN energy absorption, 119-120 relation with static and dynamic, 405 stress and critical flaw sizes, 336

requirements, specifying, 367 service conditions affecting, 69-76 shear lip size and, 102-103 temperature and strain rate effect, 386-387 test, weldments, 277-279 Trans Alaska Pipeline Service oil tankers, 441-443 transition behavior, steels, static and impact loading, 476, 481 under linear-elastic condition, 68-69, 72 values of steels, 150 see also Stress-intensity factors Free surface correction factor, 35 stress-intensity factors, 44 Frequency-of-occurrence data, 217-218

## G

Good design practice, 140 Griffith analysis, 35 Griffith fracture criterion, 59– 60 Griffith Theory, 58–60

## H

Heat treatment effect on K<sub>1scc</sub>, 287, 290 postweld, effects on aswelded components, fatigue behavior, 263– 264 Histogram, fatigue loading,

Trans Alaska Pipeline Service oil tankers, 445–447 Holes, subjected to point or pressure loading, stress-intensity factors equation, 42–43 Hydro-test, to establish fitness for continued

## Ι

service, 402-404

Ingram Barge, 428-437

constraint effect on structural behavior, 428-431 failure, 431-436 triaxial stress loading, 429-430 Initiation life, relation to propagation life, 212-213 Instrumentation, test, 82-85 Interim Guidelines for Welded Steel Moment Frame Structures, 338 Irwin, George R., comprehensive fracture-control plan, 360-363

# J

J integral, 54–55, 63–64 calculation, 91–93 stress-intensity factors relationship, 126–127

## K

K<sub>Isee</sub>, 286–290
corrosion-fatigue-crack-propagation behavior below, 313–320
cutoff time effect, 290
date for material-environment systems, 291–294
design use, 343, 345
tests using cantilever-beam specimen and bolt-loaded WOL specimens, 287, 289

## L

Leak-before-break criterion, 378–381 Load-crack-mouth-opening displacement, 85–87 Loading rate affecting fracture toughness, 70–72 effect on fitness for service analysis, 386–389 fracture toughness, 98– 101 stress-intensity factors, 96–100

evaluating remaining life, 388 fracture toughness, effect on behavior of structures, 387-388 reduction, fracture-control plan, 353 Loading-rate shift, see also Structural steels Load-line displacement, 84, 86 Load-load-line displacement, 85 - 87Lock-and-dam sheet piling, 455-467 failure analysis of sheet 55, 462-466 failure description, 457, 459 - 461steel properties, 457, 461-462 Long-life behavior, corrosionfatigue-crack initiation, 303 Low-cycle fatigue, tapered welded specimen, 251-253 Lower-transition region, short- vs. deep-crack specimens, 391–393

## Μ

Magnification factor, 154–155 Martensitic steels, fatiguecrack propagation, constant amplitude load fluctuation, 199-200 Materials selection, 142, 144-146 economics, 145  $K_{\rm lc}/\sigma_{\rm vs}$  ratio, 144 Material toughness k<sub>iscc</sub>, 22 relationship with stress and flaw size, 18 Metallographic analysis, steel casings, 476, 478, 481-483 Microstructure effect on fracture-toughness behavior, 273 weld metal and heateffected base metal, 274-279

Mohr's circle of stress, 105, 429–430 Motor case, 260-in.-diameter, failure analysis, 146– 150 Multiple-load fracture paths, 351–352

#### Ν

Nil-ductility temperature test, 13 Nil-ductility transition temperature, K<sub>Id</sub> value, 123-126 Northridge earthquake, 394-39Š Notched geometries, constraint to plastic flow cause by, 429-430 Notches cause stress intensification, 183 predicting fatigue-crack initiation, 189-192 single-edge, stress-intensity factor equation, 35-37 Notch toughness, 10-14 brittle fractures and, 9 criterion specification, 366-367 fracture-control plan, 351 implied vs. guaranteed, 423-424 measurement, 11 relation to structural performance, 364--365 transition temperatures, 12 - 13

## 0

Oil tankers, see Trans Alaska Pipeline Service oil tankers Out-of-plane constraint, 389– 390

## P

PD 6493, 338, 396–400 failure assessment diagram, 397–399 Plane strain, 32–33 limiting conditions, 374– 376 macroscopic, 109 Plane-stress, limiting conditions, 374-376 Plastic flow, constraint effects on fracture toughness, 102 - 104Plasticity, microscopic, 109 Plastic zone size, 50–52 large, effective stressintensity factors, 51-54 Point Pleasant Bridge fracture, 6-8 Pop-in, 388 Probability-density distribution, 216-219 Proof test, to establish fitness for continued service, 402-404 Propagation life, relation to initiation life, 212-213

# R

Random-stress loading, 165 Rayleigh curves, 218 Reaction stresses, 239 Reduction factor, 443-444 Residual stress beneficial and detrimental, 239 development in weldments, 240-241 effect on crack growth, 343 fatigue crack behavior, as-welded components, fatigue behavior, 260-263 elimination, 263-264 induction, 239 measuring, 240 redistributed under cyclic loading, weldments, 248 superposition of applied compressive stress, 262-263 applied tensile stress, 262 weldments, 238-241 Residual-stress model, 220 Resistance force, 15-16 definition, xv analysis of results, 85-87 **ASTM Standard Fracture** Tests, 76–79 critical, in terms of stressintensity factors, 90 overview, 67-69

test fixtures and instrumentation, 82–85 test specimen notch, 82 size, 80–82 Retardation, fatigue-crackgrowth, 220 Roberts-Newton lower-bound CVN-K<sub>Ic</sub> relation, 126– 127 Root-mean-square model, 221–225 Rotating-beam fatigue tests, 169 Rough machining, 252

## S

SAC Report 95-09, 395 Safe-life design, 135 Service conditions, affecting fracture toughness, 69-76 constraint, 71–76 loading rate, 70-72 temperature, 70 Shear stress planes, 104 relationship with normal stress, 104–105 Ship failures, 4-6, 338 constraint experiences, 431 see also Ingram Barge; Trans Alaska Pipeline Service oil tankers Ship steels, CVN impact criterion, 370-373 Single-edge notch, stressintensity factors equation, 35–37 Smooth welded components, fatigue crack behavior, 250-253 specimen geometries and test methods, 250-251 surface roughness effects, 251-253 S-N curve, 168-171, 212 initiation and propagation components, 21, 183 Specimen notch, 82 Specimen size, 80-82 SR16 Impact Testing, 473 Static loading fracture-toughness transition behavior, steels, 476, 481

transition region, 368, 373 Steel bridges failures, 5-6 fracture-control plan, 354-360 AASHTO Charpy Vnotch requirements, 356-359 design, 354-355 fabrication, 355 high-performance steels, 357 material, 355-356 verification of AASHTO fracture toughness requirement, 357 fracture criterion, 381-382 see also Bryte Bend Bridge Steel casings API specifications, 482–483, 487 chemical composition, 468-469 Steels chemical composition, restrictions, 5 fatigue-crack growth, 225-229 fracture-toughness transition behavior. static and impact loading, 476, 481 high-performance, fracturecontrol plan in bridges, 357 properties, 457, 461-462 Steel weldments, fatiguecrack propagation, 210-212 Storm avoidance, fatigue life and, 438 Strain-controlled test specimen, 172 Strain-life tests, 170, 172 Stress allowable, 133-134 design, 153 effect on life under fatigue loading, 349-350 flow lines, 242 history, 216-217 limiting values, 67 mean, effect on fatiguecrack propagation, 203-206 nominal, relation to critical stress-intensity factor, 136, 141

normal, relationship with shear stress, 429 principal, 104 relation with critical flaw sizes and material fracture toughness, 336 flaw size and material toughness, 18 Stress amplitude, 165–166 Stress analysis, cracks in elastic solids, 31-32 Stress concentration caused by grooves, scratches, and cracklike surface irregularities, 252 effect on fatigue, 184-187 fatigue-crack growth, 207, 209-210 magnitude, 242-243 effects of dimensions, 258 regions, 244 weldments, 241-245, 246 Stress-concentration factor, 29 - 30Stress-corrosion cracking, 281-296 cantilever-beam specimen, 284-286 crack-growth-rate tests, 294 - 296experimental procedures, 283-288 fracture-mechanics approach, 283 K<sub>Iscc</sub>, 286-290 date for materialenvironment systems, 291–294 test duration, 290-291 test geometries, 282 Stress intensification, 183 planar discontinuities, 243 surface discontinuity, 243 Stress intensity factor analysis lock-and-dam sheet piling, 463-465 Stress-intensity factors, 15, 28 - 64applied, 135 calculation, 28, 67, 91 vs. crack length, lock-anddam sheet piling, 464-465

critical, 67-68 intermediate load, rate shift, 111 intermediate-loading rate, 100 limiting thickness for plane-strain behavior, 106-107 predicting using CVN impact tests, 119-121 relationship with uppershelf CVN test results, 120 - 124slow-loading, effect of loading rate, 98, 100 thickness effect, 101-103 under plane strain, 74–76 critical crack size as function of, 144-145 for critical details, Trans Alaska Pipeline Service oil tankers, 443-444 critical resistance force in terms of, 90 critical value, 15-16 CTOD relationship, 126-127 effective, large plastic zone size, 51-54 effect on incubation time, 290-291 general form, 34 impact, 457 value at NDT temperature, 123-126 increased by fatigue to critical stress intensity factor, 141 J-integral relationship, 126-127  $K_{\rm Ic}$ - $K_{\rm Id}$  impact-loading-rate shift, 110–111 limiting values, 67 materials selection. economics, 145 nearly related to stress, 33 for place strain, 88 prediction using CVN- $K_{Id}$ - $K_{\rm Ic}$ -J and S relations, 126 - 131relation to nominal stress and flaw size, 136, 141 subcritical-crack-growth rate, 295 root-mean-square corrosion-fatigue-crackgrowth rate as

function of, 311-312, 316-319 crack-growth rate as function of, 223-225 studying stress-corrosion cracking, 283 surface flaw, 403 temperature and loading rate effects, 96-99 temperature shift, 109-110 value of crack geometrics, 137 Stress-intensity factor equations cracks growing from round holes, 40-41 embedded elliptical or circular crack in infinite plate, 37-39 estimation of other factors, 42, 44-47 holes or cracks subjected to point or pressure loading, 42-43 single crack in beam in bending, 41-42 single-edge notch, 35-37 superposition, 47-50 surface crack, 39-40 through-thickness crack, 35 Stress-life test, 168-171 Stress raisers, 177 Stress range, 165 effective, 272 vs. fatigue life, 255–256 maximum, 184 Stress ratio, 166 dependence of fatiguethresholds stressintensity-factor range on, 198-199 effect on corrosion-fatigue-crack initiation, 302 fatigue-crack propagation, 205 Stress-strain curve, ductile and brittle materials, 9 - 10Structural failures, brittle, 3-9 Structural steels inherent fracture toughness, temperature and loading rate and, 95 loading-rate shift, 109-116 CVN temperature shift, 109-110

 $K_{Ic}$  and  $K_{Id}$  impactloading-shift, 110-111  $K_{\rm Ic(t)}$ intermediate-loadingshift, 111 predictive relationship for temperature shift, 112 regions of fracture behavior, 77 significance of temperature shift, 112-116 Surface crack, stress-intensity factors equation, 39-40 Surface crack model, 447 Surface finish, effect on the fatigue limit of steels, 254 Surface flaw, stress intensity factor, 403 Surface roughness, fatigue crack initiation effects, smooth welded components, 251-253

## Т

Temperature affecting fracture toughness, 70 effect on stress-intensity factors, 96-100 reference, establishing master curve, 93-94 Temperature shift, 119 between K<sub>Id</sub> and K<sub>e</sub>, 126 Thermal stress relief, 263 Three-point bend test, setup, 83 Threshold stress-intensityfactor range, 196–199 dependence on stress ratio, 198 - 199Through-thickness crack constraint conditions, 105-106stress-flaw-size relation, 138 - 140stress-intensity factors equation, 35 Through thickness crack growth model, 448 Through-thickness stresses, 101 Through-thickness yielding criterion, 374-378 plane stress condition, 376– 377 Time to failure

influence of specimen geometry, 286, 288 tests, stress-corrosion cracking, 284 Titanium alloys, fatigue-crack propagation, constant amplitude load fluctuation, 202–203 Total fatigue life, 163 Trans Alaska Pipeline Service oil tankers, 438-454 application of methodology to a detail, 441–450 critical details, identification, 441 fatigue crack propagation in bottom shell plates, 447-450 fracture toughness, 441-443 histogram of fatigue loading, 445, 447 inspection capability for initial crack size, 444-445 stress intensity factors and critical crack size, 443-444 background, 439 fracture mechanics methodology, 439-441 reduced fatigue loading effect, 450-453 storm avoidance, 438 Transient loading, environmental effects during, corrosionfatigue-crack propagation, 320-323 Transition temperature, notch toughness, 12–13 Transition-temperature criterion, 373-374 Transition temperature shift loading rate and, 113 predictive relationship, 112 significance, 112–116 Triaxial tensile state of stress, 101Two-stage CVN-K<sub>Id</sub>-K<sub>Ic</sub> correlation, 126-127

## U

Uniaxial tension test, 429 Useful life, structural component, 334 Variable amplitude cyclic loads, 166–167 weldments, 269–272 example problem, 270– 272

v

## W

Waveform, effect on fatiguecrack propagation, 206-209 Welded bridge components, AASHTO fatigue design curves, 265-267 Weldments, 237-279 arc-welding, 273-274 crack extension, 369 discontinuities, 243, 245 categories, 245-246 effect on fatigue behavior, 247 fatigue crack initiation sites, 246-250 geometric, 257-258

their effects, 243, 245-250 distortion, 240-241 fatigue crack behavior, 250-264 smooth welded components, 250-253 as welded components, 253-264 weld termination, 248-249 fracture-toughness behavior, 272-279 fracture-toughness test, 277 - 279gouges and weldimperfection stress raisers, 267 methodologies of codes and standards, 264-269 AASHTO fatigue design curves for welded bridge components, 265-269 primary cause of fractures, 335

reducing magnitude of stress concentration. 258 residual stresses, 238-241 steel, fatigue-crack propagation, 210-212 stress concentration, 241-245 variable amplitude cyclic loads, 269-272 example problem, 270– 272 Welds, defective, 4--5 Williams stress function, 394 WOL specimens, bolt-loaded, Klscc tests, 287, 289

## Y

Yielding, 104 Yield strength critical crack size as function of, 144–145 fatigue-crack initiation threshold dependence on, 189, 260–262 values of steels, 150