

# Subject Index

---

## A

- Adjusted compliance ratio, 388  
 Aluminum  
     ductile crack growth, 85  
     early state fatigue damage, 427  
     stress-life fatigue curves, 388  
 ASTM E 399, 357  
 ASTM E 813, 69, 357  
 ASTM E 1152, 69, 357  
 ASTM E 1737, 357  
 ASTM E 1820, 61, 357  
 ASTM E 1921, 21, 51, 357  
 Atomistic simulation, 278

## B

- Bending stresses, induction-hardened shafts, 240  
 Biaxial fatigue, 299  
 Bolt-loaded specimen, 377  
 Brittle cracks, welded beam-column connections, 439

## C

- Cell modeling, ductile-to-brittle transition, 152  
 Charpy impact energy, 61  
 Cohesive strength, ductile fracture modeling, 139  
 Cohesive zone models, 139  
 Common format equation, 34  
 Compliance ratio, 185  
     adjusted, 388  
 Confocal scanning laser microscopy technique, 299  
 Constraint  
     physical evidence, 115  
     quantifying, 102  
     semi-elliptical cracks, 403  
 Crack  
     elliptical subsurface, 240  
     environmental, 377  
 Crack closure, 201, 227, 388  
     elastic, 185  
     metal alloys, 263  
     plasticity-induced, 227  
 Crack face displacements, 115  
 Crack growth  
     ductile, 85  
     hydrogen, 377  
 Crack initiation, 347  
 Crack propagation, 227  
     stress intensity factor, 201  
 Crack tip opening angle, 85  
 Crack tip opening displacement, 115  
 Crack tip shielding, 227  
 Crack tip stress field, 347

- Crack wake influence, 185  
 Creep deformation, accumulated, 313  
 Creep-fatigue crack growth rate, 313  
 Creep fracture parameter, effects of accumulated  
     creep deformation, 313  
 CVN impact test, 61

## D

- Damage mechanics, 152  
 Damage tolerance, honeycomb core sandwich panels, 169  
 Debonding, stiffener, 456  
 Disbond, facesheet-from-core, 169  
 Discontinuities, 115  
 Dissipation rate, 139  
 Ductile fracture, modeling, 139  
 Ductile-to-brittle transition  
     fracture toughness, 21  
     modeling, 152  
 Ductility, welded beam-column connections, 439

## E

- Earthquake engineering, 439  
 Elasticity, semi-elliptical cracks, 403  
 Elastic-plastic fracture mechanics, 3, 357  
 Elastic region, common format equation, 34  
 Energy release rate, 169  
 Environmental cracking and fracture, 377

## F

- Facesheet-from-core disbond, honeycomb core  
     sandwich panels, 169  
 Failure assessment, fusion line cracks, 102  
 Fatigue, stress-life curves, 388  
 Fatigue crack, subsurface initiation, 240  
 Fatigue crack growth  
     biaxial strain ratio and, 299  
     mechanism, 299  
     multiparameter model, 327  
     niobium aluminide intermetallics, 278  
     stress-life curves, 388  
 Fatigue crack propagation, 201  
     lap joint specimens, 214  
     metal alloys, 263  
     subsurface, 240  
 Fatigue life, effective, 299  
 Finite element analysis, 227  
     creep fracture parameter, 313  
     honeycomb core sandwich panels, 169  
     semi-elliptical cracks, 403

size criteria, 357  
 3-D, 85  
 welded beam-column connections, 439

Finite radii notches, 69

Fracture  
 displacement-based characterization, 115  
 environmental, 377  
 niobium aluminide intermetallics, 278  
 semi-elliptical cracks, 403

Fracture mechanics  
 computational approach, 169  
 elastic-plastic, 3, 357  
 history, 347  
 linear elastic, 357  
 multiparameter model, 327  
 time dependent, 313  
 validity limits, 115

Fracture toughness  
 apparent, 69  
 evaluations in transition range, 21  
 niobium aluminide intermetallics, 278  
 predicting *J-R* curve, 61  
 testing, notched round bars, 69  
 transition behavior, 51  
 unifying principles for evaluating, 34  
 welded beam-column connections, 439

Fusion line cracks, failure assessment, 102

**G**

Geometry effects, 102, 139  
 Gurson model, 139

**H**

Hole expansion, 214  
 Honeycomb core sandwich panels, facesheet-from-core disbond, 169  
 Hoop strain, 299  
 Hydrogen embrittlement, 377  
 Hydrogen-induced cracking, 377

**I**

Impact energy, Charpy, 61  
 Induction hardening, 240  
 Instrumented bolt, 377

**J**

*J*-integral, 69, 357  
 as function of depth below surface, 115  
*J-Q-M* approach, 102  
*J-R* curve, predicting, 61

**L**

Lap joints, 214  
 Large-scale tests, ductile-to-brittle transition, 152  
 Leon, Alfons, 347  
 Life prediction  
 induction-hardened steel, 240  
 lap joint specimens, 214  
 stress-life fatigue curves, 388  
 structural metallic materials, 327  
 titanium, 201

Linear elastic fracture mechanics, 357  
 Load interaction, 201  
 Load transfer mechanism, 214

**M**

Magnetometers, 427  
 Master curve, 21, 201  
 micromechanical evaluation, 51  
 Material mismatch effects, 102  
 Meandering Winding Magnetometer, 427  
 Metal alloys, fatigue crack propagation, 263  
 Micromechanical models, 278  
 ductile fracture, 139  
 Modified crack closure method, 169  
 Multi-cell modeling, ductile-to-brittle transition, 152  
 Multiparameter model, 327  
 Multiple site damage, 214

**N**

Niobium aluminide intermetallics, forged damage-tolerant, 278  
 Notched round bar, 69  
 Notch stresses, 347

**O**

Out-of-plane bending, 85  
 Overload effects, 227  
 Overstrains, compressive, 299

**P**

Periodic compressive overstrain, 299  
 Planar fracture specimens, fracture toughness evaluation, 34  
 Plasticity, semi-elliptical cracks, 403  
 Plastic region, common format equation, 34  
 Plate finite element, 456  
 Pressure vessel steels  
 fracture toughness evaluations, 21  
 modeling ductile-to-brittle transition, 152  
 Probabilistic methods, 327

**R**

- Reference temperature, 51  
 Residual stresses, 201  
     induction-hardened shafts, 240  
 Rivets, 214

**S**

- Seismic design, 439  
 Separation energy, ductile fracture modeling, 139  
 Size criteria, consistent, 357  
 Slenderness ratio, 456  
 Stainless steels, early state fatigue damage, 427  
 Steel  
     biaxial fatigue tests, 299  
     crack closure effects, 227  
     high-strength, 377  
     induction-hardened, 240  
     semi-elliptical cracks, 403  
     welded beam-column connections, 439  
 Stiffener debonding, 456  
 Stitching, 456  
 Strain  
     mean, 227  
     range, 227  
 Strain energy release, stitching effect, 456  
 Strain ratio, biaxial, 299  
 Stress, semi-elliptical cracks, 403

**S**tress intensity, 357

    effective, 185, 388

**S**tress-intensity factor

    crack propagation, 201  
     semi-elliptical cracks, 403

Structural metallic materials,fatigue crack growth,  
     327

**S**ubstructuring, 227

Surface cracks, semi-elliptical, 403

**T**

- Titanium, fatigue crack propagation, 201  
 Transition range, fracture toughness evaluation, 21

**U**

- Unloading compliance, 357  
 Unstable fracture, 102

**W**

- Weighardt, Karl, 347  
 Welded beam-column connections, finite element  
     analysis, 439  
 Weldments, constraints, quantifying, 102  
 Woven composites, plate element-based model, 456