

INDEX

A

Alignment, specimen 22
 Analysis data 52
 thermal and mechanical cycling 185
 Antigalling 91
 Atmosphere, protective 133

B

Backlash elimination 89
 Baldwin-Lima-Hamilton Corp. strain
 gages 153
 Barber Coleman controllers 96
 Bending, fatigue tests 149
 operation 156
 Biaxial stress 186
 ratio 150
 Break detection 96
 Brush, Mark 280 recorder 47

C

Calibration 136
 computer 123
 controls 141
 extensometer 42, 136
 load cell 167 (fig.), 172
 strain sensor 113
 Clip gage 6, 21, 41
 slipping 22
 Collins transducer 95
 Command signals 82
 Console 33
 control 80, 105, 136
 Control, axial strain 92
 closed-loop 81
 computer 122
 cyclic bending 156
 heating system 138
 strain (specimen) 136
 temperature 80, 103, 173
 thermal 79
 Crack
 initiation 32, 80, 94, 97
 detection 69, 79

 elevated temperature 98
 measurement 79
 morphology 53
 observation 80
 propagation 32, 80
 Cryogenic testing 85
 Cryostat 85
 Cycle changes (mechanical properties)
 9
 for failure 144
 Cyclic, bending tests 150
 creep testing 85
 frequencies 19
 plasticity 97
 strain hardening exponent 7
 thermal-mechanical 185
 Cyclic strain hardening curves 11, 52
 cyclic strain softening curves 11, 52
 cyclic stress-strain curves 9, 11, 12,
 13, 53
 methods determining 12
 Cyclically hardening 7, 158
 softening, 7, 158

D

Data, analysis (interpretation), re-
 duction, and presentation 22, 52,
 144, 160
 Data-Trak 12
 measurements 28
 output 157
 recording 47, 60, 124
 (Also see *Measurements*)
 Data-Trak (MTS Systems Corp.) 12,
 33, 44, 51, 174, 176
 Daytronic 60
 (Model No. 300 CL-60) 55
 Definition, of engineering stress-strain
 properties 6, 24
 of failure 49, 116, 142, 156, 185
 of thermal fatigue 164
 of true stress-strain properties 7, 24
 Dewar Flask 55
 Dial indicator(s) 75

Die set, advantages and disadvantages 73

Dislocation structures 61
studies 64

E

Elastic component 14

strain amplitude 17

strain-life curve 17

Electrohydraulic (closed loop) 103

Electropolishing, specimen 61

Engineering (and true) stress-strain, definitions 24

Environment(s), atmosphere (protection) 133

extensometers 95

saltwater 156

Extensometer 21, 112, 135, 178

attaching 75

calibration 42

clip gage, slipping of 22, 42

diametral 111

drift 42

environment testing 95

high temperature 94

low temperature 55, 58

optical 33, 42

resolution 43

ridge 93, 94

strain gage type 56

support 75

Extensometry 41, 53, 92

F

Facility, arrangement 141

Failure, definition 49, 116, 142, 156, 185

determination 49, 61

Fatigue, bending 150

crack indication (hysteresis loop) 21

crack initiation 69

cumulative 85

cyclic bending (flexural) 150

ductility coefficient 11

ductility exponents 15

ductility properties 14, 15

failure 116, 142

flexural 149

flexural (comparison direct) 161

problems, low cycle fatigue 87

property relationships 10

strength coefficient 16

strength exponent 16

strength properties 14, 16

thermal 87, 163

thermal, definition 164

transition life, definition 22

Fixtures, loading 108

(Also see *Grips*)

Flexure fatigue testing 149

comparison to direct stress 161

operation 156

specimen 150

Fracture surfaces 61

Frequency 105

(Also see *Test Speed* and *Test Frequency*)

G

Generator, high frequency 103

induction 118

Grain diameter 93

Grip(s) 70, 89

alignment 134

design 133

liquid metal 22

water-cooled 110, 169

(Also see *Fixtures*)

Gripping 168

assembly, 172

(mounting), 110

(Also see *Woods Metal Joint*)

H

Heater, element 79, 96

internal 78

Heating 116

elements 79

induction 109, 116, 138, 173

resistance 173

Heating system 138

Hourglass specimen 107, 131

Hydraulic control 84

system, 84, 153

Hydraulic supply 113

ram 30, 33

Hydrogen (liquid) 85

Hysteresis loop(s) 21, 46, 47, 49, 51,
60, 83, 89, 116, 139, 140, 155,
164, 167, 178, 180
crack indication 49
fatigue crack indication 21

I

Incremental step test 12, 51
Induction coil 109
heating 118
Infrared, temperature measurement
175
Installation, specimen 91
Instron Corp. (testing) 29, 53, 142,
176
clip gage 41
load cell 134
recorder 60
strain gage 135

L

Leeds and Northrup controls 174
Lehigh University, specimen 150
Leitz Metallux ND microscope 32
Limited life (fatigue definition) 130
Liquid metal grip 22
(Also see *Woods Metal*)
Load, holding 96
measurement 110
measuring gage 155
Load cell 30, 55, 110, 155
calibration 167 (fig.), 172
Instron 55, 134
Strainert 32
Loading fixtures 108
frame 29, 72, 103, 109
alignment 72
rods 70
Low cycle fatigue, definition 27
philosophy 27, 129
test speed 153
(Also see *Frequency*)
Low temperature tests 55
Lubricants, high temperature 90

M

Measurement(s) 153
crack initiation 79
load 74
observations 73

strain 77
temperature 78
test conditions 83
Mechanical, components (of strain)
185
extension (specimen) 177
hysteresis loop 10
variables 29
Metallographic techniques
(associated with low cycle fatigue)
61
Microscope (for crack detection) 79
Modes of operation 84, 118
Monotonic strain hardening exponent
7
stress-strain properties 6
tension test 7, 13, 51
Moog servovalve 31
Moseley (Hewlett-Packard Corp.) 2D
recorder 155
Mounting plates 110
MTS Corp. (Materials test system) 19,
21, 29, 33, 95
extensometer calibrator 40
(Also see *Data-Trak*)
Multiple step test(s) 11

O

Objectives, low cycle fatigue testing 88
Operating procedure 123
Operation(s) 84, 139, 142, 156
(Also see *Test Start-up*)
Operation modes 84, 118
Optical pyrometer 173, 175
Optron optical extensometer 33
Oscilloscope 22, 83
Tektronix 47

P

Plastic component of strain 14
Plastic strain amplitudes 16
range 52, 60
Power supply 139
transformer 173
Presentation, data 52
Program, synchronization (thermal
and extension) 176
Program(mer) 105
parameters 101
selection 43, 60

Proving ring 75
Pyrometer 173, 175

R

Recording data 47, 60
equipment 103, 116
Reduction data 52
Results, interpretation 97

S

Schaevitz, linear variable differential transformer 58
Servovalve, (Moog No. B-102) 31
Shutoff (-down) 114
automatic 84, 116, 125, 140, 156
device 49
Slip band(s) 32
damage 61
Slip band topography 28
Specimen(s) 3, 33, 56, 106, 150, 168
alignment 22
bend 150
buckling 34, 132
coding 70
cooling 91
decreasing 133
design(s) 4, 34, 68, 131
electropolishing 37
finish 3, 36, 108, 132
flexure (bending) 150
stress concentration, K_t 150
gripping 70, 89, 168
heating 108, 116
heating effects 22
hourglass 107, 131
installation 91
measurement 4, 37, 56
mounting 37
preparation 132
shape 3, 34, 130
size 3
storage 5
threads 3, 35
Spectrum straining 13
Speed, flexure test 153
Strain
amplitude (set) 13, 18
test 18
axial (control) 123, 124

control 95, 102, 118, 124
accuracy 113
control (low cycle fatigue testing) 13
conversion (diametral to axial) 77, 119
cycle 38
diametral 124, 136
elastic 17
gage 56, 153
hardening exponent 7
holding 96
-life curves (plot) 14, 17, 18, 23
measurement 110, 178, 180
(high temperature) 75
measuring gage 155
mechanical (components of) 185
(cycling analysis) 185
plastic 124
range, diametral 77, 136
plastic 98
total 98
sensor 112
true (definition) 24
Strainert load cell 32
Stress amplitude (flexure) 158
true tensile (definition) 24
Stress control 21
Stress-strain engineering properties 6
true properties 7
Structural variables 29

T

Tektronix Model No. RM56.4 oscilloscope 47
Temperature control 96, 103, 118, 173
gradient (distribution) 117
low (liquid nitrogen) 53
measurement 78, 173
program 173
Test(ing) 5
conditions (measurement) 83
control 49
cryogenic (low temperature) 55
cyclic creep 85
equipment 102
frequency 22, 46, 73, 105
incremental step 12

- method 166
 - approach 101, 102
 - parameters 101
 - procedures 19, 102
 - multiple step 11
 - objectives 88
 - philosophy 129
 - sequence (summary) 20
 - speed 153
 - start-up 49, 60
 - tension versus compression 127
 - test systems (machines) 29, 54, 139, 153
 - (Also see *Operations*)
 - Thermal components 172
 - control 79
 - cycling (analysis) 185
 - fatigue 163
 - fatigue (definition) 164
 - length (specification) 175
 - sequence summary 20
 - Thermocouple(s) 80, 96, 117, 174
 - manufacture 175
 - specimen attachment 78, 96, 117, 133, 175
 - time constant 175
 - Thermoelastic effect 96
 - Total strain-life curve 17
 - Transducers, Inc. load cell 155
- U**
- Ultrasonic, crystal attachment 72
 - detection, fatigue crack 69, 80
 - sensor 69
- V**
- Varian recorder 47
- W**
- Wave form, saw-tooth 95
 - Wiedmann-Baldwin 96
 - Woods metal joint (grip) 22, 37, 56
 - advantages 40
 - pot 55