

## Subject Index

- A**
  - ASTM standards
    - A 515, 100
    - A 533B, 100, 286, 425
    - E 399, 445, 519
    - proposed practice, fracture toughness in transition, 286
- B**
  - Bending loads, 21
  - Bend specimens, 445
    - small, 519
  - Biaxial loading, 316, 501
  - Biaxial stress effect, 3
  - Brittle-ductile transition, 3, 191
  - Brittle fracture, 519
  - Burst test, 392
- C**
  - Cavity growth modeling, 363
  - Center cracked specimens, 392
  - Circumferentially notched round bar specimens, 344
  - Cleavage fracture, 3, 134, 163, 191, 445
    - toughness, 100, 519
  - Compact tension specimens, 71, 88
  - Constraint elevation, 134
  - Constraint factor, 21, 134, 209, 255
    - out-of-plane, 71
  - Constraint gurson model, 163
  - Constraint model, 461
  - Cracked round bars, 255
  - Cracked welds, 363
  - Crack growth, 134, 191
    - resistance, 163
    - resistance curve, 71, 209, 232, 392
    - stable, 71, 100
  - Crack initiation assessment, weld, 363
  - Crack opening stress, 191
  - Crack propagation, 88
  - Crack tip constraint, 43, 209, 316, 392, 479, 501
  - Crack tip displacement, 21, 100
  - Crack tip opening angle, 21
  - Crack tip opening displacement, 425
  - Crack tip stress fields, 3, 461
- D**
  - Deformation, 255
    - limits, 445
  - Deformation theory plasticity, 43
  - Double-edge cracked tension geometries, 461
  - Double-edge notch specimen, 316
  - Ductile/brittle fracture, 134
  - Ductile crack extension, 100
  - Ductile failure,
    - micromechanisms of, 209
  - Ductile fracture, 71, 134, 163, 191, 425
  - Ductile tearing, 100, 134, 363
    - resistance, 232
  - Ductile-to-brittle transition region, 100, 134, 286
  - Ductile to cleavage fracture mode, 255
- E**
  - Elastic-plastic analyses
    - plane strain, 43
    - finite element analyses, 21, 344, 425
    - fracture, 3, 425
  - Elevation, constraint, 134
- F**
  - Ferritic materials, 100
  - Ferritic steel, 191, 255, 286

## 542 CONSTRAINT EFFECTS IN FRACTURE

Finite element analysis, 43, 71,  
88, 232

elastic-plastic, 344, 425

round bars, 255

three-dimensional, 316

Finite elements, 21, 100, 134,  
163, 191

Flaw, semi-elliptical surface,  
88

Four-point-bend specimens,  
191

Fracture resistance, 163

Fracture toughness, 425, 461,  
479, 501

ASTM E 399, 445, 519

cleavage, 100

ductile/brittle, 134

in transition range, proposed

ASTM standard, 286

measurements, 255

### G

Geometry

effects, 344, 461

shallow-flaw, 501

variation effects, 71

Zr-2.5Nb, 392

GURSON model, 232

constraint gurson, 163, 191

### H

Hydrostatic field, 479

### J

J-A<sub>2</sub> methodology, 3

J-concept, modified, 88

J-integral, 3, 286, 425, 445

J-Q approach, 316, 363, 461, 479,  
501

J-R curve, 209, 392

J-R curve, 71, 232

J-T characterization, 43, 363

### K

$K_{Ic}$ , 445

### L

Loads and loading, 43, 363

bending, 21

biaxial, 316, 501

dynamic, 232

effects, 344

static, 232

tension, 21

unloading, 479

### M

Micromechanical model, 209

Middle tension specimens, 88

Models and modeling

cavity growth, 363

constraint, 461

constraint gurson, 163, 191

GURSON, 232

micromechanical, 209

numerical, 100

numerical, stable crack  
growth, 88

scaling, 286

statistical, 461

three-dimensional, 21

two-dimensional, 21

Molecular weight, 344

### N

Numerical model, 100

stable crack growth, 88

### P

Plane strain conditions, 71, 134

Plane strain elastic-plastic  
analyses, 43

Plane strain fracture, 445, 519  
toughness, 255

Plastic deformation, 134

Plasticity, 21, 344

deformation theory, 43

$J_2$  flow theory, 163

Polymethylmethacrylate, 344

Pressure tube material, 392

Pressurized thermal shock, 479

**Q**

*Q* stress, 209

**R**

R-curves, 425

**S**

Scaling models, 286

Scatter, 100

Short crack bend specimens, 286

Side-grooved specimens, 88

Single-edge notch specimens, 344

Size effect, 344, 461, 519

Small-scale yielding, 445

Stable crack growth, 71, 100

Standards

ASTM A515, 100

ASTM A533B, 100, 286, 425

ASTM E 399, 445, 519

ASTM proposed, fracture toughness, 286

BS4360, 425

Statistical model, 461

Steel, 100, 191, 255, 286, 316, 425, 461

Stress, out of plane, 316

Stress strain curves, 425

Stress triaxiality, 100, 134, 363

Surface tension, part-through, specimens, 88

**T**

Tension loads, 21

Tension specimens, 286

Thermal shock, 501

pressurized, 479

Three-dimensional model, 21, 88

Titanium, 255

Transition fracture toughness, 461

Triaxiality, 88, 209

stress, 100, 134

Tridimensional analysis, 71

TSE-5A, 501

Two-dimensional model, 21

Two-parameter characterization, 43, 134, 316, 363

*T*-stress, 43

**V**

Validity, 519

Void coalescence, 163

Void growth, 163

Void nucleation, 191

**W**

Weibull analysis, 286

Weibull model, 461

Welds, cracked, 363

Work hardening, 425

**Y**

Yielding, 100

small scale, 445

Yield strength, 425

**W**

Warm prestress, 479

**Z**

Zr-2.5Nb, 392