

Subject Index

A

- Acoustic emission, impact damage evaluation, 127
- Adhesion assessment, interfacial, composites, 401
- Aluminum laminates, aramid-reinforced, 637
- Angle-ply laminates
 - damage and failure mechanisms, 257
 - delamination, 491, 507
- AS4/PEEK laminates, specimen thickness effect, 281

B

- Bond strength, interfacial, surface treatment effects, 419
- Bundle strength theory, 453

C

- Carbon fiber, ceramic matrix composites, 620
- Carbon fiber/epoxy resin, impact damage evaluation, 127
- Central deflection, 218
- Ceramic matrix composites
 - fatigue damage, 620
 - progressive matrix damage, 176
- CFRP, 139
- Combined loading, graphite/epoxy tubes, 72
- Complementary energy, ply crack growth, 195
- Compliance, ply crack growth, 195
- Composites
 - with angle ply matrix cracks, 491, 507
 - with cutout, 473
 - delamination modeling, 218
 - dynamic response, 575
 - edge delamination, stress ratio effects, 538
 - failure initiation and ultimate strength, 35
 - fiber fracture, 430

- hardness testing, 401
- in-plane matrix failure, 341
- interfacial bond strength and surface treatment effects, 419
- interleaved, fracture toughness, 299
- macromodel, 381
- meso-indentation testing, 401
- micromechanical behavior, 381
- notched, interleaves, 552
- scaled angle-ply, 257
- specimen thickness effect, 281
- tensile deformation, 161
- tensile strength, 453
- unsymmetrical, interlaminar fracture analysis, 341

Compression

- cross-ply laminates, 473
- notched tubes, 72

Continuous ball indentation testing, 401

Copper matrix, 608

Crack growth

- aramid-reinforced aluminum laminates, 637
- notched tubes, 72
- rate, crossply laminates, 139

Crack propagation

- aramid-reinforced aluminum laminates, 637
- stable and unstable, 86
- water and jet fuel absorption effects, 318

Crack size, fiber fracture, 430

Cross-ply laminates

- curved, 105
- with cutout, 473
- tensile deformation, 161
- thermal cycling, 139

D

Damage

- characterization using load/stroke-frequency response measurement, 575
- prediction, cross-ply curved laminates, 105
- progress, with notches, 55

Damage (*cont.*)
 propagation, 5
 thermal expansion coefficient change
 as parameter, 139
 Damage mechanisms
 notched laminates, 552
 scaled angle-ply laminates, 257
 Damage modes, SiC/Ti-15-3 laminates,
 161
 Damage tolerance, delamination, 538
 Deformation, interleaf behavior, 299
 Delamination
 aramid-reinforced aluminum
 laminates, 637
 cross-ply curved laminates, 105
 edge, stress ratio effect, 538
 effect on Mode I and II interlaminar
 fracture toughness, 239
 fracture analysis, 507
 free edge, unsymmetrical laminates,
 341
 induced, graphite/epoxy composites,
 86
 interleaf deformation behavior and
 film-resin adhesion, 299
 laminates with angle ply matrix
 cracks, 491, 507
 modeling, interlayer shear slip
 theory, 218
 specimen thickness effect, 281
 water and jet fuel absorption effects,
 318
 Double-cantilever beam test, 239
 thickness effect, 281
 Durability, laminates, 538
 Dynamic mechanical analysis, 419
 Dynamic response, 575

E

End-notch flexure test, 239
 Energy release growth, ply crack
 growth, 195
 Environmental effects, water and jet
 fuel absorption, 318
 Epoxy systems, fiber-reinforced, meso-
 indentation testing, 401

F

Failure analysis, 35
 notched tubes, 72
 Failure mechanisms
 scaled angle-ply laminates, 257

 water and jet fuel absorption effects,
 318
 Failure mode, edge delamination, 538
 Fatigue
 characterization, laminates with
 angle ply cracks, 507
 crack growth, aramid-reinforced
 aluminum laminates, 637
 edge delamination, 538
 high-temperature tension-
 compression, 608
 loading, axial, notched laminates, 552
 thermomechanical, titanium metal
 matrix composites, 591
 threshold, aramid-reinforced
 aluminum laminates, 637
 Fatigue damage
 ceramic matrix composites, 620
 cross-ply laminates with cutout, 473
 Fatigue fracture threshold,
 delamination effect, 239
 Fiber bridging
 aramid-reinforced aluminum
 laminates, 637
 zone length, 281
 Fiber end effects, micromechanical
 behavior, 381
 Fiber fracture
 aramid-reinforced aluminum
 laminates, 637
 micromechanical analysis, 381, 430,
 453
 Fiber/matrix interface strength, 419
 Fibers, PAN- and pitch-based, 419
 Fiber spacing, 453
 fiber fracture, 430
 Fibrous composite laminates, in-plane
 matrix failure, 341
 Filament wound tube, impact damage
 evaluation, 127
 Film-resin adhesion, fracture
 toughness, 299
 Finite element analysis
 2-D, 5
 3-D, laminates with angle ply cracks,
 491
 interlayer shear slip theory, 218
 nonlinear, graphite/epoxy
 composites, 86
 Fractography, 318
 Fracture, notched tubes, 72
 Fracture analysis, interlaminar,
 unsymmetrical laminates, 318,
 341

Fracture mechanics approach, ply
 crack growth, 195
 Fracture strength, 55
 Fracture toughness (*see also*
 Interlaminar fracture toughness)
 interleaved composites, 299
 laminates, 105
 Free edge effect, 35

G

GFRP system, 139
 Glass-ceramic matrix composites,
 progressive matrix damage, 176
 Glass/epoxy laminates, delamination
 effect, 239
 Glass matrix composites, progressive
 matrix damage, 176
 Graphite/epoxy composites
 with angle ply matrix cracks,
 delamination, 491, 507
 cross-ply curved laminates, 105
 delamination, water and jet fuel
 absorption effects, 318
 edge delamination, 538
 matrix cracking-induced delamination
 propagation, 86
 notched, 55
 notched tubes, 72
 Graphite/epoxy fabric composites, 5
 Graphite fiber-reinforced plastic
 systems, damage and failure
 mechanisms, 257
 Graphite/PEEK composites, notched,
 55
 Graphite/thermoplastic laminates, with
 notches, 55

H

Hardness testing, composites, 401
 High-temperature tension-compression
 fatigue, tungsten copper
 composite, 608
 Hoop stress, 35

I

Impact damage, evaluation, acoustic
 emission, 127
 Ineffective length, 430, 453
 In-phase testing, titanium metal matrix
 composites, 591
 Interface, titanium metal matrix
 composites, 591

Interfacial quality, meso-indentation
 testing, 401
 Interlaminar fatigue toughness
 delamination effect, 239
 specimen thickness effect, 281
 Interlayer shear slip theory, 218
 Interleaves
 deformation behavior and film-resin
 adhesion, 299
 notched laminates, 552
 Internal variables, ply crack growth,
 195
 Interphase, fiber fracture, 430
 Isothermal fatigue, 591

J

Jet fuel, absorption and delamination,
 318

L

Laminates (*see also* Cross-ply
 laminates; Graphite/epoxy
 composites; Notched laminates)
 with angle ply matrix cracks,
 delamination, 491, 507
 aramid-reinforced aluminum, 637
 combined stress states, 195
 with cutouts, failure initiation and
 ultimate strength, 35
 edge delamination, stress ratio
 effects, 538
 fibrous composite, in-plane matrix
 failures, 341
 scaled angle-ply, 257
 specimen thickness effect, 281
 tensile deformation, 161
 unidirectional, notched, 575
 unsymmetrical, interlaminar fracture
 analysis, 341
 Load/stroke frequency response
 measurement, 575
 Local stress concentration, composites,
 453
 Low-velocity impact, evaluation,
 acoustic emission, 127

M

Matrix crack
 angle ply laminates, 491, 507
 crossply laminates, 139
 graphite/epoxy composites, 86

Matrix crack (*cont.*)

- growth under combined stress states, 195
- laminates, 105
- micromechanical behavior, 381
- progressive, 176

Matrix failure, in-plane, fibrous composite laminates, 341

Mechanical analysis, dynamic, 419

Meso-indentation testing, composites, 401

Metal matrix composites

- titanium, 591
- tungsten copper, 608

Microcracks

- discontinuous, fibrous composite laminates, 341
- orientations, 195

Micromechanical analysis

- behavior evaluation, model composites, 381
- composites, 453
- fiber fracture, 430
- glass-ceramic matrix composites, 176
- titanium metal matrix composites, 591

N

Notched laminates

- interleaves, 552
- tensile behavior, 55

Notched tubes, 72

Notch sensitivity, 55

O

Out-of-phase testing, titanium metal matrix composites, 591

P

Paris relation, 139

Peel stress distribution, unsymmetrical laminates, 341

Phase lag, dynamic response, 575

Phenomenological models, 195

Plasma treatment, film-resin bond strength, 299

Plycracks, combined stress states, 195

Polymer matrix composites, fracture toughness, 299

Q

Quasi-isotropic specimens, 575

R

Residual strength

- cross-ply laminates with cutout, 473
- notched laminates, 552

Residual stress, titanium metal matrix composites, 591

Resin matrix composites, 473

S

Scaling effects, laminates, 257

Shear, scaled angle-ply laminates, 257

Shear-lag model, 139

Shear slip, interlaminar, 218

Shear strength, interfacial, composites, 401

Shear stress, interlaminar, 218

SiC/LAS composites, progressive matrix damage, 176

SiC/Ti-15-3 laminates, tensile deformation, 161

Silicon-carbide fibers, thermomechanical fatigue, 591

Statistical failure model, 176

Stiffened panels, 5

Stiffening strips, 5

Stiffness, 575

Stitching, cross-ply laminates, 473

Strain

- concentration, fiber fracture, 430
- control, tungsten copper composite, 608

Strain energy, ply crack growth, 195

Strain energy release rate

- crossply laminates, 139

delamination, 239

laminates, 105

angle ply laminates, 507

unsymmetrical laminates, 341

water and jet fuel absorption effects, 318

Stress

- interlaminar, unsymmetrical laminates, 341
- laminates with angle ply cracks, 491

Stress concentration, 5

- micromechanical analysis, 453

Stress intensity, threshold, aramid-reinforced aluminum laminates, 637

Stress pattern analysis by thermal emission, 620
 Stress range, titanium metal matrix composites, 591
 Stress ratio, edge delamination characteristics, 538
 Stress/strain response, scaled angle-ply laminates, 257
 Surface treatment, interfacial bond strength and, 419

T

Tensile strains, orientation, graphite/epoxy panels, 5
 Tensile strength
 composites, 453
 fiber fracture, 430
 Tension, notched tubes, 72
 Tension-tension fatigue tests, laminates with angle ply cracks, 507
 Tension test
 cross-ply laminates, 473
 laminates with angle ply cracks, 491
 T800/epoxy laminates, specimen thickness effect, 281
 Thermal cycling, crossply laminates, 139
 Thermal expansion coefficient, change, as damage parameter, 139
 Thermoelastic technique, ceramic matrix composites, 620

Thermomechanical fatigue,
 unidirectional titanium metal matrix composites, 591
 Titanium metal matrix composites,
 unidirectional, thermomechanical fatigue, 591
 Torsion, notched tubes, 72
 Toughness, notched laminates, 552
 Transverse loading, graphite/epoxy composites, 86
 Transverse ply crack, 139
 Tungsten copper composite, high-temperature tension-compression fatigue, 608

V

Vibration frequency, 218
 Vickers fixed-load hardness test, 401

W

Water, absorption and delamination, 318
 Weibull shape factor, 453

X

X-radiography, dye penetrant-enhanced, laminates with angle ply cracks, 507