

# Subject Index

## A

- ACH (Air changes per hour) (*see* Air exchange measurements)
- Air exchange (*see also* Air exchange measurement, Air leakage measurements), 36, 61-69, 70-97, 399, 400
  - Following retrofit, 42-43 (Table 3, Fig. 5), 86, 265-267
  - Retrofit, Navy family housing, Mechanics manual, 296, 297 (Fig. 1)
  - Swedish standard SP1977:1, National Swedish Authority for Testing Inspection and Metrology: Standard method description, 400
- Air exchange measurements (*see also* Perfluorocarbon tracer system), 399-405
  - Air changes per hour (ACH), 240 (Equation 14), 295
  - Equations (15-22), 246-247
  - In high-rise office buildings, 137 (Fig. 1), 138, 139 (Figs. 2-3), 148, 149
  - In passive perfluorocarbon tracer system, 203, 220-221
    - Results and discussion, 222-226 (Fig. 6, Tables 5-8)
  - In pressurization testing, 275-277 (Table 5)
  - Infiltration and exfiltration, 71, 240 (Equation 14—ACH), 247-249 (Fig. 13, Table 21)
    - Mechanics' handbook, Navy family housing, 296
- Air exchange rates (*see* Air exchange measurements, Air infiltration measurement, Air leakage measurement)
- Air filtration (*see* Air infiltration)
- Airflow measurement (*see* Air exchange measurement)
- Airflow resistance
  - Of common building materials, 373 (Table 1)
- Air-handling equipment, large federal buildings, 185
- Air infiltration/exfiltration (*see also* Air leakage, Airtightness, Infiltration, Pressurization/depressurization, Perfluorocarbon tracer systems), 33, 61-69, 315
  - BNL classic comparison house, 308 (Table 1)
  - Caused by exhaust fan/ventilation system operation, 315
  - Central duct fan, 62
  - Effects on energy use, 70, 316
  - HVAC systems, 62
  - In large federal buildings, 184, 195 (Fig. 4)
  - Infiltration models (PFT systems) (*see also* Air infiltration measurement), 260-261
  - Infiltration reduction, 265
  - In military aircraft hangers, 121
  - In high-rise office buildings, 151

Air infiltration/exfiltration (*cont.*)

- In large federal office buildings, 162, 163, 164-165 (Fig. 10), 184
  - Infiltration versus wind speed, 166, 167 (Figs. 10-11), 168, 169 (Tables 3-8), 170 (Tables 9-10)
- In military aircraft hangars, 121
- In passive solar homes, 46-60
- Mechanically induced, 345
- Reduction, 266, 295, 312
- Retrofitting, to reduce rate, 34
- Stack-induced infiltration, 197, 313, 315, 327, 328, 332, 333 (Equations 16, 21), 345
  - Model for Swedish houses, 386
- Temperature, effects on infiltration, 93, 327
  - Model for Swedish houses, 386
- Tracer gas testing, 61, 73, 386
- Tracer leakage area, 8-10 (Tables 1-4), 15, 61-69
- Vent-induced infiltration, 332, 386
- Wind effect, 71, 93, 315
- Wind-induced infiltration, 327, 330-333 (Equations 11-16, 21), 345
  - Model, Swedish houses, 386, 387
- Air infiltration barrier, 305, 306, 360
  - Advantage, discussion 311
  - Air leakage before and after installation, 309 (Fig. 2)
  - Function in relation to building envelope, 307
- Air infiltration measurement
  - Blower doors
    - Accuracy, 273 (Tables 3-4)
    - Tracer gas testing, 285, 387 (Table 10)
    - Used to find air leaks, 265-266, 274, 285-286 (Table 9)
  - In Brookhaven house, 257 (Fig. 15)
  - In industrial buildings, 106-117
    - Use of tracer dilution method, 107
  - In large federal office buildings, 162-163, 164-165 (Fig. 10), 184
    - Dependence on inside-outside temperature, 240 (Fig. 10), 365
  - Exfiltration rate, Equations 15-22, 246-247
  - Measured data, results, 170-171 (Tables 11-13), 172-173 (Tables 14-17)
  - Measured ventilation rates, 174-179 (Figs. 12-20), 180-183 (Fig. 21, Tables 19-20)
    - Passive perfluorocarbon tracer system, 203
  - In military aircraft hangars, 132-33 (Table 7)
  - In residential buildings
    - Dual Infiltration Reduction Experiment (DIRE), 265
    - Modular Retrofit Experiment (MRE), 98 single-family houses, New Jersey and New York, 265
    - New Zealand, 365
    - Study of two test houses, 34, 35 (Fig. 1)
    - Sweden, discussion, 397
- Models, 1, 2, 55, 197 (Table 5), 334, 384
  - Behavior over a range of infiltration rates, 538
  - Comparison of average measured and predicted infiltration, 342 (Table 3)
  - Histograms, 337-341 (Figs. 6-9)
  - Modular Infiltration Test Unit (MITU), comparison with LBL model, 343 (Table 4), 343 (Figs. 10-11)
  - Multi-zone residential, 260, 261
  - Natural infiltration and pressur-

- ization testing
  - Kronvall and Persily (KP), 274-275 (Fig. 1, Equations 3-4)
  - Lawrence Berkeley Laboratory (LBL), 274 (Equation 2), 325, 342, 379
  - LBL modified for Swedish homes, 384, 386
  - Predicted infiltration compared to MITU data, 336, 337
  - Predicted rates sensitive to site exposure details, 365
  - Prediction models, 379
  - Summary of model, 332, 333 (Equations 17-23), 346
  - Tracking ability, 337
- Review of European research into airtightness and air infiltration measurement techniques, 407-415
- Discussion, 414
- Short-term, 333, 334 (Fig. 1)
- Weather correlation, 239 (Table 18), 240 (Equation 14), 259
- Wind speed, 241 (Fig. 11), 342, 385
- Air leakage (*see also* Air exchange, Airflow, Air infiltration, Airtightness)
- Aircraft hangars, military, 120
- Airflow sources (leakage openings), 378 (Tables 3-4)
- Construction joints, 376
- Doors and Windows, 374, 375 (Fig. 5)
- New Zealand standard NZS 4211, 376
- Services entry, 376
- Blower door measurements, 266-289 (Tables 9-11)
- BNL classic comparison house (CCH), 308, 309
- Building envelope characteristics, 374
- Ceilings, 247
- Characteristics, 5-16
- ELA (Effective Leakage Area), 269 (Equation 2), 349 (Equations 1-3)
- Electric residential heating systems, 73
- Exfiltration rates (Equations 15-22), perfluorocarbon tracer systems, residential house tests, 246-247
- Federal buildings, 184
- Fossil fuel-fired residential heating systems, 73
- House tightening
  - Humidity ratio in relation to, 30 (Fig. 8)
  - To effect energy savings, 269-272 (Tables 1-3)
- Industrial buildings, 101-105
- Measurements
  - ASTM E741-80: 121
  - ASTM E779-81: 348
  - Blower door measurements to determine building tightness, 348
  - Canadian compared to U.S., 361
  - Pressurization/depressurization, 349, histogram, 353 (Fig. 1)
  - ASHRAE/DOE conference (LBL report LBL 94160), 364
  - Correlation of flow exponent with specific leakage, 362 (Fig. 6)
  - Discussion, 364
  - Random variability, suggested research, 361
  - Related to house envelope construction, 350, 354
  - Test houses, sample of 711 houses, frequency distribution for specific leakage and flow exponent, 355

Air leakage (*cont.*)Test houses (*cont.*)

(Fig. 2)

Variability with age, 356 (Fig. 3)

Office buildings, high-rise, 140-141

Perfluorocarbon tracers, 203

Leak tightness constant, 240, 241 (Equation 14)

Residential buildings, 348-364

Data base, 341 (Table 1)

New Zealand, 365

Swedish houses, 384, 404

Discussion, 406

## Retrofit

Air leakage report form, 298 (Fig. 2)

In Navy family housing, 294-297 (Fig. 1)

Air change rate for 34 units, 300 (Fig. 4)

Demonstration results, 299 (Table 1)

Handbooks, 295, 296

Retrofit experiments, 266-269

Sealed combustion furnaces (mobile homes), 73

Sealing, to reduce air infiltration, 313

Seasonal variation, 17

Moisture content of wood framing, 27-28 (Figs. 6-7)

Outdoor temperature and humidity ratio, 24-27 (Figs. 4-5)

Shell tightening, 267, 268, 269

Sherman air leakage model, 5, 8, 9

Sites, in Navy family housing, 301 (Fig. 5), 302

Structures, effects of air leakage

On duct fan operation in HVAC systems, 62

On uninsulated, insulated or poorly insulated, 5-16

Summary of papers, ASTM STP 904, 416-422

## Testing

Dual Infiltration Retrofit Experiment (DIRE), 267

ELA (Equivalent leakage area), applied in sealing, 314

Modular Retrofit Experiment (MRE), 267

Navy family housing, 302

Results, conventional houses, 319, 310 (Table 1)

ELA, 321 (Table 2)

Results, Flora Place houses, 319, 321 (Table 3)

To evaluate effectiveness, 318, 319

Tracer data, naval housing, 12-15

Weatherization studies, 247, 259, 295

Air leakage management manual, for Navy family housing, 295

## Air leakage rate

## ASTM Standards

E741-80: 121

E741-83: 75

Measured versus predicted, 5-16, 314, 325

## Measurement

Reduction, 265, 266, 295

Use of infrared thermography, 267

Use of pressurization to facilitate, 265, 410

## Air pollution, 35, 61

Bedroom above attached garage, 66 (Fig. 1)

## Air quality

Indoor, 33, 61, 70, 312, 400, 408

Infiltration rate, effect on, 34

## Measurement

Blower fan measurements, 62

Duct fan measurements, 62

European research, 410, 411

Perfluorocarbon tracer system, 203  
 Airtightness (*see also* Air leakage), 407, 409  
 Common building materials, air-flow resistance, 373 (Table 2)  
 Construction, 408  
 Correlation models, 29 (Table 4)  
 Design details, influence on, 371 (Fig. 4), 372  
 Detached houses, seasonal variation in, 17, 18  
 Energy use, relation to, 33  
 Federal buildings, large, 184  
 Humidity, effects of, 18  
 HVAC systems, pressure measurement, 62  
 Literature review, 407-415  
 Measurement, 366, 408  
 Navy family housing, discussion, 303  
 Passive solar homes, measurement in, 46-60  
 Research, European, 408  
 Residential buildings, 348, 360, 361, 407  
 Blower doors, pressurizing, 37, 43, 348, 349  
 Canadian versus U.S. testing, 361  
 Test houses, 18-21 (Table 1, Figs. 1-2), 36-37, 61-69  
 Measured leakage, correlation of residuals with pressure, 369 (Fig. 1)  
 New Zealand, 365  
 Air change rates, histogram, 370 (Fig. 3)  
 Sweden, 385, 389, discussion, 397  
 Wind influence  
 On air leakage, 24 (Fig. 3)  
 Repeatability test, 22, 23 (Table 2)  
 Aircraft hangars, military

Air leakage, 120  
 Ambersorb (*see* Perfluorocarbon tracer system, CATS)  
 ASHRAE 62-81: 180 (Table 19)  
 Smoking requirement  
 Window leakage standard, 193  
 ASTM COMMITTEE E-6 on Performance of Building Construction Standards, E779-81: 8  
 ASTM STP 606: 1  
 ASTM STP 719: 1  
 ASTM standards  
 E741-80: 121  
 E741-83: 75, 161  
 E779-81: 136  
 ASTM Subcommittee E06.41 on Infiltration Performances, 1  
 Attic, source of air leakage, 247

## B

BATS (*see* Perfluorocarbon tracer systems)  
 Blower doors, 62  
 Use to find air leakage, 266-268, 348, 382  
 Accuracy, 273 (Tables 3-4), 382  
 Airtightness data, 380 (Table 5)  
 ASTM E779-81: 348  
 Tests, 36, 61-63, 86-87, 350, 368  
 Reproducibility, 368 (Table 1)  
 Summary, New Zealand residential buildings, 382  
 BNL/AIMS (*see* Brookhaven National Laboratory Air Infiltration Measurement)  
 Brookhaven National Laboratory Air Infiltration Measurement System (BNL/AIMS) (*see also* Perfluorocarbon tracer system), 204, 232-233 (Table 13a-b)

- Perfluorocarbon tracer (PFT) concentration, 249 (Table 21)
- Building construction
  - Aircraft hangars, military, description, 122-127 (Tables 1-3)
- Building envelope
  - Conventional comparison house (CCH), 308
  - New Zealand, 365
  - Pressure differences, calculations for Swedish houses, 386
  - Use of house doctor procedure for energy conservation, 267
- Building site measurements, New Zealand, 365
- Common building materials, airflow resistance, 373 (Table 2)
- Concrete tilt slab Wherry units, Navy family housing, 301
- Conventional comparison house (CCH), air infiltration barrier, 307, 308
- Federal buildings, description, 152-153 (Table 1), 154-155 (Figs. 2-3), 156-157 (Figs. 4-5), 158-159 (Figs. 6-7) 160-161 (Figs. 8-9), 184, 187-189, 198
- Industrial buildings
  - Concrete frame, prefabricated, 102
  - Steel frame, sheet metal attached with thermal insulation, 102
  - Technical descriptions, 104-105 (Table 1), 110-111 (Table 1, Fig. 2)
- Naval housing
  - Corey unit, 11, 12 (Fig. 3), 13 (Table 6)
  - East Tennessee, 31 houses, 61-69
  - Great Lakes Naval Training Center, 301
  - Lexington Terrace, 13, 14 (Fig. 4)
  - Norfolk, Virginia, 13
  - Pensacola, Florida, 11 (Table 5)
  - Willoughby Bay housing units, 7, (Figs. 1-2)
- Office buildings, high-rise, 135
- National Bureau of Standards Administration Building Description, 138 (Table 1)
- Residential
  - BNL, Colonial, New England Cape Cod
    - One-, two-, three-zone types, 252 (Fig. 14), 253 (Table 23)
  - Passive solar housing, 46-60
  - Ranch style, 304
    - Two-zone, ventilated with separate HVAC systems, 217-218, perfluorocarbon tracer systems (Fig. 5)
  - Sample, 711 houses, effect of vapor barriers on air leakage, 357, specific leakage by age, construction type, flow exponent, 358-359 (Figs. 4-5)
  - Swedish houses, 290, 291
- Building envelope (*see also* Building construction, Pressurization)
- Airtightness measurements, 366
- Function in relation to air infiltration barrier (AIB), 307
- Residential housing, pressurization tests, 350
- Swedish housing, 395, 404
  - Airflow model, 400, 401 (Fig. 1)
  - Application, 402
  - Calculations for pressure differences, 386
  - Use of house doctor procedure for energy conservation, 267
- Building materials, common, airflow resistance, 373 (Table 2)
- Building ventilation (*see* Heating,

ventilation and air conditioning)  
 Buildings, Industrial (*see* Building construction)  
 Buildings, Residential (*see* Residential buildings, Building construction)

## C

Canadian General Standards Board, ventilation air quantity requirement, 317  
 Capillary adsorption tube sampler (CATS) (*see* Perfluorocarbon tracer system)  
 CATS (*see* Perfluorocarbon tracer system)  
 CCH (*see* Building construction, conventional comparison house)  
 Ceilings, air leakage, 247  
 Climate, effect on house construction in relation to air leakage, 357  
 Combustion heating, 70-97  
 Commission of the European Communities  
     Energy conservation research program, 409  
 Concrete frame industrial buildings, prefabricated, 102  
     Pressurization measurements, results, 104 (Table 1)

## D

Dampers sealed in plastic  
     Effect on infiltration rates in federal buildings, 197-198  
 Depressurization (*see* Pressurization/depressurization)  
 DIRE (Dual Infiltration Reduction Experiment), 265  
 Duct fans, in HVAC systems, 61-62

Ductwork, central heating systems (*see* Heating, ventilating and air conditioning)  
 Ductwork leakage, 61-69

## E

Electric heating, 70-97 (*see also* Heating, ventilating and air conditioning systems)  
 Electron capture detector (ECD), 205  
 Energy, U.S. Dept. of, Passive and Hybrid Solar Energy Division Contract DE-AI101-76PR06010, 58  
 Energy conservation, 120, 121, 267-269, 295, 395  
     Air infiltration barrier, 304, 305  
         Energy savings in classic comparison house (CCH), 310  
     Air leakage sealing, 313  
     Blower door tests, 285  
     Building envelope, 396  
     By reduction in air infiltration, 278-284, (Equations 5-6, Tables 6-8)  
     By reduction in air leakage, Navy family housing, 294, 302  
     Dual Infiltration Reduction Experiment (DIRE), 284  
     European research program, 409  
     Navy family housing, 301  
     Use of "house doctor" procedures, 265-266  
 Energy consumption, 36  
     In relation to air infiltration barrier, 309  
     In relation to infiltration, 93, 304, 305  
     Ranch-style house, 304  
 Energy efficiency (*see* Energy conservation)  
 Energy savings (*see* Energy conservation)

Environment, 36

Equations

PFT measurement

ACH, 14

Air exchange rates, 15-22

Tracer concentrations, 1-12

Equipment, air handling (*see* Air handling equipment)

Exfiltration (*see* Air exchange rate, Air infiltration)

## F

Factory buildings (*see* Industrial buildings)

Fan pressurization/depressurization (*see also* Airtightness)

HVAC duct systems, 62-63

In federal buildings, 184

In industrial buildings, 102

In Navy family housing, 294

Measurements, 5-15, 17, 43, 62

Naval housing, 5-15

Office buildings, high-rise, 136

Passive solar homes, 47

Residential buildings, 348, 349 (ELA Equations 1-3)

Results, 38-39 (Figs. 3-4)

Swedish houses, 396

Tests, 17, 22, 37, 62

Tracer gas decay, 63

Federal buildings (*see* Building construction, Fan pressurization, Pressurization measurements)

Flowmeter, 103

Fossil fuel-fired heating system (*see* Heating, ventilating and air conditioning systems)

Freon 12 tracer (*see* Tracer gas studies)

Fumes (*see* Hazardous fumes)

## G

Gadzo blower door assemblies. (*see* Blower doors, Pressurization measurements)

Gas chromatograph, 203

Electron-capture, 121

Use in Perfluorocarbon tracer system, 210, 211, 213, 214

Gas chromatographic analyzer

Gas decay rate (*see* Tracer gas studies)

Gas-fired heating systems (*see* Heating, ventilating and air conditioning systems)

Great Lakes Naval Training Center, Air leakage reduction in family housing, 294

## H

Hazardous fumes from HVAC ductwork, 68

Heat exchanger, 33, 36, 44, 61

Heat loss due to air infiltration, 313

Heat pump, 72

Heating (*see* Combustion heating, Electric heating)

Heating, ventilating and air conditioning systems (HVAC) (*see also* Building construction, Airflow, Air infiltration)

Air quality, 61-62

Central ductwork systems, 62

Electric and combustion, 76-77 (data, unnumbered tables)

Fossil fuel-fired system, 73

Hydronic gas-fired systems, 84

Hydronic oil-fired system, 84

Hydronic (perimeter) systems, 153

Literature review of different types of systems in relation to infiltration, 75-95

Natural gas-forced air



- Perfluorocarbon tracer system, 203
- High-rise office buildings (*see* Building construction, Office buildings, Pressurization measurements)
- Humidity, Indoor, in relation to air leakage, 30-31 (Figs. 8-9)
- Humidity ratio, outdoor, 24-27 (Figs. 4-5)
- In relation to air leakage, 30-31 (Figs. 8-9)
- Hydronic heating systems [*see* Heating, ventilating and air conditioning (HVAC)]

## I

- Industrial buildings
  - Air leakage, measuring equipment, description, 101
  - Infiltration, 106
- Induced-pressure measurements (*see* Pressurization measurements)
- Infiltration [*see also* Air exchange, Air infiltration, Airtightness, Heating, ventilating and air conditioning (HVAC) systems], 76-89, 399-405
  - Air changes per hour (ACH) PFT Equation 14, 240
  - Aircraft hangars, military, 120
    - McClellan Air Force Base, California, 126, 127 (Table 3)
    - Minot Air Force Base (AFB), North Dakota, 124 (Table 2)
    - Naval Air Rework Facility (NARF), Norfolk, 122, 128-130 (Tables 1, 5-6)
    - Naval Air Station (NAS), Brunswick, Maine, 128-129 (Table 4)
- ASTM
  - STP 719: 1
    - Subcommittee E06.41: 1
- Heating systems, Electric and Combustion, data, 76-79
- Heating systems, literature review, 75-93
- Industrial buildings, 106
  - Descriptions of test buildings, 110-111 (Table 1, Fig. 2)
  - Test conditions, 112-113 (Table 2, Figs. 3-4)
- Leakage areas, uncertainty in calculation, 10, 197
- Literature review, different heating systems, 75-93
- Measurement, 1, 122, 197, 396
- Models
  - Appendix, 260-261
  - Infiltration rate prediction, 379, 381 (Fig. 7)
  - Lawrence Berkeley Laboratory (LBL), 325, 327, 379, 381 (Fig. 7)
  - National Research Council of Canada, 184
  - Pressurization measurements and weather conditions
    - Equation, 54-55 (Tables 2a-b)
  - Passive solar homes
    - Tracer gas decay technique, 49
    - Weather conditions, effects on, 50 (Fig. 2, Table 1)
  - Reduction, 265
  - Swedish residential houses, 385
- Infiltration research, 407-415
- Infrared thermography (*see also* Air leakage)
  - Use in conjunction with blower door to discover air leakage, 267
- Institute for Building Research, data on residential infiltration

rates for different types of buildings and heating systems, 76-83

Institute of Gas Technology, infiltration rates, 75

Insulation, industrial buildings, 102

International Council for Building Research, 408

## L

Lawrence Berkeley Laboratory (LBL) infiltration model, 325, 327

Leakproofing of ductwork, 68

Literature review, airtightness and air infiltration measurement techniques, 407-415

Literature review, infiltration in different heating systems, 75-93

## M

Magnehelic pressure gage, 62

McClellan Air Force Base, California, 126

Mechanical ventilation system (*see* Air infiltration, Airtightness, Ventilation)

Military aircraft hangars, air infiltration (*see* Air leakage, Aircraft hangars, Air infiltration)

Minot Air Force Base (AFB), North Dakota, 124

Mobile Infiltration Test Unit (MITU), 327, 343

Modular Retrofit Experiment (MRE), 265

Multizone modeling, perfluorocarbon tracers, 203

Moisture (*see also* Humidity)

Airtightness, effect on, 32, 37

Content, measurement, 21, 400

Of wood framing, seasonal variation in, 27-28 (Figs. 6-7), 317

Damage, 6, 317

## N

National Bureau of Standards, 58

National Research Council of Canada

Infiltration model, large buildings, 184

National Testing Institute (*see* Swedish National Testing Institute)

Naval Air Rework Facility (NARF), Norfolk, 123, 128-130 (Table 5)

Naval Air Station (NAS), Brunswick, Maine, 128-129 (Table 4)

Naval housing (*see* Building construction)

Nordtest, 101, 102

## O

Office buildings (*see* Air infiltration, Building construction, Pressure measure, Ventilation)

Office of Navy Family Housing, Air leakage reduction program, 294

## P

Passive sampler (*see* Perfluorocarbon tracer system)

Perfluorocarbon tracer system (PFT) (*see also* Pressurization/depressurization)

BATS (Brookhaven atmospheric tracer sampler), 210

BNL/AIMS (Brookhaven National Laboratory/Air infiltration measurement system),

- field use, 232-236 (Tables 13*a-b*, 14*a-b*)
- Comparison with other techniques, 235, SF<sub>6</sub>, 236 (Tables 15-16)
- National Association of Home Builders, conventional comparison house, 238, 239 (Table 18)
- Sample of home air infiltration rates, 236-238 (Fig. 9, Table 17)
- CATS (Capillary adsorption tube sampler), 207-210, 227, 228 (Tables 10-11)
- Description, 203-207
- Gas chromatograph, 210-211 (Table 2), 213 (Tables 3*a-b*), 258
- Calibration, 214
- Performance, 229-231 (Figs. 7, 8)
- Plumbing and valving, 212, 213 (Fig. 4)
- Infiltration models, 260, 261
- Radon results, 219, 254, 255
- Two-three zone, N-zone cases, 218-220
- Tracer concentration, 217-219, 231 (Equations 1-12), 263, 264
- Tracer samplers
  - Passive, capillary adsorption tube sampler (CATS), 207-209 (Figs. 2-3)
  - Programmable, Brookhaven atmospheric tracer sampler (BATS), 210
- Tracer source, 206 (Table 1) (Fig. 1)
  - Calibration, 225 (Table 7)
  - Effect of temperature, 207, 225, 227 (Table 10)
  - Performance, 223-225 (Tables 5-6)
- PFT (*see* Perfluorocarbon tracer systems)
- Prefabricated concrete frame industrial buildings, 102
- Pressurization/depressurization (*see also* Air infiltration measurement, Air leakage reduction, Perfluorocarbon tracer system), 399-405
- ASTM pressurization test E779-81: 5, 8, 348
- Federal buildings, 184, 185
  - Results, in relation to air infiltration rates, 195, 196 (Fig. 4)
- Industrial buildings, 102
  - Fan description, 103
  - Flowmeter, 103
- Navy family housing, 294
- Blower doors
  - House doctor procedures to determine air leakage data, 268 (Table 1, Equations 1-2)
  - Tests, 265
  - Used to locate air leakage, accuracy, 273 (Tables 3-4), 351
- Suggested research, 361
- Pressurization measurements, 135
  - Dual Infiltration Reduction Experiment (DIRE), 265
- Duct leakage areas, 61-69
- Effected by age and construction of buildings, 360
- Evacuation
  - Using blowers to equalize pressure, 8-11 (Tables 1-5)
- Factory buildings, 107
- Federal buildings, 184-200
  - Compared to other types of homes, 52
  - Pressurization test results, 48, 49 (Fig. 1), 51 (Fig. 3), 53 (Fig. 4)
  - Using sulfur hexafluoride (SF<sub>6</sub>), 48

Pressurization measure (*cont.*)

- Weather conditions, Equation, 54-55 (Tables 2a-b)
- Federal buildings, large, 184 (*see also* Building construction)
- Airflow rate, 186
- Test equipment, 186
- Whole building pressurization, 187
  - Results, 180-191 (Tables 1-2, Figs. 2-3)
- Flow equation under windy conditions, 22
- Freon-12 tracer, 68
- Gadzo blower door assemblies, 6, 8-11, 61-69
- HVAC systems, 62-63
- Induced, 5, 6, 62-63, 135, 137, 186, 196
- Industrial buildings, 101, 102
  - Equipment, 102
  - Fan, Axico, 103
  - Tests, 102
  - Tracer gas, 102
- Military aircraft hangars, 120
- Modular Retrofit Experiment (MRE), 265
- Naval housing (*see* Building Construction)
- Office buildings, high-rise, 135, 138
  - Single-floor depressurization, 142 (Fig. 4)
- Passive solar homes, 47, 52-53
  - Flow rate, equation, 48
  - Infiltration measurement in relation to weather conditions, 50
  - Infiltration rates compared to other types of homes, 46
- Perfluorocarbon tracer systems, 203-264
- Swedish houses, 384, 396, 399, 402, 403 (Table 1), 404

## R

- Radon, 400
  - Two-zone houses, perfluorocarbon tracer systems, 218-219
- Randon concentrations, 248
- Residential housing (*see* Air exchange, Air infiltration, Airtightness)
- Retrofit, 86, 265-267
  - Fan pressurization/depressurization results, 38, 39
- Procedure, Navy family housing, 302

## S

- Sealing measures, air leakage, 312
- Shell tightening
  - For Energy conservation, 266-269
- Sherman air leakage model (*see* Air leakage)
- Single-cell industrial buildings (*see* Air infiltration, Industrial buildings)
- Smoking requirement, ASHRAE 62-81: 180
- Solar Energy Research Institute, 46
- Solar homes, passive (*see also* Pressurization measurements, Passive solar homes)
  - Air infiltration and airtightness, 46-60
  - Airtightness measurement techniques, actual performance
    - Pressurization testing, 46, 47
    - Model predictions, 55-57 (Table 3)
  - Thermal performance evaluation, 46
  - Tracer gas testing, 46, 47, 86, 120
- Space heaters, gas or kerosene, CO from, 254

Stack effect, in air exchange, 72,  
197, 313  
Steel frame industrial buildings, 102  
Pressurization measurement re-  
sults, 104 (Table 1)  
Sulfur hexafluoride (SF<sub>6</sub>) (*see* Pres-  
surization measurements)  
Swedish Building Code, 101  
Swedish Institute for Building Re-  
search, 400  
Swedish National Testing Institute,  
101

## T

Temperature, 24-27 (Figs. 6-7)  
Difference between inside and out-  
side air, effects on air ex-  
change, 71, 365  
Induced infiltration, federal build-  
ings, 196  
Tennessee East test houses (*see*  
Building construction)  
Thermal insulation, industrial build-  
ings, 102  
Thermal integrity, large federal  
buildings, 185  
Tracer concentration decay, 5  
Dilution method, 5-6, 48  
Industrial buildings, single-cell,  
107, 112-114, 118, 119  
Military aircraft hangars, 121  
Portable gas monitor, 6, 121  
Test, ASTM E741-83: 16  
Tracer gas studies, 36, 37, 40, 41  
(Table 1), 44, 309  
Air bag technique, 48  
Aircraft hangars, military, 122,  
124-126 (Tables 2-3)  
Decay, 266  
European research, literature re-  
view of air infiltration mea-  
surement techniques, 407  
Federal buildings, large, 185

HVAC systems, 61-63 (Table 1),  
74, 86, 87  
Blower door measurements, 62,  
73, 74  
Duct fan operation, 62  
Induced pressure measure-  
ments, 63 (Table 2)  
Industrial buildings, 101, 102, 103  
(Fig. 1), 108  
Airflow calculations, formula,  
102  
Tracer gas measurements, 108,  
109 (Fig. 1)  
Nitrous oxide system, 108  
Results, 104, 114-117 (Tables  
3-5)  
Sulfur hexafluoride (SF<sub>6</sub>) sys-  
tem, 108, 120, 121  
Test conditions, 112-117 (Ta-  
ble 2, Figs. 3-5)  
Office buildings, high-rise, 135,  
137  
Tracer gas measurements, 143-  
149 (Table 2), 151  
Office buildings, large federal, 163  
Passive solar homes, 48, 49  
Tracer gas measurements, 62,  
73, 74  
Perfluorocarbon tracer system,  
203, 214-216  
Exfiltration rates, 217 (Table 4)  
Swedish residential houses, 385,  
399, 402, 404, 405 (Fig. 2)

## V

Vapor barrier, 360, 361  
Ventilation [*see also* Heating, venti-  
lating and air conditioning  
(HVAC), Air infiltration],  
151, 162, 317  
Effect on infiltration, 345  
European research survey, 408  
(Table 1)

# Ventilation (*cont.*)

Review of air infiltration measurement techniques, 407

Industrial buildings, 106

Office buildings, 135, 151, 162, 174-179, 181, 182

Perfluorocarbon tracer system for buildings, 203

Swedish houses, 389

Measured rates, 390 (Fig. 1), 391 (Fig. 2), 392 (Fig. 3), 393 (Fig. 4), LBL model parameter values, 393 (Table 4)

Measured rates versus predicted, 394 (Fig. 5)

Mechanical ventilation system, 395

Predicted rates, 395 (Table 5, Fig. 6)

# W

Weather conditions (*see also* Infiltration, Pressurization measurements)

Effects on air infiltration, 37, 48, 50, 195

Effects on air leakage, 17, 48

Aircraft hangars, 123

Large federal buildings, 195

Weatherization, 203, 259

Willoughby Bay housing units (*see* Building construction)

# Wind

Aircraft hangars, 123

As a cause of infiltration, 71, 313, 381

As a cause of variations in pressure, 22, 71

Classic comparison house, 310

Federal buildings, 196

Wind speed (*see also* Air infiltration)

Federal buildings, large, 168, 169 (Tables 3-8), 170 (Tables 9-10), 179, 180 (Figs. 20-21), 200

Related to Blower door pressurization testing, 285-287

Related to infiltration rates in perfluorocarbon tracer systems, 241 (Fig. 11)

Related to retrofit of Navy housing, 295

Windows, air leakage

Pressure testing in federal buildings, 192-194 (Tables 3-4)

Residential, 247, 266