

Subject Index

A

Acid rain, 287
 Aeration, 187
 Aluminum, 17, 262
 2024, 132
 6061, 132
 7075, 20, 131, 132
 Anodized aluminum, 135
 ASTM standards
 A 262, 455–464
 B 457, 139
 C 665, 215
 C 764, 216
 D 610, 129
 D 1141, 249
 E 399, 34
 E 647, 34
 G 1, 225, 231, 375
 G 3, 74, 403
 G 5, 255, 328
 G 28, 437, 438, 442, 450, 452
 G 30, 251, 376
 G 31, 67, 78, 250, 375
 G 36, 376
 G 38, 252
 G 39, 252
 G 40, 359
 G 43, 19
 G 46, 375
 G 48, 251, 315, 375
 G 53, 159, 161
 G 59, 198, 233
 G 61, 326, 328, 334
 Autoclave, 339, 417

B

Bent beam test, 251
 Biofouling, 203
 Bode plot, 126–137
 Brass, 262
 Braze joints, 177
 Brick masonry, 285–296
 cracking, 293
 Brine, 341

C

Cabinet tests
 Cyclic, 19
 Humidity tests, 215–227
 Kesternich, 144
 Salt spray, 14, 144
 Sulfur dioxide, 144
 Sulfur dioxide-salt fog, 15
 Calcareous deposit, 212
 Can corrosion
 Accelerated test, 48–64
 Effects of chromium, 60–61
 Effect of lacquer, 57
 Pack test, 59
 Solder attack, 53
 Storage conditions, 57
 Cathodic depolarizer, 49, 71
 Cathodic protection, 207–214
 Cement
 Calcium chloride content, 277
 Clad metal, 260–274
 Coatings
 Alodine 600, 131

- C**
- Coatings (*continued*)
 - Chromate conversion, 123
 - Deterioration of, 159
 - Epoxy/polyurethane, 20
 - Inorganic, 17
 - Lacquer, 48
 - Undermining, 60
 - Coinage material, 260–274
 - Soilage properties, 271–274
 - Computer program, 28
 - Concrete, 275–284, 429
 - Sodium thiocyanate content, 283
 - Copper and copper alloys, 262
 - 614 yellow brass, 360
 - Correlation
 - ASCC test, 54
 - Corrosion ranking, 225
 - Cyclic sulfur dioxide-salt fog, 21
 - Electrochemical tests, 144
 - Environmental wear behavior, 274
 - FUCA test, 160
 - Immersion tests, 177
 - Laboratory tests, 11
 - Pit ranking, 244
 - Salt spray tests, 14
 - Tafel extrapolation, 238
 - Corrosion behavior diagram, 75–79
 - Corrosion fatigue, 34, 174
 - Fatigue crack growth, 34
 - Creep, 292
 - Crevice corrosion, 9, 78, 103, 227, 250, 299–323, 324–336, 337–357, 376
 - Area ratio effects, 318
 - Critical concentration, 10
 - Critical temperature, 9
 - Effect of geometry, 10, 313, 354
 - Effect of pH, 315, 349
 - Incubation period, 354
 - Mathematical model, 300
 - Multiple crevice assembly, 385, 396
 - Oxygen concentration effects, 319
 - Propagation, 303
 - C-ring test, 251
 - Cupro-nickel, 262
 - Current decay curve, 210
- D**
- Data acquisition, 24–35
 - Dealloying
 - Solders, 57
 - Deformation
 - Corrosion induced, 292
 - Deicing salts, 275
 - Desiccification, 176
 - Double cantilever beams, 251
- E**
- Electrochemical tests, 65–90, 325
 - Cell design, 339
 - Compartmentalized cell, 304
 - Controlled potential, 72, 210, 406, 416, 431
 - Cyclic potentiodynamic polarization, 77, 95, 110, 228, 328
 - Electrical resistance, 67
 - EPR test, 421
 - Galvanostaircase polarization, 112
 - Galvanostatic polarization, 254, 276
 - Impedance, 87, 122–142
 - Polarization resistance, 71, 113–120, 147, 197–206, 233
 - Effect of scan rate, 201
 - Potential measurements, 236, 277, 309, 345
 - Metallic coated steel, 146–151
 - Nickel-aluminum bronze, 30
 - Potential step method, 327
 - Potentiodynamic polarization, 31, 71, 72, 255
 - Effect of scan rate, 72, 96
 - Rapid scan technique, 75
 - Slow scan technique, 73
 - Potentiostaircase polarization, 113
 - Potentiostatic polarization, 254, 401

Tape method, 91–107
 Tafel region, 69, 154, 199, 233
 Environmental wear test, 260–274
 Environments

Aircraft carrier, 17
 Erosion corrosion, 175, 358–372
 Effect of velocity, 361
 Jet test, 360
 Shear stress, 363
 Exfoliation tests, 19

F

Ferric chloride test, 375
 Fluid velocity, 82
 Fluorescent UV and condensation test, 159
 Fretting corrosion, 262

G

Galvanic corrosion, 7, 50, 147
 Area ratio effects, 50
 Current distribution, 32
 Soldered tin, 57
 Tin plated steel, 49
 Zero resistance ammeters, 32
 Galvanized steel, 147, 172

H

Heat exchanger, 36–47
 Galvanic corrosion, 33
 Zirconium, 36
 Heat exchanger tubes, 359
 Current distribution, 33
 Heat transfer
 Corrosion effects, 36
 High temperature
 Reference electrode, 417
 Humidity test
 Cyclic, 261
 Hydrogen embrittlement, 251
 Hydrogen induced cracking, 7, 254
 Hydrogen sulfide, 246

Hydrothermal conditions, 338
 Hysteresis, 110, 111, 229, 242, 325

I

Immersion tests, 66, 374
 Electrolyte-volume ratio, 51
 Inhibitors, 12, 228–245
 Insulation, 215–217
 Intergranular corrosion, 437–454
 Effect of mill condition, 459
 Effect of surface preparation, 455
 Stress corrosion cracking, 421

L

Localized corrosion, 66
 Weld metal attack, 41

M

Masonry, 286
 Metal pick-up, 179
 Microcomputer, 24–35
 Mortar, 275–284
 Multiple crevice assembly, 302, 329

N

Nickel and nickel alloys, 262
 Hastelloy C, 437–454

P

Pipe
 Brass, 176
 Copper, 173
 Galvanized steel, 172
 Pitting, 10, 77, 91–107, 172, 250,
 324–336, 444
 Effect of pH, 98
 Pitting potential, 10, 242, 413
 Effect of surface pretreatment, 97
 Polarization curves
 3003 aluminum, 112
 Brass, 113, 367
 Copper, 112, 114

- Polarization curves (*continued*)
 Nickel-aluminum bronze, 32
 Stainless steel
 18-2 ferritic, 101
 Type 304, 96, 97, 100
 Type 316, 319
 Type 420, 404–412
 Steel, 280, 281
 Coated, 155–156
 N80, 232
 Pore water, 280
 Potable water, 170
 Pourbaix diagrams, 67–68
 Precracked specimen, 253
 Prestressed steel (see reinforcing steel)
- R**
- Reinforcing steel, 102, 275–284, 286, 428–436
 Repassivation potential, 324
 Effect of scan rate, 96
 Rotating cylinder, 82
- S**
- Seawater, 197–206, 207–214, 304
 Fouling, 203
 Synthetic, 208, 304
 Sensitization, 456
 Austenitic stainless steel, 416
 Slow strain rate tests, 253, 415–425
 Solder attack, 177
 Can corrosion, 53
 Lead dissolution, 56
 Solder joints, 178
 Sour gas, 7, 249
 Specimen preparation, 231, 342, 455–464
 Stainless steel
 17-4, 20
 18Cr-2Mo, 100, 307
 18Cr-4Ni-2Mo, 308
 26Cr-1Mo, 308
 254 SMO, 308
 Type 304, 94, 307, 327, 415, 421, 455
 Type 316, 307
 Type 317, 308
 Type 420, 401
 Type 430, 307
 Type 904, 306, 317
 Steel, 17, 185, 198, 209, 216, 262, 276, 428
 A36, 287
 N80, 231
 1005, 203
 1010, 130
 Metallic coated, 144
 Polybutadiene coated, 125
 Pore resistance, 127
 Tin plate, 48
 Stress corrosion cracking, 6, 84, 251, 376, 415–427, 428
 Constant load test, 432
 Controlled potential test, 406
 Critical stress, 10
 Effect of chloride concentration, 407
 Effect of hydrogen sulfide, 406
 Effect of pH, 407
 Intergranular
 Critical potential for, 421
 Modulus measurements, 85
 Polarization tests, 86
 Slow strain rate test, 84, 433
 Step-stress tension test, 404
 U-bend specimens, 251, 392
 Stress intensity, 253
 Stress-strain curves
 Type 304 stainless steel, 423
 Sulfide stress cracking, 7, 251, 400–414
 Step-stress tension test, 404
 Surface preparation, 105, 217, 223
 Surface treatment, 128

T

- Tensile bars, 251
Tin plate
 Can corrosion, 49
 Passivation treatment, 60–62
Titanium
 Grade 2, 338
 Grade 12, 337

V

- Vapor phase corrosion, 44
Velocity effects, 81–83

W

- Wear corrosion, 262
Wear tests, 260–274
Weld metal attack, 41, 100, 450

Z

- Zirconium, 36
P60707, 37
Effect of heat flux, 42
Weld metal attack, 41