

Subject Index

A

- Acoustic emission, 713
- Adherent, 635
- Adhesive bonds, 635
- Adhesive failure, 635
- Aerospace materials, 474, 515, 568
- Aging conditions, aluminum-lithium-zirconium alloys, 515
- Airframe components, fatigue crack growth rate, 568
- Allowable flaw size, 498
- Alloys, aluminum-lithium-zirconium, 515
- Aluminum alloys, 568, 619
- Aluminum-lithium alloys, 515–517, 521
- Alternating technique, stress intensity solutions, 396
- Autofrettaged thick cylinders, 461
- Anti-plane Mode III loading conditions, 185, 194, 199, 208
- Application methodology
ductile fracture mechanics, 229
- Asperities, 619
- ASTM standards
 - A 710, 810
 - D 1002-72, 635
 - D 1876-72, 635
 - D 2094-69, 635
 - E 399-83, 740
 - E 647-88a, 568
 - E 813-87, 840
- Asymptotic analysis, 185, 208
- Axisymmetric loading, 417

B

- Bending, welded wide plates, 284
- Biaxial loading, 738
- Biaxial particulate composites, 775
- Bimaterial interface, 208
- Boundary element method stress intensity factor, 461
- Brittle fracture, 115, 809, 826

- Bulge tests, 809
- Butt-welded wide plates, 284

C

- Calibrations, 229
- Casks for nuclear transportation, 840
- Ceramics, 788
- Charpy test, 168, 365, 826
- Circumferential cracks, 37, 417
- Cleavage fracture
 - transition range data, 80
- Compact crack arrest specimen, 365
- Composite materials, 649, 751, 775
- Compressed natural gas, 498
- Concrete fracture, 797
- Constraint
 - fracture toughness material, 55
 - transition range data, 80
 - transverse strain effects, 95
- Contact stresses, 383, 619
- Continuum damage mechanics, 680
- Crack arrest, 365, 826
- Crack closure, 536, 619
- Crack extension, 115, 219–220
- Crack initiation and growth
 - aluminum alloy forgings, 568
 - autofrettaged thick cylinders, 461
 - behavior of titanium aluminide, 551
 - closure, 265
 - constraint, 55
 - ductile bimaterial interface, 208
 - equivalent plastic strain, 55
 - fatigue, 498
 - fracture behavior, 668
 - high performance ceramics, 788
 - measurements in aluminum alloy forgings, 558
 - near tip behavior, 775
 - reactor pressure vessel, 37
 - shape, 265
 - small-scale yielding conditions, 344
 - steel on-board gas cylinders, 498
 - surface cracks during loading, 265

Crack initiation and growth—continued
 titanium aluminide, behavior, 551
 toughness, 37
 transverse strain effects, 95

Crack length measurement, 133

Crack opening, 668, 775, 797

Crack propagation, 474, 826

Crack shape development, 498

Crack tip blunting, 95

Crack tip field, 185

Crack tip opening displacement (CTOD),
 37, 284

Cracked strip, 383

Cracks, limit pressure analysis, 310

CTOD (*see* Crack tip opening
 displacement)

Cylinder tests, 503

Cylinders, pressurized, 461

D

Damage, 649, 668

Damage initiation, 713

Damage prediction, 713

Damage progression, 713

Damage tolerance

aluminum alloy forgings, 568

laminated composite structures, 751

Debonding angle, 635

Debonding force, 635, 696

Defect assessment, 284

Deformation characteristics, 185, 713

Delamination toughness, 515, 649

Displacement, 133

Dominant eigenvalue, 775

Double cantilever beam, 635

Doubly bonded zone, 635

Ductile fracture

crack growth, 265

tension tests, 115

mechanics, 229

tearing, 265

Ductile to brittle transition, 365, 840

Dynamic crack growth, 208

Dynamic crack opening displacement,
 619

Dynamic crack resistance, 826

Dynamic fracture testing, 168, 826

E

Elastic adhesives, physical constants, 641

Elastic plastic fracture mechanics

brittle zones in steel weldments, 809

cylindrical vessel, 330

ductile iron (DI) alloy, 840

dynamic fracture toughness, 168

loading cycles, 265

welded wide plates, 284

Elastic plastic materials, 185

Electron beam welding, 365

Elliptical cracks, 396

Empirical formula J-R curves, 133

Energy dissipation rate, 797

Energy release rate, 797

Environmental cracking, 443

Environmental effects, titanium aluminide,
 Ti-25Al-25Nb, 551

Epoxy laminates, 751

Equivalent plastic strain, 55

Equivalent remote biaxial stresses (ERBS),
 738

ERBS (*see* Equivalent remote biaxial
 stresses)

Erosion, 461

Error sources and management—
 microphotography, 77

Eta factor, 168

Explosive bulge tests, 809, 823

F

Failure conditions, 635, 680, 713, 738

Failure probability, brittle zones in steel
 weldments, 809, 823

Failure process zone, 668, 713

Fatigue crack closure, 619

Fatigue crack growth, 474, 498, 536, 568
 analysis, 590

test summary, 479

Fatigue (materials)

aluminum alloy forgings, 568

Aluminum-lithium-zirconium (Al-Li-Zr)
 alloy, 515

A710 steel, 809

A723 steel, 443

autofrettaged thick cylinders, 461

brittle failure, 115

composite material, 668

circular cylinders, 417

crack closure, 619

crack initiation and growth, 5, 37, 265,
 461, 474

cracked strip problem, 383

cylindrical vessel, 310, 330

damage prediction, 713

developing J-R curves, 133

ductile fracture mechanics, 229

ductile iron (DI) alloy, 840

dynamic fracture toughness, 168

- elastic plastic materials, crack growth
 - during loading cycles, 185, 265
- elliptical surface cracks, 396
- failure criterion, 738
- fatigue crack growth behavior, 551
- fracture model, 738
- graphite/epoxy laminates, 751
- life prediction, 536
- magnesia stabilized zirconia, 788
- metal matrix composites during static loading, 713
- normalization, 168
- oscillating temperature distributions, 590
- particulate composite material, 668, 775
- Polyethylene pipes, 826
- small-scale yielding conditions, 344
- space shuttle main engine (SSME), 265
- steel on-board gas cylinders, 498
- structural problems, 5
- thick wall cylinder—A723 steel, 443
- titanium aluminide, Ti-25Al-25Nb, 551
- titanium metal matrix composites, 696
- transition range data, 80
- transverse strain effects, 95
- zirconia toughened alumina, 788
- welded wide plates, 284
- Feedlines, steam generator, nuclear pressure vessels, 590
- Ferritic steels
 - nuclear transportation casks, 840
 - transition temperature, 80, 840
- Fiber reinforced composite materials, 648
- Fiber stress, 696
- Finite element analysis
 - circumferential cracks in circular cylinders, 417
 - ductile fracture in tension tests, 115
 - fiber-matrix debonding, 696
 - intergranular delamination, 515
 - nonlinear behavior, 649
 - progressive failure of laminated composites, 680
 - titanium metal-matrix composites, 696
- Flat rolled plate, 568
- Flaw size, 498
- Fractography, 551
- Fracture behavior, 515, 668
- Fracture (materials)
 - A710 steel, 809
 - autofrettaged thick cylinders, 461
 - aerospace materials, 474
 - aluminum-lithium-zirconium, 515
 - cylinder vessel, limit pressure analysis
 - 310
 - ductile iron (DI) alloy, 840
- fracture model, 738
- graphite/epoxy laminates, 751
- magnesia/zirconia toughened alumina, 788
- Fracture mechanics
 - aerospace materials, 474
 - aluminum alloy forgings, 568
 - A710 steel, 809
 - A723 steel, 443
 - autofrettaged thick cylinders, 461
 - behavior of particulate composite material, 775
 - brittle failure, 115
 - circular cylinder, 417
 - composite material, 668
 - crack extension analysis, 185, 208
 - crack initiation and growth, 55, 265
 - cracked strip problem, 383
 - cylindrical vessel, 310, 330
 - dissipation mechanism of concrete, 797
 - ductile bimaterial interface, 208
 - ductile fracture, 115, 229, 840
 - dynamic fracture toughness using normalization, 168
 - elastic plastic materials, 185, 265
 - elliptical surface cracks, 396
 - fatigue crack closure, 619
 - fatigue crack growth, 498, 551
 - fatigue life prediction, 536
 - fiber matrix debonding, 696
 - fracture model, 738
 - graphite/epoxy laminates, 751
 - high performance ceramics, 788
 - J-R curves using normalization, 133
 - metal matrix composites during static loading, 713
 - methods, 498
 - nonlinear behavior, 649
 - oscillating temperature distributions, 590
 - particulate composite material, 668
 - Polyethylene pipes, 826
 - pressure vessel steel, 365
 - small scale yielding conditions, 344
 - static fatigue in high performance ceramics, 788
 - structural problems, 229, 265, 443
 - tests, 443, 474
 - titanium aluminide, Ti-25Al-25Nb, 551
 - titanium metal matrix composites, 696
 - toughness, 515, 738
 - transition range data, 80
 - transverse strain effects, 95
 - welded wide plates, 284
- Fracture mechanics solutions, 5
- Fracture model, 738

Fracture process zone, 797

Fracture resistance of ferritic ductile iron
alloys for nuclear transportation
casks, 840

Fracture surface examinations, 713

Fracture testing, 168

Fracture toughness

aerospace materials, 474

delamination, 515

displacement measurement, 133

ductile fracture mechanics, 229, 840

fracture model, 738

graphite/epoxy laminates, 751

plane-strain conditions, 37

pressure vessel steel, 365

small-scale yielding conditions, 344

steel on-board natural gas cylinders, 498

transverse strain effects, 95

Fracture toughness specimens, 55, 229

Frequency, 551

G

Grain flow, aluminum alloy forgings, 568

Grain morphology, 515

H

Heat affected zones, 809

High-strength low alloy steel, 809

Hold time, 551

Hollow cylinder, 417

HRR (Hutchinson, Rice, and Rosengren)
stress field, 344

Hydrogen stress cracking, 443

I

Inelasticity, 649

Instrumental Charpy test, 168

Integral transform techniques, 383

Interaction effect, 536

Intermetallic materials, 551

Irradiated nuclear reactor pressure vessels,
safety analysis, 330

J

J-integral, 649, 840

J-R curves, 133, 168, 265, 344

K

K analysis, 443

L

Laminated composites, 680, 751

Large deformation analysis, 115

Large strains, 95

Leak before break failure, 498, 505

LEFM (*see* Linear elastic fracture
mechanics)

Life prediction, 536

Limit pressure, 310

Linear elastic fracture mechanics (LEFM),
738, 840

Linear fracture mechanics, 344

Lithium, aluminum-lithium-zirconium
alloys, 515

Load displacement, 168, 229

Load shielding, 619

Loading conditions

axisymmetric, 417

circular cylinders, 417

cracked strip problem, 265

ductile fracture mechanics, 229, 383,
840

ductile iron alloy for nuclear
transportation casks, 840

elastic plastic materials, 185

Loads, 133, 396

Local brittle zones, 809

M

Magnesia-stabilized zirconia, 788

Materials

Al-2.6Li-0.09Zr alloy, 515

A533-B steel, tensile strength tests, 83

7050-T74, residual stress screening, 580

metal matrix composites, 713

titanium aluminide, Ti-25Al-25Nb, 551

titanium metal matrix composites, 696,
699

Matrix damage, 680

Maximum failure stress, 635

Metal matrix composites, 713

Methodologies

ductile fracture mechanics, 229
pressurized thermal shock, 310, 330

Micrographs, 696

Micromechanics, 37, 69

Microphotography

error sources and management, 77

Mixed mode fracture, 396

Mixed mode loading conditions, 185

Mode II delamination, 649

Moiré interferometry, 797

N

- NASA/FLAGRO computer program
aerospace materials testing, 474, 480
NDE (*see* Nondestructive evaluation)
Near tip fields, 775
Necking
 ductile fracture in tension tests, 115
Nonlinear fracture mechanics, 185
Nondestructive evaluation (NDE), 265
Nonlinear finite element analysis, 649
Normalization, 133, 168
Notched laminates, 751
Nuclear reactor pressure vessels, safety
 analysis, 330
Nuclear transportation casks, 840

O

- Oscillating temperature, 590
Overloads, 619

P

- p*-version finite element, 417
Partical elliptical cracks, 396
Part-through flaw, pressure vessel, 330
Particulate composites, 668, 775
Perturbation analysis, 185
Pipeline steel, chemical composition,
 118
Pipelines, 826
Pipes, 417
Plane strain, 37, 474
Plane strain, Mode I, 185, 202, 204
Plane strain, test conditions, 443
Plane stress fracture, 515
Plane stress, Mode I, 185
Plastic deformation, 344
Plastic linear hardening materials, 208
Plastic radius, 344
Plastic strain, 55
Plastic zone, 344
PMMA (*see* Polymethyl methacrylate)
Polyethylene pipes, 826
Polymethyl methacrylate (PMMA), 738
Power law, 133
Predictions, 229
Pressure vessels
 autofrettaged thick cylinders, 461
 cracks in circular cylinders, 417
 limit pressure analysis, 310, 323–324
 thermal shock, 330

P

- Pressure vessel steel, 365
Pressurized plastic pipelines, 826
Pressurized thermal shock, 330
Pressurized water reactors
 oscillating temperature distributions, 590
 plane-strain fracture toughness, 37
Probabilistic fracture mechanics, 809
Progressive failure analysis methodology,
 680
Pump shaft cracking, 396

Q

- Quasi-static crack growth, 208, 215

R

- Random loading, 536
Range marking, 265
Rapid crack propagation, 826
Reactor pressure vessel, 37
Residual stress, 443, 461, 568
Resistance to crack initiation, 37, 265
Ring-forged pressure vessels
 circumferential flaws, 37
Ring-forged vessels, 37

S

- Safety analysis, nuclear reactor pressure
 vessels, 330
Scanning electron microscopy, 443
Shaft residual life, 396
Shear stresses, 185, 649
Singly bonded zone, 635
Size effects of specimens, 80, 87, 91
Size requirements of specimens, 80
Slip-line, 37, 310
Small-scale yielding, 344
Space shuttle main engine (SSME), 265
Space system hardware, 474
Specimen size, 840
SSME (*see* Space shuttle main engine)
Static fatigue, 788
Steady-state crack extension, 185
Steam generator feedlines, 590
Steel
 aerospace materials, 474
 AISI 4130 grade 31 HRC compressed
 natural gas cylinders, 498
 A508 class 2 pressure vessel steel, 365
 charpy impact properties, 368

Steel—*continued*

- chemical composition, 366
- fracture toughness results, 374, 377
- tensile properties, 370
- A533 grade B, transition range data, test conditions, 81
- A710 grade A class 3, brittle zones in weldments, 809
- A710 tension tests, 66–67
- A723 fracture, 443, 445, 449
- HSLA-80, brittle zones in weldments, 809
- low-alloy pipe steel, chemical composition, and mechanical properties, 170–171
- natural gas cylinders, 498
- on-board cylinders, 498
- storage fuel tanks for vehicles, 498
- tremethylcyclopentanone (TMPC) line pipe steel, 115
- Storage fuel tanks for vehicles, 498
- Strain, 95, 115
- Strength of materials, 344
- Stress
 - crack initiation, 55
 - cracked strip problem, 383, 392–393
 - deformation behavior, 696
 - ductile bimaterial interface, 208
 - elastic plastic materials, 185
 - energy release rate, 635
 - fiber-matrix debonding, 696
 - laminated composites, 680
 - near crack tip effects, 95
 - thick wall cylinder, 443
 - welded wide plates, 284
- Stress-intensity factor
 - solutions, 396, 417, 424–425, 435, 461, 635
- Structural analysis, 284
- Structural components, 229
- Structural failure/integrity, 55, 443
- Structural problems, fracture mechanics, 5
- Subcritical crack growth, 788
- Surface cracks, 265, 536
- Swedlow memorial lecture, 2nd, 5

T

- T-stress, 738
- Temperature, 551
- Temperature oscillations, 590
- Tensile stress, 310
- Tension tests, 55
 - crack initiation, 66–67
 - ductile fracture, 115
 - transition range data, 83
- Test methods, 265, 284, 443, 474
- Thermal shock, pressure vessels, 310, 330
- Thermal streaming, 37
- Thermal stresses, 590
- Thermal tensile stress, 310
- Thermal transients in metal structures, 590
- Thick laminates, 751
- Thick wall cylinder, 443
- Thickness effect, 515
- Titanium aluminide, Ti-25Al-25Nb, 551
- Titanium metal matrix composites, 696
- Three dimensional crack analysis, 396
- Through transmission, 619
- Toughness, 5, 37, 229, 474
- Transformation-toughened ceramics, 788
- Transition temperature, 80, 840
- Translamine fracture, 751
- Transverse strain, 95

U, V, W

- Ultrasonic scattering, 619
- Variable amplitude loading, 619
- Weight function, 417
- Weibull analysis, 80, 85, 87
- Weld defect distribution, 809
- Welding, electron beam, 365
- Weldments, 284, 417, 809
- Wide plate tests, 284

Z

- Zirconia toughened alumina, 788
- Zirconium, aluminum-lithium-zirconium alloys, 515