

Subject Index

A

Adjusted compliance ratio technique, 57, 79, 94, 106
 Aluminum alloys, 57, 128, 207
 2024, 14, 157, 379
 2024-T351, 246, 337, 379
 2124, 367
 7050-T76, 285
 8009, 157
 titanium-aluminum-vanadium, 94, 265
 Amplitude loadings, variable, 265, 337, 411
 Applied load, 41
 Asperity, fracture surface, 304
 Asperity heights, 367
 ASTM standards
 E 647, 79, 94, 106, 321
 Austenitic steel, 191

B

Basquin-Morrow equation, 351
 Block load tests, 14

C

Center crack specimen, 57
 Closure measurement, 157
 Compliance methods, 14, 41
 adjusted compliance ratio technique, 57, 79, 94, 106
 cut compliance technique, 175
 Compression, 285
 Compression loading, 207
 Compressive overstrain, periodic, 304
 Computer vision, measurement system
 development, 145
 Constant amplitude, 224, 285
 crack growth rates, 246
 cyclic bending, 393
 loading, 411
 straining, 304
 test, 1
 Constraint, 128
 Corrosion fatigue, 459

Crack closure, 14, 57, 106, 207
 behavior under variable amplitude loadings, 265, 337, 411
 concept, 128
 cut compliance technique, 175
 effects, 94
 effects on fatigue crack growth, 224
 fatigue, measurement, 321
 load excursion effect on, 246
 measurement, 41
 overstrain effects on, 304
 plasticity-induced, 1, 106, 128, 351
 plasticity-induced, prediction, 427
 roughness-induced, 351
 specimen thickness effect on, 246
 stresses, 440
 synergetic effects, 379
 Crack front propagation, 157
 Crack growth, 427, 459
 asymmetry, influence on geometric correction factor, 379
 behavior, nonflat crack surface effects on, 367
 notches, 411
 overload effects, 191, 224
 retardation, 14
 transgranular, 265
 rate, 57, 106, 246, 351
 rate, closure mechanisms effect on, 224
 rate under constant amplitude loading, 411
 rate under constant amplitude straining, 304
 rate under variable amplitude loadings, 265, 411
 Crack initiation, 351
 Crack nucleation model, 351
 Crack opening displacement, 145
 Crack opening load, 14, 79, 106, 157
 description using strip yield model, 459
 Crack opening stress, 285, 367
 Crack propagation methods, 41, 57, 207
 Crack tip closure, 94
 Crack tip displacement, 157, 427

Crack tip opening displacement, 246, 367
 Crack tip strain, 106
 Crack tip stretch, 459
 Cut compliance method, 175
 Cyclic bending, constant amplitude, 393
 Cyclic loading, 393, 411
 elastoplastic large deformation analysis, 440

D

Damage tolerance concepts, 246
 Deformation, 41
 analysis, cyclic load elastoplastic, 440
 behavior, 106
 crack flanks, 1
 Delay cycles, 379
 Diffusion, stress-assisted, 440
 Digital image correlation, 145
 Digital imaging displacement system, 157
 Discrete dislocation model, 1
 Dislocation arrangement, 1
 Displacement-based method, plasticity-induced
 crack closure prediction, 427
 Displacements, sliding, nonflat fatigue cracks,
 367
 Dugdale-Barenblatt model, 285
 Dugdale crack closure model, 128

E

Elastic-plastic finite element model, 106, 411
 Elastic-plastic growth model, 411
 ESACRACK software, 459

F

FASTRAN-II, 285
 Fatigue crack model, 304
 Fatigue crack growth model, 459
 Fatigue life prediction methodology, 57
 comparison, 351
 Fatigue life, total, 351
 Fatigue loading, 321
 Fatigue strength, 304
 Fatigue threshold, 57
 Finite element
 analyses, 411
 elastic-plastic, 106
 method, 157, 440
 model, 285, 321, 337, 427
 Flaw shape evolution, 393
 Forward inversion method, incremental, 175
 Fractography, 224

Fracture surface asperity, 304
 Fracture surface roughness, 265

H

Hi-Lo block loading, 337
 Hydrogen-assisted cracking, 440
 Hysteresis energy, cyclic, 128

I

Image acquisition, 145
 Image analysis, 145
 Initiation-propagation model, 351

J

J-integral, 411

L

Linear elastic fracture mechanics shape
 function, 427

Loading

 block, 337
 constant amplitude, 14, 265, 411
 cycle, 1
 cycle, loading/unloading, 145
 cycle, two-step, 265
 cyclic, 285, 393, 411
 cyclic, elastoplastic large deformation
 analysis, 440
 fatigue, 321
 frequency, 459
 variable, 337

Loads

 crack opening, 79
 displacement curves, 41, 79
 excursions, effect on crack closure
 measurements, 246
 interior opening, 157
 ratio, 14
 transfer, 57
 wave shape, 459

M

Mean stress, 157
 Mesh size, 337
 Metal fatigue, 427
 Microscope, far field, 145
 Models and modeling
 crack nucleation, 351
 discrete dislocation, 1
 Dugdale-Barenblatt's, 285
 Dugdale crack closure model, 128
 elastic-plastic, 411

elastic-plastic finite element, 106
 fatigue crack, 304
 fatigue crack growth, 459
 finite element, 285, 321, 337, 427
 Newman's crack-closure, 285
 one-dimensional strip yield, 285
 strip-yield, 321, 393, 459

N

NASGRO software, 459
 Newman's crack closure, 285

O

Opening load measurement, 79
 Overload, 285
 effects, 207, 224, 246
 effects on crack growth rate, 191
 single, 337
 single tensile, 191
 tensile, 224

P

Paris law region, 94, 106, 128
 Plane-strain conditions, 14
 crack closure under, 1
 Plane stress conditions, 337
 Plastic damage, 128
 Plastic deformation, 41, 285
 residual, 191
 Plasticity-induced crack closure, 246
 aluminum alloy, 379
 assessment, 128
 characterization, 106, 393
 control on crack opening point, 265
 nonflat crack surfaces, 367
 prediction method, 427
 thickness effects on, 285
 two-dimensional analytical model, 351
 under plane-strain conditions, 1
 Plastic zone size, 337
 Potential drop method, 14

R

Residual plastic deformation, 191
 Residual stress, 175, 207, 440
 Roughness, fracture surface, 265
 Roughness-induced crack closure, 351

S

Scanning electron microscope, 106, 224
 Shear fatigue straining, 304

Shear lip, 379
 Slope offset method
 E 647, 79, 94, 106, 321
 Specimen thickness, effect on crack closure
 measurements, 246
 Speckle pattern, random, 145
 Steel, 128, 393
 austenitic, 191
 carbon, 321
 Stereophotogrammetric reconstruction, 191
 Strain, cutting effects on, 175
 Strain intensity factor, 304
 Strain rates, 459
 Stress-assisted diffusion, 440
 Stress intensity, 1, 246, 427
 effective, 57
 factor, 94, 128, 321, 379, 411
 factor, crack propagation, 207
 factor, due to residual stress, 175
 factor, relative to small scale yielding, 440
 range, cyclic, 157
 range, effective, 41, 265
 Stress level, influence on flaw shape evolution,
 393
 Stress ratio, 57, 128
 negative, 321
 Stress redistribution, 57
 Stress, residual, 175
 Stress-strain parameters, 440
 Striation formation, 14
 Striation spacing, 191
 Strip-yield model, 321, 393, 459
 one-dimensional, 285
 Surface flaw shape evolution, 393

T

Tensile overload, 224
 single, 191
 Tensile stresses, 367
 Thickness, effect on plasticity-induced fatigue
 crack closure, 285
 Titanium alloy, 224, 367
 titanium-aluminum-vanadium, 265
 titanium-aluminum-vanadium forgings, 94
 Transient loading, 224

U

Underload, 224, 246

Y

Yield strength, 427