

Subject Index

A

Acoustic monitoring (*see* Monitoring, acoustic)
 Adhesives
 BP-907, 211
 EC 3445, 322
 epoxy (*see also* Composite materials, carbon/epoxy, graphite/epoxy, Kevlar/epoxy, S-glass/epoxy, T-300/epoxy), 256
 FM-123-2, 162
 FM-300, 322
 FM-1000, 266
 Narmco 5208, 426
 rubber-toughened, 256
 Aircraft, composite structures, 5, 34, 48
 Angle of lamination, 161
 AS1 graphite/3501-6 epoxy composite, 140
 AS1 graphite/3502 epoxy composite, 256
 ASTM Standards
 D 790-71, 427
 D 2344-76, 427
 D 3039-76, 52, 427
 D 3410-75, 52, 427
 D 3410-82 125
 D 3518-76, 52
 E 23-82, 369

B

Bismaleimide, 48
 Bolted repairs, 35

Bond strength (*see* Strength, bond)
 Bond thickness, 209
 Bonds, adhesive, 266, 322
 Boron/aluminum composite, 337
 Braided materials (*see* Composite materials, braided)
 Broadgoods, 64
 Buffer strips, 5

C

Cantilevered beam specimens, 64, 209, 257, 322
 Carbon/epoxy composite, 5
 Charpy-type specimens, 368
 ASTM Standard E 23-82, 369
 Coating, photoelastic, 232
 Compact tension specimen, 177
 Composite materials
 AS1/3501-6, 140
 AS1/3502, 256
 AS4-3K/5208, 392
 boron/aluminate, 337
 braided, 392, 404, 422, 427
 ASTM Standards D 790-71, D 2344-76, D 3039-76, D 3410-75, 427
 carbon/epoxy, 5
 E-glass/polyester, 87
 filament-wound, 64
 graphite/bismaleimide, 48
 graphite/epoxy, 5, 64, 87, 115, 140, 177, 196, 232, 256, 266, 286, 322, 392, 422

Composite materials (*continued*)

- in-lays, reinforcing, 5, 64, 256, 266
- Kevlar/epoxy, 368
- metal matrix, 337
- multidimensional, 392, 404, 422
- orthotropic, 34, 404
- quasi-isotropic, 392
- S-glass/epoxy, 368
- T-300/epoxy, 87, 177, 196, 368
- T-300/V-378A, 48
- textile (*see* Composite materials, braided)
- thermoplastic matrix, 109
- thick-wall, 64
- unidirectional, 115, 161
- Compression failures (*see* Loads, compression)
- Computer programs
 - BREPAIR, 34
 - NASTRAN, 308, 368
- Configuration, material, 177
- Coupons, 140
- Crack, center specimens, 177
- Crack propagation (*see also* Notched specimens)
 - AS1/3502 graphite/epoxy material, 256
 - cracked-lap shear specimen, 232, 322
 - resin-toughened matrix, 209
 - various reinforcing in-layers, 256
- Cracked-lap shear specimens, 232, 322
- Crack-tip damage (*see* Damage, crack-tip)

D

Damage

- circular, 35
- crack-tip, 177, 209
- impact, 5, 48, 196
- penetration, 5
- service-induced, 5
- tolerance, 48, 256, 266, 422
- various composites, 31

visible versus nonvisible, 5

- Data processing (*see also* Computer programs; Finite element analysis), 163
- Debond growth, 322
- Defects, manufacturing, in aircraft structures, 5, 48
- Deformation of metal matrices, 337
- Delamination
 - adhesive joints, 209
 - adhesive layers, 266
 - analysis design, 64, 232
 - composite joints, 308, 322
 - filament-wound composites, 64
 - edge strength, 266, 286
 - interlaminar shear, 64, 286
 - reinforcing in-lays, 256
 - stacking sequence, effect of, 161
 - stepped-lap joints, 308
 - thick-wall composites, 64
- Double cantilevered beam specimen (DCB) (*see* Cantilevered beam specimen)
- Dry test conditions (*see* Room temperature, dry (RTD))

E

- Edge strength, 266, 422
- Elasticity, braided composite, 392, 404
- Electron microscopy, 145, 209, 232, 256
- Elevated temperature, wet (ETW), 5, 48, 140
- End-gaps, 308

F

- Fabrication, braided material, 422
- Failure mechanisms
 - center-notched boron/aluminum composite, 337
 - in situ* testing, fiber/matrix bond strength, 87

metal composites, 337
 threshold in graphite/epoxy composite materials, 196
 transverse tensile strain in thermoplastic composites, 109
 unidirectional composites, 115
 wet graphite/epoxy coupons, 140
 Fasteners
 installation/removal cycles, 5
 manufacturing defects, 5
 seating depth, 5
 Fatigue loads (*see* Loads, fatigue)
 Fatigue strength (*see* Strength, fatigue)
 Fiber (*see also* Composite materials)
 buckling of, 115
 glass (*see* Glass fiber)
 graphite (*see* Graphite/epoxy composites)
 orientation, 404
 tow size, 422
 volume, 404
 Filament-wound composites, 64
 Film lamination, resins, 422
 Finite element analysis
 bolted composite repair, 34
 bond strength, 87
 dynamic/static stress, 368
 fracture resistance, 64,
 interlaminar stress, 266, 308
 Flaw size, rocket cases, 64
 Flexural specimens, 368
 Fracture, interlaminar (*see* Delamination)
 Fracture mechanisms
 adhesive joints, 5, 209
 mixed-mode, 64, 140, 232, 322
 mode I, 64, 322
 mode II, 64, 232
 notched/unnotched specimens, 64,
 161, 368
 thick-wall, filament-wound specimens, 64
 wet coupons, 140
 Fractographic analysis, 140

G

Geometric model, 392
 Glass fiber
 buffer strips, 5
 mats, 256
 polyester in composites, 87, 368
 scrim, 256
 Global-local laminate variational model, 286
 Graphite/bismaleimide composite, 48
 Graphite/epoxy composites
 aircraft structures, 5
 braided composites, 392, 404, 422
 fiber/matrix systems, 87, 115
 filament-wound, 64
 interlaminar shear studies, 286
 laminate thickness/specimen configuration, 177
 mixed mode/mode II interlaminar fracture, 232
 notch sensitivity/stacking sequence, 161
 projectile impact/tension load studies, 196
 use of reinforcing in-lays, 256, 266
 wet compression coupons, 140

H

HBRF-55A resin system, 64
 Helical layering, diagram, 72
 Hercules AS4-12K graphite, 64, 256
 Holes
 aircraft structure, 5, 34, 48
 loaded/unloaded, 48
 strains related to, 5, 14, 34, 48, 161
 Hoop layering, diagram, 72
 Humidity (*see* Water; Wet test conditions)
 Hygroscopic behavior, composites, 48

I

Image analysis, 140
 Impact damage (*see* Damage, impact)

Impact loads (*see* Loads, impact)
 In-lay materials (*see* Reinforcing in-lays)
In situ test method, 87
 Instron testing machine, 339
 Interlaminar fracture (*see* Fracture, interlaminar)
 Interlaminar shear (*see* Shear, interlaminar)
 Isochromatic monitoring (*see* Monitoring, isochromatic)

J

J-integral, 64
 Joints
 adhesive, 209, 308
 lap/strap, 232
 metal composite, 308
 stepped-lap, 308
 strength (*see* Strength, joint)
 structural, 5

K

Kevlar
 buffer strips, 5
 epoxy composites, 368
 mats, 256
 Kink band formation, 115

L

Loads
 biaxial,
 bolted composite repairs, 34
 thermoplastic composite, 109
 compression,
 aircraft fuselage panels, 18
 ASTM Standard D 3410-82, 125
 AS4 graphite/3502 epoxy composite, 232
 in situ tests various fiber/matrix composites, 87

 graphite/epoxy composites, 64, 115, 140
 ST-300/1034-C graphite/epoxy composite, 286
 thick-wall, filament wound composite, 64
 unidirectional composites, 115
 wet graphite/epoxy coupons, 140
 fatigue,
 carbon/epoxy composite, 5
 graphite/epoxy composite, 48, 196, 322
 T-300/V-378A graphite/bismaleimide composite, 55
 impact,
 carbon/epoxy composite, 5
 graphite/epoxy composite, 196
 Kevlar/epoxy composite, 368
 S-glass/epoxy composite, 368
 T-300/epoxy composite, 368
 shear,
 aircraft fuselage panels, 19
 bolted composite repairs, 34
 cracked-lap specimens, 232
 global-local laminate model, 286
 thick-wall, filament-wound composite, 64
 spectrum
 stepped-lap joints, 308
 static
 carbon/epoxy composite, 5
 graphite/epoxy composite, 266, 322
 Kevlar/epoxy, 368
 S-glass/epoxy, 368
 T-300/epoxy, 368
 T-300/V-378A composite, 55
 tensile
 boron/aluminum composite, 337
 graphite/epoxy composites, 161, 232
 strain-energy release rate, 244
 transverse strain on thermoplastic matrix, 109

M

- Manufacturing defects, aircraft structures, 5
- Mar-Lin equation, 161
- Materials (*see* Composite materials)
- Mats, reinforcing in-lay, 256
- Metal
 - composite joint, 308
 - matrix composite, 337
 - patch, 34
- Metallography, 140
- Microbuckling, 115
- Microdebonding, 87, 115
 - test apparatus, diagram, 90
- Microstructural analysis, 48, 140, 256, 286
- Modulus
 - elastic
 - braided composite, 392, 404
 - FM 1000 adhesive film, 270
 - tensile
 - braided composite, 400
- Moisture (*see* Water)
- Monitoring
 - acoustic, 164, 337
 - emission events, 353
 - isochromatic, 232

N

- Nondestructive testing, 19, 29, 87, 140, 180, 232, 286, 337
- Northrop ETL standard, 52
- Notched specimens, 64, 161, 337, 368

O

- Optical metallography, 140
- Orthotropic composite materials, 34, 368, 404

P

- Panels
 - fatigue-loaded, 18
 - shear-loaded, 19, 34, 48
- Patch, metal, 34
- Pattern, braid, 422
- Photoelastic coating, 232
- Photomicrography, 286
- Plate, finite/infinite, 34
- Point stress criterion, 161
- Poisson's ratio, 64, 112, 117, 270, 405
- Polycarbonate, 109
- Polyester, 256
- Polyetheretherketone, 109
- Porosity, aircraft structure, 5
- Postbuckling, 5
- Projectile impact loads, 196

R

- Radiographic inspection (*see also* X-ray analysis) 23, 26
- Rail shear test, 64
- Reinforcing in-lays
 - broadgoods, 64
 - buffer strips, 5
 - FM-1000 adhesive film, 266
 - glass fiber mat, 256
 - organic fiber mat, 256
 - rubber-toughened epoxy, 256
 - scrim, 256
 - various in-lays, 258
- Repairs, bolted, 34
- Residual strength (*see* Strength, residual)
- Resins (*see also* Graphite/epoxy composite)
 - BP-907, 209
 - epoxy, 115, 209
- HBRF-55A, 64
 - impregnation of braided composite, 422
 - rocket cases, 64

HBRF-55A (*continued*)

stiff versus soft, 115

Resistance, fracture

effect of laminate thickness, 177

filament-wound composite, 64

flexural specimens, 368

interlaminar, 64

Rocket booster case, 64

Room temperature, dry (RTD), 5, 48, 140, 154

Rubber-toughened adhesive, 256

S

Scanning electron microscopy (SEM)
(*see* Electron microscopy)

Scrim, glass, 256

Shear crippling, 115

Shear, interlaminar, 286, 422

Shear loads (*see* Loads, shear)Spectrum loading (*see* Loads, spectrum)

Stacking sequence, plies, 161, 196, 286

Static strength (*see* Strength, static)Stereology (*see* Image analysis)

Stitching, 5

Strain energy release rate, 64, 266, 407

Strength

bearing, 48

bond, 87

compression, 5, 115, 422

fatigue, 5, 48

flexural, 422

interfacial, 87

various fiber/matrix systems, 99

joint, 5

notched, 64, 161, 337, 368

residual, 5, 308

static, 5, 48, 368

tensile, 392, 422

Stress analysis (*see* Failure mechanisms; Fracture mechanisms; Loads; Strength)

Stress wave propagation, 368

Strip in-lays, reinforcing, 5

T

T-300/epoxy composite, 87, 177, 196, 368

T-300/V-378A graphite/bismaleimide composite, 48

ASTM Standards D 3039-76; 3410-75; 3518-76, 52

Tape, unidirectional, 48

Temperature, elevated, humid

effect on aircraft composite structures, 5

effect on AS1-graphite/3501-6 epoxy composite, 140

effect on graphite/bismaleimide composite, 48

effect on wet graphite/epoxy composite, 140

Temperature, room

effect on aircraft composite structures, 5

effect on graphite/bismaleimide composite, 48

effect on AS1-graphite/3501-6 epoxy composite, 140

Tensile strain (*see* Loads, tensile)

Tension

center-crack, 177

compact, 177

Thermoplastic matrix, 109

Thickness

bond, 209

laminate, 177

Three-point bend specimen, 177

Tolerance, damage (*see* Damage tolerance)Toughness, fracture (*see* Resistance, fracture)

U

Ultrasonic inspection, 19, 29

Unidirectional composites

ASTM Standard D 3410-82, 125

Unidirectional lamination, 115, 161

V

Velocity, projectile, 196

W

Water, absorption of, 48

Wet test conditions

effect on aircraft composite structures, 5

fiber orientation versus compression failure, 155

effect on graphite/bismaleimide composite, 48

effect on graphite/epoxy composite, 140

X

X-ray analysis, 180, 286

Y

Yarn orientation, 392, 404