

Subject Index

6092/SiC/17.5p-T6, 255

A

Acid strain corrosion tests, 178
Adhesive bonding, 151
Allowables, 291
Aluminum, 166
Anisotropy, 75, 93, 320
ASTM D 6671, 349
Autofrettage, 193
Axial tensile, 178

C

Carbon dust explosion, 132
Carbon-epoxy composite, 55, 372
 unidirectional off-axis, 336
Carbon fiber, 336
Carbon fiber reinforced polymer,
 166
Coefficient of friction, modified,
 166
Coefficient of thermal expansion,
 mismatch, 193
Composite pipes, 193
Composite rotor, 3, 121, 132
Compressive loading, 255
Computational simulation, 224
Constitutive equations, 207
Contact pressure, 166
Containment, 121, 132
Crack growth, 273
Creep, 55, 75, 336
Cryogenic, 193
Cyclic loading, 255, 336

D

Damage, 336
 accumulation, 238
 internal, 255
 progressive, 224
Deformation, 93
Degradation, 151
Delamination, 349, 372
Discontinuously reinforced aluminum,
 255

E

Energy release rate, 224
Energy storage, 3
Epoxy matrix, 336

F

Failure, 291
Failure analysis, 121, 132, 291
Failure criteria, 291
Failure modes, 291, 320
Fatigue, 273, 336
Fatigue life, 273
FEA, 121
Feed line, 193
Fiberglass, 178
Fiber/matrix bond strength, 273
Fiber-reinforced-polymers, 238
Field exposure, 151
Filament winding, 40
Filament wound flywheel, 55
Flywheel rotors, 3, 29, 55, 75, 93, 121,
 132
Flywheels, 40
Fractography, 178
Fracture control, 3
Fracture toughness, 224, 372
Frequency spectrum, 29
Friction, 166, 273

H

Hardness, 166
HTA/6376, 336
Hydroburst test, 40
Hysteresis loops, 336

I

IM7/8552, 55, 93, 372
Impact, 207
Interfacial stress, 166

L

Laminated composites, failure criteria,
 291
Linear hereditary material response, 55
Load sign effects, 55

M

Manifold burst behavior, 121, 132
 Master curve, 336
 Material properties, 40
 Mechanical degradation, 238
 Micromechanics, 207
 Microscopic damage, 238
 Mixed-mode bending test, 349

N

NOL ring, 151
 Nondestructive evaluation, 3
 Non-isothermal, 75
 Nonlinear error, 349
 Non-recurring cost, 291
 Notched beam specimen, 224

O

Off-axis, 336

P

PMC, 93
 Polymer matrix composites, 207
 Predesign, 291
 Prepreg winding, 151
 Press-fit, 75
 Principle of superposition, 55
 Product development, 291

Q

Quasi-elastic, 75

R

Reinforced aluminum, 255
 Reinforced plastic mortar, 178
 Resin infusion, 151
 Resonance, 29
 Rotating disk, 93

S

SCS5/Timetal 834, 273
 Seismic retrofit, 151
 Sewer pipes, 178
 Shear loading, 255

Shear stress, 166
 SiC-fiber reinforced titanium, 273
 Simulation, 238
 Sliding behavior, 166
 Spin testing, 3, 121, 132
 Stiffness, 336
 pipe, 178
 Strain corrosion, 178
 Strain rate, 207
 Strength, 255, 291, 320
 Stress analysis, 291
 Stress field, 320
 Stress intensity factor, 224, 273
 Stress relaxation, 55
 Stress rupture life, 3
 Structural requirements, 291

T

Tabbed specimen, 320
 Tape laminates, 372
 Tensile loading, 255
 Tensile stress-strain, 207
 Tensile test, 320
 Thermal loading, 75
 Time-dependent material, 93
 Time-temperature response, 55
 Titanium matrix composites, 273
 Toughness, 349

U

Ultrasonic spectroscopy, 29
 Unidirectional, 336, 349

V

Vessel, 193
 Viscoelasticity, 75, 93
 Viscoplasticity, 93, 207

W

Wet layup, 151
 Woven composites, 372

Y

Yield surface, 255
 Young's modulus, 320