

Subject Index**A**

Acetylene, 425
 Adiabatic compression, 224, 256
 Administrative programs,
 oxygen, national, 341
 Adsorption tests, 425
 Aging, oxygen
 effect on combustion
 properties, 73
 effect on ignition properties,
 73
 polymeric materials, 3
 Air separation unit, 134, 389, 425
 Alkali metal ions, 240
 Aluminum, 101, 134, 497
 heat exchanger, 373
 aluminum-bronze, 38
 aluminum-palladium wire,
 190
 aluminum-silicon binary
 alloys, 179
 aluminum-silicon carbide
 metal matrix
 composites, 179
 combustion, 295
 packing, 389
 regulator fire, 295
 rods, 497
 tubing, 402
 ASTM standards
 D 240, 87
 D 2512, 134
 G 63, 256
 G 72, 87, 510, 521
 G 74, 521
 G 86, 87
 G 94, 38
 G 124, 38, 179
 ASTM/NASA flammability
 test, 145
 Autogenous ignition temperature
 G 72, 87, 510, 521
 Autogenous ignition testing, 323
 Autoignition temperature, 3,
 73, 510

B

BAM, 456, 510
 Binary alloys, 179
 Brazed aluminum heat
 exchangers (BAHX), 373
 Breathing air devices
 delivery systems, 357
 polymer ignitability, 87
 ventilators, 57
 Bruceton method, 521
 Buna-N, 207, 497
 Burning mode transition, 402
 Burn rate, 469

C

Calibration study, 437
 Capacitors, 57
 Carbon monoxide, 163
 Carbon oxide production, 240
 Carbon steel, 119
 Cardiopulmonary resuscitation,
 341
 Cellulose, 240
 Chlorine, 456
 Chloroprene, 73
 Chromium-molybdenum low
 alloy steel, 119
 Circuits, medical device
 electronic, oxygen fires
 in, 57
 Cleaning processes tests, 3
 Cobalt, oxygen solubility in, 145
 Combustion, 497
 aluminum packing, 389
 aluminum tubing, 402
 behavior, metallic material
 G 124, 38
 cellulosic fabric, 240
 heat of, 3, 323, 469
 iron, 190
 metals, 145, 163, 179, 190,
 266
 microgravity, 266
 promoted, 87, 119
 propagation, steel, 163

532 FLAMMABILITY AND SENSITIVITY OF MATERIALS

- reduced gravity, 266
tests, heat of, 3, 73
 D 240, 87
trayed columns, 389
- Composites, metal matrix, 179
- Compressed Gas Association,
 373, 469
- Compression, adiabatic, 224, 256
- Compressors, oxygen, 373
- Copper, 134
- Cotton, 240
- Cryogenic vessels, 134
- Cylinder valve outlets, 456
- D**
- Data recording system, strip
 chart, 437
- Degradation, 73
- Delrin, 87
- Dewar flange, 207
- Dimensional instability, 21
- Diving, 357
- Dynamic flow, 437
- E**
- Elastomers, 73
 ignition, 207
- Electrical loading conditions, 57
- Electronic circuits of medical
 devices, oxygen fires in, 57
- Electron microscopy, 190
- Elongation at break, 73
- Equation of state for oxygen, 256
- Ethane, 456
- Ethylene/propylene rubber, 87
- Exchangers, 134
- F**
- Fire, electronic circuits of
 medical devices, 57
- Fire potential, 456
- First aid, 341
- Flat gasket combustion, 3
- Flow friction, 21
- Flow modeling, 437
- Fluid flow analysis, 224
- Fluid temperature, 256
- Fluorine, 456
- Food and Drug Administration,
 341
- Fourier transform infrared
 spectroscopy, 323
- G**
- Gaseous impact test, 224
- Gaseous oxygen shell, 402
- Glass fiber, 134
- Glass transition, 21
- Gravity tests, 190
- H**
- Hardness, durometer, 73
- Heat of combustion tests, 3,
 323, 469
- Heat transfer, 240
 coefficient, 266
- Hexadecane, 134
- Hexafluoropropylene/vinylidene
 fluoride copolymer, 521
- Hot spot formation, 224
- Hydrocarbon adsorption, 425
- Hydrocarbon fuels
 D 240, 87
- Hydrocarbons, 134
 hydrocarbon-based oil films,
 357
- I**
- Igniter effects, metals
 combustion testing, 190
- Ignition cell, 389
- Ignition-combustion, promoted,
 119, 179, 373, 437
- Ignition, contaminant promoted,
 295, 323, 357
- Ignition mechanism, 101, 357
- Ignition, promoted, 402
- Ignition, oxygen aging effects
 on, 73
- Ignition, regulator, 295
- Ignition source, 256
- Ignition tests
 aluminum, impact, 134
 autogenous ignition
 temperature
 G 72, 87, 510, 521
 autogenous ignition 323

INDEX 533

- autoignition temperature, 3, 73, 510
cellulosic fabric, 240
elastomer, 207
metals, 497
resistance, 101, 357
sensitivity, 521
 G 86, 87
system, 497
temperature
 G 72, 87
Ignition, welding regulator fire, 323
Impact ignition sensitivity, 521
Impact, particle, 295
Impact, pneumatic, 357
Impact sensitivity, 21
Impact tests
 aluminum, 134
 gaseous, 224
 gaseous oxygen, 38
 mechanical, 3, 87, 207
 particle, 38, 101, 295
 pneumatic, 521
Inconel, 38
Insect ignition, welding regulator fire, 323
Insulation, 134
International Organization for Standardization
 ISO 10156, 456
 ISO TC58/SC2, 456
Iron
 flammability tests, 266
 oxygen solubility in, 145
 rods, burning, 145
- K**
- Kel-F, 21, 87
Kindling chain, 497
- L**
- Labeling, 456
Liquid oxygen (LOX), 373, 389, 425
 G 86, 87
 aluminum ignition by impact in, 134
- aluminum tubing
 combustion, 402
ignition, Buna-N O-rings, 207
- M**
- Mass diffusion, 240
MATLAB, 266
Mechanical impact tests, 3, 207
 G 86, 87
Medical devices, electronic circuit oxygen fires, 57
Metallic materials, flammability evaluation, 437
Metals, 240
 combustion tests, 3
 flammability, 119, 373, 469
 ignition, 497
 matrix composite, 179
 oxidation, 266
 ranking
 G 94, 38
Metal selection, oxygen valves, 38
Models and modeling
 compression, 256
 drop tower, 266
 flammability, 469
 flow, 437
 ignition, 207
 mathematical, 497
 smolder, cellulosic fabric, 240
 two-dimensional, 224
- N**
- National Aeronautics and Space Administration, 357, 437, 469
ASTM/NASA flammability test, 145
metals ignition test system, 497
particle impact test, 38
NASA-STD-6001, 87
National Fire Protection Association, 469
Neoflon, 21, 73
Neoprene, 73, 87
Neutral Buoyancy Lab, 357

534 FLAMMABILITY AND SENSITIVITY OF MATERIALS

Nichrome-hydrocarbon, 373
Nickel, 119

oxygen solubility in, 145
Nitric oxide, 456

Nitrogen trifluoride, 456
Nitrous oxide, 425, 456

Nitrox, 357

Noryl, 87

Nylon, 73

O

O-rings, 207, 497

Oxygen index, 469
tests, 3

P

Paar Bomb test, 510

Packing, structured, thin
aluminum sheet, 389

Palladium, 190

Particle impact, 38, 101, 295

Pneumatic impact tests, 3,
357, 521

Polyamide, 521

Polychlorotrifluoroethylene,
21, 73

Polyetheretherketone, 101

Polyethylene, 521

Polyhexamethylene adipamide,
73

Polymeric materials, 521
oxygen aging, 3
oxygen compatibility, 73, 87
particle impact ignition
behavior, 101

Polymer promoter, 497

Polyoxymethylene, 521

Polytetrafluoroethylene, 73, 521

Pressure, threshold, 469

Propane, 425

Pyrofuze, 437
wire, 190

R

Reaction kinetic parameters,
240

Reduced gravity combustion,
190, 266

Regression, melting interface,
190

Regression, melting sample, 266

Regulator burnout, aluminum
bodied, 295

Regulator explosion, 323

Rubber

chloroprene, 73

fluorocarbon, 73

silicone, 73, 87

S

Safe handling programs,
oxygen, 341

Scanning electron microscopy,
323

Scuba, 357

Shearing load, 207

Sieve trays, 389

Silicon, 179

Silicone, 497, 521

Slag bubble, 163

Slag droplet, 163

Static flow, 437

Steel

carbon, 119

carbon content, 163

chromium-molybdenum low
alloy, 119

stainless, 38, 119, 179, 437,
497

stainless, tubes, 357

Steelmaking process
metallurgy, 163

Storage, gases and gas mixtures,
456

Striker pin, modified, 134

T

Teflon, 73, 87, 101, 497, 510

Tefzel, 87

Temperature gradient, hot gas
plug, 224

Temperature, real fluid, 256

Test and calculation method,
456

Thermal conductivity, 469

Thermodynamic analysis, 256
metals, 145

Thermomechanical analysis, 21

INDEX 535

Thermomechanical properties,
73

Thermoplastics, 73

Threshold pressure, 469

Training, medical oxygen users,
341

Tubing, aluminum, violent
energy release, 402

U

Underwater diving industry, 357

V

Valve, gas cylinder, 456

Valve, metal selection, 38

Valve seats, 21

Ventilators, 57

Vespel

SP-1, 101

SP-21, 87

Violent energy release, 373,
389, 402

Viton, 73, 87, 497, 510

W

Welding regulator, 295, 323

Z

Zytel 42, 73, 87, 510