

Subject Index

A

- Absorbed energy, 3, 32, 101, 111
 - striker effect on, 140, 153
- Acceptance limits, 181
- Anvil, 91
- ASTM standards
 - A 302B: 70
 - A 533: 245
 - A 533B: 70, 111
 - E 23: 19, 39, 70, 91, 101

C

- Calibration specimens, 32
- Certification, machine, 181
- Charpy testing machines
 - certification for, 181
 - compliance, 231
 - Japanese standards for, 170
 - verification, 194, 267
- Charpy V-notch specimens, 3, 101
 - impact energy, 19, 194
 - Japanese standards for, 170
 - lower bound toughness, 245
 - miniaturized, 39
 - neutron damage monitoring with, 39
 - notch location, 153
 - reconstituted, 70
 - reference specimens, 181, 194
 - striker, 111, 231
 - striker radii, 140
 - subsize, 32
 - surface finish, 91
 - velocities, 220
- Crack initiation, 245

D

- Damping absorbers, load, 231
- Damping, viscous, 267
- Deformation analysis, large, 39
- Density, 220

- Drop-weight testing machines, 267
- Ductile-brittle transition temperature, 39

E

- Elastic-plastic analysis, 39
- Electronic frequency response, 282
- Energy levels, references for, 170
- European Structural Integrity Society, 111

F

- Finite element analysis, 39
- Force measurement, 267
- Forging, 111
- Fourier analysis, 267
- Fracture behavior, transitional, 39
- French standards, 194
- Friction, 91

I

- Impact, controlled, experiments, 267
- Impact energy, 19, 194

J

- Jamming after fracture, 19
- Japanese standards, 170

K

- Kinetic energy, 220, 282

L

- Lateral expansion, 111, 153
- Load cells, 267
- Load/displacement data, 231
- Loading, asymmetry of, 3
- Load traces, 282
- Lower bound toughness, 245

M

- Mechanical damping, 231
 Metals, 3, 32, 70
 Charpy V-notch squareness tolerance, 19
 A 302B: 70
 A 533: 245
 A 533B: 70, 111
 E 23: 19, 39, 70, 91, 101
 Modeling, Charpy shift trend curve, 39

N

- National Institute of Standards and Technology, 111, 181
 National Testing Laboratory, 194
 Neutron damage monitoring, 39
 Nuclear reactor, 39, 70
 Nylon alloy, 267

P

- Polymeric specimens, 282
 Pressure vessel, 39, 70, 111
 Projection welding, 91

R

- Reconstitution, 70
 Reference specimens, 19, 111, 140, 181, 194
 Restitution, coefficient of, 220

S

- Shear lips, 3
 Spinning, specimen, 19
 Squareness tolerance, 19

Standards (See also ASTM standards)

- EN 10045-2, 194
- ISO DIS 442, 194
- ISO TC, 140
- Japanese, 170
- National Institute of Standards and Technology, 111, 181

Steel, 32, 70
 high strength, 3

Stress intensity, 245

Stress waves, 267

Strike marks, 3

Striker, 91, 101, 111
 edge, 153

radius, 140

striker geometry, 101
 tups, 282

Surface finish, 91

Symmetry effects, 153

T

- Three-dimensional analysis, 39
 Three-point bend test, 231
 T-test, 19
 Toughness, 70, 245
 Tup, instrumented, 245
 Tup, striker, 282
 Tup, verifier, 267
 Two-dimensional analysis, 30

U

- Upper shelf energy, 39, 70
 Upper shelf submerged arc weld, 111

V

Velocity, 220

W

- Weld, 111
 Welding, projection, 70, 91