

# Subject Index

## A

- Accuracy, manual/automatic comparison chart ratings, 212–215
- Aerospace material specifications
  - AMS 2301, 48, 51–52, 171, 268, 271, 346
- Air-melted and vacuum-arc remelted steels, M-50 comparison with VAR-VAR and VIM-VAR steels, 13
- Alternating shear stress hypothesis (*see* Orthogonal shear stress hypothesis)
- Aluminates, type B
  - ladle steelmaking and, 73
  - RHP inclusion index
    - 4720 steel,  $L_{10}$  fatigue life, 67
    - 52100 steel,  $L_{10}$  fatigue life, 67
  - SAM ratings
    - 1070 modified steel, 51
    - 52100 steel
      - fatigue  $L_{10}$  life, 69
      - fatigue  $L_{50}$  life, 71
      - history, 50
    - carburizing steels, fatigue  $L_{10}$  life, 72
- Aluminum deoxidation, 361
- Ammonia atmosphere, compressive residual stress induction, 28
- AM-VAR steels (*see* Air-melted and vacuum-arc remelted steels)
- Antimony contents, DIN 100 Cr 6 steel, 299
- Argon ladle refining
  - chemistry control
    - argon refining processes, 339
    - vacuum arc degassing, 338–339
  - oxygen contents, 343, 345
  - procedure, 337–338
  - standard ladle, 334
  - with vacuum arc degassing and argon refining, 332–333
  - vacuum arc remelting and, 333
- Argon oxygen decarburization, carbon steel, Swedish standard SS 111116, 254
- Argon treatment
  - bubbling, 266
  - gas shrouding, 7, 52
  - injection via porous plugs, 265
  - soft bubbling, 361
  - stirring in ladle, 336
- Arsenic contents, DIN 100 Cr 6 steel, 299
- ASEA ladle refinement, 166
  - bottom-poured ingots
    - macroinclusions, 170–171
    - microinclusions, 179–182
    - oxygen content, 182–184, 186
    - sulfur content reduction, 172
- ASTM standards
  - A 45-85, 331
  - A 295, 61, 69, 222, 312, 325, 327–328
  - A 295-79, 251
  - A 295-84, 1, 46–47, 72, 157, 161, 172, 179, 267–268, 300, 303, 344, 346, 363
  - A 485, 311
  - A 485-79, 338, 340, 342, 346
  - A 534, 64, 311
  - A 534-79, 344, 346
  - A 535-79, 346
  - E 29, 207
  - E 45, 61, 79, 157, 263, 267, 344
  - E 45-63, 22
  - E 45-76, 363, 366, 370

ASTM standards (*cont.*)

E 45-85, 47-48, 168, 172, 211, 226-227, 251, 254, 258-300, 303

E 50, 207

E 59, 207

E 112-63, 22

E 173, 194, 207

E 351, 195

E 352, 195

E 353, 195

E 354, 195

E 485-79, 344

E 562-83, 227

E 1019, 192, 207

E 1091, 195

E 1122, 226

P 187, 195

ASTM subcommittee E03, 191-192, 194-195

Ausforming method, 24-25

Austenite, retained

decomposition at different contact stresses, 106

effects on rolling-element fatigue, 31-35

microstructural change monitoring, 105

**B**

Ball bearings (*see also* Roller bearings)  
6206

fatigue life improvement, 133

Weibull life distributions, 133

M-50 VIM-VAR steel

endurance characteristics, 11

endurance tests, 12

Bars (DIN 100 Cr 6)

inclusion rating (SEP 1570-71), 295

microstructure (SEP 1520-78), 295

specifications, 294

Basic oxygen furnace melting, 361-362  
DIN 100 Cr 6

arsenic and antimony contents, 299

copper and tin contents, 298

nickel and molybdenum contents, 298

phosphorus contents, 299

tramp elements, 297

Bearings (*see* Ball bearings; Roller bearings)

Bloom casters, shrouding at, 266

Blue fracture test, 363-364

B-thin ratings

fatigue properties and, 157

oxygen content of SKF 52100 steel and, 326

RBF limit for steelmaking processes and, 157

steelmaking processes comparison, 269

Butterflies, under raceways, 84, 87

**C**

Calcium

content

fatigue properties and, 160-161

ratings with, 163

injection, 270

treatment effects, 368-369

Carbide factor, derivation, 20

Carbides

ausforming method, 24-25

in bearing steel microstructures, 114

effects on rolling-element fatigue, 20-25

furrow creation, 121

grain size, effect on machinability, 370-371

M-50NiL steel, 126, 131

M-50 steel, 125-129

peeling and, 118, 120

segregation, continuous-cast steels, 74-77

stress-raising effect, 121

surface roughness contribution, 115

Carbon control, in vacuum arc degassing, 338

Carburizing atmosphere, compressive residual stress induction, 28-29

## Chemical analysis

- inclusion determination by, 223–224
- oxygen determination (*see* Proposed Method for the Determination of Oxygen in Steel and in Iron, Nickel, and Cobalt Alloys)

## Chemistry control

- DIN 100 Cr 6 steel, 297
- in ladle refining, 264–265, 273
- in vacuum arc degassing, 342–344

## Chromium control, in vacuum arc degassing, 339

## Cleanliness

- assessment, 385–386
- continuous-cast and ingot-cast steels
  - blue fracture test, 363–364
  - oxides, 365–369
  - oxygen content and, 366–367
  - SAM ratings, 285
  - step-down test, 364–365
  - sulfides, 369–370
  - titanium-carbonitrides, 369
  - ultrasonic testing, 363
- continuous-cast steels from European manufacturers, 74–77
- fatigue life and, 8–14, 371–372
- fatigue performance and, 139, 381–383
- inclusion evaluation methods, 156–157
- ladle refining, fatigue properties and, 379–381
- microcleanliness ratings, 47
- micrographical, 161, 163
- particle size distribution, 385–386
- ratings, 161–163
- vacuum arc degassing and argon refining process steels, 344–346

## Cold working, effect on fatigue life, 290

## Comparison chart ratings, accuracy, 212–215

## Compressive residual stresses

- effect on
  - fatigue behavior, 97–99
  - rolling-element fatigue, 28–31

## *S-N* curves, 99

- heat treatment effects, 140
- induction processes, 28–30

## Concast blooms, segregation and, 304–305

## Continuous casters

- curved, 348–350
- vertical, 278–280

## Continuous-cast steel, 73–74

- fatigue life, 136, 349–350
  - center segregation effect, 285–287
  - effect of residuals, 357
  - high-purity steel, 287
  - improvement, 352–353, 357
- flaking, 285–286
- macroscopic cleanliness, 363–365
- microscopic cleanliness, 365–370
- product evaluation, 74–77
- quality, 77–79
- SAM ratings, 285
- segregation in, 372
- tube bore defects, 77

## Controlled fibers

- effects on rolling-element fatigue, 25–28
- in races, 26
- raceway forging, 7

## Controlled hardness, discovery, 7

## Copper contents, DIN 100 Cr 6 steel, 298

## Crack growth

- preferred orientation of texture and, 107
- tensile residual stresses and, 107

## Crack initiation, 107, 110

## Crack propagation, during second phase of fatigue, 91–92

## D

## Dark etching areas, 83–84

## Deoxidation

- aluminum, 361
- MR processes, 308–309

Diameters, ideal, in vacuum arc degassing, 339–340

Distortion energy hypothesis, 86

Double-vacuum arc remelted steels, M-50 comparison with AM-VAR and VIM-VAR steels, 13

## E

Elastohydrodynamic film, 7

peeling and, 118, 120

Elastohydrodynamic lubrication, 7

Electric arc furnace—ladle furnace—Ruhrstahl-Heraeus vacuum degassing vessel—vertical continuous caster process, 278–280

Electric arc furnace melting, 361–362

blue fracture test results, 364

DIN 100 Cr 6

arsenic and antimony contents, 299

copper and tin contents, 298

nickel and molybdenum contents, 298

phosphorus contents, 299

oxide cleanliness

E 45-76 inclusions, 367

number and size of inclusions, 366

SAM rating, 367

SEP 1570-71 values, 365

step-down test results, 364

oxygen contents, 367

steels, blue fracture test results, 364

tramp elements, 297

Electric arc furnaces, 5

Whiting Hydro, 333

Electric furnace—vacuum slag cleaner

—ladle furnace—Ruhrstahl-Heraeus degassing-curved continuous caster process, 348–350

Electro slag remelting, 187

carbon steel, Swedish standard SS 111116, 254

inclusion elimination, 161

steel oxygen content and fatigue properties, 159

step-down test results, 364

## F

Fatigue

8620 309-size roller bearings, life distribution, 13

bearing life, major advances, 6

carbide effects, 20–25

carburized steels, 67

controlled fiber effects, 25–28

crack propagation, 91–92

effect of component hardness combinations, 19–20

failure

distortion energy hypothesis, 86, 89

mechanism, 86, 89

fractures, origin, 152–155

hardness effects, 14–20

material cleanliness and, 8–14, 381–383

material defects and, 9

mechanism, 62–64

nonmetallic inclusions, 8–9

plastic deformation during first phase, 89

residual stresses, 28–31

retained austenite effects, 31–35

S-N curve, 105

spalling under rolling contact stressing and, 85–86

structural changes during first phase, 86, 89

subsurface cracks during second phase, 89

successive remelting effects, 10–11, 13

testing, RHP inclusion index technique, 66–69

vacuum-melting techniques and, 9

variation with specimen size and test conditions, 139–140

Fatigue life

cleanliness and, 371–372

continuous-cast steel, 285, 349–350

center segregation effect, 285–287

effect of residuals, 357

European manufacturers, 74–77

high-purity, 287

improvement in, 352–353, 357  
 specimen preparation, 283–284  
 effects of  
   cold working, 290  
   forging ratio, 144, 147  
   impurities, 287–290  
   material cleanliness, 139  
   material strength, 95, 97  
   nonmetallic inclusions, 92, 94–95  
   oxygen, 139  
   sulfur, 288  
   titanium, 288–290  
 heat-resistant steels, 143, 145  
 ingot-cast steel, 285  
 model, 102  
 nitride inclusion size and, 154  
 oxide inclusion size and, 154  
 prediction model, 104–105  
 residual stresses and, 97–99  
 RHP inclusion index and, 66–69  
 SAM ratings and, 69–71  
 subzero treatment effect, 144, 146–147  
 through hardened versus carburized steel, 136  
 Fatigue properties  
   calcium content and, 160–161  
   microcleanliness during ladle refining and, 379–381  
   MR steel, 310–311  
   oxygen content and, 158–159  
   titanium content and, 159–160  
 Fatigue strength, rotating-bending, impurities effect, 287–290  
 Fatigue testing  
   flat washer tests, 313–314  
   MR steel, 311–313  
   rod tests, 315–316  
   rotating beam tests, 317–318  
   Unisteel washer-type rolling contact test, 383, 389  
 Fibers  
   controlled (*see* Controlled fibers)  
   orientation  
     effect on fatigue life, 143–144, 146  
     flow angle effect on fatigue life, 146

Field performance, integral wheel bearing, 56–58  
 Flakings  
   fatigue life of continuous-cast steel and, 285–286  
   rolling bearings, 278  
 Flat washer tests, MR steel, 313–314  
 Forging  
   fiber patterns and, 25–26  
   raceways, with controlled fiber orientation, 7  
   ratio, effect on fatigue life, 144, 147  
 Fracture toughness  
   effect on rolling-element fatigue, 35–40  
   nickel effects, 39–40  
   MR steel, 319–320  
 Furrows  
   creation, carbides and, 121  
   in raceways  
     honed, caused by carbides, 125  
     microspalls at carbides near, 123

## G

Gas shrouding  
   active, 309  
   argon, 7, 52  
   argon, Tetrene, and propane, 171  
   protective, 171  
 Glazing, carbide-related, 118, 120

## H

Hardenability  
   control in vacuum arc degassing, 339–340  
   ranges in ladle refining, 273  
 Hardness  
   effect on fatigue life, 14  
   combinations, effect on 52100 steel fatigue life, 19–20  
   controlled, discovery, 7  
   long-term hot hardness, vacuum-melted steels, 17–19

**Hardness** (*cont.*)

short-term hot hardness, through-hardened and case-hardened steels, 14–17

**Heat treatment**

compressive residual stress effects and, 140

M-50 steel, carbide changes during, 125, 130–131

**Homogeneity, sample** (*see* Sample homogeneity)**Hot-working reduction, effects on fatigue, 150–151****Hydrogen levels, argon ladle refining, 336****I****Ideal diameter, control in vacuum arc degassing, 339–340****Image analysis**

52100 steel microinclusion contents, Quantimet 800 Steelscan, 212–215

extremely low inclusion contents, 226

method (*see* Method for Determining the Inclusion Content of Steel and Other Metals by Image Analysis)

**Immersion nozzle, inclusion buildup reduction, 285, 291****Impurities**

effects on

fatigue life and rotating-bending fatigue strength, 287–290

vacuum induction melted steels, 287–290

reduction in continuous-cast high-purity steel, 287

**Inclusions** (*see also* Macroinclusions; Microinclusions)

assessment

optical methods, 388–389

problem of, 385–386

chemical analysis, 223–224

common shapes, 253

continuous-cast and ingot-cast steels, SAM ratings, 285

critical, 251

evaluation methods, 156–157

extremely low, image analysis, 226

hard metallic, MR steel, 319

MR steel, rating procedures, 323–327

nonmetallic

DIN 100 Cr 6, requirements, 299–300

critical, 95

fatigue and, 8–9, 92, 94–95

fatigue crack nucleation, 62

oxides, 62

RHP inclusion index (*see* RHP inclusion index)

origin of fracture, micrographic distribution and, 157

oxides

DIN 100 Cr 6 steel, 300–301

distribution on polished and RBF specimens, 158

field-specific measurements, 213

fine, effect on continuous-cast steel fatigue life, 357

oxygen content and, 159

phases during ladle refining, 383–384

size distributions, 162, 257

sulfides in DIN 100 Cr 6, sulfur contents and, 303

titanium nitride size distributions, titanium content and, 159

various, relative harmful effects, 156

**Inert-gas fusion technique, 191, 193****Ingot-cast steel**

macroscopic cleanliness, 363–365

microscopic cleanliness, 365–370

SAM ratings, 285

segregation in, 372

**Instrumentation, uncertainty of measurements, 193, 196****Integral wheel bearing** (*see* Wheel spindle bearing)

International Standards Organization,  
281/1-1977 (E), 102

## J

Jernkontoret method, 47, 61  
 accuracy of manual/automatic comparison chart ratings, 212–215  
 Chart II, 252  
 inclusion assessment with, 250  
 ladle refined steel quality, 268  
 limitations, 66  
 MR steel inclusions, 325–326  
 oxide microinclusion content versus oxygen content, 221  
 revised (*see* Swedish standard SS 111116)  
 sulfide microinclusion content versus sulfur content, 220  
 sulfides and oxides, 218–221  
 vacuum arc degassing and argon refining-processed steels, 344–345  
 vacuum degassing-carbon deoxidation steel quality, 268  
*J-K ratings (see Jernkontoret method)*

## L

Ladle refining, 136  
 AMS 2301 macroinclusions, 271  
 Allmanna Svenska Electuska Aktiebolaget (*see* ASEA ladle refining)  
 argon (*see* Argon ladle refining)  
 B-type alumina inclusions, 73  
 carbon steel, Swedish standard SS 111116, 254  
 chemistry control, 264–265  
 clean steel  
 E 45, *J-K* inclusion ratings, 269  
 production, 268  
 hardenability ranges, 273  
 load cells, 265  
 microcleanliness and fatigue properties, 379–381

MR process, 308–309  
 oxide inclusion phases, 383–384  
 oxygen content control, 266  
 oxygen levels, 272  
 porous plug-argon bubble, 265–266  
 reheat, 265  
 reheat capability, 265, 269  
 shrouding of ladle streams, 266  
 SAM B ratings, 270  
 SAM D ratings, 271  
 slag control, 265  
 standard deviations from melt aim, 273, 277  
 vacuum degassing, 266  
 wire feeding, 265

## Load

increasing, steady-state stability and, 111–112  
 magnitude, raceway plastic deformation and, 91  
 number of cycles, raceway plastic deformation and, 91

Load cells, ladle, 265

## Lubrication

elastohydrodynamic, 7  
 thin-film, peeling and, 118

## M

### Machinability

carbide grain size effects, 370–371  
 DIN 100 Cr 6 steel  
 requirements, 303  
 sulfur effect, 304  
 sulfur effects, 370–371

### Macroinclusions (*see also* Inclusions)

52100 steel  
 bottom-poured ingots from ASEA ladle refinement heats, 170–171  
 top-poured and bottom poured ingots from vacuum-degassed heats, 169–170  
 top-poured ingots from vacuum-degassed and non-vacuum degassed heats, 168–169

Macroinclusions (*cont.*)

## AMS 2301 ratings

process quality comparison, 271

system description, 48

quality improvement, 51–53

Magnetic particle inspection (*see* Aerospace material specifications)

## Main shear stress hypothesis, 86

## Manganese control, in vacuum arc degassing, 338

Material cleanliness (*see* Cleanliness)

## Material defects, effect on rolling-element fatigue, 9

## Measurement

instrumentation-related uncertainty, 193, 196

sample inhomogeneity and, 196

Melting processes (*see specific process*)

## Method for Determining the Inclusion Content of Steel and Other Metals by Image Analysis

area fraction, 228

as-cast specimens, 230–231

bar specimens, 240, 243

billet specimens, 231

calculated and measured  $A_A$  values, 243–245

confidence interval, 228

field measurements, 227

measurement area effect on percent relative accuracy, 245–246

percent relative accuracy, 228

sample preparation, 229–230

specimen preparation, 229–230

VIM/EBR, VIM/VAR, and VIM/ESR M-50 materials, 228–229

Microcleanliness (*see* Cleanliness)Microinclusions (*see also* Inclusions)

## assessment

manual, reproducibility, 213–215

sampling errors in, 215–223

sectioning and, 215–217

automatic ratings, limitations, 215

bottom-poured ASEA ladle-refined 52100 heats, 179–182

chemical analysis, 223–224

*J-K* rating method (*see* Jernkontoret method)

performance and, 213

quality improvement, 49–50

ratings, effects of

angle of section, 218

area investigated, 217

polishing planes, 216

SAM ratings, 47–48, 59–60

SEP-K3 ratings of different product forms, 222

through-hardened steels, analysis, 211

top- and bottom-poured ingots from vacuum-degassed 52100 heats, 177–179

top-poured ingots from vacuum-degassed and non-vacuum-degassed 52100 heats, 172–177

## Microstructure

carbides in, 114

changes

preferred orientation of texture, 106

residual stresses and, 29

retained austenite, 105–106

DIN 100 Cr 6 steel, requirements, 304–305

VIM-VAR M-50NiL and VIM-VAR M-50 steels, 39

Molybdenum contents, DIN 100 Cr 6 steel, 298

## N

## Nickel

DIN 100 Cr 6 steel, contents, 298

fracture toughness improvement, 39–40

## O

## Orientation (fibers)

effect on fatigue life, 143–144, 146

flow angle effect on fatigue life, 146



Orthogonal shear stress hypothesis,  
86  
material stressing during fatigue,  
89

## Oxides

fatigue crack nucleation and, 62  
field-specific measurements, 213  
inclusion phases during ladle  
refining, 383–384  
microinclusion content versus oxy-  
gen content, *J-K* method, 221  
oxygen content and, 366–368  
SEP-K3 ratings, different product  
forms, 222  
steels processed differently, cumula-  
tive size distribution, 257  
stereologically based image analysis,  
227–228  
as-cast specimens, 230–231  
bar specimens, 240, 243  
billet specimens, 230–231  
calculated and measured  $A_A$  val-  
ues, 243–245  
measurement area effect on per-  
cent relative accuracy, 245–  
246  
specimen preparation, 229–230  
test materials, 228–229  
type D globular  
1070 modified steel, SAM ratings,  
50  
4720 steel, RHP inclusion index,  
 $L_{10}$  fatigue life, 68  
52100 steel RHP inclusion index,  
 $L_{10}$  fatigue life, 68

## Oxygen analysis

ASTM standard analytical method,  
development, 191  
continuous-cast bearing steel, 280,  
283  
proposed method (*see* Proposed  
Method for the Determination  
of Oxygen Content in Steel and  
in Iron, Nickel and Cobalt Al-  
loys)  
round-robin testing, 198–206, 273

## Oxygen contents

1070 steel by ladle treatment and  
ingot position, 345  
52100 steel  
bottom-poured ingots, ASEA  
ladle refined, 182–184, 186  
effect of steelmaking practices, 379  
top- and bottom-poured ingots,  
RH vacuum degassed heats,  
182, 185–186  
various steels, 367  
continuous-cast bearing steel, 284–  
285  
control in vacuum arc degassing,  
342–343  
DIN 100 Cr 6, 300  
effect on oxide cleanliness, 368  
fatigue life and, 139  
fatigue properties and, 158–159  
inert-gas fusion technique, 191,  
193  
ladle refining and vacuum degassing-  
carbon deoxidation processes,  
270–273  
liquid steel during ASEA-SKF ladle  
furnace treatment, 310  
MR steel  
oxide microinclusion content and,  
*J-K* method, 221  
oxides and, 366–367  
ratings with, 163  
sample treatment effect, 194  
B-thin rating and, 326  
determination, 320–323  
distribution, 322–323  
vacuum fusion technique, 191, 193

## P

### Peeling

carbide-related, 118, 120  
distress, 34  
pattern, carbide pattern and, 120  
tapered roller bearing raceway, 35

Phase transformations, residual  
stresses and, 29

## Phosphorus contents

- DIN 100 Cr 6 steel, 299
- electric arc furnace and basic oxygen furnace processes, 297

## Plastic deformation

- elements in rolling contact, 84
- subsurface regions, 11, 91

## Point contact rolling contact test rig, 135-136

## Polishing

- planes, effect on microinclusion ratings, 216
- techniques, automatic, 214

## Porous plugs

- argon bubbling, 266
- argon injection, 265, 333

## Preferred orientation

- tensile residual stresses and, 107
- texture, 106

## Prestressing, compressive residual stress induction, 30-31

## Proposed Method for the Determination of Oxygen in Steel and in Iron, Nickel and Cobalt Alloys

- apparatus, 208-209
- calculations, 210
- calibration, 209-210
- interferences, 208
- procedure, 210
- reagents, 208
- safety precautions, 208
- sample preparation, 209
- scope, 207
- significance and use, 207
- standards, 207
- summary, 208

## Protection, argon gas, 7, 52

## Q

## Quality assurance sampling, heat control method, 185

## Quantimet 800 Steelscan, 212

## R

## Races

- controlled fiber flow, 26
- fatigue spall in, 9
- fiber flow, 27
- tangential residual stress patterns, 29

## Raceways

- butterflies, 84
- carbide-related failure
  - furrow creation, 121
  - peeling and glazing, 120
  - stress-raising effect, 121
- dark etching areas, 83-84
- forging, with controlled fiber orientation, 7
- furrows, microspalls at carbides near, 123
- honed, furrow caused by carbides, 125
- peeling and glazing, 118
- peeling on tapered roller bearings, 35
- peeling pattern, 118
- plastic deformation, 84, 91
- retained austenite decomposition, 105
- shear stresses below surface, 91
- swirl pattern caused by carbides on balls, 117
- tube bore defects in continuous-cast materials, 77
- white bands, 84

## Radial segregation, effects on fatigue, 150-151

## Reheat capability, ladle refining, 265, 269

## Remelting, successive, effect on bearing life and reliability, 10-11, 13

## Reoxidation, gas shrouding and, 171

## Reproducibility

- manual assessment of microinclusions, 213-215
- manual/automatic microinclusion ratings with SEP 1570-71, 214

- oxygen measurements on NBS-SRM 1091, 193
  - Residual stresses
    - circumferential direction versus depth beneath inner ring raceway, 106
    - compressive (*see* Compressive residual stresses)
    - effect on equivalent stresses, 98
    - microstructural changes and, 29
    - radial direction versus depth beneath raceway, 107
    - tensile, preferred orientation and, 107
  - X-ray diffraction analysis, 84
  - RHP inclusion index
    - B-type alumina, fatigue  $L_{10}$  life, 67
    - D-type globular oxides, fatigue  $L_{10}$  life, 68
    - fatigue life and, 66–69
    - SAM ratings and, 69, 72
    - technique, 66
  - RH vacuum degassing (*see* Ruhrstahl-Heraeus vacuum degassing)
  - Rod tests, MR steel, 315–316
  - Roller bearings (*see also* Ball bearings)
    - 4320 steel, retained austenite effects, 34–35
    - 8620 309-size steel
      - fatigue life distribution, 13
      - ultrasonic inspection, 14
    - ball and cylindrical, 37
    - flakings, 278
    - fracture toughness, 37, 39
    - Osako 6309
      - endurance tests, 312
      - fatigue properties, 310–311
      - subsurface changes, 105–112
      - tapered, 35, 37
  - Rolling-contact tester
    - AM-VAR, VAR-VAR, and VIM-VAR M-50 steels, 13
    - VIM-VAR M-50 and carburized VIM-VAR M-50NiL steels, 40
  - Rotating beam tests, MR steel, 317–318
  - Rotating-bending fatigue strength, effect of impurities, 287–290
  - Rotating-bending fatigue tests, 151–152
  - Roughness, surface, carbides and, 115
  - Round-robin testing for oxygen content
    - instructions, 206–207
    - procedures, 199–200
    - proposed method (*see* Proposed Method for the Determination of Oxygen in Steel and in Iron, Nickel and Cobalt Alloys)
    - results, 201–203
    - statistical analysis, 204
  - Ruhrstahl-Heraeus vacuum degassing, 166
    - macroinclusions
      - top- and bottom-poured 52100 ingots, 169–170
      - top-poured 52100 ingots, 168–169
    - microinclusions
      - top- and bottom-poured 52100 ingots, 177–179
      - top-poured 52100 ingots, 172–177
    - oxygen contents
      - ASEA ladle-refined heats, 182–184
      - bottom-poured ingots, 182–184, 186
      - top-poured ingots, 182, 185
      - vacuum-degassed and non-vacuum-degassed heats, 182
    - residual calcium and, 161
- S
- Sample homogeneity
    - measurement process and, 196
    - NBS-SRM 1090 ingot iron, 192
  - Sample preparation
    - error sources, 195
    - measuring processes and, 196
  - Sample treatment, effect on oxygen content, 194

- Sampling errors, in microinclusion assessment, 215–223
- SAM ratings, 1, 47–48, 59–60, 251
  - 1070 modified steel
    - type B aluminates, 49
    - type D globular oxides, 50
  - 1070 steels by vacuum arc degassing and argon refining processes, 346–347
  - 52100 steel
    - type B aluminates, 50, 69
    - type D globular oxides, 51
- B-type inclusions
  - alumina for carburizing steels, fatigue  $L_{10}$  life, 72
  - ladle refining and vacuum degassing-carbon deoxidation processes, 270
- continuous-cast and ingot-cast steels, 285
- D-type inclusions
  - steelmaking processes comparison, 271
  - fatigue life and, 69–72
  - limitations, 157–158
  - MR 52100 steel, 326, 329
  - practical use, 72–73
  - RHP inclusion index and, 69, 72
  - SEP 1570-71 and, 368
  - technique, 69
  - through-hardened steels, 366
- SANTRON Morphologic Inclusion Classifier, 250
  - method structure, 257
- Scanning electron microscopy
  - apex of peel, 119
  - calcium-enriched sulfide, on RBF specimen, 154
  - complex oxide inclusion on RBF specimen, 153
  - cracked/broken carbides at apex of peel, 119
  - furrow with peeling and microspall, 126
  - microspalls at carbides near furrows, 123
  - titanium nitride on RBF specimen, 154
- Sectioning, microinclusion assessment and, 215–217
- Segregation
  - center, effect on continuous-cast steel fatigue life, 285–287
  - concast blooms and, 304–305
  - ingot-cast and continuous-cast steel, 372
  - radial, effects on fatigue, 150–151
- SEP ratings (*see* Stahl-Eisen-Prüfblatt ratings)
- Shoegrinding, 5
- Shrouding
  - active gas, 309
  - argon gas, 7, 52
  - at bloom caster, 266
  - bottom-pour, 266
  - ladle streams, 266
  - top-pour, 266
- Silicon control, in vacuum arc degassing, 338
- Slag control, ladle refining, 265
- S-N* curves, 105
  - effect of
    - compressive residual stresses, 99
    - material strength, 97
    - nonmetallic inclusions, 95
    - elements in rolling contact, 91–92
- Spalling, under rolling contact stressing, 85–86
- Spalls
  - carbides near raceway furrows, 123
  - early failures, 110
  - rolling contact fatigue, 62
- Stahl-Eisen-Prüfblatt ratings
  - K3, different product forms, 222
  - MR 52100 steel, 326–327
  - SEP 1520-78, 295
  - SEP 1570, 172, 254, 258
  - SEP 1570-71, 211, 365–366
  - 52100 steel microinclusions, Quantimet 800 Steelscan, 212–215

comparison with SAM ratings, 368  
 DIN 100 Cr 6 bars and wire rods, 295  
 SEP 1580, 363, 364  
 SEP 1584, 363  
 Standard reference material 1094, 192  
 Steelmaking practices  
   B-thin ratings and RBF limits, 157  
   effect on 52100 oxygen content, 379  
   history, 5-7  
   ladle steelmaking, 73, 136  
   oxygen content monitoring, 192  
   rotating bending fatigue tests, 150-152  
   sampling errors and, 215  
   vacuum-melting techniques, 9  
 Steelmaking processes (*see also specific process*)  
   Atlas Specialty Steels, 332-335  
   Krupp Stahl AG, 296-297  
   MR, 308-309  
   Stocksbridge Engineering Steels, 375-378  
   Thyssen Stahl AG and Thyssen Edelstahlwerke AG, 360-363  
 Steels  
   18-4-1, chemical composition, 115  
   18Cr-2Ni-4WA, carburized, retained austenite and fatigue life, 33-34  
   440C  
     chemical composition, 115  
     short-term hot hardness, 14-17  
   1050, life levels, 141, 142  
   1053, life levels, 141  
   1070, 331, 375  
   1070 modified  
     AMS 2301 macroinclusion ratings, 51  
     composition, 46  
     SAM ratings, 49-50  
     wheel spindle bearing, 45  
   1552, 375  
   4150, life levels, 141  
   4320, 331  
     life levels, 141  
     retained austenite effects, 34-35

4720  
   fatigue  $L_{10}$  life and B-type alumina RHP inclusion index, 67  
   fatigue  $L_{10}$  life and D-type globular oxide RHP inclusion index, 68  
 52100, 308, 331, 375  
   AMS 2301 macroinclusion ratings, 52  
   carbide factor, 20-22  
   chemical composition, 115  
   component hardness effect on fatigue life, 19-20  
   composition, 46  
   compressive residual stress induction, 28-29  
   fatigue  $L_{10}$  life, 67-70  
   fatigue  $L_{50}$  life, 71  
   long-term hot-hardness, 17-19  
   macroinclusions, 168-171  
   microinclusions, 171-182  
   oxygen content, 182-184  
   RBF limit and  $L_{10}$  values on 6309 bearings, 151  
   SAM ratings, 50-51  
   short-term hot hardness, 14-17  
   wheel spindle bearing, 45  
   white bands, 34  
 8620  
   309-size roller bearings, fatigue life distribution, 13  
   life levels, small-size point contact specimens, 141  
   short-term hot hardness, 14-17  
 AMS 5749, retained austenite, 31-33  
 bearing  
   chemical composition, 36  
   oxygen content, round-robin testing, 198-206  
   temperature factors  $\alpha$  and exponents  $\beta$ , 17  
 carburizing  
   life levels, 141-142  
   small-size specimen life, 139  
 case-hardened, short-term hot hardness, 14-17

Steels (*cont.*)

CBS 1000, short-term hot hardness,  
14-17

CBS 600, short-term hot hardness,  
14-17

DIN 100 Cr 6, 293-306

## Halmo

carbide factor, 22

long-term hot-hardness, 17-19

short-term hot hardness, 14-17

heat-resistant, fatigue lives, 143,  
145

high-purity, fatigue life, 139

induction hardened

life levels, 141, 142

small-size specimen life, 139-140

## M-1

carbide factor, 23

long-term hot-hardness, 17-19

short-term hot hardness, 14-17

M-2, M-10, and M-42, carbide fac-  
tors, 22-23

## M-50

ausforming, 24-25

carbide composition by supplier,  
125

carbide factor, 22

carbides in, 125-129

chemical composition, 115

extremely low inclusion contents,  
stereologically based image  
analysis, 226-231, 240, 243-247

long-term hot-hardness, 17-19

MC and  $M_2C$  carbides, 115, 125

short-term hot hardness, 14-17

strain-induced precipitation, 25

VIM-VAR, 7, 11

## M-50NiL, 7

carbides, 126, 131

chemical composition, 115

Matrix II, short-term hot hardness,  
14-17

S50C, life levels, 142

S53C, life levels, 141

SCM 420, life levels, 141

SCM 440, life levels, 142

SCr 420 life levels, 141

SUJ2, 348

continuous-cast, 278

fatigue life improvement, 134

life levels, small- and large-size

point contact specimens, 139-  
141

Super Nitralloy, short-term hot  
hardness, 14-17

## T-1

carbide factor, 23

controlled fiber in races, 26

through-hardened, 360

life levels, 132, 141-142

microinclusion analysis, 211

short-term hot hardness, 14-17

small-size specimen life, 139

vacuum-melted

bearing life and, 10

cleanliness, bearing life and, 10

long-term hot-hardness, 17-19

Vasco X-2, short-term hot hardness,  
14-17

## WB-49

long-term hot hardness, 17-19

short-term hot hardness, 14-17

WD-65, short-term hot hardness,  
14-17

Step-down tests, 364-365

Stereology, Method for Determining  
the Inclusion Content of Steel  
and Other Metals by Image  
Analysis, 227-228

## Stirring

argon gas, 308-309, 336

inductive, 308

Strain-induced precipitation, M-50  
steel, 25

## Strength of materials

effect on *S-N* curve, 97

fatigue behavior and, 95, 97

## Stresses

carbide-related, 121

compressive residual (*see* Compress-  
ive residual stress)

cycling, subsurface changes and, 11

retained austenite decomposition, 106

rolling contact, 62

shear, below raceway surface, 91

Subsurface changes

- cracks
  - during second phase of fatigue, 89
  - formation, 89
  - interaction, 108
  - microstructural, 105-112

Subzero treatment, effect on fatigue life, 144, 146-147

Sulfides

- calcium-enriched, crack initiation site, 161
- DIN 100 Cr 6, sulfur contents and, 303
- microinclusion content versus sulfur content, *J-K* method, 220
- rolling contact fatigue life and, 64
- SEP-K3 ratings, different product forms, 222
- stereologically based image analysis, 227-228
  - as-cast specimens, 230-231
  - bar specimens, 240, 243
  - billet specimens, 230-231
  - calculated and measured  $A_A$  values, 243-245
  - measurement area effect on percent relative accuracy, 245-246
  - specimen preparation, 229-230
  - test materials, 228-229
- sulfur content effect, 370

Sulfur content

- control
  - in argon ladle refining, 336
  - in vacuum arc degassing, 324
- DIN 100 Cr 6, sulfide inclusions and, 303
- effect on
  - DIN 100 Cr 6 machinability, 304
  - fatigue life, 288
  - machinability, 370-371
  - sulfide cleanliness, 370

reduction in continuous-cast high-purity steel, 287

sulfide microinclusion content and, *J-K* method, 220

Swedish standard SS 111116, 250-251, 254, 327

- advantages for clean steels, 259
- distribution of B- and D-type inclusions, 254
- productivity effects, 258
- translation of ASTM E 45-85 ratings, 258

## T

Teeming, in MR processes, 309

Texture, preferred orientation, 106-107

Thyssen-blowing-metallurgy, 361

- blue fracture test results, 364
- number and type of oxide inclusions, 366
- oxide cleanliness
  - E 45-76 standard, 367
  - SAM rating, 367
  - values, 365
- oxygen contents, 367
- step-down test results, 364

Tin contents, DIN 100 Cr 6 steel, 298

Titanium-carbonitrides

- bearing steels, 301-302
- DIN 100 Cr 6, relation to titanium contents, 302
- effect on fatigue life, 68
- ladle refining, 379
- size distributions, titanium content and, 159
- titanium effect, 369

Titanium contents

- control in argon ladle refining, 343-344
- DIN 100 Cr 6, various alloying practices, 302
- effect on number of titanium-carbonitrides, 369
- fatigue life and, 160, 288-290

- Titanium contents (*cont.*)
  - fatigue properties and, 159–160
  - ratings with, 163
  - reduction in continuous-cast high-purity steel, 287
- Tramp elements, basic oxygen furnace and electric arc furnace, 297

## U

- Ultrasonic inspection
  - 8620 309-size roller bearings, 14
  - for macroscopic cleanliness, 363
  - vacuum arc remelted steels, 384–385

## V

- Vacuum arc degassing
  - argon refining procedure, 337–338
  - chemistry control, 338–339
    - major elements, 338–339
  - ladle and covers, 335
  - ladle design, 333
  - oxygen content comparison with argon refining, 343, 345
  - procedure, 336–337
  - process of, 333–334
- Vacuum arc remelting process, 187
  - inclusion elimination by, 161
  - procedure, 337–338
- Vacuum arc remelted steels
  - number and size of inclusions (SEP 1570-71), 366
  - oxide cleanliness
    - E 45-76 standard, 367
    - SAM rating, 367
    - SEP 1570-71 values, 365
  - oxygen contents, 367
  - oxygen content and fatigue properties, 159
  - production, 384
  - step-down test results, 364
  - ultrasonic testing, 384–385
- Vacuum degassing, 7
  - ladle refined steels, 266
- Vacuum degassing-carbon deoxidation, 263
  - AMS 2301 macroinclusions, 271
  - E 45-*J-K* inclusion ratings, 268
  - oxygen levels, 272
  - SAM B ratings, 270
  - SAM D ratings, 271
- Vacuum fusion technique, 191, 193
- Vacuum-induction melted, electron beam remelting steels, M-50 inclusion content, 226
- Vacuum-induction melted, electro slag remelting steels, M-50 inclusion content, 226
- Vacuum induction melted steels, fatigue life, impurities effects, 287–290
- Vacuum-induction melted, vacuum-arc remelting steels, 226
  - M-50, 7
    - comparison with AM-VAR and VAR-VAR processes, 13
    - fatigue life comparison with M-50NiL, 40
    - inclusion content, image analysis, 226
    - M-50NiL, fatigue life comparison with M-50, 40
- Vacuum-melted steels
  - cleanliness, bearing life and, 10
  - consumable-electrode, 7
  - process, 7
- VAR-VAR steels (*see* Double-vacuum arc remelted steels)
- VIM-VAR steels (*see* Vacuum-induction melted, vacuum-arc remelting steels)

## W

- Weibull distributions, fatigue lives
  - continuous-cast and ingot-cast steels, 141, 287
  - high-purity and conventional steel, 143



Weibull distributions, (*cont.*)  
 through-hardened and carburizing  
 steels, 139–141  
 Wheel spindle bearing, 44–46  
 analysis, 54  
 bearing steels used in, 45–46  
 design, 53  
 field performance analytical model,  
 56–58  
 testing, 54–56  
 White bands, 84  
 52100 steel, 34

figure, 88  
 Wire feeding, alloys, 265  
 Wire rods (DIN 100 Cr 6)  
 inclusion rating (SEP 1570-71), 295  
 microstructure (SEP 1520-78), 295  
 specifications, 294  
 Worst-field ratings (*see* Jernkontoret  
 method)

## X

X-ray diffraction, residual stresses, 84