

Subject Index

A

ABAQUS F.E., 74, 86
 Adhesion, 257
 Aluminum flake, 149
 conductivity, 153
 Anisotropy, 73, 78, 88
 Aramid sewing yarn, 285
 nonideal behavior in stitching, 295
 ASTM standards
 proposed heat flow technique, 147
 D 412-51T: 35
 D 695: 200
 D 790: 200
 D 2344: 200
 D 3039: 200
 D 3418: 200
 Autohesion, 34
 bond strength development, 34
 temperature dependence, 41

B

Backward finite difference method, 6
 Boundary-fitted coordinate systems (BFCS), 20
 Brittleness, 258

C

Carbon fiber, 50, 148, 183
 Chevron notch short bar/rod method, 236
 Coatings, on carbon fiber, 50
 distribution, 59
 evaluation, 51
 matrix polymer redistribution, 59
 powder deposition, 52
 process, 53
 thickness, 61
 uniformity, 53, 54
 Compact tension tests
 fracture toughness test, 35
 healing test, 38
 Composites—APC-1
 tension and compression strength, 96
 Composites—APC-2/AS-4, carbon/polyetheretherketone (PEEK) laminates
 brittle fracture, 273

 compression test, 205
 crack instability, 273
 creep, 201, 206
 critical stress intensity factor, 269
 cyclic loading, 208
 deformation, 270
 delamination crack growth, 266
 delamination growth, 264
 ductility, 270
 elastic properties, 202
 fatigue crack growth, 267
 fatigue tests, 201, 208
 fiber deformation, lamellae, 272
 fiber fracture, 205
 fracture morphology, 270
 instrumented falling weight impact test, 205
 interlaminar fracture toughness, 203
 Mode I delamination toughness, 265
 Paris law, 267
 short-beam test failure, 202
 slow crack growth, 266
 stiffness and strength properties, 200, 202
 stress, process zone, 270
 temperature profiles, 268
 thermal expansion coefficients, 203
 toughness tests, 200, 203
 Composites—APC-2, carbon/polyetheretherketone (PEEK) laminates
 dynamic viscosity, 8
 one-dimensional heat flow, 5
 physical properties, 7
 process model, 5
 temperature profiles, 9
 thermal diffusivity, 7
 thermal properties, 7
 Composites—APC-2, graphite/polyetheretherketone (PEEK) laminates, 91
 bonding characteristics, 101
 compression tests, 92, 98
 interlaminar matrix deformation, 102
 intralaminar fracture, 106
 intralaminar deformation, 106
 intralaminar separation, 99
 material properties, 93
 notch strength, 94

- strength prediction, three parameter method, 95
- temperature effects on strength, 92
- Composites—AS-4-graphite/J1 polymer, 279
 - crack growth, 283
 - critical strain energy release rate, 280, 286
 - delamination resistance, 290
 - effects of yarns slacks on, 298
 - fiber damage, 298
 - geometric stitching parameters, 293
 - strengthening effects, 298
 - interlaminar crack growth, 290
 - load displacement characteristics, 295
 - Mode I fatigue crack propagation, 280, 287
 - Mode I interlaminar failure, 280
 - Mode I interlaminar fracture, 287
 - plastic deformation processes, 279
 - residual strength, 293
 - effects of yarn stiffness on, 298
 - stiffness, 285
 - stitching, 280, 285
 - stress intensity factor, 285
 - yarn behavior, 295
 - Composites—AS4/polycarbonate laminates, 252
 - adhesion, 257
 - double cantilever beam test, 253
 - edge delamination, 253
 - interlaminar toughness, 260
 - matrix deformation, 257
 - modulus, 255
 - ply properties, 255
 - stiffness, 255
 - thermal expansion, linear coefficient of, 257
 - Composites—AS4/polyetheretherketone (PEEK) laminates, 133
 - compressive strength, 137
 - damage region, 141
 - damage tolerance, 133, 145
 - delamination, 141
 - failure mode, 144
 - fatigue lives, 134, 142
 - fatigue loading, 136
 - fatigue tests, 136
 - fiber fracture, 142
 - monotonic mechanical tests, 136
 - radiographs during cyclic loading, 141
 - residual strength, 139
 - residual tensile strength, 143
 - specimen stiffness, 137
 - stiffness ratio, 138
 - tensile strength, 137
 - Composites—AS4/polyimidesulfone blend laminates, 252
 - adhesion, 257
 - double cantilever beam test, 253
 - edge delamination, 253, 261
 - fiber bridging, 261
 - interlaminar toughness, 262
 - modulus, 255
 - ply properties, 255
 - stiffness, 255
 - thermal expansion, linear coefficient of, 257
 - Composites—AS4/TPI blend laminates, 252
 - adhesion, 257
 - double cantilever beam test, 253
 - edge delamination, 253, 261
 - fiber bridging, 261
 - interlaminar toughness, 262
 - modulus, 255
 - ply properties, 255
 - stiffness, 255
 - thermal expansion, linear coefficient of, 257
 - Composites—BMI toughened laminate, 113
 - fatigue behavior, 113
 - fatigue life, 115
 - in-plane shear modulus, 114
 - stress-strain, 114
 - Composites—Graphite-epoxy
 - fatigue life, load frequency effect on, 113
 - fatigue tests, 114
 - finite element pultrusion model application, 68
 - in-plane shear modulus, 114
 - laminates, 68, 113, 245
 - temperature effect on strength, 93
 - tension and compression strength, 97
 - toughness, 133
 - Composites—Graphite/polysulfone, 3
 - critical strain energy release rate, 39
 - factors affecting, 47
 - double cantilever beam fracture, 37
 - healing function, 45
 - healing test, 38
 - refracture toughness, 38
 - Composites—IM6/PEEK, graphite/polyetheretherketone laminates, 231
 - crack tip stress, 234
 - critical strain energy release rate, 239
 - fiber bridging, 240
 - fracture mechanisms, 240
 - fracture surface morphology, 241
 - fracture toughness, 237, 239
 - chevron notch short bar/rod method, 236
 - interlaminar fracture, 239
 - laminate construction, 233
 - Mode I delamination fracture toughness, 232

- moisture absorption, 236, 238
- short bar hybrid test specimen, 231
- stress distribution, 236
- Composites—IMP6/APC-2 laminates, 113
 - crack propagation, 124
 - failure modes, 127
 - fatigue life, 119
 - fatigue life prediction, 126
 - fatigue tests, 115, 121, 128
 - frequency-dependent fatigue model, 126
 - load-frequency effect on fatigue, 113
 - material properties, 115
 - shear modulus, 114
 - stiffness variation during cyclic loading, 116
 - temperature increase summary, 130
 - tension-compression fatigue tests, 117
 - test temperature increase history, 115
- Composites—Polyamide-imide (PAI), carbon fiber reinforced, 184
 - creep tests, 185
 - fatigue tests, 185
 - fiber orientation distribution, 186
 - orientation angles, 187
 - fracture morphology, 183, 192, 196
 - modulus, 185
 - spatial fiber distribution, 183
 - ultimate tensile strength, 185
- Composites—Polyetheretherketone (PEEK), carbon fiber reinforced
 - creep tests, 185
 - fatigue tests, 185
 - fiber orientation distribution, 186
 - orientation angles, 187
 - fracture morphology, 183, 192
 - modulus, 185
 - spatial fiber distribution, 183
 - ultimate tensile strength, 185
- Composites—Polyphenylene sulfide (PPS), carbon fiber reinforced, 154
 - constant deformation, 155
 - creep tests, 166, 176, 185
 - crystallinity, 158, 166
 - dynamic mechanical tests, 155, 158
 - fatigue tests, 185
 - fiber orientation distribution, 186
 - orientation angles, 187
 - flexure tests, 155, 166
 - fracture morphology, 183, 192
 - frequency sweeps, 166
 - modulus, 185
 - relaxation tests, 166, 176
 - spatial fiber distribution, 183
 - stiffness, 176
 - temperature scans, 158
 - thermal response, 155
 - torsional tests, 155
 - ultimate tensile strength, 185
- Composites—Polyphenylene sulfide (PPS), glass fiber reinforced, 213
 - crystallinity, 214
 - debonding, 227
 - glass transition temperature, 214
 - microstructures, 226
 - modulus, elastic, 222
 - moisture absorption, 217
 - moisture effects on samples, 226
 - moisture resistance, 213
 - molding, prepregs, 217
 - molding, stampable sheets, 217
 - stress-strain curves, 219
 - tensile strength, 219, 225
- Composites—Ryton, carbon fabric reinforced, 155
 - constant deformation, 155, 175
 - creep tests, 166, 175
 - crystallinity, 158, 176
 - dynamic mechanical tests, 158
 - relaxation tests, 166, 175
 - stiffness, 176
 - temperature scans, 158
- Composites—XAS/polycarbonate laminates, 252
 - adhesion, 257
 - double cantilever beam test, 253
 - edge delamination, 253
 - interlaminar toughness, 260
 - matrix brittleness, 258
 - matrix deformation, 257
 - modulus, 255
 - ply properties, 255
 - stiffness, 255
 - thermal expansion, linear coefficient of, 257
- Compression molding, 15, 26
- Compression tests, 92, 98, 205
- Compressive strength, 137
 - prediction, 95
- Computational domain equations, 22
- Computational fluid dynamics, 14
- Conduction-convection matrix, 66
- Conductivity, composite packaging for electronics, 146
- Constant loading boundary condition, 18
- Contact point relocation method, 25
- Crack growth rate, 266, 283
- Crack propagation, 75, 124, 279, 287
- Crack tip stress, 75, 86, 234
- Creep tests, 166, 176, 185, 201, 206
- Critical strain energy release rate, 45, 239, 251, 277, 280
 - factors affecting, 47

Crystallinity, 158, 166, 176, 214
Cyclic loading, 140, 208

D

Damage region, 141
Damage tolerance, 33, 133, 145
Darcy's laws, 17
Debonding due to moisture, 227
Deformation
 constant, 155
 interlaminar matrix, 102
 intralaminar, 106
 laminate, 117
 matrix, 257
 viscoelastic, 34
Delamination, 141, 264
 crack growth, 266
 edge, 253, 258, 261
 fracture toughness, 73
 resistance, 279, 290
 effects of yarn slacks on, 298
Density, 7
Diffusion, 35
 modeling, 41
 moisture, 236
 self-diffusion coefficient, 42
Dirichlet boundary conditions, 21
Double cantilever beam (DCB) composite
 test, 37, 45, 251
 fracture toughness parameters, 89
 specimens, 76
Dynamic viscosity, 8
 temperature profiles, 9

E

Eastobond FA252, 51, 54
Electrical conductivity, 151
Electrical resistance heating and powder deposition apparatus, 52
Electronics packaging, 146
Electrostatic powder deposition, 51

F

Failure mode, 127, 144
Fatigue
 behavior, 113
 frequency dependent model, 126
 life, 115, 134
 load frequency effect on fatigue life, 113
 life prediction, 126
 tests, 114, 121, 136, 185, 201, 208
Fiber
 bridging, 45, 83, 240, 258, 261
 damage, 298
 deformation, lamellae, 272
 deposition process, 52
 distribution, 183, 186

 filler, 146
 matrix debonding, 258
Fibrous preform, 26
Filler, fiber, 146
Finite difference techniques, 6
Finite element method, 63
 conduction-convection matrix, 66
 model, 74
 model results, 76
 weighted residuals, 65
Flexure tests, 155, 166
Fracture, fiber, 142, 205
Fracture mechanisms, 240
Fracture properties
 sensitivity to flaw microstructure, 86
Fracture morphology, 183, 192, 196, 270
 surface, 192, 241
Fracture toughness, 45, 91, 133, 237
 chevron notch short bar/rod method, 236
 compact tension test, 35, 37
 double cantilever beam test, 36
 fracture toughness parameters, 89
 interlaminar, 46, 203, 239, 251, 279
 moisture effects on, 231
 specimens, 76
Frequency-dependent fatigue model, 126
Frequency sweeps, 166

G

Galerkin method, 65
Geometrical transformation coefficients, 23
Geometric stitching parameters, 293
 strengthening effects, 298
Glass transition
 temperature, 214
 zone, 154
Graphite-polysulfone composites, 3

H

Healing
 function, 45
 isothermal model, 43
 lower toughness, 47
 nonisothermal, 41
 polymer flow during, 47
 rehealing, 46
 tests, 35, 40
Heat capacity, 7
Heat flow technique, 147
Heat transfer
 coefficient, 41
 model, one-dimensional, 5, 62, 64
High temperature testing, 91

I

Imposed orthogonality method, 25
Impregnation configurations, 27

Impregnation front, resin, 19
 movement, 24
 Impregnation processes
 resin, 14
 thermoplastic on carbon, 50
 Injection molding, 183
 Instrumented falling weight test, 205
 Interfacial tests, 35
 Interlaminar crack growth, 290
 Interlaminar fracture, 46, 203, 239, 251
 Interlaminar matrix deformation, 102
 Intralaminar deformation, 106
 Intralaminar fracture, 106, 203
 Intralaminar separation, 99
 Interlaminar toughness, 260
 Isothermal healing model, 46
 Isotropic model, 75
 stress distribution, 77

L

Laminates (*see also* Composites—types)
 heat transfer, 6
 system comparison, 97
 temperature effects on strength of, 92
 LARC-TPI (Langley Research Center—Thermoplastic Polyimide), 51
 powder, 54
 Lewis-Nielson semitheoretical prediction
 methods, 146
 Line zone model for failure process, 268
 Load displacement characteristics, 295
 Load-frequency effect on fatigue, 113

M

Matrix brittleness, 258
 Mechanical tests, dynamic, 155, 158
 Mesh generator, finite quadtree, 75
 Mode I delamination fracture toughness, 232, 265
 temperature effects on, 265
 Mode I delamination growth, 264
 Mode I failure, 73, 280
 anisotropy, 78, 88
 characterization, 82
 displacement analysis, 75
 fiber bridging, 83, 89
 isotropic model, 75
 orthotropic analysis, 78
 stress distribution, 74
 Mode I fatigue crack propagation, 280, 287
 Mode I fracture, 285
 Mode I interlaminar fracture, 231, 280, 287
 Mode I strain energy release, 239
 Mode II failure, 73
 anisotropy, 85, 88

characterization, 79
 crack length effect on shear stress distribution, 81
 crack propagation, 85
 isotropic analysis, 79
 orthotropic analysis, 79
 stress distribution, 74, 79
 Modeling
 autohesion, 34
 delamination resistance, 290
 diffusion, 41
 finite element, 74
 finite element results, 67
 frequency-dependent fatigue, 126
 heat transfer, 5, 62
 interlaminar crack growth, 290
 isotropic, 75
 Lewis and Nielson, 146
 line zone for failure process, 268
 nonisothermal healing, 44
 numerical grid generation, 14
 one-dimensional heat flow, 5
 one-dimensional heat transfer, 62
 orthotropic, 74
 porous medium flow, 16
 process, 5
 pultrusion process, 62
 resin flow, 16
 thermal conductivity, 147
 viscoelastic constitutive, 8
 Modulus, 185, 255
 elastic, 222
 Moisture absorption, 217, 232, 236, 238
 Moisture resistance, 213
 Mold die movement, 26
 Monotonic mechanical tests, 136

N

Neat resin/fibrous preform interface, 18
 Negligible internal resistance (NIR) heat
 transfer solution, 40
 Nonisothermal healing model, 44
 Notch strength, 94
 Numerical grid generation, 14
 Nylon 6/6, 146

O

Orthotropic modeling, 74
 stress distribution, 77

P

Paris law, 267
 PET, glass-fiber reinforced, 184
 Plastic deformation processes, 279

Ply properties, 255
 Polyester coated carbon fiber, 53
 Polymer distribution in composites, 55
 Polypropylene, glass fiber reinforced, 184
 Porous medium flow, 16
 Powder deposition on carbon fibers, 51
 coating uniformity, 53
 continuous process, 52
 distribution, 59
 evaluation, 53
 Process simulation (*see* Modeling)
 Pultrusion, 62
 heat transfer model, 64
 rate, 64

R

Relaxation tests, 166, 176
 Residual strength, 139, 293
 Residual tensile strength, 143
 Resin film stacking, 15, 26
 Resin flow, 14
 Resin impregnation, 14
 boundary fitted coordinate systems, 20
 fibrous preform interface, 18
 fibrous preform interface front, 19, 24
 Resin interface, neat and impregnated, 18
 Resin movement, 24
 Resin, neat
 autohesive bond strength development, 35
 temporal distribution of depth, 27
 Resin, PEEK, dynamic viscosity, 13
 Resin, polysulfone, 33
 autohesive bond strength development, 37
 compact tension test, 37
 critical strain energy release rate, 39
 healing test, 38
 refracture toughness, 38
 Resin systems, 50
 Resin, thermosetting, 50, 62
 pultrusion process, 63
 Resin toughness, 251
 Resin transfer molding, 15

S

Shear modulus, in-plane, 114
 Short bar hybrid test specimen, 231, 233
 Short-beam test failure, 202
 Slow crack growth, 267
 Stiffness and strength properties, 133, 176,
 200, 255, 285
 moisture effects on, 213, 232
 Stiffness ratio, 138
 Stiffness variation during cyclic loading, 116
 Stitching, 280, 285
 Strain energy, 84
 Strain energy release rate, 45, 74, 239, 251,
 280

 factors affecting, 47
 Strength development, interply, 36
 Strength prediction method, 95
 Stress distribution, 73, 236
 Stress intensity factor, 269, 285
 Stress, process zone, 270
 Stress-strain curves, 114, 219

T

Tack measurements, 35
 Temperature profiles, 268
 Tensile strength, 137, 219, 225
 residual, 143
 ultimate, 185
 Tension-compression fatigue tests, 117
 Tension/compression loading, 133
 Tension strength prediction, 95
 Thermal conductivity, 7, 146
 model, 147
 Thermal diffusivity, 7
 Thermal expansion, 189, 203, 257
 Thermal profiles, 5
 Thermal properties, 7
 Thermal response, 155
 Thermodynamic pressure, 19
 Thermoplastic coating
 carbon fibers, 51
 distribution, 59
 evaluation, 51
 melting, 51
 powder deposition, 52
 process, 53
 uniformity, 53, 54
 Thermosetting resins
 pultrusion, 62
 systems, 50
 Three dimensional fiber structures, 279
 Three parameter strength prediction method,
 95
 Torsional tests, 155
 Toughness rankings, 262
 Toughness tests, 200, 203
 Tungsten powder, 149
 Two-dimensional Darcy flow, 14

V

Viscoelastic constitutive model, 86
 Viscosity, dynamic, 8
 temperature profiles, 9

W

Weighted residuals method, 65
 Wetting, 35
 WLF temperature dependence, 42