

# Subject Index

## A

AASHTO Guide for Design of Pavement Structures, 74

AASHTO Interim Guide for Design of Pavement Structures, 21, 30–31

AASHTO standards

M283, 122

T48, 107

T49, 107

T51, 107

T53, 107

T96, 7, 10

T104, 6

T112, 7

T165, 124

T176, 7

T179, 107

T180, 66–67, 69

T201, 107

T209, 124

T210, 107

T215-70, 70

T228, 107

AC (*see* Asphalt concrete)

Additives

antistrip, for moisture damage reduction, 101

various, tensile strength ratio and, 101

Adhesion failure, 96–97

Admixtures, low-quality aggregates, 6

Age effects

AC mixtures, 49

moisture damage, 97

Aggregates

fine sand, in asphalt mixtures, 44

low-quality (*see* Low-quality aggregates)

properties, critical bitumen content and, 50–61

quality, 5

Saudi Arabia

location, 7–9

physical and mechanical properties, 9–10

quality specification, 6–7

size effects on asphalt concrete, 45–47

source effects

ELSYM5 analysis, 139–142

fatigue, 128–130, 137

mix design, 126–128, 132–134

permanent deformation, 130–132, 137–139

resilient modulus, 128–130, 134–136

split tension, 132, 139

type effects

AC mixtures, 49

moisture damage, 97

permanent deformation, 165–170

Air voids

effect on

tensile strength, 91

tensile strength ratio, 92

versus tensile strength

Lottman procedure, 80

modified Lottman procedure, 81

moisture sensitivity study, 83–88, 91

American Association of State Highway and Transportation Officials (*see* AASHTO standards)

Antistrip

additives, for moisture damage reduction, 101

rating, with boiling-soak test, 92–93

Asphalt concrete

characterization, predictive equations, 159–162

critical bitumen content, 50–61

permanent deformation data, 160

predicted and measured permanent strain versus loading cycles, 158

Asphalt content, effect on permanent deformation parameters, 159–164

Asphaltic mixtures

characterization, 11

critical bitumen content, 50–61

effect of

aging and aggregate type, 49

filler amount, 39

- Asphaltic mixtures, effect of (*cont*)
  - filler type, 35–39
  - maximum aggregate size, 45–47
  - percent fracture and gradation, 120, 126–134
  - evaluation
    - with gyratory testing machine, 47–48
    - with repeated load diametral test device, 124–127
  - fine sand aggregates in, 44
  - mix design, effect on moisture damage, 97–98
  - modulus of resistance, 13–14
- Asphaltic pavements, moisture damage, 97–98
  - evaluation, 98–99
  - reduction, 98–99
- ASTM standards
  - C 127-84, 13
  - D 5, 107
  - D 36, 107
  - D 76, 107
  - D 92, 107
  - D 113, 107
  - D 448-80, 20
  - D 1075, 98
  - D 1557-78, 20, 23
  - D 1664, 145
  - D 1754, 107
  - D 1856-79, 23
  - D 2170, 107
  - D 2172-79, 23
  - D 3625, 98

## B

- Base course
  - granular, predictive equations for characterization, 162–163
  - predicted and measured permanent strain versus loading cycles, 157
- Benkelman beam tests, thin-surfaced crushed-stone base pavement, 25–27

- Bitumen content, critical, 50–61
- Blending, low-quality aggregates, 5
- Boiling water test
  - moisture damage, 98
  - moisture susceptibility, 93

## C

- Cement-coating method, low-quality aggregates, 6, 11–13

- Coating processes, low-quality aggregates, 6
- Cohesion failure, 97
- Compaction
  - critical bitumen content and, 50–61
  - filler effects, 36, 43–44
  - kneading, by gyratory testing machine, 60–61
- Comprehensive stress, coated/uncoated LQA asphaltic mixtures, 12
- Construction procedures, to reduce moisture damage, 101
- Creep effects, on elastic modulus values for thin-surfaced crushed-stone base pavements, 32
- Critical bitumen content, asphalt concrete, 50–61
- Critical void content, asphalt concrete, 50–61
- Crushed-stone base pavements, thin-surfaced, 19–20
  - backcalculated moduli from FWD deflection basic data, 27–28
  - base characteristics, 23, 69
  - base course layer coefficients, 30–31
  - Benkelman beam tests, 25–27
  - bituminous surface treatment, 23
  - construction, 20, 66–67
  - elastic moduli back-analysis, 27
  - elastic modulus, 31–32
  - equivalent axle loads, 31, 73–74
  - falling weight deflectometer tests, 27–28
  - permeability, 70
  - rut depths, 21–22
  - rutting history, 70–73
  - static plate load tests, 23–25
  - strength variations, 32
  - subgrade characteristics, 22–23, 67–69
  - surface strain tests, 25–27
  - surface treatment, 69–70
  - traffic loadings, 21

## D

- Data analysis, moisture susceptibility tests, 88–94
- Debonding
  - classification of seal coats, 150–153
  - seal coat debonding test, 145–149
- Deleterious aggregates, definition, 5
- Density effects
  - on asphalt concrete permanent deformation, 159–162
  - on granular base material permanent deformation, 162–163

- on permanent deformation parameters, 159
- on subgrade soil permanent deformation, 163–164

## E

- Elastic Layered System computer program (*see* ELSYM5)
- Elastic modulus (*see* Modulus of elasticity)
- ELSYM5, fracture and fines contents effects on pavement performance, 139–142
- Emulsion-based seal coats
  - seal coat debonding test, 145–149
  - vulnerability to moisture damage, classification, 150–153
- Equivalent axle loads, thin-surfaced crushed-stone base pavements, 31, 73–74

## F

- Falling weight deflectometer
  - backcalculated moduli from deflection basin data, 28–32
  - tests for structural strength, 27–28
- Fatigue, percent fracture and gradation effects, 128–130, 137
- Field compaction, filler effects, 43–44
- Field construction procedures, moisture damage reduction, 101
- Field evaluations
  - bituminous mixes at hot-mix asphalt plants, 48–50
  - thin-surfaced crushed-stone base pavement
    - Benkelman beam deflections, 25–27
    - falling weight deflectometer tests, 27–29
    - static plate load tests, 23–25
    - surface strain measurements, 25–27
- Field screening tests, for moisture damage, 100–101
- Fillers
  - amount, effect on asphalt concrete quality, 39
  - content
    - versus indirect tensile strength, 38
    - versus mix density, 37
    - versus mix voids in mineral aggregate, 37
    - versus stability, fig. 38
  - effect on
    - asphalt concrete, 35–39
    - field compaction, 43–44

- Fines content effects, on AC mixture performance
  - ELSYM5 analysis, 139–142
  - fatigue, 128–130, 137
  - mix design, 126–128, 132–134
  - permanent deformation, 130–132, 137–139
  - resilient modulus, 128–130, 134–136
  - split tension, 132, 139
- Flexible pavements, permanent deformation
  - characterization, 155–157
  - effects of aggregate characteristics, 164–170
  - prediction, 157–164
- Fracture level effects, on AC mixture performance
  - ELSYM5 analysis, 139–142
  - fatigue, 128–130, 137
  - mix design, 126–128, 132–134
  - permanent deformation, 130–132, 137–139
  - resilient modulus, 128–130, 134–136
  - split tension, 132, 139
- Freeze-thaw pedestal test, 99
- Freezing effects, on tensile strength ratio, 93–94
- FWD (*see* Falling weight deflectometer)

## G

- Gradation effects, on AC mixture performance, 50–61
  - ELSYM5 analysis, 139–142
  - fatigue, 128–130, 137
  - mix design, 126–128, 132–134
  - permanent deformation, 130–132, 137–139
  - resilient modulus, 128–130, 134–136
  - split tension, 132, 139
- Granular base material, predictive equations for characterization, 162–163
- Gyratory elasto-plastic index, 48
- Gyratory testing machine
  - evaluation of bituminous mixes at hot-mix asphalt plants, 48–50
  - kneading compaction, 60–61
  - procedure for evaluating AC mixtures, 47–48

## H

- Hot-mix asphalt
  - antistrip rating with boiling-soak test, 92–93

**Hot-mix asphalt (*cont*)**

curve fitting and averaging of tensile strength data, 90

effect of

air voids on tensile strength, 91–92  
freezing cycle on tensile strength ratios, 93–94

Lottman and modified Lottman procedures, 88–94

sample preparation, 81–82

tensile strength

versus air voids, 83–88, 91  
regression models, 89  
two-tier specification, 94  
versus saturation, 93

Hveem stability test, property curves for SEA mixtures, 115–116

**I****ILLI-PAVE program**

aggregate type effects on permanent deformation, 164–170

elastic moduli of thin-surfaced crushed-stone base pavements, 32

Immersion-compression test, 98

modified, 98–99

Impregnation, low-quality aggregates, 5

Impulse stiffness modulus, thin-surfaced crushed-stone base pavements, 28–29

Index of retained strength, coated/uncoated LQA asphaltic mixtures, 12

Indirect tensile strength, coated/uncoated LQA asphaltic mixtures, 12

**L**

Loading cycles, permanent strain and, 155–157

Lottman procedure (hot-mix asphalt), 99  
antistrip rating with boiling-soak test, 92–93

data analysis, 88–94

multiple freeze-thaw cycles, 99

sample preparation, 81–82

tensile strength

versus air voids, 83–88, 91  
data, curve fitting and averaging, 90  
effect of air voids, 91–92

regression models, 89

two-tier specification, 94

versus saturation, 93–94

tensile strength ratios, freezing-cycle effects, 93

**Low-quality aggregates**

beneficiation methods, 5–6

characterization, 11

coating method, 11–13

physical and mechanical properties, 9–10

test results on, 13–17

LQA (*see* Low-quality aggregates)

**M**

Marshall design criteria, for low-, medium-, and high-quality aggregates, 11, 13

Marshall stability test

crushed limestone mixtures, 112

property curves for SEA mixtures, 113–115

Maximum aggregate size, effect on asphalt concrete, 45–47

Mechanical processing, low-quality aggregates, 5

Mix design

effect on moisture damage, 97–98

Marshall and Hveem methods, 109–112

percent fracture and gradation effects on AC performance, 126–128, 132–134

resistance to moisture damage, 99–100

sulfur-extended asphalt, 109, 112–116

Modified Lottman procedure (hot-mix asphalt), 88–94

antistrip rating with boiling-soak test, 92–93

sample preparation, 81–82

tensile strength

data, curve fitting and averaging, 90

effect of air voids, 91–92

regression models, 89

two-tier specification, 94

versus air voids, 83–88, 91

versus saturation, 93

tensile strength ratios, freezing-cycle effects, 93–94

Modulus of elasticity

back-analysis from Benkelman beam tests, 27

backcalculated from falling weight deflection basin data, 28–31

base and subgrade moduli, 26

- ILLI-PAVE method, 32
- thin-surfaced crushed-stone base pavements, 31–32
- Modulus of resilience
  - coated/uncoated LQA asphaltic mixtures, 12
  - moisture damage, 99
  - percent fracture and gradation effects, 128–130, 134–136
  - temperature effects, 13–15
  - thin-surfaced crushed-stone base pavement subgrade, 22–23
- Moisture content effects
  - asphalt concrete permanent deformation, 159–162
  - granular base material permanent deformation, 162–163
  - permanent deformation parameters, 159
  - subgrade soil permanent deformation, 163–164
- Moisture damage
  - adhesion failure, 96–97
  - cohesion failure, 97
  - definition, 96–97
  - evaluation methods, 98–99
  - factors affecting, 97–98
  - prediction, 100
  - reduction methods, 99–101
  - seal coat debonding test, 145–149
  - vulnerability to, seal coat classification, 150–153
- Moisture susceptibility tests
  - Lottman procedure (*see* Lottman procedure)
  - modified Lottman procedure (*see* Modified Lottman procedure)

## O

- Overasphalting, rutting caused by, 112

## P

- Pavement condition ratings, Dhahran-Abqaiq Road, 15–16
- Pavements
  - asphaltic, moisture damage, 97–98
  - evaluation, 98–99
  - reduction methods, 99–101
  - flexible, permanent deformation
    - characterization, 155–157
    - effects of aggregate characteristics, 164–170
    - prediction, 157–164
  - thin asphalt surfaces over aggregate base course, 64–66
  - aggregate base course characteristics, 69
  - construction, 66–67
  - equivalent axle loads, 73–74
  - permeability, 70
  - rutting history, 70–73
  - subgrade characteristics, 67–69
  - surface characteristics, 69–70
  - thin-surfaced crushed-stone base
    - base characteristics, 23
    - base course layer coefficients, 30–31
    - Benkelman beam test, 25–27
    - bituminous surface treatment, 23
    - construction, 20
    - creep effects, 32
    - elastic modulus, 31–32
    - equivalent axle loads, 31
    - falling weight deflectometer tests, 27–30
    - static plate load tests, 23–25
    - strength variation, 32
    - subgrade characteristics, 22–23
    - surface strain measurements, 25–27
    - traffic loadings, 21
- Permanent deformation (*see also* Rutting)
  - characterization, 155–157
  - effects of
    - aggregate characteristics, 165–170
    - percent fracture and gradation, 130–132, 137–139
  - loading cycles and, 155–157
  - prediction, 157–159
  - predictive equations, 159
    - asphalt concrete, 159–162
    - granular base material, 162–163
    - subgrade soil, 163–164
- Permanent strain
  - loading cycles, 155
  - predicted and measured versus loading cycles
    - for asphalt concrete, 158
    - for base course materials, 157
    - for subgrade soil, 156
- Plate load tests, thin-surfaced crushed-stone base pavements, 23–25
- Prediction
  - moisture damage, 100
  - permanent deformation, 157–159
  - equations for material constants, 159–164

## Q

Quality control, rutting caused by poor, 104

## R

Regression analysis, equations for permanent deformation prediction, 159–164, 170

Regression models, tensile strength data, 89

Rehabilitation, rutted pavements in Saudi Arabia, 116–117

Resilient modulus (*see* Modulus of resilience)

Retained strength index, coated/uncoated LQA asphaltic mixtures, 12

Rutting (*see also* Permanent deformation)  
Marshall and Hveem mix-design methods, 109

maximum aggregate size effects, 45

overasphalting and, 112

poor field quality control and, 104

rehabilitation plans in Saudi Arabia, 116–117

roads of LQA asphaltic mixtures, 15–16

sulfur-extended asphalt mixtures, 109

Hveem test property curves, 115–116

Marshall test property curves, 113–115

thin-surfaced crushed-stone base pavement, 21–22

VESYS III program predictions, 15–17

## S

Sample preparation, for moisture susceptibility tests, 81–82, 88–91

Saturation  
tensile strength, 93

Screening tests, for moisture damage, 100–101

SEA (*see* Sulfur-extended-asphalt mixtures)

Seal Coat Debonding Test  
apparatus, 145–146

classification of seal coats, 150–153

materials, 146–147

procedure, 147–149

Skid resistance, maximum aggregate size effects, 45

Slurry seals, moisture damage and, 98

Split tension, percent fracture and gradation effects, 132, 139

## Stability

filler content, 38

maximum aggregate size effects, 45

Strength, *in situ* evaluation

Benkelman beam tests, 25–27

elastic moduli analyses, 27–30

static plate load tests, 23–25

surface strain measurements, 25–27

variations, 32

## Stress effects

asphalt concrete permanent deformation, 159–162

granular base material permanent deformation, 162–163

on permanent deformation parameters, 159

subgrade soil permanent deformation, 163–164

## Stripping

classification of seal coats, 150–153

potential, coated/uncoated LQA asphaltic mixtures, 12

seal coat debonding test, 149–151

## Subgrade soils

characterization, predictive equations, 163–164

predicted and measured permanent strain versus loading cycles, 156

thin-surfaced crushed-stone base pavement, 22–23

## Sulfur-extended-asphalt mixtures, 109–116

Hveem test property curves

cured for 2 days, 115

cured for 14 days, 116

Marshall test property curves

cured for 2 days, 113

cured for 14 days, 114

penetration values against time for binder, 112

Surface strain, thin-surfaced crushed-stone base pavement, 25–27

## Surface treatments

bituminous, thin-surfaced crushed-stone base pavement, 23

effect on moisture damage, 98

## T

## Temperature effects

asphalt concrete permanent deformation, 159–162

granular base material permanent deformation, 162–163

modulus of resilience, 13–15

- on permanent deformation parameters, 159
- subgrade soil permanent deformation, 163–164
- Tensile strength
  - air voids
    - Lottman procedure, 80
    - modified Lottman procedure, 81
    - moisture sensitivity study, 83–88, 91
  - antistrip rating with boil-soak test, 92–93
- data
  - curve fitting and averaging, 90
  - regression models, 89
- effect of air voids, 91
- filler content, 38
- indirect, coated/uncoated LQA asphaltic mixtures, 12

- minimum, specification, 94
- percent saturation, 93
- Tensile strength ratio, 79
  - effect of
    - air voids, 92
    - freezing, 93–94
    - various additives, 101
  - minimum, specification, 94
- Traffic volume effects
  - moisture damage, 97
  - rutting, 103–104
- Tunnichliff–Root procedure (*see* Modified Lottman procedure)

## V

- VESYS III program, rutting prediction, 15–17