

Index

A

abrasion resistance, 17, 18
adhesive, 8
aftermarket insert, 2, 21, 35
ankle/leg height, 4
aramid, 17
articulated strut tribometer, 51–52
ASTM F1116, 38
ASTM F1117, 38, 40
ASTM F1646, 43
ASTM F1897, 33
ASTM F2412, 33, 34, 35, 36, 37, 40
ASTM F2413, 20, 21, 33, 39, 40
ASTM F2508, 54
ASTM F2892, 33, 39, 37, 40
ASTM F2913, 56
ASTM International Committee F13
 Pedestrian/Walkway Safety and
 Footwear, 58
available friction, 45–46

B

blown soling, 12
bond welt construction, 9
bootie construction. *See* membrane
 waterproofing
BOT 3000, 49 (figure)
breathability, 16–17
Brungraber MK II, 52 (figure)
Brungraber MK III, 52 (figure)

C

Canadian Standards Association
 (CSA), 56

cement construction, 6 (figure), 9
 (figure)
chemical resistance, 28
chemically treated natural fibers, 17
close edge construction, 9
closure systems, 17–18
coefficient of friction (COF), 44,
 45–47, 54–55, 57
 safe threshold COF number,
 57–58
 utilized (uCOF), 46–47
cold weather protection, 20
compression molded rubber, 13
compression test, 34 (figure)
conductive materials, 37, 39
conductive protective footwear, 36
 (figure)
construction, 4–5
 direct-attach, 10 (figure), 10–13,
 11 (figure)
 external, 16–18
 internal, 18–22 19 (figure)
 materials of, 11–13. *See also*
 materials
 methods, 5–13, 6 (figure)
corner stitch. *See* Opanka (corner
 stitch)
crepe, 29

D

damaged footwear. *See* footwear,
 damaged
dielectric footwear, 38–39
dielectric testing, 38 (figure)

direct-attach construction, 6 (figure),
10–13
drag sled tribometer, 48–50
dual density, 13, 28

E

eight-inch, 4, 5 (figure)
electric hazard (EH) resistant footwear,
36–38, 37 (figure)
EN ISO 13287, 55–56
environment, 15, 31
ethylene vinyl acetate (EVA), 28–29
European Committee for
Standardization Personal Protective
Equipment (PPE) Footwear
Committee, 55–56
external footwear construction, 16–18.
See also closure systems; leather;
synthetic material; thread
eyelets, 17–18

F

flame-resistant treatment, 18
flat lasted construction, 8
footbeds, 21–22, 22 (figure)
footwear
care and disposal, 35–38,
39–40, 41
construction, 4–5, 10–13, 16–22.
See also construction; direct-
attach construction; Goodyear
welt construction; *specific*
methods
damaged, 35–38, 39–40, 41
design of, 4, 5 (figure), 8, 29–31
fit and sizing, 2–3
materials, 8, 10, 11–13, 25. *See*
also materials; soling materials
test methods for, 55–56, 57–58
types, 33–41. *See also* polymeric
footwear; slip resistance;
stitching; upper materials

force lasted construction, 8–9
friction, 45–47
available, 45–46
coefficient of, 44, 45–47. *See also*
coefficient of friction (COF)
walkway testing and, 47–54

G

Goodyear welt construction, 5–7
grounded reaction forces (GRF), 46

H

hazard assessment, 15, 16
heel materials, 19–20
high oil content. *See* leather, high oil
content
Horizontal Dynamometer Pull Meter,
48–49, 49 (figure)
Horizontal Pull Slipmeter (HPS), 48
(figure)
hybrid construction, 17. *See also*
specific materials

I

impact tests, 33, 34 (figure), 35 (figure)
injection molding, 10, 28
insensible perspiration, 19
insoles, 21–22. *See also* footbeds
internal footwear construction, 18–22.
See also insoles; linings

L

last, 3, 11. *See also* lasting
lasting, 8–9, 10. *See also* direct-attach
construction
leather, 16
high oil content, 8
insulation and, 20
as a lace material, 18
as a soling material, 29
See also seam seal waterproofing
lightweight technology, 28–29

low-cost material, 29
lug pattern, 30 (figure)

M

materials, 18, 20–21. *See also specific materials*
membrane waterproofing, 16–17
metal impact resistance, 35 (figure)
metallic plates, 21
metatarsal guard, 21
midsole design, 10
Model 80 slip tester, 48, 49 (figure)
molds, 12, 13
molten protection, 18
motorized drag sleds, 49

N

net fit construction, 9
non-metallic devices, 21, 27 (figure)
nylon materials, 17, 18
nylon-based synthetic uppers, 17

O

Opanka (corner stitch), 6 (figure), 8
open pour, 10
outsole, 13, 25. *See also* soling materials
Oxford, 4, 5 (figure)

P

pendulum tribometer, 50–51
perspiration, 18–19, 19 (figure), 20
polymeric footwear, 10–11
polyurethane (PU), 11–12, 25–28, 26 (figure)
polyvinyl chloride (PVC), 13, 29
portable tribometer, 48
protective footwear. *See* footwear
protective toe compression resistance, 33–34, 34 (figure), 35
protective toe impact resistance, 33, 34 (figure), 35

puncture-resistant device testing, 40, 41 (figure)
puncture-resistant footwear, 21, 40 (figure), 40–41
steel, 27 (figure)
testing, 40, 41 (figure)

R

rubber, 26 (figure), 28. *See also* crepe; thermal plastic rubber (TPR)

S

safe threshold COF number, 57–58
safety, 15. *See also* footwear; hazard assessment; safety toe footwear; *specific types of footwear*
safety toe footwear, 33–34
SATRA STM 603, 55 (figure)
SATRA Technology Centre of the United Kingdom, 55
SATRA TM142, 22
SATRA TM144, 55
SATRA TM159, 21–22
SATRA TM230, 16
SATRA TM376, 17
seam seal waterproofing, 16, 17
sensible perspiration, 19
shock absorption, 28
shock-resistance, 38
shoe-floor interface, 43, 45–46, 47. *See also* friction; slip resistance
Sigler pendulum, 51 (figure)
single density, 12, 28
six-inch, 4, 5 (figure)
slip resistance value, 54. *See also* safe threshold COF number
slip resistance, 28, 30 (figure), 43
problems of testing, 54–55
test methods, 55–56, 56–57
testing, 44, 47–54, 54–57. *See also* tribometers
slip resistant, 43. *See also* slip resistance

slipping, 44–45. *See also* slip resistance
 sole design, 8
 soling designs, 29–30, 30 (figure)
 soling materials, 9–13, 25–29
 static dissipative (SD) footwear, 39–40
 steel puncture resistant devices, 27
 (figure)
 stitch-down construction, 6 (figure), 8
 stitching, 5–7, 6 (figure)
 string lasted, 9
 Strobel construction, 8–9
 synthetic material, 16, 20. *See also*
 nylon-based material; *specific*
 materials

T

temperature
 hazard assessment and, 17
 perspiration rate and, 19
 polyurethane and, 12
 See also molten protection
 thermal plastic rubber (TPR), 13, 29
 thermal set, 28
 thermoplastic polyurethane, 27
 (figure), 28
 thread, 18
 toe cap, 2, 20–21
 toe shapes, 21
 Tortus II, 49
 Tortus III, 49

tread, 30 (figure)
 tribometers, 4, 47–54, 48 (figure),
 48–53 (figure). *See also* whole shoes
 testers

U

unit sole, 25
 upper materials
 external, 16–18
 internal, 18–22, 19 (figure)
 urethanes, 28
 utilized friction, 46

V

vulcanized footwear. *See* polymeric
 footwear

W

walking, 46
 walkway friction, 44, 47–54, 48–53
 (figure)
 waterproof technology, 11, 12. *See also*
 membrane waterproofing; seam seal
 waterproofing
 Wellington, 4, 5 (figure)
 Wessex pendulum, 51 (figure)
 whole shoe testers, 54–57, 55 (figure),
 56 (figure)
 woven textiles, 17