

Subject Index

A

Aluminum alloy, 17, 279, 381
 separability property, 49
 Aspect ratio, 381
 A285 steel, 399
 ASTM C 1421-99, 315, 336
 ASTM E 399, 263, 353
 ASTM E 1820-96, 49, 139, 263
 ASTM E 1921-97, 3
 Atomic-force microscopy, 122

B

Backtracking method, 105, 214
 α -Brass, 122
 Brittle fracture, 17, 247
 Brittle-to-ductile transition region, 195

C

Calibration function, 263
 Ceramics, fracture toughness, 315, 336
 Chevron notch, 336
 Cleavage resistance, 195
 Compact type specimens, 88
 Compliance ratio method, 139
 Composite laminates, modeling multilayer damage, 301
 Compressive residual stress, 247
 Computational cell model, 195
 Constraint loss, 195
 Crack arrest toughness, correlation with static initiation toughness, 17
 Crack closure, 75, 381
 Crack extension, 139
 Crack growth, 75, 195, 381
 creep, 179
 ductile, 229
 random load, 88
 slow, 315
 surface, 381
 time-dependent, 179
 Crack growth rates, 88
 Crack initiation, 122
 load and location prediction, 353
 Crack length, 263
 compliance ratio method, 139
 estimation, 49

Crack opening displacement, 75
 Crack propagation, 229
 Cracks, part-through, 353, 381
 Crack tip opening angles, three-dimensional analysis, 279
 Crack tip opening displacement, 279
 critical, 247
 Creep crack growth, 179
 Cyclic loading, 381
 Cyclic plasticity, 75

D

Damage mechanics, 195
 Deformation property, 49
 Delaminations, matrix crack-induced, 301
 Dislocation mechanics, 3
 Dissipation rate, 229
 Ductile crack growth, 229
 Ductile tearing, 399
 Dynamic fracture toughness tests, 139
 Dynamic testing, 139

E

Elastic compliance, 139, 263
 Elastic-plastic fracture, 279
 Energetic approach, 229
 Equivalent constraint model, 301

F

Fatigue
 random, 88
 SA533-B1 steels, 105
 slip-bands, 122
 Fatigue crack propagation, correlation with reduced stress intensity range, 75
 Fatigue loading, 301
 Fatigue testing, 381
 Ferritic steels, 3, 139
 Finite-element analysis, 279
 Fractograph, 105
 Fracture, 37
 Fracture energy, 229
 Fracture instability, residual stress effects, 247
 Fracture mechanics, 49

Fracture toughness, 399

ceramics, 315, 336

temperature dependency, 3

thin-walled tube, 214

Fracture toughness tests, 17, 139

dynamic, 139

Fuel cladding, 214

G

Geometry effect, 195

H

Heat affected zone, 179

High-cycle fatigue, 105

High-strength steel, 353

HY-100, 139

Hydrostatic stress, 75

J

J-integral, 37, 49, 229, 399

K

Key curve, 37, 139

L

Limit load, 139

Linear-elastic fracture mechanics, 88, 263

Local approach, 195, 247

Longitudinal cracking, 301

Low-cycle fatigue, 105

M

Martensitic steel, 3

Master Curve

applicability, microstructural limits, 3

crack arrest, 17

Matrix crack-induced delaminations, 301

Micromechanics, 122

N

Normalization, 139

sensitivity study, 37

separability property and, 49

Normalization function, 139

Nuclear reactor pressure vessels, 3

ηpI factor, 49

P

Part-through cracks, 353, 381

Plane-strain fracture toughness, 353

Plastic zones, 88

Power-spectrum shapes, 88

Precracked beam, 336

Q

Quasi-static loading, 301

R

Random fatigue, 88

J-*R*-curve, 315

Reference material, 336

Residual stress effects, 247

σ_5 -Resistance curves, 279

Round robin, 336

S

SA533-B1 steels, 105

Scanning atomic-force microscopy, 122

Sensitivity, 37

Separability property, 49

Shear lag method, 2-D, 301

Ship-band, 122

Specimen geometry, 88

Stability, 315

Standard reference material 2100, 336

Static initiation toughness, correlation with crack arrest toughness, 17

Static loading, 301

Stiffness degradation, 301

Strength mismatch, 195

Stress intensity factor, 105

concise, 263

Stress intensity range, reduced, 75

Stress ratios, 381

Structural integrity, 229

Structural tests, 229

Surface crack, in flexure, 336

Surface crack bend specimens, 88

Surface crack growth, 381

T

Tension-tension fatigue, 301

Thermal cycling, 301

Thin-walled tube, fracture toughness, 214

Transferability analysis, 195

Traverse cracking, 301

U

Uncertainty analysis, 381

V

VAMAS, 336

W

Warm preloading, 247

Waste tanks, 399

Weibull stress, 195, 247

Welds

creep crack growth, 179

mismatched, brittle-to-ductile transition region, 195

under-matched, 139

X

X20CrMoV 12 1 steel, 179

X-specimen test, 214

Z

Zircaloy fuel cladding, 214