

Subject Index

A

Alloys

aluminum

corrosion fatigue crack growth, 246–249

CTOD ductile instability, 414, 417

Incalloy 718

threshold crack growth behavior, 628–637

viscoplastic-induced closure, short cracks, 530–546

one-phase

age-hardened and strain distribution, 186–188

stress corrosion cracking, 209–231, 233–260

titanium

diffusion-controlled crack growth, 246–249

strain-induced hydrides, 569–579

two-phase

age-hardened and strain distribution, 188–191

characteristics of, 198–199

Aluminum

5456-H116 plates, 414–427

7075-T651, 246

6061-T651 plates, 414–427

weldments, 410–427

ASTM Committee E-24

fracture testing, 1

ASTM Standards

E 647, 515, 550

E 23–86, 175–179, 464, 515, 550, 647–81

E 399–83, 608, 660, 662–663

E 813–81, 374, 435–436, 616

B

Blunting model (*see* Crack tip, blunting of)

Boundary cavities (*see* Grain boundaries)

Bridging zone

ceramics, 277, 280

Brittle fracture

A-533B steel, 369–388

concrete, 447–457

C

C* integral, 103–109

crack growth and, 105–106

crack-tip blunting and, 115–119

Carbide particles, 190–191

Catastrophic failure

prediction of

slanted crack, metal plate, 506–512

Cathodic charging

effects in steel, 615–627

Cavitation (*see also* Nucleation)

intergranular, 133–136

in metals, 129–133

Cell model

void nucleation, 61–82

Center-crack specimens

aluminum alloys, 414, 416

concrete, 447–457

HT 60 steel, 514–522

nickel-base superalloy, 630

rectangular metal plate, 497, 502–512

Ceramics

toughening of, 267–290

Charpy V-notch specimens

A 533B steel, 373–374

stainless steel, 460, 464

Clay soils

cracking of, 659–666

Cleavage

nuclear power vessel steel, 375

Compact tension specimens

4340 steel, 607

A 588A steel, 548–563

austenitic stainless steels, 435–438

HT 60 steel, 514–522

micro-/macrodamage-free zone, 18, 21

nickel-base superalloy, 630

Composite particles

and toughness in polymers, 143–146

- Composites, ceramic
 - fiber/whisker, 269, 280–289
 - steady-state cracking, 270
- Concrete
 - dynamic brittle fracture analysis, 447–457
- Configurational stability, 30
 - weight function
 - three-dimensional crack analysis, 54–56
- Contamination
 - effect on hydrogen adsorption, 219–220
- Continuum damage mechanics, 9
 - analytical model, 448–449
 - inclined crack, concrete, 447–457
- Cooling (*see* Temperature, reduced)
- Corrosion (*see also* Stress corrosion cracking)
 - crack closure, 561–563
- Crack arrest
 - threshold, 631–637
 - versus temperature, 93–95
- Crack closure
 - corrosion-induced, steel, 561–563
 - high tensile strength steel, 514–529
 - Mode II loading, chromium steel, 489–495
 - oxide-induced, 154–156, 597–603
 - plasticity-induced, 154–156
 - roughness-induced, 154–156, 596–603
 - subsurface cracks, Hertzian loaded, 679–686
- Crack-defect interaction, 42–56
- Crack growth (*see also* Creep crack growth; Fatigue crack growth)
 - and C^* interval, 105–106
 - compacted fine-grained soils, 659, 661–666
 - controlled environment and, 235–239
 - corrosion and (*see* Stress corrosion cracking)
 - diffusion-controlled, 246–249
 - effect of crack-tip plasticity, 84–96
 - microchemistry and, 222–229
 - retardation of, 560–563
 - stable environment and, 410–427
 - surface energy density/volume and, 21–24
 - thermal mechanical interaction and, 17–21
- Crack initiation
 - critique of formulas/analyses, 10–11
 - micro-/macrodamage ahead of crack, 13, 15
 - stress corrosion and, 210–214
 - surface energy density/volume and, 12–17
 - thermal mechanical interaction and, 17–24
- Crack opening/closing
 - subsurface cracks, Hertzian loaded, 679–686
- Crack opening displacement (COD)
 - critique of, 10
- Crack path, 195–197
- Crack propagation (*see* Crack growth; Crack initiation)
- Crack tapping
 - weight function and, 53–54
- Crack tip
 - blunting of, 115–119, 165–169
 - hydride formation in titanium alloys and, 578–579
 - macrodamage free zone and, 21
 - plasticity of, 84–96
 - in relation to material microstructure, 12
 - stress corrosion cracking and, 215
- Crack tip opening displacement (CTOD)
 - 4340 steel, 589, 608–618
 - aluminum weldments, 410–427
 - aluminum wide-plate specimens, 410–427
 - HT 60 steel, 518–519
 - stress corrosion rate and, 223–228
- Crack tunneling, 123–124
- Crack wall
 - microchemistry effects, 220–222
- Cracks, types of
 - center
 - 5456-H116 aluminum, 414, 416
 - 6061-T651 aluminum, 414, 416
 - concrete, 447–457
 - HT 60 steel, 514–522
 - nickel-base superalloy, 630
 - thin metal sheets, 497, 502–512
 - corner
 - in plates, 297–315
 - edge
 - creep crack growth, 123–124
 - on disc, 358–360
 - in finite-thickness plate, 503–512
 - Incolloy 718, 530–546
 - on strip, 357
 - elliptical, 668–686
 - embedded
 - in steel plate, 390, 394–409
 - half-plane
 - weight-function for, 33–34, 44–45, 50–53

inclined

- in concrete panel, 447–457
- in metal plate, 495, 503–512

planar, 351–364

short

- closure of, 154–156
- corrosion fatigue and, 252–254
- definition of, 151, 158
- propagation of, 170–175
- review of, 152
- in steel plate, 309–312

small (*see* Cracks, types of, short)

surface

- Hertzian contact, 668–686
- in steel plate, 317–326, 390–409

transverse

- in finite composite laminates, 641–658

Crazing

- in homogeneous glassy polymer, 136–146

Creep crack growth

- definition of, 101
- effects of elasticity, 109–112
- and intergranular cavitation, 130–133
- review of, 101–124

CTOD (*see* Crack tip opening displacement)**D**

Damage mechanics

- creep crack growth
- review, 101–124
- unified approach to, 9–26

Deformation

- cyclic loading, 152–154
- effect on surface adsorption, 215–218

Delamination, 641–658

Dilatation

- due to void nucleation, 66, 70
- versus distortion, 25

Dimpled rupture

- austenitic steels, 434–445, 466, 471

Dislocation emission

- three-dimensional weight-function theory, 42–46

Ductile-brittle transition

- ferritic steels, 369–371

Ductile fracture

- review of, 129–133

Ductile instability

- aluminum wide-plate specimens, 419–422, 424–425

Ductile phases

- ceramic toughening, 277–280

E

Earth structures

- fracture mechanics of, 659–666

Eigenvalues

- complex planar cracks, 354, 362–364
- crack at free surface, 318, 320–321

Elastic-plastic fracture (*see also* Plasticity; Viscoplasticity)

- austenitic stainless steels, 459–474
- flat steel plates with part-wall flaws, 390–409

parameters of, 156–157

pressure vessel steels, 369–388

review, 89–91

three-dimensional, 29–56

two-dimensional

review of, 29

weight-function theory/application, 29–56

Elasticity

- creep crack growth, 109–112

Electrochemistry

- stress corrosion cracking, 244–249

Energy dissipation, 10–11

- ahead of crack, 15–17

Environmentally-assisted cracking

- helium, 581–603, 615–626
- hydrogen, 569–603
- hydrogen/hydrogenous gases, 240
- microstructure analysis, 200–203
- seawater, 605–613
- structural alloys, 233–260
- life prediction, 254–258

F

Fatigue crack growth

- center-crack, high-strength steel, 514–529

constant amplitude load

- ASTM Standard E 647, 515, 550

corrosion and, 246–249

crack opening, steel plate, 548–563

critique of formulas/analyses, 10–11

edge crack, thin metal plate, 497–512

hydrogen/helium effects, 4340 steel, 581–603

microstructure, age-hardened alloys, 186–191

near threshold

- chromium steel, 479, 481–495

low-alloy steel, 581–603

nickel-base superalloy, 628–637

seawater effects, 4340 steel, 603–618

Fatigue crack growth (*cont.*)
 slanted crack, thin metal plate, 497–512
 small cracks, 151–180
 ultrasonic, 481–495
 universal ultrasound testing machine, 481
 variable amplitude load, 548–563
 viscoplastic-induced closure, Incolloy 718, 530–546
 Ferrite, continuous (CF), 199
 Fibers/whiskers
 ceramic toughening, 269, 280–289
 fiber failure, 285–286
 Finite composite laminates, 641–658
 Finite element-alternating method
 surface/corner cracks in plates, 300–305, 309
 computational time, 309
 flow chart, 301
 Finite element analysis
 errors of, 25
 inclined crack
 concrete, 451
 thin metal plate, 498–503
 mixed-mode cracks, orthotropic material, 327–350
 plasticity-induced crack closure, 519–522
 single edge-cracked specimen, alloys, 530–546
 surface/corner cracks in plates, 299, 304–305
 viscoplastic-induced closure, short cracks, 530–546
 Flaws, types of (*see* Cracks, types)
 Flow law, 531
 Flow strength
 embedded flaws in steel plates, 399
 Fractography
 crack closure, steel, 489
 Fracture mechanics
 analyses/critique, 9–29
 future challenges, 2–3
 history of, 1, 9–26
 overview of applications, 1
 Fracture toughness
 4340 steel, 85–89
 ASTM Standards
 E 813–81, 374
 austenitic steels, 433, 435–438, 459–474
 A 533B steel, 374–383
 high-strength steels, 615–627
 nuclear industry requirements, steel, 371
 Free-surface effects, 317–326

Frozen stress photoelasticity
 finite-thickness plates, 317–326
 Mode I LEFM algorithm for, 323–326

G

Geometric effects
 transverse crack, laminates, 656–658
 Grain boundaries
 and crack propagation, 172
 and creep crack growth, 101, 105
 and fracture, 132–136
 and hydrogen partitioning, 242–243

H

Hard particles
 and fracture of metals, 129–133
 Hardening models
 effect of void nucleation, 68–72
 strain distribution, age-hardened alloys, 186–199
 Heating (*see* Temperature, elevated; Thermal aging)
 Helium
 crack growth, 4340 steel, 581–603
 Hertzian contact, 668–686
 Heterogeneities in materials
 effect on fracture, 127–146, 190–191, 434, 435
 History
 of fracture mechanics, 1, 9–26
 Homogeneous ductile solids
 failure of, 127–129
 Humidity
 crack growth, 4340 steel, 581–603
 Hydride formation
 titanium alloys, 569–579
 Hydrogen embrittlement
 300 M steel, 615–627
 4340 steel, 581–603, 615–627
 6304 steel, 615–627
 of alloys, 240–241, 257–258, 569–579
 Hydrogen supply
 partitioning of, 242–243
 and surface adsorption, 219–220, 241–244

I

Inclusions (*see also* Carbide particles; Hard particles; Heterogeneities in materials; Oxide particles)
 and rupture of steels, 434, 435

- Influence function
 - planar cracks, 351–364
 - two- and three-dimensional cracks
 - data base, 361
- Intergranular cavitation, 133–136
- Isotropic hardening model
 - and void nucleation, 76–78

J

- J_2 -flow theory
 - void nucleation, 66–68
- J -integral
 - critique of, 10
 - hydrogen embrittled steel, 615, 621–627

K

- K_{Ic}
 - fracture toughness, A 533B steel, 375
- Kinematic hardening model
 - and void nucleation, 68–70

L

- Laminates, finite composite (*see* Finite composite laminates)
- Least squares solution
 - fracture toughness, 375
 - planar elastic crack problem, 355–356
- LEFM (*see* Linear elastic fracture mechanics)
- Lifetime predictions
 - cracked components, 106–109
 - structural alloys, 254–258
- Linear elastic fracture mechanics (LEFM)
 - crack at free surface, 317–326
 - crack tip plastic zone, 185
 - critique of, 10
 - soil cracks/fractures, 660, 664–666
- Load displacement
 - austenitic stainless steels, 467–469
- Load parameter map
 - for creep crack growth, 114–115
- Loading
 - bending
 - corner-cracked steel plates, 298
 - various steels, 396
 - biaxial, 162–165
 - orthotropic material, 327–350
 - combined mode
 - chromium steel, 479–480, 485–495

- constant amplitude
 - ASTM Standard E 647, 515–517
 - steel, 515–517
- cyclic
 - A 588A steel, 548–563
 - crack closure, 154–156
 - elastic-plastic parameters, 156–157
 - fatigue crack growth, 152–157, 185
 - Incalloy 718, 530–546
 - plastic deformation, 152–153
- elastic-plastic, 165
- Hertzian contact, 668–686
- limit, 407–409
- mixed-mode
 - chromium steel, 479–480
 - orthotropic material, 327–350
 - plastics, fiber-reinforced, 162–165
 - steel, 162–165
- Mode I
 - chromium steel, 479–495
 - steel, 497–512
- Mode II
 - chromium steel, 479–480, 485–495
- Mode III
 - steel, 495–512
 - thin metal sheets, 497–512
- monotonically-increasing, 605–613
- multiaxial (*see* Loading, mixed mode)
- sustained
 - structural alloys, 241–243
- tension
 - corner-cracked steel plates, 298
 - various steels, 395
 - variable amplitude
 - steel plate, 548, 553–563
- Localization of damage
 - inclined crack, concrete, 454
- Lubrication
 - and crack growth, 672–678

M

- Macroscopic stress-strain behavior
 - void nucleation and, 63
- Martensite, continuous (MF), 199–200
- hydrogen partitioning, 242–243
- transformation toughening, ceramics, 271–273
- Material constants
 - of transverse-cracked laminate, 658
- Material damage (*see* Damage mechanics)
- Material science
 - definition, 9
 - overview, 10–26

Matrix strain hardening
 void nucleation and, 76–78
 Metals (*see also* Alloys; Aluminum; Steels)
 ductile fracture of, 129–133
 Micro-/macrodamage free zone, 21
 Micro-/macromechanics of fracture
 review of, 151–180, 186–203
 theory, 11–17, 21
 Microchemistry
 stress corrosion cracking, 209–231, 249
 sustained load crack growth, 241–243
 Microcracking
 ceramics, 274–276
 Microstructure (*see also* Heterogeneities in materials; Inclusions; Oxide particles; Void nucleation)
 and fatigue crack propagation, 184–203
 and fracture of stainless steel, 434–445
 scanning electron microscopy, 437–440

N

National Symposium on Fracture Mechanics
 goals, 1–2
 overview, 1–3
 NEWINF
 data base of influence functions, 361
 Nickel-base alloy
 threshold crack behavior, 628–637
 viscoplastic-induced closure, short cracks, 530–546
 Notched specimens, 175–179, 464
 ASTM E 23–86, 175–179, 464
 Nuclear power vessel steel
 ductile-brittle fracture, 369–388
 fracture toughness of, 369–388
 Nucleation (*see* Cavitation; Pit nucleation; Void nucleation)

O

Oil lubrication
 and crack growth, 672–678
 Orthotropic material
 stress-intensity factors, 327–350
 Overloads/underloads
 fatigue crack growth, 548–563
 Oxide particles
 and crack closure, 154–156
 and fatigue properties, 190–191
 near-threshold fatigue crack growth, 593–606, 636–637

P

Photoelastic material
 surface flaws in, 317–326
 Mode I LEFM algorithm for, 323–326
 Pit nucleation
 lubricated rolling/sliding surface, 668
 Pitting
 relationship to cracking, 210
 Plastic collapse
 modified strip yield model, 412, 426–427
 part-wall flawed plates, 399–409
 Plastic deformation
 residual in steel, 523–525
 Plasticity (*see also* Elastic-plastic fracture)
 crack closure, 519–522
 crack-tip deformation, 84–96
 energy density theory and, 22–24
 plastic zone size and, 191–195
 void nucleation and, 79
 Plates, metal
 center-cracked, 497, 502–512
 compact tension specimen, 548–563
 corner-cracked, 297–315
 edge-cracked, 497, 502–512
 inclined crack, 497, 503–512
 part-wall flaws in, 390–409
 short cracks, 309–312
 surface-cracked, 297–315, 317–326
 Polymers
 block copolymers
 crazing in, 142–143
 toughened
 cavitation in, 136–146
 crazing in, 136–146
 fracture in, 138–146
 Power-law viscous materials
 C* interval and, 104–105
 Process zone
 ceramic toughening, 267–269

R

Reference curves (R-curves)
 4340 steel, 609–610
 aluminum wide-plate, 419–422
 ceramics, 266, 273
 Reference stress
 CTOD model, 427–428
 Retardation of crack growth (*see* Crack arrest; Crack closure; Crack growth, retardation of)
 Rock
 damage modeling of, 447

Rolling/sliding contact fatigue, 668, 672–686

S

Seawater

and crack growth, 4340 steel, 605–613

Shear lips

creep crack growth, 123–124

fatigue growth, thin metallic sheets, 497–512

Similitude concept, 157–159

applications of, 251–254

Size effect

fracture toughness, A 533B steels, 369, 371

prediction of, 380–383

Slip character

and fatigue crack growth, 186–191

and plastic zone size, 191–195

Small-scale yielding model

crack closure, steels, 522–526

Softening effect

of pressure-bulk strain, 453

of void nucleation, 61–82

Soil fracture, 659–666

Space/time/temperature interaction

1020 steel specimen, 17–21

theoretical aspects, 26

Steady-state cracking

composite ceramics, 269–270

Steels

1020, 17–21

4340, 581–603, 605–613, 615–627

6304, 615–627

300 M, 615–627

304 SS, 459–474

308 SS, 459–474

316 SS, 459–474

A 588A, 548–563

austenitic, high-strength, 433–445, 459–474

A 533B, 369–388

chromium, 483–495

ferritic, 398–407

HT 60, 514–529

low alloy, 581–603

pressure vessel, 369–388

SM 41A, 514–529

stainless, 398–407, 433–445, 459–474

weldments, 459–474

Strain distribution (*see* Slip character)

Stress corrosion cracking, 209–231

crack initiation, 210–214

crack propagation, 214–229, 236

historical review, 233–250

life prediction and, 254–258

microchemistry, 211–213

stages of, 236–237

Stress cycle

variable amplitude loads, 548, 553–563

Stress-intensity factors

central crack in finite plane, 500–512

compact/center-crack specimens, steel, 518

compact specimens, steel, 553–563

complex planar cracks, 351–364

crack formation, plates, 297–315, 317, 320–326

crack velocity, 224–228

fatigue crack propagation, 157–165

mixed-mode cracks, orthotropic material, 327–350

rolling/sliding contact fatigue, 668, 672–686

slanted crack in finite plane, 503–512

three-dimensional weight function, 42–56

threshold

low-alloy steel, 585–589, 601

structural alloys, 235

transverse crack in laminates, 640, 656–658

ultrasonically-stressed steel, 493–495

Stress ratio

fatigue crack growth, 517–519, 527–529

threshold crack growth, 628–637

variable amplitude loads, 553–554

Stress singularity

crack-tip in laminates, 640, 645–647

loss of, free surface flaws, 317–326

Stress-strain behavior

continuum damage, concrete, 449–454

effect of void nucleation, 61–82

Strip yield model, 412, 426–427

Surface adsorption

contamination and, 215–220

deformation and, 215–220

hydrogen supply and, 241–243

Surface and volume energy, 10–15

surface energy density, 11–13

volume energy density, 13–15

Surface flaws

oil seepage into, 676

photoelastic material, 317–326

plates, 390–409

review, 394–398

Surface flaws (*cont.*)

- rolling/sliding contact, 668–686
- subsurface cracks, 668–686

Surface roughness

- and crack closure, 154–156
- and near-threshold fatigue crack growth, 591–593, 596–603

T

Temperature, elevated (*see also* Thermal aging)

- effect on crack growth, titanium alloys, 569–570, 577–579
- effect on ductile-brittle transition, steel, 369–371
- effect on fracture toughness, steels, 369–388, 459–474
- effect on hydrogen partitioning, steels, 242–243
- effect on intergranular cavitation, 133–136
- effect on stress-corrosion cracking, alloys, 239
- effect on surface phase transformation, steels, 242–243
- effect on threshold crack growth, nickel-base superalloy, 628–630, 637
- effect on viscoplastic closure of short cracks, stainless steel, 530–546
- effect on yield strength, hydrogen-embrittled steel, 617–621

Temperature, reduced

- cryogenic effects on austenitic steels, 433
- effect on ductile fracture, metals and alloys, 127–146
- effect on hydrogen partitioning, steels, 242–243

Tensile strength

- soils, 662–666

Tension softening

- inclined crack in concrete panel, 453, 457

Tension specimens

- austenitic steels, 435–438

Thermal aging (*see also* Temperature, elevated)

- effect on fracture toughness, steel plates, 459–474

Three-dimensional analysis

- creep crack growth, 119–124
- Hertzian contact crack, 669–671
- steel plates, 393–394, 398–407
- weight function theory, 29–46

Three-point bend specimens

- A 533B steel, 372
- various steels, 396

Threshold/near-threshold conditions

- combined Mode I and Mode II loading, 481–495
- elevated temperature effects, 628–637
- hydrogen/helium effects, 581–603
- review, 169–170
- review, environmentally-assisted crack growth, 235–239
- seawater effects, 605–613

Titanium alloys

- diffusion-controlled crack growth, 246–249
- strain-induced hydrides in, 569–579

Transformation toughening

- ceramics, 270–273

Transmission electron microscopy (TEM)

- in situ* study, Ti–6Al–4V alloy, 569–577

Triaxial stress

- and void nucleation, 63–70

Tribology problems

- fracture mechanics solutions, 668–696

Turbine engine components, 628

U

Ultrasonic fatigue, 481–495

- universal-ultrasound testing machine, 481

Ultrasound

- crack opening measurements, 550–551, 553–554

V

Virtual crack extension, 327–350

Viscoplasticity

- closure of small cracks, 530–546

Viscous materials

- C* interval and, 104–105

Void nucleation

- in austenitic steels, 433–445
- effect on macroscopic stress-strain behavior, 63–65
- in elastic-plastic solid, 61–86
- in glassy polymers, 136–146
- and hard particles, 129–133
- in hydrogen-embrittled steel, 620–621, 627
- isotropic vs kinematic hardening, 68–70, 76–82
- mechanical model, 65–70

W**Weight-function theory**

- orthotropic material cracks, 327–350
- review of, 30–31
- three-dimensional elastic cracks, 31–56

Welds

- aluminum, 410–427
- austenitic steels, 465–467

Wide plate specimens

- aluminum alloys, 416