

Index

A

Absolute Seebeck coefficient, 246
 calculation, 17
 Absolute Seebeck emf, 5, 8–9, 246
 across homogeneous nonisothermal
 segment, 9
 Absolute temperature, 246
 Absolute thermoelectric Seebeck emf,
 38
 Absolute zero temperature, 246
 Accuracy, 246
 Adiabatic recovery factor, fluids, 173
 Aluminum, freezing point, 271
 Annealing
 optimum temperature, 145
 wire, 144–145
 ANSI, 246
 Argon, triple point, 270
 Asbestos, 90
 Assemblies
 with protecting tubes, 101
 using quick disconnect connectors,
 102
 ASTM E 77, 156
 ASTM E 207, 141, 161
 ASTM E 220, 141, 154
 ASTM E 230, 189–190, 237
 ASTM E 235, 113
 ASTM E 452, 141
 ASTM E 563, 141
 ASTM E 585, 109, 117
 ASTM standards, 258–259
 Attachment methods, 177
 Average, 235

B

B, thermocouple type, 145, 189
 applications, 48
 emf-temperature reference, 192t–
 193t
 polynomial coefficients, 208t
 Seebeck coefficients, 46t
 Bare wire junction, 117, 121
 Base-metal thermocouples, calibration,
 155–156
 Bead, 14, 246
 Bias, 236, 246
 Type K wire, 238–239
 Binary systems, minimum melting
 temperatures, 84, 85

C

Calibration, (*see also* International
 Temperature Scale of 1990),
 141–167, 246
 base-metal thermocouples, 155–156
 drift, 246
 emf measurement, 145–146
 fixed installations, 156–158
 general methods, 147–148
 high temperature standards, 144
 homogeneity, 146–147
 initial tolerances, 190, 191
 interpolation methods, 158–163
 noble-metal thermocouples, 153–155
 point, 247
 reference thermometers, 142, 144
 secondary fixed points, 143

- shift, 247
 - single thermoelement materials, 161, 163–167
 - emf indicator, 165–166
 - measuring junction, 165
 - procedure, 166–167
 - reference junction, 164–165
 - reference thermoelement, 164
 - test specimen, 163–164
 - test temperature medium, 165
 - stirred liquid baths, 156
 - uncertainties, 148–151
 - envelope determination, 158, 161
 - using comparison methods, 150–151
 - using fixed points, 149–150
 - using comparison methods, 153–158
 - using fixed points, 151–152
 - CCT, 247
 - Celsius temperature scale, 247
 - Centigrade, 247
 - Ceramic insulators, hard-fired, 93, 95–96
 - Ceramic tubes, use temperatures, 98
 - “Cermets”, 98
 - Certify, 247
 - Characterize, 247
 - Chromel 3-G-345-Alumel 3-G-196 thermocouple, 77–78
 - CIPM, 247
 - Circuit complexity, 27
 - Circuit model, 4–5
 - Coaxial thermocouple, 247
 - Cold junction (*see* Reference junction)
 - Compensating extension leads, 25–26, 247
 - Computer based data acquisition systems, 131
 - Connection head, 247
 - Convention, 247
 - Cryogenics, 214–232, 247
 - materials, 215–216
 - thermocouple pair sensitivity, 215–216
 - wire, 238–240
- ## D
- Data acquisition systems, 131
 - Data loggers, 131
 - Decalibrate, 247
 - Defining fixed point, 247
 - Deflection millivoltmeters, 125–126
 - Degree, 247
 - Degrees of freedom, 236–237
 - Differential thermocouple, 248
 - Digital voltmeters, 126
 - Dissimilar materials, 248
- ## E
- E, thermocouple type, 189
 - applications, 47
 - emf-temperature reference tables, 194t–195t
 - polynomial coefficients, 208t
 - as reference thermometer, 144
 - Seebeck coefficients, 46t, 215, 217t–220t
 - thermoelectric voltage, 217t–220t
 - Electrical compensation, reference junctions, 136–138
 - Electrical conducting material, 248
 - Electromotive force (emf), 248
 - indicator, calibration, 165–166
 - measurement, calibration, 145–146
 - Entropy, change, 36
 - EP, thermocouple type
 - Seebeck coefficient, 229t–232t
 - thermoelectric voltage, 229t–232t
 - EPT-76, 274t–276t, 277
 - Error, surface temperature measurement
 - determination, 181–183
 - minimization, 183

Error sources, 20–21
 extension wires, 54–55, 58–59, 62
 ideal thermocouple assembly, 21–22
 nominal base-metal thermocouple
 assembly, 22–25
 precious-metal thermocouple
 assembly with improper
 temperature distribution, 25–28
 reference junctions, 138–139
 Exposed junction, 117, 121
 Extension lead
 in electricity, 248
 error, 248
 in thermoelectric thermometry, 248
 Extension wires, 51, 54–55, 58–62
 advantages, 51, 54
 categories, 54
 design, 99–100
 disparity in thermal emf, 54–55
 error sources, 54–55, 58–59, 62
 insulation, color codes, 91, 93t–94t
 types, 60t–61t

F

Fahrenheit temperature scale, 248
 Fiber glass, 90
 Fibrous silica, 90
 Fixed installations, calibration, 156–
 158
 Fixed point, 248
 reference, 248
 Fixed reference temperature, reference
 junctions, 133–136
 Fluids, temperature measurement,
 169–175
 recovery, 172–173
 response, 169–172
 thermal analysis, 173–175
 thermowells, 173
 Freezing point, 248
 calibration using, 151–152
 Functionally equivalent form, 20

Fundamental law of thermoelectric
 thermometry, 8–10
 corollaries, 10

G

Gallium, freezing point, 271
 Galvanic error, reference junctions,
 139
 Gas thermometer, 264–266
 Gaussian distribution, 235
 Geminol thermocouple, 75
 Gold thermocouples, 81–83
 Graduate, 248
 Ground, 248
 Grounded junction, 121, 248

H

Hard-fired ceramic insulators, 93, 95–
 96
 Heads, 100
 Helium, as thermometric gas, 264–266
 Homogeneity
 calibration, 146–147
 thermoelement, 8
 Hot junction (*see* Measuring junction)
 Hydrogen, triple point, 266–272

I

Ice point, 249
 automatic, 136
 reference junctions, 133–135
 Ideal assembly, 21–22
 Immersion error, reference junctions,
 138
 Incidental junction, 14, 249
 Indicator, calibration, 24–25
 Indium, freezing point, 271
 Inhomogeneity, 249
 thermoelement, 11
 Instability, 249

Installation, fluid temperature measurement, 173–175

Insulation

- characteristics, 92t, 111t
- chemical deterioration, 91
- color codes, 91, 93t–94t
- flexible, 90
- hard-fired ceramic, 93, 95–96
- maximum temperature, 90
- moisture resistance, 88–89
- nonceramic, 88–93
- resistance, 249
- sheathed, compacted, ceramic-insulated thermocouples, 110–112

Interface, 14

Interlaboratory comparison test, 249

International Practical Temperature Scale of 1948, 249, 273, 276

International Practical Temperature Scale of 1968, 249, 274t–276t

International Temperature Scale of 1927, 273

International Temperature Scale of 1948, 273

International Temperature Scale of 1990, 141–142, 249, 260–272

- defining fixed points, 143t, 264t
- pressure effects, 265t

- helium vapor-pressure temperature equations, 262, 264

- platinum resistance thermometer, 266–272

- principles, 261–263

- triple point of neon, 264–266

- units, 261

Interpolation methods, calibration, 158–163

Intrinsic thermocouple, 249

IPTS (*see* International Practical Temperature Scale)

Iridium-rhodium thermocouples, 68–70, 71t

Iridium thermocouples, 68–70, 71t

Iron/constantan thermocouple, calibration, 158–160

Isolated junction, 121, 249

Isothermal, 249

ITS-90 (*see* International Temperature Scale of 1990)

J

J, thermocouple type, 189

- applications, 46–47

- emf-temperature reference tables, 196t–197t

- polynomial coefficients, 209t

- Seebeck coefficients, 46t

Joint, 249

Junction, 249

- class, 249

- incidental, 14

- measuring, 13–15

- real, 14

- reference, 14, 20

- style, 250

- thermoelement endpoints, 14–15

- virtual, 15

Junction-temperature/circuit position plot, 22–23

K

K, thermocouple type, 190

- applications, 47

- Chromel 3-G-345-Alumel 3-G-196, 77–78

- emf-temperature reference tables, 198t–199t

- polynomial coefficients, 209t

- Seebeck coefficients, 46t, 215, 225t–228t

- thermoelectric voltage, 225t–228t

- Tophel II-Nial II, 75, 77

- voltage drop compensation, 180

Kelvin, 250

- relations, 36–38

KP, thermocouple type
 Seebeck coefficients, 215, 229t–232t
 thermoelectric voltage, 229t–232t
 KTTS, 250

L

Laboratory furnaces, calibration, 153–156
 “Law” of homogeneous metals, 33
 “Law” of intermediate metals, 33
 “Law” of successive or intermediate temperatures, 33
 Leads, 250
 Least-square line, 237
 Linearization
 overall, 174
 stepwise, 175
 Liquid-in-glass thermometer, 144, 250
 Loop resistance, 250

M

Matching extension leads, 250
 Material gradient, 248
 Materials
 cryogenics, 215–216
 inappropriate pairings, 26–27
 Mean, 235
 Measurements (*see also* Output measurements)
 error, surface temperature measurement, 175–176
 standard, 250
 uncertainty, 250
 Measuring junction, 13–15, 250
 calibration, 165
 surface temperature measurement, 176–178
 Mechanical reference compensation, reference junctions, 138
 Melting point, 250
 calibration using, 152

Mercury
 contaminated, reference junctions, 139
 triple point, to gallium melting point, 272
 Metal-ceramic tubes, 98
 Mil T12124, 113
 MIMS, 250

N

N, thermocouple type, 190
 applications, 47–48
 emf-temperature reference tables, 200t–201t
 polynomial coefficients, 210t
 Seebeck coefficients, 46t
 Naming convention, 16–17
 NBS, 250
 Neon, triple point, 264–266
 Net Seebeck emf, 15, 251
 Nickel chromium alloy thermocouples, 74–75, 76t, 77–78
 Nickel-molybdenum thermocouples, 78–79, 80t
 NIST, 251
 Noble-metal thermocouples, calibration, 153–155
 Nominal base-metal thermocouple assembly, 22–25
 Nonceramic insulation, 88–93
 Normal distribution, 235

O

Onsager relations, 38–39
 Open-circuit emf, 251
 Output measurements, 125–131
 data acquisition systems, 131
 deflection millivoltmeters, 125–126
 digital voltmeters, 126
 potentiometers, 126–129
 reference junction compensation, 130

temperature transmitters, 130–131
 voltage references, 129–180
 Ovens, constant temperature, 135–136
 Oxygen, triple point, 270

P

Palladium thermocouples, 65–67
 Pallador I, 73–74
 Pallador II, 74
 Peltier coefficient, 251
 Peltier cooler, 126
 Peltier effect, 251
 discovery, 30–31
 Peltier emf (*see* Seebeck emf)
 Peltier heat, 251
 Permanent installations, surface
 temperature measurement, 176
 Perturbation error, 181
 Pigtail leads, 251
 Planck radiation law, 272
 Platinel thermocouples, 71–73
 Platinum-cobalt thermocouple, 67–68
 Platinum-iridium thermocouples, 65–
 66, 67t
 Platinum-molybdenum thermocouple,
 67–68, 69t
 Platinum resistance thermometer, 266–
 272
 Platinum-rhodium thermocouples, 63–
 64, 65t, 69–70
 Polynomial approximations, 208t–211t,
 212
 Potentiometers, 126–129, 251
 circuits, 127–128
 theory, 126–127
 types, 128–129
 Precious-metal thermocouple
 assembly, with improper
 temperature distribution, 25–28
 Precision, 236, 251
 Precision index, 251
 Precision of the mean, 237, 241

Primary reference standard, 251
 Primary standard thermocouple, 251
 Probe
 with auxiliary heater, 178–179
 surface temperature measurement,
 178–180
 types, 184–185
 Projected junction, 251
 Protecting tube, 87, 251
 choice factors, 95, 97
 selection guide, 100, 102t–107t
 use temperatures, 97–98
 1976 Provisional 0.5 K to 30 K
 Temperature Scale EPT-76,
 274t–276t, 277
 Pt-27, 251
 Pt-67, 251

Q

Qualify, 252
 Quick disconnect terminals, 122–123

R

R, thermocouple type, 190
 annealing, 145
 applications, 48
 calibration uncertainties, 149t
 emf-temperature reference tables,
 202t–203t
 polynomial coefficients, 210t
 as reference thermometer, 144,
 148
 Seebeck coefficients, 46t
 Range, 252
 Real junction, 14, 252
 Recovery factor, fluids, 172–173
 Reduced diameter junction, 121–122
 Reference, 252
 Reference junction, 14, 132–139, 252
 automatic ice point, 135
 calibration, 164–165
 compensation, 130

- constant temperature ovens, 135–136
 - electrical compensation, 136–138
 - error, 252
 - contaminated mercury, 139
 - galvanic, 139
 - immersion, 138
 - sources, 138–139
 - wire matching, 139
 - extended uniform temperature zone, 138
 - fixed reference temperature, 133–136
 - ice point, 133–135
 - mechanical reference compensation, 138
 - triple point of water, 133
 - zone box, 137
 - Reference tables
 - equations used to derive, 212
 - KP or EP versus gold-0.07 atomic percent iron thermocouple, thermoelectric voltage, and Seebeck coefficient, 229t–232t
 - polynomial approximations, 208t–211t, 212
 - Type B thermocouples, emf-temperature, 192t–193t
 - Type E thermocouple
 - emf-temperature, 194t–195t
 - thermoelectric voltage and Seebeck coefficient, 217t–220t
 - Type J thermocouples, emf-temperature, 196t–197t
 - Type K thermocouple
 - emf-temperature, 198t–199t
 - thermoelectric voltage and Seebeck coefficient, 225t–228t
 - Type N thermocouple, emf-temperature, 200t–201t
 - Type R thermocouple, emf-temperature, 202t–203t
 - Type S thermocouple, emf-temperature, 204t–205t
 - Type T thermocouple
 - emf-temperature, 206t–207t
 - thermoelectric voltage and Seebeck coefficient, 221t–224t
 - Reference thermoelement, calibration, 164
 - Reference thermometers, 142, 144
 - Refractory insulating materials,
 - thermal expansion coefficient, 111t
 - Refractory oxides, properties, 96t
 - Refractory thermocouple, 252
 - Regression analyses, 244–245
 - Regression line, 237
 - Relative Seebeck coefficient, 16, 252
 - calculation, 17
 - Relative Seebeck emf, 16, 252
 - Repeatability, 252
 - Replicate, 252
 - Reproducibility, 252
 - Resistance, thermoelements, 57t
 - temperature and, 56t
 - Resistance thermometers, 142, 144
 - Resistor, temperature sensitive, 136
 - Round-robin test, 252
 - RX extension, 25
- S
- S, thermocouple type, 145, 190
 - applications, 48
 - calibration uncertainties, 149t
 - emf-temperature reference tables, 204t–205t
 - polynomial coefficients, 211t
 - as reference thermometer, 144, 148
 - Seebeck coefficients, 46t
 - Screw terminals, 122–123
 - Secondary reference standard, 253
 - Secondary standard thermocouple, 253
 - Seebeck cell, 10
 - pair of, 12–13

- Seebeck characteristics
 - absolute, 5–10
 - relative, 11–18
- Seebeck coefficient, 6, 253
 - absolute, 17, 246
 - KP or EP thermocouple, 229t–232t
 - relative, 16–17, 252
 - in terms of Peltier or Thomson coefficient, 37
 - thermocouple types, 46t
 - thermoelements, 53t
 - Type E thermocouples, 215, 217t–220t
 - Type K thermocouple, 215, 225t–228t
 - Type KP, 215
 - Type T thermocouples, 215, 221t–224t
- Seebeck effect, 34–35, 253
 - discovery, 29–30
- Seebeck emf, 5, 253
 - absolute, 5, 8–9, 246
 - disparity in extension wires, 54–55
 - iridium-rhodium and iridium thermocouples, 70
 - net, 15, 251
 - nickel-chromium alloy thermocouples, 74
 - nickel-molybdenum and nickel thermocouples, 79
 - platinel thermocouples, 72
 - platinum-iridium and palladium thermocouples, 66
 - platinum-molybdenum thermocouples, 68
 - relative, 16, 252
 - thermoelements, 58
 - tungsten-rhenium thermocouples, 81–82
- Seebeck inhomogeneity, 253
- Seebeck instability, 253
- Sensing element, 253
- Sensing element assembly, 87–89
- Separated junction, surface temperature measurement, 177–178
- Sheathed, compacted, ceramic-insulated thermocouples, 108–124
 - applications, 122, 124
 - combinations of sheath, insulation, and wire, 112, 116t, 117
 - compatibility of wire and sheath material, 116t
 - construction, 108–110
 - dimensions and wire sizes, 117
 - installation, 123–124
 - insulation, 110–112
 - materials, 112–113, 114t–115t
 - measuring junction, 117, 121–122
 - outside diameter versus internal dimensions, 109
 - parts, 108–109
 - sheath, 112, 114–115
 - terminations, 122–123
 - testing, 113, 117, 118t–120t
 - wires, 112
- Sheathed thermocouple, 253
 - accuracy, 240t
 - junction types, 178–179
 - material, 253
- Sheathed thermoelement, 253
- Silver, freezing point
 - platinum resistance thermometer, 270–272
 - range above, 272
- Similar materials, 253
- Specific heat of electricity, 32
- Standard, 254
- Standard deviation, 235–236
- Standard error of estimate, 244–245
- Standard platinum resistance thermometer (SPRT), 254
- Step response, 254
 - time, 254
- Stirred liquid baths, calibration, 156

Superconductivity, 9
 Superconductor, 254
 Surface temperature measurement,
 175–185
 aerodynamic heating, 182–183
 attachment methods, 177
 commercial thermocouples, 183–
 185
 current carrying surfaces, 180
 error
 determination, 181–183
 measurement, 175–176
 minimization, 183
 sources, 180–181
 installation types, 176
 measuring junctions, 176–178
 moving surfaces, 180
 permanent installations, 176
 probes, 178–180
 steady-state conditions, 181–182
 surface heated by radiation, 182
 transient conditions, 182–183
 Surface thermocouples, 183–185

T

T, thermocouple type, 190
 applications, 45–46
 emf-temperature reference tables,
 206t–207t
 polynomial coefficients, 211t
 as reference thermometer, 144
 Seebeck coefficient, 46t, 215, 221t–
 224t
 thermoelectric voltage, 221t–224t
 Temperature (*see also* International
 Temperature Scale of 1990)
 difference, 254
 emf relationships, computation, 212
 gradient, 254
 high, compatibility problems, 84, 85t
 improper distribution, precious-
 metal thermocouple, 25–28

measurement uncertainty, 234–245
 average, 235
 bias, 236
 degrees of freedom, 236–237
 Gaussian distribution, 235
 general considerations, 237
 least-square line, 237
 mean, 235
 means and profiles, 240–241
 normal distribution, 235
 precision, 236
 precision of the mean, 237, 241
 probability paper, 242–243
 regression analyses, 244–245
 regression line, 237
 standard deviation, 235–236
 variance, 235–236
 wire calibration, 238–240
 multioordered response, 170
 ramp change, 169–171
 scale, 254
 sensor, response, 169–172
 step change, 170–171
 thermoelement resistance to change
 with, 56t
 transmitters, 130–131
 units, 261
 upper limits for protected
 thermocouples, 44t, 45, 52t
 voltage determination form, 21–
 22
 zone, 23–24
 boundaries, 13
 emf increments, 24
 extended uniform, reference
 junctions, 138
 Temperature sensitive resistor, 136
 Terminal blocks, 100
 Terminations, 87–88
 flexible connecting wires, 122
 sheathed, compacted, ceramic-
 insulated thermocouples, 122–
 123

- Testing, sheathed, compacted, ceramic-insulated thermocouples, 113, 117–120
- Test temperature medium, calibration, 165
- Thermal emf (*see* Seebeck emf)
- Thermal emf test, circuit diagram, 163–164
- Thermal expansion coefficient, refractory insulating materials, 111t
- Thermocouple, 4, 13, 254
 - with different temperature distributions, 13–14
 - extension wires, 60t–61t
 - reference, 19
- Thermocouple assembly, 254
- Thermocouple cable, 254
- Thermocouple circuit, 254
 - basic, 132–133
 - thermometry, 18–19
- Thermocouple connector, 254
- Thermocouple gland, 255
- Thermocouple head, 255
- Thermocouple junction, 13
- Thermocouple material
 - compatibility problems at high temperatures, 84, 85t
 - primary, 26
- Thermocouple probe, 255
- Thermocouple style, 255
- Thermocouple types, (*see also* B, E, EP, J, K, KP, N, R, S, T), 189–190, 255
 - nonstandardized, 62–83
 - Chromel 3-G-345-Alumel 3-G-196
 - thermocouple, 77–78
 - geminol thermocouple, 75
 - gold thermocouples, 81–83
 - iridium-rhodium thermocouples, 68–70, 71t
 - iridium thermocouples, 68–70, 71t
 - nickel chromium alloy thermocouples, 74–75, 76t, 77–78
 - nickel-molybdenum thermocouples, 78–79, 80t
 - palladium thermocouples, 65–67
 - pallador I, 73–74
 - pallador II, 74
 - platinel thermocouples, 71–73
 - platinum-cobalt thermocouple, 67–68
 - platinum-iridium thermocouples, 65–66, 67t
 - platinum-molybdenum thermocouple, 67–68, 69t
 - platinum-rhodium thermocouples, 63–64, 65t, 69–70
 - Thermo-Kanthal special thermocouple, 75
 - Tophel-Nial thermocouple, 75, 77
 - tungsten-rhenium thermocouples, 78–82, 83t
 - standards, 43–45
- Thermodynamics, 36–39
- Thermoelectrically homogeneous material, 8
- Thermoelectric circuit, 255
 - analysis, 18–28
 - elementary, 11–12
 - traditional “laws”, 33–34
- Thermoelectricity
 - historic background, 28–32
 - mechanisms, 34–36
- Thermoelectric power (*see also* Seebeck coefficient)
 - in energy generation, 255
- Thermoelectric pyrometer, 255
- Thermoelectric thermometry, 255
 - elementary theory, 32–39
 - Kelvin relations, 36–38
 - “laws” of circuits, 33–34
 - mechanisms, 34–36
 - Onsager relations, 38–39
 - fundamental law, 8–10

Thermoelectric voltage
 Type E thermocouples, 217t–220t
 Type K thermocouple, 225t–228t
 type KP or EP thermocouple, 229t–232t
 Type T thermocouples, 221t–224t
 Thermoelectric voltage source, 5
 Thermoelement, 13, 255
 endpoints, 14–15
 inhomogeneous, 11
 pairings, 13
 Thermoelement materials
 calibration, 161, 163–167
 emf indicator, 165–166
 measuring junction, 164–165
 procedure, 166–167
 reference junction, 164
 reference thermoelement, 164
 test specimen, 163–164
 test temperature medium, 165
 properties, 48–58
 chemical composition, 49t
 designations, 48–49
 environmental limits, 50t–51t
 physical, 54t–55t
 resistance, 57
 resistance and temperature, 56t
 Seebeck coefficients, 53t
 thermal emf, 58
 upper temperature limits, 52t
 Thermojunction, 13
 Thermo-Kanthal special thermocouple, 75
 Thermometry
 naming convention, 16–17
 thermocouple circuits, 18–19
 Thermopile, 255
 Thermopower (*see* Seebeck coefficient; Thermoelectric power)
 Thermowell, 87, 98–99, 255
 fluid measurement, 173
 Thomson coefficient, 31–32, 255

Thomson effect, (*see also* Seebeck emf), 255
 discovery, 31–32
 Thomson heat, 256
 Time constant, 256
 Tin, freezing point, 271
 Tip solution, 174–175
 Tophel-Nial thermocouple, 75, 77
 Total temperature, 256
 TP/RN pairing, improper, 26
 Traceability, 20
 Transducing element, 256
 Triple point, 256
 argon, to triple point of water, 270
 equilibrium hydrogen, 266–272
 above freezing point of silver, 272
 from 0° to freezing point of silver, 270–271
 triple point of water, 269–270
 mercury, to melting point of gallium, 272
 neon, 264–266
 to triple point of water, 270
 oxygen, to triple point of water, 270
 water, 269–270
 reference junctions, 133
 Tungsten
 application problems, 80
 doping, 81
 Tungsten-rhenium thermocouples, 78–82, 83t
 calibration uncertainties, 150t

U

Uncertainty, 256
 bias, 256
 calibration, 148–151
 definition, 236
 envelope, determination, 158, 161
 measurement, 24
 precision, 256

temperature measurement (*see*
Temperature measurement
uncertainty)
Uncertainty envelope method, 160,
162–163
Ungrounded junction, 121
Unsheathed thermocouples, accuracy,
238t

V

Validate, 256
Variance, 235–236
Verify, 256
Virtual junction, 15, 256
Voltage, 256
references, 129–180

W

Water, triple point, 133, 256, 269–
270
Wire (*see also* Extension wires)
annealing, 144–145
cryogenics, 238–240
homogeneity, calibration, 146–147
matching error, reference junctions,
139
sheathed, compacted, ceramic-
insulated thermocouples, 112

Z

Zinc, freezing point, 271
Zone box, reference junctions, 137
Zone plate, 257