

Subject Index

A

Acicular precipitate, duplex micro-
structure, 177

A508 Class 2 steel, silicon content
effect on ferrite nose posi-
tion, 71, 73

Alloy 51, 238
creep strength, 253
 γ' phase volume fraction, 257
stress rupture, 252–254

Alloy 69, 238

Alloy 143
creep, 213–214
 γ' precipitate and dislocation
structure, 206
influence of initial γ size on creep
curves, 207–208
lamellar structures, 207, 209
lattice mismatch, 211
Mo content effect, 213

Alloy
chemistry, 271
development, 116
elements, loss or gain, 26

Alloy W-545, 278, 280, 282

Alpha-2, 176

Aluminides. *See* Nickel and nickel-
iron aluminides

Aluminum
alloys, 183, 199–200
oxide formation, 287
residual element, 61, 63–64

Analytical electron microscopy, 165
dislocation substructure, 176, 178
duplex microstructure of acicular
precipitate, 176–177

electron diffraction capability,
176
gas turbine materials, 171, 174–
179

Annealing, 238

Antimony, residual element, 65–66

Arsenic, residual element, 65–66

ASME Boiler and Pressure Vessel
Code, Section VIII, 96, 101

ASTM A 508, 51–52

ASTM A 788–85, 48

Atomization, 183–184, 193–194

centrifugal, 187–188

gas. *See* Gas atomization

mode, cumulative powder size
fraction dependence on, 189

ultrasonic gas, 188–189

vacuum, 187

Attack parameter, 276–278

Austenitic stainless steels, 116–157

alloy chemistries of small heats of
PCA modifications, 146–147

cold-worked, 123

crystal structures and composi-
tions of phases, 12–13

D9 type, 119

helium embrittlement resistance,
129–137

higher Ti + Nb and Nb levels,
146, 150

high-temperature strength char-
acteristics, 154–156

histograms of elemental compo-
sition, 138–139

phase stability and formation dur-
ing neutron irradiation, 137–
146

Austenitic stainless steels—

Continued

- phosphide precipitation, 151–154
- with tailored precipitation characteristics, 146–154
- tensile yield strength, 155–156
- void, 117–118
- void swelling resistance, 117–129
 - bubble evolution as function of dose, 124, 128
 - critical cavity size, 125
 - delay of void formation, 119, 121
 - design window, 120, 122
 - differences in void and fine MC formation, 124, 126–127
 - as function of fluence, 120
 - helium effects, 120, 123, 129
 - irradiation-induced solute segregation, 125, 129
 - macroscopic description, 119–120
 - precipitate effects, 125, 129
 - ratio of dislocation of cavity sink strength, 125
 - silicon and titanium effect, 119
 - swelling expectations for fusion, 122

B

- B3 pretreatment, 133–136
- Bainite, 110
- Baker-Nutting diagram, 88, 92
- Beta phase, 176
- Boride, 165
- Borocarbide, 68
- Boron
 - microalloying, intergranular fracture, 223–226
 - residual element, 67–70
 - segregation behavior, 223, 225
- Boundary migration, 243
- Braid, 290, 296
 - composite, 292–294
 - cross-sectional regions, 297
- Burgers vectors, 176

C

- Calcium, residual element, 67–68
- Carbide
 - formation, 88, 92
 - morphologies, 111
 - species as function of tempering parameter, 88, 95
- Carbide-free acicular bainite, 110–111
- Cavitating grain boundaries, versus life fraction consumed, 34
- Cavity
 - critical size, 125
 - microstructures, thin foils, 141–142
 - growth, 31–33
- Central Electricity Generating Board, research and development, 5–6
- Centrifugal atomization, 187–188
- Ceramic matrix, 290
- CG-27, 278, 280–281
 - internal oxidation of aluminum, 286
 - oxidation and corrosion behavior, 285
- Charpy 54 J transition temperature, 107
 - versus ultimate tensile strength, 89, 96
- Charpy fracture, 54–55
- Charpy impact energy, 60–61, 95
- Cleanliness, effect of Mn content, 71
- Clean steel, 47, 50, 53, 71
- Cleavage fracture stress, 20
- Climb by-pass models, 30
- Clinch River breeder reactor, tube-sheet forgings, 74, 76–78
- CMSX-2
 - creep, 218
 - γ' size effects, 215
 - creep curves, 207–208
 - lamellar structures, 207, 210
 - lattice mismatch, 211–212

- Cobalt-base alloys, composition, 274
- Coble creep, 29–31
- Cold cracking, prevention, 104
- Composite
 - materials, 290
 - stiffness matrix, 296
- Compressive strength, concrete, 8
- Concrete, 3, 8–9
- Consolidation, high temperature
 - aerospace materials, 194–195
- Continuous filament system, 291
- Copper, 65, 75, 78
- Corrosion
 - attack parameter, 276–278
 - oxide dispersion strengthened alloys, 265–267
 - resistance, 238, 257
- Cr_2O_3 , 278, 285
- Crack
 - growth, low chromium ferritic steels, 103–104
 - initiation, 34–36
 - nucleation, 34–35
 - opening displacement
 - versus intergranular failure to, 70
 - stainless steels, 21
 - propagation, 36
- Cracking
 - cold, 104
 - hot, 106
 - post-weld reheat, 105
- Creep, 22–34, 83, 202, 222, 238
 - anisotropy, nickel-base superalloys, 213–214, 218–219
 - climb by-pass, 30
 - 2.25Cr–1Mo steel, 111
 - curve, Cr–Mo steels, 100–101
 - embrittlement, 47
 - endurance equation, 37
 - ferritic steels, 24
 - grain size dependence, 30
 - IC–264, 230, 233
 - irradiation effects, 26–28
 - loss or gain of alloying elements, 26
 - low chromium ferritic steels, 96–101
 - nickel and nickel-iron aluminides, 227, 229
 - oxide formation, 26–27
 - properties, stainless steel welds, 25
 - resistance, 271
 - secondary rate, 29
 - strength, INCONEL alloy MA 6000, 253
 - threshold stress, 29
 - viscous, 30
- Creep crack growth, 24–25
- Creep deformation, stainless steels, 31
- Creep-fatigue, 37–38
- Creep mechanisms
 - cavity growth, 31–33
 - deformation, 29–31
 - remnant life assessments, 33–34
- Creep rate
 - Cr–Mo steels, 99, 101
 - as function of hafnium concentration, 227, 229
- Creep rupture
 - ductility versus rupture time, 72
 - oxide dispersion strengthened alloys, 249–258
 - stainless steels, 22–24
- Critical radius theory, 125
- Critical resolved shear stress, 16
- $(\text{Cr},\text{Mo})_2\text{CN}$ carbides, 88, 92
- Cr–Mo steel, 83
 - Charpy 54 J transition temperature versus ultimate tensile strength, 89, 96
 - composition and
 - microstructure, 86
 - welding, 105–106
 - creep rate, 99, 101
 - creep strain versus time, 99–100
 - development, 84
 - hextenary phase diagram, 72

Cr-Mo steel—*Continued*

- hydrogen attack resistance, 83
- modified, 84
 - rupture strength, 97–98
 - ultimate tensile strength, 89
- rupture strength versus Larson-Miller parameter, 97–98
- strain-controlled fatigue, 101–102
- ultimate tensile strength, versus temperature, 89, 96–98
- see also* Ferritic pressure vessel steels; specific steels
- 2.25Cr–1Mo steel, 59, 109–111
 - Al-N particle, 64–65
 - Al-Si and Si deoxidation, 64
 - carbide formation, 88, 92
 - copper particles extracted from ferrite matrix, 76–77
 - continuous cooling diagrams, 88
 - effect of boron on ferrite nose position, 67, 69
 - embrittlement, 108
 - grain boundary cavities and precipitate-free zone, 24
 - hardenability, 86
 - modified, M_3C carbide, 109
 - phosphorus effect, 59–60
 - quenched-and-tempered, 110
 - rupture stress, 64
 - strain-controlled fatigue curves, 103
 - tempering sequence, 88
 - yield strength versus copper content, 76, 78
- 3Cr–1Mo–1Ni steel, transmission electron micrographs, 86, 88, 90–91
- 3Cr–1.5Mo–0.5Ni steel
 - carbide species as function of tempering parameter, 89, 95
 - carbon extraction replica, 88, 93
 - creep curve, 100–101
 - creep strain versus time, 99
- 3Cr–1Mo steel, embrittlement, 106–108
- 3Cr–1.5Mo steel, 103, 108–109

- 9Cr–1Mo steel, 16, 20
- 12Cr–Mo–V–Cb–N, 49
- 3Cr–1.5Mo–0.1V–1.5Mn steels, continuous cooling diagrams, 88
- 9Cr–1Mo–V–Nb steel, crack growth, 103–104
- Cr–Mo–V steel, 49
 - tensile ductility, 66–67
- 3Cr–1.5Mo–V steel, strain-controlled fatigue curves, 102
- 2.25Cr–1Mo–V–Ti–B steel, 100–101, 103
- 18Cr–8Ni austenitic stainless steels, compositional modifications, 10

D

- Damage volume, 23
- Deformation, 29–31
- Dendritic microstructures, fine-scale, 190
- Densification mechanism map, 194
- Directionally solidified alloys, 202
- Discrete fiber system, 291
- Dislocation
 - distribution, 217
 - substructure, 176, 178
- Dissimilar weld metal joints, 25–26
- Dortmund-Hoerder degassing, 56
- Ductility, 222
 - boron addition effect, 223–224
 - IC–145, 228, 230
 - INCONEL alloy MA 6000, 263
 - nickel and nickel-iron aluminides, 198, 237

E

- Electric arc furnaces, 56–57
- Electron microprobe analysis, 165
 - gas turbine materials, 170–171
 - Stirling engine, 278, 280–281
- Electroslag hot-topping, 57
- Electroslag refining, 47, 50, 56–57, 76

Elongation
 effect of chromium additions, 232
 as function of temperature, 259, 261
see also Ductility
 Embrittlement, 52–55
 dynamic, 222, 228–232, 237
 nickel aluminides, 223
see also specific types of embrittlements
 Endurance ratio, INCONEL alloy MA 6000, 263
 Endurance testing, Stirling engine, 283–284, 286
 Energy dispersive X-ray analysis, 167
 ESHT. *See* Electroslag hot-topping
 ESR, 47, 50, 56–57, 76

F

Fabrication, 222
 nickel and nickel-iron aluminides, 232–234
 Fabric geometry model, 290, 296–297
 Failure strain, 295
 Fast breeder reactors, 117, 119
 Fatigue, 34–38
 crack initiation, 34–36
 crack propagation, 36
 creep-fatigue, 37–38
 high cycle
 INCONEL alloy MA 754, 264
 INCONEL alloy MA 956, 264–265
 INCONEL alloy MA 6000, 262–263
 low chromium ferritic steels, 101–103
 low cycle
 INCONEL alloy MA 754, 264–265
 INCONEL alloy MA 956, 264–266
 INCONEL alloy MA 6000, 263–264
 mechanisms of environmental influence, 38, 40–41
 oxide dispersion strengthened alloys, 262–265
 Fatigue crack growth, graphite, 7
 Fatigue resistance, 238
 Fe_2O_3 , 278
 δ -Ferrite, 10–11
 Ferrite steel welds, HAZ microstructure, 16
 Ferritic pressure vessel steels
 creep, 96–101, 111
 fatigue, 101–103
 crack growth, 103–104
 hardenability, 110
 heat treatment effect on microstructure, 86, 88–89
 hydrogen effects, 108–109
 hydrogen embrittlement, 106–108
 low chromium, 83–112
 materials and initial processing, 85–87
 stress rupture, 96–101
 temper embrittlement, 106–108
 tensile strength, 89, 94–96
 toughness, 89, 94–96
 weldability and weldment properties, 104–106
 Ferritic steels, 3
 creep, 24
 creep strength and composition, 39
 environmental interactions, 16, 18
 fracture toughness, 18, 20–21
 sulfide characteristics, 17
 tensile properties, 16–18
 yield stress changes, 18
 Fiber architecture, 290–298
 categories, 291
 continuous filament system, 291
 control of microstructure, 297
 discrete fiber system, 291

Fiber architecture—*Continued*

- effect on properties of composites, 292–293
 - failure strain, 295
 - fiber volume fraction, 297
 - flexural strength effect, 292–293
 - fully integrated structure, 291
 - inherent bending strain, 295
 - microstructure analysis, 293–296
 - planar interlaced system, 291
 - processing science base for microstructural control, 293–297
 - stiffness matrix, 296
 - translation efficiency effect, 292
- Fiber orientation, 290, 297
- Fiber reinforcement, 167, 291
- Fiber volume fraction, 290–291, 297
- Flexural strength, fiber architecture, effect, 293
- Formability, 238
- FP/AL-Li composites, 285, 296
- Fraction of rare gas release, 9
- Fracture
- appearance transition temperature, 53–54, 106–107
 - behavior, 222
 - boron addition effect, 223–224
 - mode, 228, 231, 246
 - toughness, 18–21
- Fully integrated structure, 291

G

- γ' , 202–203, 238
- alloys, secondary recrystallization, 243
 - directional coarsening, 204–205
 - lattice mismatch effect, 211
 - matrix
 - INCONEL alloy MA 6000, 247
 - ordered, 229
 - undersaturated, 213
 - particle shearing, 215–216
 - phase, 137, 141, 255
 - coalescence, 253
 - coarsening and rafting, 255
 - morphology, 255–256
 - size variation with rupture life, 255–256
- precipitates, 184, 243
- and dislocation structure, 206
- shape, 204
- size effects, nickel-base superalloys, 207–209, 215
 - solvus temperature, 243
- Gas atomization, 185–186
- process control system, 193
 - sensor needs for feedback control, 193
- ultrasonic, 188–189
- Gas-cooled reactors, 6
- Gas turbine materials, 165–181
- analytical electron microscopy, 171, 174–179
 - cast blades, 167, 169
 - development procedure, 166
 - electron microprobe analysis, 170–171
 - future analytical development needs, 179
 - image analysis, 170
 - mu phase, 174–176
 - oxide rafts, 170, 172–173
 - precipitate phase, coarsening on dislocation mobility, 179, 181
 - scanning electron microscopy, 167–170
 - titanium alloys, 176
 - ultra-fine array of dispersoid, 179–180
 - yttrium effects, 169
- Gatorizing, high temperature aerospace materials, 192
- G phase, 137, 140–141
- Grain aspect ratios, 244, 246
- Grain-boundary cohesion, 223
- Grain-boundary fracture, 222
- Grain growth, 238
- Granular bainite, 110–111

Graphite, 3, 7–8
 Graphitization, 64

H

- Hafnium additions, 226, 229
 Hairpin tubes, 286–287
 Hardenability, 47
 2.25Cr–1Mo steel, 86, 110
 boron effect, 68
 Hardening, 111, 225–230
 HAZ microstructure, ferrite steel welds, 16
 Heat treatment, microstructure effect, 86, 88–89
 Heavy forgings, residual elements.
 See Residual elements
 Helium
 bubble formation, 135
 embrittlement, 117
 embrittlement resistance, 129–137, 156
 B3 pretreatment, 133–136
 bubble formation, 135
 design window, 132–133
 grain boundary carbides, 132–133
 tensile elongation, 132
 tensile properties, 130–132
 induced suppression of void formation, 129
 induced void suppression, 141
 microstructural evolution effect, 140–142
 production via nuclear transmutation reactions, 117, 119
 RIS effect, 143
 suppression of irradiation-induced phase formation, 143
 void formation enhancement, 129
 void swelling effects, 120, 123
 Helium-induced extended transients, 123
 High temperature aerospace materials, 183–200
 atomization, 193–194
 centrifugal atomization, 187–188
 consolidation, 194–195
 densification mechanism map, 194
 dependence of cumulative powder size fraction on atomization, 189
 dispersion-strengthened aluminum alloys, 199–200
 effect of process parameters on droplet and preform characteristics, 196–197
 fine-scale dendritic microstructures, 190
 gas atomization, 185–186
 Gatorizing, 192
 historical profile, 184
 hot extrusion, 191
 hot forging, 192
 hot isostatic pressing, 190–191
 interface between powder metallurgy and rapid solidification, 189–190
 liquid and partially solidified droplets in transit to substrate, 196
 ordered intermetallics, 197–199
 Osprey process, 195
 post-consolidation thermomechanical processing, 192
 rotating electrode process, 186–187
 spray deposition, 195–197
 titanium alloys, 200
 ultrasonic gas atomization, 188–189
 vacuum (soluble gas) atomization, 187
 High-temperature strength, austenitic stainless steels, 154–156
 Holloman-Jaffee parameter, 18
 Hot consolidated powder, 240–243
 Hot cracking, 106

Hot extrusion, high temperature aerospace materials, 191
 Hot forging, high temperature aerospace materials, 192
 Hot isostatic pressing, 179, 190–191, 194
 HS-188, hydrogen permeability coefficient, 285
 Hydrogen
 low chromium ferritic steel effects, 108–109
 residual element, 58–59
 service, temperature-pressure regimes, 108–109
 Hydrogen attack, 83, 108
 Hydrogen embrittlement, 53, 83, 106–108
 Hydrogen flaking, 47, 50, 53, 58–59
 Hydrogen permeability, 271
 coefficient, 275, 283–285
 Stirling engine, 280, 283

I

IC-50, oxidation rates, 231, 234
 IC-63, hot fabricability, 234–235
 IC-72, oxidation rate, 232, 234
 IC-145, ductility, 228, 230
 IC-159, hot fabricability, 234–235
 IC-218, oxidation rate, 232, 234
 IC-264, tensile properties, 230, 233
 Image analysis, 165
 gas turbine materials, 170
 oxide rafts, 170, 172–173
 Impact properties, stainless steel, 18–19
 Impact toughness, 9Cr-1Mo, 20
 IN-939, corrosion resistance, 257
 Inclusions, 47
 calcium, 67–68
 egg-type, 74–75
 Ni-Cr-Mo-V rotor forging steels, 74–75
 sulfide, 60–61, 74
 INCOLOY 800, distribution of aluminum, 286

INCOLOY alloy MA 956, 238, 250–251, 253
 INCONEL 718, 278, 280
 INCONEL alloy MA 6000, 238, 240
 γ' phase, morphology, 255–256
 creep rupture, 249, 251–252
 creep strength, 253
 dispersoid size variation with rupture life, 257
 ductility, 263
 endurance ratio, 263
 formation of coarse grains, 243
 γ' size variation with rupture life, 255–256
 grain aspect ratio, 246
 high cycle fatigue behavior, 262–265
 intermediate temperature strength, 252
 long-term stress rupture, 255
 low cycle fatigue behavior, 263–266
 macrostructure, 244–245
 microstructure, 240–241
 oxidation resistance, 266
 recrystallized grain size, 244
 rupture strength, upward break, 257–259
 submicron grain size, 242
 yield strength, 259
 zone-annealed, 247
 INCONEL alloy MA 753, 243
 INCONEL alloy MA 754, 238, 243
 high cycle fatigue resistance, 264
 low cycle fatigue resistance, 264–265
 oxidation resistance, 266
 secondary recrystallization, 247–248
 yield strength, 259
 INCONEL alloy MA 956
 macrographs, 248, 250
 oxidation resistance, 266–267
 secondary recrystallization, 248–249
 Ingots, nickel aluminides, 232–233

Inherent bending strain, 295
 Interaction solid-solution hardening, 111
 Intergranular failure, 70, 130–131
 Intergranular fracture, boron microalloying, 223–226
 Intermediate temperature strength improvements, oxide dispersion strengthened alloys, 252–255
 Intermetallic compounds, 183–184, 222
 Iron-base alloys, 271, 274, 284
 Irradiation effects, creep, 26–28
 Irradiation-induced phase, 116, 137, 139
 Irradiation-induced solute segregation, 116, 125, 129, 137
 helium effect, 143
 intensity, 140–141
 negative effect on MC stability, 144
 Irradiation-modified phase, 116, 137, 139
 Isothermal annealing, 247–249
 Isothermal embrittlement, 53–54

J

J factor, 53–54, 106

K

Kachanov relationship, 23

L

Ladle refining furnace, 47, 57, 59, 68
 Lamellar structures
 alloy 143, 207, 209
 CMSX-2, 207, 210
 Larson-Miller equation, 88–89
 Larson-Miller parameter, 18, 96–98
 versus tensile strength, 89, 94
 Lattice mismatch, nickel-base superalloys, 209–212, 221

Laves phase, 141, 143, 150
 Ni concentration, 141, 143
 Light water reactors, 117
 Lithium, additions to aluminum alloys, 200
 LRF. *See* Ladle refining furnace

M

M₃C carbide, 88, 108–109
 M₅B₃, 165
 M₆C carbide
 energy dispersive X-ray spectra, 94
 helium embrittlement, 132
 neutron irradiation, 137
 M₂₃C₆ carbide
 energy dispersive X-ray spectra, 94
 helium embrittlement, 132
 retardation during fusion breeder reactor, 137
 Magnetic fusion reactor, 117, 119–120, 123
 alloy development, 132
 design window, 120, 122
 Magnetic particle, indications in Ni-Cr-Mo-V rotor forgings, 74–75
 Manganese, as residual element, 70–72
 MAR-M200, creep, 213, 218
 MAR-M247, 212–214, 218
 Martensite, formation, 11
 MC
 B3 pretreatment, 133, 135
 formation, 124, 126–127
 grain boundary, 146, 148–150
 interface, clustered fine bubbles at, 144
 matrix, formation characteristics, 146, 150–151
 as nucleation multipliers, 125
 phase composition, 150
 Mechanical alloying, 238
 powder, 240

Mechanical properties, 83, 183–184, 202, 222
 nickel and nickel-iron aluminides, 230–233
 relationship with microstructure, 3, 7–38
 titanium alloys, 176
see also specific properties
 Metallography
 nickel and nickel-iron aluminides, 230–233
 Stirling engine, 278, 280, 284, 287
 Metal matrix, 290
 Microalloy region, composition under irradiation, 140
 Microcomposition, 116
 Mil-S-23194F, 48, 51–52
 Misfit dislocations, 207
 Mo₂C carbides, energy dispersive X-ray spectra, 88, 92
 Mu phase, 174–176
 MXON alloy, 212
 Co effect, 215, 218
 γ size effects, 215, 217

N

N-155, 272, 275, 283
 Nabarro-Herring creep, 29–31
 NASAIR 100
 Co content, 217
 precipitation, 212
 Neutron irradiation, 116–117
 phase stability and formation, 137–146
 Ni-Al-Nb, stress-strain response, 199
 Nickel, 141, 143, 165
 Nickel and nickel-iron aluminides, 222–236
 alloy design, 233–234
 boron-doped, fracture mode, 228, 231
 cold and hot fabrication, 232–234
 composition ranges, 234–235

correlation of strengthening potency to lattice strain, 225, 228
 crack-free weldments, 236
 creep, 227, 229–230, 233
 ductility, 198, 237
 dynamic embrittlement and environmental effects, 228–232
 effect of chromium additions, 229, 232
 hafnium additions, 226, 229
 intergranular fracture and microalloying with boron, 223–226
 mechanical and metallurgical properties, 230–233
 oxidation resistance, 231, 234
 solid solution hardening and strength improvement, 225, 230
 stress-strain response, 199
 sulfur attack, 236
 tensile properties, 230, 233
 yield stress, 197–198, 225, 227
 Nickel-base alloys, 274, 284
 Nickel-base superalloys, 184, 202–219
 compositions, 204
 creep around 1000°C, 204–214, 205
 annoying effects, 212–213
 creep anisotropy, 213–214
 γ' size effects, 207–209
 lattice mismatch, 209–212
 raft formation, 204–207
 creep around 760°C
 alloying effects, 215, 217–218
 creep anisotropy, 218–219
 γ' size effects, 215–216
 directional solidification, 202
 lattice mismatch, 221
 microstructure, 203–204
 misfit dislocations, 207
 single crystals, 203
 Ni-Cr-Mo-V steel, 49, 67

rotor forgings, magnetic particle indications, 74–75
turbine disk steel, low sulfur, yield strength, 76, 78–79
3.5Ni-Cr-Mo-V steel, 49, 53, 72
Nitrogen, residual element, 66–67
Nondestructive evaluation, 49

O

Ordered intermetallics, 197–199
Orowan looping, 215–216
Osprey process, 195
Oxidation, 222, 271
 attack parameter, 276–278
 resistance, 238
 nickel aluminides, 231, 234
 oxide dispersion strengthened alloys, 265–267
Oxide, formation, 26–27
Oxide dispersion strengthened alloys, 238–267
 boundary migration, 243
 boundary motion isotherm, 246–247
 composition, 239
 configurations of coarse grain initiation and growth, 246
 creep rupture, 249–258
 intermediate temperature strength improvements, 252–255
 structural effects on long-term rupture strength, 255–259
 dispersoid morphology after stress rupture testing, 258
 effect of alloy design on stress rupture characteristics, 257, 260
 fatigue, 262–265
 grain aspect ratios, 244, 246
 grain size, 242
 hot consolidated powder, 240–243
 hot corrosion, 265–267

mechanically alloyed power, 240
secondary recrystallization, 243–248
 isothermal annealing, 247–249
 zone annealing, 244–247
tensile properties, 259, 261–263
see also INCONEL alloy MA 6000, 243
Oxide rafts, image analysis, 170, 172–173
Oxide scale adherence, 286–287
Oxygen, residual element, 66–67

P

Phase
 classifications, 137, 139
 formation during irradiation conditions, 140–141
 stability, aged and irradiated steels, 137–140
Phosphide phase, 144
Phosphide precipitation, 151–154
Phosphorus, residual element, 59–60
Planar interlaced system, 291
Plasma arc melting furnaces, 58
Plastic zone size, 36
Point defects, 116–117
Post-consolidation thermomechanical processing, high temperature aerospace materials, 192
Post-weld heat treatment, 74, 76, 104–105
Post-weld reheat cracking, resistance to, 105
Powder metallurgy, 183–184
Power generation equipment, 3–42
 design aspects, 6–7, 39
 extrapolation to plant conditions, 42
 fabrication, 39
Prealloyed powders, 183–184

Precipitate phase, coarsening on dislocation mobility, 179, 181
 Precipitation, 116, 202
 Preform geometries, via spray deposition, 195
 Pressure vessel forgings, 47, 51–52
 Pressure vessel steels, 83
 development, 84
 see also Ferritic pressure vessel steels
 Processing science, 290

R

Radiation
 damage, 116
 resistance, 116
 Raft formation
 γ' size effects, 207
 lattice mismatch, 209–211
 nickel-base superalloys, 204–207
 Rapid solidification-hot consolidation, 183–184
 Rapid solidification processing, 176, 179, 198–199
 rate process, 188
 Rare earths
 oxides, dispersion/precipitation, 179
 residual elements, 68, 70
 Ratio of dislocation of cavity sink strength, 125
 Recovery-controlled creep, 29–31
 Recrystallization, 238
 secondary, oxide dispersion strengthened alloys, 243–248
 Reheat cracking, 47
 Remnant life assessments, 33–34
 Residual elements, heavy forgings, 47–79
 aluminum, 61, 63–64
 antimony, 65–66
 arsenic, 65–66
 boron, 67–70
 calcium, 67–68
 compositions of grades, 48

copper, 65
 embrittlement, 52–55
 hydrogen, 58–59
 manganese, 70–72
 nitrogen, 66–67
 oxygen, 66–67
 phosphorus, 51, 59–60
 pressure vessel forgings, 51–52
 rare earths, 68, 70
 silicon, 70–74
 sulfur, 51, 60–62
 tin, 65–66
 turbine rotor forgings, 48–50
 Resolved shear stress increase, 16
 Rheinstahl-Heraeus degassing, 56
 RIS. *See* Irradiation-induced solute segregation
 Rotating electrode process, 186–187
 Rupture life, grain aspect ratio effect, 246
 Rupture strength
 versus Larson-Miller parameter, 97–98
 long-term, structural effects, 255–259
 versus temperature, 251
 Rupture stress, versus rupture time, 64

S

Sanicro 32, 278, 280
 SC 7–14–6, creep, 213
 Scanning electron microscopy, 165
 fiber-reinforced composite microstructure, 167–168
 gas turbine materials, 167–170
 size distribution of microstructural features, 169
 X-ray energy maps, 169
 Segregation, 47
 Shape welding, 58
 SiC/SiC composites, 292–293
 Sigma phase, 150
 Silicon, 70–74, 119

Single crystals, 202–203
 Spray deposition, high temperature
 aerospace materials, 195–197
 Stainless steels, 3
 composition effect, 10–11
 creep deformation behavior, 31
 creep rupture, 22–24
 creep strength and composition, 39
 environmental effects, 16
 honeycomb carbide structure, 14
 irradiation effects, 26, 28
 metallurgical variables, 23–24
 properties related to ageing, 11–14
 role of metallurgical variables, 21
 tensile properties, 9–16
 thermal ageing, 11–13, 23
 thermomechanical treatment, 11
 toughness properties, 21
 welds, creep properties, 25
 Steel
 chemistries, 87
 clean, 47, 50, 53, 71
 grain size effect, 76–79
 hydrogen content, 56
 ingots, 50
 low alloy, 83
 microcleanliness, 59
 processing history, 85–86
 Steelmaking, 47, 49–50
 innovations, 55–58
 installed capacity, 58
 Stiffness matrix, 296
 Stirling engine, 271–288
 change in specific weight, 273–274
 hydrogen permeation and endurance tests, 280, 283–285
 materials, 273–274
 operation, 271–272
 oxidation and corrosion tests, 275–280
 attack parameter, 276–278

 electron microprobe analysis, 278, 280–281
 metallography, 278, 280
 weight change, 275–277
 X-ray diffraction, 278–279
 schematic, 272
 simulator materials test rig, 273–275
 Strain rate, 27
 Stress corrosion cracking, 47, 52–53
 Stress rupture, 238
 alloy 51, 252–254
 alloy design effect, 257, 260
 2.25Cr–1Mo steel, 105
 3Cr–1.5Mo steel, 105
 INCONEL alloy MA 754, 249–250, 252–253
 INCONEL alloy MA 956, 250–251, 253
 low chromium ferritic steels, 96–101
 Stress-strain, 290, 296
 Sulfides, 17, 60–61
 Sulfur
 attack, nickel and nickel-iron aluminides, 236
 effect on mechanical properties, 76, 78
 residual element, 60–62
 Superclean steels, 47

T

Tank degassing, 56
 Td-Ni-Cr, 243
 Temper embrittlement, 47, 49, 53, 83
 antimony, 65
 arsenic, 65
 composition, 54
 heat treatments used to assess susceptibility, 107
 low chromium ferritic steels, 106–108
 phosphorus role, 59
 tin, 65

Tempering parameter, Charpy V impact energies as function of, 89, 95

Tensile ductility, Cr-Mo-V steel, 66–67

Tensile elongation
boron addition effect, 224, 226
B3 pretreatment, 133–134
steels irradiated in HFIR, 131–132

Tensile properties, 7–18, 238
concrete, 8–9
ferritic steels, 16–18
graphite, 7–8
nickel aluminide, 230, 233
stainless steels, 9–16
uranium dioxide, 8–9

Tensile strength
austenitic stainless steels, 155–156
CW Type 316 stainless steel, 130–131
versus Larson-Miller tempering parameter, 94
low chromium ferritic steels, 89, 94–96
steels irradiated in HFIR, 131–132
versus temperature, 89, 96–98

Texture, 238

Thermally activated glide-controlled creep, 29–31

Thermal phase, 116, 137, 139, 145–146

Thermomechanical processing, 183–184, 238

Threshold stress, 238

Tin, residual element, 65–66

Titanium, 119, 165

Titanium alloys, 200
dislocation substructure, 176, 178
dispersion strengthened, 183
mechanical properties, 176

Titanium superalloy, ultra-fine array of dispersoid, 179–180

Toughness, 21–22
environmental interactions, 21–22
low chromium ferritic steels, 89, 94–96

Trepan boring, 50

Tubesheet forgings, Clinch River breeder reactor, 74, 76–78

Turbine rotor forgings, 48–50

Type 304 stainless steel, 21, 2, 3

Type 316 stainless steel
COD effects, 21
cold-worked, 123, 130–131
creep rupture properties, 23
fatigue endurance, 35
grain-boundary carbide and ferrite formation, 15
impact properties, 18–19
short-term thermal ageing, 11
time-temperature-transformation diagram, 14

U

Ultrasonic gas atomization, 188–189

Uniaxial modulus translation efficiency, 293

Uranium dioxide, 3, 8–9

V

Vacuum arc degassing, 57

Vacuum arc double electrode remelting, 58

Vacuum arc refining, 50, 56–57, 76

Vacuum carbon deoxidation, 50, 56, 70

Vacuum degassing, 56, 59

Vacuum oxygen decarburization, 57

Vacuum reladling, 56

Vacuum (soluble gas) atomization, 187

Vacuum stream degassing, 56

Vanadium, effects on early stages of tempering, 89

VAR, 50, 56–57, 76

VCD, 50, 56, 70

VOD, 57

Void

austenitic stainless steels, 117–118

suppression, helium-induced, 141

swelling, 117; *see also* Austenitic stainless steels, void swelling resistance

W

Waspaloy, 230, 233

Weldability, low chromium ferritic steels, 104–106

Weldment, 104–106, 236

Welds, creep properties, 25–26

metals, 25–26, 39

practices, 105

X

X-ray diffraction, Stirling engine, 278–279

X-ray spectrometers, 171

Y

Yield strength

versus copper content, 76, 78

equation, 259

as function of temperature, 259, 261

low sulfur Ni-Cr-Mo-V turbine disk steel, 76, 78–79

Ni₃Al, 197–198

Yield stress, 16

as function of hafnium concentration, 226, 229

as function of test temperature, 225, 227

irradiated steel specimens, 18

Yttrium, oxidation resistance, 169

Yttrium oxide, 238

Z

Zone annealing, oxide dispersion strengthened alloys, 244–247