



Vehicle, Tire, Pavement Interface

Henry/Wambold, editors



STP 1164

STP 1164

Vehicle, Tire, Pavement Interface

J. J. Henry and James C. Wambold, editors

ASTM Publication Code Number (PCN)
04-011640-08



ASTM
1916 Race Street
Philadelphia, PA 19103

Library of Congress Cataloging-in-Publication Data

Vehicle, tire, pavement interface / John J. Henry and James C. Wambold, editors.

(STP ; 1164)

Proceedings of the conference held Oct. 28, 1990, in Santa Barbara, Calif.

"ASTM publication code number (PCN) 04-011640-08."

Includes bibliographical references and index.

ISBN 0-8031-1483-4

1. Pavements—Performance—Congresses. 2. Pavements—Live loads—Congresses. 3. Pavements—Skid resistance—Congresses. 4. Trucks—Tires—Inflation pressure—Congresses. I. Henry, John J. (John Jewett), 1938—. II. Wambold, James C. III. Series: ASTM special technical publication ; 1164.

TE251.5.V44 1992

92-16574

625.8—dc20

CIP

Copyright © 1992 AMERICAN SOCIETY FOR TESTING AND MATERIALS, Philadelphia, PA. All rights reserved. This material may not be reproduced or copied, in whole or in part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of the publisher.

Photocopy Rights

Authorization to photocopy items for internal or personal use, or the internal or personal use of specific clients, is granted by the AMERICAN SOCIETY FOR TESTING AND MATERIALS for users registered with the Copyright Clearance Center (CCC) Transactional Reporting Service, provided that the base fee of \$2.50 per copy, plus \$0.50 per page is paid directly to CCC, 27 Congress St., Salem, MA 01970; (508) 744-3350. For those organizations that have been granted a photocopy license by CCC, a separate system of payment has been arranged. The fee code for users of the Transactional Reporting Service is 0-8031-1483-4/92 \$2.50 + .50.

Peer Review Policy

Each paper published in this volume was evaluated by three peer reviewers. The authors addressed all of the reviewers' comments to the satisfaction of both the technical editor(s) and the ASTM Committee on Publications.

The quality of the papers in this publication reflects not only the obvious efforts of the authors and the technical editor(s), but also the work of these peer reviewers. The ASTM Committee on Publications acknowledges with appreciation their dedication and contribution to time and effort on behalf of ASTM.

Printed in Baltimore, MD

June 1992

Foreword

This book represents the proceedings of the conference on Vehicle, Tire, Pavement Interface sponsored by ASTM Committee E-17 on Pavement Management Technologies. The conference was held in Santa Barbara, CA on October 28, 1990. John J. Henry and James C. Wambold were chairmen of the conference and are coeditors of this publication.

Contents

Introduction	vi
The Use of Semi-Active Suspensions to Reduce Pavement Damage—K. YI AND K. HEDRICK	1
Some Results from Ongoing Research on Road Roughness—R. R. HEGMON	14
Spectral Characteristics of Longitudinal Highway Profiles as Related to Ride Quality—G. F. HAYHOE	32
Pavement Damage as Related to Tires, Pressures, Axle Loads, and Configurations—P. E. SEBAALY	54
Dynamic Force Measurement Vehicle (DFMV) and Its Application to Measuring and Monitoring Road Roughness—S. C. ASHMORE AND H. C. HODGES, JR.	69
Vehicle Fatigue Induced by Road Surface Roughness—M. A. POELMAN AND R. P. WEIR	97
Measurement and Modeling of Truck Tire Traction Characteristics— B. T. KULAKOWSKI, M. CHI, AND C. LIN	112
A Review of Tire Traction—A. R. WILLIAMS	125
Past and Future Analysis of Moving Dynamic Loads on Structures—C. F. SHEFFEY	149
Impact Factors for Highway Bridges—H. V. S. GANGARAO	155
Structural Implications of Poor Bridge Surface Performance—B. S. YANEV	167

Overview

The vehicle and tire meet the pavement at the vehicle-tire-pavement interface. Successful and safe travel by land transportation over pavement or rail and by air transportation as it relates to taxiways and runways is fundamental to a country's economy. In this age of specialization, many separate groups from the highway, rail, vehicle, structures, and other communities are studying elements of the vehicle-tire-pavement interface, but true system designs are not being developed. In recent years there has been a shift toward a multidisciplinary approach in research, with each member of the research team contributing his or her expertise to the solution of a given problem. Representatives of the vehicle, tire, and pavement fields agree that coordination of their research and technologies is essential for successful and efficient design and operation of the transportation system.

This Special Technical Publication (STP) has been published as a result of the October 1990 Engineering Foundation Conference on the Vehicle-Tire-Pavement Interface, held in Santa Barbara, California, in an effort to provide a means for members with expertise in the various fields to share the state of the art in their own fields and to witness the potential benefits of collaboration. The cooperation of such organizations as the American Society for Testing and Materials, the Permanent International Association of Road Congresses, the Transportation Research Board, and the Federal Highway Administration led to the organization of this conference.

This volume serves as a record of the conference and makes papers available to a broader public. The 11 papers in this volume are presented in the order in which they were presented at the conference: experimental studies of full-scale systems, ride quality, trade-off analysis between vehicle and way, pavement-induced vehicle wear, traction, and the effect of vehicle dynamics on the design of structures. In some of these subject areas, much attention was focused on the increasing amount of truck traffic and its effects on the nation's highways.

Analytic Methods for Vehicle-Structure Problems

The Use of Semi-Active Suspension to Reduce Pavement Damage—Hedrick

The importance of semi-active suspension was discussed relative to the question, "Should suspensions be developed to reduce dynamic loads or should smoother pavements be designed?" Based on the results of computer modeling in one study, semi-active suspensions have the potential to reduce pavement damage by significantly reducing dynamic loads. Reducing road roughness and improving tire design (for traction, low wear, and low noise) and suspension (good handling and low pavement loading) are two areas noted for future investigation in addition to laboratory and field testing.

Experimental Studies of Full-Scale Systems

Roughness Effects on Vehicle-Pavement Interactions—Hegmon

This paper offers a brief overview of problems caused by road roughness and the extensive work done over the years to understand and alleviate the effects of road roughness, with the

major portion dealing with current work in the FHWA laboratory, the equipment and methods used, and the expected results. The objective of this study was to decrease pavement damage and therefore increase pavement life. Current research emphasis is on ways for increasing pavement life through a reduction of pavement damage by heavy truck traffic, and cooperation among the trucking industry, manufacturers, and users is necessary to arrive at the least damaging combination of trucks and highways. Pavement surface characteristics can certainly affect the highway user. While roughness per se is undesirable, other micro- and macrotextures are needed for good skid resistance on wet pavements. Interactions among rough pavements and heavy trucks, field and laboratory measurements, and computer simulations to predict the interaction forces are discussed as well. This research is leading to a better understanding of the dynamic interactions between heavy trucks and pavements and the detrimental effects of the factors involved.

Ride Quality

An Examination of the Spectral Characteristics of Longitudinal Highway Profiles—Hayhoe

Pavement profiles typically contain pulse-like disturbances that are hypothesized to have a significant effect on the perceived ride quality of the pavement. In the study reported in this paper, pavement profiles were compared to subjective ratings of ride quality in an effort to explain anomalies in the relationship between ride quality and profile characteristics. The relationship between the two measures is obtained from a panel rating study in the form of a regression equation giving the best statistical fit between the two measures. The roughness measures that give the best fit do not have clear physical interpretation in terms of the usually accepted characteristics describing the response of human subjects to vibration.

Trade-Off Analysis Between Vehicle and Way

Pavement Damage as Related to Tires, Pressures, Axle Loads, and Configurations—Sebaaly

The performance of highway pavements is directly related to the magnitude and frequency of the applied load. The way in which traffic loads are transferred to the pavement surface and to the entire pavement structure is controlled by the tire-pavement interaction mechanism. Tire inflation pressure, tire type, axle load, and axle configuration all affect the response of asphalt concrete (flexible) pavements. But which of these factors has the greatest influence on pavement response? Prediction models in theoretical analyses are often used to try to identify the critical factor or factors. In situ instrumentation of pavements provides a means to monitor the response of a pavement when subjected to various combinations of these factors.

Pavement-Induced Vehicle Wear

Dynamic Force Measurement Vehicle (DFMV) and its Application to Measuring and Monitoring Road Roughness—Ashmore

Different road roughness measurement systems are in use worldwide, systems that measure the profile directly and systems that measure vehicle response to road roughness. The DFMV fits into the first category but is unique because it uses force-motion measurements made at each axle end to define the terrain elevation, while the majority of profilometers use motion measurements only. The DFMV is a multipurpose test vehicle that has been used for several terrain, tire, and suspension studies, and one of its functions is to measure terrain elevation profiles. The DFMV was designed for off-highway profiling, so that long sections of rough

durability test courses could be profiled within a day. A wave-number spectrum proved to be an efficient and accurate technique for presenting long sections of various terrain types, including paved roads and off-highway durability test courses.

The DFMV measures the dynamic vertical, longitudinal, and side forces at the tire/ground interface at four individual wheel ends. The life of a vehicle can be accelerated by up to 20 to 1 by selecting a test course environment that is slightly rougher than the cross-country terrain. Two measurements are needed to describe completely the operating environment of the vehicle system from a fatigue standpoint, the terrain and the material fatigue curves showing the number of cycles versus stress for each material type in the vehicle. DFMV methodology is an accurate and established profile technique that can be used to measure and monitor test course severity and represents a meaningful step toward defining the life-cycle requirements of a particular type of vehicle.

Vehicle Damage Induced by Road Surface Roughness—Poelman

An experiment was conducted to determine surface roughness effects, as measured by a response-type meter, on vehicle suspension. Results suggest that greatly accelerated vehicle suspension fatigue damage occurs on road surfaces with measured road roughness less than 1.5 on a pavement serviceability index (PSI) scale. The important implication of this result is that vehicle manufacturers should be aware of how their vehicles are used in the real world and they should design vehicles that can accept road load input from roads with a 1.5 PSI rating or less. Also, when determining maintenance and resurfacing schedules, road planners should be aware of the point at which the operator may experience significant vehicle damage. If road surfaces deteriorate to less than 1.5, then operators will begin to have accelerated vehicle durability problems.

Traction

Measurement and Modeling of Truck Tire Traction Characteristics—Kulakowski

Braking performance of trucks is a critical element of highway safety. One of the most important variables affecting the braking performance of trucks is the frictional force developed between the truck tire and the road surface when brakes are applied. The frictional force, tire traction, depends on variables representing both the vehicle and the pavement surface characteristics. Tire traction characteristics are determined by forces generated at the tire-pavement interface as a result of driving, steering, and braking actions applied to the vehicle. The objective of this research was to measure the frictional forces for different trucks on different pavements under various speed and tire vertical load conditions during braking as well as combined braking and cornering maneuvers. The results were then used in an attempt to derive regression models representing tire traction parameters as functions of vehicle and pavement variables. Emphasis was placed on the significance of field tests versus laboratory and computer simulation because the results of field tests reflect all elements of the actual system.

A Review of Tire Traction—Williams

Road safety under wet conditions remains a major area of concern. It is an accepted fact that the risk being involved in a wet-weather accident increases with decreasing tread depth. This paper includes a review of the practical knowledge of tire-to-road friction relative to the tire tread pattern, tread compound, and road surface condition. Also discussed is the influence

on tire wet roadhold performance of unevenly worn tires versus normally reported evenly worn tire conditions. Results for truck tires as well as car tires are discussed, and the author suggests that continued improvements in new tire wet roadhold performance will only increase the difference between the new tire and the tire worn to the legal minimum tread depth. It is recommended that the difference between new and worn tires be reduced by increasing the minimum legal tread depth or by designing a constant performance tire.

Structures

The effects of vehicle dynamics on structures are discussed from three perspectives: historical, experimental, and practical (observational).

Past and Future Analysis of Moving Dynamic Loads on Structures—Scheffey

This paper presents a history of the problem of dealing with the effects of moving loads on a bridge. In recent years, better dynamic instrumentation has produced a resurgence of full-scale studies of highway, rail, and rapid transit bridges. The importance of tire and suspension system characteristics for pavement and safety problems has made some accurate data on these elements available. The author hopes to stimulate a broad perspective on the dynamic problems of all types of bridges and transportation structures.

Impact Factors for Highway Bridges—Gangarao

The problem of bridge vibrations due to moving truck loads has been under way for some time. This paper presents a critical review of the literature on impact or dynamic allowance factors and suggests modifications to the impact factor in the current AASHTO specifications for highway bridges by properly accounting for dominant bridge parameters other than span length. Impact values were found to be less than AASHTO's maximum value.

Structural Implications of Poor Bridge Surface Performance—Yanev

Specific to metropolitan New York City bridges, the NYC DOT Bridge Bureau inspected bridges under their responsibility and found that 42% needed complete rehabilitation. The remaining 58% need considerable structural repairs in order to avoid the need for premature rebuilding of that portion as well. A further step is the identification of structural components requiring repair or replacement and the optimal frequency of such measures. A program of rehabilitation is expected to result from this study. The elimination of certain problem-prone structural components from future design can be considered as well. Ultimately, schedules for timely repairs can be generated in order to extend the useful life of a bridge. The following structural components emerged as the primary sources of problems on most of the bridges: joints, drainage, and wearing surface (deck). No other bridge component other than joints deteriorates faster. In all these cases, problems originate at the roadway surface and rapidly propagate throughout the structure. The progress of this path of rapid deterioration is traced for several bridge types frequently encountered in New York. Measures used with varying levels of success in the elimination of the surface and structural deficiencies are described.

Santa Barbara Conference Participants

S. Colin Ashmore, Nevada Automotive Test Center
Alessandro Correra, Fondazione Politecnica, Italy

Hota Gangarao, West Virginia University
 James M. Giustino, General Tire, Inc.
 Gordon Hayhoe, Consultant
 Rudolph R. Hegmon, Federal Highway Administration
 John Jewett Henry, The Pennsylvania State University
 Bohdan T. Kulakowski, The Pennsylvania State University
 Byron N. Lord, Federal Highway Administration
 Wolfgang E. Meyer, The Pennsylvania State University
 Elena Molinaro, University of Rome, Italy
 Dick Parker, Strategic Highway Research Program
 George L. Parker, National Highway Traffic Safety Administration
 Mark A. Poelman, Chrysler Motors Corporation
 Michael N. Salgo, Consulting Engineer
 Ulf Sandberg, Swedish Road and Traffic Research Institute
 Charles F. Scheffey, Consulting Civil Engineer
 Frank W. Schmidt, The Pennsylvania State University
 Peter Sebaaly, University of Nevada-Reno
 Paul Senstad, Norway Public Roads Administration
 Susan L. Simoneau, The Pennsylvania State University
 Som P. Singh, Association of American Railroads
 Jorge B. Sousa, University of California
 Frank E. Timmons, Rubber Manufacturers Association
 James C. Wambold, The Pennsylvania State University
 A. R. Williams, SP Tyres UK Limited
 Bojidar S. Yanev, New York Department of Transportation

J. J. Henry

Penn State University,
 Penn. Transportation Institute,
 University Park, PA 16802.
 conference cochairman and coeditor.

James C. Wambold

Penn State University,
 Penn. Transportation Institute,
 University Park, PA 16802.
 conference cochairman and coeditor.

ISBN 0-8031-1483-4