

Subject Index

A

Acicular ferrite, *see* Intragranular ferrite plates

AFNOR NF A 81460, 195

AISI 1215 steel, 51-66

chemical analysis, 53, 56

experimental procedure, 53

hardness, 53, 58

machinability, 54-55, 58, 60-64

MnS inclusion

aspect ratio, residual effect, 53, 59

size, residual effect, 53, 58

oxide inclusion, 53-54, 59

properties, 53-54, 56-59

residual levels investigated, 52-53

roto-bar rejection rate, 53, 56

tensile ductility and strength, residual effect, 57

Alloy steel

high strength, 266

relative cost of restricting residual levels, 32-33

Alumina inclusions, machinability, 72

Aluminum

content during ladle refining, 42-43

deoxidation constant, 41

Aluminum oxide, 76

Arc length, 243-258

back-gouging, 257

deposit nitrogen and oxygen level effects, 251-256

SMA electrodes, 257

specimen extraction and testing, 248

Ashby-Orowan equation, 225

ASTM Standards

A 20/A20M-86a, 117

A 240-85, 151, 153

A 242, 34

A 255-67, 36

A 262-85a, 150, 154, 158-162, 164

A 266-69, 115

A 266-84a, 114, 117, 123

A 266-85, 115

A 269-85, 151, 153

A 352/A 352M-85, 122

A 376, 6

A 430, 6

A 450/A 450M-86A, 151, 153

A 480/A 480M-84A, 151, 153

A 508-84a, 100-101, 107, 114, 117

A 508/A 508-86, 115

A 516/A 516M-84, 196

A 530/A 530M-85a, 151, 153

A 533/A 533M-85b, 100-101, 106

A 588, 34

A 751, 1

A 771-83, 124-125

A 788, 202, 208

A 858/A 858M-86, 122

A 860/A 860M-86, 122

E 8, 212

E 23, 212

E 45-76, 193

E 112, 125, 212

E 139-83, 126-127

E 618-81, 51, 53

G 5-82, 154

G 31-72(1985), 154

G 48-76(1980), 154

Auger spectroscopy, 100

Austenitic stainless steel

carbide contents, 160

high temperature ductility, 164

see also Titanium stabilized austenitic stainless steel

Austenitization

martensitic 12% chromium steel, 88

temperature, 113

Automatic screw machine test, 53-54

Axisymmetric specimens, 100

B

Ball bearing steels, calcium, 70

Biaxial stress rupture

tests, D91, 127

titanium stabilized austenitic stainless steel, 132, 135

Borides, 163

Boron, 150

corrosion resistance of Type 304 stainless steel and, 152

D9 levels, 125-126

stress rupture life effect, 128-130

Boron (cont.)

- tertiary creep and, 146
- titanium stabilized austenitic stainless steel effect, 145-147
- see also* Titanium stabilized austenitic stainless steel
- British Standards 4060 50E, 169
- British Standards 5762:1979, 175

Butt weld

- Charpy toughness, 180-184
- chemical analyses, 174-177
- crack tip opening displacement, 184-185
- cutting scheme, 174
- fractographic examination, 186-188
- microstructural observations, 177-179
- tensile and hardness data, 179-183

C

Calcium

- alloys, *see* Inclusion control
- ball bearing steels, 70
- carbo-nitriding, 70-71
- cleanness and, 69-72
- cold upsetting, 71-72
- fatigue life, 70-71
- machinability, 72-73

Calcium-aluminum, deoxidation constant, 41

Calcium oxide, 77

Calcium sulfide, 77

Carbides, 83, 150

- martensitic 12% chromium steel, 98-99
- precipitation reactions, 215
- strengthening, 202, 227

Carbaborides, 163

Carbon

- content effect on heat affected zone toughness, 269, 271-273
- equivalent, 114, 120-122
- interstitial, 225
- segregation, negative, 114

Carbo-nitriding, calcium treatment, 70-71

Carbon-manganese steels, 169, 243

- welds, mechanical property, 179, 181

Carbon steel forgings, 114

- chemical composition, 115, 122
- heat analyses and product analyses, 117, 119
- heat treatment, 114, 116-117
- impact test results, 117-118
- mechanical property test locations, 114, 116
- results, 117-120

Caustic embrittlement, 5-6

Charpy impact test

- fracture appearance transition temperature, 269, 271
- weld metal, 239-240

Charpy toughness, 100, 170

- butt weld, 180-184
- DC straight polarity deposits, 186
- de-embrittling treatment, 104, 106
- forged and plate steel, 106, 108

Charpy V notch

- fracture energy, 104
- impact test properties, X-70 line pipe steel, 291-292
- specimens, 103, 288
- transition curves, heat affected zone, 294

Chromium, 51

Cleanness, calcium treatment and, 69-72

Cleavage, 100

- isolated regions, welds, 186, 188
- stress, critical, 108, 110

Clinch River breeder reactor, 203

C-Mn-Ni welds, 179, 182-183

Cold cracking

- heat affected zone, 296
- hydrogen induced, 296-297

Cold formability, residuals and, 35-36

Cold upsetting, calcium treatment, 71-72

Columbium-vanadium steel, low carbon, 286

Compact tension specimens, 103

Constituent ratios

- LN steel, 275-276
- Ti-oxide bearing steel, 275-276

Continuous casting, 26

- growth of, 28
- percent of U. S. production, 28
- trends, 11, 13

Continuous cooling transformation diagram

- LN steel, 273-274
- Ti-oxide bearing steel, 273-275

Copper, 51, 150, 202-227

- average monthly residual, scrap, 19, 21
- corrosion resistance, 208

- Type 304 stainless steel and, 151-152, 154-158

dilatometry, 212

- factors favorably affecting hot workability, 34

hardenability, 208

iron-copper phase diagram, 207-208

laboratory-produced steels, 221-223

light microscopy, examination, 212

load-elongation curve, 224

machinability and, 51-52

materials, 204-206

particles, 215-216, 220

precipitation, grain boundary, 213, 218
 procedure, 209-212
 regression analysis, scrap, 16, 19
 restriction, hot shortness and, 34-35
 tensile/impact testing, 212
 values of purchased scrap grades, 22
 yield strength, 224
 annealed, 224
 PWHT/AC, 226-227
 PWHT/FC, 224-226
 see also Weld metal, embrittlement
 Copper alloys, elimination, 7
 Corrosion, 7
 Corrosion resistance
 copper and, 208
 Type 304 stainless steel, 150-165
 boron effects, 152
 copper and molybdenum effects, 151-152, 154-158
 corrosion rates, 158
 effect of alloy boron content and sensitizing treatment, 161-162
 intergranular corrosion rates, 158-159
 materials, 152-154
 potentiodynamic anodic polarization curves, 155-157
 reference standards, 160
 Counterfeit bolts, 25
 Cracking
 hydrogen induced, 286
 solidification, 297
 Crack tip opening displacement, 169, 175
 butt weld, 184-185
 C-Mn-Ni deposits, 188
 scatter in values, 189-190
 Creep, 124
 Creep resistance, 83
 Creep test, martensitic 12% chromium steel, 96-97
 CrMo steel, HAZ tempering characteristics, 264-265
 2-1/4Cr-1Mo steel, 202
 chemical analysis, 205
 critical temperatures, 213
 laboratory-produced
 residual copper, 221-223
 yield and tensile strengths, 223
 CrMoV steel, HAZ tempering characteristics, 264-265
 Current supply, 243-258
 AC, 244
 DC reverse polarity, 186
 deposit nitrogen and oxygen level effects, 251-256
 SMA welding, 243-244
 welding, 170, 174

D

D9, 124-125
 boron effect
 ductility, 130-131
 stress rupture life, 128-130, 132-134
 creep curves, modified by additions of boron phosphorus, 130
 in-reactor creep behavior, 135, 139-141
 neutron-induced swelling, 141, 143
 phosphorus and boron levels, 125-126
 phosphorus effects
 ductility, 130-131
 stress rupture life, 128-129
 precipitate-free zones, 146
 swelling behavior, 136, 139
 unirradiated, 133-139
 as-received condition, 136
 carbide and Laves distribution, 135, 138
 creep cavitation, 134, 137
 high phosphorus-high boron heat, 135, 138
 MC precipitates, 135, 139
 phase identification, 134-135, 137
 D9I, 127-128
 Deoxidation, 38
 Deoxidation constant, aluminum, 41
 Dephosphorization, 40
 Desulfurization, 38
 Diffusion deoxidation, 43-44
 Dilatometry
 production forgings, 213
 residual copper, 212
 DIN 50602, 193
 Dissociation, ladle lining, 42-43
 Dropweight tear test, 300
 Ductile to brittle transition temperature, 101, 107-108
 Ductility, optimum, 261

E

Electric arc furnaces, 26
 Electric furnace steelmaking, 26-27
 trends, 11-12
 Electron microscopy, *see* Production forgings
 Electroslag remelting, 202, 204, 206
 ferrite matrix, 216, 220
 Embrittlement, effect of phosphorus segregation, 296
 End quench hardenability test, 36
 Engineered bar products
 maximum levels of residual content, 29
 nickel-copper ratio, 34
 Erosion-corrosion, in feedwater and wet steam piping, 7

F

Fatigue life, calcium treatment, 70-71
 Fatigue limit, versus tensile strength, 70-71
 Fe-Al-Ca-O-S system, equilibrium diagram, 73-74
 Ferritic steel, *see* Sulfur, weldability and Formability, 26
 Fractography, temper embrittlement, 103-104
 Fracture appearance transition temperature, 300
 charpy impact test, 269, 271
 sulfur content and, 278-279, 281
 X-70 line pipe steel, 291
 Fracture surface
 heat affected zone, 296-296
 martensitic 12% chromium steel, 93, 96
 microstructure below, 279, 281
 Fracture toughness, 7, 104-105, 169
 effect of reausenitization and temper, 104, 107
 temper embrittlement, 104-105
 Free-machining steel, 51
 Fuel cladding, 125
 Furnace, advanced procedures, 14

G

Galvanized material, in scrap, 24
 Gas metal arc weld, 193
 Gas-shielded welding, nitrogen, 256-257
 Grain size, 266
 Graphitization, 5-6

H

Hardenability, 26
 end quench test, 36
 residual copper, 208
 residual levels and, 36-37
 Hardening
 dynamic strain, 238
 see also Precipitation hardening
 Hardness, 261
 AISI 1215 steel, 53, 58
 butt welds, 179-183
 martensitic 12% chromium steel, 88, 90-93
 postweld heat treatment, 263
 X-70 line pipe steel, 293-294
 see also Underbead hardness
 Heat-affected zone, 261-262, 266-267
 charpy V notch transition curves, 294
 cold cracking, 296
 fracture surfaces, 296-296
 mechanical properties, 293-296

 microstructure, 269
 niobium content, 271-272
 scanning electron fractographs, 295
 shelf energy, 295
 simulated coarse-grained microstructure, 290
 tempering characteristics of CrMo and CrMoV steels, 264-265
 toughness, 286, 296
 carbon or niobium content effect, 269, 271-273
 heating temperature effect, 269, 271
 test, 267
 underbead hardness, 192
 weld thermal cycle, 288-289
 Heat analyses and product analyses, carbon steel forgings, 117, 119
 Heat treatment, 101, 103
 carbon steel forgings, 114, 116-117
 inter-critical, 114, 117
 temper embrittlement, 101, 103
 Hollomon-Jaffe parameter, 261-262
 Homogenization
 martensitic 12% chromium steel, 85, 87
 temper embrittlement, 113
 Hot ductility test, 6
 Hot shortness, 26
 copper restriction, 34-35
 Huey test, 159-160, 164
 Hydrogen, 192
 induced cold cracking, 296-297
 induced cracking, resistance, 286
 sensitivity and sulfur, 198
 weld deposit content, 195
 weldment effects, 196-197

I

Impact test
 carbon steel forgings, 117-118
 martensitic 12% chromium steel, 93, 95
 residual copper, 212
 Impact toughness, 169, 285
 laboratory-produced steels, 222-223
 Inclusion, 192, 266
 composition, predictive model, 73-76, 78
 control
 aluminum oxide, 76
 calcium oxide, 77
 calcium sulfide, 77
 calcium treated steels, 73-79
 shape control, 297
 harmfulness, 70
 oxide, AISI 1215 steel, 53-54, 59
 phase analysis, 76-79
 precipitation path, 74, 76

In-reactor creep, titanium stabilized austenitic stainless steel, 145
 In-reactor stress rupture, titanium stabilized austenitic stainless steel, 135-136, 139-141
 Intragranular ferrite plate, 267
 area ratio and length of ferrite side plate, 280, 282
 cooling time effects, 275-277
 fine-grained structure, 296
 formation, 266, 272-273
 toughness effect, 279-282
 nucleus, 269
 formation, 278-281
 nucleation
 cooling time effect, 276-277
 by Ti_2O_2 particle, 281-283
 transformation
 effect of MnS, 278-279, 281
 effect of thermal history in austenite region, 278, 280
 Intergranular rupture, 100
 Iron-copper phase diagram, 202, 207-208, 225
 ferritic region, 207, 209
 Iron-oxide, slag content, 44-45
 Irradiation-induced swelling, titanium stabilized austenitic stainless steel, 136, 139, 141-143
 Isothermal transformation diagram, 88-93

J

Jominy test, 36

L

Ladle
 phosphorus removal, 47
 lining, 38
 dissociation, 42-43
 influence on deoxidation effect, 43-44
 refining, 38
 effect of slag type, 41-42
 procedure, 40
 Larson Miller parameter, representation of in-reactor creep rupture, 141, 143-144
 Lateral expansion transition temperature, X-70 line pipe steel, 291
 Light microscopy
 laboratory-produced steels, 221-222
 production forgings, 213, 216
 residual copper, examination, 212
 LN steel
 constituent ratios, 275-276

continuous cooling transformation diagram, 273-274
 microstructure, 273, 275
 quenching on cooling stage, 275-276
 Local rupture criterion approach, 110

M

Machinability, 51, 69
 AISI 1215 steel, 54-55, 58, 60-64
 finish formed surface roughness, 54, 61-62
 rake face, 54-55, 62
 surface roughness, 55, 63-64
 test conditions, 55
 tool life, residual effect, 54, 60-61
 calcium treatment, 72-73
 copper and, 51-52
 effect of aluminum and calcium to oxygen ratio, 72
 evaluation, 53, 55
 steel Grade 4140, 73
 Martensite island, high carbon, formation, 277-278
 Martensitic 12% chromium steel, 83-99
 austenitization, 88
 carbides, 98-99
 chemical composition, 85-86
 comparison between standard and super-clean heat dilatometry, 87-88
 creep test, 96-97
 dilatometric results after austenitization, 88-89
 fracture surfaces, 93, 96
 hardness, 88, 90-93
 homogenization treatment, 85, 87
 influence of cooling rate on structure, 88, 91-92
 mechanical properties after quenching and tempering, 93-97
 mechanical tests, 87
 pure heat procedure, 85-86
 quenching, 87
 research objectives, 84
 structural examination of impact test pieces, 96
 super clean heat, 83, 85
 tempering temperature, 87
 tension test, 88, 90, 93-94
 transformation temperatures, 88-93
 MC precipitates, uniaxial stress rupture, 135, 139
 $M_{23}C_6$ type carbides, production forgings, 215, 217
 Melting yield, scrap, 14
 Microalloyed steels, 285

Microbial corrosion, 7

Microsegregation, Ti-oxide bearing steel, 269

Microstructure

LN steel, quenching on cooling stage, 275-276

Ti-oxide bearing steel, quenching on cooling stage, 275-276

Mixed sulfur, formation, 78

MnS

IFP transformation effect, 278-279, 281

inclusion aspect ratio, AISI 1215 steel, residual effect, 53, 59

inclusion size, AISI 1215 steel, residual effect, 53, 58

Molybdenum, 150

corrosion resistance of Type 304 stainless steel and, 151-152, 154-158

M₂X carbides

molybdenum/chromium ratios, 213, 315, 226-227

production forgings, 213, 218-219, 226-227

M₂X carbonitrides, 219, 221

N

Neutron-induced swelling, 141-143

Nickel, 51

Nickel-copper ratio, engineered bar products, 34

3.5% NiCrMoV steel, 38-39

Niobium, content effect on heat affected zone toughness, 269, 271-273

Nitrogen, 169, 243

deposit contents, 255-257

arc length and current supply effects, 251-256

gas-shielded welding, 256-257

welds, 186

interstitial, 226

pick-up during welding, 243-244

requirement, 7

Notch toughness, 232

O

Obsolete scrap, 29

Oxide inclusion, AISI 1215 steel, 53-54, 59

Oxygen, 169, 243

deposit contents, 176-177, 254-255

arc length and current supply effects, 251-256

pick-up during welding, 243-244

transportation mechanism in slag, 46

P

Phosphorus, 285-300

D9 levels, 125-126

increase in transition temperature, 297

microsegregation, 101

removal, ladle, 47

segregation, embrittlement effect, 296

stress rupture life effect, 128-129

titanium stabilized austenitic stainless steel effect, 145-147

see also Titanium stabilized austenitic stainless steel

Polarity, 169-170, 177, 243

deposit nitrogen and oxygen level effects, 251-256

Postweld heat treatment, 202-203, 232, 261-265

AC condition, production forgings, 216-217, 221

FC condition, production forgings, 213, 215-216, 219-220

hardness, 263

heat affected zone tempering response, 262-263

procedure, 262-263

temperature-time relationships, 262

Postweld stress relief heat treatment, 237

Precipitation

hardening, 232, 236, 238

strengthening, 202

Pressure vessel, 100

Pressurized water reactor, 100

Probability of cleavage fracture, 110, 111

Production forgings, 213-221

dilatometry, 213

electron microscopy, 213, 215-221

annealed, 213, 217-218

PWHT/AC, 216-217, 221

PWHT/FC, 213, 215-216, 219-220

eutectoid phase, 213, 217

iron-copper phase diagram, 225

light microscopy, 213, 216

load-elongation curves, 213, 215

M₂₃C₆ type carbides, 215, 217

M₂X carbides, 213, 218-219, 226-227

Purchased scrap, 11, 29

Q-R

Quenching, martensitic 12% chromium steel, 87

Reactor pressure vessel steels, 7

Refinement, 146

Revert scrap, 29

Rupture, fractographic aspects, 104-105

S

- Scrap, 28-31
 - charges, 32-33
 - chemistry, 15-16, 19
 - continuous casting, 28
 - copper levels, hot shortness and, 34-35
 - electric arc furnace steelmaking, 26
 - "free of alloys", 29
 - grade, 16, 18
 - home, residual levels and, 65
 - homogeneity, 16
 - inclusion of galvanized material, 24
 - inspection, 15-17
 - management for residual control, 32-33
 - material segregation, 19-21
 - melting yield, 14
 - number 1 bundle price trend, 32
 - obsolete, 29
 - versus other raw materials, 15
 - production as percent of consumption, 13
 - purchased, 11, 29
 - ratio of purchases to steel produced, 11-12
 - regression analysis, 16, 18
 - relative cost to control residual levels, 32-33
 - residual levels
 - cold formability and, 35-36
 - control, 24
 - hardenability and, 36-37
 - revert, 29
 - shredded
 - copper content, 23
 - density, 23
 - size and density, 14-15
 - sources, 14
 - specifications, 15
 - suppliers, 22-23
 - trends in steel industry, 11-14
 - types, 30-31
 - Segregation, 100
 - Sensitization, 150
 - Shield metal arc welding, 169-170, 193, 243
 - electrodes, arc length, 257
 - current supply, 243-244
 - Slag, 38
 - chemical composition, 41-42
 - iron-oxide content, 44-45
 - oxygen transportation mechanism, 46
 - Solidification cracking, weld, 297
 - Solid-solution strengthening, 202, 207-208
 - Steam generator, 202-203
 - Steam turbines, super critical, 83
 - Steel
 - chemical analyses, 171, 194, 211, 245, 268
 - Grade 4140, machinability, 73
 - industry trends, 11-14
 - low carbon, 266
 - low temperature service, 266
 - making, 192
 - percent of U. S. production by furnace type, 27
 - producers, 11
 - U. S. raw steel capability, 27
 - Strain aging, welds, 188-189
 - Stress corrosion, 5
 - Stress rupture, 124-126
 - Stress-strain behavior, serrated, 242
 - Submerged arc weld, 285
 - Sulfur
 - constant and fracture appearance transition temperature, 278-279, 281
 - content, X-70 line pipe steel, 286
 - weldability and, 192-201
 - critical preheat temperature, 196-200
 - hydrogen sensitivity, 198
 - materials, 192-194
 - stress direction, 196-197, 199-200
 - sulfide shape, 199-200
 - underbead hardness, 195-196, 198
 - welding conditions, 196-198
 - welding tests, 193, 195
 - Super-clean heat, 83, 85
 - dilatometry, 87-88
 - influence of cooling rate on structure, 88, 92
 - Super clean steels, production, 38-46
 - equipment and sequence, 40
 - experiments, 39-40
 - Surface roughness, AISI 1215 steel, residual effects, 55, 63-64
 - Swelling, 124-125
 - D9, 136, 139
 - neutron-induced, 141-143
 - resistance, D9I, 128
 - titanium stabilized austenitic stainless steel, 145
- T**
- Temper embrittlement, 38, 100-113
 - auger electron spectroscopy, 106-107, 109
 - fractography, 103-104
 - heat treatment, 101, 103
 - homogenization, 113
 - materials, 101-102
 - onset susceptibility, 113
 - reversible, 101
 - specimens and mechanical tests, 103
 - Tempering response, 261
 - Tempering temperature, martensitic 12% chromium steel, 87
 - Tensile ductility, AISI 1215 steel, residual effect, 57

- Tensile/impact testing, residual copper, 212
 Tensile strength, 114-123, 232
 against product analysis carbon content, 120-121
 AISI 1215 steel, residual effect, 57
 butt welds, 179-183
 fatigue limits versus, 70-71
 laboratory-produced steels, 221-223
 production forgings, 213-215
 residual copper, 212
 step cooled and de-embrittled smooth specimens, 104, 107
 test
 martensitic 12% chromium steel, 93-94
 weld metal, 234-237
 X-70 line pipe steel, 288
 X-70 line pipe steel, as-rolled plates, 290-291
 Ti₂O₃ particles, stability, 266
 Ti-oxide bearing steel, 266-283
 CMA patterns, 273
 constituent ratios, 275-276
 continuous cooling transformation diagram, 273-275
 effective grain size, 279, 282
 high carbon martensite island formation, 277-278
 IFP nucleus, analysis, 269-270
 microsegregation, 269
 microstructure, 273, 275
 analysis, 269
 quenching on cooling stage, 275-276
 shelf energy, 295
 size and distribution of martensite-austenite constituent, 278-279
 specimen preparation, 267-268
 transformation characteristics from γ to α , 269
 see also Heat affected zone
 Titanium stabilized austenitic stainless steel, 124-147
 biaxial stress rupture, 132, 135
 effect of phosphorus and boron, 145-147
 experimental procedures, 125-128
 in-reactor creep, 145
 in-reactor stress rupture, 135-136, 139-141
 irradiation-induced swelling, 136, 139, 141-143
 neutron-induced swelling, 141-143
 swelling, 145
 uniaxial stress rupture, 128-134, 143-145
 Tool life, residual effects, AISI 1215 steel, 54, 60-61
 Toughness, 100, 266
 influence of composition, 186, 188
 welds, 186, 188-190
 Transformation temperatures, martensitic 12% chromium steel, 88-93
 Tubesheet forgings, 202-204
 comparison of ESR and VAR, 210
 copper level, 208
 cross section, 204
 heat treatment cycles, 204, 206, 210
 yield strength, 204, 207
 Turbine rotors, 38, 83
 martensitic 12% chromium steel, 97
 Type 304 stainless steel, 6-7
 ASTM compositional specifications, 151
 modified
 chemical composition, 153
 corrosion test results, 156
 potentiodynamic anodic polarization curves, 156-157
 weldability, 164
 see also Corrosion resistance, Type 304 stainless steel
 Type 316 stainless steel, 6, 125
 Type 316 LN stainless steel, weldability, 163-164
- ## U
- Underbead hardness, 195-196, 198
 heat affected zone, 192
 Uniaxial stress rupture
 boron effect, 128-130, 132-133, 143-144
 creep curves, 130
 distribution of carbides and Laves, 135, 136
 ductility, 130-131
 MC precipitates, 135, 139
 phase identification, 134-135, 137
 phosphorus effect, 128-129, 132-133, 143-144
 titanium stabilized austenitic stainless steel, 128-134, 143-145
 creep cavitation, 134, 137
 Unspecified elements, service experience related to, 5-8
- ## V
- Vacuum arc remelting, 202, 204, 206
 Void swelling, 124-125
- ## W
- Weathering steel, 232
 Weld, 169-191
 charpy toughness, root and subsurface regions, 180, 184
 CTOD scatter in values, 189-190
 deposit hydrogen content, 195

deposit nitrogen contents, 186, 188
 isolated regions of cleavage, 186-188
 local initiation at large inclusion, 186-187
 mechanical property, 179, 181-183
 mechanical testing, 174-175
 metallographic and fractographic examination, 175, 177-179
 oxygen contents, 176-177
 solidification cracking, 297
 straight and reverse polarity, 177
 strain aging, 188-189
 toughness, 186, 188-190
 transverse sections, 177-178
 vertical-up, 179-180, 183
 strain aging, 189
see also Butt weld
 Weldability, 5, 266
 Type 304 stainless steel, 164
 Type 316 LN stainless steel, 163-164
see also Sulfur, weldability and
 Welding
 current supply, 170, 174, 244
 equipment, 169
 parameters, 195
 procedure, 246, 248
 vertical-up, 169
 Welding electrodes, 170, 172-173, 244, 246
 chemical analyses, 246-247
 coating, 246, 249
 handling characteristics, 248
 oxygen levels, 252, 260
 Weld metal, 169, 243
 as-deposited, 177-178
 charpy impact test, 239-240
 embrittlement, 232-242
 chemical composition of materials, 234
 fracture appearance transition temperature, 234, 240
 location of mechanical test specimens, 234
 postweld stress relief heat treatment, 237
 procedure, 233-234
 serrated stress-strain behavior, 242
 upper shelf energy test, 241

 yield strength, 236, 238-239
 reheated, main initiations point, 186-187
 tensile test, 234-237
 Weld pad, chemical analyses, 248, 250-251

X

X-70 line pipe steel, 285-300
 as-rolled plates, mechanical properties, 290-292
 Charpy V notch impact properties, as-rolled plates, 291-292
 chemical composition, 286-287
 economics, 286
 fracture appearance transition temperature, 291
 hardness, 293-294
 lateral expansion transition temperature, 291
 materials, 286-288
 mechanical property tests, 288-289
 metallographic and fractographic studies, 289
 microstructure, 289-290
 pass temperatures during rolling, 286, 288
 phosphorus content, 297
 segregation tendency of phosphorus, 296
 shelf energy, 285
 solidification cracking, 297
 splitting tendency, CVN specimens, 292-293
 sulfur content, 286
 tensile properties, as-rolled plates, 290-291
 tension tests, 288

Y

Yield strength
 residual copper, 224
 annealed, 224
 PWHT/AC, 226-227
 PWHT/FC, 224-226
 tubesheet forgings, 204, 207
 weld metal, embrittlement, 236, 238-239