

Subject Index

A

Adhesive joints, stress analysis and energy release rate, 580
 Aluminum alloy
 crack-tip opening angle, 90
 large-scale thin-sheet, 451
 mixed mode I/II loading, 105
 Anisotropic solids, cracks, boundary element method, 517
 ASTM A 533, 352
 ASTM E 399, 31
 ASTM E 1152, 406

B

Beam-truss elements, 580
 Biaxial stress effect, 31
 Boundary element method, cracks in anisotropic solids, 517
 Boundary force method, stress intensity factor, 530
 Brittle fracture, 550
 constraint effect, 31

C

Calibration, stress intensity factor, 530
 Chell WPS model, 243
 Cladding, 387
 Cleavage fracture, local approach, 387
 Coach-peel specimen, 469
 Constraint, 175, 367
 brittle fracture, 31
 modelling, crack growth, 72
 Contact stresses, pin-loaded lug joints, 598
 Corner crack, 563
 Crack aspect ratio, 550
 Crack closure, 301, 317, 352
 Crack depth, effect on fracture toughness, 175
 Crack depth to width ratio, 175
 Crack geometries, 216
 Crack growth
 constraint modelling, 72
 initiation, 72
 stable, 61, 105
 subcritical, 3

Crack growth resistance
 geometry and size effects, 126
 mismatched weld joints, 427
 Crack initiation
 mixed mode I/II loading, 105
 S-N curve, 352
 Crack interacting factor, 550
 Cracks
 anisotropic solids, 517
 perforate titanium, 490
 Crack shape, 352
 Crack surface, morphology, fracture behavior and, 152
 Crack surface friction, 152
 Crack tip
 ductile-brittle transition, 27
 stress fields, 31
 Crack tip opening angle
 mixed mode I/II loading and grain orientation, 105
 plane stress, 61
 stable tearing and fracture prediction, 90
 Crack tip opening displacement, 105
 crack depth and, 175
 Crack tip plastic zone, 287
 Crack-tip stress strains, 216
 Crack-tip stress triaxiality, 367
 Cyclic loading, ductile tearing, 406

D

Deformation, inelastic, 598
 Delta J , 317
 Dislocations
 anisotropic solids, 517
 mobility, hydrogen effects, 338
 Dodds-Anderson scaling model, 367
 Ductile-brittle transition, fracture, 27
 Ductile tearing
 cyclic loading, 406
 welded structural details, 201

E

Edge-notched beam, stress intensity factor calibration, 530

Elastic analysis, interaction between surface cracks, 550
 Elastic-plastic analysis, pin-loaded lug joints, 598
 Elastic-plastic fatigue crack growth, 317
 Elastic-plastic fracture, 61
 mechanics, 267
 mismatched weld joints, 427
 Elastic-plastic notch tip stresses and strains, 613
 Elastomeric materials, fatigue crack growth damage, 505
 Embedded crack, 563
 Energy dissipation rate, 126
 Environment
 absorbed hydrogen effect, 338
 natural rubber, 505
 η -factor method, 367

F

Fatigue crack, nucleus size, 352
 Fatigue crack growth, 287
 damage, elastomeric materials, 505
 near-threshold, absorbed hydrogen effect, 338
 perforate titanium, 490
 pin-loaded lug joints, 598
 short crack, 301
 Fatigue crack propagation, thresholds, 267
 Finite element analysis
 crack depth role, 175
 crack-tip opening angle, 90
 ductile tearing, 406
 energy dissipation rate, 126
 full-thickness clad beams, 367
 pin-loaded lug joints, 598
 stable tearing analysis, 201
 stress intensity factor, 530
 stress-strain response, 216
 two and three dimension adhesive elements, 580
 warm prestress data, 243
 weight function method, 563
 Fractography
 natural rubber, 505
 pin-loaded lug joints, 598
 Fracture, crack-tip opening angle, 90
 Fracture analysis, full-thickness clad beam specimens, 367
 Fracture mechanics, 287
 constraint modelling, 72
 large-scale thin-sheet aluminum alloy, 451
 natural rubber, 505
 two and three dimension adhesive elements, 580
 underclad cracks, 387
 Fracture resistance, cyclic loading effect, 406
 Fracture stress, 31

Fracture toughness
 A533-B steel, 175
 brittle fracture, 31
 cyclic loading effect, 406
 finite element analysis, 367
 J-Q model, 27
 large-scale thin-sheet aluminum alloy, 451
 underclad cracks, 387
 Front solver, 550
 Full-thickness clad beams, fracture analysis, 367

G

Geometry effects, 126
 Grain orientation, 105
 Griffith's criterion, 505

H

Hydrogen, absorbed, effect on microstructure, 338

I

Impact failure, resistance spot welds, 469
 Instability, energy dissipation rate, 126
 Integral equation, 152
 Interference fit, 598
 Internal stresses, 301
 Iosipescu beam, 530

J

J-integral, 61, 175, 406
 energy dissipation rate, 126
 stable tearing analysis, 201
J-Q methodology, 367
 crack growth experiments, 72
 fracture in ductile-brittle transition, 27
J-R curve, 406
 mismatched weld joints, 427

L

Laminar flow control, 490
 Large deformation, finite element analysis, 216
 Life prediction, 287, 317
 multidisciplinary research, 3
 nuclear pressure vessel steel, 352
 perforate titanium, 490
 Limit load, 201
 Linear elastic fracture mechanics, 31, 267
 Loading, combined, 317
 Load ratio, natural rubber, 505
 Local approach cleavage fracture, 387
 Low-alloy steel, absorbed hydrogen effect, 338
 Lug joints, pin-loaded, 598

M

Materials, life prediction, 3
 Mechanisms, life prediction, 3
 MFM threshold condition, 267
 Microstructural fracture mechanics, 267
 Microstructure
 absorbed hydrogen effect, 338
 fatigue crack growth, 287
 Mismatching, 427
 Mixed mode fracture, crack surface morphology, 152
 Mixed mode I/II loading, 2024-T3 aluminum, 105
 Mixed mode I/III loading, fracture behavior, 152
 Modelling
 constraint, crack growth, 72
 fracture in ductile-brittle transition, 27
 Multiaxial loading, proportional, 613
 Multidisciplinary approach, life prediction, 3
 Multiple cracks, 550
 Multiple site damage, large-scale thin-sheet aluminum alloy, 451

N

Neuber rule, generalized, 613
 Notch fatigue, 301
 Notch stress fields, 301
 Notch tip stresses and strains, 613
 Nuclear pipe steels, cyclic loading effect, 406
 Numerical solution algorithm, 613

O

Overload conditions, resistance spot welds, 469
 Oxygen, effect on natural rubber, 505

P

PD 6493, 201
 Peel stresses, 580
 Pin-loaded lug joints, fatigue crack growth, 598
 Plane stress crack growth, 61
 Plastic zone, large-scale thin-sheet aluminum alloy, 451

Q

Quasi-compatible elements, 550

R

R-curve, 451
 Reactor pressure vessel, 367
 Replication method, 352
 Residual stresses, 301
 Resistance spot weld failure, overload conditions, 469

RKR model, 72
 Rubber, natural, fatigue crack growth, 505

S

Self-consistency, 152
 Shallow crack, 367
 Shallow flaw, 175, 387
 Shear beam, edge-notched beam, 530
 Short crack growth, 301
 Similitude, 287, 301
 Single crystal threshold, 267
 Single-edge notch bend specimens, 367
 Singular elements, 550
 Size effects, 126
 brittle fracture, 31
 Small cracks, 352
 S-N curve, 352
 Stable tearing analysis, 201
 Strain energy density method, generalized, 613
 Stress
 ductile-brittle transition, 27
 reference, 317
 Stress analysis, 517
 Stress intensity factor
 edge-notched beam, 530
 normalized, 550
 pin-loaded lug joints, 598
 weight function method, 563
 Stress-strain response, finite element analysis, 216
 Structural integrity, 387
 Subclad flaw, 243, 387
 Surface cracks, 317, 550
 interaction between, 550
 weight function method, 563
 Surface flaw, 243

T

Tear-fatigue, 317
 Tearing, stable
 crack-tip opening angle, 90
 mixed mode I/II loading, 105
 Temperature, natural rubber, 505
 Tensile response, perforate titanium, 490
 Tensile-shear specimen, 469
 T^* integral, 61
 Testing, life prediction, 3
 Threshold stress intensity factor, 287
 Titanium, commercially pure, fatigue response, 490
 Toughening, 152
 Transition, crack growth, 72
 Transition toughness, 27

U

Underclad cracks, fracture mechanics, 387
Undermatched welds, 427

W

Warm prestressing, 243
Weak link, stress-controlled fracture, 27

Weibull model, 387
Weight function method, 563
Welded structural details, ductile tearing, 201
Weld joint geometry, mismatched, 427
Weldments
 resistance spot weld failure, 469
 strength, 427
Weld nugget/heat affected zone, 469