

Subject Index

A

accelerated cooling, 692-727, 682-691
ageing, 991-1018
aging, 1055-1065
alkaline media, 584-595
aluminum, 991-1018, 309-331, 332-351
aluminum alloy, 104-114
aluminum alloys, 1055-1065
atomized spray quenching, 91-103
austenite, 843-858
axle shaft, 609-9

B

bainite, 843-858
bismuth, 596-10
boiling water heat transfer, 16-39
bright hardening, 584-595

C

carbonitriding, 364-17
carburizing, 489-499
CCT-diagram, 935-952
CFD simulation, 205-227
CHTE quench probe, 104-114
“cold sink” effect, 609-9
comparison, 205-227
computational fluid dynamics (CFD), 450-463
computer modeling, 609-9
computer simulation, 228-244, 622-628
continuous cooling, 295-306
convective heat transfer, 795-819
coolants, 3-15

cooling characteristic, 900-913
cooling curve, 953-976, 935-952, 1021-1031
cooling curve analysis, 531-570
cooling curves, 692-727, 914-934
cooling power, 977-990
cooling rate, 525-530
cracking, 622-628
crankshaft, 609-9
critical cooling rate and equation, 843-858
cryogenic, 332-351
crystal lattice parameters, 269-283

D

determination guideline, 63-83
diffusion, 295-306
digitally timed quenching, 622-628
dilatometer, 1055-1065
dilatometry, 295-306
direct quenching, 935-952
distortion, 117-156, 411-435, 309-331, 450-463, 609-9, 364-17
distortion mechanism, 398-410
dual-phase steel, 843-858
ductile cast iron, 295-306
dynamic characteristics, 935-952

E

eco-friendly quenchant, 525-530
energy savings, 629-11
environment, 629-11
equipment, 629-11
experimental flow investigation, 776-794

F

FEM, 411-435, 820-829, 253-268
 ferrous, 269-283
 finite difference method, 84-90
 finite element, 450-463
 finite element analysis (FEA), 450-463
 fittings, 662-681
 flow homogenization guidelines, 776-794
 FORTRAN subroutines, 436-449

G

gas quenching, 795-819, 776-794, 820-829, 757-775
 generalized equation, 205-227
 glycol, 309-331
 glycol quenching, 332-351

H

hardenability, 843-858, 833-842
 hardening, 609-9
 hardening power, 977-990, 1021-1031
 hardness prediction, 467-488
 heat conduction problem, 245-6
 heat penetration depth, 245-6
 heat transfer, 3-15
 heat transfer coefficient, 467-488, 63-83, 728-18, 571-583, 40-62
 heat transfer coefficients, 104-114
 heat treating, 309-331
 heat treatment, 117-156, 662-681, 596-10, 935-952, 833-842, 500-522, 977-990, 332-351
 heat treatment simulation, 398-410, 352-363
 heat treatments, 1055-1065
 high pressure gas quenching, 63-83

high speed gas quenching, 84-90

I

immersion quenching, 1032-1051
 inclusion rigidity factor, 253-268
 induction hardening, 398-410
 induction heating, 609-9
 induction showers, 914-934
 inductor, 609-9
 industrial application, 525-530
 infrared thermography, 91-103
 intensive quenching, 644-661, 205-227, 629-11
 inverse heat conduction, 16-39
 IQ technologies, 629-11
 IQLab software, 662-681

K

kinetics, 284-294

L

Leidenfrost phenomenon, 1032-1051
 Leidenfrost problem, 91-103
 liquid nitrogen, 332-351

M

magnetic field, 833-842
 martensite, 843-858
 mechanical properties, 692-727, 228-244, 820-829, 622-628
 microalloyed steels, 682-691
 microstructure, 692-727, 117-156
 modeling, 991-1018, 757-775, 728-18, 450-463
 modified heat conduction coefficient, 245-6
 modified Jominy holder and

specimen, 843-858
 modified Jominy-test, 228-244
 monitoring, 914-934
 moving heat source, 245-6
 multi-step accelerated-interrupted
 (AI) quenching, 662-681

N

nanofluids, 571-583
 new ferrite, 843-858
 new method, 662-681
 nitrocarburizing, 364-17
 nitrogen, 757-775
 nonmetallic inclusion-steel matrix
 interface, 253-268
 numerical algorithm, 500-522
 numerical simulation, 776-794,
 820-829

O

oil quenchant, 525-530
 optimization, 411-435
 oxidation, 531-570

P

peak temperature, 525-530
 pearlitic steel, 692-727
 phase diagram, 284-294
 phase transformation, 436-449,
 411-435, 295-306, 500-522
 photothermal deflection technique,
 489-499
 pipelines, 662-681
 plasticity, 411-435
 plate rolling, 682-691
 polyalkylene glycol, 309-331
 polyethylene glycol, 977-990
 precipitation, 991-1018
 prediction, 953-976

pressure drop correlation, 776-794

Q

quench design, 629-11
 quench distortion, 352-363
 quench factor analysis, 991-1018,
 728-18
 quench severity, 40-62
 quenchant, 953-976
 quenchants, 531-570, 935-952,
 914-934, 1021-1031
 quenching, 692-727, 467-488,
 795-819, 436-449, 117-156, 411-435,
 900-913, 309-331, 728-18,
 622-628, 914-934, 833-842, 450-463,
 977-990, 571-583, 584-595
 quenching and tempering, 228-244
 quenching heat treatment,
 104-114
 quenching media, 900-913, 596-10
 quenching simulation, 795-
 819
 quenching uniformity, 795-819

R

rail steel, 692-727
 regression analysis, 269-283
 residual stress, 692-727, 352-363,
 436-449, 117-156, 411-435,
 309-331, 450-463, 364-17, 332-351
 retained austenite, 364-17
 rewetting behavior, 1032-1051

S

SAE 1010 steel, 364-17
 salt bath, 584-595
 Segerberg equation, 1021-1031
 silver probe, 953-976
 simplified calculation, 662-681
 simulation, 117-156

solid solution, 269-283
 solution treatment, 991-1018
 spray cooling, 3-15
 spray quenching, 609-9
 stagnant area, 205-227
 starch quenchant, 525-530
 steel, 935-952
 steel dies, 228-244
 steel heat treating, 609-9
 steel quenching, 500-522
 steels, 833-842
 stress concentration zone, 253-268
 stress relief, 332-351
 super strengthening, 644-661
 superstrengthening, 629-11
 surface heat transfer coefficient, 84-90
 surface properties, 584-595

T

temperature, 84-90
 temperature measurement, 16-39
 testing, 914-934
 thermal analysis, 284-294
 thermal conductivity, 489-499
 thermal diffusivity, 489-499

thermally induced strain, 253-268
 thermocouple, 16-39
 thermodynamics, 284-294
 thermomechanical controlled
 processing, 682-691
 TRIP steel, 284-294
 TTT and CCT diagrams, 436-449
 TTT-diagram, 935-952

U

uphill quenching, 332-351

V

validation, 757-775
 vegetable oils, 531-570, 571-583
 Vickers hardness, 489-499

W

warpage, 309-331
 water quench, 104-114, 16-39
 water quenching, 332-351
 wetting, 571-583, 40-62

X

X-ray diffraction method, 269-283