

# Subject Index

## A

- Acoustic emission, graphite/epoxy laminates, 263
- Adhesive strips, in delamination arrestment, 176
- Aluminum
  - boron composites, stiffness loss, 173
  - graphite continuous-fiber composites, interface chemistry and crystallography, 51
  - SCS<sub>2</sub> continuous-fiber composites, fatigue mechanisms, 161
  - SiC discontinuous-fiber composites
    - fracture mode and surface chemistry, 51
    - interface chemistry and crystallography, 51
- Arrestment, graphite/epoxy delamination, 176
- Auger electron microscopy
  - graphite/aluminum continuous-fiber, and SiC/Al discontinuous-fiber composites, 51

## B

- Bolt loads, graphite/epoxy laminates, 115
- Boron/aluminum composites, stiffness loss, 173

## C

- Carbon fiber reinforced plastic laminates, cross-ply cracking, 84
- Chemistry, interface (*see* Interface chemistry)
- Composites
  - carbon fiber reinforced plastic, cross-ply cracking, 84
  - eutectics (*see* Composites, natural)
  - graphite/epoxy laminates
    - crack propagation in, 5
    - damage mechanisms and accumulation, 274
    - delamination arrestment with adhesive strip, 176
    - fiber fracture and ply cracking in, 252
    - internal load distribution effects during fatigue loading, 233
    - longitudinal splitting and delamination, ply thickness effect, 335
  - notched, effect of
    - brittle and ductile matrices, 134
    - tension-compression cyclic loads, 314
  - quasi-isotropic
    - under bolt-bearing loads, failure analysis, 115
  - 32-ply, effect of sublaminar cracks on tension fatigue behavior, 361

- Composites, graphite/epoxy laminates
    - (*continued*)
    - thick, with part-through surface flaws, fracture, 100
    - high-modulus continuous-fiber laminates, cumulative damage model, 298
    - metal matrix
      - graphite/aluminum continuous-fiber, interface role in fracture, 51
      - SCS<sub>2</sub>/Al continuous-fiber, fatigue mechanisms, 161
      - SiC/Al discontinuous-fiber, interface role in fracture, 51
    - natural, probabilistic fracture kinetics, 73
    - notched pultruded rod, fatigue damage mode, 197
    - R25 sheet molding compounds, notch strength, 32
    - unidirectional
      - E-glass/epoxy, fatigue failure mechanisms, 210
      - graphite/epoxy, fatigue failure mechanisms, 210
  - Compression-tension cyclic loading, effect on thick notched graphite/epoxy, 314
  - Cracking
    - cross-ply, of carbon fiber reinforced plastic laminates, 84
    - matrix, in composite laminates, 233
    - ply, and fiber fracture in graphite/epoxy laminates, 252
    - transverse (*see* Cracking, matrix)
  - Crack propagation
    - in graphite/epoxy laminate, 5
    - in natural composites, 73
    - environmentally-assisted, 77
    - physical process of, in degrading environment, 74
  - Cracks
    - arrestment, 176
    - propagation (*see* Crack propagation)
    - size, probabilistic distribution in natural composites, 73
    - sublamine, 361
    - time dependency, 14
    - velocity, 5
  - Crystallography, graphite/aluminum continuous-fiber and SiC/Al discontinuous-fiber composites, 51
- D**
- Damage
    - accumulation in unidirectional composites, 210
    - cumulative model
      - for graphite/epoxy laminates, 291
      - in high-modulus continuous-fiber composite laminates, 298
    - fatigue in notched pultruded composite rods, 197
    - in graphite/epoxy laminates, 252
    - failure under bolt-bearing loads, 115
    - matrix effects, 134
    - mechanisms and accumulation, 274
    - mechanisms during tension-compression fatigue, 332
    - stress redistribution in composite laminates, 233
  - Damage zone model, notched laminates, 135
  - Debonding, fiber-matrix, in notched pultruded composite rods, 200
  - Deflection, dynamic, during fatigue in notched pultruded composite rods, 201
  - Delamination, in graphite/epoxy laminates
    - arrestment of, 176
    - crack propagation in, 5
    - effect of sublamine cracks, 361
    - under compressive cyclic load, 335

under cyclic tension-compression loads, 314  
matrix cracking in, 233

## E

Edge distance effects, in graphite/epoxy under bolt-bearing loads, 125

Edge effect, on crack formation in carbon fiber reinforced plastic, 84

### E-glass

continuous-fiber notched pultruded composite rods, fatigue, 197  
-epoxy unidirectional composites, fatigue failure mechanisms, 210  
-T300 graphite unidirectional composites, fatigue failure mechanisms, 210

### Epoxy

-E-glass fiber composites, fatigue failure mechanisms, 210  
-graphite laminates  
fatigue failure mechanisms, 210  
fiber fracture and ply cracking, 252  
ply thickness effect on splitting and delamination, 335  
transverse cracking, 233

Eutectics (*see* Composites, natural)

## F

### Failure

graphite/epoxy laminates under bolt-bearing loads, 115  
edge distance effects, 125  
predictions, 121, 129  
stress analysis, 120  
width effects, 122  
modes in unidirectional composites, 210  
tensile, in graphite/epoxy laminates, 254

### Fatigue

in continuous-fiber SCS<sub>2</sub>/Al composites, 161  
in high-modulus continuous-fiber composite laminates, cumulative damage model, 298  
in graphite/epoxy laminates  
delamination arrestment with adhesive strip, 176  
effect of sublaminar cracks, 361  
internal load distribution effects, 233  
ply cracking and fiber fracture in, 252  
thick notched, under tension-compression cyclic loads, 314  
in notched pultruded composite rods, 197  
in unidirectional composites, failure mechanism, 211

Fiberdux 914C matrix, effect on fracture of notched carbon/epoxy composite, 134

Fiberite 1034 matrix, effect on fracture of notched carbon/epoxy composites, 134

### Fibers

continuous  
graphite/aluminum, interface role in fracture, 51  
SCS<sub>2</sub>/Al composites, fatigue, 161  
discontinuous SiC/Al, interface role in fracture, 51

fracture and ply cracking in graphite/epoxy laminates, 252

### matrix

debonding in notched pultruded composite rods, 200  
interface in SCS<sub>2</sub>/Al composites, 167

### unidirectional

continuous E-glass in notched pultruded rods, fatigue damage, 197

# Fibers, unidirectional (*continued*)

E-glass/epoxy, fatigue failure mechanisms, 210

T300 graphite/epoxy, fatigue failure mechanism, 210

## Fracture

in carbon/epoxy laminates

dynamic, 5

notched, matrix effects, 134

thick, with part-through surface flaws, 100

toughness (*see also* Notch strength), 5

in natural composites, crack propagation kinetics, 73

in SiC/Al composites, mode and surface chemistry of, 51

## G

Graphite/aluminum continuous-fiber composites, interface role in fracture, 51

## Graphite/epoxy laminates

A5/3501-6, transverse cracking, 233

AS1/3501-6, longitudinal splitting and delamination, ply thickness effect, 335

AS-4/3501-6

damage mechanisms and accumulation, 274

delamination arrestment with adhesive strip, 176

T300-5208

under bolt-bearing loads, failure analysis, 115

notched, effect of tension-compression cyclic loads, 314

thick, with part-through surface flaws, fracture, 100

and T300/code 91, fiber fracture and ply cracking in, 252

T-300/934, crack propagation, 5

T300/1034E unidirectional, effect of sublaminar cracks, 361

## H

Heat effects, in graphite/aluminum continuous-fiber and SiC/Al discontinuous-fiber composites, 61, 63

## I

Inherent flow model, notched laminates, 136

Interface chemistry, graphite/aluminum continuous-fiber and SiC/Al discontinuous-fiber composites, 51

## L

### Laminates

carbon fiber reinforced plastic, cross-ply cracking, 84

composite, internal load distribution effects during fatigue loading, 233

eutectic (*see* Laminates, natural)

graphite/epoxy

under bolt-bearing loads, failure analysis, 115

crack propagation, 5

damage mechanism and accumulation, 274

delamination arrestment with adhesive strip, 176

fiber fracture and ply cracking in, 252

internal load distribution effects during fatigue loading, 233

longitudinal splitting and delamination, ply thickness effect, 335

notched

matrix effects on fracture, 134

pultruded rod with continuous unidirectional fibers, fatigue damage, 197

tension-compression cyclic loading effects, 314  
 thick, with part-through surface flaws, fracture, 100  
 32-ply, effect of sublamine cracks on tension fatigue behavior, 361  
 unidirectional, fatigue failure mechanisms, 210  
 natural, crack propagation, 73  
 Loading  
   cyclic  
     compressive, splitting and delamination in graphite/epoxy, ply thickness effect, 335  
     general, cumulative damage model in high-modulus continuous-fiber composite laminates, 298  
     tensile, damage mechanisms and accumulation in graphite/epoxy laminates, 274  
     tension-compression, effect on thick notched graphite/epoxy laminates, 314  
 internal load distribution effects, 233  
 quasi-static tensile, fiber fracture and ply cracking in graphite/epoxy laminates, 252  
 static and cyclic, effect of sublamine cracks in graphite/epoxy laminates, 361  
 static and fatigue tension, delamination arrestment in laminated composites, 176  
 Loads, bolt-bearing, graphite/epoxy laminate failure, 115

## M

Markovian process, probabilistic fracture of natural composites, 73

Moiré interferometry, graphite/epoxy under compressive cyclic load, 340  
 Mold coverage, effect on notch strength of R25 sheet metal compounds, 32

## N

Notch strength  
   R25 sheet metal compounds, mold coverage effect, 32  
   thick graphite/epoxy laminates with part-through surface flaws, 100

## P

Photography, high-speed, crack propagation in graphite/epoxy laminate, 5  
 Ply  
   cracking, 90-deg (*see* Cross-ply cracking)  
   thickness, effect on graphite/epoxy laminate splitting and delamination, 335  
 Point stress criterion, notched laminates, 137

## R

Radiography  
   failure modes of graphite/epoxy laminates under bolt-bearing loads, 115  
   X-ray (*see* X-ray radiography)  
 Residual strength  
   critical-element model of loaded composite coupons, 298  
   delamination arrestment in fiber- and matrix-dominated laminates, 183  
   graphite/epoxy  
     after compressive cyclic loading, 355

Residual strength, graphite/epoxy  
     (*continued*)  
     under cyclic tensile loadings, 287  
     under tension-compression cyclic  
     loads, 314

## S

Scanning electron microscopy, graph-  
     ite/aluminum continuous-fiber  
     and SiC/Al discontinuous-fi-  
     ber composites, 51

Sheet molding compounds, R25, ef-  
     fect of mold coverage on notch  
     strength, 32

Silicon carbide/aluminum composites  
     continuous-fiber

    fatigue mechanisms, 161

    stiffness loss, 169

    versus boron/aluminum compos-  
     ites, 173

    discontinuous-fiber, interface role  
     in fracture, 51

Splitting, longitudinal, ply thickness  
     effect, 335

Stereoradiography (*see* X-ray radiog-  
     raphy)

Stiffness

    loss in continuous-fiber SCS<sub>2</sub>/alu-  
     minum composites, 161

    residual, in graphite/epoxy lami-  
     nates, 286

    static, after fatigue in notched pul-  
     truded composite rods, 205

    in thick notched graphite/epoxy  
     laminates under tension-com-  
     pression cyclic loads, 314

Strength

    graphite/epoxy laminates under bolt-  
     bearing load, 115

    residual (*see* Residual strength)

Stress

    in graphite/epoxy laminates under  
     bolt-bearing loads, 120

    redistribution during fatigue load-  
     ing of composite laminates,  
     233

Surface flaws, part-through, fracture  
     of thick graphite/epoxy lami-  
     nates with, 100

## T

Temperature dependency, crack growth  
     in natural composites, 73

Temperature effects (*see* Heat effects)

Tension-compression cyclic loading,  
     effect on thick notched graph-  
     ite/epoxy laminates, 314

Time dependency, crack velocity in  
     graphite/epoxy laminate, 5

Transmission electron microscopy  
     graphite/aluminum continuous-fiber  
     composites, 51

    SiC/Al discontinuous-fiber com-  
     posites, 51

## U

Ultrasound, pulse-echo, graphite/epoxy  
     damage under compressive  
     cyclic load, 340

## W

Weibull strength distribution, 90-deg  
     ply cracking in carbon fiber  
     reinforced plastic, 84

## X

X-ray radiography, graphite/epoxy  
     composites

    fatigue loading, 274

    fiber fracture and ply cracking, 252  
     notched

        under cyclic tension-compression  
         loads, 327, 330, 331

        matrix effects, 139