

Index

A

AASHTO Standard T 242, 38
 Anionic asphalt emulsion, 77
 Asphalt cement, AC 2.5, 77
 Asphalt polymer, 66, 68
 ASTM standards
 D 1856, 77
 D 3387, 82
 E 274, 38
 E 503, 37
 E 556, 39
 E 670, 36

B

Balmer, Glenn G., 33-50

C

Chong, George J., 3-17
 Cold-mix recycling, 75
 Condition survey, highway, 4
 Cost effectiveness of maintenance treatment, 8
 Crack sealing
 Guidelines, 14
 Methods and materials, 14, 15
 Rationale, 11, 12
 Research and improvement, 15

D

Deen, Robert C., 18-32
 Deflections, dynamic
 Deflection bowl, 21

Errors, 23

Kentucky Road Rater, 20
 Reference conditions, 21
 Sampling and statistics, 28

E

Expected life of maintenance alternatives, 7, 8

F

Friction characteristics, remedial procedures
 Grooving, 47, 48
 Milling, 46, 47
 Open-graded friction course, 48, 49
 Resurfacing, 48
 Sprinkle treatment, 48
 Friction, pavement measurement methods
 Articulation angle, 41, 42
 At intersections, 43
 Diagonal braked vehicle, 37, 38
 Dynamic vertical test-wheel load, 43, 44
 Mu-meter, 36, 37
 Saab friction tester, 45, 46
 Side force measurement transducer, 39
 Single wheel tester, 44, 45

G

Gyratory indices
 Compactibility, 80

Elasto-plastic, 79

Stability, 79

Gyratory testing machine, 75, 76

O

Overlay design, 29

H

Hoffman, Gary L., 51-64

K

Kallas, Bernard F., Editor, 1, 2

Knight, Norman E., 51-63

M

Maintenance guidelines, pavement, 4

Maintenance performance standards, 7

Marshall stability, 80

Membranes

Asphaltic mastic and nonwoven
polypropylene fabric, 54Fiberglass mesh polymer modified
asphalt and nonwoven poly-
propylene fabric, 54Fiberglass woven fabric and poly-
merized asphalt, 54Polypropylene woven mesh and
self-adhesive rubberized as-
phalt, 54Rubberized asphalt impregnated
nonwoven polypropylene fab-
ric, 54Rubberized asphalt with polypro-
pylene mesh, 52

Moduli, asphalt concrete, 24

P

Pavement condition rating, 10

Phang, William A., 3-17

Preventive maintenance, 10

R

Recycling agents, 77

Rowlett, David R., 64-73

S

Sharpe, Gary W., 18-32

Southgate, Herbert F., 18-32

Stabilometer resistance value, 80

Subgrade strength, 25

T

Tia, Mang, 74-94

Tonda, Richard D.,

U-Z

Uffner, William E., 64-73

Wood, Leonard E., 74-94

Woven glass fiber fabric, 66

Zimmer, Richard A., 33-50