

Subject Index

A

Abrasion

- metal-ceramic coatings
 - performance, 37–38
 - tests in Alundum and silica sand slurries, 23–25, 27–28
 - wear morphology, 31–35

Abrasion resistance

- CM 500L-coated steel mud pump liners
 - field simulation, 107, 111–114
 - laboratory tests, 105–107, 109–111
- Miller Slurry Abrasivity Test
 - adaptation, 105–107
 - optimum hardness value, 114
 - wear life predictions, table, 113

Abrasive wear, alloy and stainless steels under dry and wet corrosive conditions, fig., 10

Alloy and carbon steels

1018

- abrasion tests in Alundum and silica sand slurries, 23–25, 27–28, 31–35
- CM 500L-coated mud pump liners, 105–114
- erosion tests in Alundum and silica sand slurries, 25, 29–31, 35–37
- erosivity of coal particles in

coal-solvent slurries, 68–76

- 1020, 1060, 1080, 4142, and 8740, flow-through slurry wear rates, table, 177

1065

- ball mill test, 6, 9, 11–16
- hub test, 6–11

- 1090, fifth SAE round-robin test results, table, 220

4340

- ball mill test, 6, 9, 11–16
- hub test, 6–11

4342

- cutting and deformation wear in recycled slurry test, fig., 179

slurry wear in flow-through slurry system, fig., 176

slurry wear in recycled-slurry system, fig., 178

5145

flow-through slurry wear rate, table, 177

slurry wear in flow-through slurry system, fig., 176

slurry wear in recycled-slurry system, fig., 178

A36

- corrosion loss in limestone slurry scrubbers, 121–130
- linear polarization and weight

- loss measurements, fig., 128
 - pitting, spray slurry effect, 132
 - scrubber location effect, fig., 126
 - A514
 - flow-through slurry wear rate, table, 177
 - slurry wear comparison in flow-through and recycled systems, fig., 180
 - slurry wear in flow-through slurry system, fig., 176
 - slurry wear in recycled-slurry system, fig., 178
 - wear surfaces comparison in flow-through and recycled slurry tests, fig., 182
 - Astralloy V
 - ball mill test, 6, 9, 11–16
 - hub test, 6–11
 - Hadfield manganese
 - ball mill test, 6, 9, 11–16
 - hub test, 6–11
 - Ni- and Co-based hardfacings,
 - slurry wear in recycled slurry system, 177–182
 - T-1 low-alloy, fifth SAE round-robin test results, table, 221
 - various, Wet Sand/Rubber Wheel Test results, table, 225
 - Alumina particles
 - oscillatory device for simulating wear by friction, 189–192
 - wear patterns in dense slurry flow, 188–189
 - Aluminum alloys
 - Al 6061
 - ball mill test, 6, 9, 11–16
 - hub test, 6–11
 - Aluminum, recycled coal-water slurry erosivity, 81–84
 - Alundum slurries
 - abrasion of metal coatings
 - material loss, 27–28
 - test procedure, 23–25
 - erosion of metal coatings
 - material loss, 29–31
 - test procedure, 25
 - particulate hardness and abrasion/erosion, 37–40
 - Ash content, coal, effect on erosivity, 67–68, 76
 - ASTM Standards
 - A 36/A36M-84a:121
 - D 1141-75:12
 - D 2000-80:226
 - D 2240-84:229
 - E 10-84:94
 - E 140-84:96
 - E 384-84:94
 - G 1-81:121
 - G 65-84:23
 - G 75-82:93
 - G 75-82:155
- B**
- Ball mill test for corrosive wear
 - alloy and stainless steels, 6, 13–16
 - methods, 9
 - Nitronic 30, 6, 13–15
 - Brinell hardness, 94
 - pipe materials, table, 97
 - slurry materials, table, 98
- C**
- Carbon steels (*See* Alloy and carbon steels)
 - Ceilcote systems, characteristics, application rates, and costs, table, 136
 - Centrifugal pumps, 254–255
 - conversion of water performance to slurry performance, 256–257
 - Ceramics, in pumps, 246
 - Chemical vapor deposition, 104
 - reactor, fig., 105

CM 500L

- coated steel mud pump liners,
wear life prediction, table,
113
- controlled nucleation thermochem-
ical deposition, 104, 107–
109
- long-time simulation tests for
slurry resistance, fig., 112
- optimum hardness value, 114
- properties, table, 108
- slurry abrasion behavior
 - in alkaline slurry, fig., 111
 - of chromium plating and, fig.,
112
 - in neutral slurry, fig., 110
 - on steel, long-time simulation,
fig., 102

Coal-kerosene slurries

- erosion of 1018 steel, 68–73
 - ash content effect, 67–68, 71–73
 - ash oxide effects, 67–68
 - particle shape and distribution
effects, 63, 68
 - particle size effects, 66–68, 69–
72
 - pot tester, 67–68

Coal-oil slurries

- erosivity for mild and stainless
steels
 - erosion-corrosion interaction, 57
 - mass loss data, 52–56
 - pot tester, 50–51, 60–61
 - solids loading effects, 52–53, 55
 - specimen rotation speed effects,
57–58
 - stabilizing additives, 56–57

Coal particles

- shape, effect on erosivity, 63, 68,
76
- size, effect on erosivity, 68–73,
75–76

Coal vacuum bottoms-tetrahydrofuran
slurries

- erosion of 1018 steel, 73–76
 - cumulative erosion rates, fig.,
75
 - incremental erosion rates, fig.,
74

Coal-water slurries

- erosivity of mild and stainless
steels
 - erosion-corrosion interaction, 57
 - mass loss, 52, 54, 56
 - solids loading effects, 54
 - stabilizing additives, 56
- recycling during erosivity testing
mineralogy, 85–87
- peaking behavior, 81–84
- procedure, 80–81
- viscosity, pH, and particle size
changes, 84–85

Coatings

- CM 500L (*See* CM 500L)
- thickness, wear distribution meas-
urement, 196–197
- Wet Sand/Rubber Wheel Test,
table, 225

Cobalt-based hardfacings, slurry wear
in recycled slurry system,
177–182

Coke-oil slurries

- erosivity of mild and stainless
steels
 - erosion-corrosion interaction, 57
 - factors affecting, 53–56
 - pot tester, 50–51
 - solids loading effects, 51–53
 - specimen rotation speed effects,
57–58
 - stabilizing additives and, 56–57

Concentration effects, erosivity of
coal-oil, coal-water, and
coke-oil slurries, 52–56Controlled nucleation thermochemical
deposition

- chemical vapor deposition reactor,
104, fig., 105

- CM 500L coating on steel mud pump liners
 - development, 104, 107–109
 - properties, table, 108
- Corrosion-erosion protection
 - limestone slurry scrubbers, 134–138
 - coating failures, 136–138
 - materials selection, 134–136
 - surface preparation, 137–138
- Corrosion rates
 - in limestone spray slurry, 121–130
 - 316 and T304L stainless steel, table, 127
 - A36 carbon steel, table, 126–128
 - two-electrode linear polarization system, 119–130
- Corrosive wear
 - alloy and stainless steels, 9–16
 - hub test, fig., 11
 - ball mill test, fig., 13
 - ball mill test with synthetic seawater, fig., 15
- Corrosivity, in limestone slurry scrubbers, 121–122

D

- Departure value, formulas, 163
- Diaphragm pump, 248, fig., 250
- Dry sand rubber wheel abrasion test, 38

E

- Electrical capacitance, pipeline erosion measurement, 93
- Energy approach, erosion wear distribution, 195–197
- Epoxy resin, 188, 194–195
- Erosion
 - in dense slurry flow
 - energy approach, 195–196
 - numerical flow simulation, 197–198

- predictive approach, 189
 - procedure, 198
- flow-through and recycled-slurry tests
 - comparison, 179–182
 - equipment and specimens, 170–174
 - procedures, 175
 - wear losses and wear rates, 175–179
- metal-ceramic coatings
 - performance, 39–40
 - tests in Alundum and silica sand slurries, 25–26, 29–31
 - wear morphology, 35–37
- Erosion-corrosion interaction, effect of stabilizing additives, 57
- Erosion-corrosion tests
 - vibratory and jet-in-slit apparatuses, 143–145
 - damage on pump components, 150–151
 - materials and damage rates, 145, 148–149
 - particle impact parameters, 153
 - slurries, table, 146, 152–153
- Erosion testing
 - peaking behavior, 88–89
 - peaking behavior of recycled coal-water slurries, 81–84
 - in pipeline systems
 - absolute measurements, 92–93
 - comparative hardness values for pipeline materials, table, 97
 - Miller numbers and hardness values for slurry materials, table, 98
 - relative values, 93–96
- Erosivity
 - coal particles in coal-solvent slurries, 67–73
 - ash content effects, 67–68
 - incremental and cumulative erosion, 68–73

- oxide shape and distribution
 - effects, 68
 - particle size distribution effects, 68
- coal vacuum bottoms in coal-solvent slurries, 73-76
- relative, coal-oil, coal-water, and coke-oil slurries, 47-61
- Erosivity testing
 - coal-water slurry recycling, 80-88
 - mineralogy, 85-87
 - peaking behavior, 81-84
 - viscosity, pH, and particle size changes, 84-85

F

- Flow, dense (*See* Slurry flow, dense)
- Flow rate, effect on erosion wear distribution in casing, fig., 206
- Flow-through slurry test
 - electromechanical measurements, 174
 - equipment and specimens, 170-174
 - particles, comparison with recycled slurry test particles, fig., 181
 - procedure, 175
 - and recycled-slurry tests, 179-182
 - wear losses and wear rates, 176-177

- Friction erosion, oscillatory device for simulation, 189-192
- Fuel recycling during erosivity testing
 - mineralogy, 85-87
 - peaking behavior, 83-84, 87-89
 - slurry erosivity, 81-84
 - viscosity, pH, and particle size changes, 84-85

G

- Gypsum slurries, erosion-corrosion tests, 145-146, 152-153

H

- Hardfacings, Ni- and Co-based, slurry wear in flow-through and recycled-slurry tests, 175-179
- Hardness
 - Alundum and silica particulates, 37-40
 - CM 500L, optimum value, 114
 - indices for pipeline erosion, 94-95
 - metal-ceramic coatings
 - abrasion performance, 37-38
 - Alundum abrasion tests, fig., 31
 - erosion performance, 39-40
 - silica abrasion tests, fig., 29
 - silica and Alundum erosion tests, fig., 33
 - table, 22
- Hastelloy C, slurry erosion-corrosion, 145-150
- Hub test for corrosive wear
 - alloy and stainless steels, 6, 9-11
 - methods, 6-9

I

- Impact
 - erosion wear patterns by particle, 188-189
 - particles-wall interaction, 195-197
- Impingement
 - angle, effect on pump wear, 244
 - particles in dense slurry flow, 188-189
- Inclined wall
 - erosion wear by impact, 192-196
 - total wear distribution, energy approach, 197-198

J

- Jet impingement slurry erosion tester, 25-26
 - suitability for coatings, 40-42
- Jet-in-slit method for erosion-corrosion tests

apparatus and procedure, 144–145
 damage rates, fig., 148–149
 materials, 145

K

Kerosene-coal slurries (*See* Coal-kerosene slurries)
 Kinetics, corrosion, in limestone slurry scrubbers, 131, 135
 Knoop Hardness Number, 94, 96
 pipe materials, table, 97
 slurry materials, 98

L

Lap wear, degrees, 158
 LCO-17
 abrasion tests
 materials loss, 27–28
 procedure, 23–25
 wear morphology, 31–35
 erosion tests
 materials loss, 27–28
 procedure, 25
 wear morphology, 35–37

LCO-22

abrasion tests
 materials loss, 27–28
 procedure, 23–25
 wear morphology, 31–35
 erosion tests
 materials loss, 27–28
 procedure, 25
 wear morphology, 35–37

Limestone slurry scrubbers
 corrosion protection
 coating failures, 136–138
 materials selection, 134–136
 surface preparation, 137–138
 corrosion rate
 distribution and chemical composition of deposits, table, 130–131
 effect of dissimilar metals and

scaling deposits, 131–134
 linear polarization method, 119–121

probe multiplier, 123–125
 weight-loss and linear polarization results, tables, 127–128

weight-loss method, 121

Linear polarization, two-electrode
 corrosion rates in limestone slurry scrubbers, 119–123
 comparison with weight-loss methods, table, 126–128
 method, 119–121
 pitting factor, 130–134
 probe multiplier, 123–125

Lock Hopper pumps, 248, fig. 249

LW-5

abrasion tests
 materials loss, 27–28
 procedure, 23–25
 wear morphology, 31–35
 erosion tests
 materials loss, 27–28
 procedure, 25
 wear morphology, 35–37

LW-26

abrasion tests
 material loss, 27–28
 procedure, 23–25
 wear morphology, 31–35
 erosion tests
 materials loss, 27–28
 procedure, 25
 wear morphology, 35–37

M

Metal-ceramic coatings
 abrasion performance, 37–38
 abrasion tests in Alundum and silica sand slurries
 materials loss, 27–28
 procedure, 23–25
 wear morphology, 31–35

erosion performance, 39–40
erosion tests in Alundum and silica sand slurries
 materials loss, 29–31
 procedure, 25
 wear morphology, 35–37
hardness, 29, 31, 33, 37, 40, 42
Metals, deformation wear in pumps, 245–246
Metrology, pipeline erosion measurement, 93
Mild steel
 erosion damage pattern in coke-oil slurry, 58, fig., 60
 erosivity in coal-oil and coke-oil slurries, 52–55
 surface damage in coke-oil slurry, 57, fig. 59
Miller number, 93–94
 pump material selection, 244–245
 SAR test and, 155–156
 slurry materials, table, 98
Miller Slurry Abrasivity Test
 adaptation for abrasion resistance, 105–107
 apparatus modifications, table, 108
 procedure modifications, table, 107
 for CM 500L-coated steel mud pump liners, 105–107
 field simulations, 107, 111–114
 laboratory test methods, 105–107, 109–111
Miller Slurry Abrasivity Tester, fig., 106

N

Neutron activation, pipeline erosion measurement, 93
Nickel-based hardfacings, slurry wear in recycled slurry system, 177–182
Nitronic 30

abrasive wear under wet and dry corrosive conditions, fig., 10
corrosive wear, figs., 11, 13, 15
 ball mill test, 6, 9, 11–16
 hub test, 6–11
Nucleonic gaging, pipeline erosion measurement, 93
Numerical flow simulation
 dense slurries, 197–198
 pump casing, basic equations, 208

O

Oscillatory device for simulating erosion by friction, 189–190
Oxides, coal, effects on erosivity, 68, 76

P

Packings
 piston and plunger pumps, 252–253
 in slurry pumps, 251–252
Particle(s)
 impingement angle, effect on pump wear, 244
 shape, effect on erosivity, 63, 68, 76
 size
 changes during coal-water slurry recycling, 84–85
 and sharpness, effect on pump wear, 244
 velocity, vibratory and jet-in-slit erosion-corrosion tests, 143, 153
Particles-wall interaction, 195–197
Peaking behavior
 cause, 87–88
 characterization, 83–84
 erosion testing and, 88–89
Permanent magnet gaging, pipeline erosion measurement, 93

Petroleum coke-oil slurries (*See*
Coke-oil slurries)

pH, changes during coal-water slurry
recycling, 84–85

Pipeline erosion by slurries
absolute measurement methods,
92–93
hardness values for pipe materials,
table, 97

Miller numbers and hardness
values for slurry materials,
table, 98

relative erosion values, 93–96
research, 98–99

Pipes, typical wear patterns, fig., 206

Piping, positive displacement pumps,
253–254

Piston pumps, 248
life of expendables, table, 254

Pitting factor, in limestone slurry
scrubbers, 130–134

Plastics, in pumps, 246

Plunger pumps, 248, fig., 250
life of expendables, table, 254

Polyamide resin, 188, 194–195

Positive displacement pumps, 248,
fig. 251

station piping design, 253–254

Pot tester
coal-oil, coal-water, and coke-oil
slurries, 50–51

coal-solvent slurries, 65–67, 76
problems, 60–61

for relative corrosivity of coal-oil,
coal-water, and petroleum
coke-oil slurries, 50–51

Predictive model for numerical
simulation of wear by
impact and friction, 197–
198

Pumps
casing, basic equations for
numerical flow simulation,
208

centrifugal, 254–257

erosion component, energy
approach, 197–200

positive displacement
fluid end, 248–251
fluid end valve, 251
lock hopper, 248
maintenance, 253
packings, 251–252
pistons and plungers, 252–253
station piping design, 253–254

vibratory and jet-in-slit erosion-
corrosion testing
apparatuses and procedures,
143–145

component damage, 150–151
materials, 145

wear, factors affecting
hydraulic design, 246–247
pump material properties, 245–
246

slurry properties, 244–245
solid particles, 244

Pyrite, in sink fraction during coal-
water slurry recycling, 86–
87

Q

Quartz sand, in Wet Sand/Rubber
Wheel Abrasion Test, 226

R

Radionuclides, wear distribution
measurement, 196–197

Recycled slurry test
electromechanical measurements,
174
equipment and specimens, 174
flow-through tests and, 179–182
particles, comparison with flow-
through test particles, fig.,
181
procedure, 175
slurry wear, 177–179

- wear kinetics, 178–179
- Rubber, deformation wear in pumps, 246
- “Rubber Wheel Abrasion Test” (Borik), 215
- Rubber Wheels, in Wet Sand/Rubber Wheel Abrasion Test, 226, 229, 230

S

- Sand particles
 - oscillatory device for wear by friction, 189–192
 - wear patterns in dense slurry flow, 188–189
- Sand-water slurries, impact erosion on an inclined wall, 192–196
- SAR number
 - calculation, 159–161
 - departure value, 163
 - typical, 162
 - uses, 161–162
- SAR test (*See* Slurry Abrasion Resistance Test)
- Scrubbers, limestone slurry (*See* Limestone slurry scrubbers)
- Silica sand slurries
 - abrasion of metal-ceramic coatings materials loss, 27
 - test procedure, 23–25
 - abrasive particles, comparison in flow-through and, recycled slurry tests, fig., 181
 - erosion-corrosion tests, 145–146, 152–153
 - erosion of metal coatings material loss, 29–31
 - test procedure, 25–26
 - flow-through and recycled-slurry tests, 176–179
 - particulate hardness and abrasion/erosion, 37–40
- Sink fraction, during coal-water

- slurry recycling, 85–87
- Sliding-bed erosion, oscillatory device for simulation, 189–192
- Slurry Abrasion Resistance Test
 - equipment, 156–157
 - lap wear, 158
 - procedure, 157–158
 - SAR number
 - calculation, 158–161
 - departure value, 163
 - typical, 162
 - uses, 161–162
- Slurry flow, dense
 - erosion on an inclined wall, 192–196
 - numerical analysis and applications
 - flow modeling, 197–198
 - procedures, 198
 - results for pumps, 198–200
 - wear by friction, 189–192
 - wear distribution measurement, 196–197
 - wear patterns, 188–189
- The Society of Automotive Engineers Iron and Steel Technical Committee, 213
- SAE Draft XJ1185 (Wet-Sand Rubber-Wheel Abrasion, Test Method), 232–239
- Stainless steels
 - 17-4 PH
 - ball mill test, 6, 9, 11–16
 - hub test, 6–9
 - 304
 - ball mill test, 6, 9, 11–16
 - erosivity of coal-oil, coal-water, and coke-oil slurries, 52–61
 - fifth SAE round-robin test, 223
 - flow-through slurry wear, fig., 176
 - flow-through slurry wear rate, table, 177
 - recycled-slurry wear, fig., 178

- hub test, 6–9
- 316
 - ball mill test, 6, 9, 11–16
 - corrosion loss in limestone
 - slurry scrubbers, 121–130
 - flow-through slurry wear rate,
 - table, 177
 - hub test, 6–9
 - recycled slurry wear, fig., 178
- 316L
 - corrosion loss in limestone
 - slurry scrubbers, 121–130
 - vibratory and jet-in-slit tests for
 - erosion-corrosion, 145–150
- 409
 - ball mill test, 9, 11–16
 - hub test, 6–9
- 410
 - ball mill test, 6, 9, 11–16
 - hub test, 6–9
- 416, recycled coal-water slurry
 - erosivity, 81–84
- Nitronic 30 (*See* Nitronic 30)
- Standardization, in pipeline erosion
 - studies, 98
- Stauffer's Grinding Pot Device, 142
- Steel mud pump liners, 111–114
 - CM 500L coating
 - controlled nucleation
 - thermochemical deposition, 104
 - properties, table, 108
 - field simulation procedures, 107, 111–114
 - laboratory testing procedures, 105–107, 109–111
 - Miller Abrasivity Test
 - modifications, 105–107
 - apparatus, table, 108
 - procedure, table, 107
 - Surface activation, pipeline erosion
 - measurement by, 93

T

- Tetrahydrofuran-coal slurries (*See* Coal-tetrahydrofuran slurries)
- Thermosetting resins, for limestone
 - slurry scrubbers, 134–137
- Tool steel D-2, fifth SAE round-robin test, table, 222
- Tungsten carbide, recycled coal-water slurry erosivity, 81–84

U

- UHMW polyethylene, flow-through
 - slurry wear rate, table, 177
- Ultrasonic gaging, pipeline erosion
 - measurement, 93

V

- Vacuum bottoms, coal (*See* Coal vacuum bottoms)
- Valves, slurry, 251
- Velocity effects, surface damage, 57–58
- Vibratory method for erosion-corrosion tests
 - apparatus and procedure, 143–144
 - damage rates, fig., 148
 - materials, 145
- Vickers Hardness Number, 94–96
 - for pipe materials, table, 97
- Viscosity, changes during coal-water
 - slurry recycling, 84–85

W

- Wear
 - CM 500L-coated steel mud pump
 - liners
 - field simulation experiments, 107, 111–114
 - laboratory test methods, 105–107, 109–111
 - prediction, table, 113

- deformation
 - metals in pumps, 245–246
 - rubbers in pumps, 246
- distribution in casing, flow rate
 - effect, fig., 206
- by friction
 - alumina particles on various plate materials, fig., 191
 - sand particles on polyamide resin, fig., 191
- by impact
 - in dense slurry flow, 192–196
 - energy approach to, 195–197
- morphology of metal-ceramic coatings
 - abrasion tests, 31–35
 - erosion tests, 35–37
- patterns
 - in dense slurry flow, 188–189
 - in slurry pipes, fig., 206
- Wear resistance, SAR number
 - calculation, 158–161
- Wear tests
 - flow-through (*See* Flow-through slurry test)
 - recycled (*See* Recycled-slurry test)
- Weighing, pipeline erosion
 - measurement, 93
- Weight-loss method for corrosion
 - rates in limestone slurry
- scrubbers
 - comparison with linear polarization methods, table, 126–128
- procedure, 121
- Wet Sand/Rubber Wheel Abrasion Test
 - 304 stainless steel, table, 223
 - 1090 steel, table, 220
 - D-2 tool steel, table, 222
 - round-robin tests
 - first, 215–216
 - second, 216–217
 - third, 217
 - fourth, 217–218
 - fifth, 218–224
 - summary, table, 218
 - status, 219–224
 - T-1 low-alloy steel, table, 221
 - variables
 - abrasives, 226
 - laboratory techniques, 228–229, 230–231
 - rubber wheels, 226, 230
 - test equipment, 228
 - test material, 227–228
 - various material groups, table, 225
- Wet sand/rubber wheel abrasion
 - testing machine, 24–25
 - suitability for coatings, 38–39