

Subject Index

A

adhered (bonded) wood products, 59–61
 adsorption, 2–3
 adsorption isotherm, 2
 aerated concrete, 48
 aerobiology, bacteria, 82
 air
 ambient, 111
 barrier systems, 18–19
 barriers, high-rise, 416
 distribution, 124
 infiltration and ventilation, 111–116
 leakage characteristics for building enclosure, assembly and materials, 19–21
 air conditioning, residential buildings, 397–398
 airtightness, 111
 data, 113
 tests, 31–32
 ambient air, 111
 apparent thermal conductivity, 39
 architects
 and engineer role, quality, 496
 certificates, 570–571
 arthropods, 82
 assemblies, 18
 assumed design responsibility, 568
 ASTM standard guidelines and practices, 476–477
 attics
 condensation, 197–198
 manufactured housing, 431–432
 axial and radial system, wood, 54–56

B

bacteria, 74, 82
 aerobiology, 82
 and water temperature and light, 82
 barrier systems, air, 18–19
 basements, 108–109
 case studies, 197
 wall and below grade drainage systems, 25–26
 bathrooms, 105
 biocides for contamination prevention, 86
 biological attack, 73
 Boston Cap roof, 321
 Brady Array, 144
 British standards, 477
 building envelopes
 airtightness, 113
 defined, 494
 high-rise buildings, 401–425
 quality design, 551–556
 buildings
 airflow, 150–151
 components, 238–240
 enclosures, 229–242
 industry challenges, quality design, 497–498
 pressurization/depressurization, high-rise, 403–404

C

Canadian standards, 477
 canopy connection to wall, 276
 capacitance techniques, 146–147
 capillary breaking layer, 25
 capillary moisture content, 27, 34–35
 capillary transport, 30–31
 carbon, 144
 carpenter ants, 75
 case studies, 181–224
 attic condensation, 197–198
 basements, 197
 crawl spaces, 193–196
 dehumidifiers, 192–193
 exterior moisture problems, 183
 exterior wall moisture problems, 183, 193–215
 indoor moisture problems, 181–182, 183–193
 inside exterior walls, 215–219
 moisture inside exterior walls, 215
 mold and mildew problems, 182–183
 roofing, 198–200
 siding, 200–201
 southern climates, 213–215
 weatherization, 189–190
 cathedral ceilings, 322
 cell wall, lumen, moisture, wood, 56
 cell-to-cell connections, wood, 56
 cladding design, high-rise buildings, 409–416
 climate
 data sheets, 91–103
 new residential buildings, 343, 347–348
 cockroaches, 82
 codes, 486–488
 cold climate
 issues, 124
 new residential buildings, 347–348
 combustion appliances, residential buildings, 398
 commercial buildings, 241
 concentration decay method, 151
 condensation of humid air on colder surfaces, 164–166
 constant concentration method, 151–152
 constant injection method, 152
 constant volume terminal reheat, 125
 construction
 contract documents, 515–519
 influence on process, 127–128
 management firm role, 496
 moisture, 104, 167
 construction failure
 defined, 567
 trail, 575–579
 construction project
 meetings, 527–530
 plan, 535–547
 team, 519–527
 contract documents
 moisture control, 464–472
 using specifications in investigations, 469–470

- water vapor, air, weather barriers/retarders, 471–472
- writing specifications, 470–471
- contractors failure, 567–568
- cooling
 - coils, 120–124
 - of moist air and condensation, 11–12
- cork, 49
- crawl spaces, 166
 - case studies, 193–196
 - residential buildings, 394–396
- creep, wood, 71–72
- curtain wall, 290
 - foundation, 291
 - parapet, 293–297
 - spandrel, 292

D

- deficiency/rework tracking guidelines, 558–565
- dehumidifiers, 192–193
- design
 - professional failure, 569
 - tools, 129–138
 - wind pressures, 404–407
- developments during last decade, 589–590
- dew cell, 142
- dew point
 - hygrometers, 140–142
 - method, 130
- dimensional changes, wood, 65–71
 - bonded wood products, 66–69
 - compression set shrinkage, 70–71
 - stability, 65–66
 - surface checking, 70
 - warp, 69–70
- distribution, air, 124
- driving forces, 112–113
- driving rain, 91
- dual duct, 125
- duct systems, 432–433
- Dunmore, 144
- durability assessment, 594–598

E

- effects on thermal insulating materials, 38–51
- electrical resistance techniques, 145–146
- electrolytic hygrometer, 145
- enclosures, 18
- energy codes, buildings, 488
- envelope water leakage, high-rise buildings, 417–420
- environmental barriers and driving forces, 583
- environmental loads, new residential buildings, 343
- European standards, 477
- evaporation from wet surfaces, 105–106
- exfiltration, 111
- exhaust air, 111
- expanded polystyrene, 46
- experience-based design, 232–238
- exterior climate

- data, 87–103
- elements, 90–91
- exterior moisture problems, 183
- exterior sources, 161
- exterior thermal insulation, 29
- exterior wall moisture problems, 183, 193–215
- extruded polystyrene, 46

F

- facilities contracting process, quality design, 498–503
- failure to warn of known defects, 568–569
- fastener performance, 72–73
- fenestration, ASTM standards, 481–482
- flooded basement, 108
- floors
 - ASTM standards, 485
 - manufactured housing, 430
- fog-type dew point meter, 142
- foundations
 - new residential buildings, 360–362
 - residential buildings, 393–397
 - to wall, 251
- Fourier's law, 38–39
- framed membrane roofing systems, 328–330
- framed water-shedding roofing systems, 320–327
- fresh air ventilation, manufactured housing, 433
- fungal aerobiology, 82
- fungal ecology, 81
- fungi, 80
 - physiology, 80–81

G

- Glaser diagram, 133
- grain angle, wood, 56–57
- ground, moisture source, 109
- growth rings, wood, 56–57
- gutters, residential buildings, 392

H

- heartwood, 57–58
- heat transfer mechanisms, dry insulating materials, 38–39
- heat, air, and moisture (HAM) transport, 1
- heating and cooling equipment, 118–128
- heating of moist air, 11
- high-rise buildings, 378–387
 - air barriers, 416
 - building envelope, 400–425
 - building pressurization/depressurization, 403–404
 - cladding design, 409–416
 - design wind pressures, 404–407
 - envelope water leakage, 417–420
 - humidification/dehumidification, 403
 - masonry cladding, 407
 - mechanical equipment performance, 402–403
 - plaza-deck waterproofing, 420–421
 - precipitation, 413

- roof systems, 407
- roofing and, 422–423
- temperature, 412
- ventilation, 403
- wall systems, 407–409, 423–424
- waterproofing and, 424–425
- weather data, 414–415
- wind effects, 382–387
- wind forces, 413
- historic buildings and preservation, 443–461
 - historic exteriors, 446–456
 - historic interiors, 456–461
 - moisture sources, 443–446
- holistic approach to building design, 16–17
- hot, humid climates, new residential buildings, 351–353
- HUD regulations, manufactured housing, 435–437
- human health effects, 82–86
- human sources of moisture, residential buildings, 398
- humid air, 109
- humidification/dehumidification, high-rise buildings, 403
- humidity ratio, 10–11
- HVAC equipment, 124–125
- hygric properties measurements, 35
- hygrothermal characteristics
 - measurement, 31–35
 - of materials, 16–35
- hypersensitivity diseases, 82–83

I

- ideal gas law, 10
- identification of moisture sources, 161–167
- IECC climate zone map, 489
- improvements, roofs, 316–317
- in-plant construction environment, manufactured housing, 433–434
- indoor moisture problems, 181–182, 183–193
- indoor sources of moisture, 104–108
- infections, 83
- infiltration, 111, 112–115
 - air, 111–116
 - manufactured housing, 433
 - measurement, 115
- insects, 75
- inside exterior walls, 215–219
- inspection of work, 569–570
- installation on site, manufactured housing, 434–435
- institutional buildings, 241
- interior sources, 161
- interior steam leak in historical building, 174–175
- interlocked grain, 57
- interzone airflows, 116
- investigation checklist, 168–169
- ion exchange, 144

J

- Jason, 144
- juvenile wood, 58

K

- Kieper diagram, 133–134
- kitchens, 105

L

- laboratory versus field testing, 157–158
- laminated strand lumber, 59–61
- leakage characteristics for building enclosure, assembly and materials
 - air, 19–21
- legal considerations, 567–579
- libraries and museums, 377
- limiting material performance characteristics, 585–587
- liquid penetration resistance (LPR) test method, 32–33
- liquid transport, 6–7
- loose-laid and mechanically attached membranes, 317–318
- Lyman-alpha hygrometer, 142–144

M

- makeup air, 111
- managing quality, 508–515
- manual design tools, 129–130
 - limitations, 134–135
- manufactured housing, 429–441
 - attics, 431–432
 - duct systems, 432–433
 - floors, 430
 - fresh air ventilation, 433
 - HUD regulations, 435–437
 - in-plant construction environment, 433–434
 - infiltration control, 433
 - installation on site, 434–435
 - moisture dynamics, 429–434
 - mold, 441
 - recommendations, 438–440
 - remediation, 441
 - walls, 430–431
- masonry cladding, high-rise buildings, 407
- material characteristics
 - airflow control, 17–18
 - rain and ground water control, 21–27
- materials, 18
- mature wood, 58
- measurement
 - basics, 153
 - in solid materials, 145–147
 - techniques and instrumentation, 140–158
- mechanical, 144–145
- mechanical equipment performance, high-rise buildings, 402–403
- mechanical ventilation, 111, 115–116
- metal roofing, 318
- microbes, 73
- microbial growth prevention, 84
- mildew

- case study, 571–574
- problems, 182–183
- mineral fibers, 49
- mites, 82
- mixed climates, new residential buildings, 348–351
- modeling heat, air and moisture transport, 9
- moist material measurement, 43–44
- moisture, 61–65
 - caused by building envelope problems, 161–179
 - content of air, 90
 - control issues, quality design, 494–495
 - from occupancy, 166
 - in service, 64–65
 - inside exterior walls, 215
 - manufactured housing, 429–434
 - new residential buildings, 344–347
 - retention curve, 30
 - sources, 104–110
 - transfer to heat transfer, 40–42
 - transport control, 27–31
 - transport equations, 4
- moisture-originated damage, 592–594
 - further needs, 603
 - recent developments, 598–603
- molds, 73–74
 - case study, 571–574
 - manufactured housing, 441
 - new residential buildings, 343–344
 - problems, 182–183
- multifamily housing in northwest, 173–174
- multiple trace techniques, 153
- multizone, 125

N

- natatoriums, 378
- natural durability, 57–58
- natural ventilation, 111, 115
- need for quality design, 495
- neutron thermalization methods, 147
- new commercial buildings, 365–389
 - design, 365–368
 - institutional buildings, 376–377
 - predicting moisture performance, 368–376
- new high-rise buildings, 365–389
- new institutional buildings, 376–377
- new residential buildings, 343–362
 - climate dependence, 343
 - cold climates, 347–348
 - environmental loads, 343
 - foundation assemblies, 360–362
 - hot, humid climates, 351–353
 - mixed climates, 349–351
 - moisture control practices, 344–347
 - roof assemblies, 359–360
 - surface mold, 343–344
 - wall assemblies, 353–359
- North American industry guidelines, 478

O

- open water surface, 107
- organisms, 80
- organizations, for standards, 556–557
- oriented strand board, 59–61
- outdoor air, 111
- outdoor sources, 108–109
- overhang section, 275
- overhanging sloped roof, 278
- owner's role, quality design, 495–496

P

- parapets, 241–249
 - to wall junction, 253–261
- partnering, quality design, 498
- people, moisture source, 104–105
- performance analysis, 584–585
- performance evaluation, design process and, 587–588
- perlite, 47
- phase changes, 3
- phenolic foam, 48
- piezoelectric crystal, 144
- plans and programs for quality control, 530–535
- plants, moisture source, 105
- plaza-deck waterproofing, high-rise buildings, 420–421
- plumbing, residential buildings, 397
- plywood, 59–61
- polyurethane foam, 47
- polyvinylchloride foam, 46
- poor workmanship, 568
- poroelasticity, 600
- precipitation, high-rise buildings, 413
- process-generated moisture, 128
- properties of moist air, 10
- psychrometric calculations, 9–10
- psychrometric chart, 11–12
- punch-out list, 546
- punched window, 264–268, 269–275

Q

- qualitative leak location, 155–156
- quality design
 - architect and engineer role, 496
 - building envelope commissioning, 551–556
 - building industry challenges, 497–499
 - construction contract documents, 515–519
 - construction management firm role, 496
 - construction project documents, 547–551
 - construction project meetings, 527–530
 - construction project plan, 535–547
 - construction project team, 519–527
 - deficiency/rework tracking guidelines, 558–565
 - facilities contracting process, 498–503
 - in building envelope, 493–566
 - managing quality, 508–515
 - moisture control issues, 494–495

- need for, 495
- owner's role, 495–496
- partnering, 498
- plans and programs for quality control, 530–535
- quality concepts, 503–508
- subcontractors, 497
- success tips, 557–558

R

- rain leakage, 107, 163–164
- rain-soaked walls and roofs, 108
- re-roofing, 330–333
 - wet insulation, 336–337
- reaction wood, 58
- recreational sports and entertainment buildings, 377–378
- reheat, 122–124
 - system control, 128
- relative humidity, 10
- relative humidity measurement, 140–145
- remediation
 - manufactured housing, 441
 - mold, 86
- residential buildings, 107–108, 390–398
 - air conditioning, 397–398
 - combustion appliances, 398
 - crawl spaces, 394–396
 - foundation, 393–397
 - gutters, 392
 - human sources of moisture, 398
 - plumbing, 397
 - roof, 390–392
 - slab, 396
 - sump pump, 397
 - surrounding soil, 393
 - ventilation, 398
 - walls, 392–393
 - water from indoors, 397–398
 - water from outdoors, 390–392
 - windows, 393
- return air, 111
- rising damp, 167
- roofs, 313–321
 - and high-rise buildings, 422–423
 - ASTM standards, 480
 - case studies, 198–200
 - high-rise buildings, 407
 - new residential buildings, 359–360
 - residential buildings, 390–392
 - to wall connection, 249–250
 - sill, 282–284, 286–287
 - sill to curtainwall, 279
 - sill to roof, 281
- slab, residential buildings, 396
- sliding snow and ice, roofs, 326
- sling psychrometers, 140
- slope of grain, 57
- sloped glazing, 275
- software for heat, air, moisture (HAM) transport, 135–138
- sorption isotherm (equilibrium moisture content in hygroscopic range), 29–30
- southern climates, 213–215
- spatial climate, 88–89
- spiral grain, 57
- stains, 74
- standard practices and protocols, 177–179
- steady state measurements, 43
- storage of moisture and energy changes, 8–9
- strength, wood, 71
- structural connector, 277
- structural penetrations, 275
- subcontractors, quality design, 497
- sump pump, residential buildings, 397
- sun, 90
- supply air, 111
- surface condensation on windows, 12–13
- surrounding soil, residential buildings, 393
- system selection, 125–129

T

- temperature, 90
 - high-rise buildings, 412
- terminology, moisture control, 473–476
- termites, 75
- tests, 168
 - airtightness, 31–32
- thermal conductivity, 45
 - of wet insulating material, 42–43
 - techniques, 147
- thermal moisture diffusivity, 8
- thermal performance of moist insulation, 49–50
- thermodynamic states of moisture, 1–2
- thin film polymer, 145
- time scale of exterior conditions, 89–90
- toxicoeses, 83–84
- trace gas measurement techniques, 152–153
- transfer air, 111
- transient heat flow measurements, 43
- transport of moisture, 3–4

U

- ultrasonic techniques, 147
- urea formaldehyde foam, 47

V

- sapwood, 57–58
- saturation vapor pressure, 10
- siding, 200–201
- simultaneous heat and mass transfer models, 39–40
- skylights
 - head at wall, 289
 - ridge, 288
- vapor transport, 4–6
- vapor traps, roofs, 315–316
- variable air volume (VAV) reheat, 125

ventilation, 111, 115
 air, 111–116
 high-rise buildings, 403
 requirements, 116
 residential buildings, 398
 roofs, 315–316
 vermiculite, 48

W

walls
 and below grade drainage systems, 25–26
 ASTM standards, 481–482
 drainage systems, 24
 high-rise buildings, 407–409, 423–424
 manufactured housing, 430–431
 new residential buildings, 353–359
 residential buildings, 392–393
 to window details, 252–256
 to window isometric details, 263
 water leakage through, 149–150
 with vapor retarder, 130–131
 without vapor retarder, 131–132
 warm and humid climate, 169–170
 water, 1
 absorption coefficient, 7–8, 26–27, 34
 access limitation, 84–86
 bacteria and, 82

leakage through walls, 149–150
 residential buildings, 390–392, 397–398
 water resistive barrier (WRB), 22
 classification, 22
 performance, 22–23
 testing, 32–34
 water vapor
 permeance and permeability, 5, 28–29
 transmission, 32
 transmission tests, 147–149
 water vapor retarder, 27–28
 water-shedding roofing, 318–320
 waterproofing and high-rise buildings, 424–425
 weather data, high-rise buildings, 414–415
 weatherization, 189–190
 weeping holes and flashings, 24–25
 wet basements, 166
 wet insulation, 335–337
 wind, 90–91
 high-rise buildings, 382–387, 413
 windows
 residential buildings, 393
 surface condensation on, 12–13
 wood
 composition materials, 60–61
 decay, 74
 structure, 54–58
 wood-boring beetles, 75