

Subject Index

A

Acetylcholinesterase monitoring, 780
 Aerosol spray
 permeability testing, 738-744
 Airborne contaminants
 instrumentation for, 454, 477-479, 482
 Airtight suit, 307-313
 Allergens
 electron microscopy chemicals, 389-395
 skin cleaners, 345
 Aluminized fabrics
 molten metal splashes, 137
 American Association of Textile Chemists
 and Colorists
 test method 135-1978, R-85, 699, 707
 American Industrial Hygiene Association,
 6
 Asbestos
 gloves/mittens, 152, 155
 ASTM Committee F23, 3-6
 activities and accomplishments, 3-6
 history of, 3-6
 organization of, 6
 service awards, 5
 subcommittees, 4-6
 ASTM Standards
 D 471-79, 729
 D 568-77, 519
 D 737-75, 33-34, 123
 D 751-83, 850
 D 1059-76, 681
 D 1388-64, 34, 123
 D 1518-85, 123
 D 1682-64, 34
 D 1777-64, 34, 123
 D 1910-64, 123
 D 3775-79, 681
 D 3776-79, 681
 D 4108-82, 110-111, 114-119
 D 3786-80a, 34
 E 96-66, 33-34
 E 96-80, 317
 E 662, 143, 145
 F 739-81, 226, 236, 239, 252-256, 277,
 328, 853

F 739-85, 239-241, 244, 263, 267, 317,
 321, 519, 730, 733, 849, 856
 F 903-84, 5, 853
 F 955-85, 102
 F 1001-84, 853
 F 1001-86, 849, 857, 858
 F 1052-87, 525
 Audit scheme, 401
 Autoradiograph
 chemical permeation tests, 287-288

B

Behavioral science
 protective clothing use, 804
 Biological monitoring
 pesticides, 560-562, 767-768, 770, 780-
 783
 Breakthrough times
 after contamination, 362-367, 369, 372-
 374
 data base, 407
 materials
 butyl, 219, 222-224, 369
 butyl-coated nylon, 320
 butyl rubber, 203-207, 264-265, 330-
 331
 Challenge 5100, 851
 chlorinated polyethylene, 851
 latex, 330-331
 natural rubber, 203-207, 264-265
 neoprene, 219, 222-224, 245-251,
 292, 330-331, 365-366, 369
 neoprene rubber, 203-207, 264-265
 nitrile, 245-251, 362-367,
 nitrile rubber, 203-207, 219, 222-224,
 264-265, 319, 330-331
 Nomex/Teflon, 369
 polyethylene, 203-207, 264-265
 polyvinyl alcohol, 203-207, 330-331
 polyvinylchloride, 203-207, 219, 222-
 224, 330-331, 523
 rubber sheeting, 735
 saran/chlorinated polyethylene, 523

Breakthrough times, materials—

Continued

Tyvek, 330–331, 369

Tyvek/Saranex, 369

Viton, 203–207, 330–331

Viton/chlorobutyl, 230–234, 851

permeation cells, 238–242, 245–251

Breathable fabrics (*See also* Gore-Tex), 295–304

Breathing apparatus

children, 43–49

gas masks, 46–47

emergency air supply, 488

environmental control system, 488

pesticide penetration of, 594–596

self-contained(SCBA), 351

comfort of, 447–450

NFPA standard 1971–75, 433–434

vent valve testing, 536–540

Burn injury (*See* Thermal injury)

Butyl, 219, 222–224, 320, 369

C

Carbon

bonded to latex, 832–846

Carbon-14 labelling

permeation testing, 286–294

pesticide decontamination, 715–726

Certification system

for protective clothing, 7–14

Chain saw handlers

protective clothing for, 159–172

Chambray fabric

physical properties versus comfort factors, 31–42

Chemical Hazard Response Information System(CHRIS), 409–412

Chemical protective clothing (*See also* Gloves; Permeability, clothing/materials; Total encapsulating suits)

adhesives for, 486–487

bibliography, 406

challenge

aerosol, 307–313, 527–528

chemical mixture, 342–343

gas, 307–313, 475–483, 528–530

petroleum/synfuel, 326–338, 342–343

vapor, 501–516

data base, 403–408, 409–412

design qualification tests, 526–528

development of, 847–861

disposable, 368, 373, 375

electronic components operations, 348–355

field evaluation, 307–313, 315–325, 341–346, 475–483, 531–533

simulation of, 501–516

glove dexterity, 50–56

leakage tests, 307–313, 475–483, 501–516, 524–534

ASTM Standard F 1052–87:, 525, 530–531

maintenance of, 492–500

materials

chlorobutyl-coated Nomex, 485–486

chlorobutyl-coated rubber, 212–218, 230–235, 289–290, 320

neoprene elastomers, 290–291

nitrile rubber, 319

polymeric, 204–205, 219–225, 257–268, 269–273, 289–294, 475–483, 848–860

Teflon, 212–218, 230–235, 475–483

Viton, 212–218, 289–290

performance criteria, 399

physiologic measurements, 488–489, 541–553

propellant handler's ensemble, 484–491, 492–500, 541–553

regulation of, 7–14

repair of, 492–500

seam testing, 858–860

selection of, 397–400, 403–408, 409–412, 454–460

self-contained atmospheric protective ensembles(SCAPEs), 484–491

solar radiation testing, 489

solubility parameters for, 197–207, 209–218, 219–225, 226–235, 269–273

standards development, 7–9

test chamber for, 501–516

U.S. coast guard chemical response suit, 209–218, 476–483, 527–530, 847–861

vapor sorption of, 832–846

vendors, 406

Chemical resistance test methods (*See also* Permeability, clothing/materials), 263–266

Chemicals (*See also* Herbicides; Pesticides) airborne, 454

Carbon-14 labelled, 286–294

decontamination (*See* Decontamination, protective clothing)

diffusion coefficients for, 197–207, 257–268, 406

dipropyl sulfide, 307–313

electron microscopy laboratories, 389–395

- Freon 12 gas, 527-529
 - hazardous, 459
 - data base, 409-412
 - response decisions, 454-460
 - helium, 490
 - hydrogen fluoride gas, 475-483, 528-530
 - isoamyl acetate, 502-516
 - low volatility, low water solubility compounds, 277-285
 - marine pollutants, 409-412, 452-460
 - mixtures of, 342
 - permeation testing of, 197-207, 209-218, 219-225, 226-235, 236-242, 243-251, 252-256, 257-268, 277-285, 286-294, 406, 409-412, 852-856
 - polyethylene glycol, 527-529
 - priority list
 - data base, 409-412
 - propellants, 489-490
 - semiconductor operations, 348
 - solvents, 209-218
 - volume change, 406
 - weight change, 406
 - Children
 - respiratory protective clothing for, 43-49
 - Chloramide-ester-congo(CEC), 309-310
 - Citrus grove workers
 - protective clothing for, 611-624, 766-767
 - Climatic conditions
 - hot, humid
 - use of protective clothing, 17-29, 790-792, 803-809
 - thermal clothing
 - comfort of, 25-29, 461-469
 - physiologic responses, 82-86
 - wind penetration potential, 642-643, 645-646
 - thermal stress calculation, 22-27
 - Coatings, high-temperature
 - fiberglass mittens, 142-158
 - Comfort factors (*See also* Thermal comfort)
 - clothing radiant temperature(Clort), 645-646
 - fabric physical properties, 31-42
 - firefighters' clothing, 446-450, 464-469
 - International Organization for Standardization
 - standards for assessment, 17-29
 - pesticide protective clothing, 569-572, 644-647
 - Predicted Mean Vote(PMV) index, 18-19
 - Predicted Percentage of Dissatisfaction(PPD) index, 18-19
 - resin-treated cotton, 121
 - U-values, 644-645
 - Wet Bulb-Globe Temperature(WGBT) index, 21-23
 - woven versus nonwoven fabrics, 31-42
 - Conducting materials, 814-826
 - Conductive heat exposure, 88-100
 - Contamination profile, 371, 390
 - Continuous-feed stirred tank reactor, 832, 836-846
 - Convective heat
 - thermal protection, 119, 129
 - Cotton/polyester, 599
 - CPCbase, 403-408
 - Cut protective clothing, 159-172
 - laboratory test methods, 162-165, 170-172
- D**
- Data base
 - chemical protective clothing, 403-408, 409-412
 - pesticide exposure, 772-775
 - Data presentation
 - chemical protective clothing testing, 13-14
 - Decontamination, protective clothing
 - air drying, 359-367
 - aqueous extraction, 376-385, 717, 720-725
 - dry-cleaning, 697-704, 715, 717, 719-720
 - effect of solvents, 745-749
 - fluorocarbon finish, 671-679
 - Freon 113 immersion, 288-289, 368-375
 - Gore-Tex, 651-659
 - laundrying, 359-367, 651-659, 671-679, 700-702, 705-714, 717, 720-725, 745-749
 - pesticide formulation, 745-749
 - propellant handler's ensemble, 493-494
 - review of, 400
 - sunlight effect, 653-654
 - thermal, 288-289, 359-367, 372, 375
 - U.S. Coast Guard response suit, 459-460
 - vaporization, 717-719
 - Degradation tests, 316, 318-321
 - Dermal exposure, herbicides
 - 2,4-(dichlorophenoxyacetic acid), 625-629

Dermal exposure, herbicides—*Continued*
 pattern of, 625–629
 Dermal exposure, pesticides
 data base, 772–775
 deposition pattern, 578–582, 612–623
 enclosed versus open tractor cab, 605–610
 EPA guidelines for, 765–771
 hand exposure, 767
 monitoring of, 768–769, 776–787
 predictive models, 584–596
 risk assessment, 761–764, 778–779
 video imaging system, 640–648
 work practices, 778–779

Dermal toxicology
 chemical mixtures, 341–346
 epoxy resins, 389–395
 pesticides, rats, 177–192
 Dermatitis
 electron microscopy chemicals, 389–395
 skin cleaners, 345
 Detectable limits, minimum
 chemical permeation, 252–256
 Developing countries
 protective clothing use, 796–800, 802–809
 Diffusion coefficients
 chemicals, 197–207, 257–268, 406
 solute/polymer matrix systems, 261–263
 Dipropyl sulfide
 physical properties of, 309
 protective clothing for, 307–313
 Disposable protective clothing, 368, 373, 375
 worker acceptability of, 32

E

Ecuador
 pesticide use, 802–809
 Electric arcs
 laboratory simulation, 61–68
 protective clothing, 59–80, 829
 Electrical equipment workers
 protective clothing for, 813–831
 Electron microscopy
 pesticide residues, 653–654, 682, 684–687
 Electron microscopy laboratory workers
 protective clothing for, 389–395
 Electronics industry workers
 protective clothing for, 343, 347–355
 Electrostatic protection
 conducting materials, 825–826

Faraday suit, 827–829
 Embedding resins
 allergic effects of, 389–395
 Epoxy resins
 allergic effects of, 389–395
 Eurorpean community
 pesticide regulations, 758
 Evaporative resistance (*See also* Vapor permeability)
 protective clothing, 82–86
 Eye/face protection
 semiconductor workers, 349–350

F

Fabric softeners
 pesticide residues, 705–714
 Face shields, 349–350, 427–428, 433–434
 Faraday suit, 815–831
 Fiber morphology
 pesticide dispersion, 680, 684–690
 Fiberglass
 use in mittens, 142–158
 Fick's law of diffusion, 227–230, 263
 Firefighters' protective clothing, 439–451
 breathing apparatus, 433–434
 comfort factors, 446–450, 464–469
 gloves, 429–433, 469
 helmets, 427–428
 physiological measurements, 444–450, 464–468
 standards, 108–120, 426–438
 ASTM Standard D 4108–82, 108
 National Fire Protection Association
 Standard 1971–86, 108
 steam burns, 415–421
 subjective evaluation, 447–450
 thermal injury, 415–421, 422–437
 underwear, 415–421
 Flame-retardant fabrics, 69–74, 77
 Flashovers
 electrical
 laboratory simulation of, 61–68
 thermal
 protective clothing, 426–438
 thermal injury, 424–425
 Fluorescent tracer
 pesticide skin deposition, 630, 633
 Foot protection
 semiconductor workers, 352
 Fruit orchard workers
 protective clothing for, 565–572, 573–583, 766–767

G

- Gas chromatography
 - hydrocarbon fuels
 - permeability testing, 329
- Gas masks
 - use in children, 46-47
- Gases, in-process
 - semiconductor processing, 348
- Gloves
 - decontamination of, 359-367, 376-385
 - for electron microscopy workers, 394
 - for firefighters
 - standards for, 429-433
 - high-temperature coatings for, 143, 145, 155, 157
 - manual dexterity, 50-56
 - materials
 - asbestos, 152, 155
 - fiberglass, 142-158
 - rubber, 356-385, 394, 858
 - Teflon, 858
 - vinyl-coated, 343
 - Viton, 858
 - Zetex, 142-158
 - nitrile-dipped, 343
 - permeability
 - chemicals, 197-207, 376-385, 858
 - hydrocarbon fuels, 325-338
 - manganese nitrate, 343-344
 - pesticides, 633-634, 727-737, 767
 - single palm versus double palm, 155-156
- Gore-Tex
 - decontamination of, 651-659
 - laundering of, 651-659
 - thermal comfort of, 567, 640-648
- Gravimetric measurements, 315-325

H

- Hand protection (*See also* Gloves)
 - electron microscopy laboratory workers, 393-394
 - semiconductor workers, 350-352
- Hearing protection
 - semiconductor workers, 349
- Heat exchange/transfer
 - fiberglass coated fabric, 147-152
 - moisture, 415-421
 - molten metal splashes, 136-140
 - protective clothing, 82-86, 87-100, 108-120
 - resin-treated cotton, 126-129
 - thermal manniken, 441-444, 446

Heat hazards and protective clothing (*See* Thermal protective clothing)

- Heat measurement
 - electric flashovers, 61-80
- Heat stress (*See* Thermal stress)
- Heat tolerance, 17-29
 - effect of clothing, 17-29
 - exposure limits, 25
 - standards for evaluation, 17-29
- Herbicides
 - 2,4-D, 625-629
 - 2,4-dichlorophenoxyacetic acid, 625-629
 - dermal exposure, 625-629
 - skin deposition, 625-629
- Hot surface contact
 - fabric insulation and, 87-100
- Humidity
 - effect on pesticide penetration, 580-581, 692-696
 - heat tolerance, 27
 - water-repellant fabrics, 295-304
- Hydrocarbon fuels
 - permeability, clothing, 326-338

I

- Immersion cup tests, 316, 318-321
- Industrial hygiene
 - protective clothing
 - role of, 341-346
 - training in use of, 345, 354, 400
- Inhalation exposure, pesticides, 769-770
- Inspection program
 - chemical protective clothing, 401
- Insurance companies, 11
- International Organization for Standardization (ISO), 10, 13, 17
- International Symposiums, 5-6
- ISO Standards
 - 7243, 21-22
 - 7730, 18-19
 - 7933, 22-25
 - 9151, 112-119
 - DIS 9185:1986, 131-141

K

Kawabata Evaluation System (KES), 34-41

L

- Labels
 - household pesticides, 790, 793-794
- Laboratories, 11

- Latex, 330-331
 - vapor sorption of, 834, 839
- Lawn care specialists
 - protective clothing for, 557-564
- Layering
 - protective clothing, 353-354
- Leakage testing
 - aerosols, 525-534
 - ASTM Standard F 1052-87, 525, 530-531
 - gases, 307-313, 525-534

M

- Manniken, thermal, 441-444, 446
- Manual dexterity
 - tests of, 50-56
- Marine pollutants, 409-412, 452-460
- Matrix release, 366, 369
- Methylene blue
 - fabric penetration, 738-744
 - pesticide penetration, 738-744
- Microporous fabrics, 299
- Mittens (*See* Gloves)
- Moisture (*See also* Humidity; Vapor permeability)
 - effect on thermal insulation, 92-94, 118
 - thermal injury, 415-421
- Molten metals impact, 101-107, 131-141, 146, 152, 155
 - ASTM Standard F 955-85, 102
 - ISO DIS 9185:1986, 131-141
- Multiple-layer fabrics
 - electrical thermal protection, 72-75, 77

N

- National Fire Protection Association (NFPA) Standards
 - 1971-75, 426-435
 - 1971-86, 111-112, 114-119
 - 1972-85, 427
- Neoprene, 219, 222-225, 245-251, 292, 330-331, 365, 366, 369
- Neoprene elastomer, 290-291
- Netherlands
 - pesticide regulations, 753-764
- Nitrile, 245-251, 362-367, 363-364
- Nomex, 485-486
- Nonwoven fabrics (*See also* Gore-Tex; Saranex-laminated Tyvek; Teflon; Tyvek; Viton)
 - permeability of, 634-637, 738-744
 - physical properties versus comfort factors, 31-42

O

- Occupational medicine
 - biological monitoring, 560-562, 767-768, 770, 780-783
 - electronics industry, 343
 - pesticide regulations, 757-764
 - protective clothing selection, 341-346
- Office of Toxic Substances (EPA), 257-258, 263
- Olefin, 599
- Organic compounds
 - nonvolatile, 329
 - volatile, 328-332, 334

P

- Pads, protective
 - cut protection, 159-172
- Passive sampling device(PSD), 501-516
- Pennsylvania Bi-Manual Worksample Assembly Test(PBWAT), 51, 54
- Performance criteria
 - chemical protective clothing, 399
- Permeability, clothing/materials (*See also* Chemical protective clothing; Radiation protection clothing)
 - air, 33
 - ASTM Standards
 - D 737-75, 33
 - F 739-85, 244, 263, 267, 317, 321, 519, 730, 733, 849, 856
 - F 1001-86, 849
 - chemical resistance testing, 848-856
 - chemicals (*See* Chemicals)
 - data base, 403-408
 - dispersion mechanism, 680, 684-690
 - effect of fabric content, 602-603
 - effect of fabric finish, 602-603
 - effect of humidity, 580-581, 692-696
 - effect of material thickness, 233-234
 - effect of temperature, 220-233, 580-581
 - fabric and yarn geometry, 681-682
 - ASTM Standards D 1059-76; D 3775-79; D 3776-79, 681
 - field testing, 307-313, 314-325, 341-346, 573-583
 - laboratory tests for
 - Carbon-14 labelling, 286-294
 - chemical resistance methods, 263-267, 848-856
 - dispersion mechanism, 680-691
 - gas chromatography method, 277-285
 - immersion, 316, 319-321
 - manniken use, 589-591, 593-594

- methylene blue dye, 738-744
- permeation cell, ASTM, 220, 230-231, 234, 236-242, 243-251, 727-737
- permeation cup, 316-317, 321
- spray system, 660-670
- temperature/humidity, 692-696
- materials
 - fluorocarbon finish, 671-679, 738-744
 - Gore-Tex, 651-659
 - multiple-layer fabrics, 295-304
 - neoprene, 735
- nitrile, 735
- polyvinylchloride, 523
- rubber, 734-737
- saran/chlorinated polyethylene, 523
- woven versus nonwoven fabrics, 634-637, 738-744
- predictive model for, 257-268
- radioactive liquid, 518-524
- standards development, 7-14
- steady-state permeation rate, 219, 222-224, 238-242, 245-251, 264-265, 318-320, 331-336
- sunlight effect, 653-659
- Permeability, skin
 - keratin and, 273
 - pesticide absorption, rats, 177-192
- Permeation cell
 - Arthur D. Little
 - glove testing, 727-737
 - ASTM, 220, 230-231, 234
 - comparison with standard cell, 236-242
 - glove testing, 727-737
 - versus Radian Microcell, 243-251
- Permeation cup tests, 316-317, 321
 - ASTM Standard E 96-80, 317
- Permeation theory, 227-230, 257-268, 269-273
- Pesticide protective clothing
 - agricultural workers (*See also* specific types, that is, Citrus grove workers), 565-572, 573-583, 584-604, 599-603, 605-609, 610-624, 630-639, 796-800, 802-809
 - comfort factors, 569-572, 591-593, 640-648
 - decontamination of (*See* Decontamination, protective clothing)
 - design of, 558-560, 566-572, 575
 - fabric finishes
 - fluorocarbon, 671-679, 738-744
 - soil-repellent, 697-704, 705-714
 - starch, 705-714, 709-712
 - fabric softeners, 705-714, 709-712
 - field testing, 557-564, 565-572, 573-583, 587-604, 605-610, 611-624, 630-638, 643-644, 646, 776-785
 - experimental design, 780-783
 - gloves, 727-737, 785
 - heat stress, 607-609, 640-648
 - lawn care specialists, 557-564
 - pesticide penetration of, 560-563, 589-591, 593-596, 599-603, 612-623, 625-629, 635-638, 651-659, 660-670, 680-691, 692-696, 727-737, 738-744, 777-778
 - dispersion mechanism, 680-691
 - regulation compliance, 607-609
 - screening methods, 738-744
 - selection of, 774-775
 - starching of, 705-714
 - thermal comfort, 591-593, 607-609, 640-648
 - training in use of, 799-800, 802-809
 - use by householders, 790-792
 - use in developing countries, 796-800, 802-809
 - use in hot climates, 790-792
 - Pesticides
 - 4,4-alpha-trichloromethylbenzylhydrol, 693
 - application methods
 - airblast, 606-608
 - ground boom, 606-608
 - household, 788-795
 - spray, 607-608, 611-624
 - azinphos-methyl, 574-583
 - biological monitoring of, 560-562, 767-768, 770, 780-783
 - captafol, 611-623
 - carbaryl, 716, 746
 - Carbon-14 labelling, 716, 746
 - chlorothalonil, 716, 746
 - chlorpyrifos, 559, 560, 699, 708
 - DDT, 681
 - dermal exposure (*See* Dermal exposure, pesticides)
 - developing countries use, 796-800, 802-809
 - dicamba, 746
 - Dicofol, 693
 - Difolatan 80 Sprills, 611-624
 - dosimetry, passive, 766-767
 - Dursban, 557-564
 - glyphosphate, 746
 - Guthion, 574-583
 - labelling for household use, 790, 793-794
 - LINDAN, 589

Pesticides—*Continued*

- malathion, 631–632, 651–659, 738–744
 - methyl parathion, 672
 - organophosphorous compounds, 729
 - parathion, 609
 - permethrin, 599–603
 - registration of, 753–757, 759
 - regulation of, 753–771
 - risk assessment, 584, 759–764, 772–775
 - and work practices, 778–779
 - skin absorption, rats, 177–192
 - skin deposition (*See* Dermal exposure, pesticides)
 - urinary metabolites, 560–562, 767, 780–783
- Petroleum industry workers
protective clothing for, 326–327
- Phosphorescence, room-temperature
hydrocarbon fuels, 329–330
- Photo-resist procedures
semiconductor processing, 348
- Photoionization detection
hydrocarbon fuel, 329
- Physical properties, protective materials
comfort factors, 31–42
evaluation of, 34–39
- Physiological responses
climatic effects versus clothing, 84–86
- Polyethylene, 203–207, 264–265
- Polymers
ASTM Standard D 3132–84, 211
protective clothing, 204–205, 219–225, 269–273, 289–291, 327–328
predictive model, 257–268
- Polynuclear aromatic compounds, 332–335
- Polyvinyl alcohol, 203–207, 330–331
- Polyvinylchloride, 203–207, 219, 222–224, 330–331, 522–523
- Predicted Mean Vote(PMV) comfort index, 18–19, 22, 26, 28–29
- Predicted Percentage of Dissatisfaction(PPD) index, 18–19, 22
- Propellant handler's ensemble, 484–491, 492–500, 541–553
- Protective clothing (*See* Chemical protective clothing; Firefighters' protective clothing; Pesticide protective clothing; Radiation protective clothing; Thermal protective clothing)
- Psychological reaction
children, 43–49
- R**
- Radiant heat
electrical flashover, 65–66
- thermal protection, 119, 417–421
- Radiation protective clothing
air-supplied suit, 518–524
tritium challenge, 518–524
- Radioactive tracer
pesticide dispersion, clothing, 286–294, 682–683
- Resins
epoxy
allergic effects, 389–395
thermal protective clothing, 121–130
- Respirator valves
leak rate, 538–540
- Respiratory protection devices
children, 43–49
emergency air supply, 488
environmental control system, 488
pesticide penetration of, 594–596
self-contained(SCBA), 351
comfort of, 447–450
NFPA standard 1971–75, 433–434
- Royal Institute of Technology, Stockholm, 6
- Rubber, 203–207, 212–218, 230–235, 264–265, 289–290, 330–331, 734–737
gloves, 327–328
- S**
- Sample trapping system, 278–285
- Saran/chlorinated polyethylene, 519–524
- Saranex-laminated Tyvek, 576–583
- Self-contained atmospheric protective ensembles(SCAPEs), 484–491
- Self-contained breathing device
comfort of, 447–450
NFPA Standard 1971–75, 433–434
- Semiconductor workers
protective clothing for, 352–353
- Sensitization
electron microscopy resins, 389–395
skin cleaners, 345
- Single-crystal ingots, 348
- Single-layer assemblies
electrical thermal protection, 69–72, 74
- Skin
deposition (*See* Dermal exposure, herbicides; Dermal exposure, pesticides)
injuries of (*See* Dermal exposure, herbicides; Dermal exposure, pesticides)
- rats
pesticides absorption, 177–192

- Software
 chemical protective clothing
 data base, 403-408, 409-412
- Soil-repellent finish, 697-704, 705-714
- Solar radiation
 chemical protective clothing, 489
- Solubility parameters
 chemical protective clothing, 197-207, 209-218, 269-273
- Solvents
 flushing of, 371-372
 glove decontamination testing, 377
- Sorption kinetics
 mathematical model, 832-846
- Soybean field workers
 protective clothing for, 599-603
- Specimen mounting
 thermal protection tests, 110-111, 113
- Spray chamber
 pesticide penetration tests, 660-670
- Standards (*See also* ASTM Standards; ISO Standards)
 ASTM committee F23, 3-6
 certification system, 9-10
 chemical protective clothing, 7-9
 conductive clothing, 830
 development of, 3-6, 7-14
 organizations and, 11
 EPA guidelines for pesticides, 765-771
 firefighter's protective clothing, 108-120, 426-438
 gloves for firefighters, 429-433
 international, 7-14
 National Fire Protection Association(NFPA), 426-435
 national systems, 13
 Netherlands, for pesticides, 753-764
 thermal comfort
 ISO standards, 17-29
 thermal protective clothing, 426-438
- Steel yarns, 825
- Steelworkers
 protective clothing for, 101-107
- Sweat
 pesticide excretion in, 783
 rate of versus thermal stress, 22-25
 light activity, 27
- Syringe pump
 permeation testing, 252-256
- T**
- Teflon, 212-218, 230-235, 475-483
- Temperature, elevated
 coated mittens, 142-158
 effect on chemical permeation, 230-233
 effect on pesticide penetration, 692-696
 insulation fabrics, 88-100, 108-120
- Thermal comfort, 17-19
 clothing radiant temperature, 645-646
 influence of clothing, 25-29, 82-86
 pesticide protective clothing, 591-593, 640-648
 standards for, 18
 U-values, 641-642, 644-646
 vapor permeability, 591-593
 various fabrics, 640-648
 wind penetration potential, 642-643, 645-646
- Thermal injury
 firefighters, 415-421, 422-437
 flashovers, 422-426
 hot surface contact, 87, 92
 molten metal splashes, 139-140
 test simulations of, 108, 114
- Thermal protective clothing (*See also* Firefighters' protective clothing)
 electrical flashovers, 59-80
 hot surface contact, 87-100
 insulation of, 20-21, 27, 87-100
 International Organization for Standardization(ISO) standards, 17-29
 measurement of, 88-89, 92, 102-107, 109-119
 ASTM Standard D 4108-82, 110-111
 ISO 9151, 111-119
 NFPA 1971, 111-112
 mittens, fiberglass, 142-158
 moisture barrier in, 448-449
 molten steel impact, 101-107
 physiological strain, 82-84
 resin-treated cotton, 121-130
 standards for, 17-29, 426-438
 state of the art technology, 435-438
 thermal manniken, 440, 441-444, 446
 underwear, 415-421
 vapor permeability, 118
- Thermal stress
 influence of clothing, 82-86
 propellant handler's ensemble, 550-552
 standards for, 17-29
 WBGT index, 21
- Thermography, 819, 820
- Total encapsulating suits (*See* Propellant handler's ensemble; Self-contained atmospheric protective ensembles(SCAPEs); U.S. Coast Guard chemical response suit)
- Toxicology
 pesticide regulation, 759-764

Tractor drivers
 dermal exposure, pesticides, 605-610, 611-624
 protective clothing for, 605-609, 610-624
 Tritium
 ASTM Standard F 739-85, 519
 chemical protective clothing for, 518-524
 Tyvek, 330-331, 369, 567-569

U

U.S. Coast Guard
 Atlantic strike team, 452-460
 chemical response suit, 209-218, 476-483, 527-530, 847-861
 fabric testing, 848-861
 glove testing, 858-860
 visor testing, 856-857
 data base, 409-412
 Underwear
 thermal injury protection, 415-421
 Urinary metabolites
 pesticides, 560-562, 767, 780-783
 Utility workers
 protective clothing for, 60-63, 74-80

V

Vapor permeability
 heat stress calculation, 22
 latex-bonded carbon, 832-846
 protective clothing, 82-86, 448-449, 832-846
 mathematical model, 82-83, 832-846
 moisture barrier, 448-449
 thermal comfort, 591-593
 thermal insulation, 92-94, 118
 water-repellent fabrics, 296-299, 302
 woven versus nonwoven fabrics, 33, 37

Vapor prime
 semiconductor processing, 348
 Vent valves
 leak rate, 538-540
 Vermiculite
 use as coating, 143-158
 Video imaging
 pesticide skin deposition, 630-639
 protective clothing evaluation, 630-639
 Viton, 203-207, 212-218, 230-235, 330-331, 475-483
 Viton/chlorobutyl, 230-234, 851
 Viton/chlorobutyl laminate, 289-290
 Volatility
 chemical contaminants, 376

W

Water-repellent fabrics, 295-304
 dynamic testing of, 299-303
 Water rinsing
 glove decontamination, 376-385, 383-384
 Water solubility
 chemical contaminants, 376
 Wet Bulb-Globe Temperature(WBGT) Index, 21-23
 Wind penetration potential
 thermal comfort, 642-643, 645-646
 Wool
 molten metal splashes, 138
 Woven fabrics
 ASTM Standards
 D 3775-79, 681
 D 3776-79, 681
 comfort of, 31-42
 permeability
 chemicals, 634-637
 pesticides, 738-744
 vapor, 33, 37