

Subject Index

A

Admixtures (*see also* Fly ash; Lime-stone; Silica fume; Slags)
 accelerating, 109
 chemical, 106–127
 mineral, 106–143
 compressive strength, 115, 116, 118, 120
 drying shrinkage, 115, 116
 water-reducing, 109
 Air entrainment, 29, 93
 deicer scaling, 41
 efficiency factor, 96
 Air-void systems, 43
 Alkali-aggregate reaction
 ASTM Standard C 441-81, 12, 17
 correlation with Blaine fineness, 26
 correlation with vitrification, 27
 sulfur trioxide content, 26
 Alkali silica expansion, 5
 Anhydrite, 7
 ASTM Committees
 C-1 on cement, 1
 ASTM nomenclature, 8
 ASTM specifications
 blended/portland cements, 1
 clinker versus slag content, 8
 ASTM Standards
 C 39-83a, 32, 110
 C 109-80, 9, 11, 16, 31, 109, 121
 C 114-82a, 16
 C 157-80, 31, 110
 C 186-82, 12, 16, 31
 C 191-82, 31

C 204-81, 16
 C 441-81, 12
 C 469-81, 110
 C 666-80, 32
 C 672-76, 32

B

Belgian Standard B 12-213 for cement
 heat of hydration, 12
 BENELUX (Belgium, Netherlands, and Luxembourg) cements
 compressive strength of, 9
 nomenclature of, 8
 production of, 5
 sulfur trioxide content, 7
 Blaine fineness (*see* Fineness)
 Blast-furnace slags (*see* Slags, blast-furnace)
 Brine, hot, test for cement durability, 139
 British Standard 1370 for cement heat of hydration, 12

C

Calcium chloride, 109, 120
 Calcium hydroxide, 130, 138
 hydration of fly ash, 65
 various blended cements, 140
 Calcium lignosulfonate, 109
 Calcium sulfate, 7
 Calorimeter, isothermal conduction, 12

Cembureau (European Cement Association), 146

Cements (*see also* Portland cement; Low-heat cements; Pozzolans; Slags)

 production, world-wide, 152

Chemical analysis

 ASTM Standard C 114-82a, 16

Chemical composition (*see also* Oxide composition)

 blended cements, 32

 clinker, portland, 17, 51

 slag, blast-furnace, 17, 31, 51

Chemical properties, various cements, 150

Chloride ion, diffusion of, 12

Clinker, portland, 6, 17, 51, 107, 145

Cold weather (*see* Temperatures, low)

Compressive strength

 ASTM Standard C 39-83a, 32, 110

 ASTM Standard C 109-80, 9, 16, 31, 109, 121

 Belgian/US comparison, 11

 BENELUX cements, 9

 Blaine fineness, 18-20, 34

 calcium chloride, 126

 creep, 57

 curing method, 35

 cylindrical concrete specimens, 110

 flexural strength, 123

 ground granulated blast-furnace slags, 33-47

 hydration heat, 24, 53

 mineral admixtures, 115, 116, 118

 mortars, 33-39

 portland cement pastes, 114

 sulfur trioxide content, 19-22

 temperature, 35, 98

 water/solid ratio, 115, 116, 118, 133

 workability, 96

 vitrification, 19-23

Container, concrete, 128

Cracking, shrinkage, 139

Creep

 compressive strength, 57

 differential sorption, 57

Curing

 accelerated, 38

 moist, 35, 38, 109

Cylinder strength

 air/water content, 95

 ASTM Standard C 39-81, 11

 temperature, 98

D

Data processing, 131

Deicer scaling (*see* Scaling, deicer)

Differential sorption, 53-57

Diffusion coefficients of ions, 12

Drying shrinkage (*see* Shrinkage, drying)

Durability

 correlation with freeze-thaw cycles, 43, 47

 correlation with permeability, 139

 hot brine test, 139

E

Efficiency factors, 89-105

 mass-strength, 89

 air entrainment agent, 96

 as "break-even" cost factor, 93

 fineness, 99

 formula, 92

 ignition loss, 99

 use of superplasticizer, 96

 workability, 96

 maturity, 89

 calculation of, 102

 formula, 92

Elastic modulus, 110

Energy conservation, 1, 127

Environmental protection, 145

European cement standards, 144

 testing methods, 147

European Committee for Standardization, 144

Expansion of concrete

- alkali silica, 5
- ASTM Standard C 441-81, 12, 13
- chloride/sulfate water, 139
- de-ionized water, 139

F**Fineness**

- alkali-aggregate reaction, 26
- ASTM Standard C 204-81, 16
- compressive strength, 18–20, 36–37, 40
- hydration heat, 33
- sulfate resistance, 25

Flexural strength versus compressive strength, 123**Fly ash, 89, 106–143**

- Belgian, 65–88
- effect on cement microstructure, 68–71
- hydration mechanism, 65–88
- particle size distribution, 112
- permeability and pore structure, 128–143
- pore size distribution, 73–82
- pozzolanic activity, 71–73
- surface area, 112

Formulas

- cement permeability, 132
- cement workability, 91
- efficiency factor
 - mass-strength, 92
 - maturity, 92
- hydraulic index, 5

Freeze-thaw cycles

- ASTM Standard C 666-80, 32
- durability, 44, 47

G**Glass (*see also* Vitrification)**

- blast-furnace slags, 17
- compressive strength, 19–23

Groundwater, granitic, 128**Gypsum, 7, 19, 20, 106****H****Heat of hydration**

- Blaine fineness, 33
- clinker composition, 21
- compressive strength, 24
- low-heat cements, 12
- standards,
 - ASTM C 186-82, 12, 16, 31
 - British 1370, 12
 - Dutch NEN 3550, 12
 - sulfur trioxide content, 33

Humidity, effect on compressive strength, 36**Hydration**

- blast furnace slag blends, 138
- blended cements
 - slurries, 52
 - solid cubes, 52
- fly ash blends, 65, 138
- hydraulic index, 54
- silica fume blends, 138

Hydraulic index

- formula, 5
- hydration, 54
- slag quality, 6

Hydraulicity,

- blast-furnace slag, 5, 98
- factor, computation of, 5, 98
- fly ash mixtures, 98
- portland cement mixtures, 98

Hydrochloric acid, 65**Hydrofluoric acid, 65****I****Ignition loss, 99****International Organization for Standards (ISO), 144**

- conversion of ISO standards to ASTM C 109 Standard, 9, 11

K**Kerosene, in differential sorption tests, 54**

L

- Limestone, 106
 - particle size distribution, 112
 - surface area, 112
- Low-heat cements, 12

M

- Mass-strength efficiency factor (*see* Efficiency factor, mass-strength)
- Maturity efficiency factor (*see* Efficiency factor, maturity)
- Mehta test, 17
- Mercury porosimetry, 65, 131, 135–138
- Microstructure, fly ash blends, 65
- Mortars
 - ASTM Standard C 109, 9, 16, 31, 109, 121
 - compressive strength, 33, 35, 40
 - drying shrinkage, 42
 - freeze-thaw cycles, effect of, 44
 - ground granulated blast-furnace slags, 29–48
 - particle size distribution, 106–127

N

- Netherlands NEN-3550 Standard, heat of hydration, 12
- Network formers/modifiers, 6
- Nomenclature
 - blended cements, 8, 144
 - European Committee for Standardization, 144
 - portland cements, 144
 - pozzolanic cements, 144

O

- Oxide composition
 - blast furnace slags, 51, 93, 111, 130
 - fly ash, 66, 93, 111, 130
 - limestone, 111

- portland cements, 51, 93, 111
- silica fume, 111, 130
- various cement materials, 111, 130
- Oxides in hydraulic index formula, 6

P

- Particle size distribution, effect on cement performance, 106–127
- Pastes
 - cement
 - fly ash blends, 65–88, 106–127
 - microstructure of, 65–88
 - portland, 106–127
 - pozzolanic, 106–127
 - ground granulated blast furnace slag, 29–48
 - particle size distribution, 106–127
 - pore structure, 65–88, 128–143
- Permeability
 - coefficients for various cement blends, 134
 - formula, 132
 - kerosene, 57, 106
 - pore structure, 128–143
 - water, 58–59, 131–132
- Permeability cell diagram, 132
- Phospho-gypsum, 7
- Plastic mortar test, 146
- Poissons ratio, 110
- Pore size distribution, 65, 131–138, 139, 141
- Porosimetry, 65–87
- Porosity, mercury intrusion curves, 135
- Portland blast-furnace slag cements, 5–64, 88–143
 - nomenclature, 3
 - standards, 144–153
- Portland cements (*see also* Clinker, portland)
 - blast-furnace slag blends, 5–64, 88–143
 - controlled particle size blends,

106–127
efficiency factors, 89–105
fly ash blends, 65–105
silica fume blends, 106–143
standards, 144–153
Potassium ion, diffusion of, 12
Pozzolan cements, 106–127
standards, 144–153
Pozzolan activity, fly ash blends, 65
Production, commercial cement, 5,
144
Pyknometer bottle, 51, 57–58

Q

Quartzite, 53
Quantachrome automatic scanning
porosimeter, 131

R

Radioactive waste disposal, 128
RILEM-Cembureau test method, 146
Rock flour, 92

S

Scaling, deicer
ASTM Standard C 672-76, 32
cement air content, 41–43
Seawater corrosion effect, 5
Setting time
ASTM Standard, C 191-82, 31
measurement with Vicat needle, 109
pastes/mortars, 33
Shrinkage
chemical, 49–64
drying 139
ASTM C 157-80, 31, 110
effect of mineral admixtures, 115,
116, 123
sulfate content, 42
Silica fume, 106–143
particle size distribution, 112

specific surface area, 112
Slags (*see also* Portland blast-furnace
slag cements)
blast-furnace
applications, 5
chemical composition, 17
chemical shrinkage, 49–64
differential sorption, 49–64
particle size distribution, 106–127
performance, 5, 89–105
permeability, 128–143
review, 5–14
standards, 5–14, 144–153
blast-furnace, pelletized, 128
ground granulated blast-furnace,
29–48
ground iron blast-furnace, 6
Sodium ion, diffusion of, 12
Standards
blast-furnace slags, 5–14
European, review, 144–153
sulfur trioxide content, 7
Strength (*see* Compressive strength;
Cylinder strength; Flexural
strength)
Sulfate content (*see also* Sulfur tri-
oxide content)
drying shrinkage, 42
groundwater, 128
heat of hydration, 33
Sulfate resistance, 5, 17–18, 110, 125,
128
Blaine fineness, 25
expansion of cements, 17
glass content, 24
Sulfonated naphthalene formaldehyde,
109
Sulfur trioxide content
alkali-aggregate reaction, 26
compressive strength, 19–22
standards, 7
Superplasticizer, 93, 96–97, 101
Surface area, various cement materi-
als, 112

T

Temperatures, low
 compressive strength, 35
 construction with concrete, 29
 curing, 38–39, 44

V

Vicat needle, 109
Vitrification (*see also* Glass)
 alkali-aggregate reaction, 27
 compressive strength, 19–23

 measurement by X-ray diffraction,
 17
 sulfate resistance, 24

W

Waring blender, 109
Water, permeability of, 58–59, 131
Water reducer, 128
Water/solid ratio, 109, 128–143
 compressive strength, 115, 116, 118
Workability, 90–91, 93, 96, 133