

Index

A

adverse weather conditions
 compaction in, 18–19
 ASTM D558, 22, 25–26, 51, 52
 ASTM D559, 26
 ASTM D560, 26
 ASTM D698. *See* Standard Proctor Test (ASTM D698)
 ASTM D1556. *See* sand cone method (ASTM D1556)
 ASTM D1557. *See* Modified Proctor Test (ASTM D1557)
 ASTM D2166, 22
 ASTM D2167. *See* rubber balloon method (ASTM D2167)
 ASTM D2216. *See* oven-dry method (ASTM D2216)
 ASTM D2435, 22
 ASTM D2850, 22
 ASTM D2937. *See* drive cylinder method (ASTM D2937)
 ASTM D3107, 42
 ASTM D3665, 39
 ASTM D4253, 16, 22, 27–29, 43, 54
 ASTM D4254, 16, 22, 27–29, 43, 54
 ASTM D4287, 30
 ASTM D4564, 30, 39–40
 ASTM D4643. *See* microwave-oven method (ASTM D4643)
 ASTM D4718, 32, 34, 36, 53–54
 ASTM D4914. *See* sand replacement in test pit method (ASTM D4914)
 ASTM D4944. *See* calcium carbide gas pressure tester method (ASTM D4944)
 ASTM D4959. *See* direct heating method (ASTM D4959)
 ASTM D5030. *See* water replacement in test pit method (ASTM D5030)
 ASTM D5080. *See* rapid determination of percent compaction (D5080)
 ASTM D5084, 22
 ASTM D6938. *See* nuclear method (ASTM D6938)
 ASTM STP523, 43
 ASTM test methods, 1, 4–5, 8, 22
 Atterberg Limits, 8

B

backfill, 9, 11f, 36
 backscatter mode
 of nuclear gauge, 36, 37f, 38

C

calcium carbide gas pressure tester method (ASTM D4944),
 25, 44, 48–54, 87f, 91f
 calibration curve with, 49–50, 88f
 and nuclear density method, 38
 and sand replacement in test pit method, 42
 Casagrande, Arthur, 2–3
 CH soil, 30, 35
 clay, 13–17, 22, 51–52
 clayey soil, 13–15, 17–19, 52–54
 clay silt, 22
 CL soil, 30, 33, 35
 cohesionless soils, 15f, 16t
 equipment used with, 16, 20

 methods for evaluating density and unit weight of,
 26–29
 relative density methods for, 22
 and sleeve method, 40

cohesive soils
 and rubber balloon method, 33
 and vibrating tamping foot rollers, 20

compacted soil
 soil classes of, 68t
 typical properties of, 64–65t
 variables determining density of, 2

compaction, 13
 in adverse weather conditions, 18–19
 effect of compactive effort on, 14f
 effect of effort of on penetration resistance, 61f
 effects of on shrink and swell of soil, 16–17
 equipment for, 3, 9, 11, 19–20, 66–67t
 history of, 2
 impact methods of and types of soil for, 22
 influence of on engineering properties, 16–18
 quality control flow chart for, 60f

compaction curve, 2
 for dry density, 25
 and energy applied, 13f
 family of, 8f
 of gravel, 15
 for modified compaction test, 14, 23
 and percent saturation, 26f
 for reference density, 71f, 72f
 relationship of to ZAV curve, 15
 of sand, 15f, 28f
 of soil-cement mixtures, 25
 for standard compaction test, 14, 23
 for wet density, 25
 compaction tests, standard reference, 22–23

D

density
 and cohesionless soils, 16, 22, 26–29
 compaction curve for dry density, 25
 comparing to standard reference, 51, 55
 curve for for dry soil conditions, 19
 of finer particle rock fill, 43
 index test method of, 26–29
 and nuclear method, 36, 38, 39
 plotting of, 59
 and rapid determination of percent compaction, 55–57
 relative method of, 22, 27f, 29
 and rubber balloon method, 33
 and sand replacement in test pit method, 40–41
 and sleeve method, 40
 variables determining, 2
 and vertical vibration, 28
 of very-coarse-grained soils, 42–43
 density, standard reference, 14
 compaction curve for, 71f, 72f
 comparing to compacted soil, 51, 55

influence of on engineering properties and performance
 of soil, 22
 and Modified Proctor Test, 54
 selection of, 4–5, 55
 and Standard Proctor Test, 54
 density test, in-place, 8, 12, 30
 and clayey soil, 17–18
 and cohesionless soils, 16
 comparing to laboratory tests, 55, 59
 and drive cylinder method, 51, 78f, 79f
 and nuclear method, 51–53
 and rubber balloon method, 51, 52, 76f, 77f
 and sand cone method, 51, 52
 and sand replacement in test pit method, 52
 and silty soil, 17–18
 and water replacement in a test pit method, 43, 52, 80f, 81f
 and ZAV curve, 15
 direct heating method (ASTM D4959), 25, 44, 47–48, 51, 52, 54
 and finer particle rock fill, 43
 moisture determination using, 86f
 and nuclear density method, 38
 direct transmission mode
 of nuclear gauge, 36, 37f, 38
 diskings, 12f
 drainage zones, 9
 drive cylinder method (ASTM D2937), 8, 19, 30, 35–36, 51, 78f, 79f, 90f
 dumped fill, 9

F

family of curves, 55, 57, 58f, 62f, 63f
 field-testing methods, 19
 fine-grained soil, 22
 free-draining soil, 22
 freezing temperatures, 18–19
 frost-heave problems, 16

G

GC soil, 30, 33
 GM soil, 30, 33
 grading, 12
 grain size distribution, 8
 gravel, 52–54
 compaction testing of, 15–16
 and relative density method, 22

H

heat sink
 and microwave-oven method, 47
 hydraulic fill, 9

L

linear construction, 12f
 low-plastic soil, 20

M

mass, 13f, 33, 42
 method compaction control, 54
 MH soil, 30, 33, 35
 microwave-oven method (ASTM D4643), 25, 44, 46–47, 51, 52, 54

and nuclear density method, 38
 and sand replacement in test pit method, 42
 summary data sheet for, 85f

ML soil, 30, 33, 35

Modified Proctor Test (ASTM D1557), 3, 14, 23–24
 and compaction characteristics of soil, 22, 51, 52
 comparing in-place density test to, 59
 comparing to degree of compaction, 55
 and maximum dry density, 54
 and maximum dry unit weight, 29
 and rubber balloon method, 34
 and sheepsfoot roller, 20
 steps of, 24–25

moisture content test. *See* water content test

moisture-density

curve for, 2f, 22
 and sand cone method, 74f, 75f
 test methods for, 25–26

N

nuclear density method, 36–39
 nuclear gauge, 5, 8, 19, 36–39
 nuclear method (ASTM D6938), 30, 36–39, 44, 50–54, 90f, 91f
 compaction test data for, 82f
 and rapid method, 55

O

one-point compaction test, 55, 57–58
 one-point Proctor test, 55
 organic soils, 47
 oven-dry method (ASTM D2216), 4, 25, 32, 44, 45–46, 51, 52, 54, 56, 84f
 and calcium carbide gas pressure tester method, 48–50
 and finer particle rock fill, 43
 and nuclear density method, 38
 and rubber balloon method, 34
 and sand replacement in test pit method, 42

P

penetration resistance curve, 17
 penetrometer needle test (ASTM D1558), 17
 percent compaction, 51
 plastic rebound, 14
 Proctor, R. R., 2

R

rapid determination of percent compaction (ASTM D5080), 19, 30, 52, 55–58
 and drive cylinder method, 35
 and rubber balloon method, 33
 and sand cone method, 31
 rollers, 9, 11, 19–20, 89f
 rubber balloon method (ASTM D2167), 30, 33–35, 51, 52, 54, 90f
 in-place moisture-density determination for, 76f, 77f

S

sand
 compaction curves for, 15f, 28f
 compaction testing of, 15–16
 and relative density method, 22

sand cone method (ASTM D1556), 8, 19, 30–33, 31f, 51, 52, 54, 90f
 density and calibration for, 73f
 in-place moisture-density determination for, 74f, 75f
 sand replacement in test pit method (ASTM D4914), 30, 40–42, 52, 54–55
 sandy fine grained soil, 51–52
 sandy silt, 22
 saturation, 25, 30
 SC soil, 30, 33, 35
 sieve, 8
 silt, 13–15, 51–52
 silty soil, 17–20, 52–54
 sleeve method, 39–40
 SM soil, 16, 22, 30, 33, 35
 soil
 classification system of, 2–3
 engineering use of, 10t
 testing samples of, 5, 8
 soil-cement mixtures
 test methods for, 25–26
 soil liners, 11
 soil load, 30
 soil mass stress, 30
 “Speedy Moisture Meter Test,” 48–50
 Standard Proctor Test (ASTM D698), 2, 3, 14, 19, 23–24
 and compaction characteristics of soil, 22, 51, 52
 comparing in-place density test to, 59
 comparing to degree of compaction, 55
 and maximum dry density, 54
 and maximum dry unit weight, 29
 and rubber balloon method, 34
 and sheepsfoot roller, 20
 steps of, 24–25

T

test fill report, 89f
 test pit configurations, 40f
 tractor, crawler, 20

U

uncontrolled fill, 9
 Unified Soil Classification System (ASTM D2487), 3, 49, 69f

Unified Soil Classification System (ASTM D2488), 3, 70f
 unit weight, maximum dry, 25, 29
 unit weight test, 24–30
 and drive cylinder method, 35
 and rubber balloon method, 33
 and sand cone method, 30–32
 and sand replacement in test pit method, 40–41
 and sleeve method, 40

V

vertical vibration, 28
 void ratio, 30
 volume, 33, 40, 42

W

water content, maximum, 22
 water content, optimum, 2, 14, 24–25
 and compaction, 16–17
 comparing to compacted soil, 51
 and penetrometer needle test (ASTM D1558), 17
 and rapid method, 56
 and water-retaining structures, 9
 water content test, 8, 17f, 24, 43–45
 comparing to optimum water content, 51
 and drive cylinder method, 35, 36
 and nuclear density method, 36–39
 and oven-dry method, 45–46
 and rapid determination of percent compaction, 55–57
 and rubber balloon method, 33, 34
 and sand cone method, 30–32
 and sand replacement in test pit method, 42
 summary data sheet for, 83f
 water replacement in test pit method (ASTM D5030), 30, 42, 43, 52, 54–55
 in-place moisture-density determination for, 80f, 81f

Z

zero-air voids, 14–15, 25, 55, 59
 zoned earth fills, 11, 12f