

Subject Index

A

ABAQUS, 58–66
 ADINA, 390
 Aging
 polyethylene pipes, 453
 Type 304H stainless steel, 153–172, 181
 Alloys
 800/800H, 112–125, 195–213
 316L steel, 27, 32–53
 4340 steel, 340–357
 7075-T6 aluminum, 416–431
 A710 steel, 340–357
 A533B steel, 243–272
 chromium-molybdenum steel, 58–66,
 129–152
 chromium-molybdenum-vanadium steel,
 15–19
 HSLA steel, 340–357
 HY100, 363–386
 iron-nickel-chromium, 112–125, 195–213
 low-alloy steels, 129–152, 340–357
 nickel-molybdenum-vanadium steel, 401–
 413
 nickel structural steels, 298, 301–316, 340–
 357
 Type 304H steel, 153–172, 363–386
 Aluminum, 7075-T6 alloy, 416–431
 Annealing, 453
 ASTM Committee E-24, 1
 ASTM Standards
 A 469-82: 401
 E 292-83: 154
 E 399-83: 154
 E 647-83: 362
 E 813-81: 206, 302, 341, 345–347, 363,
 448–449
 E 1153-87: 154

B

Bilby, Cottrell, and Swinden (BCS) model,
 433–444

C

C* parameter
 Alloy 800H, 118–125, 194–195, 206–213
 low-alloy steels, 142–143
 Type 304H stainless steel, 161–172
 void growth mechanisms, 96–97, 105–108
 Caustics, 318–339, 331(illustration), 341–
 357, 343(illustration)
 Cavities (*See* Void growth mechanism)
 Center crack tensile specimens
 A533B steel, 250–264
 chromium-molybdenum steel, 58–66
 small scale creep, 58–66
 Ceramics, 457–469
 ceramic composite, 469
 Chromium, in steel alloys, 15–19, 58–66,
 129–152
 Coherent optics, 415–431
 Cold working, Alloy 800H, 113, 116–
 118(tables)
 Compact tensile specimens
 5% nickel steel, 340–357
 4340 steel, 340–357
 HSLA steel, 340–357
 HY100 alloy, 154–157, 363
 low-alloy steels, 131, 340–357
 nickel-molybdenum-vanadium steel, 401–
 413
 polyethylene, 448
 Computer programs, 35–43, 58–66, 390
 Computer simulation, 132(illustration),
 148(illustration), 365–366
 Concrete, 457–469
 Crack bridging, 460
 fiber, 469
 Crack closure
 Alloy HY100, 382–383, 386
 ceramic/ceramic composite, 462, 467–469
 concrete, 462, 467–469
 Type 304H stainless steel, 382–383
 Crack-tip growth velocities, 77–83

Crack-tip opening displacement

7075-T6 aluminum alloy, 421–423,
423(table)

A533B steel, 249–250, 250, 251(tables),
264

Alloy 800H, 202

ceramic/ceramic composite, 462–469

concrete, 462–469

gage, 285–297, 299, 302, 316

polyethylene pipe, 454–455

Crack-tip stress fields

caustics measurement of, 318–339

dislocation-free zone model, 433–444

Hutchinson-Rice-Rosengren, 28–29, 71,
274–281, 319, 326–329, 336–339

Riedel and Hui, 71–74

Riedel and Rice, 29

Creep, small-scale (SSC)

and C_r parameter, 7–25, 55–66

Mode I propagating crack, 68–94

Creep crack growth

at elevated temperatures (*See* Tempera-
ture, elevated)

global approach, 47–48

in helium environment, 112–125,
118(table)

metals

316L stainless steel, 27, 32–53

Alloys 800/800H, 112–125, 116–
118(tables), 195–213

low-alloy steels, 127, 130–143, 145–148

Type 304H stainless steel, 153, 154–158,
158(table), 161–172, 164(table), 169–
172, 173–193

Mode I fracture, 68–94

nonproportional, 173–193

non-steady state, 55–66

one-dimensional model, 88–93

power law exponent, 77, 97

small scale, 7–25, 55–66, 68–94

transient regime, 8–25

by void coalescence, 96–110

continuous, 101–103

discrete, 103–105

Creep ductility

Alloy 800H, 195–213

low-alloy steels, 136–142, 148–152

Type 304H stainless steel, 168–172

C_r parameter, 7–25, 18(table), 55–66

D

Damage mechanics, 125, 173–193

damage growth law, 177–181, 184

Deformation behavior

7075-T6 aluminum alloy, 415–431

A533B steel, 252–264

Deformation plasticity, 389, 407

delta J

fatigue crack growth, 361–386

usefulness of concept, 3

Dislocation emission, 435, 439–444

Dislocation-free zone (DFZ), 433–444

Drop-tower testing, 285–297, 298, 301–316

Ductile fracture, 243

Dynamic fracture

caustics measurement, 318–357

drop-tower fracture specimen, 247–297,
298–316

planar compact tension fracture specimen,
340–357

small-scale notched bend ductile fracture
specimen, 242–272

three-point-bend drop-tower fracture
specimen, 274–297

three-point-bend ductile fracture speci-
men, 217–240

uniaxial ductile fracture specimen, 242–
272

wide plate ductile fracture specimen, 242–
272

E

Elastic-plastic fracture

caustics measurement of, 318–339, 343,
347–357

metals

3% nickel structural steel, 298–316

Alloy 800H, 195–213

Alloy HY100, 363–386

high-strength steels, 318–339, 343, 347–
357

Type 304H stainless steel, 363, 378–387

solid cylinder, 388–413

symposia on, 1–2

thin-walled tube, 388–413

Electron microscopy, 139, 141, 157, 165,
167–168(illustration)

Embrittlement, due to creep, 127–152

F**Fatigue**

- constant-amplitude loading, 418–431
- J*-integral range, 361–386
- precracking, 361–386, 448–449, 455–456
 - ASTM Standard E 813-81: 363, 448–449
- torsional loading, 388–413

Finite element analysis

- caustics measurement, 327–329
- center-crack specimens, 58–66
- ceramic/ceramic composite materials, 467
- concrete materials, 467
- creep crack initiation/growth, 35–43
- Mode I crack growth, 74–88, 323–339
- nozzle neck, reactor, 143
- small scale creep, 19–24, 37, 38(tables), 55, 74–88
- three-point-bend fracture specimens, 227–240, 274–297, 467
- tubular specimens, 389–413

Fluid catalytic cracking units (FCCU), 153**Fractographs, 139, 158–159, 171, 452****Fracture process zone, 458, 462–466****Fracture toughness, 264–272, 274–297****ASTM Standards**

- E 399-83: 154
- E 813-81: 206, 302, 341, 448–449

G**Gages, crack-tip opening displacement, 285–297, 299, 302, 316****H****Heat-affected zone (HAZ), 129****Helium, 117, 118(table)****High-temperature fracture mechanics (*See* Temperature, elevated)****I****Impurity elements**

- effect on ductility, 136–142
- in reactor metals, 129, 133, 137, 145–146
- Incoloy 800/800H (*See* Alloys, 800/800H)
- Iron-nickel-chromium alloy, 112–125, 195–213

J***J*-integral**

- caustics measurement of, 318–339, 340–357
- fatigue crack growth, 361–386, 388–413
- high temperature effects, 195–213
- polyethylene pipe, 447–456
- three-dimensional crack front, 218–240, 274–297, 337–339
- torsional loading, 388–413
- usefulness of concept, 3
- viscoelastic material, 447–456

J*-resistance curves*ASTM Standards**

- E 813-81: 345–347
- E 1151-87: 154
- A533B steel, 269–271
- high temperature effects, 195–213
- nickel structural steel, 298–316

L**Load estimations, Nakamura, 282–283****Loading**

- constant amplitude, 418–426
 - ASTM Standard E 647-83: 362
- cyclic, 181–193, 361–386, 388–413, 415–431, 433–444
- direct-current potential drop (DCPD), 196–202
- drop-tower, 285–297, 298–316
- Mode I, 69–94, 323–339, 388–413
- Mode II, 388–413
- Mode III, 388–413
- partial unloading compliance (PUC), 196–202
- rate of, 242–272
- small-scale, 323–339
- variable amplitude, 415–431

M**Metallographic studies, 123–124(illustration)****Mode I fracture, 69–94, 323–339, 388–413****Mode II fracture, 388–413****Mode III fracture, 388–413**

Moiré interferometry, 416–431, 417(illustration), 421(table), 423(table)
 Molybdenum, in steel alloys, 15–19, 58–66, 129–152, 403–413
 Multiaxial specimens, 173–174, 181–193

N

Nickel, in steel alloys, 298, 301–316, 340–357, 401–413
 Nonmetals, 447–469
 Notched bend specimens, 154, 242–272, 301–316
 deformation of, 255–257
 NOVNL, 35–43

O

Optical measurements, 318–339, 331(illustration), 340–357, 343(illustration), 415–431, 417(illustration)
 Overload effects, 427

P

Piping, 447–456
 Plane strain, Type 304H stainless steel, 169–170
 Plane stress analysis, high-strength steels, 323–339, 340–357
 Plasticity
 crack-tip, 420
 cyclic, 173–174, 181–193
 deformation, 389, 407
 Polyethylene, 447–456
 Post weld heat treatment (PWHT), 129
 Potential drop, 407
 Power-law creep exponent, 77, 97

R

Ramberg-Osgood model, 321
 Razor-notched specimens, 449, 455–456
 Reactors, 127–152
 life estimation of, 143–144
 Recrystallization, Alloy 800H, 113, 116–118(tables)

Rupture tests, 154–158, 158(table), 169–171
 ASTM Standard E 292-83: 154

S

Semielliptical surface notched tensile specimens, 250–264
 Silicon nitride, 469
 Single-edge notched specimen, 418
 Slow constant extension rate technique (SERT), 129–131, 135
 Specimens (*See* specific types, *i.e.* Center crack tensile, Tubular)
 Steels
 4340, 340–357
 A710, 340–357
 A533B, 243–272
 chromium-molybdenum, 58–66, 129–152
 chromium-molybdenum-vanadium, 15–19
 high-strength, 285–297, 340–357
 HSLA, 340–357
 low-alloy, 129–152, 340–357
 nickel-molybdenum-vanadium, 401–413
 nickel structural, 298, 301–316, 340–357
 Steels, stainless
 316L, 27, 32–53
 Type 304H, 153–172, 363–386
 Strain rate, A533B steel, 244, 246–272
 Strain softening, ceramic specimens, 460
 Stress-intensity factor, 37, 398–401, 406, 418
 Stress-strain field, 35–43

T

TDFM (*See* Time-dependent fracture mechanics)
 Temperature, elevated
 effect on creep crack growth, 15–19, 31–43, 68–94, 115–118, 129–152, 130(table), 161, 169, 184–193, 195–213
 effect on deformation and ductile fracture, 242–272
 effect on *J*-resistance curves, 195–196, 202–206, 207–213
 Three-dimensional crack analysis, 217–240, 274–297, 337–339

Three-point-bend specimens, 218, 223–240,
274–297, 277(illustration), 301–316,
467
Time-dependent fracture mechanics
(TDFM), 55
Torsion, 388–413
 and tension, 174–193, 395–397
Transient regime, creep crack growth, 7–25,
55–66, 96–110
Transition time, 48–49, 277–281, 290–291
Tubular specimens, 173–193, 388–413
Turbine generator, 15, 388–413

U

Uniaxial specimens, 245–249
 deformation of, 252–253

V

Vanadium, in steel alloys, 15–19, 403–413
Viscoelastic materials, 447–456
Viscoplastic materials, 173–193
Void growth mechanism, 96–110, 143,
147(illustration)
 nucleation, 98–110, 99(illustration)

W

Wide-plate specimens, 250–252
 deformation of, 252–264
 fracture of, 264

Z

ZEBULON, 35–43