

Subject Index

A

Acceleration, 120, 126, 132
 Accelerometer, 130, 284-285
 Acetal, 351-367
 Acrylonitrile-butadiene-styrene (ABS), 236-237
 bottles, 19
 ductile-brittle transition, 240-242, 245-246
 fatigue testing, 282
 impact behavior of, illustration, 166
 incipient crack formation testing, 327-333
 terpolymers, 176
 Aircraft materials and structure, 224, 227
 Aluminum alloys, 166
 energy absorption, 234
 impact data, 171
 Type 6061 T6, 221
 Analog/digital (A/D) converter, 12
 Analog/digital (A/D) resolution, 14
 Antialiasing filter, 84
 Aramid-reinforced composites, 219-235
 ASTM Committee D-20 on plastics, 45, 174
 ASTM standards
 D 256-81: 19, 147, 162, 284, 285
 D 256-84: 237
 D 638-82a: 262
 D 790-81: 149, 266
 D 1709-15(1980): 148
 D 1822-83: 162
 D 1822-84: 147

D 2585-68(1980): 221
 D 3029-82: 164, 165
 D 3763-79: 19, 178, 183
 E 23-82: 180, 182
 E 399-83: 349, 353

Automotive applications

 dart impact evaluation of materials, 44-57
 impact data for steel and aluminum in, 171
 impact stress states in, 28-30, 31-32
 impact testing materials, 24-43
 plastics in, 58, 162

B

Bending

 biaxial, 27, 39, 43, 160
 illustration, 31-32
 table, 28
 normal shear, 39
 uniaxial, 27, 43
 illustration, 31-32
 table, 28

Bismaleimide systems, 253, 259

Boat laminates, 192-197

Bottles, burst pressure, 221, 223, 226-227, 233, 234

Boxcar function, 84-86, 94
 illustration, 88

Break

 elongation at, 148, 239
 energies, 282
 point, 34-35
 response, 42

Brittle behavior, 94, 98, 350
 Brittle-ductile transition, 329, 330
 Brittle initiation, 344
 Bulk molding compound (BMC), impact damage, 303
 Bump impact, 192
 illustration, 196, 198, 202, 204–205
 table, 199, 203
 Burst pressure, 221, 223, 226–227, 233, 234
 Burst testing, 226–227

C

Carbon dioxide, 105
 Carbon fibers, 221, 223, 226, 230, 233, 234
 Charpy testing, 39, 54, 59, 145, 147, 159
 apparatus, 166
 evaluation of composites, 180–183
 inadequacies, 164, 168, 169
 of metals, 16, 284
 Cinematography, high-speed, 284
 Circuit board laminates, table, 171
 Composite materials
 aramid-reinforced, 219–235
 in automotive applications, 41–42
 impact controlling variables, 28–33
 table, 36
 instrumented dart impact evaluation, 44–57
 selecting impact tests, 25–28, 43
 table, 39
 testing analysis and specifications, 35–41
 illustration, 37
 carbon fiber, 223, 226, 230, 233, 234
 glass fiber, 180, 181
 graphite/epoxy, 248–249, 253–260
 impact behavior analysis, 58–80

 impact characterization, 248–261
 impact damage tolerance, 219
 nonmetallic, 169
 prediction of end-use impact resistance, 187–216
 Compression characteristics, 122–123
 Compression testing
 of foams, 140–141
 static, 127
 Compressive strength, 260
 Computer simulation of impact response, 313–317
 Crack, 49, 53
 extension of, 49–50
 formation in polymers, 324–334
 initiation, 53, 54, 269
 instability, illustration, 354
 length, 346–347, 355, 359–363, 366
 penetration depths, 329
 propagation plane, 362
 Cracks, multiple unstable, 325
 Crack tip
 blunting, 359
 stress field around, 74
 Craze, 314, 362
 deformation, 245
 initiation, 240–241, 245–246
 multiple, 237
 termination, 240
 Crystalline materials, 290, 292, 298, 300, 359
 Cushioning material, 119
 deformation, 121–122
 impact and compression testing of, 118–142
 Cylindrical blowout, 328

D

Damage measurement method, 259, 260

- Damping, 141
 - characteristics, 118–120, 124
 - in cushioning material, 127–130
 - effect of, 136, 140
 - illustration, 121
 - quarter cycle, 132–134
 - table, 136
 - Rayleigh, 119
 - Deceleration, impact, 120, 130–135
 - Deflection, 46–47, 110
 - absorbing, 32–33
 - at failure, 99
 - yield, 151
 - Deformation, 54, 119
 - biaxial flexural, 47
 - in cushioning material, 121–122, 127
 - ductile, 331
 - elastic analysis, 271
 - filament wound pipe, 200
 - of foams, 135, 136
 - without fracture, 314
 - idealized dart, 47–50
 - impact velocity and, 315
 - illustration, 316
 - linear elastic, 33
 - linear load-deflection, 47, 49
 - with partial impacts, 306, 317–320
 - illustration, 316
 - plastic, 33, 49
 - with ram displacement, 310
 - rates, 238
 - stable or slow-rate, 49–50
 - stages and transitions, 50
 - Delamination, 180, 233, 260
 - glass fiber/resin matrix, 200
 - inhibition of, 253
 - plastic, 52
 - Density, 11, 108
 - Discontinuities, 85, 166
 - Displacement, 119
 - compression, 126–127
 - nodal, 123
 - reliability of values, 284
 - Driven dart testing, 145, 149–151, 155, 160–161
 - Drop dart testing, 145, 148, 159, 160
 - illustration, 149
 - Drop height, 329
 - Drop testing
 - of low-energy compression impact, 123–130
 - polystyrene, 136–141
 - results, table, 130
 - Drop tower, 332, 333
 - impact tester, 325
 - instrumented, 175, 178
 - Drop tower impact testing, 220, 333
 - impact fatigue testing of polymers, 281–301
 - table, 328
 - Drop-weight testing, 59, 145
 - limitations, 165
 - machines, 10
 - Ductile failure, 239, 245
 - Ductile-brittle material, 84, 86
 - illustration, 92
 - Ductile-brittle transition, 237, 239–242, 244–246
 - Ductility index, 166–169, 173–174
- E**
- Elastic distortion, 119
 - Elastic modulus, 349
 - Elongation at break, 148, 239
 - Embrittlement (*see also* Failure, brittle) 268, 270, 275, 276, 277
 - End-use impact resistance, 187–216
 - Energy, 47
 - absorption, 32, 241, 259, 298
 - in ductile fracture, 287–289
 - analysis of measurement, 337–350
 - break, 110–111, 282
 - calculation and filtering effect, 83
 - to crack, 110–112
 - deformation, 119

Energy (*cont.*)

- elastic, 64
- fracture, 113, 238, 244–245, 294–297, 346–347
- illustration, 239, 243
- impact, 30, 110, 251, 252, 268, 281, 282, 289, 290, 309–310, 312–313
- absorption, 223–224, 227, 228
 - illustration, 230–232
- criterion for material selection, 333
- normalization, 300
- penetration depth and, 331
- thickness and, table, 171
- at ultimate failure, 325
- velocity and, 332
- with incipient damage, 260
- potential, 12
- propagation, 56, 57
- returned and retained, 292–294
- strain, 342–344
- total, 39–40, 151
- yield, 40, 64, 151

Energy (absorbed)-deflection traces, 149

Expoxies

- glass-fiber-reinforced, 170
- rigid and soft, 221, 233

Ethylene-propylene copolymer injection molded disks, 274

F**Failure**

- brittle, 84, 85, 109, 266–271, 274–277, 286, 310
 - illustration, 272
- catastrophic, 311
- component, 21
- criteria, 19–20
 - illustration, 21
- with different test methods, 154–155

- ductile, 84, 239, 245, 266, 266–270
- fiber, 223
- incipiency of, 35
- mode, 109, 165, 272, 306
 - table, 275
- plane-strain, 362, 363
- shear, 200
- short and long-term, 290
- total, 64–66
- transspherulitic, 362, 366
- Failure limits, impact, 33–35, 152
- Falling dart impact test apparatus, 325
- Falling weight testing, 39–40, 148, 263
- Fatigue
 - constant-load, 290
 - damage caused by, 21
 - impact, 281–301
 - response, 4–5
- Fatigue testing, 281–301
- Fiber breakage, 34–35
- Filament wound pipe, 197–203
- Filter
 - antialiasing, 84
 - electronic variable, 285
 - low-pass, 88, 97, 98
 - illustration, 92, 100, 102
 - notch, 97
 - two-pole, 87
 - illustration, 91
 - universal for impact testing, 100
- Filtering, 14–15
 - analog, 14, 81, 100
 - digital, 15, 18, 81–102
 - effect, 83
- Finite element (FE) analysis, 73–75, 118, 123
- Finite element grids, 75–77
- Flaws, 314
- Flex impact testing, 145, 149, 155, 162
 - illustration, 150
- Fluorocarbon, 105

Foam
 deformation, 135-136
 nonuniform and uniform density
 of, 107
 Force/deflection, 149, 164-165
 Force measurement analysis, 337-350
 Fourier transform approach, 81-82, 96
 Fracture
 behavior, 236-247
 brittle, 287, 289-290, 297-298
 cracking, 306
 ductile, 286, 287, 297-298
 energy, 238, 244-245, 292-297
 illustration, 239, 243
 morphology, 362
 Fracture mechanics analysis, 342-349, 359
 Fracture toughness, 5, 60, 66-73, 245
 degree of, 62
 dynamic, 78
 effect of loading rate on, 351-367
 testing, 353-355
 transitions, 356-359, 363
 Frequency domain methods, 81, 82
 Frequency spectrum, 94-95, 99-100
 illustration, 96, 97

G

Gardner testing, 107-108, 113-115
 anvil, 148, 160, 162
 apparatus, 325
 1.25-in. ring, 148
 standard, 39-40, 148, 157, 162
 Gas bubbles, 106, 107, 113
 Gas counterpressure (GCP) method, 107
 Geometries, 68-74
 configuration, 108

dependency in printed circuit boards, 171
 illustration, 77-78
 impact, 145
 impact problems, 82
 influence of, 176, 177
 Graphite/epoxy composites, 174, 248-249, 253-260

H

Helmets, 118-119
 Hole diameter (specimen), 264-265
 Hydrodynamic-elastic-magneto-plastic code (HEMP), 313

I

ICI/Battenfeld (Billion) process, 107
 Impact
 controlling variables, 28-33, 42
 damage assessment, 303
 digital filtering of data, 81-102
 energy, 30, 281
 failure limit, 33-35
 idealized histories, 82-89
 low-pressure thermoplastic structural foam, 105-116
 problem, model of, 90-95
 puncture
 illustration, 207-208
 table, 209
 strength, 164
 toughness, 290
 Impact behavior
 brittle-ductile, 151, 165
 of plastics and composites, 58-80
 Impact characteristics, 3-4
 of low-pressure single-component thermoplastic structural foam, 113
 new composite materials, 248-261
 in polymers, 324-334

- Impact characteristics (*cont.*)
 testing, simulation, and interpretation of, 117-143
- Impact fatigue treatment, 325
- Impact modulus, 346-349
- Impact parameters, key, 25-26, 28, 33, 37
- Impact resistance
 assessment of, 303, 325
 composite ranking, 259
 of polyether sulphone, 268, 276
 prediction, 187-216
- Impact response of polymeric materials, 302-323
- Impact speed (*see* Velocity, impact)
- Impact stress states, 26-32, 36, 41, 188
 illustration, 151
 in impact testing, 159, 160-162
 one and two-dimensional, 314
- Impact tester, 108, 303, 325
 high-rate, 188-192, 215, 303, 304
 variable-speed, evaluation of, 58-80
- Impact testing (*see also* Compression testing; Puncture testing)
 analysis of force and energy measurements in, 337-350
 of aramid-reinforced composites, 219-235
 comparative evaluation, 152-157
 correlation of methods, 145, 157-162, 174-177
 data interpretation, 9-23
 for end-use applications, 3
 flexed-plate, 262-277
 good, conditions for, 24, 155-157
 high-speed, 81
 historical review, 165-166
 instrumented dart, 44-57
 instrumented systems, 13
 methodology, 2-3, 144-162
 methodology for selecting, 24-43
 parameters, 10-18, 169-170
 partial, 4-5
 of polyether sulphone, 262-277
 of polymeric materials, 163-186
 program/design development, 127, 178
 rate dependency, 173-174
 rate sensitivity, 170
 repeated blows, 287-289, 325
 single-blow, 281-282, 286, 297, 300
 specification of methods, 37-40
 test applicability, 19-22, 153, 154-155
 test-specific effects, 23
 utilization of data, 18-23
 variable-rate, 163-186
- ISO/DIS 6603/1, 263, 264
- ISO Draft Specification 6603/2, 19
- Izod testing, 33, 39, 54, 59, 145
 excess-energy pendulum, 107
 extension of, 284
 inadequacy, 164
 notched, 147, 157, 159, 162
 of polyvinyl chloride, 242
 reverse notched, 147, 159
 of rubber-modified polymers, 237
- ## K
- Kevlar, 197
 illustration, 226
 improved, 233-234
- Kevlar 29, 221, 227, 230, 233-234
- Kevlar 49, 173-174, 221, 227, 230
- ## L
- Laminates
 E glass, 193, 197
 honeycomb-core, 220, 224-226, 233, 234
 S glass, 193, 197
 skin/core, 192-197
 solid, 220

Laser-Doppler system, 338
 illustration, 340
 Laser-Doppler techniques, 338, 342, 349
 Light beam/photodetector, 13
 Linear elastic fracture mechanics (LEFM), 66, 352
 Linear load-deflection behavior, 52
 Linear variable displacement transducer (LVDT), 46
 Load, 46, 47
 ductility index and, 168
 dynamic, 59, 119
 failure dynamic, 78
 histories, 82, 86-89, 98-99
 illustration, 92
 idealized, 84
 inertial, 15-16
 maximum, 49, 53
 monotonic increase and decrease, 12
 oscillations of, 50, 51-52, 57
 range and time, 10-13
 resolution, 12
 Load cell/amplifier, 54
 Load-deflection, 47, 50, 53, 56-57, 79
 signals, 64-67
 Load-displacement history, 83
 Loading
 biaxial, 44
 compressive, 119
 geometry, 27, 44
 impact, 26-27
 material behavior under, 188
 rate effect, 351-367

M

Macrocracking, unstable, 50
 Matrix molecular weight effects, 240-242
 Melt flow rate (MFR), 178
 Microprocessor system, 188, 215

Mold-filling process, 106-107
 Molecular energy absorption, 26
 Molecular relaxation mechanisms, 358, 366

N

Noise
 characterization, 95-97
 excessive, 134
 generation, 82
 level, 98
 reducing or removing, 14, 82, 89
 sources, 94
 Nomex aramid structural sheet, 221
 NONSAP program, 77, 123, 126
 Noryl test plaque, 109
 Notched specimen development, 262-277
 Nylon 66, 282, 286-297
 Nylon A, 285, 287-300
 Nylon B, 286-294
 Nylon-reinforced reaction injection molding (RRIM), 52-53
 Nyquist criteria, 84

O

Oscillations
 amplitude, 16, 120
 creation of, 82
 excessive, 134
 harmonic, 16-18
 of load, 50-52, 57
 source and frequency, 17
 Oscilloscope, 122, 285
 digital, 249-251, 325-326
 external, 60, 62

P

Parametric material evaluation, 18-19

- Pendulum impact apparatus, 164, 338-339
- Pendulum testing, 145, 147, 159
- Penetration depths, 302-323
- Penetration testing, 251-252
- Photodetector triggers, 14
- Plastics
- automotive applications, 44-57, 162
 - damage, 52
 - deformation, 49
 - fatigue response, 4-5
 - foaming, 106
 - impact behavior analysis, 58-80
 - industry, 59
 - instability, 52
- Polyacetal, 282, 290
- Polycarbonate, 59, 60, 62-80
- behavior, 263
 - load range, 12
 - thickness, 177
- Polycarbonate film, 282
- Polyether sulphone (PES), 262-277
- Polyethylene
- high-density (HDPE), 60, 64-80, 97-101, 303, 313, 338, 344
 - computer simulation, 313-317
 - impact responses, 304-313, 318-322
 - illustration, 305, 316
 - table, 308
 - low-density (LDPE), 59
 - low-pressure high-density (HDPE), 108
 - terephthalate (PET), 282
 - ultrahigh-molecular-weight, 282
- Polymers, 58 (*see also* Crystalline materials)
- dynamic impact loading, 351
 - impact characteristics for incipient crack formation, 324-334
 - impact fatigue, 281-301
 - impact response with depth of penetration, 302-323
 - rubber-modified, 236-247
 - semicrystalline, 359
 - structure, 188
 - thermoplastic, 59
 - toughness, 281
 - ultimate strength, 188
 - viscoelastic, 120-121, 163-186
- Polymethyl methacrylate, 177, 351-367
- Polypropylene
- drop testing, 136
 - failure, 154
 - foam, 123-141
 - glass-reinforced, 181
- Polystyrene, 98, 313
- acrylonitrile (PSAN), 237, 241
 - illustration, 242
 - drop testing, 136-141
 - foam, 121
 - high-impact (HIPS), 236-237, 282, 313-317
 - illustration, 299, 305
 - impact responses, 303-313, 318-322
- Polystyrene plaques, 109
- Polyurethane foam, 121, 123, 130, 131
- illustration, 131, 138
- Polyvinyl chloride (PVC)
- rubber modified, 236
 - fracture behavior of, 242-245, 246
 - sheeting, extruded, 176
- Puncture impact
- illustration, 207-208
 - table, 209
- Puncture resistance, 203-215
- Puncture road hazards, 203-204
- Puncture testing, 54, 56, 108-113, 200, 203-215, 259
- illustration, 49
- R**
- Ram displacement, 192, 197, 200 310-311

Ram penetration, 193, 200
 Ram travel distance, 304, 309–310, 311
 Reaction injection molding (RIM) material, 27, 52–53, 55–56, 154
 Reinforced reaction injection-molded polyurethane (RRIM) material, 59, 64–80
 Resin, 106–107, 113
 carbon fiber in, 221
 polyphenylene oxide-based, 109
 properties, 109, 223
 rigid, 233
 Ringing, 17
 postfailure, 94
 reducing amplitude, 17–18
 Road testing, 203–215
 Rubber, 206
 effect on ductile-brittle transition, 240

S

Scanning electron microscopy, 355, 364–366
 Service failure criteria, 19–20
 Servohydraulic machines, 56, 325
 Sheet molding compound (SMC), 27, 59, 62–80, 303
 SMC-R65 material, 50, 55–56
 SPE ANTEC Conference, 177–178
 Specimen shape, 145
 Stiffness, 35, 90–91, 124
 bending, 259
 compression, 124–127
 flexural, 313, 322
 properties of cushioning material, 119
 Strain energy release rate, 342–344
 Stress
 concentrators, 314
 distribution, 271–274
 high-tensile-yield, 262

 impact, 188
 tensile, 314
 Stress intensity factor, 282
 critical, 344–346, 349
 Stress intensity factors (SIFs), 60
 calculation/computations, 74–75, 77–78
 Stress states (*see* Impact stress states)
 Stress whitening, 310–311, 314, 328

T

Tearing, 27, 43, 53, 54
 Temperature effects, 236–247, 253–259, 329–332
 Tensile tester, high-speed, 147
 Tensile testing, 145, 147–148, 157, 162
 Tensile toughness, 148, 233
 illustration, 231
 Tension
 biaxial, 27–32, 43, 160
 normal shear, 43
 uniaxial, 27, 43
 illustration, 31
 table, 28
 Test fixture design, 145
 Test frequency effect, 291
 table, 292
 Test rate effects, 236–247
 Thermoplastics, 175, 305 (*see also* specific types)
 impact test data, 178, 183
 structural foam (TSF), 105–116
 Thickness
 dependency, 170–173
 effects, 107, 180, 291–292
 illustration, 318–319
 end-use, 57
 after impact, 306
 increasing, 327
 skin, 108, 113
 strength and, 176–177
 of tire, 204–205

- Three-point bend testing, 245
- Through-penetration testing, 251-252
- Time
 - history, 89-92
 - illustration, 98-99
 - load range and, 10-13
- Time-velocity data, 342, 344
- Tire
 - construction variables, 209-215
 - materials, 206
 - puncture resistance, 203-215
- Titanium alloys, 166
- Torso-head-helmet impactor system, 118
- Toughness, 292, 344
- Toughness transitions, 356-359, 363-366
- Triggering method, 13-14
- Tup
 - acceleration, 165
 - natural frequencies, 17
 - velocity, 15
 - vibrations, 14
- U**
- UFX 82-17, 221
- Ultimate force, 151
- Ultrasonic C-scan, 259, 260
- Uniaxial tensile testing, standard, 52
- USM expanding mold method, 107
- V**
- Velocity, 120
 - in finite element simulation, 126-127
 - impact, 16-17, 45, 46, 132, 134, 180-185, 309, 315-317, 322, 332, 333
 - measurements, 60-64, 338-342, 349
 - pendulum, 338
 - illustration, 341
 - testing, 16, 60
- Velocity-time data, 342, 344
- Video testing, high-speed, 45, 54-55
- Y**
- Yield, 33-34, 49, 149
 - behavior, 154-155
 - characteristic of, 52
 - deflection, 151
 - energy, 40, 64, 151
 - point, 35, 56
 - position, 52
 - response, 42
 - strength, 239