

Author Index

A

Aiyangar, A. K., 15-24
 Anderson, M. C., 222-233, 234-245,
 273-286
 Anderson, P. A., 15-24, 37-50
 Au, A. G., 15-24

B

Beger, J., 134-153
 Blice, R. L., 66-72

C

Cheng, B. C., 154-168
 Cobian, D., 37-50
 Cook, D. J., 154-168
 Cuchanski, M., 154-168

D

Daehn, N., 37-50
 Dawson, J. M., 171-180
 Day, J. S., 73-94

F

Fisher, J., 51-65
 Froehlich, M., 97-118
 Fröhlich, M., 119-133

H

Hall, R., 51-65
 Hansen, T., 3-14
 Heiderscheit, B., 37-50
 Hyde, P., 51-65

I

Isaza, J., 73-94

J

Jensen, L. M., 171-180, 255-272

K

Kincaid, B. L., 255-272
 Konz, R. J., 255-272
 Krüger, S., 134-153
 Kurtz, S. M., 73-94

L

Linovitz, R., 66-72
 Lissy, C. J., 222-233, 273-286
 Lissy, D. A., 234-245, 273-286

M

MacDonald, D., 73-94
 Metheny, C. W., 25-32

N

Niosi, C. A., 97-118

P

Pirris, S. M., 154-168
 Ploeg, H.-L., 15-24
 Prevost, J., 181-199

R

Rubín de la Borbolla, I., 181-199
 Rundell, S. A., 73-94

S

Schilling, C., 134-153
Schwarzenbach, O., 119-133
Scifert, C., 181-199
Seebeck, J., 119-133
Shah, V. G., 273-286
Shorez, J. P., 200-209
Siskey, R., 73-94
Spenciner, D., 210-221

T

Thompson, R. E., 97-118, 119-133
Turner, J., 181-199

V

Vadapalli, S., 246-253
Vicars, R., 51-65

W

Welch, W. C., 154-168
Wing, C., 134-153
Woods, D. L., 246-253

Z

Zimmers, K. B., 66-72

Subject Index

A

anterior-posterior, 171-180
 artificial lumbar disc, 66-72
 ASTM, 37-50, 154-168
 ASTM F1717, 171-180, 181-199, 210-221
 ASTM F2077-03, 25-32
 ASTM F2624-07, 222-233, 234-245
 ASTM F543, 255-272
 axial gripping capacity, 246-253
 axial pullout, 255-272

B

biomechanical study, 154-168
 biomechanical testing, 200-209
 biomechanics, 3-14, 15-24, 134-153
 bone screw interface, 154-168
 bone screws, 255-272

C

center of rotation, 134-153
 Charite, 51-65
 compression-shear, 25-32
 corpectomy, 154-168, 171-180
 cyclical loading, 154-168

D

daily living motion, 37-50
 disc, 51-65
 disc arthroplasty, 37-50
 disc replacement wear test, 73-94
 discectomy, 181-199
 driving torque, 255-272
 dynamic pedicle-screw system, 134-153

dynamic stabilization, 222-233, 234-245
 dynamic stiffness, 222-233

F

F1717, 273-286
 F1717 construct stiffness, 273-286
 F1717 fixture, 273-286
 F1798, F1717, interconnection, 246-253
 fatigue, 171-180
 fixture, 25-32
 flexibility protocol, 154-168
 flexibility testing, 97-118
 flexible rods, 181-199
 frequency, 66-72
 FSU model, 3-14
 fusion, 210-221

G

growth rods, 200-209

I

insertion load, 255-272
 interbody device, 15-24
 interlaboratory study, 210-221
 ISO, 37-50

K

kinematics, 134-153

L

lateral mass bone screw, 154-168
 load application, 97-118

load-sharing, 181-199
 lumbar, 73-94
 lumbar fusion device, 3-14
 lumbar spine, 97-118
 lumbar total disc replacement,
 119-133
 lumbar vertebra, 15-24

N

non-fusion implants, 97-118

P

pedicle screw, 171-180
 PEEK rods, 181-199
 pin diameter, 273-286
 pin material, 273-286
 pocket, 25-32
 polymer, 181-199
 polymeric, 181-199
 polyurethane foam, 15-24
 posterior cervical fixation,
 154-168
 posterior stabilization, 234-245
 primary stability, 119-133
 Prodisc, 51-65
 prosthetic wear testing, 37-50

R

range of motion, 3-14
 replacement, 51-65

S

scoliosis, 200-209
 self-drilling, 255-272
 self-tapping, 255-272
 semirigid, 181-199
 shear, 119-133, 171-180, 181-199
 single-level constructs, 181-199
 spinal construct, 210-221
 spinal implants, 246-253
 spinal kinematics, 37-50
 spine, 3-14, 73-94, 134-153
 spine implants, 222-233
 stability testing, 3-14
 static, 25-32
 subsidence, 15-24
 surrogate, 15-24
 synthetic vertebra, 15-24

T

TDR, 51-65
 total, 51-65
 total disc replacement, 66-72
 tribology, 51-65

V

vertebrectomy, 171-180
 viscoelastic, 66-72

W

wear, 51-65