

## Index

- A**
- aboveground storage tank (AST), 119–120
  - accelerated corrosion tests, 335
  - acidity
    - ethanol, 27, 29
    - methanol, 30
  - acidity test, for white mineral oils, 252
  - acid number
    - biodiesel fuel, 64, 66
    - diesel fuels, 54
    - fuel oils, 200 (table), 203
    - nonaviation gas-turbine fuel, 54
    - total, 103–104
  - additives
    - aftermarket, 153
    - anti-foam, 149
    - anti-icing, 91, 94
    - antioxidant, 90, 94, 150, 294
    - anti-wear agents, 294, 309
    - automotive engine oils, 289, 293–294
    - aviation fuels, 87–94, 89 (table)
    - biocides, 92, 94, 151
    - California regulations on, 152
    - cetane number improver, 147–148
    - color dyes, 89–90, 94, 146
    - conductivity, 91–92, 149
    - contamination control, 151
    - corrosion inhibitors, 90–91, 151
    - defoaming, 294
    - de-icer, 149
    - demulsifiers, 151
    - detergent, 294
    - diesel fuel, 143, 146–153, 148 (figure), 150 (table)
    - diesel ignition improvers, 147–148
    - dispersants, 150, 294
    - distribution system additization, 152
    - drag reducer, 149
    - engine and fuel delivery system performance, 147
    - fuel cleanliness, 151
    - fuel handling improvement, 149–150, 150 (table)
    - fuel stability, 150
    - fuel system icing inhibitor, 91, 94
    - gasoline, 143–146, 153
    - gum inhibitors, 90
    - ignition control, 93
    - injection during RPVOT, 306
    - injector cleanliness, 148, 148 (figure)
    - leak detector, 92, 94
    - low temperature operability improver, 149–150, 150 (table)
    - lubricity, 90–91, 148
    - metal deactivator, 90, 94, 150
    - nonspecification, 92
    - oil, 289
    - pipeline drag reducer, 92–93
    - smoke suppressants, 148
    - spark-ignition engine, 11, 12 (table)
    - stabilizers, 150
    - static dissipater, 91–92, 94
    - TEL, 89, 94
    - tests for, 93–94
    - thermal stability improver, 92, 94
    - U.S. regulations, 14–15
    - viscosity modifiers, 293–294
  - aftermarket fuel additives, 153
  - air atomizing, 38–39
  - air-atomizing burners, 195
  - air compressor oils, 282
  - aircraft wing tank, undetectable water in, 124 (figure)
  - Alcohol and Tobacco Tax and Trade Bureau (TTB), 24–25
  - alcohols, 55
  - alkyl ester biodiesel, test methods needed for, 211
  - all-levels sample, 135
  - aluminum soap greases, 323
  - American civil jet fuels, 78, 79 (table)
  - American military jet fuels, 77–78, 77 (table)
  - American Petroleum Institute (API)
    - gravity, 14, 32, 98–99, 184, 253, 273
    - research projects on crude oil initiated by, 97
  - AN-F-32 specification, 77
  - “aniline-gravity” method, 84
  - aniline point
    - base oils, 263
    - rubber oils, 319
    - of white mineral oils, 252
  - anti-foam fuel additive, 149
  - anti-icing additive, aviation fuels with, 91, 94
  - antiknock rating (AKI)
    - automotive spark-ignition engine fuel, 4–6
    - aviation gasoline, 71
    - combustion properties, 5–6
    - Federal Trade Commission regulations with, 6
  - antioxidants
    - fuel additive, 90, 94, 150, 294
    - gasoline additive, 144–145
    - responses in RPVOT of, 304 (figure)
  - anti-wear agents, 294, 309
  - API gravity, 14, 32, 98–99, 184
    - lubricating oils, 273
    - for white mineral oils, 253
  - aromatic content
    - diesel fuels, 50
    - nonaviation gas-turbine fuel, 50
  - aromatics
    - calibrations for, 184
    - chromatographic methods in analyses of, 165, 166 (table)
  - arsenic, crude oils, 101
  - artificial carbon, 238
  - aseptic condition, 135
  - ash content
    - biodiesel fuel with, 62, 64
    - crude oil, 105
    - diesel fuels, 53
    - fuel oils, 198, 199 (table)
    - graphite, 244
    - manufactured carbon, 244
    - nonaviation gas-turbine fuel, 53

- petroleum coke, 238
- pitch, 243
- asphaltenes, crude oil, 105
- assay, 97–110, 108 (table), 135
- Association Française de Normalisation, 1
- ASTM C559, 239 (table), 244
- ASTM C560, 240 (table), 245
- ASTM C561, 239 (table), 244
- ASTM C562, 240 (table), 245
- ASTM C565, 240 (table), 245
- ASTM C611, 240 (table), 244–245
- ASTM C625, 240 (table), 245
- ASTM C651, 240 (table), 246
- ASTM C662, 241 (table), 245
- ASTM C695, 240 (table), 245
- ASTM C709, 241 (table), 244
- ASTM C714, 241 (table), 246
- ASTM C747
  - elasticity for manufactured carbon and graphite in, 245–246
  - fundamental frequencies for manufactured carbon and graphite in, 245–246
  - petroleum coke, pitch, and manufactured carbon and graphite tested with, 240 (table)
- ASTM C748, 239 (table), 245
- ASTM C749, 240 (table), 246
- ASTM C769, 240 (table), 246
- ASTM C781, 240 (table)
- ASTM C783, 240 (table), 246
- ASTM C808, 240 (table), 246–247
- ASTM C816, 241 (table), 247
- ASTM C838, 239 (table), 244
- ASTM C886, 245
- ASTM C1025, 240 (table), 247
- ASTM C1039
  - petroleum coke, pitch, and manufactured carbon and graphite tested with, 239 (table)
  - porosity for manufactured carbon and graphite in, 244
  - specific gravity for manufactured carbon and graphite in, 244
- ASTM C1179, 240 (table), 247
- ASTM correlation equation, 184
- ASTM D02, 33
- ASTM D5, 113
- ASTM D36, 109, 113
- ASTM D56, 55, 83, 94, 196, 207, 208, 282
  - flash point of diesel fuels tested with, 49
  - kerosine requirements in, 206 (table)
- ASTM D61, 241 (table), 242
- ASTM D71, 239 (table), 242
- ASTM D86, 7, 17, 34, 55, 73, 94, 145, 168, 197, 198, 207, 208, 218, 230, 256
  - distillation characteristics measured by, 46
  - distillation range for white mineral oils in, 253
  - fuel oil requirements with, 199 (table)
  - kerosine requirements in, 206 (table)
  - natural gas in, 234
- ASTM D87, 349
- ASTM D92, 256, 282, 319, 320, 350
  - flash and fire points with white mineral oils in, 253
- ASTM D92-16b, 265
- ASTM D93, 55, 67, 83, 94, 145, 196, 208, 256, 273, 282, 319, 320, 350
  - flash and fire points with white mineral oils in, 253
  - flash point of diesel fuels tested with, 49
  - fuel oil requirements with, 199 (table)
- ASTM D93-16a, 265
- ASTM D95, 197, 208, 217 (table), 221, 276, 282, 337
  - fuel oil requirements with, 199 (table)
  - water and sediment methods with, 223
- ASTM D96, 100, 113
- ASTM D97, 42, 55, 101, 113, 150, 153, 202, 208, 256, 272, 283, 319, 320
  - pour point testing with, 47
- ASTM D97-17b, 265
- ASTM D127, 349
- ASTM D128, 337, 338 (table)
- ASTM D129, 52, 55, 99, 113, 198, 208, 271, 283, 337, 356 (table)
- ASTM D130, 9, 10, 17, 32, 33, 34, 52, 55, 67, 85, 94
- ASTM D0130, 131
- ASTM D130, 146, 153, 200 (table), 201, 208, 283
- ASTM D156, 34, 94, 208, 256, 273, 283, 349
  - color of white mineral oils in, 252
  - kerosine requirements in, 206 (table)
- ASTM D187, 206 (table), 207, 208
- ASTM D189, 53, 55, 67, 104, 113
- ASTM D189-06, 265
- ASTM D216, 230, 234
- ASTM D217, 325, 326, 338
- ASTM D240, 51, 55, 94, 204, 208
- ASTM D287, 17, 98, 113, 256, 273, 283, 350
  - gravity and density with white mineral oils in, 253
- ASTM D322, 276, 283
- ASTM D323, 6, 17, 94, 103, 113
- ASTM D341, 101, 113, 283
- ASTM D381, 12, 17, 26, 31, 32, 34, 94, 217 (table)
  - cleanliness and contamination methods with, 223
- ASTM D396, 40, 55, 64, 67, 151, 192, 197, 201, 202, 208, 214, 215, 217 (table), 218, 219
- ASTM D445, 34, 55, 67, 94, 101, 113, 197, 208, 256, 269, 283, 320, 349
  - fuel oil requirements with, 199 (table)
  - kerosine requirements in, 206 (table)
  - viscosity with white mineral oils in, 255
- ASTM D445-17a, 265
- ASTM D447, 256
- ASTM D473, 100, 113, 197, 208, 217 (table), 221
  - fuel oil requirements with, 199 (table)
  - water and sediment methods with, 223
- ASTM D477, 253
- ASTM D482, 53, 55, 67, 113, 208, 356 (table)
  - fuel oil requirements with, 199 (table)
- ASTM D482-13, 265
- ASTM D483, 255, 256
- ASTM D524, 53, 67, 198, 209
  - fuel oil requirements with, 199 (table)
- ASTM D524-15, 265
- ASTM D525, 12, 17, 34, 145, 153, 214, 217 (table)
  - stability methods with, 222
- ASTM D565, 256
- ASTM D566, 329, 338
- ASTM D611, 94, 256, 318, 319, 320
  - aniline point of white mineral oils in, 252
- ASTM D611-12, 265
- ASTM D612, 350
- ASTM D613, 55, 67, 82, 148, 153
- ASTM D664, 67, 103, 104, 113, 209
  - fuel oil requirements with, 200 (table)
- ASTM D664-17a, 265
- ASTM D665, 9, 13, 17, 145, 153, 281, 283
- ASTM D721, 350
- ASTM D808, 283, 337, 356 (table)
- ASTM D873, 12, 17, 94, 215, 217 (table)
  - stability methods with, 222

- ASTM D874, 67, 276, 283, 356 (table)  
 ASTM D877, 252–253, 256  
 ASTM D892, 265, 274, 281, 283  
 ASTM D893, 276, 283  
 ASTM D909, 94  
 ASTM D910, 70–71, 72 (table), 74–75, 91, 94, 217 (table)  
 ASTM D925, 319, 320  
 ASTM D938, 349  
 ASTM D942, 331, 332, 338  
 ASTM D943, 280, 283  
 ASTM D972, 320, 328, 330, 338  
 ASTM D974, 40, 42, 43 (table), 45–55, 58–60, 62–65, 67, 94, 283  
 ASTM D975, 51, 52 (table), 53, 55, 64, 67, 94, 148, 151, 214, 215, 217 (table), 218, 219, 221  
 ASTM D976, 45, 55, 67  
 ASTM D1003, 274, 283  
 ASTM D1018, 356 (table)  
 ASTM D1025, 234  
 ASTM D1070, 233  
 ASTM D1072, 233  
 ASTM D1089, 234  
 ASTM D1091, 283, 356 (table)  
 ASTM D1092, 327, 338  
 ASTM D1094, 94, 217, 222, 223  
 ASTM D1142, 233  
 ASTM D1148, 319, 320  
 ASTM D1152, 21, 30, 34  
 ASTM D1157, 234  
 ASTM D1160, 67, 107, 113, 168, 197, 209, 256, 350  
   distillation range for white mineral oils in, 253  
 ASTM D1209, 34  
 ASTM D1218, 255, 319, 320  
   refractive index for white mineral oils in, 254  
 ASTM D1250, 98, 113, 202, 209  
 ASTM D1262, 337  
 ASTM D1263, 331, 338  
 ASTM D1264, 335, 338  
 ASTM D1265, 129, 233, 234  
 ASTM D1266, 10, 17, 34, 55, 67, 94, 198, 209, 356 (table)  
   kerosine requirements in, 206 (table)  
   natural gas in, 234  
 ASTM D1267, 233  
 ASTM D1296, 34  
 ASTM D1298, 17, 32, 34, 55, 84, 94, 98, 113, 202, 209, 255, 265, 273, 283, 318, 320, 347, 350  
   fuel oil requirements with, 200 (table)  
   gravity and density with white mineral oils in, 253  
   natural gas in, 234  
 ASTM D1317, 337, 356 (table)  
 ASTM D1318, 356 (table)  
 ASTM D1319, 10, 17, 55, 94  
   aromatic content measurement with, 50  
   EPA's designated test methods, 163 (table)  
   hydrocarbons in naphthas tested with, 160 (table)  
   olefins in naphthas and blended gasolines with testing based on, 164–165, 164 (table)  
 ASTM D1321, 349  
 ASTM D1322, 84, 94, 205, 209  
 ASTM D1353, 34  
 ASTM D1368, 356 (table)  
 ASTM D1401, 281, 283, 336  
 ASTM D1402, 337  
 ASTM D1403, 326, 338  
 ASTM D1404, 336, 338  
 ASTM D1405, 94  
 ASTM D1465, 350  
 ASTM D1478, 328, 338  
 ASTM D1500, 149, 265, 273, 283, 319, 320, 349  
 ASTM D1548, 356 (table)  
 ASTM D1550, 232, 234  
 ASTM D1552, 52, 55, 94, 99, 113, 198, 209, 271, 283, 356 (table)  
   petroleum coke, pitch, and manufactured carbon and graphite tested with, 241 (table)  
   sulfur in petroleum coke in, 238  
 ASTM D1613, 29, 34  
 ASTM D1655, 78, 81–83, 86, 94, 217, 217 (table), 218  
 ASTM D1657, 229, 233  
 ASTM D1660, 214  
 ASTM D1688, 27, 34  
 ASTM D1740, 84  
 ASTM D1741, 337  
 ASTM D1742, 338  
 ASTM D1743, 335, 338  
 ASTM D1747, 319, 320  
 ASTM D1748, 283  
 ASTM D1796, 67, 217 (table), 219, 221  
   water and sediment methods with, 223  
 ASTM D1826, 233  
 ASTM D1831, 327, 338  
 ASTM D1835, 122, 229  
 ASTM D1838, 233  
 ASTM D1840, 84, 94  
 ASTM D1945, 226  
   gas chromatography in analyses of gases with, 166–167, 166 (table)  
   natural gas and ethane in, 233  
 ASTM D1946, 166 (table), 167  
 ASTM D1988, 233  
 ASTM D2007, 316, 318, 320  
 ASTM D2008, 319, 320, 345, 350  
 ASTM D2068, 48, 55, 218, 223  
 ASTM D2069, 151, 214, 215  
 ASTM D2140, 316, 320  
 ASTM D2156, 205, 209  
 ASTM D2157, 209  
 ASTM D2158, 229, 233  
 ASTM D2161, 114, 350  
 ASTM D2163, 228, 230  
   gas chromatography in analyses of gases with, 166 (table), 167  
   liquefied petroleum gas in, 233  
   propylene concentrates in, 234  
 ASTM D2226, 318, 320  
 ASTM D2244, 273, 283  
 ASTM D2265, 329, 338  
 ASTM D2266, 334, 338  
 ASTM D2268, 161 (table)  
 ASTM D2269, 252, 255  
 ASTM D2270, 265, 283  
 ASTM D2272, 283, 304 (figure), 305  
 ASTM D2274, 55, 67, 203, 209, 213, 215  
   stability methods with, 222  
 ASTM D2276, 13, 17, 86, 94, 131, 217, 218, 219  
   cleanliness and contamination methods with, 223  
 ASTM D2318, 239 (table), 242  
 ASTM D2319, 241 (table), 242  
 ASTM D2320, 239 (table), 242  
 ASTM D2384, 234  
 ASTM D2386, 83, 95, 206 (table), 209  
 ASTM D2392, 95  
 ASTM D2415, 239 (table), 243  
 ASTM D2416, 239 (table), 243  
 ASTM D2420, 229, 233

- ASTM D2421, 233  
 ASTM D2423, 350  
 ASTM D2425, 50, 55  
 ASTM D2426, 166 (table), 167, 234  
 ASTM D2427, 161 (table), 234  
 ASTM D2500, 55, 67, 150, 153, 202, 209, 255, 265, 272, 283, 319, 320, 349  
     cloud point measured by, 46  
     cloud point with white mineral oils in, 252  
 ASTM D2501, 318, 320  
 ASTM D2503, 350  
 ASTM D2504, 166 (table), 167, 234  
 ASTM D2505, 166 (table), 167, 234  
 ASTM D2509, 333, 334, 338  
 ASTM D2534, 350  
 ASTM D2547, 356 (table)  
 ASTM D2569, 241 (table), 242  
 ASTM D2593, 166–167, 166 (table), 234  
 ASTM D2595, 330, 338  
 ASTM D2596, 333, 334, 338  
 ASTM D2597, 233  
 ASTM D2598, 228, 230, 233  
 ASTM D2599, 356 (table)  
 ASTM D2603, 283  
 ASTM D2622, 10, 17, 27, 33, 34, 52, 55, 64, 67, 85, 95, 99, 114, 201, 209, 271, 283, 356 (table)  
     fuel oil requirements with, 199 (table)  
 ASTM D2624, 86, 95, 131, 149, 153, 200 (table), 209  
 ASTM D2638, 238, 239 (table)  
 ASTM D2669, 349  
 ASTM D2670, 283  
 ASTM D2699, 5, 17, 35, 95, 234  
 ASTM D2700, 5, 17, 35, 95, 234  
 ASTM D2709, 13, 17, 35, 55, 67, 197, 209, 217 (table), 219, 221  
     cleanliness of diesel fuels measured with, 48  
     fuel oil requirements with, 199 (table)  
     water and sediment methods with, 223  
 ASTM D2710, 265  
 ASTM D2711, 283  
 ASTM D2712, 166–167, 166 (table), 234  
 ASTM D2713, 233  
 ASTM D2764, 239 (table), 242–243  
 ASTM D2782, 283  
 ASTM D2783, 283  
 ASTM D2784, 234, 356 (table)  
 ASTM D2785, 356 (table)  
 ASTM D2872, 109, 114  
 ASTM D2880, 40, 43, 52, 54, 55, 67, 151, 214, 215, 217 (table), 218, 219, 221  
 ASTM D2885, 5, 17, 188  
 ASTM D2887, 55, 95, 105, 114, 207, 209, 255, 265, 350  
     distillation characteristics measured by, 46  
     distillation range for white mineral oils in, 253  
     simdis analysis for petroleum types with, 172, 172 (figure)  
     simulated distillation test methods with, 168 (table)  
 ASTM D2892, 106, 107, 114, 168  
 ASTM D2893, 283  
 ASTM D2896, 276, 283  
 ASTM D2982, 276, 283  
 ASTM D2983, 283  
 ASTM D3104, 241 (table), 242  
 ASTM D3116, 356 (table)  
 ASTM D3117, 35, 67  
 ASTM D3120, 10, 17, 27, 35, 52, 67, 356 (table)  
 ASTM D3227, 10, 17, 85, 95, 209, 356 (table)  
     kerosine requirements in, 206 (table)  
 ASTM D3228, 104, 114, 209, 356 (table)  
 ASTM D3229, 356 (table)  
 ASTM D3230, 100, 114, 356 (table)  
 ASTM D3231, 10, 17, 30, 35, 356 (table)  
 ASTM D3232, 327, 328, 338  
 ASTM D3235, 350  
 ASTM D3236, 349  
 ASTM D3237, 10, 17, 35, 95, 356 (table)  
 ASTM D3238, 316, 320  
 ASTM D3240, 86, 95, 217, 218  
     cleanliness and contamination methods with, 223  
 ASTM D3241, 80, 85, 95, 131, 214, 217 (table)  
     stability methods with, 222  
 ASTM D3242, 67, 85, 95  
 ASTM D3244, 376  
 ASTM D3246, 233, 234, 356 (table)  
 ASTM D3279, 105, 114  
 ASTM D3336, 329, 332, 333, 338  
 ASTM D3337, 329, 333, 338  
 ASTM D3338, 84, 95  
 ASTM D3340, 337, 356 (table)  
 ASTM D3341, 9, 17, 95, 356 (table)  
 ASTM D3343, 95  
 ASTM D3344, 350  
 ASTM D3348, 18, 356 (table)  
 ASTM D3427, 281, 283  
 ASTM D3428, 337  
 ASTM D3431, 356 (table)  
 ASTM D3461, 241 (table), 242  
 ASTM D3524, 276, 283  
 ASTM D3525, 276, 283  
 ASTM D3527, 329, 339  
 ASTM D3588, 233  
 ASTM D3605, 131, 356 (table)  
 ASTM D3606, 11, 18, 160 (table), 163 (table)  
 ASTM D3699, 151, 192, 205, 208, 214, 217 (table), 218, 219, 221  
 ASTM D3700, 110, 114, 233  
 ASTM D3701, 84, 95, 356 (table)  
 ASTM D3703, 12, 18, 95  
 ASTM D3704, 334, 339  
 ASTM D3710, 168 (table), 172 (figure)  
 ASTM D3828, 55, 67, 83, 95, 196, 207, 209, 273, 283  
     flash point of diesel fuels tested with, 49  
 ASTM D3831, 18, 35, 356 (table)  
 ASTM D3941, 49, 55  
 ASTM D3944, 349  
 ASTM D3948, 95, 131, 217 (table), 218, 223  
 ASTM D4006, 100, 114  
 ASTM D4007, 100, 114  
 ASTM D4045, 18, 35, 356 (table)  
 ASTM D4047, 356 (table)  
 ASTM D4048, 335, 339  
 ASTM D4049, 336, 339  
 ASTM D4052, 18, 35, 55, 83, 95, 202, 209, 255, 265, 283, 318, 320  
     gravity and density with white mineral oils in, 253  
     natural gas in, 234  
 ASTM D4053, 11, 18  
 ASTM D4054, 95  
 ASTM D4055, 283  
 ASTM D4057, 18, 35, 67, 95, 110, 114, 119, 122, 124, 212, 222  
     manual sampling of petroleum in, 129–130  
     sampling methods with, 224  
 ASTM D4072, 239 (table), 243  
 ASTM D4084, 233  
 ASTM D4170, 334, 339  
 ASTM D4171, 94  
 ASTM D4172, 283

- ASTM D4175, 18, 238, 241 (table), 243
- ASTM D4176, 31, 33, 35, 55, 95, 217, 217 (table), 219  
cleanliness and contamination methods with, 223
- ASTM D4177, 18, 35, 67, 110, 114, 222  
automatic sampling of petroleum in, 130–131  
sampling methods with, 224
- ASTM D4289, 283, 336, 339
- ASTM D4290, 329, 331
- ASTM D4291, 276, 283
- ASTM D4292, 238, 239 (table)
- ASTM D4293, 283
- ASTM D4294, 18, 52, 55, 67, 95, 99, 114, 201, 209, 271, 283,  
356 (table), 358 (table)
- ASTM D4296, 240 (table), 243
- ASTM D4305, 95
- ASTM D4306, 18, 35, 95, 222  
aviation fuel sample containers in, 131–132  
sampling methods with, 224
- ASTM D4308, 95, 131, 149, 204, 209  
fuel oil requirements with, 200 (table)
- ASTM D4310, 280, 283
- ASTM D4312, 243
- ASTM D4377, 100, 114, 221
- ASTM D4418, 54, 55, 215, 222, 224
- ASTM D4419, 349
- ASTM D4421, 238, 241 (table)
- ASTM D4422, 238, 239 (table)
- ASTM D4423, 234
- ASTM D4424, 166 (table), 234
- ASTM D4425, 339
- ASTM D4485, 283
- ASTM D4529, 84, 95
- ASTM D4530, 67, 104, 114
- ASTM D4539, 55, 153
- ASTM D4616, 240 (table), 243
- ASTM D4625, 55, 67, 145, 153, 203, 209, 213, 214, 215, 217 (table)  
stability methods with, 222  
storage stability tested with, 49
- ASTM D4628, 356 (table)
- ASTM D4629, 104, 114, 265, 271, 283, 356 (table)
- ASTM D4636, 284
- ASTM D4683, 269, 284
- ASTM D4684, 269, 284
- ASTM D4693, 328, 339
- ASTM D4715, 239 (table), 243
- ASTM D4735, 166 (table), 175 (table)
- ASTM D4737, 45, 55, 60, 64, 67
- ASTM D4739, 284
- ASTM D4740, 112, 114, 204, 209, 221  
cleanliness and contamination methods with, 223  
compatibility methods with, 223
- ASTM D4741, 269, 284
- ASTM D4746, 240 (table)
- ASTM D4756, 242
- ASTM D4805, 356 (table)
- ASTM D4806, 16, 17, 21, 22, 26, 28, 34
- ASTM D4807, 100, 105, 114
- ASTM D4809, 84, 95, 204, 209
- ASTM D4810, 233
- ASTM D4814, 3–19, 17, 22, 28, 34, 76, 94, 119, 123, 146, 147, 217  
(table), 219  
antiknock rating test measurements standardized in, 5  
copper specification limit in, 9  
distillation, 7  
driveability index, 7  
ferrous corrosion specification limit, 9  
fuel volatility measurement in, 6–7  
gum content, 12  
SIP limits in, 15  
sulfur as specified in, 10  
vapor lock protection requirements, 8  
volatility and vehicle performance, 8–9
- ASTM D4815, 18, 35, 164  
CARB designated test methods for motor gasoline fuels  
using, 164 (table)  
oxygenates in naphthas and blended gasolines tested with,  
162 (table)
- ASTM D4840, 111, 114, 131 (figure), 132, 134
- ASTM D4860, 48, 55, 219, 223
- ASTM D4865, 67, 95
- ASTM D4868, 51, 55, 204, 209
- ASTM D4870, 114, 221, 223
- ASTM D4888, 233
- ASTM D4892, 239 (table), 242
- ASTM D4893, 241 (table), 243
- ASTM D4927, 271, 284, 356 (table)
- ASTM D4928, 100, 114, 221
- ASTM D4929, 104, 114, 356 (table)
- ASTM D4930, 238, 239 (table)
- ASTM D4931, 240 (table)
- ASTM D4951, 67, 270, 284, 356 (table)
- ASTM D4952, 10, 18, 95, 209, 255, 356 (table)
- ASTM D4953, 18, 28, 30, 32, 35, 95  
fuel volatility measurement in, 6–7  
natural gas in, 234
- ASTM D4984, 226, 233
- ASTM D5001, 86, 95, 131
- ASTM D5002, 114
- ASTM D5003, 238, 239 (table)
- ASTM D5004, 238, 239 (table)
- ASTM D5006, 93, 95
- ASTM D5018, 241 (table), 243
- ASTM D5056, 238, 240 (table), 356 (table)
- ASTM D5059, 9, 10, 18, 30, 35, 89, 95, 356 (table)
- ASTM D5060, 166 (table)
- ASTM D5134, 109, 114, 158, 159 (table)
- ASTM D5135, 166 (table)
- ASTM D5182, 284
- ASTM D5184, 356 (table)
- ASTM D5185, 114, 270, 276, 284, 356 (table)
- ASTM D5186, 50, 55, 179
- ASTM D5187, 238, 239 (table), 242
- ASTM D5188, 7, 18
- ASTM D5190, 95
- ASTM D5191, 28, 30, 35, 73, 95, 103, 114  
fuel volatility measurement in, 7  
natural gas in, 234
- ASTM D5234, 166 (table), 167, 234
- ASTM D5236, 107, 114
- ASTM D5273, 166 (table), 167, 234
- ASTM D5274, 234
- ASTM D5291, 114, 271, 284
- ASTM D5292, 50, 55
- ASTM D5293, 284
- ASTM D5303, 166 (table), 167, 234
- ASTM D5304, 49, 56, 209, 215, 222
- ASTM D5305, 105, 230, 233
- ASTM D5306, 281, 284
- ASTM D5307, 105, 106, 114
- ASTM D5384, 356 (table)
- ASTM D5386, 35
- ASTM D5441, 35, 162 (table)
- ASTM D5442, 174 (table), 350
- ASTM D5443, 159, 160 (table)
- ASTM D5452, 67, 95, 131, 217, 219, 223

- ASTM D5453, 10, 18, 27, 30, 33, 35, 52, 56, 64, 67, 85, 95, 201, 209, 356 (table)  
 fuel oil requirements with, 199 (table)  
 natural gas in, 234  
 sulfur content of ethanol determined by, 29
- ASTM D5454, 233
- ASTM D5481, 269, 284
- ASTM D5482, 7, 18, 35, 234
- ASTM D5483, 325
- ASTM D5500, 16, 18, 144, 153
- ASTM D5501, 26, 35, 162 (table)
- ASTM D5502, 239 (table), 243
- ASTM D5504, 165, 166 (table), 167, 175 (table), 233
- ASTM D5505, 167
- ASTM D5580, 11, 18, 28, 35  
 CARB designated test methods for motor gasoline fuels using, 164 (table)  
 hydrocarbons in naphthas tested with, 160 (table)
- ASTM D5598, 16, 18, 144, 153
- ASTM D5599, 18, 162 (table), 163 (table), 164
- ASTM D5600, 238, 240 (table), 356 (table)
- ASTM D5622, 356 (table)
- ASTM D5623, 175 (table)
- ASTM D5662, 284
- ASTM D5705, 105, 114 (table)
- ASTM D5706, 334, 339 (table)
- ASTM D5708, 102, 114, 356 (table), 358 (table)
- ASTM D5709, 241 (table), 242
- ASTM D5713, 166 (table)
- ASTM D5762, 104, 114, 284, 356 (table)
- ASTM D5769, 11, 18, 160 (table), 163 (table)
- ASTM D5771, 46, 56, 67
- ASTM D5772, 46, 56, 67
- ASTM D5773, 46, 56, 67
- ASTM D5797, 17, 21, 30, 34
- ASTM D5798, 17, 21, 22, 28, 34
- ASTM D5799, 234
- ASTM D5800, 274, 284
- ASTM D5842, 18, 35, 114, 132
- ASTM D5845, 18, 35
- ASTM D5853, 101, 114
- ASTM D5854, 18, 35, 110, 114, 122, 132–133, 133 (table)
- ASTM D5863, 102, 114, 356 (table), 358 (table)
- ASTM D5901, 95
- ASTM D5917, 166 (table)
- ASTM D5949, 47, 56, 202, 209, 272, 284
- ASTM D5950, 47, 56, 202, 209, 284, 319, 320
- ASTM D5969, 335
- ASTM D5972, 83, 95, 209
- ASTM D5983, 16, 17, 21, 31, 34
- ASTM D5985, 47, 56, 202, 209
- ASTM D5986, 11, 18, 160 (table), 164
- ASTM D6006, 281, 284
- ASTM D6045, 273, 284
- ASTM D6046, 281, 284
- ASTM D6078, 50, 56, 153
- ASTM D6079, 50, 56, 153, 199 (table), 209
- ASTM D6082, 284
- ASTM D6120, 240 (table), 243
- ASTM D6122, 187
- ASTM D6159, 166 (table), 234
- ASTM D6160, 168, 168 (table)
- ASTM D6201, 16, 18, 153
- ASTM D6217, 48, 56, 67, 217, 217 (table), 219, 223
- ASTM D6227, 75, 94, 217 (table)
- ASTM D6228, 166 (table), 233
- ASTM D6258, 151, 153
- ASTM D6293, 10, 18
- ASTM D6296, 11, 18, 160 (table), 164, 164 (table)
- ASTM D6299, 376
- ASTM D6300, 67, 376
- ASTM D6304, 86, 95, 221, 223, 276, 284
- ASTM D6334, 18, 356 (table)
- ASTM D6352, 168 (table), 172 (figure)
- ASTM D6353, 243–244
- ASTM D6354, 241 (table), 243–244
- ASTM D6371, 153
- ASTM D6374, 238, 241 (table)
- ASTM D6375, 274, 284
- ASTM D6376, 238, 240 (table), 241 (table)
- ASTM D6377, 103, 114
- ASTM D6378, 18, 35, 95, 234
- ASTM D6379, 95
- ASTM D6407, 174 (table)
- ASTM D6417, 174 (table), 274, 284
- ASTM D6421, 16, 18, 153
- ASTM D6423, 29, 35
- ASTM D6426, 48, 56, 218, 223
- ASTM D6428, 56
- ASTM D6443, 356 (table)
- ASTM D6444, 356 (table)
- ASTM D6445, 18, 356 (table)
- ASTM D6446, 95
- ASTM D6447, 12, 18
- ASTM D6448, 193, 208, 217 (table)
- ASTM D6450, 35, 67, 273, 284
- ASTM D6468, 214, 217 (table), 222
- ASTM D6469, 13, 18, 67, 87, 95, 197, 205, 209, 216, 221  
 cleanliness and contamination methods with, 223
- ASTM D6470, 100, 114, 356 (table)
- ASTM D6481, 356 (table)
- ASTM D6521, 109, 114
- ASTM D6526, 166 (table)
- ASTM D6547, 284
- ASTM D6550, 11, 18, 28, 35, 179  
 CARB designated test methods for motor gasoline fuels using, 164 (table)  
 hydrocarbons in naphthas tested with, 161 (table)  
 olefins in naphthas and blended gasolines with testing based on, 164–165, 164 (table)
- ASTM D6558, 240 (table), 244
- ASTM D6559, 240 (table), 244
- ASTM D6560, 105, 114, 221, 223
- ASTM D6563, 166 (table)
- ASTM D6584, 35, 67
- ASTM D6593, 284
- ASTM D6595, 356 (table)
- ASTM D6615, 78, 94
- ASTM D6667, 233, 356 (table)
- ASTM D6708, 376
- ASTM D6728, 216, 356 (table)
- ASTM D6729, 10, 18, 158, 159 (table), 234
- ASTM D6730, 10, 18, 158, 159  
 hydrocarbons in naphthas tested with, 159 (table)  
 natural gas in, 234
- ASTM D6732, 356 (table)
- ASTM D6733, 11, 18, 158, 159 (table), 234
- ASTM D6744, 241 (table), 244
- ASTM D6745, 241 (table), 244
- ASTM D6748, 215, 222
- ASTM D6749, 202, 209
- ASTM D6751, 40, 56–60, 62–64, 67, 93, 94, 208, 214, 217 (table), 219  
 biodiesel quality issues in, 60

- ASTM D6756, 151, 153  
 ASTM D6791, 239 (table), 242  
 ASTM D6792, 376  
 ASTM D6811, 214, 222  
 ASTM D6822, 98, 114  
 ASTM D6824, 218, 223  
 ASTM D6839, 159  
     hydrocarbons in naphthas tested with, 160 (table)  
     natural gas in, 234  
     olefins in naphthas and blended gasolines with testing based on, 164, 164 (table)  
     oxygenates in naphthas and blended gasolines tested with, 162 (table)  
 ASTM D6849, 233  
 ASTM D6890, 35, 67, 148  
 ASTM D6891, 284  
 ASTM D6892, 202, 209  
 ASTM D6897, 233  
 ASTM D6898, 50  
 ASTM D6920, 10, 18, 35, 356 (table)  
 ASTM D6968, 166 (table)  
 ASTM D6969, 241 (table), 242  
 ASTM D6970, 241 (table), 242  
 ASTM D6974, 216, 223  
 ASTM D6985, 219  
 ASTM D7011, 166 (table), 175 (table)  
 ASTM D7039, 10, 18, 27, 35, 52, 67, 201, 209, 356 (table)  
     sulfur content of ethanol determined by, 29  
 ASTM D7040, 356 (table)  
 ASTM D7041, 356 (table)  
 ASTM D7042, 95, 269, 284  
 ASTM D7057, 166 (table)  
 ASTM D7059, 114, 162 (table)  
 ASTM D7060, 221, 223  
 ASTM D7061, 221, 223  
 ASTM D7094, 196, 207, 209, 273, 284  
 ASTM D7095, 131  
 ASTM D7096, 18, 168 (table), 172 (figure)  
 ASTM D7111, 356 (table)  
 ASTM D7112, 221, 223  
 ASTM D7153, 83, 95  
 ASTM D7154, 95  
 ASTM D7157, 112, 114, 221, 223  
 ASTM D7165, 166 (table)  
 ASTM D7169, 105, 107, 114, 168 (table), 172 (figure)  
 ASTM D7170, 148, 153  
 ASTM D7171, 356 (table)  
 ASTM D7175, 110, 114  
 ASTM D7212, 356 (table)  
 ASTM D7213, 168 (table), 172 (figure)  
 ASTM D7214, 272, 284  
 ASTM D7215, 174 (table)  
 ASTM D7216, 284  
 ASTM D7219, 241 (table), 247  
 ASTM D7220, 19, 35, 52, 201, 209, 356 (table)  
 ASTM D7223, 94  
 ASTM D7224, 218, 223  
 ASTM D7260, 102, 114, 356 (table), 358 (table)  
 ASTM D7261, 218, 223  
 ASTM D7266, 166 (table)  
 ASTM D7279, 269, 284  
 ASTM D7280, 240 (table), 242  
 ASTM D7301, 241 (table), 247  
 ASTM D7303, 356 (table)  
 ASTM D7315, 274, 284  
 ASTM D7318, 35, 356 (table)  
 ASTM D7319, 27, 28, 29, 35, 356 (table)  
 ASTM D7320, 284  
 ASTM D7321, 217 (table), 219, 221, 223  
 ASTM D7328, 28, 29, 31, 35, 356 (table)  
 ASTM D7343, 114, 356 (table), 358 (table)  
 ASTM D7344, 7, 19, 67  
 ASTM D7345, 7, 67, 95  
 ASTM D7346, 101, 114, 202, 209  
 ASTM D7347, 35, 161 (table), 164, 164 (table)  
 ASTM D7360, 166 (table)  
 ASTM D7371, 56, 200 (table), 204, 209  
 ASTM D7372, 376  
 ASTM D7397, 67  
 ASTM D7398, 168 (table), 172 (figure)  
 ASTM D7423, 166 (table)  
 ASTM D7451, 218, 222, 223  
 ASTM D7454, 238, 239 (table)  
 ASTM D7455, 358 (table)  
 ASTM D7462, 222  
 ASTM D7463, 216, 223  
 ASTM D7464, 124, 212, 216, 222  
     microbial contamination in fuels in, 133–134, 133 (figure)  
     sampling methods with, 224  
 ASTM D7467, 56, 64, 67, 214  
 ASTM D7482, 102, 114, 134  
 ASTM D7493, 166 (table)  
 ASTM D7500, 168 (table), 172 (figure)  
 ASTM D7501, 67, 217 (table), 219, 223  
 ASTM D7504, 166 (table)  
 ASTM D7524, 96  
 ASTM D7525, 153, 213, 222  
 ASTM D7528, 284  
 ASTM D7542, 240 (table)  
 ASTM D7544, 208  
 ASTM D7545, 214, 217 (table), 222  
 ASTM D7547, 94  
 ASTM D7550, 166 (table)  
 ASTM D7566, 82, 86, 94  
 ASTM D7576, 28, 164 (table)  
 ASTM D7589, 284  
 ASTM D7618, 21, 33, 34  
 ASTM D7619, 217 (table), 219, 223  
 ASTM D7621, 105, 114  
 ASTM D7622, 102, 114  
 ASTM D7623, 102, 114  
 ASTM D7652, 166 (table)  
 ASTM D7667, 9, 19, 35, 146, 153, 234  
 ASTM D7668, 67, 148, 153  
 ASTM D7671, 9, 19, 35, 234  
 ASTM D7687, 216, 223  
 ASTM D7688, 199 (table), 209  
 ASTM D7689, 46, 56, 67  
 ASTM D7691, 102, 115  
 ASTM D7717, 132  
 ASTM D7718, 122, 134–135  
 ASTM D7739, 131  
 ASTM D7740, 102, 115, 358 (table)  
 ASTM D7753, 160 (table)  
 ASTM D7754, 162 (table), 164 (table)  
 ASTM D7756, 166 (table), 229, 233  
 ASTM D7757, 19, 35  
 ASTM D7775, 240 (table), 247  
 ASTM D7777, 99, 115  
 ASTM D7779, 239 (table), 247  
 ASTM D7794, 17, 21, 22, 34  
 ASTM D7795, 29, 35  
 ASTM D7796, 33, 35, 162 (table)  
 ASTM D7797, 94, 96

- ASTM D7798, 168 (table), 172, 172 (figure)  
 ASTM D7807, 168 (table), 172 (figure), 174 (table),  
 175 (table)  
 ASTM D7827, 223  
 ASTM D7828, 166 (table), 233  
 ASTM D7829, 100, 115  
 ASTM D7833, 165, 166 (table)  
 ASTM D7845, 168, 168 (table)  
 ASTM D7846, 241 (table), 247–248  
 ASTM D7861, 56, 204, 209  
 ASTM D7862, 3, 17, 21, 32, 34  
 ASTM D7871, 166 (table)  
 ASTM D7872, 93, 96  
 ASTM D7875, 32, 35, 162 (table)  
 ASTM D7876, 103, 115, 358 (table)  
 ASTM D7892, 166 (table)  
 ASTM D7900, 115  
 ASTM D7920, 35, 162 (table)  
 ASTM D7922, 168, 168 (table)  
 ASTM D7923, 27, 32, 33, 35  
   water content of ethanol in, 29  
   water content of methanol determined by, 31  
 ASTM D7945, 96  
 ASTM D7959, 96  
 ASTM D7972, 239 (table), 246  
 ASTM D7975, 103, 115  
 ASTM D7978, 216, 223  
 ASTM D7994, 233  
 ASTM D7996, 223  
 ASTM D8003, 174 (table)  
 ASTM D8009, 110, 115 (table), 135  
 ASTM D8011, 230  
 ASTM D8029, 282, 284  
 ASTM D8045, 104, 115  
 ASTM D8049, 219, 223  
 ASTM D8056, 358 (table)  
 ASTM D8070, 216, 223  
 ASTM D8071, 160 (table), 162 (table), 164, 164 (table)  
 ASTM D8076, 21, 22, 34  
 ASTM D8091, 240 (table), 248  
 ASTM D8097, 238, 239 (table)  
 ASTM D8098, 166 (table), 168  
 ASTM D8110, 356 (table)  
 ASTM D8149, 104, 115 (table)  
 ASTM D8150, 104, 115 (table)  
 ASTM D8166, 219, 223  
 ASTM D79001, 174 (table)  
 ASTM E29, 19  
 ASTM E168, 272, 284  
 ASTM E203, 27, 32, 33, 35  
   water content of ethanol in, 29  
   water content of methanol determined by, 31  
 ASTM E300, 35  
 ASTM E0300, 123, 128–129  
 ASTM E456, 376  
 ASTM E691, 376  
 ASTM E1064, 27, 32, 33, 35  
   water content of ethanol in, 29  
 ASTM E1252, 271, 284  
 ASTM E2412, 272, 276, 284  
 ASTM E3050, 21, 22, 34  
 ASTM EN1575, 209  
 ASTM International, accelerating change in, 1  
 ASTM MONO12, 17  
 atmospheric residuum, temperature ranges for, 106  
 atomic absorption spectroscopy (AAS), 102, 360, 360 (figure)  
 atomic emission detector (AED), 155, 176 (table), 177  
 atomic emission spectroscopy (AES), 360  
 automatic sampler, 135  
 automatic sampling  
   containers, 130  
   control systems, 130  
   crude oils, 130  
   performance monitoring, 130  
   petroleum and petroleum products, 130–131  
   proportionality, 130  
   sample system security, 130  
 automatic sampling system, 135  
 automatic transmission fluids, 279–280, 280 (table)  
 automotive engine oils  
   additives, 289, 293–294  
   antioxidant additives, 294  
   anti-wear agents, 294, 309  
   bench test development in emulation of turbocharger  
     deposits, 308  
   bench test methods, 289–290  
   city driving effecting, 289  
   defoaming additives, 294  
   detergency, 311–312  
   detergent, 294  
   dispersants, 294  
   early application and experience with, 287–288  
   early studies, 288  
   engine standards needed for, 287–288  
   engine tests, 289  
   evolution of, 287–288  
   examination of used oil, 276  
   foaming tendency, 311, 311 (figure)  
   freeway driving effecting service of, 288  
   functions, 290–291  
   high-temperature, high-load driving conditions, 288–289  
   hydrodynamic lubrication, 308  
   ILSAC required test methods, 288  
   oil additives, 289  
   oxidation and deposit formation, 303–308, 303 (figure),  
     304 (figure), 305 (figure), 306 (figure), 307 (figure)  
   oxidation vulnerability, 291–293, 291 (figure), 292 (figure),  
     293 (figure)  
   properties, 274–275  
   quality levels, 288  
   service types comparison, 291–293, 291 (figure), 292 (figure),  
     293 (figure)  
   service types effecting, 288–289  
   shear rate's effects on, 294–303  
   short-trip driving effecting, 289  
   specifications and procedures, 275–276  
   temperature's effects on, 294–303  
   TFOUT oxidation test on, 306, 306 (figure), 307 (figure)  
   turbocharger oxidation simulation tests on, 307–308, 307 (figure)  
   viscosity, 294–303, 295 (figure), 296 (figure), 298 (figure),  
     299 (figure), 300 (figure), 302 (figure)  
   viscosity modifiers, 293–294  
   volatility, 311  
   wear, 308–311, 309 (figure)  
 automotive gasoline, use in aircraft, 75–76  
 automotive spark-ignition engine fuel  
   additives regulations, 14–15  
   antiknock rating, 4–6  
   ASTM specifications applicable for, 17–19  
   common terms for, 3  
   composition properties, 9–11  
   contamination, 12–13  
   copper corrosion, 9  
   corrosion properties, 9

- definitions for, 3–4
  - density, 13–14
  - distillation, 7
  - driveability index, 7
  - elastomers compatibility, 13
  - ferrous corrosion, 9
  - fuel additives, 11, 12 (table)
  - fuel blending components, 14–15
  - gasoline-oxygenate blends, 16–17
  - gum content, 11–12
  - hydrocarbon composition, 10–11
  - importance of specifications for, 4–5
  - lead content, 9–10
  - manganese content, 10
  - oxygenated fuel programs, 15–16
  - oxygenates, 11
  - performance, 8–9
  - peroxides, 12
  - phosphorus content, 10
  - plastics compatibility, 13
  - regulations driving changes in, 4
  - relative density, 13–14
  - sampling procedures, 14
  - silver corrosion, 9
  - spectroscopic methods for, 183–190, 184 (figure)
  - storage stability, 11–12
  - sulfur content, 10
  - sulfur regulations, 15
  - U.S. legal requirements for, 14–16
  - vapor-liquid ratio, 7–8
  - vapor pressure, 6–7
  - volatility, 6–9
  - volatility regulations, 15
  - water tolerance, 13
  - workmanship, 12–13
  - average sample, 136
  - Aviation Engine Octane Rating Group, 74
  - aviation fuels
    - additives, 87–94, 89 (table)
    - American civil jet fuels, 78, 79 (table)
    - American military jet fuels, 77–78, 77 (table)
    - anti-icing additive, 91, 94
    - antioxidants additive, 90, 94
    - ASTM/IP test methods, 94–96
    - ASTM specifications, 94
    - automotive gasoline, 75–76
    - aviation turbine fuels, 76
    - biocides, 92, 94
    - British military fuels, 76–77, 77 (table)
    - bulk properties, 82–84
    - color dyes additive, 89–90, 94
    - combustion quality, 84
    - compatibility with system materials, 85
    - composition, 81–87
    - conductivity improver additive, 91–92
    - contaminants, 86–87
    - corrosion, 85
    - corrosion inhibitors additive, 90–91
    - density, 73, 84
    - DERD 2482, 76–77
    - electrical conductivity, 85–86
    - emissions, 84
    - fuel system icing inhibitor, 91, 94
    - gasoline, 69–81 (*See also* aviation gasoline)
    - GOST specifications, 70–71, 71 (table), 80–81, 80 (table)
    - gum inhibitors additive, 90
    - high temperature stability, 85
    - historical development of, 69
    - ignition control additive, 93
    - inspection data on, 87, 98 (figure)
    - international standard specifications, 80–81, 81 (table)
    - jet fuels, 76
    - leak detector additive, 92, 94
    - low temperature properties, 83–84
    - lubricity, 82, 86
    - lubricity improvers additive, 90–91
    - manufacture, 81
    - metal deactivator additive, 90, 94
    - for nonconventional aircraft, 82
    - nonconventional sources of, 82
    - other national specifications, 80, 80 (table)
    - pipeline drag reducer additive, 92–93
    - Russian jet fuels, 80, 80 (table)
    - sampling, 87
    - separating properties, 87
    - special tests and miscellaneous properties, 87
    - specification requirements, 82
    - specific heat, 84
    - static dissipater additive, 91–92, 94
    - storage stability, 85
    - TEL, 70–71, 74, 75, 89, 93
    - thermal stability improver, 92, 94
    - trace properties, 84–87
    - viscosity, 82
    - volatility, 83
    - water content of, 86
    - water retention, 87
  - aviation gasoline
    - antiknock properties, 71
    - characteristics and requirements, 71–81
    - component of high-octane, 70
    - composition, 69–70
    - content, 70
    - density, 73
    - freezing point, 73
    - fuel grades, 70–71, 70 (table), 71 (table), 72 (table)
    - manufacture, 69–70
    - quality control parameters, 69
    - specifications, 70–71, 70 (table), 71 (table), 72 (table)
    - specific energy, 73
    - storage stability, 73–74
    - sulfur content, 74
    - unleaded, 74–75
    - vapor lock in fuel lines with, 73
    - vapor pressure for, 73
    - volatility, 71–73
    - water reaction, 74
  - aviation turbine fuels, 76, 211
- B**
- bacterial endotoxin, with white mineral oils, 252
  - ball bearings, 328, 332
  - base oils
    - aniline point, 263
    - ASTM/IP lubricant test methods, 265
    - ASTM tests, 258, 258 (table)
    - biological properties, 264
    - characterization methods, 258–264
    - composition, 257
    - evaporative loss/volatility characteristics, 262
    - hydrocarbon-type compositional analysis, 258–259
    - international standards, 264
    - miscellaneous properties, 264
    - nitrogen compounds in, 261

- olefins, 261–262
  - oxidation, 260–261, 260 (figure)
  - pour point and rheology, 262–263
  - refining, 257–258
  - rubber compatibility, 263–264
  - solvency, 263
  - spectrometric identification, 259–260
  - sulfur compounds, 261
  - batch, 136
  - bearings
    - ball, 328, 332
    - hardness and finish, 308
    - small, lubricating greases in, 333
    - tapered roller, 328
    - wheel, 331, 331 (figure), 333
  - bench test
    - development in emulation of turbocharger deposits, 308
    - lubricating oils in laboratory, 268
    - methods, 289–290
  - benzene, 11, 184
  - bias, relative, 374–375
  - biocides
    - aviation fuels with, 92, 94
    - fuel additives, 151
  - biodiesel content
    - fuel oils, 203–204
    - heating fuels, 192
  - biodiesel fuel, 54–55
    - acid number, 64, 66
    - ash content, 62, 64
    - ASTM specifications, 67
    - ASTM task force history for, 58
    - blends, 57
    - blend specifications, 62–64
    - carbon residue, 62, 64
    - cetane number, 62, 64
    - characteristics, 64–66
    - characterization of, 58–59, 59 (table)
    - cold soak filterability parameter, 62
    - composition of, 57–58
    - defined, 58–59
    - density, 66
    - described, 58–59
    - detailed requirements, 61 (table)
    - distillation curve for, 60
    - fatty acid profile used in, 62 (table)
    - federal and state-based public policy, 57
    - flash point, 62
    - free glycerin method, 66
    - funding standards development for, 59
    - oxidation stability, 66
    - petrodiesel distinguished from, 60
    - phosphorous content, 62, 66
    - potassium, 66
    - quality determination for, 59
    - reaction, 59 (table)
    - reduced pressure distillation, 66
    - sodium, 66
    - sodium and potassium combined in, 62
    - stability, 62, 66
    - standards, 60–62
    - standards development history for, 59–60
    - sulfated ash, 64
    - sulfur content, 64
    - testing methods for measurement of, 62
    - total glycerin method, 66
    - vacuum distillation, 62
  - biofuels
    - gas chromatography test methods for, 168, 168 (table)
    - state mandates, 26
    - test methods needed for, 211
  - blended gasoline
    - ASTM test methods based on chromatography for, 161–164, 163 (table), 164 (table)
    - olefins in, ASTM test methods for, 164–165, 164 (table)
    - oxygenates in, ASTM test methods for, 162 (table)
  - blend planning, spectroscopic methods with proactive use of, 189–190
  - blue-flame high-pressure gun burners, 194
  - boiling point, ethane, 226
  - boiling point distribution
    - crude oil, 105–106
    - petroleum waxes, 345
  - bomb oxidation test, 331–332, 332 (figure)
  - boring sample, 136
  - bottom sample, 136
  - bottom water sample, 136
  - Brayton cycle, 37
  - British military fuels, 76–77, 77 (table)
  - bubble point, 136
  - burner fuels, 191–209, 199–200 (table), 206 (table)
    - ASTM specifications, 208
    - lubricating oil used as, 193
  - burning equipment
    - air-atomizing burners, 195
    - blue-flame high-pressure gun burners, 194
    - description of, 194
    - domestic heating oils, 194
    - kerosine, 194–195
    - low-pressure atomizing burner, 194
    - residual oil, 195
    - rotary-type burners, 195
    - wick-fed blue-flame-type burner, 195
    - wick-fed yellow-flame-type burner, 194
  - butadiene ( $C_4H_6$ )
    - ASTM specifications, 234
    - petrochemical applications, 232
    - production of, 232
  - butanes, 225, 226
    - quality criteria, 227
  - butanol
    - acidity, 33
    - appearance, 33
    - color, 33–34
    - copper strip corrosion, 33
    - density, 34
    - existent gum content, 34
    - inorganic chloride content, 33
    - inorganic sulfate content, 33
    - solvent-washed gum content, 33
    - test methods for, 32
    - water content, 32–33
    - workmanship, 33
  - butylene ( $C_4H_8$ )
    - ASTM specifications, 234
    - petrochemical applications, 231–232
    - quality criterion for, 232
- C**
- cadmium content, crude oils, 102
  - calcining process, 236
  - calcium content
    - diesel fuels, 54
    - nonaviation gas-turbine fuel, 54

- calcium soap greases, 323
- calcium sulfonate greases, 323–324
- calibration, 169 (figure), 170 (figure), 184
  - direct match technique for, 186
  - general, 186
  - site-specific, 186
  - spectroscopic methods, 186
  - stream-specific, 186
- California Air Resource Board (CARB)
  - ASTM test methods for, 164 (table)
  - correlation equation, 184
- Canadian Crude Quality Technical Association, 112
- carbon residue
  - biodiesel fuel with, 62, 64
  - crude oil, 104
  - diesel fuels, 53
  - fuel oils, 198
  - nonaviation gas-turbine fuel, 53
- carbonyl sulfide (COS), 225
- centrifuge test, lubricating greases, 330–331
- cetane index
  - diesel fuels, 45–46
  - nonaviation gas-turbine fuel, 45–46
- cetane number, biodiesel fuel, 62, 64
- cetane number improvers (diesel ignition improvers), 147–148
- characterization factor, crude oil, 101
- charged aerosol detection (CAD), 157
- chloride content
  - butanol, 33
  - ethanol, 27, 29
  - methanol, 31
- chromatographic methods
  - analyses of aromatics, feedstocks, and products using, 165, 166 (table)
  - atomic emission detector, 176 (table), 177
  - blended gasoline testing based on, 161–164, 163 (table), 164 (table)
  - comprehensive two-dimensional GC, 179
  - detailed hydrocarbon analyses with, 158–161, 158 (table), 159–161 (table)
  - flame photometric detector, 176 (table), 177
  - forms used by petroleum industry of, 155
  - future improved selective detectors, 180
  - future trends in, 179–180
  - gas chromatography, 155, 156 (figure), 165–175, 166 (table), 168 (table), 169 (figure), 170 (figure), 172 (figure), 172 (table), 173 (figure), 174 (table), 175 (table), 176 (figure), 176 (table), 178 (figure), 179 (table)
  - gas chromatography-vacuum ultraviolet, 177–178
  - ICP-MS detection system, 177, 178 (figure)
  - ion chromatography, 155, 157
  - liquid chromatography, 155–157, 156 (figure), 178, 179 (table)
  - MS and coupled MS as future, 180
  - multidimensional PIONA test methods with, 158–161, 158 (table), 159–161 (table)
  - naphtha range petroleum samples analyses with, 158–164, 158 (table), 159–161 (table)
  - nitrogen chemiluminescence detector, 175–177
  - olefins in naphthas and blended gasolines with testing based on, 164–165, 164 (table)
  - selective detectors for petroleum fractions, 175–179, 176 (figure), 176 (table), 178 (figure), 179 (table)
  - simdis analysis, 168–174, 169 (figure), 170 (figure), 172 (figure), 172 (table), 173 (figure), 174 (table), 175 (table)
  - simulated distillation of naphthas, distillates, and high-boiling streams by, 168–175, 169 (figure), 170 (figure), 172 (figure), 172 (table), 173 (figure), 174 (table), 175 (table), 176 (figure), 176 (table), 178 (figure), 179 (table)
  - sulfur chemiluminescence detector, 175, 176 (figure), 176 (table)
  - supercritical fluid chromatography, 155, 157–158, 157 (figure), 178–179, 179 (table)
  - ultrafast GC, 179–180
- Clean Air Act, U.S.
  - additives regulations, 14–15
  - fuel oxygenates regulation with, 22–24, 25 (table)
  - gasoline regulations from, 4
- cleanliness
  - ASTM methods for, 223
  - color, 222
  - diesel fuels, 47–48
  - lead precipitate, 222
  - light fuels differs from residual fuels with, 211
  - liquid fuels, 211–224, 217 (table)
  - microbial, 220–221
  - miscellaneous properties related to, 222
  - nonaviation gas-turbine fuel, 47–48
  - requirements for, 217 (table)
  - sampling, 222
  - sediment content, 220
  - test methods for, 215–220, 217 (table)
  - water content, 220
  - water reaction interface rating, 222
  - workmanship and general requirements with, 212
- clearance sample, 136
- cloud point
  - diesel fuels, 47
  - fuel oils, 202–203
  - lubricating oils, 272
  - nonaviation gas-turbine fuel, 47
  - rubber oils, 319
  - white mineral oils with, 252
- coal tar pitch. *See* pitch
- cold filter plugging point, 47
- cold soak filterability parameter, biodiesel fuel, 62
- color
  - cleanliness, 222
  - kerosine, 208
  - lubricating oils, 273
  - petroleum waxes, 344
  - rubber oils, 318–319
  - stability, 222
  - white mineral oils, 252
- color dyes additive
  - aviation fuels with, 89–90, 94
  - gasoline, 146
  - red dye, 53, 151–152, 192
- combustion characteristics
  - diesel fuels, 45
  - nonaviation gas-turbine fuel, 45
- combustion process
  - diesel engine, 38, 39 (figure)
  - nonaviation gas-turbine engine, 38–39
- combustion quality, aviation fuels, 84
- compartment-tank composite sample, 136
- compatibility
  - ASTM methods for, 224
  - fuel oils, spot test for, 204
  - heavy and residual fuels, 221–222
  - test methods for, 221–222
- complex soap greases, 323
- component testing, 136
- composite sample, 136
- compositional analysis, liquefied petroleum gas, 230
- composition properties, 9–11

- conductivity
    - aviation fuels, 85–86
    - diesel fuel, 149
    - fuel oils, 200 (table), 204
    - thermal, 244
  - conductivity improver additive, in aviation fuels, 91–92
  - constant volume sample container, 136
  - container fill, 230
  - contaminants
    - ASTM methods for, 223
    - aviation fuels, 86–87
    - liquid fuels, 211, 212
    - natural gas, 225
  - contamination
    - automotive spark-ignition engine fuel, 12–13
    - lubricating greases, 336, 336 (figure)
  - contamination control additives, 151
  - continuous sample, 136
  - Coordinating Research Council (CRC), 8, 10, 93
    - Aviation Engine Octane Rating Group, 74
    - Diesel Performance Panel, 220
    - Driveability Task Force, using data from, 7
  - copper content
    - crude oils, 102
    - ethanol, 27, 29
  - copper corrosion
    - aviation fuel sampling affected by, 131
    - butanol, 33
    - fuel oils, 201
    - kerosine, 206 (table), 208
    - liquefied petroleum gas, 229
    - lubricating greases, 335, 335 (figure)
    - methanol, 32
    - spark-ignition engine fuel, 9
  - copper corrosion inhibitors, gasoline additive, 146
  - core sample, 136
  - corrosion. *See also* copper corrosion
    - aviation fuels, 85
    - lubricating greases, 335–336, 335 (figure)
    - properties, 9
  - corrosion inhibitors, fuel additives, 151
  - corrosion inhibitors/lubricity improvers (CI/LIs)
    - aviation fuels with, 90–91
  - crude oils, 226
    - analysis of, 97
    - analytical method improvements needed for, 113
    - API gravity, 98–99
    - API research projects on, 97
    - arsenic content, 101
    - ash content, 105
    - asphaltenes, 105
    - ASTM/UOP standards, 113–115
    - automatic sampling, 130
    - boiling point distribution, 105–106
    - cadmium content, 102
    - carbon residue, 104
    - characterization factor, 101
    - chromatogram of high-temperature simdis of, 172 (figure)
    - compatibility, 111–112
    - complex composition of, 97
    - comprehensive assay format, 108 (table)
    - comprehensive assays, 106–110
    - copper content, 102
    - dead, 136
    - distillate fuel oil fraction, 109
    - economics in assays of, 97
    - fluidity, 100–101
    - as fuel, 111
    - future needs in characterization, 112–113
    - gas fraction, 107
    - HTSD in assessment of, 106, 110, 171
    - hydrogenation processes for reduction of sulfur and nitrogen in, 112
    - hydrogen sulfide, 104–105
    - inspection assays, 98–106
    - iron content, 101
    - kerosine fraction, 109
    - lead content, 101
    - live, 137
    - manual piston cylinder sampling for volatile, 135
    - methanol, 105
    - naphtha fraction, 107, 109
    - nickel content, 101
    - organic chlorides, 104
    - organic halides, 104
    - pour point, 100–101
    - propane, and butanes from, 226
    - referee test methods, 110
    - residuum fraction, 109–110
    - salt content, 99–100
    - sampling, 110–111
    - sediment content, 100
    - sulfur content, 99
    - total acid number, 103–104
    - total nitrogen content, 104
    - trace elements, 101–103
    - true boiling point distillation curves for, 107 (figure)
    - vacuum gas oil fraction, 109
    - vanadium content, 101
    - vapor pressure, 103
    - viscosity, 100–101
    - water content, 100
    - zinc content, 102
- D**
- dead bottom sample, 136
  - dead crude oil, 136
  - dead legs, 136
  - dead volume, 136
  - deck composite sample, 136
  - deep-draft vessel propulsion, 40
  - defoaming additives, 294
  - dehazers, 146
  - de-icer additives, 149
  - demulsifiers
    - fuel additives, 151
    - gasoline additive, 147
  - denaturants, ethanol, 28
  - D.Eng.RD. (DERD)
    - 2482 specification of, 76–77
  - density
    - anode/cathode tests for, 243
    - automotive spark-ignition engine fuel, 13–14
    - aviation fuels, 73, 84
    - biodiesel fuel, 66
    - butanol, 34
    - defined, 136
    - diesel fuels, 45
    - fuel oils, 200 (table), 201–202
    - graphite, 244
    - liquefied petroleum gas, 229
    - manufactured carbon, 244
    - nonaviation gas-turbine fuel, 45
    - petroleum coke, 238

- petroleum waxes, 344
- pitch, 242
  - for white mineral oils, 253
- detailed hydrocarbon analysis (DHA)
  - naphtha analyses with, 158–161, 158 (table), 159–161 (table)
- detergents, 294
  - automotive engine oils, 311–312
  - gasoline additive, 143–144
- Deutsches Institut für Normung, 1
- dielectric breakdown voltage, of white mineral oils, 252–253
- diesel engine, 276–277
  - alternative fuels for, 54–55
  - applications, 37
  - classification, 37
  - combustion process, 38, 39 (figure)
  - design, 38
  - fuel characteristics and specifications for, 39–40, 41 (table)
  - fuel properties for, 38
  - ignition, 38
  - ignition delay, 38
  - injection of fuel, 38
  - operating speeds, 37
  - pressure charging, 38
  - pressure variations in, 40 (figure)
  - range of, 38 (table)
  - three grades of diesel fuel for, 42, 43 (table)
- diesel fuel additives
  - aftermarket, 153
  - anti-foams, 149
  - antioxidants, 150
  - biocides, 151
  - California regulations on, 152
  - cetane number improvers, 147–148
  - conductivity additive, 149
  - contamination control additives, 151
  - corrosion inhibitors, 151
  - de-icer additives, 149
  - demulsifiers, 151
  - diesel ignition improvers, 147–148
  - dispersants, 150
  - distribution system additization, 152
  - drag reducer, 149
  - engine and fuel delivery system performance, 147
  - fuel cleanliness, 151
  - fuel handling improvement additives, 149–150, 150 (table)
  - fuel stability additives, 150
  - functions of, 143
  - injector cleanliness, 148, 148 (figure)
  - low temperature operability improver additives, 149–150, 150 (table)
  - lubricity additives, 148
  - metal deactivators, 150
  - red dye, 53, 151–152, 192
  - smoke suppressants, 148
  - stabilizers, 150
  - types of, 146–147
- diesel fuels
  - acid number, 54
  - alternative, 54–55
  - aromatic content, 50
  - ash content, 53
  - ASTM standards, 55–56
  - calcium content, 54
  - carbon residue, 53
  - cetane index, 45–46
  - cleanliness, 47–48
  - cloud point, 47
  - cold filter plugging point, 47
  - combustion characteristics, 45
  - density, 45
  - distillation characteristics, 46, 46 (figure)
  - flash point, 49
  - grades of, 43–45
  - heat content, 50–51, 51 (table)
  - ignition characteristics, 45
  - ISO marine fuels specification, 43
  - lead content, 54
  - low-temperature flow test, 47
  - lubricity, 49–50
  - oxidative stability, 48–49
  - potassium content, 54
  - pour point, 47
  - properties, 45–55
  - red-dyed, 53, 151–152, 192
  - requirements for, 44 (table)
  - sodium content, 54
  - stability, 48–49
  - storage stability, 49
  - sulfur grades with, 42
  - supercritical fluid chromatography for, 178–179, 179 (table)
  - tests, 45–55
  - thermal stability, 48
  - three grades of, 42, 43 (table)
  - total sulfur, 51–52, 52 (table)
  - ultra-low sulfur, 143
  - vanadium content, 54
  - viscosity, 46–47
  - volatility, 46
- diesel ignition improvers. *See* cetane number improvers (diesel ignition improvers)
- diesel ignition improvers fuel additive, 147–148
- Diesel Performance Panel, 220
- diisopropyl ether (DIPE), 16
- dimethylformamide insolubles, pitch, 242–243
- diolefins, petrochemical applications, 231–232
- dipper sample, 136
- direct match technique, 186
- dispersants, 150, 294
- dissolved water, 136
- distillate fuel oil
  - crude oil fraction, 109
  - temperature ranges for, 106
- distillate fuels, representative sample, 122
- distillation
  - fuel oils, 197
  - kerosine, 206 (table), 207–208
  - pitch, 242
  - spark-ignition engine characteristics with, 7
  - for white mineral oils, 253
- distillation characteristics
  - diesel fuels, 46, 46 (figure)
  - nonaviation gas-turbine fuel, 46, 46 (figure)
- distillation curve, for biodiesel fuel, 60
- domestic heating oils, 191–192
  - burning equipment associated with, 194
- drag reducer fuel additive, 149
- drain sample, 136
- driveability index, spark-ignition engine characteristics with, 7
- Driveability Task Force, 7
- droplet dispersion condition, 136
- dropping point, lubricating greases, 329–330, 329 (figure)
- dry-bath RPVOT, 305, 305 (figure)
- dust control material, for petroleum coke, 238

## dyes

- aviation fuels additive, 89–90, 94
- gasoline additive, 147
- red, diesel fuel additives, 53, 151–152, 192

dynamic viscosity, 268–269, 296

**E**

E85. *See* flex fuel (E85)

e-diesel, 55

elastomers compatibility, 13

electrical conductivity

- aviation fuels, 85–86
- aviation fuel sampling affected by, 131

electrical resistivity

- anode/cathode tests for, 243
- graphite, 244–245
- manufactured carbon, 244–245

electron capture detectors (ECD), 155

emissions, aviation fuels, 84

emulsified fuels, 55

emulsion, 136

Energy Independence and Security Act of 2007 (EISA 2007), 21, 23, 25, 25(table)

Energy Institute, 1

Energy Policy Act of 2005 (EPACT 2005), 25

engine and fuel delivery system performance additives, 147

engine oil bench test methods, 289–290

entrained water, 137

Environmental Protection Agency (EPA)

- additives regulations, 14–15
- ASTM test methods for, 163 (table)
- correlation equation, 184
- fuel oxygenates regulation with, 21, 22
- gasoline regulations from, 4
- manganese content, 10
- red dye required as additive by, 151, 192
- reformulated gasoline adopted by, 25

ethane

- ASTM specifications, 233
- boiling point of, 226
- quality criteria, 227

ethanol

- acidity, 27, 29
- Alcohol and Tobacco Tax and Trade Bureau in regulation of, 24–25
- alternative fuels program in regulation of, 26
- ASTM fuel specifications for, 26–34
- Clean Air Act in regulation of, 22–24, 25 (table)
- Clean Fleets Program in regulation of, 26
- copper content, 27, 29
- denaturants, 28
- EPA approval for, 21
- existent sulfate content, 27–28
- fuel blends test methods for, 28
- hydrocarbons, 29
- inorganic chloride ion content, 27, 29
- octane specification with, 188
- organometallic compounds content, 30
- pHe, 27, 29
- regulatory approval of, 22–26
- sampling procedures for, 34
- solvent-washed gum, 26, 29
- state biofuel mandates, 26
- sulfur content, 27, 29
- test methods needed for, 211
- vapor pressure, 28
- water content, 27, 29
- workmanship, 28–30

ethers, 55

ethylene (C<sub>2</sub>H<sub>4</sub>)

- ASTM specifications, 234
- gas chromatography in analyses of, 166–168, 166 (table)
- petrochemical applications, 231

Ethyl tert-Butyl Ether (ETBE), 16

- butanol, 33
- test methods for, 33

European Committee for Standardization, 1

European Pharmacopoeia (EP), 249

- bacterial endotoxin requirement in, 252

evaporation loss

- lubricating greases, 330
- lubricating oils, 274
- rubber oils, 319

evaporative light scattering detection (ELSD), 157

existent gum content, butanol, 34

existent sulfate content, ethanol, 27–28

**F**

fatty acid methyl esters (FAME), 86, 93–94

- test methods needed for, 211

Federal Trade Commission, antiknock rating regulations of, 6

feedstocks, chromatographic methods in analyses of, 165, 166 (table)

ferrous corrosion, 9

ferrous corrosion inhibitors, gasoline additive, 145

fire point

- fuel oils, 196
- lubricating oils, 272–273
- for white mineral oils, 253

Fischer-Tropsch fuels, 55

flame ionization detector (FID), 155, 157–158, 170–171

flame photometric detector (FPD), 155, 176 (table), 177

flash point

- biodiesel fuel, 62
- defined, 137
- diesel fuels, 49
- fuel oils, 196, 199 (table)
- kerosine, 206 (table), 207
- lubricating oils, 272–273
- nonaviation gas-turbine fuel, 49
- petroleum waxes, 344
- for white mineral oils, 253

flex fuel (E85), 3

floating piston cylinder (FPC), 137

floating roof sample, 137

flow-proportional sample, 137

fluidity, crude oil, 100–101

foam, lubricating oils, 274

foaming tendency, automotive engine oils, 311, 311 (figure)

Food Chemical Codex (FCC), 249

- bacterial endotoxin requirement in, 252

four-ball test, 309, 309 (figure)

- lubricating greases, 333–334

Fourier-transform infrared spectroscopy (FTIR), 155, 183. *See also* spectroscopic methods

free glycerin method, 66

free water, 137

freezing point

- aviation gasoline, 73
- kerosine, 206 (table), 208

fuel additives, 11, 12 (table). *See also* diesel fuel additives

- aviation, 87–94, 89 (table)
- biocides, 151
- cleanliness, 151
- handling improvement, 149–150, 150 (table)
- stability, 150
- U.S. regulations, 14–15

- fuel blends test methods, for ethanol, 28
- fuel injection  
diesel engine, 38  
nonaviation gas-turbine engine, 38–39
- fuel oils  
acid number, 200 (table), 203  
ash content, 198, 199 (table)  
biodiesel content, 203–204  
carbon residue, 198  
classification, 196  
cloud point, 202–203  
conductivity, 200 (table), 204  
copper corrosion, 201  
density, 200 (table), 201–202  
distillation, 197  
fire point, 196  
flash point, 196, 199 (table)  
heat content, 204  
laboratory tests, 196–205  
lubricity, 199 (table), 201  
microbial contamination, 205  
nitrogen, 204–205  
oxidation stability, 203  
pour point, 200 (table), 202  
regulations affecting, 192  
requirements, 199–200 (table)  
sediment content, 196–197  
specifications, 196  
spot test for compatibility, 204  
stability, 203  
storage stability, 203  
sulfur content, 198–201, 199 (table)  
viscosity, 197–198  
water content, 196–197, 199 (table)
- fuel oxygenates  
Alcohol and Tobacco Tax and Trade Bureau in regulation of, 24–25  
alternative fuels program in regulation of, 26  
ASTM fuel specifications for, 26–34  
ASTM test methods for, 34–35  
Clean Air Act in regulation of, 22–24, 25 (table)  
Clean Fleets Program in regulation of, 26  
EPA approval for, 21, 22  
regulatory approval of, 22–26  
renewable fuels standard in regulation of, 25  
sampling procedures for, 34  
state biofuel mandates, 26  
types of, 22–26
- fuels. *See also* aviation fuels; diesel fuels  
automotive spark-ignition engine fuel, 3–19  
burner, 191–209, 199–200 (table), 206 (table)  
diesel engine, 37–56  
gaseous, 55, 232–234  
gas-to-liquids, 55  
gas-turbine engine, 37–56  
heating, 191–209, 199–200 (table), 206 (table)  
heavy, 221–222  
light, 211  
lighting, 191–209, 199–200 (table), 206 (table)  
liquid, 211–224, 217 (table)  
oxygenates, 21–35
- fuel system icing inhibitor (FSII)  
aviation fuels with, 91, 94
- G**
- gas, 3  
crude oil fraction, 107  
temperature ranges for, 106
- gas chromatography (GC)  
analyses of gases by, 165–168, 166 (table)  
biofuels and miscellaneous test methods with, 168, 168 (table)  
comprehensive two-dimensional, 179  
detectors used in, 155  
future trends and prospects for, 179–180, 365–367, 367 (figure)  
naphtha analyses with, 158 (table)  
schematic, 156 (figure)  
separation mechanisms in, 155  
simdis analysis by, 168–174, 169 (figure), 170 (figure), 172 (figure), 172 (table), 173 (figure), 174 (table), 175 (table)  
simulated distillation of naphthas, distillates, and high-boiling streams by, 168–175, 169 (figure), 170 (figure), 172 (figure), 172 (table), 173 (figure), 174 (table), 175 (table), 176 (figure), 176 (table), 178 (figure), 179 (table)  
ultrafast, 179–180
- gas chromatography-flame ionization detector (GC-FID), 158
- gas chromatography-Fourier-transform infrared spectroscopy (GC-FTIR), 158
- gas chromatography-mass spectrometry (GC-MS), 155, 158
- gas chromatography-vacuum ultraviolet (GC-VUV), 177–178  
analyses of naphthas with, 158
- gas engine oils, 278
- gaseous fuels, 55  
ASTM specifications, 233–234  
test methods used for, 232–234
- gasohol, 3
- gasoline, 3  
automotive, use in aircraft, 75–76  
aviation, 69–81 (*See also* aviation gasoline)  
defined, 4  
natural, 230–231  
regulations driving changes in, 4  
supercritical fluid chromatography for, 178–179, 179 (table)
- gasoline additives  
antioxidants, 144–145  
application throughout fuel delivery system of, 147  
ASTM specifications, 153  
copper corrosion inhibitors, 146  
demulsifiers and dehazers, 146  
detergents, 143–144  
dyes, 146  
ferrous corrosion inhibitors, 146  
markers, 146  
metal deactivators, 145  
octane improvers, 146  
silver corrosion inhibitors, 146
- gasoline-ethanol blend, 3
- gasoline-oxygenate blends, 4  
sampling of, 17  
test methods for, 17  
use of, 16–17
- gas-to-liquids fuels, 55
- gas-turbine lubricants, 277–278, 278 (table)
- gear oils, 278–279
- Gelation Index curves, 302 (figure)
- gel permeation chromatography (GPC), 156, 156 (figure)
- GOST (Gosstandart) specifications, 70–71, 71 (table), 80–81, 80 (table)
- grab, 137
- grab sample, 137
- graphite  
anode/cathode tests for, 243–244  
ash content, 244  
atomic structure associated with, 235–236, 236 (figure)  
calcining process for, 236  
compressive strength, 245

density, 244  
 elasticity, 245–246  
 electrical resistivity, 244–245  
 flexural strength, 246  
 flow diagram for production of, 237 (figure)  
 fracture toughness, 247  
 friction and wear, 246–247  
 fundamental frequencies, 245–246  
 graphitization process for, 236–237  
 high-temperature gas-cooled nuclear reactors, 246  
 impervious graphite pipe and threading, 245  
 irradiation results, 245  
 manufacturing methods for, 237–238  
 measurements, 247  
 metals, 245  
 modulus of rupture in bending, 247  
 moisture, 245  
 nuclear graphites specification, 247  
 oxidation mass loss, 247  
 porosity, 244  
 properties of, 235–248  
 pyrolytic graphite in manufacture of, 237–238  
 reactivity, 247  
 Rockwell hardness, 245  
 sample preparation, 248  
 sampling, 246  
 scleroscope hardness, 245  
 sonic velocity, 246  
 specific gravity, 244  
 sulfur content, 247  
 tensile properties, 245  
 tensile stress-strain, 246  
 terminology methods, 244  
 test methods for, 239–241 (table), 244–248  
 thermal diffusivity, 246  
 uniaxial strength, 247–248  
 graphitization process, 236–237  
 greases. *See also* lubricating greases  
   in-service samples of lubricating, 134–135  
   sample, 122, 137  
 gum content, 11–12  
   solvent-washed, 26, 29, 30, 32, 33  
 gum inhibitors additive, aviation fuels with, 90

## H

Hardgrove Grindability Index, for petroleum coke, 238  
 heat content  
   diesel fuels, 50–51, 51 (table)  
   fuel oils, 204  
   nonaviation gas-turbine fuel, 50–51, 51 (table)  
 heating fuels, 191–209, 199–200 (table), 206 (table)  
   ASTM specifications, 208  
   biodiesel in, 192  
   burning equipment associated with, 194  
   kerosine as, 192  
   transportation of distillate, 193  
 heating oils, domestic, 191–192, 194  
 heat of combustion, 84  
 heat resistance, lubricating greases, 328–329, 329 (figure)  
 heavy-ends limitation, liquefied petroleum gas, 228–229  
 heavy fuels, compatibility with residual and, 221–222  
 heavy naphtha, temperature ranges for, 106  
 heavy vacuum gas oil (HVGO), 106  
 helium, natural gas with, 232  
 heterogeneity, 119–122, 120 (figure), 121 (figure)  
 high pressure cylinder, 137  
 high pressure sample cylinder, 137

high temperature simulated distillation (HTSD), 169–171, 173–175  
   analysis of crude oils with, 171  
   boiling point distribution determination with, 106  
   crude oil assessment with, 106, 110  
   sample dilution required in, 170  
 high temperature stability, aviation fuels, 85  
 homogeneity, 119–122, 120 (figure), 121 (figure), 137  
 hydraulic fluids, representative sample, 122  
 hydraulic oils, 281–282, 281 (table)  
 hydrocarbons, 225, 226  
   ethanol, 29  
   methanol, 30  
   naphtha, test methods for, 159–161 (table)  
   spark-ignition engine fuel with, 10–11  
   test methods used for, 232–234  
 hydrocarbon-type compositional analysis, 258–259  
 hydrodynamic lubrication  
   bearing hardness and finish, 308  
   load-bearing contact area, 308  
 hydrogenation processes, 112  
 hydrogen sulfide, crude oil, 104–105

## I

ignition, diesel engine, 38  
 ignition characteristics  
   diesel fuels, 45  
   nonaviation gas-turbine fuel, 45  
 ignition control additive, aviation fuels with, 93  
 ignition delay, 38  
 ignition standard test, 338  
 inductively coupled plasma (ICP), 103, 270–271  
 Inductively Coupled Plasma-Atomic Emission Spectrometry (ICP-AES), 102, 360–361, 361 (figure)  
 inductively coupled plasma/mass spectrometry (ICP-MS), 155, 361–362, 362 (figure)  
   petroleum fractions detection system, 177, 178 (figure)  
   triple quadrupole, 363–364, 363 (figure)  
 inductively coupled plasma-optical emission spectrometry (ICP-OES), 360–361  
 industrial chemicals, sampling, 128–129  
 industrial engine oils, 277  
 inert gas, 137  
 inerting, 137  
 infrared (IR) technologies, 183–184. *See also* spectroscopic methods  
 injector cleanliness additives, 148, 148 (figure)  
 inorganic chloride ion content, ethanol, 27, 29  
 inorganic species, in petroleum products and lubricants  
   analytical methods in determination of, 351–355, 352–354 (table), 356 (table)  
   atomic spectroscopy, 358–363, 359 (table)  
   current state, 351–358  
   elemental analysis, 351  
   future prospects, 365–367, 365 (figure)  
   historical perspective, 351  
   quality assurance of results, 297  
   recent instrumental developments, 363–365  
   sample preparation in determination of, 355–358, 357 (figure), 358 354 (table)  
 inorganic sulfate content  
   butanol, 33  
   methanol, 31  
 intermediate conditions, 371  
 intermediate sample container, 137  
 Internal Revenue Service (IRS)  
   red dye required as additive by, 151, 192  
 International Air Transport Association (IATA), 80

International Organization for Standardization, 1  
ion chromatography (IC), 155, 157

IP 2, 256, 265  
IP 13, 265  
IP 14, 265  
IP 15, 256, 265, 283  
IP 34, 256, 265, 282  
IP 36, 256, 265, 282  
IP 40, 222  
IP 53, 221, 223  
IP 61, 283  
IP 71, 255, 256, 265, 283  
IP 74, 221, 223, 282  
IP 123, 256  
IP 131, 12, 223  
IP 135, 9, 283  
IP 138, 222  
IP 139, 283  
IP 146, 265, 283  
IP 154, 10, 283  
IP 160, 255, 265  
IP 163, 283  
IP 177, 265  
IP 196, 265, 283  
IP 216, 223  
IP 219, 255, 265  
IP 226, 265, 283  
IP 299, 265  
IP 323, 222  
IP 356, 221, 223  
IP 365, 255, 265  
IP 375, 221, 223  
IP 378, 215, 222  
IP 379, 265  
IP 386, 221, 223  
IP 388, 213, 222  
IP 406, 265  
IP 415, 223  
IP 423, 219, 223  
IP 496, 265  
IP 583, 94  
iron, crude oils, 101  
isooctane, 70

## J

Japanese Industrial Standards in Japan, 1  
Japan Pharmacopeia (JP), 249  
    bacterial endotoxin requirement in, 252  
jar sample, 137  
jet fuels, 76  
    American civil, 78, 79 (table)  
    American military, 77–78, 77 (table)  
    Russian, 80, 80 (table)  
    supercritical fluid chromatography for, 178–179, 179 (table)  
jet skis, 3  
joule cycle, 37

## K

kerosine  
    burning characteristics of, 205–207  
    burning equipment associated with, 194–195  
    burning tests for, 207  
    char formation on wick with, 206  
    color, 208  
    copper strip corrosion, 206 (table), 208  
    crude oil fraction, 109  
    defined, 192

    distillation, 206 (table), 207–208  
    feed to wick constancy with, 205–206  
    flash point, 206 (table), 207  
    freezing point, 206 (table), 208  
    initial flame height smoke point with, 205  
    laboratory tests for, 207–209  
    lamp-glass deposit formation with, 206–207  
    mercaptan sulfur, 206 (table), 208  
    performance evaluation, 205–207, 206 (table)  
    requirements for, 206 (table)  
    sulfur, 206 (table), 208  
    temperature ranges for, 106  
kinematic viscosity, 269–270  
    application of, 295–296

## L

laboratory information management system (LIMS), 187–188  
laboratory sample, 137  
lead content, 9–10  
    crude oils, 101  
    diesel fuels, 54  
    methanol, 30  
    nonaviation gas-turbine fuel, 54  
lead precipitate  
    cleanliness, 222  
    stability, 222  
leak detector additive, aviation fuels with, 92, 94  
light ends, 137  
light fuels, residual fuels differs from, 211  
lighting fuels, 191–209, 199–200 (table), 206 (table)  
    ASTM specifications, 208  
    kerosine as, 192  
light naphtha, temperature ranges for, 106  
light vacuum gas oil (LVGO)  
    temperature ranges for, 106  
linefill, 137  
liquefied petroleum gas (LPG), 225  
    ASTM specifications, 233  
    component analysis, 230  
    copper corrosion, 229  
    defined, 137  
    density, 229  
    heavy-ends limitation, 228–229  
    percentage fill of cylinders of, 230  
    properties, 228–230  
    quality criteria, 227  
    representative sample, 122  
    residue, 229  
    sampling, 129, 228  
    sulfur content, 229–230  
    test methods, 228–230  
    vapor pressure, 228  
    water content, 230  
liquefied refinery gas, 226  
liquid-bath RPVOT, 303, 303 (figure)  
liquid chromatography (LC), 155  
    classification, 156 (figure)  
    detectors used in, 157  
    future prospects, 367  
    separation mechanisms in, 156, 156 (figure)  
    supercritical fluid chromatography applications, 178, 179 (table)  
liquid fuels  
    contaminants, 211, 212  
    sediment content, 212  
    stability and cleanliness, methods for assessing, 211–224, 217 (table)

- water content, 212
- workmanship and general requirements with, 212
- lithium soap greases, 323
- live crude oil, 137
- loading zone sample, 137
- lot, 137
- lower sample, 137
- low-pressure atomizing burner, 194
- low temperature engine startability, 296
- low-temperature flow test (LTFT), 47, 150
- low temperature operability improver additives, 149–150, 150 (table)
- lubricant base oils, 257–265. *See also* base oils
- lubricants
  - inorganic species in, 351–367
  - representative sample, 122
- lubricating greases
  - accelerated corrosion tests, 335
  - aluminum soap greases, 323
  - apparent viscosity, 327–328
  - ASTM/IP standards, 338–339
  - ball bearings, 328, 332
  - block penetration, 326
  - bomb oxidation test, 331–332, 332 (figure)
  - calcium soap greases, 323
  - calcium sulfonate greases, 323–324
  - centrifuge test, 330–331
  - characteristics, 323–324
  - chemical analysis, 337
  - classification and specifications, 324–325, 325 (table)
  - compatibility, 337
  - complex soap greases, 323
  - composition, 322
  - cone penetration, 325–326
  - consistency, 325
  - consistency stability, 326
  - contamination, 336, 336 (figure)
  - copper corrosion, 335, 335 (figure)
  - corrosion, 335–336, 335 (figure)
  - defined, 321
  - described, 321–322
  - discontinued standards, 337
  - dropping point, 329–330, 329 (figure)
  - elastomer compatibility, 336–337
  - at elevated temperatures, 332
  - evaporation loss, 330
  - extreme pressure and wear, 333–335
  - flow properties, 327
  - four-ball test, 333–334
  - fretting wear, 334
  - function, 321
  - heat resistance, 328–329, 329 (figure)
  - ignition standard test, 338
  - international standards, 338
  - ISO standards, 338, 338 (table)
  - leakage from wheel bearings, 331, 331 (figure)
  - lithium soap greases, 323
  - low-temperature penetration, 326–327
  - low-temperature torque, 328
  - NLGI consistency numbers, 326, 326 (table)
  - oil separation, 330–331, 331 (figure)
  - organoclay greases, 324
  - oscillating motion, 334
  - oscillating wear tests, 334–335
  - oxidation stability, 331–333, 332 (figure)
  - polyurea, 322, 324
  - pressure differential scanning calorimetry oxidation test, 332
  - prolonged worked penetration, 326–327
  - roll stability, 327
  - rust prevention, 335
  - selection, 322–323
  - in small bearings, 333
  - sodium soap greases, 323
  - standards under development, 338
  - static bleed tests, 330, 331 (figure)
  - tapered roller bearings, 328
  - test methods, 325–331
  - Timken method, 333
  - undisturbed penetration, 326
  - unworked penetration, 326
  - urea greases, 324
  - water effects, 335
  - water spray-off, 336, 336 (figure)
  - water washout, 335–336
  - wear preventive characteristics, 334
  - wheel bearing grease life, 333
  - worked penetration, 326
- lubricating oils
  - air compressor, 282
  - API gravity, 273
  - ASTM/IP standards, 282–284
  - automatic transmission fluids, 279–280, 280 (table)
  - automotive engine, 274–276
  - burner fuel using, 193
  - chemical tests, 267
  - cloud point, 272
  - color, 273
  - composition, 268
  - elemental analysis, 270–271
  - engine and rig tests, 268
  - evaporation loss, test method, 330
  - evaporative loss, 274
  - flash and fire points, 272–273
  - foam, 274
  - function, 267
  - gas engine, 278
  - gas-turbine, 277–278, 278 (table)
  - gear, 278–279
  - general properties, 268–274
  - haze/turbidity, 273–274
  - hydraulic, 281–282, 281 (table)
  - inductively coupled plasma, 270–271
  - industrial and railway engine, 277
  - laboratory bench tests, 268
  - machine tool tableway, 282
  - manufacture, 268
  - marine diesel engine, 276–277
  - physical tests, 267
  - physicochemical tests, 268
  - pour point, 272
  - quality assessment, 267–268
  - refrigerator compressor, 282
  - relative density, 273
  - significance of tests, 268
  - specifications and procedures, 275–276
  - specific gravity, 273
  - steam cylinder, 282
  - steam-turbine, 280–281
  - viscosity, 268–270, 270 (table)
  - viscosity index, 270
  - volatility, 274
  - x-ray fluorescence in analysis of, 271
- lubrication
  - hydrodynamic, 308
  - viscosity index improvers' impact on, 297–299, 298 (figure)

- lubricity
  - additives, 148
  - aviation fuels, 82, 86
  - diesel fuels, 49–50
  - fuel oils, 199 (table), 201
  - improvers, aviation fuels with, 90–91
  - nonaviation gas-turbine fuel, 49–50
- luminosity, methanol, 31
- M**
- M85. *See* methanol fuel (M85)
- machine tool tableway lubricating oils, 282
- manganese content, 10
- manual piston cylinder (MPC), 137
- manual sampling
  - liquid fuels, 133–134, 133 (figure)
  - microbial contamination in fuels, 133–134, 133 (figure)
  - petroleum and petroleum products, 129–130
- manufactured carbon
  - anode/cathode tests for, 243–244
  - ash content, 244
  - atomic structure associated with, 235–236, 236 (figure)
  - calcining process for, 236
  - compressive strength, 245
  - density, 244
  - elasticity, 245–246
  - electrical resistivity, 244–245
  - flexural strength, 246
  - flow diagram for production of, 237 (figure)
  - fracture toughness, 247
  - friction and wear, 246–247
  - fundamental frequencies, 245–246
  - high-temperature gas-cooled nuclear reactors, 246
  - impervious graphite pipe and threading, 245
  - irradiation results, 245
  - measurements, 247
  - metals, 245
  - modulus of rupture in bending, 247
  - moisture, 245
  - nuclear graphites specification, 247
  - oxidation mass loss, 247
  - porosity, 244
  - properties of, 235–248
  - reactivity, 247
  - Rockwell hardness, 245
  - sample preparation, 248
  - sampling, 246
  - scleroscope hardness, 245
  - sonic velocity, 246
  - specific gravity, 244
  - sulfur content, 247
  - tensile properties, 245
  - tensile stress-strain, 246
  - terminology methods, 244
  - test methods for, 239–241 (table), 244–248
  - thermal diffusivity, 246
  - uniaxial strength, 247–248
- marine diesel engine oils, 276–277
- marine fuels specification, 43
- markers, gasoline additive, 146
- mass spectroscopy (MS), 103
  - future trends in, 180
- maximum fill density (reduced fill density), 137
- maximum fill volume (reduced fill volume), 138
- medium naphtha, temperature ranges for, 106
- melting point, petroleum waxes, 343
- mercaptans, natural gas contaminated with, 225
- mercaptan sulfur, kerosine, 206 (table), 208
- metal deactivators, 150
  - aviation fuels additive, 90, 94
  - gasoline additive, 145
- metals
  - aviation fuel sampling affected by trace, 131
  - graphite, 245
  - manufactured carbon, 245
  - in petroleum coke, 238
  - with white mineral oils, 253
- methane, 225
- methanol
  - acidity, 30
  - API gravity, 32
  - appearance, 31
  - butanol, 32
  - chloride content, 31
  - color, 31
  - copper strip corrosion, 32
  - crude oil, 105
  - hydrocarbons, 30
  - inorganic sulfate content, 31
  - lead content, 30
  - luminosity, 31
  - in MTBE, 32
  - phosphorus content, 30
  - solvent-washed gum content, 30, 32
  - sulfur content, 30–32
  - vapor pressure, 30, 32
  - water content, 32
  - workmanship, 31, 32
- methanol fuel (M85), 3
- methylcyclopentadienyl manganese tricarbonyl (MMT), 10
- Methyl Tertiary-Butyl Ether (MTBE), 16, 32
- microbial contamination, fuel oils, 205
- microwave plasma-atomic emission spectrometry (MP-AES), 364–365, 364 (figure), 365 (figure)
- middle sample, 138
- MIL-DTL-25524 specification, 78
- MIL-DTL-83133 specification, 77
- MIL-F-5624B specification, 77
- MIL-G-5572 specification, 69
- MIL-T-5616 specification, 77
- MIL-T-5624 specification, 77
- mixed sample, 138
- Mobile Source Air Toxics (MSAT), 11
- Mogas, 3
- molecular weight, petroleum waxes, 346
- mono-alkyl esters
  - biodiesel as, 59
  - conversion of fat or oil to, 60
  - defined, 59
- motor gasoline, 3
- motor octane, calibrations for, 184
- motor octane number (MON), 4
- multidimensional PIONA (MD-PIONA)
  - naphtha analyses with, 158–161, 158 (table), 159–161 (table)
- multiple tank composite sample, 138
- N**
- naphtha, 55
  - analyses of range petroleum samples for, 158–164, 158 (table), 159–161 (table)
  - crude oil fraction, 107, 109
  - detailed hydrocarbon analyses for, 158–161, 158 (table), 159–161 (table)
  - examples of, 158 (table)

- gas chromatographic approaches for analyses of, 158 (table)
  - multidimensional PIONA test methods for, 158–161, 158 (table), 159–161 (table)
  - olefins in, ASTM test methods for, 164–165, 164 (table)
  - oxygenates in, ASTM test methods for, 162 (table)
  - simulated distillation of, 168–175, 169 (figure), 170 (figure), 172 (figure), 172 (table), 173 (figure), 174 (table), 175 (table), 176 (figure), 176 (table), 178 (figure), 179 (table)
  - temperature ranges for, 106
  - test methods for hydrocarbons in, 159–161 (table)
  - virgin, 158 (table)
  - National Formulary (NF) standard, 249, 252
  - National Lubricating Grease Institute (NLGI), 324–325
    - consistency numbers, 326, 326 (table)
  - natural gas
    - associated products, 232
    - ASTM specifications, 233–234
    - contaminants, 225
    - helium with, 232
    - primary uses for, 226
    - quality criteria, 226
    - subclassification of, 225
    - sulfur with, 232
  - natural gas liquids (NGLs), 225–226
  - natural gasoline, 230–231
  - nickel, crude oils, 101
  - nitrogen
    - base oils in compounds of, 261
    - crude oil, 104
    - fuel oils, 204–205
  - nitrogen chemiluminescence detector (NCD), 175–177
  - nonaviation gas-turbine engine
    - air atomizing, 38–39
    - applications, 37
    - combustion process, 38–39
    - fuel characteristics and specifications for, 39–40, 42 (table)
    - fuel injection, 38–39
    - pressure atomizing, 38
    - prevaporizing, 39
    - range of, 38
  - nonaviation gas-turbine fuel
    - acid number, 54
    - aromatic content, 50
    - ash content, 53
    - ASTM standards, 55–56
    - calcium content, 54
    - carbon residue, 53
    - cetane index, 45–46
    - cleanliness, 47–48
    - cloud point, 47
    - cold filter plugging point, 47
    - combustion characteristics, 45
    - density, 45
    - distillation characteristics, 46, 46 (figure)
    - flash point, 49
    - grades of, 43–45
    - heat content, 50–51, 51 (table)
    - ignition characteristics, 45
    - lead content, 54
    - low-temperature flow test, 47
    - lubricity, 49–50
    - oxidative stability, 48–49
    - potassium content, 54
    - pour point, 47
    - properties, 45–55
    - requirements for, 44 (table)
    - sodium content, 54
    - stability, 48–49
    - storage stability, 49
    - tests, 45–55
    - thermal stability, 48
    - total sulfur, 52–53, 52 (table)
    - trace metal limits of, 54 (table)
    - vanadium content, 54
    - viscosity, 46–47
    - volatility, 46
  - normal phase liquid chromatography (NP-LC), 156, 156 (figure)
- O**
- octane improvers, gasoline additive, 146
  - octane number, calibrations for, 184
  - odorization, 230
  - oil-extended rubber, 316
  - olefins, 225
    - base oils, 261–262
    - calibrations for, 184
    - naphthas and blended gasolines with, 164–165, 164 (table)
    - petrochemical applications, 231–232
  - on-board quantity (OBQ), 138
  - on-line spectral analyzers, 188
  - open container, 138
  - organic chlorides, crude oil, 104
  - organic halides, crude oil, 104
  - organoclay greases, 324
  - organometallic compounds content, ethanol, 30
  - oscillating wear tests, 334–335
  - outage tube, 138
  - outlet sample, 138
  - oxidation
    - base oils, 260–261, 260 (figure)
    - engine oils and deposit formation, 303–308, 303 (figure), 304 (figure), 305 (figure), 306 (figure), 307 (figure)
    - exothermic oxidation measurement using RPVOT, 305, 305 (figure)
    - liquid-bath RPVOT, 303, 303 (figure)
    - resistance, 303
    - RPVOT, 303–306, 303 (figure), 304 (figure), 305 (figure), 306 (figure)
    - test criterion, 303–304, 304 (figure)
    - TFOUT test, 306, 306 (figure), 307 (figure)
    - turbocharger oxidation simulation tests, 307–308, 307 (figure)
  - oxidation stability
    - biodiesel fuel, 66
    - diesel fuels, 48–49
    - fuel oils, 203
    - nonaviation gas-turbine fuel, 48–49
  - oxygenated fuel programs, 15–16
  - oxygenates, 11. *See also* fuel oxygenates
    - gasoline blends with, 16
    - naphthas and blended gasolines with, 162 (table)
  - ozone nonattainment, 4
- P**
- paraffins, isoparaffins, aromatics, naphthenes (PIAN), 108 (figure), 109
  - particulate contamination, aviation fuel sampling affected by, 131
  - passenger car engine oil. *See* automotive engine oils
  - performance, spark-ignition engine characteristics with, 8–9
  - permanent viscosity loss (PVL), 297–299, 298 (figure)
  - peroxides, 12
    - in petroleum waxes, 345
  - petrodiesel, 57, 60
  - petrol, 3

- petroleum and petroleum products
  - automatic sampling, 130–131
  - inorganic species in, 351–367
  - manual sampling, 129–130
  - mixing and handling of liquid samples of, 132–133, 133 (table)
- petroleum coke
  - anode/cathode tests for, 243–244
  - ash content, 238
  - atomic structure associated with, 235
  - calcining process for, 236, 237 (figure)
  - crystallite size in, 238, 242
  - density, 238
  - dust control material for, 238
  - flow diagram for production of, 237 (figure)
  - grain stability with, 242
  - Hardgrove Grindability Index for, 238
  - metals in, 238
  - properties of, 235–248
  - quality production of, 236
  - sample preparation, 242
  - sampling, 242
  - sizing for, 242
  - stability, 242
  - sulfur, 238
  - synthetic graphite production with, 236
  - terminology in, 238
  - test methods for, 238–242, 239–241 (table)
  - volatile matter in, 238
- petroleum oils, for rubber, 315–320, 316 (table), 318 (table).  
*See also* rubber oils
- petroleum waxes
  - adhesion, 346
  - applications, 343
  - blocking properties, 346
  - boiling point distribution, 345
  - carbonizable substance, 346
  - chemical properties, 344–346, 348–349
  - classification, 341
  - color, 344
  - definitions, 342–343
  - density, 344
  - flash point, 344
  - food grade, 345
  - functional properties, 346–347, 349
  - hardness, 344
  - international test standards used for, 349–350
  - melting point, 343
  - moisture barrier properties, 346
  - molecular weight, 346
  - odor, 344
  - oil content, 345
  - peroxide content, 345
  - physical properties, 343–344, 347–348
  - production, 341–342
  - quality criteria, 343–347
  - slip properties, 346
  - solvent extractables, 345
  - substrates, 346
  - test methods, 347–350
  - ultraviolet absorptivity, 345
  - viscosity, 343–344
- pHe, ethanol, 27, 29
- phosphorus content, 10
  - biodiesel fuel, 62, 66
  - methanol, 30
- pin and V-block test method, 310–311, 310 (figure)
- pipeline, transporting heating fuels with, 193
- pipeline drag reducer (PDR)
  - aviation fuels with, 92–93
- pitch
  - anode/cathode tests for, 243–244
  - ash content, 243
  - atomic structure associated with, 235
  - calcining process for, 236
  - coking value in, 243
  - density, 242
  - dimethylformamide insolubles, 242–243
  - distillation, 242
  - mesophase in, 243
  - properties of, 235–248
  - quinoline insolubles, 242
  - sample preparation, 243
  - softening point of, 242
  - synthetic graphite production with, 236
  - terminology methods, 243
  - test methods for, 239–241 (table), 242–243
  - toluene insolubles, 243
  - viscosity, 243
  - volatility, 243
- plastics compatibility, 13
- polycyclic aromatic hydrocarbon (PAH), 317
- polyethylene, 166
- polypropylene, 166
- polyurea, 322, 324
- porosity, 244
- portable manual sampling unit (PSU), 138
- portable sample container, 138
- potassium content
  - biodiesel fuel, 66
  - biodiesel fuel and sodium combined with, 62
  - diesel fuels, 54
  - nonaviation gas-turbine fuel, 54
- pour point
  - base oils, 262–263
  - crude oil, 100–101
  - diesel fuels, 47
  - fuel oils, 200 (table), 202
  - lubricating oils, 272
  - nonaviation gas-turbine fuel, 47
  - rubber oils, 319
  - for white mineral oils, 254
- precision, 371–375, 372 (table), 373 (figure)
- pressure atomizing, 38
- pressure charging, 38
- pressure differential scanning calorimetry oxidation test, 332
- prevaporizing, 39
- primary sample container, 138
- profile average, 138
- profile testing, 138
- propane, 226
  - ASTM D1835, 227–228
  - commercial, 228
  - quality criteria, 227
  - special duty, 227–228
- propylene (C<sub>3</sub>H<sub>6</sub>)
  - ASTM specifications, 234
  - gas chromatography in analyses of, 166–167, 166 (table)
  - petrochemical applications, 231
  - trace impurities in, 231
- pyrolyate liquid fuel, 193–194
- pyrolytic graphite, 237–238

**Q**

- quality criteria
  - butanes, 227
  - butylene, 232
  - ethane, 226
  - finished products, 226
  - liquefied petroleum gas, 227
  - natural gas, 226
  - petroleum waxes, 343–347
  - product, 1
  - propane, 227
- quinoline insolubles
  - pitch, 242

**R**

- railway engine oils, 277
- Raman technology, 183
- Ravenfield Tapered-Plug Viscometer, 300
- Readily Carbonizable Substance test, 346
- red dye, diesel fuel additives, 53, 151–152, 192
- reduced fill density. *See* maximum fill density (reduced fill density)
- reduced fill volume. *See* maximum fill volume (reduced fill volume)
- reduced pressure distillation, biodiesel fuel, 66
- reformulated gasoline (RFG), 23, 25
- refractive index
  - rubber oils, 319
  - for white mineral oils, 254
- refrigerator compressor oils, 282
- Reid vapor pressure (RVP), 138, 184
- relative bias, 374–375
- relative density
  - automotive spark-ignition engine fuel, 13–14
  - lubricating oils, 273
- relief lines, 138
- remaining on board (ROB), 138
- renewable fuels standard (RFS)
  - fuel oxygenates regulation with, 25
- Renewable Fuel Standard, 1
- repeatability conditions, 371
- representative sample
  - defining, 122–123, 123 (figure), 138
  - distillate fuels, 122
  - greases, 122
  - hydraulic fluids, 122
  - liquefied petroleum gas, 122
  - lubricants, 122
  - summary, 124
- reproducibility conditions, 372
- research octane, calibrations for, 184
- research octane number (RON), 4
- residual fuels
  - compatibility with heavy and, 221–222
  - light fuels differs from, 211
- residual oil burning equipment, 195
- residue, liquefied petroleum gas, 229
- residuum
  - atmospheric, 106
  - crude oil fraction, 109–110
  - temperature ranges for, 106
  - vacuum, 106
- reverse phase liquid chromatography (R-LC), 156, 156 (figure)
- risk-cost analyses, sampling plan with, 121
- rotary-type burners, 195
- Rotating Pressure Vessel Oxidation Test (RPVOT)
  - additive injection during, 306
  - analysis of engine-turbocharger oil, 306 (figure)
  - ASTM D2272, 304 (figure)

- dry-bath, 305, 305 (figure)
- exothermic oxidation measurement using, 305, 305 (figure)
- liquid-bath, 303, 303 (figure)
- oxidation test, 303
- precision of, 305
- responses of antioxidants in, 304 (figure)
- test criterion, 303–304, 304 (figure)
- unit testing for multiple, 304–305, 304 (figure)

**rubber**

- natural, 315
- oil-extended, 316
- synthetic, 315

**rubber oils**

- aniline point, 319
- ASTM/IP standards, 320
- carbon-type analysis, 316–317
- classification, 316 (table), 318, 318 (table)
- cloud point, 319
- color, 318–319
- composition, 316–317, 316 (table)
- evaporation loss, 319
- history, 315–316
- importance of composition to compounders, 317–318
- molecular-type analysis, 316, 316 (table)
- physical properties, 318–319
- pour point, 319
- process oils, specialty applications, 319–320
- refractive index, 319
- specific gravity, 318
- ultraviolet absorptivity, 319
- viscosity, 318
- running sample, 138
- Russian jet fuels, 80, 80 (table)
- rust prevention, 335

**S****safety issues**

- container fill, 230
- odorization, 230

**salt content, crude oil, 99–100****sample**

- appropriate, 119
- automatic, 135
- average, 136
- aviation fuel, 131–132
- boring, 136
- bottom, 136
- bottom water, 136
- clearance, 136
- compartment-tank composite, 136
- composite, 136
- continuous, 136
- core, 136
- dead bottom, 136
- deck composite, 136
- defined, 138
- dilution required HTSD, 170
- dipper, 136
- disposal, 128
- distillate fuels, 122
- drain, 136
- floating roof, 137
- flow-proportional, 137
- from fungible systems, 123
- grab, 137
- graphite with preparation of, 248
- grease, 122, 137

- high pressure sample cylinder, 137
- hydraulic fluids, 122
- intermediate container for, 137
- jar, 137
- laboratory, 137
- liquefied petroleum gas, 122
- loading zone, 137
- lower, 137
- lubricants, 122
- lubricating grease, 134–135
- manufactured carbon with preparation of, 248
- middle, 138
- mixed, 138
- multiple tank composite, 138
- naphtha range of petroleum, 158–164, 158 (table), 159–161 (table)
- outlet, 138
- petroleum coke with preparation of, 242
- pitch with preparation of, 243
- representative, 122–124, 138
- running, 138
- scrape, 139
- small tank, 125 (figure)
- spectroscopic methods and handling of, 186–187
- spot, 139
- storage, 128
- suction, 139
- sump, 139
- surface, 139
- system security, 130
- tank composite, 139
- tank tap, 139
- time-proportional, 139
- top, 139
- tube, 125 (figure), 139
- upper, 139
- vacuum, 125 (figure)
- volumetric composite, 139
- zone, 140
- sample container
  - aviation fuel, 131–132
  - constant volume, 136
  - intermediate, 137
  - portable, 138
  - primary, 138
  - secondary, 139
  - stationary, 139
- sample controller, 138
- sample extractor, 138
- sample loop, 139
- sample probe, 139
- sampling, 139
  - anode/cathode tests for, 243–244
    - ASTM D1265, 129
    - ASTM D4057, 129
    - ASTM D4177, 129
    - ASTM D4306, 131–132
    - ASTM D4840, 131 (figure), 132
    - ASTM D5842, 132
    - ASTM D5854, 132–133, 133 (table)
    - ASTM D7464, 133–134
    - ASTM D7482, 134
    - ASTM D7718, 134–135
    - ASTM D8009, 135
    - ASTM E0300, 128–129
    - ASTM methods for, 224
    - automatic, 122
      - for automotive spark-ignition engine fuel, 14
      - aviation fuels, 87
      - chain-of-custody procedures, 131 (figure), 132
      - cleanliness, 222
      - considerations for collection, 126–128, 127 (table)
      - container cleanliness, 128
      - containers, 122
      - container selection, 126–128, 127 (table)
      - containers for aviation fuel, 131–132
      - crude oil, 110–111
        - defined, 119
        - diagnostic, 124
        - documentation, 126
        - extraction process, 122
        - flow stream condition, 122
        - for fuel oxygenates, 34
        - fuels for volatility measurement, 132
        - glossary, 135–140
        - graphite, 246
        - handling, 126–128, 127 (table)
        - handling and mixing, 122
        - handling of liquid petroleum and petroleum products, 132–133, 133 (table)
        - homogeneity and heterogeneity, 119–122, 120 (figure), 121 (figure)
        - hydrocarbons for mercury analysis, 134
        - industrial chemicals, 128–129
        - in-service lubricating grease, 134–135
        - liquefied petroleum gas, 129, 228
        - liquid fuels, 133–134, 133 (figure)
        - location with manual, 122
        - manual, 122
        - manual piston cylinder for volatile crude oils, 135
        - manufactured carbon, 246
        - microbial contamination in fuels, 133–134, 133 (figure)
        - objectives, 123
        - optimal plan for, 123
        - performance monitoring, 122
        - performance verification, 122
        - petroleum and petroleum products, 129–131
        - petroleum coke, 242
        - practices, 128–135, 131 (figure), 133 (figure), 133 (table)
        - qualifications of personnel collecting, 123
        - representative sample, 122–124
        - risk-cost analyses, 121
        - spot positions, 120 (figure)
        - stability, 222
        - system configuration, 124, 124 (figure), 125 (figure)
        - tests affected by trace contamination with, 131–132
- sampling system, 139
- sampling system verification test, 139
- scrape sample, 139
- secondary sample container, 139
- sediment content
  - ASTM methods for, 223
  - crude oil, 100
  - fuel oils, 196–197
  - liquid fuels, 212
- silver corrosion, 9
- silver corrosion inhibitors, gasoline additive, 146
- simdis analysis, 168
  - applications and correlations related to, 175, 175 (table)
  - application to crude oils of, 171
  - boiling point calibration plot with, 170 (figure)
  - chromatogram of calibration standard for high-temperature, 169 (figure)
  - chromatogram of crude oil by high-temperature, 172 (figure)

- chromatogram of lube oil by high-temperature, 173 (figure)
- GC columns applied to, 171
- principles of, 169–170, 169 (figure), 170 (figure)
- special applications using, 174 (table)
- test methods by various organizations, 174 (table)
- test methods per petroleum types with, 172 (figure)
- test methods review for, 171–174, 172 (figure), 172 (table), 173 (figure), 174 (table)
- simple liquid, 139
- skim sample. *See* surface sample (skim sample)
- slipstream sample loop, 139
- slipstream take-off probe, 139
- slip tube, 139
- smoke suppressants, 148
- snowmobiles, 3
- Society of Automotive Engineers (SAE), 324
- sodium content
  - biodiesel fuel with, 62, 66
  - diesel fuels, 54
  - nonaviation gas-turbine fuel, 54
- sodium soap greases, 323
- softening point, pitch, 242
- solid paraffin test, 255
- solvent-washed gum content
  - butanol, 33
  - ethanol, 26, 29
  - methanol, 30, 32
- specific energy, aviation gasoline, 73
- specific gravity
  - graphite, 244
  - lubricating oils, 273
  - manufactured carbon, 244
  - rubber oils, 318
  - for white mineral oils, 253
- specific heat, aviation fuels, 84
- spectroscopic methods
  - advantages to, 183
  - background, 183
  - calibration approaches for, 186
  - direct match technique for, 186
  - discrimination processes, 185–186
  - establishing confidence in results from, 187–188
  - ethanol conundrum with, 188
  - history of, 184–185
  - infrared technologies, 183–184
  - mathematical treatment, 185
  - nonlinearities in, 185–186
  - on-line *versus* laboratory testing with, 188–189
  - proactive use of blend planning with, 189–190
  - quantification, 185–186
  - Raman technology, 183
  - sample handling with, 186–187
  - sources of error with, 186–187
  - spark-ignition fuel analyzed with, 183–190, 184 (figure)
  - spectral normalization, 185
  - terminologies for, 184
- spot sample, 139
- stability
  - ASTM methods for, 222–223
  - biodiesel fuel, 62, 66
  - color, 222
  - diesel fuels, 48–49
  - fuel oils, 203
  - lead precipitate, 222
  - light fuels differs from residual fuels with, 211
  - liquid fuels, 211–224, 217 (table)
  - miscellaneous properties related to, 222
  - nonaviation gas-turbine fuel, 48–49
  - oxidation, 213–214
  - petroleum coke, 242
  - requirements for, 217 (table)
  - resistance of fuel to changes as, 211
  - sampling, 222
  - test methods for, 213, 217 (table)
  - thermal, 214–215
  - thermal and oxidative changes in fuels determining, 211
  - water reaction interface rating, 222
  - workmanship and general requirements with, 212
- stabilizers, 150
- standard test method data quality assurance
  - accuracy, 374
  - ASTM standards, 376
  - bias, 374
  - in determining conformance with product quality specification, 375
  - intermediate conditions, 371
  - metrics, 371–375, 372 (table), 373 (figure)
  - monitoring, 375
  - precision, 371–375, 372 (table), 373 (figure)
  - relative bias, 374–375
  - repeatability conditions, 371
  - reproducibility conditions, 372
- standpipes, 139
- state biofuel mandates, 26
- state implementation plan (SIP)
  - sulfur limits in, 15
  - vapor pressure limits, 8
- static bleed tests, 330, 331 (figure)
- static dissipater additive, aviation fuels with, 91–92, 94
- stationary sample container, 139
- statistical quality control (SQC), 184
- steam cylinder oils, 282
- steam-turbine oils, 280–281
- storage stability, 11–12, 49
  - aviation fuels, 85
  - aviation gasoline, 73–74
  - fuel oils, 203
- stream conditioning, 139
- stream conditions, 139
- styrene-butadiene rubber (SBR), 315–317
- suction sample, 139
- sulfated ash, biodiesel fuel, 64
- sulfur chemiluminescence detector (SCD), 175, 176 (figure), 176 (table)
- sulfur content
  - aviation gasoline, 74
  - base oils in compounds of, 261
  - biodiesel fuel, 64
  - crude oil, 99
  - diesel fuels, 51–52, 52 (table)
  - environmental issues regarding, 192
  - ethanol, 27, 29
  - fuel oils, 198–201, 199 (table)
  - graphite, 247
  - kerosine, 206 (table), 208
  - liquefied petroleum gas, 229–230
  - manufactured carbon, 247
  - methanol, 30–32
  - natural gas, 232
  - nonaviation gas-turbine fuel, 52–53, 52 (table)
  - petroleum coke, 238
  - spark-ignition engine fuel, 10

sulfur gases, gas chromatography in analyses of, 165–166, 166 (table)  
 sump sample, 139  
 supercritical fluid chromatography (SFC)  
   advantage over LC of, 157  
   detectors used with, 158  
   schematic, 157 (figure)  
 surface sample (skim sample), 139  
 synthetic rubber, 315

## T

tank composite sample, 139  
 tank tap sample, 139  
 tapered roller bearings, 328  
 temperature programmable inlet (TPI), 170  
 temporary viscosity loss (TVL), 297–299, 298 (figure)  
 terminology methods  
   graphite, 244  
   manufactured carbon, 244  
   for petroleum coke, 238  
   pitch, 243  
 tertamyl methyl ether (TAME), 16  
 test specimen, 139  
 tetraethyl ethyl-lead (TEL), 70–71, 74, 75, 89  
   tests for, 93  
 thermal conductivity, anode/cathode tests for, 244  
 thermal conductivity detector (TCD), 155  
 thermal oxidation stability, 131  
 thermal stability, 48  
   improver additive, aviation fuels with, 92, 94  
 thermionic nitrogen/phosphorous detectors, 155  
 thief sample. *See* tube sample (thief sample)  
 thin-film oxygen uptake test method (TFOUT), 306, 306 (figure), 307 (figure)  
 time-proportional sample, 139  
 Timken method, 333  
 toluene insolubles, pitch, 243  
 top sample, 139  
 total acid number (TAN)  
   crude oil, 103–104  
 total glycerin method, 66  
 total nitrogen content, crude oil, 104  
 trace elements  
   crude oil, 101–103  
   microwave digestion in analysis of, 103  
 trace metals, aviation fuel sampling affected by, 131  
 true boiling point (TBP)  
   crude oil distillation curves for, 107 (figure)  
 true vapor pressure (TVP), 139  
 tube sample (thief sample), 139  
 turbidity, lubricating oils, 273–274  
 turbocharger oxidation simulation tests, 307–308, 307 (figure)

## U

ullage, 139  
 ultrafast gas chromatogram (UFGC), 173 (figure)  
 ultra-low sulfur diesel fuel (ULSD), 143  
   test methods needed for, 211  
 ultraviolet absorption tests, 255  
 ultraviolet absorptivity, petroleum waxes, 345  
 United States Pharmacopeia (USP), 249  
   bacterial endotoxin requirement in, 252  
 Universal Oil Products (UOP), 101  
 unleaded aviation gasoline, 74–75  
 unleaded fuel, 4  
 upper sample, 139

urea greases, 324  
 U.S. legal requirements  
   additives, 14–15  
   for automotive spark-ignition engine fuel, 14–15  
   fuel blending components, 14–15  
   oxygenated fuel programs, 15–16  
   sulfur regulations, 15  
   volatility regulations, 15

## V

vacuum gas oil  
   crude oil fraction, 109  
   heavy, 106  
   light, 106  
   temperature ranges for, 106  
 vacuum residuum temperature ranges for, 106  
 vacuum ultraviolet (VUV), 155  
 vanadium, crude oils, 101  
 vanadium content  
   diesel fuels, 54  
   nonaviation gas-turbine fuel, 54  
 vapor control valve (VCV), 139  
 vapor-liquid ratio (V/L)  
   spark-ignition engine characteristics with, 7–8  
 vapor lock, 73  
 vapor pressure  
   for aviation gasoline, 73  
   crude oil, 103  
   defined, 139  
   ethanol, 28  
   liquefied petroleum gas, 228  
   methanol, 30, 32  
   spark-ignition engine characteristics with, 6–7  
 virgin naphtha, 158 (table)  
 viscometers  
   high shear rate, 299  
   non-Newtonian oils, 299–300, 300 (figure)  
   Ravenfield Tapered-Plug, 300  
   tapered bearing simulator, 299, 299 (figure)  
   viscometry of modern engine oils, 299, 299 (figure)  
 viscosity  
   automotive engine oils, 294–303, 295 (figure), 296 (figure), 298 (figure), 299 (figure), 300 (figure), 302 (figure)  
   aviation fuels, 82  
   crude oil, 100–101  
   defined, 295  
   diesel fuels, 46–47  
   dynamic, 268–269, 296  
   fuel oils, 197–198  
   Gelation Index curves, 302 (figure)  
   gelation of engine oils at low temperatures, 300–303, 302 (figure)  
   kinematic, 269–270, 295–296  
   low temperature engine startability with, 296  
   lubricating greases, 327–328  
   lubricating oils, 268–270, 270 (table)  
   meaningful measurement, 295–296  
   Newtonian response, 295 (figure)  
   Newton's early equation on, 295  
   nonaviation gas-turbine fuel, 46–47  
   petroleum waxes, 343–344  
   pitch, 243  
   rubber oils, 318  
   viscometry of modern engine oils, 299, 299 (figure)  
   for white mineral oils, 255  
 viscosity index, lubricating oils, 270

viscosity index improvers  
 nature of, 296  
 non-Newtonian behavior of, 297–299, 298 (figure)  
 oil-solubilized, 296 (figure)  
 permanent viscosity loss of, 297  
 solubility response of, 296 (figure)  
 temporary viscosity loss of, 297

viscosity modifiers, 293–294

volatility  
 automotive engine oils, 311  
 aviation fuels, 83  
 aviation gasoline, 71–73  
 diesel fuels, 46  
 lubricating oils, 274  
 nonaviation gas-turbine fuel, 46  
 pitch, 243  
 sampling of fuels for measurement of, 132

volatility properties  
 distillation, 7  
 driveability index, 7  
 performance, 8–9  
 spark-ignition engine characteristics with, 6–9  
 vapor-liquid ratio, 7–8  
 vapor pressure, 6–7

volume regulator sampler, 139

volumetric composite sample, 139

**W**

wall-coated open tubular (WCOT), 155

water content  
 ASTM methods for, 223  
 butanol, 32–33  
 crude oil, 100  
 ethanol, 27, 29  
 fuel oils, 196–197, 199 (table)  
 liquefied petroleum gas, 230  
 liquid fuels, 212  
 methanol, 32

water reaction  
 aviation gasoline, 74  
 interface rating, 222

water separation characteristics, aviation fuel sampling affected by, 131

water spray-off, 336, 336 (figure)

water tolerance, 13

water washout, 335–336

wax precipitation point, 255

wear, 333–335  
 anti-wear agents, 294, 309  
 automotive engine oils, 308–311, 309 (figure)  
 four-ball test, 309, 309 (figure)  
 graphite and manufactured carbon, 246–247  
 pin and V-block test method, 310–311, 310 (figure)  
 preventive characteristics, 334

wheel bearings  
 grease life, 333  
 leakage from, 331, 331 (figure)

white mineral oils  
 acidity test for, 252  
 aniline point of, 252  
 API gravity for, 253  
 ASTM/IP standards, 256  
 bacterial endotoxin with, 252  
 cloud point with, 252  
 color, 252  
 density for, 253  
 dielectric breakdown voltage of, 252–253  
 distillation range for, 253  
 fire point for, 253  
 flash point for, 253  
 fluorescence with, 253  
 heavy metals with, 253  
 identification methods for, 253–254  
 manufacture, 249  
 odor, 254  
 peroxide value, 254  
 pharmaceutical and food grades of, 250–251 (table)  
 pour point for, 254  
 purity guardianship, 249–252, 250–251 (table)  
 pyrogen test, 254  
 quality assessment, 252  
 readily carbonizable substances, 254  
 refractive index for, 254  
 smoke point for, 254  
 solid paraffin test, 255  
 specific gravity for, 253  
 sterility with, 254  
 subvisible particles for, 254  
 sulfur compounds, 254–255  
 taste, 254  
 tests for, 252–255  
 transparency of, 252  
 ultraviolet absorption tests, 255  
 unsulfonated residue with, 255  
 viscosity for, 255  
 visible particles, 255  
 wax precipitation point, 255

wick-fed blue-flame-type burner, 195

wick-fed yellow-flame-type burner, 194

workmanship  
 butanol, 33  
 ethanol, 28–30  
 methanol, 31, 32  
 spark-ignition engine fuel, 12–13  
 stability and cleanliness of liquid fuels with, 212

**X**

x-ray fluorescence, lubricating oils in analysis by, 271  
 x-ray fluorescence spectrometry (XRF), 363

**Z**

zinc content, crude oils, 102  
 zone sample, 140