

Subject Index

A

- Acoustic emissions
 - silicon carbide whisker/aluminum composite, 133–139
- Adiabatic shear (*see* Shear testing, adiabatic)
- Aircraft specifications
 - metal matrix composites, 197–204
- Alpha-alumina fiber, 31–46, 38–48
- Aluminum alloy matrix (*see also* Metal matrix composites), 121–142
 - billets, 305–316, 376–380
 - cylinders, 277–284, 305–316
 - plates, 218–221, 382
 - tubes, 222, 396–407
- Analytical models
 - conductivity, 67–72
 - high-temperature, multilayered fiber composites, 159–176, 177–196
 - short-fiber reinforced composites, 143–158
 - transverse tensile behavior, 416–424
 - work of fracture, 425–428
- Anisotropy, 63, 73, 80, 93
- ASTM Standards
 - D 790, 355
 - D 3039, 201, 322, 347
 - D 3410, 201, 319
 - D 3518, 201
 - E 8, 347
 - E 9, 198
 - E 127, 377
 - E 238, 198
 - E 399, 277, 278, 280–281
 - E 466, 198
- Axial testing
 - FP fiber/magnesium composite, 321, 323–328
 - shear modulus determination, 261–265

B

- Bauschinger effect, 307, 308, 310–315
- Billets
 - mechanical behavior, 305–316
 - ultrasonic inspection of, 376–380

- Blanking, static/dynamic
 - 3-D braided reinforced versus unreinforced aluminum-lithium composite, 48–59
- Bond joints (*see* Joints)
- Boron fibers, 285–303, 336–345, 409–430
- Braided materials, 31–46, 48–59
- Brooming, 325
- Bursting test
 - graphite, aluminum tubing, 400

C

- Charpy-type specimen
 - silicon carbide whisker/aluminum composite, 278–284
- COD (*see* Crack-opening displacement)
- Color indicators
 - computed tomography, 233
- Compliance-calibration curves
 - boron/aluminum composite, 288–293
- Composite materials (*see* Fibers; Metal matrix composites; Particulates, silicon carbide; Polymeric matrix composites; Whiskers, silicon carbide)
- Compression testing
 - alpha-allumina fiber/aluminum-lithium composite, 32, 34–37
 - FP fiber/magnesium composite, 319–328
 - graphite/aluminum composite, 20–22, 26–27
 - graphite/aluminum composite tubing, 403, 405–406
 - graphite/magnesium composite, 20–22, 26–27
 - silicon carbide whisker/aluminum composite, 147–148
 - silicon carbide whisker/aluminum composite cylinders, 310–311
- Computed tomography, 227, 230–232, 234
- Computer programs
 - for flexural testing, 273–274
- Copper matrix, 336–345, 347–375
- Crack-opening displacement (COD)
 - boron/aluminum composite, 293, 296–301

- Crack propagation
 - boron/aluminum composite, 278–284, 285–303
 - graphite/aluminum composite, 99–100
- Cylinders
 - compression testing
 - FP fiber/magnesium composite, 319–328
 - silicon carbide whisker/aluminum composite, 310–311
 - fracture toughness testing
 - silicon carbide whisker/aluminum composite, 277–284, 305–316
 - unreinforced versus reinforced aluminum composite, 277–284

D

- Damping (*see* Internal friction)
- Deformation (*see also* Dislocations)
 - boron/aluminum composite, 285–303
 - FP fiber/magnesium composite, 323–328
- Department of Defense (DOD)
 - metal matrix composite specifications, 197–204
- Dilatometer, laser interferometric, 248–258, 287, 290–293
- Dimensional stability
 - graphite/aluminum composite, 248, 254–257
 - graphite/magnesium composite, 248, 257–258
- Dislocations (*see also* Deformation)
 - silicon carbide whisker/aluminum composite, 210–214
- Dynamic modulus (*see also* Young's modulus)
 - silicon carbide particulate/aluminum composite, 208–210
 - silicon carbide whisker/aluminum composite, 208–210

E

- Elasticity testing (*see also* Strength/stiffness)
 - boron/aluminum composite, 287–293
 - graphite/aluminum composite, 222–225
 - silicon carbide particulate/aluminum composite, 207–215, 384, 390
 - silicon carbide whisker/aluminum composite, 81–88, 207–215, 384, 390
- Electrical resistivity
 - measurement of, 71–72
- Electromagnetic acoustic transducers (EMATs), 216–225

- Electron microscopy, scanning
 - boron fiber/aluminum composite, 293–296, 414–421, 425–426
 - boron fibers, 420–421
 - 3D-braided/aluminum-lithium composite, 57–64
 - silicon carbide whisker/aluminum composite, 139–142, 384, 385, 391–393
- Extensometers, 366, 374–375
- Extrusions
 - ultrasonic inspection of, 380

F

- Failure mechanisms and processes
 - electron microscopy of, 293–296
 - finite analysis of, 95–102
 - metallographic observation of, 323–328
 - television observation of, 293
- Failure modes
 - silicon carbide whisker/aluminum composite, 123, 139–142, 370–372
 - unidirectional ply composites, 165
- Fatigue, thermal-mechanical testing
 - composite specimens, test apparatus, 4–6
- Fatigue precracking, 279–284
- Federal Aviation Administration (FAA)
 - metal matrix composite specifications, 197–204
- Fibers (*see also* Particulates, silicon carbide; Whiskers, silicon carbide)
 - alumina, 31–46, 48–58, 227–247, 319–328
 - boron, 278–284, 285–303, 409–430
 - electron microscopy of, 420–421
 - transverse tension testing of, 413–415
 - failure mechanisms and processes, 293–296
 - FP, 31–46, 48–58, 319–328
 - graphite, 19–30, 93–102, 107–120, 216–225, 248, 254–258, 336–345, 347–355, 396–405
 - single filament
 - dimensional scaling, 104–120
 - size effect, 104–120
 - statistical strength, 104–120
 - tungsten, 3–17
- Filaments, testing of, 104–120
- Finite element analysis
 - high-temperature, multilayered fiber composites, 159–176, 177–196
 - micromechanical properties, 95, 97
- Fixturing, 321
- Flexural testing
 - ASTM Standard D 790, 355

computer programs, 273–274
 shear modulus, 266–272
 silicon carbide whisker/aluminum composite, 359–362, 384, 390
 FP fiber, 31–46, 48–58, 319–328
 Fracture, work of
 boron fiber/aluminum composite, 415–416, 425–429
 Fracture behavior (*see also* Failure mechanisms and processes; Failure modes) resistance
 silicon carbide whisker/aluminum composite, 277–284, 305–316
 unreinforced versus reinforced aluminum alloy cylinders, 277–284, 280–281
 toughness testing, 277–316
 ASTM Standard E 399, 277, 278, 280–281
 braided composite, 33, 38–40
 Charpy-type specimen, 278–284
 fatigue precracked specimens, 278–284
 Mode I and Mode II, 315–316

G

Graphite fibers, testing of in matrix
 biaxial loading, 100–102
 bursting test, 400, 406
 compressive properties, 20–22, 26–27, 403, 405–406
 crack propagation, 99–100
 dimensional scaling, 104–120
 elasticity testing, 222–225, 403–405
 failure strain rate, 339
 laser absorptivity, 22–26, 27–30
 micromechanical analysis, 95–102
 rapid heating testing, 329–345, 346–375
 shear testing, 99–100, 403, 405
 size effect, 104–120
 statistical strength, 104–120
 tensile testing, 198, 116–117, 118, 339–345, 353
 thermal expansion measurements, 248, 254–258
 torsion test, 401, 406
 ultrasonic evaluation, 216–225
 Weibull distribution, 105–107
 Guidelines, military
 for metal matrix composites, 197–204

H

Heat capacity
 measurement methods, 75

Heating, rapid
 effect on tensile testing, 336–345, 346–375
 equipment for, 330–335, 350
 quartz lamps, 350, 365
 Hot working
 silicon carbide/aluminum composite
 mechanical properties, 385, 386–390
 microscopic examination, 385, 391–393
 Hydrostatic strain
 silicon carbide whisker/aluminum composite, 278–279

I

Impact loads (*See* Loading, impact)
 Impact testing
 drop-weight
 3D-braided/aluminum-lithium composite, 33, 40–42
 Interface reaction
 fiber/matrix, 409, 412
 Internal friction
 silicon carbide whisker/aluminum composite, 210–215

J

Joints
 thermal-mechanical testing, 9–17

K

Kink band formation, 323–324

L

Laminates (*see* Metal matrix composites)
 Laser absorptivity
 graphite/aluminum composite, 22–26, 27–30
 graphite/magnesium composite, 22–26, 27–30
 Laser interferometric dilatometer, 248–258, 287, 290–293
 Lithium matrix, 31–46, 48–64
 Load-displacement curves
 boron fiber/aluminum composite
 notched specimens, 296–302
 room versus elevated temperature, 296–302
 Loading
 axial
 FP fiber/magnesium composite, 323–328
 shear modulus determination, 261–265

Loading (*Continued*)

- biaxial
 - graphite fiber/epoxy composite, 100–102
- cyclic
 - computer controlled, 9–17
- impact
 - 3D-braided aluminum/lithium composite, 33, 40–41
- 3-point bending
 - unreinforced versus reinforced aluminum composite cylinders, 278–284
- shear
 - FP fiber/magnesium composite, 323–328, 366
 - graphite/aluminum composite, 99–100
- tensile
 - aluminum alloy cylinder, 278–279
 - silicon carbide whisker/aluminum composite, 278–279, 307–310
- transverse tension
 - graphite/aluminum composite, 98

M

- Magnesium matrix, 19–30, 227–248, 257–258, 319–328
- Mechanical testing (*see* Blanking; Bursting test; Compression testing; Crack-opening displacement; Crack propagation; Damping; Deformation; Dislocation; Elasticity testing; Fatigue, thermomechanical; Flexural testing; Fracture behavior; Impact testing; Internal friction; Micromechanical testing; Microstresses, thermomechanical; Minimechanical testing; Pin-bearing tests; Plasticity; Shear testing; Strain hardening; Strain rate; Strength, transverse; Strength/stiffness; Stress-strain; Tensile testing; Torsion testing)
- Metal Matrix Composite Information Analysis Center (MMCIAC), 346
- Metal matrix composites
 - alpha-alumina fiber/alumina-lithium, 31–46, 48–59
 - alpha-alumina fiber/magnesium, 319–328
 - aluminum-lithium matrix, 31–46, 48–59
 - boron fiber/aluminum, 285–303, 409–430
 - borsic/aluminum, 336–345
 - 3D-braided, 31–46, 48–59
 - FP fiber/aluminum, 227–247
 - FP fiber/aluminum-lithium, 31–46, 48–59
 - FP fiber/magnesium, 227–247, 319–328

- graphite/aluminum, 19–30, 93–102, 107–120, 216–225, 248, 254–257, 336–345, 347–375
- graphite/copper, 336–345, 347–375
- graphite/magnesium, 19–30
- high-temperature, 159–176, 177–196
- honeycomb, 66
- particulates (*see* Particulates, silicon carbide)
- silicon carbide particulate/aluminum, 346–348, 350–375, 376–382, 383–395
- silicon carbide whisker/aluminum, 79–88, 121–141, 143–158, 207–225, 277–284, 305–316, 336–345, 346–348, 350–375, 376–382, 383–395
- whiskers (*see* Whiskers, silicon carbide)
- Micromechanical analysis
 - graphite/aluminum composite, 95–102
 - high-temperature, multilayered fiber composites, 159–176
- Microstresses, thermomechanical
 - equations for, 166–168, 180
 - applications, 170–172, 180–196
- Microstructural analysis (*see* Electron microscopy, scanning)
- Military handbooks
 - MIL-HBK-5, 197–200, 202–204
 - ASTM Standards E 8, 198
 - ASTM Standards E 9, 198
 - ASTM Standards E 238, 198
 - ASTM Standards E 466, 198
 - MIL-HBK-17, 201–204
 - ASTM Standard D 3039, 201
 - ASTM Standard D 3410, 201
 - ASTM Standard D 3518, 201
- Minimechanical analysis
 - silicon carbide whisker/aluminum composite, 121–142, 143–158
- Missile aerodynamic heating, 346

N

- Nondestructive evaluation (*see also* Electron microscopy, scanning)
 - acoustic emissions, 121–142
 - computed tomography, 227, 230–232, 234
 - electromagnetic acoustic transducers (EMATs), 216–225
 - laser absorptivity, 19–30
 - laser interferometer, 248–258, 287, 290–293
 - television, closed-circuit, 93
 - ultrasound, 208–209, 216–225, 232–234, 238–247, 376–382

- Notch acuity effects
 - unreinforced versus reinforced aluminum composite cylinders, 278–284
- Notched specimens (*see also* Crack propagation)
 - boron fiber/aluminum composite, 278–284, 285–303
 - graphite fiber/aluminum composite, 99–100

O

- Off-axis testing
 - for shear modulus, 261–265

P

- Particulates, silicon carbide
 - dynamic modulus, 209–210
 - elasticity testing, 384, 390
 - flexural strength, 359–362, 384
 - fracture strength, 339
 - pin-bearing tests, 362–364
 - tensile strength, 339, 351
 - ultrasonic inspection, 376–382
- Piezoelectric ultrasonic composite oscillator technique (PUCOT), 208–209
- Pin-bearing tests
 - silicon carbide particulates/aluminum composite, 362–364
 - silicon carbide whiskers/aluminum composite, 362–364
- Plasticity testing
 - silicon carbide whisker/aluminum composite, 153–156
- Plates
 - graphite/aluminum composite, 218–221
 - silicon carbide whisker/aluminum composite
 - ultrasonic inspection of, 382
- 3-Point bending tests
 - boron fiber/aluminum composite, 411–412, 415–416
- Polymeric matrix composites
 - graphite/epoxy, 107–120
- Pressure derivative
 - elastic constants, 84–85
- Pultruded tubing, 396–407

R

- Root attachments
 - bond strength testing, 10–17

S

- SEM (*see* Electron microscopy, scanning)
- Shape factor
 - compression testing
 - FP fiber/magnesium composite, 319–328
- Shear testing
 - adiabatic shear stability
 - 3D-braided unreinforced versus reinforced aluminum-lithium composite, 48–59
 - 3D-braided/aluminum-lithium composite, 32, 34–37, 48–59
 - metal matrix composites, 259–272
 - modules, composites
 - review, 259–261
 - turbine airfoils, 189
 - yield stress
 - boron fiber/aluminum composite, 301–302
- Short-fiber composites (*see* Particulates, silicon carbide; Whiskers, silicon carbide)
- Silicon carbide whiskers (*see* Whiskers, silicon carbide)
- Specifications
 - Department of Defense, 197–204
 - Federal Aviation Administration, 197–204
- Specimens, types of
 - Bauschinger effect, 307–308
 - Charpy, 278–284
 - fatigue precracked, 279–284
 - notched, 278–284
- Statistical data
 - for metal matrix composites, 197–204
- Strain hardening
 - silicon carbide whisker/aluminum composite, 123–125, 153
- Strain rate (*see also* Stress-strain curves)
 - silicon carbide whisker/aluminum composite cylinders, 306–316
- Strength, transverse
 - boron fiber/aluminum composites, 410–411, 416–424
 - metal matrix composites, 409
- Strength/stiffness (*see also* Elasticity)
 - silicon carbide whisker/aluminum composite, 123–125
- Stress-strain curves (*see also* Strain rate)
 - silicon carbide particulate/aluminum composite, 356–358
 - silicon carbide whisker/aluminum composite, 125–133, 148–156, 356–358
 - transverse tension tests, 422–424

Structural analysis

- nonlinear composites, 178, 180, 182–183
- turbine airfoils, 178, 180, 182–183

T

Television, closed-circuit

- deformation, observation of, 293

Temperature, elevated (*see also* Temperature, room; Thermal properties)

- compressive testing, 26, 27
- deformation effect, 288–302
- elasticity testing, 207, 208, 209–210, 225, 288–293, 345, 387–390
- expansion effect, 96, 253–258
- laser absorptivity testing, 27–29
- load-displacement curves, 296–302
- tensile testing, 96, 336–345, 346–375, 351, 369, 372, 387–390

Temperature, room (*see also* Temperature, elevated; Thermal properties)

- elasticity testing, 287, 345
- flexural testing, 359–362, 390
- load-displacement curves, 296–302
- pin-bearing tests, 362–364
- tensile testing, 364–375, 390

Tensile testing, 336–375

- boron fiber/aluminum composite, 409–430
 - longitudinal strength, 411, 412
 - transverse strength, 411, 412, 416–424
- 3D-braided/aluminum-lithium composite, 32, 34–37
- graphite/aluminum composite tubing, 397–400, 403, 403–405
- graphite fiber/aluminum composite, 98–99, 119, 347–375
- graphite fiber/epoxy composite, 119–120
- graphite filament, 118, 120
- silicon carbide particulate/aluminum composite, 347–375, 384, 385, 387–388, 390
- silicon carbide whisker/aluminum composite, 98, 122–133, 147–153, 278–279, 347–375, 351, 352, 367, 384, 385, 387–388, 390
- silicon carbide whisker/aluminum composite cylinders, 306–310

Test coupons

- continuously reinforced, 348–350
- discontinuously reinforced, 347–348
- ASTM Standard E 8, 347

Thermal properties (*see also* Temperature, elevated; Temperature, room)

- conductivity
- analytical models, 67–72

diffusivity

- honeycomb matrix, 73–75

expansion

- graphite/aluminum composite, 248, 254–257
- graphite/magnesium composite, 248, 257–258
- metal matrix fiber-reinforced composites, 76

fatigue testing

- bond joints, 9–17
- composite specimens, 4–9

high-temperature metal matrix composites, 162, 165, 177–196

stress testing

- measurement methods, 67–76

tensile testing

- boron fiber/aluminum composite, 409, 411–430
- boron fibers, 409, 413–430
- thermoviscoplastic behavior
- high-temperature metal matrix composites, 177–196
- turbine airfoil, 180–196

Through-transmission, 231–234

Torsion testing

- graphite fiber/aluminum tubing, 401
- silicon carbide whisker/aluminum cylinders, 310–311

Tubes, composite

- graphite fiber/aluminum, 222, 396–407
- pultruded, 396–407
- tungsten fiber reinforced, 3, 9–17

Tungsten

- fiber reinforcement, 3, 9–17

Turbine airfoils

- microstress analysis, 170–173
- thermoviscoplastic nonlinear constitutive relationships, 180–196

U

Ultrasonic inspection, 208–209, 216–225, 232–234, 238–247, 376–382

ASTM Standard E 127, 377

Uniaxial stresses

- high-temperature metal matrix composites, 166

W

Weibull distribution, 105–107, 199, 411

Whiskers, silicon carbide (*see also* Particulates, silicon carbide)

acoustic emissions, 133–139
 adiabatic elastic constants, 79–88
 Bauschinger effect, 307–308, 310–316
 compression testing, 147–148, 310–311
 dislocations, 210–214
 dynamic modulus, 208–210
 elasticity, 81–88, 207–215, 384, 390
 electron microscopy of, 139–142, 384, 385, 391–393
 failure modes, 123, 139–142, 370–372
 failure strength, 339, 345
 flexural strength, 359–362, 384, 390
 fracture toughness testing, 277–284, 305–316
 hydrostatic strain, 278–279
 minimechanical analysis, 121–142, 143–158
 pin-bearing tests, 362–364
 plasticity, 153–156

strain rate, 121–142, 305–316
 strength/stiffness, 123–128
 stress-strain behavior, 125–133, 148–156, 356–358
 tensile testing, 98, 122–133, 147–153, 278–279, 306–310, 347–375, 385, 387–388, 390
 ultrasonic inspection, 376–382

Y

Young's modulus (*see also* Dynamic modulus)
 shear modulus determination, 261, 266–272
 silicon carbide particulate/aluminum composite, 386–390
 silicon carbide whisker/aluminum composite, 208–210, 386–389, 390