

Subject Index

A

- Adhesion, 90, 122, 124–125 (fig), 147.
 - See also* Bonding
 - ductile polymers, 392
 - glass predicted work of adhesion, 174 (table)
 - graphite predicted work of adhesion, 173 (table)
 - matrix adhesion shear, 179
 - predicted work of adhesion, 175
 - silane treated glass, 176
 - polymer wetting, 166
 - surface tension, equations, 167–168
 - work of adhesion between filaments, 172
- Adhesion, fiber-resin interface, 2
- Adhesion of thermoplastics to carbon fiber, 148
- Adhesion strength between fiber and matrix
 - increased by addition of silane, 176
- Adhesive bond fracture, 147
 - fracture toughness measurements, 211 (fig)
- Adhesive bonded joints
 - fracture mechanics, 295
- Adhesive failure, 146
- Adhesive prepreg, 152, 157
- Adhesive test method for delamination resistance, 16
- Adhesives, 305–307, 311
 - as coatings to improve toughness, 151, 157
 - tests for measuring in situ toughness, 296
 - cracked lap shear specimen, 298
 - double cantilever beam specimen, 297
- Advanced composites, 62, 65–68
- Aerospace composites, 61
- Aircraft composite structures
 - to assess impact resistance and damage tolerance, 437
- Aircraft design
 - carbon fiber composites, 414
- Aircraft structural applications
 - composite structures
 - correlation between damage and impact, 437
 - design studies, 32
 - fuselage components, 21
 - of composite materials, 12
 - of epoxy matrix composites
 - design related structural performance, 414
- Aluminum versus composites, 10, 32
- Amorphous thermoplastics, 338, 340
 - polysulphone (PSF), 329
- Aramid fibers, 180
- Arc, radius of curvature, 330 (fig)
- Aromatic polymer composite (APC), panel details, 360 (table)
- ASTM Standards
 - E-399, 80, 93 (discussion), 97, 99, 121, 404
 - D-638, 99, 142
 - D-695, 407, 416
 - D-785, 288
 - D-790, 62, 320, 403, 420
 - E-813, 99

- D-882, 320, 344
- D-1708, 170
- D-2344, 63, 321, 407
- D-3039, 320, 407, 423
- D-3410, 321
- ASTM special technical publications
 - STP 873 (1985), iv
 - STP 896 (1985), iv
 - STP 907 (1986), iv

B

- Bending stiffness
 - for flutter considerations, 12
 - weight comparison
 - advanced technology wing, 11 (fig)
- Bonded joints, 298, 301, 305
 - fracture mechanics, 295
- Bonding, 91, 112. *See also* Adhesion, Fiber bonding
 - epoxy composites versus thermoplastics, 88
- Breakage, 91
- Bridging, 91
- Brittle cleavage fracture, 122
- Brittle epoxy fracture resistance, 290
- Brittle fracture, 182
- Brittle materials, tests, 24
- Brittle polymers, 89
- Brittle resins
 - crack-tip deformation, 91
 - impact results, 38, 420
 - toughness, 96, 116
- Brittle systems
 - interlaminar fracture, 302 (fig)
- Broken fiber, 186, 189
- Buckling, 40, 44 (fig)
 - coated fibers, 161
 - stress calculations, 57–60 (Appendix A) (fig)
 - sublaminates more susceptible to, 43, 44 (fig), 45
- Buckling stress, critical, 45
 - equations, 57–60 (Appendix A, fig)

C

- Carbon fiber reinforced composite
 - in aircraft design, 414
 - PEEK, 359
 - transverse impact damage, 419
- Carbon-fiber reinforced polymers (CFRP), 320
 - fractography of, 131–132
- CFRP. *See* Carbon-fiber reinforced composites
- Chemoviscosity
 - advanced matrix resins for aircraft, 438, 439 (fig), 447
 - model, 451–452
 - equations, 440
- Coated fiber composites
 - prepregs, 157, 158 (table), 160 (table)
- Coated fiber prepreg, 152, 153 (fig)
- Coated fibers, 157
 - compressive strength, 159, 163 (table), 164 (figs)
 - deformation, 159
 - to increase toughness, 151
- Composite characterization, 78 (table)
- Composite deformation zone, 90
- Composite epoxy resins, 63
- Composite fiber volume fractions, 78 (table)
- Composite fracture experiments, 82
- Composite laminates
 - properties, 46 (Table)
- Composite materials, 25
 - aircraft structural applications, 398
 - to primary wing structure, 10, 11 (fig), 21–22
 - carbon fiber epoxy laminates, 239
 - fracture mechanics, 295
 - glass fibers, 166, 176
 - graphite, 166, 173
 - graphite-epoxy composites, 116, 201, 202 (table), 207
 - advantages for aircraft materials, 398

- graphite/thermoplastic, 279
- high temperature graphite/epoxy, 279
- rubber-toughened graphite/epoxy, 279
- graphite-epoxy laminates, 96–97, 224 structure, 399 (fig)
- interlaminar cracking, 260
- semi-interpenetrating polymer network, 454
 - chemical resistance, 461 (table)
 - mechanical properties, 458, 459 (table)
- laminates under fatigue loading, 223–225, 230, 235
- postimpact compressive behavior, 30–32
- quasi-isotropic laminates
 - impact testing, 27–29 (figs)
- semi-interpenetrating polymer network, 453
- tensile strain-to-failure comparisons, 25 (table)
- tests for measuring in situ toughness, 296
- to reduce structural weight, 10
- toughened resin graphite, 23
- Composite structures
 - compared to aluminum alloys, 22
 - material systems for commercial transports, 21
- Composite toughness
 - critical characteristics for improvement, 419
 - versus neat resin toughness, 386
- Composites, 76, 125, 148
 - cause for low toughness in, 388
 - fracture mechanics, 295
 - interlaminar fracture toughness, 301, 304 (figs), 305, 313
 - PET/graphite, DSC experiments, 335
 - Ryton-PPS, 320
 - semi-interpenetrating polymer network (SIPN), 454
 - chemical resistance, 461 (table)
 - mechanical properties, 458, 459 (table)
 - thermoplastic matrices, 329, 340
- Compression, 363, 373, 378
- Compressive behavior
 - effect of resin properties on, 38
 - carbon fiber/PEEK composites, 362
 - postimpact, 416
 - tough resins versus untoughened resin composites, 30
 - stress-strain curves, 43, 44 (fig)
- Compressive deformation, 363, 373, 378
- Compressive failure, 31 (fig), 40 (fig), 45
 - deformation, 374–375 (figs, 376, 378)
 - initiated by fiber kinking, 56
 - interlayered laminate, 429
 - quasi-isotropic laminates versus unidirectional laminates, 56
 - susceptibility to impact damage, 38
- Compressive loading, 376, 378, 417
 - ultrasonic C-scans after low energy impact, 377
- Compressive properties
 - of quasi-isotropic laminates, 46 (table)
 - of graphite fiber plastic composites, 163 (table)
- Compressive strength and behavior
 - after impact, 17
 - versus resin flexural strain, 64–65 (figs)
 - and interlaminar shear strength, 419
 - effect of impact energy, 56
 - effect of resin tensile modulus, 47
 - effects of fiber diameter, 15 (fig)
 - effects of ply thickness, 16 (fig)
 - effects of resin properties, 38
 - environmental effects, 16 (fig)
 - of new generation epoxy composites, 413
 - of graphite fiber plastic composites,

- 162–164 (figs)
- of quasi-isotropic graphite/epoxy laminates, 56
- overview, 2
- poly(etheretherketone) (PEEK), 17
- post impact, 30
- tests, 30, 31 (figs)
- toughness evaluation, 18 (fig)
- Compressive strength-modulus comparison, 14 (fig)
- Crack density with delamination size, 228 (figs)
- Crack growth, 84, 87, 97, 105–106
 - in brittle materials, 234
 - in epoxy resin fracture, 142
 - in a metal, resistance to, under static loading, 224
 - interlaminar fatigue, 276, 294 (discussion)
 - load deflection curves, 265, 266–269 (figs)
 - Mode II graphite/epoxy fatigue, 276
 - rates, 278, 282–287 (figs)
 - rate, 238 (table)
 - measurement, 263, 276
 - velocity, 262, 270
- Crack propagation, 65, 82, 88, 147–148
 - double cantilever beam test, 363, 365
 - in aromatic carbon fiber, 361
 - in interfacial debonding, 104
- Crack testing, 117
- Crack-tip deformation, 90
- Cracked lap shear (CLS) specimen, 297 (fig), 310–312
 - finite element analysis of, 299
 - for testing adhesively bonded metallic joints, 298
 - toughness tests data, 303 (table), 308 (table)
- Cracking, 38, 161
- Crazing
 - toughening mechanism in plastics, 388, 389, 393
- Critical-failure mode
 - delamination after impact, 16
- Critical length experiments
 - glass filament, 170
- Critical strain energy release rates, 102 (table)
 - equations, 100
 - for crack velocity, 273 (figs), 274
 - for delamination fracture
 - loading rates, effects, 271, 272 (table)
 - graphite/epoxy composites
 - cyclic fatigue, 251–255 (figs)
- Cross-link density, 116
 - efficacy in enhancing
 - composite delamination fracture toughness, 109
 - neat resin fracture toughness, 108, 113
- Cross-linked thermoset, 140, 454
- Cross-plyed laminates
 - preliminary tests, 12, 25
- Cross-ply composite strip experiments, 330
- Crystal morphology, PEEK, 356
- Crystallinity, 321, 331, 339
 - mechanical properties, PEEK, 343, 344–347 (figs, tables) 355–356
- Crystallization, 322, 335, 340
 - matrix shrinkage during, 333
 - temperature, 332, 348
- Crystallization time
 - versus temperature, 346 (fig), 356
- Cure behavior
 - dicyanate SIPN, 456, 457 (fig)
 - prediction of, use of Lockheed Process Model, 438
- Cure cycle conditions, 17, 19 (fig)
- Cure cycle
 - for advanced matrix resins in aircraft applications, 446 (figs)
 - polymer morphology, SIPN, 458
 - viscosity range, 19 (fig)
- Cure enthalpy. *See* Enthalpy
- Cure parameters

- advanced matrix resins for aircraft applications, 440, 445–447
- Cure process modeling, 447, 451–452
- Cyclic fatigue
 - graphite/epoxy composites, 251–255 (figs)
 - tests, 244
- Cyclic loading, 278
 - delamination growth under, 276

D

- Damage. *See* Impact damage
- Damage tolerance, 362, 373
 - in aircraft applications
 - advanced matrix resin for, 438
 - semi-interpenetrating polymer network (SIPN), 454
 - toughened resin systems, 445
- Deformation/damage, 147, 148, 270
 - carbon fiber/PEEK composites, 362
 - overview, 3
- Delamination, 43, 210, 212
 - after impact, 16, 359
 - after low-energy impact, 367
 - brittle systems
 - mixed-mode interlaminar fracture toughness, 301
 - failure criteria, 216 (fig), 295
 - fatigue testing, 257 (figs), 280
 - fiber kinking, 43, 48, 56
 - fracture energies, 280
 - fracture toughness
 - characterized by stress intensity, 260
 - graphite-epoxy composites, 96, 116, 224, 255–256 (figs)
 - in fiber-reinforced composites, 75
 - onset and growth of, 223, 230 (fig)
 - stiffness reduction mechanisms, Appendix I, 240
- Delamination behavior, 359
 - under compressive loading, 376, 378
- Delamination cracks, 161, 260
- Delamination fracture, 112
 - composites compared to bonded adhesives, 295
 - in scanning electron microscope, 101, 122
 - toughness, 128
 - tests, 97, 99
- Delamination growth rate, 236–237 (figs)
 - under cyclic loading, 276
- Delamination observation
 - in scanning electron microscope, 103
 - damage zone size, 108 (table)
 - using zinc iodide enhanced radiography, 224
- Delamination of brittle matrix resins, 38, 40
- Delamination resistance, 147, 151, 220
 - 238 (table)
 - after impact, 379
 - strain energy release rate
 - under fatigue loading, 231, 232 (fig)
 - tests, 16, 18 (fig)
- Delamination tests, 101, 106, 206. *See also* Edge delamination test
 - midplane compared to mixed mode delaminations, 214
 - nomenclature, 200
- Delamination toughness, 112, 129
- Design criteria
 - applied to commercial aircraft, 12, 16 (figs)
 - for improved toughness of graphite fiber composites, 151
 - stiffness requirements, 10
 - strength of toughness composites, 23
 - test conditions, 24 (fig)
 - to reduce structural weight, 10
- Design requirements processing, 15, 13–16 (figs)
- Diaminodiphenylsulfone, 142
- Dicyanate network (SIPN), 455

- /copolyester carbonate
 - chemical resistance, 461 (table)
 - photomicrograph of, 460 (fig)
 - TEM of, 458 (fig)
 - cross-link density, 454, 455 (fig)
 - Differential scanning calorimetry, 335 (fig), 349 (fig)
 - Diglycidyl ether of bisphenol A (DGEBA) epoxies
 - fracture toughness and yield strength, 385
 - Dilatation
 - and shear strain energies, 392 (fig)
 - effected by moisture and heat, 300–301
 - Double cantilever beam method
 - for coated fiber composites, 162
 - Double cantilever beam (DCB) specimens, 132, 261
 - interlaminar mixed-mode fracture, 297, 302, 304
 - load introduction attachments, 265 (fig)
 - measurement of Mode I delamination fracture toughness, 262
 - Mode I DCB for testing adhesives and interlaminar toughness of composites, 297 (fig) -
 - Double cantilever beam test, 359, 366 (table)
 - crack propagation test methods,
 - for delamination resistance, 16, 75, 81, 261
 - for toughness measurements, 117
 - experimental procedure
 - elastomer-modified epoxy resin matrix, 264
 - PPS, 320
 - PEEK, 363 (fig)
 - scanning electron micrographs, 364 (fig)
 - Double cantilever peel test
 - for delamination resistance, 16, 17 (fig)
 - Drapability, 20
 - of bi-woven preimpregnated material, 21
 - of woven cloth, test for 21 (fig)
 - Drapability process requirements, 17
 - Dual matrix epoxy resins, 62, 70, 71
 - Ductile fracture, 391
 - neat resin properties, 389
 - Ductile neat resin
 - toughening mechanisms, 388
 - Ductile polymers
 - can be toughened by very small particles, 394
 - orientation hardening, 392, 394
 - Ductile resin failure, 122
 - Ductility
 - processes leading to, 389
 - Durability of tough composites, 2
 - Dynamic mechanical analysis
 - thermoplastic matrices, 338 (fig)
 - Dynamic viscosity profile, 19
- E**
- Edge delamination behavior, 223
 - Edge delamination growth
 - carbon-fiber epoxy laminates, 239
 - Edge delamination tension specimen, 297 (fig)
 - for testing interlaminar fracture toughness of composites, 298
 - Edge delamination test, 243–245, 359
 - advantages and disadvantages, 217, 218 (table)
 - aromatic polymer composite, 361
 - critical strain energy release rate for delamination onset, 215 (figs)
 - delamination growth, 368 (fig)
 - element size at delamination front, 209
 - interlaminar fracture toughness, 213 (fig), 367
 - nomenclature, 200
 - tension test, 201, 219
 - toughness, 378
 - Elastic fracture mechanics

- condition for crack growth, 233
 - Elastic laminated plate theory, 258
 - Elasticity, 208
 - broken fiber, 180, 189
 - Elastomer modified epoxy
 - versus graphite/epoxy with unmodified brittle matrix, 270
 - Elastomeric compounds
 - added to brittle resins, 10
 - Electron microscope examinations.
 - See* Scanning electron microscope, Fractography
 - End notch flex test, 119
 - End notched cantilever beam specimens (ENCB), 276, 291 (Appendix A)
 - End notched flexure (ENF) specimen, 297 (fig)
 - to determine Mode II toughness, 298
 - Energy release rate, critical, 99
 - equations, 100, 123 (table)
 - Enthalpy
 - advanced matrix resins for aircraft, 438–439 (figs), 441
 - Environment, effect on resin systems, 310
 - Environmental resistance, of SIPN
 - improvement needed, 454
 - Epoxy, 397
 - Epoxy composite systems
 - fracture, 88
 - in adhesive bonded joints, 151
 - Epoxy composites
 - structural performance, 414
 - Epoxy laminates, overview, 3
 - versus material systems, 22
 - Epoxy matrix composites, 61, 90, 148
 - compatible with graphite fibers, 414
 - new materials needed to improve in-plane structural properties, 414
 - projected improvements with addition of SiC whiskers, 403 (fig)
 - resistant to aircraft fluids, 414
 - Epoxy resin fracture, 142 (fig)
 - Epoxy resin systems, existing
 - compressive test data, 12
 - Epoxy resin toughness, 383
 - Epoxy/silicon-carbide, 404
 - effect of SiC on epoxy resin modulus, 405 (fig)
 - Epoxy systems
 - cure epoxies compared with tough epoxy, 77
 - Exothermic activity
 - processing requirements, 17, 20 (fig)
 - Experimental procedures, tests
 - graphite fibers versus resin systems, 25 (table)
- F**
- Failure behavior, 376
 - neat and composite systems, 91
 - Failure modes, 40 (fig), 41 (fig), 42 (fig)
 - fiber kinking, 56
 - growth of delaminations under fatigue loading, 223
 - notched specimen, 49 (fig), 50 (fig)
 - orthotropic fibers, 183 (fig)
 - overview, 3
 - quasi-isotropic graphite/epoxy laminates, 38, 43, 45, 48 (fig)
 - versus unidirectional laminates, 46
 - unnotched specimens, 39
 - Failure stress, 45
 - Fatigue
 - crack growth rate, 284–287 (figs)
 - tests, 224, 225, 230, 243
 - delamination size inferred from stiffness reduction, 233
 - graphite/epoxy composites, 248–250 (equations), 257 (figs), 279
 - Fatigue cycles. *See* Cyclic fatigue
 - Fatigue load ratio (*R* curve), 232–233 (figs), 239, 284 (fig)

- Fatigue loading, 290
 delaminations under, 223, 234 (fig)
 growth of cracks in metals under, equations, 235
 Mode II fatigue, 277 (fig)
- Fatigue tests, 277 (fig)
- Fiber bonding, 112, 166
- Fiber bonding failure, 146, 147
- Fiber breakage
 may be enhanced in presence of delamination, 223
- Fiber bridging, 87, 91, 125, 128
 as cause of high fracture energy, 386
 carbon fiber reinforced polymers, 132
 coated fibers, 159 (fig)
 effects of heat and moisture, 305
 influence of elastomer modifiers, 270
 rubber-toughened epoxy system, 280
- Fiber debonding, 270
 before resin cracking net increase in toughness, 126
- Fiber fracture
 of brittle matrix resins, 38
- Fiber kinking, 42 (fig), 56, 398
 as mechanism of failure, 43, 48
 not detected on stress-strain curves, 45
- Fiber matrix adhesive failure, 131
- Fiber-matrix bonding, 91, 166, 175
 debonding, 281
- Fiber nesting, 91, 157
- Fiber pullout, 91, 133–135 (figs), 147, 148
 overview, 3
- Finite element analysis, 208, 210 (table), 212
- Flexural strain, new generation epoxy composites, 413
- Flexure properties
 composites, SIPN, 459 (table)
- Fluid flow and fiber compaction model
 submodel of Lockheed Process Model, 438–439 (figs)
- Fractographic features, delamination, 139 (fig)
- Fractographic observations, 109, 121
- Fractography, SEM, 103, 109–111 (figs), 122, 124 (fig)
 hybridized composites, 407
 Mode II fatigue specimens, 289 (fig)
 of carbon fiber reinforced polymers, 131–132, 134 (fig)
 of coated fibers, 156 (fig), 159, 160–162 (figs)
 of epoxy-matrix composites, 148
 of graphite/epoxy static test specimens, 281, 283 (fig)
 overview, 3
- Fracture. *See also* Fractography, Fracture energies
 adhesive bond analogy for delamination, 211 (fig), 212 (fig)
 coated fiber composites, 159
 delamination, 116
 edge delamination test configuration, 205 (figs)
 delaminated modulus, 206 (table)
 laminated plate theory, 203, 204
 measurements, 117
 overview, 1
 results, 122
 strain energy release rate
 equations, 203–207
 sublaminar moduli, 205 (table)
 testing, 79 (fig), 80 (figs), 94 (discussion), 97
 neat resins, 99, 111, 121
- Fracture behavior, 75, 84, 85 (fig), 107 (figs). *See also* Brittle fracture
 double cantilever beam test, 363, 378
 elastomer modified neat resin, 264, 269
 epoxies versus thermoplastic composites, 87

experimental data, 76 (table)
 influence of composite uniformity,
 86 (fig)
 single fiber shear strength test, 179
 Fracture data, 78 (table), 82, 89 (fig)
 Fracture energies, 133 (table), 280,
 291
 excess can be due to fiber bridging,
 386
 Fracture experiments, 91
 Fracture load, 133
 Fracture mechanics
 delamination behavior, 223
 technology applied to composite
 materials, 295
 Fracture resistance, 290
 Fracture surface
 PEEK microstructure, 352-354
 SIPN, Mode I, SEM, 460-461
 (figs)
 Fracture toughness, 271, 306
 Fracture toughness values, Ryton-
 PPS, 321
 Frequency effects, 249, 258, 291
 Fuselage structural components
 new resin systems, 21

G

Glass fibers
 critical length experiments, 170
 predicted work of adhesion, 172,
 174 (table)
 surface energy components, 173
 (table)
 surface energy measurements, 169
 wettability, 166
 Wilhelmy balance measurement,
 171 (table)
 Glass transition temperatures, 116
 coated fiber composites, 154, 162
 thermoplastics, 333
 Glassy polycarbonate
 stress-strain behavior, 389

Glassy polymers, 331
 Graphite
 predicted work of adhesion, 173
 (table)
 surface energy components, 172
 (table)
 surface energy measurements, 169
 wettability, 166
 Wilhelmy balance measurements,
 171 (table)
 Graphite/epoxy composites, 24 (fig),
 25 (fig), 43
 aircraft design, weight-saving crite-
 rion, 415 (fig)
 cyclic fatigue, 251-255 (figs)
 damage development, 225
 delamination fracture toughness,
 260, 261
 double cantilever beam test, 264
 edge delamination test, 210, 211
 (fig), 219
 fatigue tests, 224, 243, 248
 finite element analysis, 209 (fig)
 edge delamination tests, 208
 interlaminar cracking, 260
 tests, 210, 211 (fig)
 lamina structure, 399 (fig)
 material design, packing concepts,
 399
 materials for toughness tests, 201,
 202 (table)
 microstructural arrangement, 399
 (fig)
 need for improved delamination re-
 sistance, 151
 static material properties, 246-247
 (tables)
 strain energy release rates, cyclic fa-
 tigue, 251-255 (figs)
 susceptibility to impact damage, 38
 tensile strength
 test conditions, 24 (fig)
 thermal/moisture stress, 207 (fig)
 toughened laminates

- aerospace applications, 116
- applications, 96
- test procedures, 203
- Graphite/epoxy laminates
 - failure modes, 398
- Graphite/epoxy/silicon-carbide (Gr/E/SiC) formulations, 404, 411
 - delamination data, 410
 - effect on composite density, 402 (fig)
 - effect on fracture energy, 406 (fig)
 - short-beam shear tests, 410
 - tensile strength, 407, 408 (tables), 409 (fig)
 - to examine hybrid technique, 398
- Graphite/epoxy structures
 - evaluation of impact damage on strength of, 24
- Graphite fibers, 397
 - composite systems
 - fatigue tests, 278
 - Mode II fatigue behavior, 276
 - static tests, 278, 280 (fig), 288
 - hybrid composites, 397
 - interlaminar fracture toughness, 383
 - overview, epoxy composites, 3
 - reinforced composite materials, 1
 - toughened, 116,
 - tests, 25 (table), 62
- Graphite fiber coatings, 151
 - versus graphite fiber composites to improve toughness, 157
- Growth law, 222–241
- Growth rate. *See* Crack growth rate

H

- Hackle markings, 131–132, 133–140 (figs)
 - Mode II fracture surface, 282
 - on fracture surfaces, 142 (fig), 147
 - reduction after thermal treatment, 135

- Heat
 - effect on mixed mode fracture, 304
 - effect on toughness, 300
 - fiber bridging, 305
- Heat and mass transfer model
 - aircraft applications
 - submodel of Lockheed Process Model, 438–439 (figs)
- Heat flow versus temperature, PEEK, 349 (fig)
- Heating, effects of, on fractographic features, 137–138 (figs), 145 (figs)
- High temperature graphite/epoxy
 - static tests, 279
- High temperature properties
 - PEEK, 342
- Hybrid composites, 61, 398, 404
- Hybridizing
 - resin-whisker blends, 402
 - SiC whiskers and graphite fibers, 401 (table)
- Hysteresis, 290 (fig)
 - PSF/graphite versus PET/graphite, 336

I

- Impact, 383
- Impact damage, 27
 - ability to carry load after, 62, 68, 69 (figs)
 - as a cause of delamination, 359
 - composite systems, 55 (fig)
 - effect of interlayering, 428
 - in aircraft applications, 9
 - resistance to, 21
 - low energy, 367, 372 (fig), 378
 - quasi-isotropic graphite/epoxy laminates, 39
 - resistance, 371, 416
 - tests, 27 (fig), 28, 29 (figs)
- Impact energy
 - damage area versus incident impact

- energy, 370 (fig)
- effect on damage area, 55 (fig), 367
- effect on compressive strength, 56 (fig)
 - first generation systems, 417 (fig)
 - low energy specimen, 369 (fig)
- Impact loading, 417
 - delaminations as result of, 223
- Impact resistance, 63, 70
 - of brittle and tough matrix resin improved by interleaving, 429 (fig)
 - of epoxy laminates, interleaved toughened epoxy laminates, and interleaved single resin composites, 430 (figs)
- Impact strength
 - improved by tough coatings, 151
- In-process modeling, 437
- In situ fracture observations, 122, 125–127 (figs) *See also* Fractography, Scanning electron microscope
- Interface mechanics, 179, 180, 181 (figs)
 - material properties, 185 (table)
 - shear strength, equations, 182 (table)
 - stress analysis model, 184 (fig)
 - equations, 184–185, appendix, 190–196
 - stress distribution, 187
- Interfaces, 175
- Interfacial bond strength, 116, 125
- Interfacial bonding, 104, 108, 122, 175
 - as primary fracture mechanism, 128–129
 - overview, 3
- Interfacial debonding, 121, 122
- Interfacial failure, 140, 147
- Interlaminar cracking, 260
- Interlaminar fatigue crack growth, 276, 294 (Discussion)
- Interlaminar fracture, 82, 86 (fig), 147.
 - See also* Coated fibers, Delamination resistance, Toughness crack propagation, 361, 365
 - Gr/E/SiC delamination data, 410
 - influence of resin on, 296
 - toughening mechanisms, 388
- Interlaminar fracture behavior, 90
 - of double cantilever beam specimens, 132
 - overview, 3, 4
 - test methods, 75, 81
- Interlaminar fracture energy, 132, 133 (table), 147
 - effects of increasing matrix toughness, 291
- Interlaminar fracture toughness, 212, 213 (fig), 217
 - APC, 359, 361
 - brittle systems, 302 (fig)
 - delamination resistance, 379
 - double cantilever beam test, 365
 - evaluating test methods, 306
 - failure criteria, 216 (fig)
 - influence of resin, 296 (table)
 - semi-interpenetrating polymer network (SIPN), 454, 458 460–461 (figs)
 - mixed mode data, 301, 307
 - nomenclature, 200
 - of composites, 304 (figs)
 - of graphite fiber composites, 384
 - of semi-interpenetrating polymer network (SIPN) matrix composite, 453
 - strain energy release rate, 296, 307 (fig), 308 (table), 309 (figs)
 - test
 - versus edge delamination test, 201
- Interlayering
 - effect on impact damage, 428
 - ensures weight savings over aluminum, 429
- Interleaf shear modulus

- effect of temperature on, 431
- Interleafed composites, 425
 - advanced system, structural performance and impact resistance, 433 (fig) (table)
 - discussion, 435–436
 - physical properties, 434 (table)
 - laminar compressive failure modes, analytical model, 432 (fig)
- Interleafing, 70, 428, 429 (fig)
- IPN (interpenetrating polymer network). *See* Semi-interpenetrating polymer network

J–K

- JOEL microscope. *See* Scanning electron microscope
- Kelly-Tyson shear lag analysis, 168
- Kinetics, 438
- Kinking. *See* Fiber kinking

L

- Lamina stacking sequences, 175
- Laminar properties
 - damage tolerance, 398
 - influence of adhesion, 148
- Laminar stiffness
 - effect on delamination fracture toughness, 109
- Laminar thickness
 - cure cycle adjustments, 19
 - exotherm versus, 20 (fig)
- Laminar plate theory
 - interlaminar fracture toughness, 203, 207
- Laminates in aircraft
 - structural applications, 9
 - tensile strength and stiffness comparisons, 12, 13 (fig)
- Linear beam theory, 119
 - in calculation of energy release rate, 99

- Load cycles, 278
- Load deformation curves, 362
- Load displacement curves, 281 (fig)
- Load displacement records, 280
 - Mode II tests, 100, 119
- Load ratio effects, 250, 258
- Lockheed Process Model
 - aircraft applications, 438–439 (fig)
 - experiment verification, 442–443 (figs)
 - use to predict cure behavior, 437
- Low energy impact (LEI) damage
 - quasi-isotropic laminates, 362

M

- Macro-buckling failure, 373, 376
- Material systems versus epoxy systems, 22
- Matrix cracking, 224, 290
 - associated with stiffness reduction, 229
 - effect on delamination and metal crack growth rate, 224
 - may be enhanced in presence of delamination, 223
 - stiffness reduction mechanisms, Appendix I, 240
 - under static loading, 234
- Matrix fracture, 133, 212
- Matrix resins
 - delamination susceptibility, 75
- Matrix synthesis, overview, 1
- Matrix toughness, 276, 281
 - effects of, on composite properties, 288
 - improved, 290, 291
- Mechanical properties, 32
 - composite fibers, 84, 175
 - graphite epoxy laminates, 101
 - test results, 102 (tables)
 - of laminates, 38, 39 (table)
 - of toughened resin graphite composites, 23

- Mechanical tests, 166, 169, 173
toughness, 117
- Methacrylate-butadiene-styrene (MBS)
rubber toughened plastic, 393
- Microbuckling, 398, 418
of interlayered laminate, 429
- Microcracking, 106 (fig), 129, 418
debonding, 104, 105 (fig), 121, 146
during fatigue loading, 242
in situ observations, 125–127 (figs)
Mode II fracture surface, 282
occurs ahead of crack tip, 143
- Micromechanics, overview, 3
- Mid plane delamination tests, 214
- Mixed mode
critical energy release rate, 101, 121
- Mixed mode delamination tests, 214
- Mixed mode fracture, 296
evaluating test methods, 306
- Mixed mode fracture toughness tests, 97, 98 (fig)
- Mixed mode interlaminar fracture
influence of resins
literature review of data, 313
toughness, 260, 276, 301, 307
measurements for, 117
- Mixed mode toughening mechanisms, 96
- Model, stress distribution, overview, 3
- Mode I crack growth resistance curves, 282 (fig)
- Mode I critical strain energy release rate, 99, 120 (table), 215 (figs), 260
analysis, 118
equations, 100, 118
- Mode I delamination fracture toughness, 127, 206, 261
- Mode I delamination growth, 280
- Mode I fracture behavior, 106, 107 (figs), 112, 282
- Mode I fracture toughness results, 122
- Mode I fracture toughness tests, 97, 98 (fig), 116
interlaminar fracture
composite matrix materials and adhesives, 296
of elastomer-modified matrix epoxy, 261
- Mode I load displacement records, 121
- Mode I loading
delamination toughness, 126, 129
- Mode I strain energy release, 91, 276
- Mode I toughening mechanisms for, 96
- Mode II critical strain energy release rate, 99
analysis, 119
equations, 100, 119
for delamination fracture, 119
- Mode II delamination fracture toughness, 113, 114, 116, 260
- Mode II fatigue behavior, 276, 282
- Mode II fatigue crack growth rate, 284–287 (figs), 291
- Mode II fracture toughness results, 122, 291
- Mode II fracture toughness tests, 97, 98 (fig)
toughening mechanisms for, 96
- Mode II hackling, 281
- Mode II interlaminar fatigue crack, 287
- Mode II loading, 129, 300
- Mode II strain energy release rate
graphite epoxy interlaminar fracture, 276
- Mode III delamination fracture toughness, 260
- Modulus characteristics
improved resin systems, 12, 13 (fig)
- Moisture, 291
effect on mixed mode fracture, 304
effect on toughness, 300
fiber bridging, 305
influence on strain energy release rate, 208
- Molding, PEEK, 343

- Molding, PPS, 320
- Molding process, PPS, 321
 - processing variables, 326
- Morphology
 - and mechanical properties, of PEEK, 344, 345, 350

N

- Neat adhesive panels, 153
- Neat materials
 - glass transition temperature, 162
- Neat resin, 89, 90
 - new composite matrices, 422 (fig)
- Neat resin flexural strain, 424 (figs)
- Neat resin fracture tests, 80, 84, 97
 - elastomer-modified epoxy, 269
- Neat resin fracture toughness, 102 (table), 111–113
- Neat resin mechanical tests, 62, 76, 77, 99
- Neat resin modulus, 425 (fig)
- Neat resin moldings and composites, 4, 89
- Neat resin properties
 - as prediction of composite properties, 63–66 (figs)
 - comparison, 426 (table)
 - composite properties, comparison, 427 (table)
 - interleafing, 428
- Neat resin toughness, 128–129
 - versus composite toughness, 386
- Nesting, 87, 91
- No-bleed cure, 19
- No-bleed resin system, 22
- Notch sensitivity, 56
 - compressive failure
 - of quasi-isotropic laminates, 39, 49 (fig), 50 (fig), 51 (fig), 52
 - dependent on matrix material, 52
 - equations, 46 (table), 51, 52
 - of composite plaques, 174 (fig)
 - strength ratios, 53 (figs), 54 (figs)
 - thermoplastic resins, 170
 - versus unnotched specimens, 39
- Notched strength
 - analysis,
 - equations, 50–54 (figs)
 - in composite materials,
 - parameters of influence, 175
- Notched tension, 25

O

- Opening mode
 - toughness measurements for, 117
- Orientation hardening
 - ductile polymers, 389, 392, 394
- Orthotropic fibers, 189
 - graphite and aramid shear lag models, 180

P

- PEEK (polyetheretherketone) matrix, 279, 285, 288, 302
 - annealing peak, compared to PPS, 322
 - DSC analysis, 325 (fig), 349
 - glass transition temperature, 342
 - hysteresis, 290 (fig)
 - interlaminar toughness, 307
 - mechanical properties and morphology, 343, 344 (fig), 345 (fig), 351 (table)
 - microstructure, 352–354
 - tensile properties, 357
 - tension testing, 350
- PETG (amorphous polyester), 170, 175
- Photomicrographs. *See* Scanning electron microscope (SEM)
- Plane-strain fracture toughness
 - hybridized composites, 404
- Plastic deformation, 389
 - PEEK system, 281
- Plastic zone size
 - in a tough bulk polymer, 385 (fig)

- neat resin, 386 (table)
- Ply orientation
 - effect on delamination fracture toughness, 109
- Polyacrylonitrile-butadiene-styrene (ABS) films, 393
- Polyamideimide, 78
- Polycarbonate
 - composite fabrication, 77
 - crack growth, 83
- Poly(etheretherketone) matrix (PEEK).
 - See* PEEK matrix
 - fiber/matrix debonding, 288
- Polyetherimide
 - composite fabrication, 77
 - fracture toughness testing, 79 (figs), 88
- Polyethylene
 - predicting work of adhesion, 175
- Polyethylene terephthalate (PET), 175, 329
 - cross-ply PET/graphite strip experiments, 330
 - differential scanning calorimetry (DSC), 335 (fig)
 - dynamic mechanical analysis (DMS), 338 (fig)
 - specific volume, 332 (fig)
 - temperature independent parameters, 337 (table)
- Polymer matrix composites, 384
 - delamination failure mode, compared to bonded joints, 295
- Polymer morphology, SIPN
 - of neat resin blend
 - cure cycle, 458
 - TEM photograph, 458 (fig)
- Polymeric coatings to increase toughness, 151
- Polymeric modifiers, 422
- Polymers
 - toughening mechanisms, 388
 - overview, 3
- Polyethyl methacrylate (PMMA)
 - relaxation behavior, 391
- Polyphenylene sulfide (PPS), 4, 320.
 - See also* Ryton-PPS
 - carbon fiber composite
 - DSC analysis, 323–324 (figs)
 - thermal transitions, 322
 - morphological structure of composites, 321
 - thermal history and mechanical properties of film, 322 (table)
- Polyphenylene sulfide (matrix), 147
 - fracture surfaces, 139, 144–145 (figs)
- Polystyrene
 - predicting work of adhesion, 175
- Polysulfones (PSF), 329
 - composite fabrication, 77
 - cross-ply composite strip experiments, 330
 - dilatation, effect on toughness, 301
 - dynamic mechanical analysis (DMS), 338 (fig)
 - fiber volumes, 84
 - fracture toughness testing, 79 (figs), 88
 - specific volume of, 332 (fig)
 - temperature independent parameters, 337 (table)
 - toughenability limitations, 383, 386
- Polytetramethyleneoxy
 - predicting work of adhesion, 175
- Polyvinyl chloride (PVC)
 - rubber toughened plastic, 393
- Postimpact compression, 23, 30
 - tests, 31 (figs)
 - failure strain versus damage area material comparisons, 32 (fig)
- PPS. *See* Polyphenylene sulfide
- Prepreg laminates, 62
- Prepreg preparation, 152, 157
- Properties
 - polyphenylene sulfide (PPS), 326 (tables)
- Pseudoplasticity

advanced matrix resin systems, 445, 447, 450 (fig)

Q

Quasi-isotropic laminates
 compressive failure of, 38, 43, 47, 56
 versus unidirectional laminates, 48 (fig)
 unnotched specimens, 39–40
 compressive properties, 46 (table)
 compressive strengths of, 47 (fig)
 impact tests, 27–29 (figs)
 structural performance
 weight saving over aluminum, 415 (fig)
 tensile strain-to-failure, 26 (figs)

R

R curve (fatigue load ratio), 232–233 (figs), 239
 Radial stress
 single fiber test, 186, 187–188 (figs)
 Rate effects
 delamination fracture toughness, 261, 271
 Reaction exotherm
 in epoxy resin curing, equations, 439–440
 Relaxation process, low temperature, and ductility, 391, 394
 Residual stresses
 thermoplastic matrices, 329, 338, 340
 Resin adhesion, 129
 Resin bleed
 processing requirements, 17
 Resin deformation, 113
 Resin fracture
 versus interfacial debonding, 121
 Resin matrix materials
 strain energy release rates, 213 (fig)
 Resin matrix systems
 for aircraft applications, 437
 Resin modification techniques, 398
 Resin modulus
 compressive strength influence, 418
 key factor in structural performance, 398
 Resin stress-strain behavior, 299, 300 (fig)
 Resin systems, 296 (table)
 composites, influence of resin content, 83
 compression after impact, 64–65 (figs)
 criteria for selection, 21
 improvement of, 12
 no-bleed resin system, 22
 tensile properties, 102 (table)
 tests, 25 (fig)
 Resin tensile modulus, 47 (fig), 56
 overview, 3
 Resin toughness, 116, 307–310
 adding elastomeric materials, 96
 increases compressive strength, 23
 Resin-whisker blends, testing procedure, 402
 Resin yielding, 145–148
 Rheometric measurement, 439 (fig)
 Rheometrics tests
 on neat resin specimens, 99
 Rubber modified epoxies, 392
 in adhesive joints, 388
 Rubber modifiers, 384
 Rubber particle additions, 112
 efficacy in enhancing composite delamination fracture toughness, 109
 neat resin fracture toughness, 108
 Rubber toughened graphite/epoxy
 fiber bridging, 280
 static tests, 279
 Rubber toughened neat matrix resins, stress-strain properties, 422 (fig)
 Rubber toughened plastics
 rubber particle size effect, 393
 Ryton-PPS (Polyphenylene sulfide), 320 *See also* Polyphenylene sulfide

- annealing, effect on mechanical properties, 326 (table)
 transverse tensile properties, effect of annealing, 326 (table)
- S**
- Scanning electron microscope (SEM), 116, 133, 154. *See also* Delamination fracture, Fractography
 hybridized composites, fracture surfaces, 407 (fig)
- Semicrystalline polymers, 389
 physical and mechanical properties, 321, 454
 PEEK, 357
 semi-interpenetrating polymer network (SIPN), 454
- Semicrystalline thermoplastics, 329, 338
- Semi-interpenetrating polymer network (SIPN), 454
 chemical resistance, 461 (table)
 mechanical properties, 458
 polymer morphology, 458
- Shear, 275, 276, 291
- Shear lag analysis, 189
 Kelly-Tyson, 168
- Shear mechanical tests, 68 (fig), 71 (fig)
- Shear mode
 toughness measurements for, 117
- Shear modulus
 quasi-isotropic laminates, effect of buckling stress, 45
- Shear strength test, single fiber, 179
- Shear stress
 interfacial, 168, 187 (fig)
 interlaminar crack growth, 276
 stable neck propagation, 389
- Shear yielding
 process leading to ductility, 389
- Silane coated glass
 versus "bare" glass
 critical length determination, 177 (fig)
 predicted to increase shear adhesion strength, 176
- Silicon carbide (SiC) whiskers
 effect on epoxy resin, 398, 401
 whisker characteristics, 400
- Single fiber test, 179, 180, 181 (figs)
 shear strength, 182 (table), 189
- Single-step pressure cycle, 19
- SIPN. *See* Semi-interpenetrating polymer network
- Smoke generation
 tests for new resin systems, 21, 22 (fig)
- Smooth resin fracture, 134
- Spectrometer, dynamic mechanical, 97
- Stable neck propagation
 process leading to ductility, 389
- Static tests, 245, 279, 280 (table), 290
 effect of matrix toughness on delamination, 291
- Stiffness loss, 233
 caused by damage accumulation, 243
 effect of matrix cracking and delamination, 226, 242
 in presence of delaminations, 223, 227, 229 (fig)
 stiffness reduction mechanisms, Appendix I, 239 (table), 244, 258 tests, 225
- Stiffness properties, 245, 258
 temperature dependence of, 340
- Strain
 accelerates processes leading to ductility, 389
- Strain energy release rates, 223, 233, 235, 238
 brittle systems, 302
 cracked lap shear specimens
 finite element analysis of, 299
 toughness tests data, 303 (table)
 fatigue cycles, graphite/epoxy, 251–254 (figs), 258
 for delamination onset, 213 (fig)
 fracture toughness, 79, 201, 260
 influence of thermal/moisture

- stresses on, 207 (fig)
 - interlaminar fracture tests, 296
 - interlaminar fracture toughness, mixed mode, Mode I, Mode II, 302
 - loading ratio parameters, 243, 250
 - Mode I improvement, 75, 261
 - Strain limitation
 - from compressive test data, 12
 - weight trade studies, 10
 - Strain-to-failure fibers
 - testing, 26, 32, 62, 71
 - Strength
 - loss of, in presence of delaminations, 223
 - of advanced technology wing, 11 (fig)
 - Strength and modulus characteristics, 12
 - improved toughness composites, 24
 - Strength comparisons
 - of quasi-isotropic laminates, 32 (fig)
 - Strength-modulus comparison, 13 (fig)
 - Stress
 - relaxation behavior
 - of polymethyl methacrylate (PMMA) 391
 - versus extension ratio behavior
 - of ductile glassy polymer, 390 (fig)
 - Stress analysis
 - appendix, equations, 190–196
 - interlaminar normal stress, 229 (table)
 - model, single broken fiber, 184 (fig), 188
 - overview, 3
 - Stress distribution
 - single fiber shear strength test, 179, 180
 - interface mechanics, 186 (fig), 187–188 (figs)
 - of fiber-resin interface, 146 (fig)
 - Stress intensity factor, 223
 - Stress-strain behavior
 - brittle and tough neat resins, 423 (figs)
 - epoxy systems, 420
 - glassy polycarbonate, 389
 - neat resins, 99, 421 (fig)
 - PEEK films, 350–351 (figs)
 - resin-whisker blends, 402
 - resins, 300 (fig)
 - Stress-strain curves, 43, 44 (fig), 46 (fig), 225
 - Structural design properties
 - of graphite fiber composites, 151
 - Supplementary reinforcement
 - hybrid composites, 397
 - Surface energy calculations in adhesion
 - basic theory, calculations, 167–168
 - Surface energy components
 - graphite, 172 (table)
 - Surface energy measurements, 169 (table), 176
 - graphite, Wilhelmy balance, 171 (table)
- T**
- Temperature, 291. *See also* High temperature
 - thermoplastics
 - dimensionless curvature as a function of temperature, 334 (figs)
 - Temperature behavior prediction
 - model, for curing advanced graphite/epoxy laminates, 452
 - thermograms, 451 (figs)
 - Temperature profiles
 - cure cycle, resin matrix for aircraft applications, 443, 444 (fig)
 - exotherm versus laminate thickness, 20 (fig)
 - glass transition, of resins, 102 (table)

- Temperature relaxation process
 - in choice of polymers for toughening, 390
- Temperature requirements
 - commercial versus military, 12
- Tensile behavior, static, 25
- Tensile properties
 - coated fiber composites, 162
 - in silane systems, 176
- Tensile strength
 - failure, 16
 - strain comparison, 26 (fig)
 - neat resin, stress-strain curves, 155–156 (figs)
 - overview, 2
- Tension-tension fatigue tests, 224, 227 (fig), 244
- Tension tests
 - of matrix resins, 142, 144 (figs)
 - of glass/polycarbonate composites, 175
 - of PEEK, 350
 - on neat adhesives, 154, 155–156 (figs)
 - on neat resin systems, 99
 - results, 102 (table)
 - to measure fracture toughness of composites, 200
- Test conditions
 - graphite composites, 24
- Test correlations, 62
- Test equipment
 - dynamic mechanical spectrometer, 97
- Tests and test procedures
 - graphite composites versus aluminum structures, 21
 - impact damage, 27, 28–29 (figs)
 - postimpact compressive behavior, 30
 - graphite/epoxy, 203
 - neat adhesives, tension tests, 154
 - quasi-isotropic laminates
 - experimental procedures materials evaluated, 25 (table)
 - static tensile-behavior, 25
- Tetraglycidylether methylene dianiline, 140, 142
- Tetraglycidylmethylenedianiline (TGMDA)/diaminodiphenylsulfone (DDS)
 - Lockheed Process Model, 437–438 (figs)
 - polymerization exotherm, 447
- Thermal analysis
 - of thermoplastics, 329
- Thermal analyzer model
 - for advanced matrix resin systems aircraft applications, 451
- Thermal expansion
 - coefficient of (CTE), 245, 336
 - of PET, 332
- Thermal history, PEEK, 343
- Thermal stress
 - influence on strain energy release rate, 208
 - single fiber tests, 186
 - thermoplastic matrices, 329, 333, 338, 340
- Thermal treatment, effect on fiber pull-out, 135, 137 (fig)
- Thermochemistry
 - important in cure process modeling, 447 (fig)
- Thermokinetic model
 - aircraft applications, 438, 439 (fig)
- Thermoplastic compounds
 - added to brittle resins, 10
- Thermoplastic composites
 - fabrication procedures, 77
 - fiber-matrix bonding, 88
 - interlaminar fracture, 88
 - overview, 3, 4
 - PEEK, 342
 - resistance to impact damage, 21
 - semi-interpenetrating polymer networks (SIPN), 454
 - tested by Douglas Aircraft, 12

- Thermoplastic matrices, 329, 333, 338, 340
 - Thermoplastic polymers, 383
 - toughening with elastomers, 393
 - Thermoplastic resins, 83
 - notch sensitivity study, 170
 - wettability, 166
 - Thermosets, 76, 78, 88
 - cross-linked, 140
 - overview, 4
 - Thermosetting polymers, 383
 - Thickness, exotherm versus laminate, 20 (fig)
 - Tough coatings
 - on graphite fibers, 151
 - Tough composites, 384
 - overview, 2
 - Tough epoxy matrix resin systems, 398
 - Tough epoxy systems
 - tests, 77
 - Tough polymer tests
 - strain energy release rates, 80
 - Tough resins, 25, 89
 - as coating for graphite fibers, 151
 - crack-tip deformation, 91
 - criteria for selection, 17, 21
 - Douglas Aircraft, 12, 16 (fig)
 - elastomer-modified epoxies, 261
 - formulated by adding elastomeric or thermoplastic compounds, 10, 12
 - tension tests, 26 (figs)
 - Tough systems, 305, 306 (fig)
 - Toughened epoxies, 115
 - Toughened epoxy matrix systems, 444
 - Toughened epoxy resins, 61
 - fracture aspects, 74
 - laminates, 95
 - strain energy release, 84, 85 (fig)
 - Toughened resins, 413
 - Toughening, 383
 - Toughening mechanisms
 - graphite epoxy composites, 96
 - in plastics, 393
 - Toughness
 - coated fiber composites, 161–162 (figs)
 - versus uncoated composites, 162
 - delamination resistance, test, 16
 - graphite-epoxy composites, 116, 217, 243
 - graphite fiber composites, 276, 281
 - relative effects of matrix toughness on, 288
 - need for improved toughness, 151
 - transfer from matrix to composite, 290 (fig)
 - increased with fiber debonding before resin cracking, 126
 - interlaminar fracture
 - mixed mode data, 301
 - tests, 201
 - mechanical tests, 62, 67
 - Mode I versus Mode II, 299
 - PEEK, 357
 - single fiber shear strength test, 179
 - Transverse sheer modulus, 45
 - Transverse strength
 - improved by tough coatings, 151
 - Transverse tests
 - glass tow, 170
 - tension tests of glass/polycarbonate composites, 175
 - Unidirectional laminates, 56, 62
- U–V**
- Viscoelastic effects
 - on behavior of tough composites, 2
 - Viscosity. *See also* Chemoviscosity
 - Viscosity behavior
 - toughened resin systems, 445
 - Viscosity profile
 - advanced resin matrix, 448–449 (figs),
 - for cure cycle, resin matrix aircraft applications, 443, 444 (fig)
 - Viscosity profile measurement
 - for cure cycle conditions, 19 (fig)

W

Weight comparison for bending stiffness
 advanced technology wing design criteria, 10, 11 (fig)
Wettability, 176
 of thermoplastics, 166
Wetting of individual filaments
 by matrix resin, 166
Whisker-resin impregnation process, 412
Width-tapered double cantilever beam

(WTDCB) specimen, 261, 263 (fig). *See also* Double cantilever beam test

Wilhelmy balance measurements
 glass and graphite, 171 (table)

Wilhelmy Technique
 method of measuring angles on filaments, 167–168

Z

Zinc iodide enhanced radiography, 224, 227 (fig)