

Index

- A**
- abiotic degradation, environmental characteristics and, 1544
 - abrasion resistance, of petroleum waxes, 109–110
 - abrasive wear, 443, 725, 725 (figure), 888, 1582–1583, 1583 (figure)
 - accelerated corrosion tests, for lubricating greases, 952
 - accelerated quenching oils, 1003–1004
 - accepted reference value (ARV), 1703, 1706–1707
 - accumulation processes, environmental characteristics and, 1549–1550
 - acid formation, oxidation and, 1364, 1368 (figure)
 - acid neutralizers, 468
 - acid number
 - compressor lubricants and, 706
 - diesel fuel oils and, 259
 - for gear lubricants, 745
 - heat transfer fluids and, 969, 969 (figure)
 - quenching and, 1008
 - total, 570, 572 (figure), 573 (figure), 1151
 - turbine lubricating oils and hydraulic fluids and, 617, 618 (figure)
 - acoustic-resonance technique, for asphaltene precipitation onset pressure, 48, 49 (figure)
 - additives. *See also* antioxidants; antiwear agents; detergents; dispersants; dispersant viscosity modifiers; extreme-pressure agents; friction modifiers; lubricants
 - antisquawk, 442–443
 - ASTM standards for, 500–502
 - for automotive engine lubricants
 - antioxidants, 765–766
 - antiwear agents, 766–767, 767 (figure)
 - balanced formulation, 768
 - corrosion inhibitors, 766
 - detergents, 768
 - dispersants, 768
 - emission-control and, 764
 - EP agents, 767–768
 - foam inhibitors, 769
 - friction and, 764, 848–849, 850 (figure), 851 (figure)
 - friction modifiers, 766
 - PPDs, 768–769
 - rust inhibitors, 766
 - VI improvers, 768
 - wear, 848–849, 850 (figure), 851 (figure)
 - aviation gasoline, 228, 228 (table)
 - base stock properties and, 352–353
 - biocides, 495
 - boundary lubrication and, 443, 449, 452 (table), 1606, 1609–1612, 1609 (figure), 1609 (table), 1610 (figure), 1611 (figure)
 - classes of, 363–366, 365 (table)
 - comparison of, 461 (table)
 - for compressor lubricants, 698–700, 699 (table)
 - corrosion and wear with, 371–372
 - corrosion inhibitors and, 470
 - couplers, 495
 - demand for, 362–363
 - demulsifiers, 470, 472, 473 (figure), 474
 - deposit-modifying, 189–190, 363–366
 - development and approval process of, 495–498, 497 (figure)
 - drag reducer, 1120
 - driveline lubricant, 358–359
 - dyes, 495
 - emulsifiers, 470, 472, 473 (figure), 474, 474 (figure)
 - engine oil, 358, 757
 - environmental impact of, 498
 - foam inhibitors, 492–494, 494 (figure), 607–608, 608 (figure)
 - for gear lubricants, 728
 - antiwear agents, 729–730, 733 (table)
 - chemically active, 731 (table)
 - chemically inert, 732 (table)
 - detergents, 730, 734 (table)
 - dispersants, 730, 734 (table)
 - EP agents, 729, 733 (table)
 - miscellaneous, 736 (table)
 - government regulations on, 351, 498–500, 499 (figure)
 - in HFA and HFB fluid composition, 536, 536 (table)
 - in HFC fluid composition, 541–542, 542 (table)
 - history of, 351
 - IL lubricants and, 1047, 1048 (figure), 1048 (table)
 - industrial lubricant, 359
 - jet fuel, 227–228, 227 (table)
 - lubricant development trends and
 - in HDDEOs, 354–355
 - in PCMOs, 353–354, 353 (figure), 355 (figure)
 - lubricants and
 - composition of, 363, 363 (figure), 363 (table)
 - engine and nonengine, 495, 496 (table)
 - properties of, by application, 358 (table)
 - samples of, 1069, 1071, 1072 (table)
 - lubricating greases and, 939
 - lubricity, 189
 - market for, 359, 360 (figure), 361–363
 - metalworking and machining fluids and, 901 (table)
 - alkalinity agents and, 911
 - antimicrobial agents and, 911–912, 913 (figure)
 - antimisting agents and, 911
 - antioxidants and, 913–914, 914 (figure)
 - corrosion inhibitors and, 911, 912 (figure)
 - couplers and, 903–904, 904 (figure)
 - dispersants and, 910, 911 (figure)
 - dyes and, 914
 - emulsifiers, 900–903, 902 (figure), 902 (table)
 - EP agents and, 905–910, 906 (figure), 907 (figure), 908 (figure), 909 (table), 910 (figure), 910 (table)
 - film formers and, 904
 - foam inhibitors and, 912–913, 913 (figure)
 - friction modifiers and, 904–905, 904 (figure), 905 (figure)
 - inorganic/organic solids and, 914–915
 - odor-control agents and, 914
 - multifunctional nature of, 495
 - oil consumption and, 371, 371 (figure)
 - oil thickening and, 371
 - in performance package, 498
 - petroleum wax, 98
 - polar and nonpolar groups in, 364, 364 (figure), 365 (figure), 365 (table)
 - polymeric, 364, 474–475
 - PPDs, 491–492, 492 (figure), 493 (figure)

- purpose of, 351
- ring sticking and, 371
- seal-swell agents, 495, 666–667
- static dissipator, 1110
- suppliers of, 359
- trends with, 361–363
- for turbine lubricating oils and hydraulic fluids, 598–603, 599 (figure), 599 (table)
- adhesion, friction due to, 1567
- adhesive wear, 443, 725, 888, 1577–1582, 1580 (figure), 1581 (figure), 1582
- adiabatic flame temperature, of gasoline, 202
- adiabatic operation, 684–685, 685 (figure)
- adipic acid, synthesis of, 563, 563 (figure)
- adsorption
 - asphaltene deposition and, 63, 63 (figure)
 - boundary lubrication and, 1606, 1609–1611, 1609 (figure), 1610 (figure), 1611 (table)
 - chemisorption, 1606, 1609 (figure)
 - environmental characteristics and, 1542
 - fluorescent indicator, 221, 306
 - friction modifiers and, 1611, 1611 (table)
 - physisorption, 1606, 1609 (figure)
- Advanced Combustion Emission Reduction Technology (ACERT), 797
- aeration
 - Caterpillar Oil Aeration Test, 801 (table), 808 (table), 816 (table), 825 (table)
 - Engine Oil Aeration Test, 803 (table), 811 (table), 819 (table)
 - GF-4/SM test of, 779 (table)
 - GF-5/SN test of, 789 (table)
 - GM test of, 780 (table), 789 (table)
 - hydraulic fluids and, 661–662, 662 (table)
- aero-derivative gas turbines, 585–586
- aerospace fuels. *See also* aviation fuels
 - air dilution of, 1309
 - ASTM standards for, 1317
 - buoyancy in air of, 1298–1299
 - calorific values of, 1307–1308, 1308 (figure)
 - combustion and
 - emissions of, 1310–1311
 - maximum temperature of, 1302, 1308
 - crude oil and, 1302–1303
 - density of, 1303
 - engine thermodynamics and, 1296–1297, 1297 (figure), 1298 (figure), 1299 (figure), 1299 (table), 1300 (figure)
 - fire safety and, 1311–1312
 - flame stabilization of, 1309
 - flammability of, 1306
 - future trends in, 1315
 - handling characteristics for, 1311–1315
 - health issues in handling, 1315
 - ignition of, 1309
 - molecular structure of, 1297–1299, 1300 (figure), 1301 (table), 1302
 - nomenclature for, 1295–1296
 - oxidant performance and, 1297, 1299 (table)
 - oxidation heat release and, 1302
 - physical state of, 1299
 - properties of, 1302–1303, 1303 (table), 1304 (figure), 1306 (table)
 - reformulation of, 1315
 - smoke tendency of, 1308–1309
 - solidification of, 1305
 - specifications for, 1315, 1316 (table)
 - specific impulse of, 1310, 1310 (table), 1311 (figure)
 - spontaneous ignitability of, 1299, 1306
 - stoichiometry and, 1302, 1306–1307
 - storage stability of, 1297–1298, 1313
 - substitution for, 1315
 - supplementation for, 1315
 - surface tension of, 1305–1306
 - thermal stability of, 1313–1314
 - turbine entry temperature distribution of, 1310
 - viscosity of, 1305
 - volatility of, 1304–1305
 - water content and, 1314–1315
- aircraft range, aviation fuels and, 223
- air dilution, of aerospace fuels, 1309
- air-fuel ratio, ONR, 195
- airports
 - fuel systems of, 229
 - quality control of, 233, 234 (table)
- air release
 - compressor lubricants and, 704
 - gear lubricants and, 749
 - of HFA and HFB fluids, 540
 - of HFC fluids, 544
 - of industrial lubricants, 323, 323 (figure)
 - turbine lubricating oils and hydraulic fluids and, 619–620
- alcohols
 - for environmentally acceptable ester-based hydraulic fluids, 555–556, 556 (figure)
 - in polymeric dispersant synthesis, 396–398, 397 (figure), 399 (figure)
- Alden, Richard C., 151
- aldol condensation, 562–563, 563 (figure)
- algae, in toxicity tests, 1556, 1557 (figure)
- alicyclics, 281, 282 (figure), 292
- alkalinity agents, metalworking and machining fluids and, 911
- alkanes, 187, 280, 282 (figure), 292
 - lattice transition in, 88, 89 (figure)
 - physical properties of, 86 (table)
- alkenes, 280, 282 (figure)
- alkenylphosphonic acids, 396, 396 (figure), 428
- alkenylsuccinates, 398, 399 (figure)
- alkenylsuccinic anhydride, 394–396, 394 (figure), 395 (figure)
- alkenylsuccinimides, 398, 399 (figure)
- alkenylthiophosphonic acids, 428
- alkylated cyclopentanes, 525–526
- alkylation, 13–15, 15 (figure), 15 (table)
- alkylbenzenes, 411–412, 411 (figure)
 - for compressor lubricants, 698
- alkyl lead, 180–182, 188
 - ASTM D4814 and, 200
- alkyl methacrylate, synthesis of, 481, 482 (figure)
- alkylnaphthalenes, 411–412, 411 (figure), 412 (figure)
- alkylphenols, 396, 396 (figure)
 - chlorides and, 414, 415 (figure)
 - detergent substrates and, 413–414, 414 (figure), 415 (figure)
 - methylene-bridged, 413, 414 (figure)
- alkyl phosphates, synthesis of, 448, 451 (figure)
- alkyl phosphites
 - hydroperoxide decomposition and, 378–379
 - hyperoxide decomposition and, 1365, 1371 (figure)
 - synthesis of, 448, 451 (figure)
- alkylphosphonic acids, detergent substrates and, 417, 417 (figure), 418 (figure)
- alkylsalicylic acids, detergent substrates and, 416, 417 (figure)
- alkylthiophosphonic acids, detergent substrates and, 417, 417 (figure), 418 (figure)
- all-hydrogen contact process, 35, 36 (figure)
- alloying composition, pipeline corrosion and, 1442, 1442 (figure)
- alternate fuels, 357, 431. *See also* base stocks, alternative Alternative Motor Fuel Act, 1988, 186

- aluminum beaker oxidation test (ABOT), 1388, 1390 (figure), 1390 (table)
- aluminum complex greases, 938, 941
- aluminum production, carbon anodes for, 1354
- aluminum soap greases, 938, 940
- American Gear Manufacturers Association (AGMA), 357
- American Petroleum Institute (API)
- base stock categories of, 755–756, 755 (table)
 - CI-4 engine oils user language of, 797
 - CJ-4 engine oils user language of, 834
 - engine oil system of, 754–755
 - gear lubricant service designation of, 737–738, 737 (table), 738 (table), 739 (table)
 - gravity, 247, 261
 - fuel oils and, 1328–1330
 - static petroleum measurement and, 1066–1067
 - hydrocarbon base oil classification by
 - categories in, 273–274, 274 (figure), 274 (table)
 - by composition, 274–275, 275 (figure)
 - Group I, 275–276
 - Group II, 276
 - Group III, 276
 - Group IV, 276
 - Group V, 276–277
 - by physical properties, 275, 275 (table)
 - static petroleum measurement standards of, 1055–1056
 - turbine lubricating oil and hydraulic fluid standards of, 640
- amine dispersants, 392
- amines, in polymeric dispersant synthesis, 396–398, 397 (figure), 398 (figure)
- amine treating, 24, 24 (figure)
- ammonia, LPG and, 167
- Amonton's law, 683
- Andrews, Thomas, 151
- aniline points, hydrocarbon base oil solvency and, 315–316, 315 (table), 316 (figure), 316 (table)
- anionic emulsifiers, 902–903, 903 (figure)
- annealing, 869
- anodes, 1405
- anodic dissolution reactions, pipeline corrosion and, 1424
- “antidumping” provisions, 183
- antifoams. *See* foam inhibitors
- antifoulants, 68
- Antiknock Index (AKI), 192–193, 193 (table), 196–197
- antimicrobial agents, metalworking and machining fluids and, 911–912, 913 (figure)
- antimisting agents, metalworking and machining fluids and, 911
- antioxidants
- ACEA tests for, 389
 - ASTM standards for, 389
 - for automotive engine lubricants, 765–766
 - base stocks and, 386, 387 (figure), 388 (figure)
 - chromium acetylacetonate and, 386, 387 (figure)
 - for compressor lubricants, 698, 699 (table)
 - detergents as, 426–427, 427 (figure)
 - diphenylaminophenolics and, 386, 387 (figure)
 - for engine oils, 757
 - gasoline, 189
 - for gear lubricants, 730–731, 735 (table)
 - hindered phenols as, 1366–1367, 1373 (figure), 1398
 - hydraulic fluids and, 650–651, 651 (figure), 652 (figure)
 - hydroperoxide decomposition
 - alkyl phosphites and, 378–379
 - mechanism of, 373, 375 (figure), 377 (figure)
 - organic sulfides and, 373–374, 378, 378 (figure)
 - phenol and, 377 (figure), 378–379
 - ZDDPs and, 379, 379 (figure)
 - hyperoxide decomposers and, 1365, 1370 (figure)
 - iron carboxylate and, 373, 376 (figure)
 - metal deactivators and, 382, 385 (figure), 1368, 1375 (figure)
 - metals and, 373, 375 (figure)
 - metalworking and machining fluids and, 913–914, 914 (figure)
 - radical scavengers
 - arylamines and, 381, 382 (figure), 384 (figure), 386, 387 (figure)
 - hindered phenol and, 379–380, 381 (figure), 383 (figure)
 - phenothiazines and, 381–382
 - ZDDPs and, 379, 380 (figure)
 - as radical scavengers, 1365, 1370 (figure)
 - structures of, 373, 377 (figure)
 - synergism and, 385–386, 386 (figure), 387 (figure)
 - transition metals as, 382, 384 (figure), 385, 385 (figure), 1367–1368, 1375 (figure)
 - turbine lubricating oils and hydraulic fluids and
 - ASTM tests for, 601–603, 602 (figure), 603 (figure), 604 (figure), 604 (table)
 - structures of, 598, 600, 600 (figure)
 - synergism of, 600, 601 (table)
 - viscosity and, 385, 386 (figure)
 - wear and, 385, 386 (figure)
 - ZDDPs as, 1365–1366, 1372 (figure)
- antisquawk additives, 442–443
- antiwear agents, 189. *See also* zinc dialkyldithiophosphates
- for automotive engine lubricants, 766–767, 767 (figure)
 - automotive service ratings and, 443, 444 (figure)
 - biodegradability of, 461, 462 (table)
 - boundary lubrication and, 1612, 1612 (figure)
 - commercial availability of, 447
 - common organophosphorus compounds as, 444, 445 (figure)
 - for compressor lubricants, 698–699, 699 (table), 708
 - dithiocarbamates as, 447
 - for engine oils, 757
 - film formation by, 444
 - for gear lubricants, 729–730, 733 (table)
 - hydraulic fluids and, 659
 - oxidation ASTM testing of
 - ASTM D943, 1370–1372, 1376 (figure), 1376 (table)
 - ASTM D2272, 1372–1373, 1377 (figure)
 - ASTM D4310, 1372, 1376 (table)
 - structures of, 443, 606 (figure)
 - thermal activation of, 1611, 1611 (figure)
 - thermal stability and, 445, 447 (figure)
 - for turbine lubricating oils and hydraulic fluids, 605–608, 606 (figure), 607 (figure), 608 (figure)
- antiwear numbers (AWNs), 452–453, 453 (figure), 453 (table)
- antiwear performance testing, for hydraulic fuels, 654, 655 (table), 658–659, 658 (figure)
- AOCS methods, for biodegradable lubricants oxidation testing, 1399
- apparent viscosity, 1487
- lubricating grease flow properties and, 945
- Appledoorn equation, 1604–1605
- aquatic toxicity tests, 1556
- aqueous polymer quenchants, 1006–1007, 1006 (figure)
- appearance of, 1011–1012
 - cloud point of, 1015, 1015 (figure)
 - conductance of, 1014, 1014 (figure)
 - cooling curve analysis for, 1017, 1017 (figure), 1018 (figure)
 - corrosion inhibitors and, 1015–1016, 1015 (figure)
 - degradation analysis for, 1016, 1016 (figure)
 - foaming and, 1016
 - pH of, 1014
 - refractive index, 1012, 1012 (figure), 1013 (figure)
 - viscosity of, 1012–1013, 1013 (figure)
 - water content and, 1014

- Archard's wear constant, 1579, 1582, 1582 (table)
- arenes, 187
- aromatic esters, 514, 514 (figure)
- aromatic hydrocarbon base oils, 284, 286, 286 (table), 289, 290 (table)
- aromaticity, of hydrocarbon base oils, 316–318, 318 (figure)
- aromatics, 187
- asphaltene chemical separation with, 68, 68 (figure), 69 (figure)
 - btx recovery, 12–13, 13 (figure)
 - characteristics of, 3–4
 - composition of, 4
 - in crude oil, 281, 282 (figure)
 - determination of, 347
 - in diesel fuel oils, 256–257
 - GC and, 1114–1115
 - LC and, 1110
 - reduction of, 15–18, 26
- Arrhenius equation, 254
- arsenic test, of used oil, 33
- arylamines
- as antioxidants, 1366–1367, 1374 (figure)
 - radical scavengers and, 381, 382 (figure), 384 (figure), 386, 387 (figure)
- aryl phosphates, synthesis of, 448, 451 (figure)
- aryl phosphites, synthesis of, 448, 451 (figure)
- AS4059 standard, for particle counting, 1235
- ash
- definition of, 365
 - in diesel fuel oils, 259–260
 - microelemental analysis of, 1096
 - in petroleum coke, 1346
 - in petroleum pitch, 1339
 - quenching and, 1010
 - sulfated
 - detergents and percent, 422–423
 - microelemental analysis of, 1096
 - phosphorus, and sulfur (SAPS) limits, 356, 428
- ashless friction modifiers, 440
- asphaltene detergents, 66
- asphaltene dispersants (ADs), 67
- asphaltene flocculation inhibitors (AFI), 67–68, 68 (figure)
- asphaltene inhibitors (AIs), 66–67
- asphaltene precipitation envelope (APE), 47, 48, 55–56, 56 (figure)
- pressure-temperature curve of, 52, 52 (figure)
- asphaltenes
- aggregation behavior of, 55–56, 56 (figure)
 - chemical separation of crude oil from, 67–68, 68 (figure), 69 (figure)
 - composition and fractions of, 41, 41 (table)
 - conversion pathways of, in direct coal liquefaction, 126–127, 128 (figure)
 - crude oil and stability of, 39–40
 - definition of, 39, 40
 - density of, 46
 - deposition of
 - adsorption and, 63, 63 (figure)
 - attachment process in, 62
 - deposition process in, 62
 - overview of, 57–58
 - in porous media and production facilities, 61–63
 - possibility criteria for, 64–65, 65 (figure)
 - prevention methods for, 65–67, 66 (figure)
 - reversibility of, 63, 64 (figure)
 - wettability alteration and, 63, 64 (figure)
 - diffusion of, 46
 - downstream issues with, 41
 - EOR and, 39, 40
 - experimental and modeling studies in processing, 69
 - flocculation of, 57, 57 (figure), 67–68, 68 (figure)
 - hypothetical structures of, 42, 42 (figure)
 - interfacial characteristics of, 46
 - IOR and, 40
 - macrostructure of, 42–43, 43 (figure)
 - midstream issues with, 41
 - molecular weight of, 44–46, 45 (figure)
 - nanostructure of, 43–44, 43 (figure), 44 (figure)
 - petroleum oil studies on, 1151
 - MS for, 1161–1162, 1162 (figure)
 - phase behavior models for, 52–55, 54 (figure)
 - precipitation of
 - CO₂ injection and, 60–61, 61 (figure)
 - composition changes causing, 58, 58 (figure)
 - overview of, 57–58
 - possibility criteria for, 64–65, 65 (figure)
 - pressure changes causing, 58–60, 59 (figure), 60 (figure), 60 (table)
 - prevention methods for, 65–67, 66 (figure)
 - precipitation onset pressure measurement of, 47
 - acoustic-resonance technique for, 48, 49 (figure)
 - comparison of methods for, 51
 - electrical-conductance technique for, 50
 - filtration technique for, 49
 - gravimetric technique for, 48, 48 (figure)
 - HPM technique for, 49–50, 51 (figure)
 - IP-143 method for, 50–51
 - light-scattering technique for, 48–49, 50 (figure)
 - viscometric technique for, 50
 - solubility parameters and, 47
 - upstream issues with, 41
 - viscosity and, 46, 47 (figure)
- asphaltene-to-resin ratio, 64, 65 (figure)
- Association des Constructeurs Européens d'Automobiles (ACEA), 754, 839, 841
- Association of Natural Gasoline Manufacturers (ANGM), 150
- ASTM Slope, 1504, 1604
- ASTM standards and tests
- for additives, 500–502
 - for aerospace fuels, 1317
 - for antioxidants, 389
 - for automotive engine lubricants, 856–858
 - for aviation fuels, 235–236
 - for biodeterioration, 1265–1266
 - for carbon materials, 1355–1358
 - for cold flow properties, 1535–1536
 - for compressor lubricants
 - acid number, 706
 - air release, 704
 - antiwear agents, 708
 - autoignition temperature, 704
 - carbon residue, 706
 - CBT test, 710–711, 711 (table), 712 (figure)
 - compressor tests, 708–709, 709 (figure), 709 (table), 710 (figure), 710 (table), 711 (table)
 - corrosion, 704
 - demulsibility, 703–704
 - evaporation, 705, 705 (figure)
 - filter bowl compatibility test, 716
 - flash and fire points, 704
 - foaming tendency, 704
 - gas solubility, 711–715, 713 (figure), 713 (table), 714 (table), 715 (figure), 716 (figure)
 - heat transfer efficiency, 715–716
 - hydrolytic stability, 704

- IR spectroscopy, 706–707, 706 (figure)
- kinematic viscosity, 701–702
- liquid heptane washing test, 708, 708 (figure)
- oxidation, 707, 707 (figure)
- paint compatibility test, 716
- pour point, 703
- precipitation number, 706
- seals compatibility, 716
- specific gravity, 702
- specific heat, 715–716
- standards, 717–718
- thermal conductivity, 715–716
- viscosity of gas/liquid mixtures under pressure, 715
- water content, 703
- for corrosion, 470
 - diesel fuel oils, 1408
 - engine oils, 1408, 1410
 - gear oils, 1410
 - HDDEOs, 1410
 - industrial lubricants, 1410–1413, 1411 (figure), 1412 (figure), 1413 (figure), 1414 (figure)
 - lubricants, 1408, 1409 (table), 1410 (figure), 1410 (table)
 - lubricating greases, 1409 (table), 1413–1414, 1414 (figure), 1415 (figure), 1415 (table)
 - standards, 1415–1416
- D4814, for gasoline
 - AKI and, 196–197
 - alkyl lead content and, 200
 - copper corrosion test and, 200
 - driveability index and, 197–198, 198 (figure)
 - gasoline and ethanol blending and, 200
 - oxidation stability and, 201
 - phosphorus content and, 201
 - silver corrosion test and, 200
 - sulfur content and, 200–201
 - vapor pressure and, 198–200, 199 (figure)
 - volatility and, 197–200, 197 (figure), 197 (table)
 - washed and unwashed gum and, 201
 - water tolerance and, 201–202
- for diesel fuel oils, 266–269
- for DME, 153–154
- for elemental analysis, 1099, 1099 (table), 1101–1104
- for engine oils, 758–759
 - oxidation testing, 1385–1387, 1386 (figure), 1389 (figure)
- for environmental characteristics, 1560–1561
- for environmentally acceptable ester-based hydraulic fluids, 575–576
- for EP agents, 1692–1693
- for flow properties, 1508–1511, 1509 (figure), 1510 (figure), 1511 (table), 1513–1515
- for friction and wear, 1691–1692
- for fuel economy, 432, 432 (table)
- for fuel oils, 1328, 1329 (table), 1355–1358
- for gasoline, 204–206
- for GC, 1120–1123
 - analytical methods, 1113–1117
 - crude oils, 1119
 - hydrocarbon analysis, 1117–1118
 - lubricants and in-service engine oils, 1118–1119
 - simulated distillation methods, 1111–1113
- for gear lubricants
 - acid number, 745
 - air release, 749
 - base number, 747
 - CCS viscosity, 748
 - channel point FTM, 749
 - chlorine, 746
 - compatibility, 749
 - copper strip tarnish test, 743
 - corrosion, 749
 - cyclic durability test, 748
 - demulsibility, 747
 - dynamic seals test, 749
 - elemental content, 747
 - flash and fire points, 743
 - foaming, 746
 - four-ball EP test, 747
 - four-ball wear test, 746
 - FZG test, PITS, 749
 - FZG test, scuffing, 747–748
 - gear scoring test, 749
 - GFC oxidation test, 748
 - gravity, 744
 - high temperature foam inhibition, 748
 - insolubles, 746
 - low speed high torque hypoid test, 748
 - low-temperature properties, 747
 - nitrogen, 747
 - oxidation of EP oils, 747
 - phosphorus content, 746
 - pour point, 743
 - precipitation number, 742–743
 - rust inhibition, 746
 - seal compatibility, 748
 - shear stability, 749
 - standards, 750–751
 - storage stability, 749
 - sulfur, 746
 - synchronizer SSP 180 test, 748–749
 - thermal and oxidation stability, 748
 - Timken EP tester, 746–747
 - VI, 746
 - viscosity, 744
 - water content, 746
- for heat transfer fluids, 972–974
- for hydraulic fluids, 676–678
- for hydrocarbon base oils, 326 (table)
- for LC, 1109–1110, 1120–1123
- for LPG, 145, 174–175
 - DME and, 153–154
 - history of, 152–153
- for lubricants, 1069, 1070 (table)
 - carbon residue, 1077–1078, 1077 (table)
 - chlorinated solvent elimination in, 1081
 - foaming, 1079
 - insolubles, 1078–1079
 - international methods, 1080–1081
 - other methods, 1080
 - proficiency testing programs, 1080
 - standards, 1081–1083
 - volatility, 1079–1080
- for lubricating greases, 942
 - chemical analysis, 954–955
 - compatibility, 954
 - consistency, 943–944, 943 (figure), 944 (table)
 - consistency stability, 944
 - contamination, 953, 953 (figure)
 - corrosion, 952, 952 (figure)
 - discontinued standards, 955
 - elastomer compatibility, 953–954
 - EP agents and wear, 950–952, 951 (figure)
 - flow properties, 944–946
 - heat resistance, 946–948, 946 (figure), 947 (figure), 948 (figure)

- ignition test, 955
- oxidation stability, 948–950, 949 (figure), 950 (figure)
- oxidation testing, 1382–1385, 1384 (figure), 1385 (figure), 1386 (figure)
- standards, 957–958
- static bleed test, 954
- water content, 952–953, 953 (figure)
- for lubrication, 1621–1622
- for measurement processes, 1709
- for metalworking and machining fluids, 928–930
- for mineral oil heat transfer fluids, 963, 964 (table), 965
- for NMR spectroscopy, 1137–1138, 1138 (table), 1148
- for olefins, 349
 - C₄ olefins, 345–346
 - ethylene, 344
 - general, 346–348
 - propylene, 344–345
- for oxidation, 601–603, 602 (figure), 603 (figure), 604 (figure), 604 (table), 649–650, 649 (figure), 649 (table)
- for oxidation testing, antiwear
 - ASTM D943, 1370–1372, 1376 (figure), 1376 (table)
 - ASTM D2272, 1372–1373, 1377 (figure)
 - ASTM D4310, 1372, 1376 (table)
 - ASTM D6514, 1379
- for oxidation testing, engine oils, 1385–1387, 1386 (figure), 1387 (figure), 1389 (figure)
- for oxidation testing, gasoline
 - ASTM D4625, 1393–1394, 1395 (figure)
 - ASTM D381, 1390–1391, 1392 (figure)
 - ASTM D525, 1391, 1392 (figure), 1393 (figure)
 - ASTM D873, 1392–1393
 - ASTM D2274, 1393, 1394 (figure), 1395 (figure)
 - ASTM D3241, 1393
 - ASTM D6468, 1394–1395
 - ASTM D7525, 1395
 - ASTM D7545, 1396
- for oxidation testing, gear oils, 1379–1381, 1381 (figure), 1381 (figure), 1382 (figure)
- for oxidation testing, lubricants, 1396–1399, 1397 (figure), 1398 (figure)
- for oxidation testing, lubricating greases, 1382–1385, 1384 (figure), 1385 (figure), 1386 (figure)
- for oxidation testing, turbine oils
 - ASTM D2070, 1374–1376, 1378 (figure)
 - ASTM D4636, 1376–1377, 1379 (figure)
 - ASTM D5846, 1378–1379, 1380 (figure)
- for particle counting, 1233, 1235
- for PC-11 engine oils, 836
- for petroleum coke, 1355–1358
- for petroleum pitch, 1355–1358
- for petroleum waxes, 81, 81 (table), 110–112
- for pipeline corrosion, 1471
- for quenching
 - acid number, 1008
 - aqueous polymer quenchants, 1011–1016
 - ash content, 1010
 - biodeterioration monitoring procedures, 1016–1017, 1017 (figure)
 - carbon residue, 1009–1010
 - cooling curve analysis, 1010–1011, 1011 (figure), 1017, 1017 (figure), 1018 (figure)
 - flash point and fire point, 1008
 - fluid biodeterioration processes, 1016
 - GM quenchemeter test, 1010, 1010 (figure)
 - IR spectroscopy, 1008, 1009 (figure)
 - precipitation number, 1010
 - saponification number, 1008
 - specific gravity, 1008
 - standards, 1028–1029
 - used quenching oil, 1010–1011
 - viscosity, 1007–1008
 - water content, 1008–1009, 1009 (figure)
- for RON and MON, 193–194, 193 (table)
- for rust inhibitors, 604–605
- for static petroleum measurement, 1068
- for synthetic lubricants, 529–531
- for temperature measurement, 1277–1278
- for turbine lubricating oils and hydraulic fluids, 601–603, 602 (figure), 603 (figure), 604 (figure), 604 (table), 637–639
- for viscosity, 1506–1508, 1506 (table), 1507 (figure), 1508 (table)
- for volatility, crude oil distillation and
 - ASTM D2892, 1200–1201, 1201 (figure), 1202 (table)
 - ASTM D5236, 1201–1203, 1203 (figure), 1204 (table)
 - international methods compared to, 1203
 - precision values, 1200, 1200 (table)
- for volatility, distillation and
 - ASTM D86, 1172–1173, 1172 (figure), 1173 (figure), 1174 (table), 1175 (table), 1176 (table), 1177 (table), 1178 (table), 1180 (table)
 - ASTM D850, 1173–1174, 1174 (table), 1176, 1178 (table), 1180 (table)
 - ASTM D1078, 1174 (table), 1176–1178, 1179 (table), 1180 (table)
 - ASTM D1160, 1179, 1181–1182, 1182 (figure), 1183 (table), 1184 (table), 1186 (table), 1187 (table), 1189 (table), 1190 (table), 1192 (table), 1193 (table)
 - ASTM D7344, 1178–1179, 1180 (table)
 - ASTM D7345, 1179, 1181 (table)
 - importance of, 1171–1172
 - international standards compared to, 1182, 1193 (table)
- for volatility, flammability and
 - ASTM D56, 1194, 1196 (figure)
 - ASTM D92, 1194–1195, 1197 (figure)
 - ASTM D93, 1195–1196, 1198 (figure)
 - ASTM D1310, 1196
 - ASTM D3278, 1197, 1199 (figure)
 - ASTM D3828, 1197
 - ASTM D3941, 1197
 - ASTM D6450, 1198
 - ASTM D7094, 1198–1199
 - ASTM D7236, 1199
 - fire point and, 1195
 - flash point and, 1192–1194, 1194 (table), 1195 (table), 1196 (table)
 - international methods compared to, 1199–1200, 1200 (table)
- for volatility, vapor pressure and
 - ASTM D323, 1205–1206, 1207 (figure)
 - ASTM D1267, 1210–1211, 1210 (figure)
 - ASTM D2533, 1209–1210
 - ASTM D4953, 1206–1207, 1207 (figure)
 - ASTM D5188, 1209
 - ASTM D5190, 1207, 1208 (figure)
 - ASTM D5191, 1207–1208
 - ASTM D5482, 1208–1209
 - ASTM D6377, 1209
 - ASTM D6378, 1209
 - ASTM D7975, 1211
 - importance of, 1204–1205
 - international methods compared to, 1211, 1211 (table)
 - precision values for, 1206 (table)
 - summary of, 1205 (table)
- atmospheric gas oil (AGO), 2, 3 (table)

- atmospheric pressure chemical ionization (APCI), 1152, 1156
atmospheric pressure laser ionization (APLI), 1156–1157
atmospheric pressure photoionization (APPI), 1152, 1156
atomic absorption spectrometry (AAS), 1088, 1091 (table)
atomic-force-microscopy (AFM), 43
attenuated total reflectance (ATR), 1130, 1130 (figure)
austenite, 977, 978 (figure), 981, 982 (table)
autoclaves, for pipeline corrosion, 1456, 1458–1459, 1459 (figure)
autoignition
 combustion and, 1283–1284
 temperature
 of compressor lubricants, 704
 of gasoline, 202
 of heat transfer fluids, 968
automated tank gauges (ATGs), 1065
 fouling and, 1250, 1251 (figure)
automatic particle counters (APCs), 1215, 1229
automatic shutdown, heat transfer fluid safety and, 971
automatic transmission fluids (ATFs)
 cold flow properties of, 1526–1527
 friction modifiers and, 434, 436 (figure), 442
 hydraulic fluids and, 671
automotive engine design improvements, 769–772
automotive engine lubricants, 321–322, 753. *See also* engine oils;
 heavy-duty diesel engine oils
 additives for
 antioxidants, 765–766
 antiwear agents, 766–767, 767 (figure)
 balanced formulation, 768
 corrosion inhibitors, 766
 detergents, 768
 dispersants, 768
 emission-control and, 764
 EP agents, 767–768
 foam inhibitors, 769
 friction and, 764
 friction modifiers, 766
 PPDs, 768–769
 rust inhibitors, 766
 VI improvers, 768
 ASTM standards for, 856–858
 base stock composition for, 764–765
 engine design improvements and, 769–772
 engine operation effects on, 763–764
 friction and wear reduction for, 841
 additives, 848–849, 850 (figure), 851 (figure)
 alternative base stocks, 842–846, 843 (figure), 844 (table),
 845 (figure), 846 (figure)
 estolides, 847, 847 (table)
 hydrocarbons, 846–847, 847 (figure)
 low and ultra-low engine oils, 847–848, 848 (table),
 849 (figure)
 thin-film coatings, 849, 850 (figure), 851 (figure), 852
 tribological testing of Stribeck curves, 853, 854 (figure),
 855 (figure)
 uncoated steel, 852–853, 852 (figure)
 functions of, 763
 LSPI test for, 770–771, 771 (figure)
 timing chain-wear test for, 771, 771 (figure)
 vehicle emissions reduction and, 842, 842 (figure)
automotive engine oils. *See* engine oils
automotive gear lubricants
 historical development of, 732–733, 737 (table)
 viscosity of, 332 (table), 770
automotive service ratings, 443, 444 (figure)
Auto-Oil Air Quality Improvement Research Program, 183
auto propane, 169
- autorefrigeration, 162
aviation fuels. *See also* aerospace fuels
 ASTM standards for, 235–236
 freezing point of, 1524–1525, 1525 (figure), 1526 (figure)
 gasoline
 additives, 228, 228 (table)
 combustion and, 219–220
 contaminants in, 230, 230 (table)
 engines for, 212, 215
 flammability of, 222–223, 223 (figure), 223 (table)
 high aromatic content unleaded hydrocarbon, specifications
 for, 212, 213 (table)
 history of, 209, 212
 hydrocarbon unleaded, specifications for, 212, 212 (table)
 knock resistance, 220
 leaded, specifications for, 210 (table)
 in low temperature environment, 217
 manufacturing of, 225–226
 unleaded, specifications for, 211 (table)
 volatility of, 221
 water content in, 217, 218 (figure), 219
 gas turbine, 264–265
 jet fuel
 additives, 227–228, 227 (table)
 combustion and, 220–221, 220 (figure)
 contaminants in, 230
 diesel, 216–217
 engines for, 215–216, 216 (figure)
 flammability of, 222–223, 223 (figure), 223 (table)
 history of, 6, 212, 214 (table)
 in low temperature environment, 217, 218 (figure)
 manufacturing of, 226–227, 226 (table)
 product color of, 232
 specifications of, 6, 6 (table), 214 (table)
 viscosity and, 217, 218 (figure)
 visual appearance of, 232
 water content in, 217, 218 (figure), 219
 military specifications for, 236–237
 oxidation stability of, 224–225, 1392–1393
 performance requirements for
 aircraft range, 223
 combustion, 219–221, 220 (figure)
 corrosion, 223–224
 flammability, 222–223, 223 (figure), 223 (table)
 high temperature, 219, 219 (figure)
 low temperature, 217, 218 (figure), 219
 lubricity, 225
 metering, 223
 static electricity, 225
 storage stability, 224–225
 volatility, 221–222, 222 (figure)
 quality control for
 aircraft procedures for, 234
 contaminants, 229–230, 230 (table)
 contamination detection equipment, 232–233
 contamination removal equipment, 230–232, 230
 (figure)
 international procedures for, 233
 philosophy of, 229
 U.S. procedures for, 233, 233 (table), 234 (table)
 transportation of, 228–229
Avogadro's law, 683, 1322
- B**
Baader test, for biodegradable lubricants oxidation testing,
 1399–1400, 1400 (figure)
bainite, 978 (figure), 979

- ball bearings, greases, at elevated temperatures, 949
- ball bearing tests, 1688
- ball-on-cylinder lubrication evaluator (BOCLE), 225
- ball rust test, for engine oils, 759
- barrier-film lubricants, 898
- Bartlesville Energy Research Center (BERC) process, 299
- base number, for gear lubricants, 747
- base stocks, 29. *See also* hydrocarbon base oils
 - additives and properties of, 352–353
 - alternative
 - for automotive engine lubricants wear and friction reduction, 842–846, 843 (figure), 844 (table), 845 (figure), 846 (figure)
 - ester historical development, 844, 844 (table)
 - fuel economy of, 844–845, 845 (figure)
 - PAGs historical development, 846
 - tribology and, 843
 - antioxidants and, 386, 387 (figure), 388 (figure)
 - API categories of, 755–756, 755 (table)
 - for automotive engine lubricants, 764–765
 - of compressor lubricants
 - alkylbenzenes, 698
 - categories of, 694, 694 (table)
 - fluorinated, 697
 - mineral oils, 694–695, 694 (table), 695 (figure)
 - PAGs, 695–696, 696 (figure)
 - PAOs, 696, 696 (figure), 697 (figure)
 - phosphate esters, 695 (figure), 698
 - polyolesters, 695 (figure), 696–697
 - silicones, 697
 - synthetic, 695
 - for engine oils, 755–757, 755 (table)
 - for gear lubricants, 731, 737 (table)
 - hydraulic fluids and, 647–648, 648 (table)
 - lubricating greases and, 935–937, 936 (table)
 - metalworking fluids classification and, 875–879, 898–900, 899 (figure)
 - mineral oil heat transfer fluids and, 962–963, 962 (table)
 - oxidation susceptible structures of, 1363, 1364 (figure)
 - for turbine lubricating oils and hydraulic fluids
 - diesters and polyolesters, 595–596, 596 (table), 597 (figure)
 - hydrocarbon oils, 590, 591 (figure), 592 (table)
 - hydrocracked/hydrotreated, 592–593, 593 (table), 594 (figure)
 - PAGs, 593–595, 595 (table)
 - PAOs, 593, 595 (table)
 - solvent-refined types, 590, 592 (figure), 593 (table)
 - triaryl phosphates, 597–598, 598 (table)
- Beer's law, 1131
- beeswax, 79, 80 (figure)
- bench test, tribology test systems
 - block-on-ring test machine for, 1683–1685, 1684 (figure), 1685 (figure)
 - designing, 1675
 - four-ball EP test device for, 1683, 1683 (figure), 1684 (figure)
 - four-ball test device for, 1681, 1682 (figure)
 - four-ball wear test device for, 1682–1683, 1683 (figure)
 - linear reciprocation test machine for, 1688–1689, 1688 (figure)
 - multispecimen test machine for, 1687–1688, 1687 (figure)
 - pin-and-vee block device for, 1679–1680, 1680 (figure), 1681 (figure)
 - pin-on-disk device for, 1680–1681, 1681 (figure)
 - selection of, 1673, 1678–1679
 - tapping torque test machine for, 1686, 1686 (figure), 1687 (figure)
 - Timken EP tester for, 1685–1686, 1685 (figure), 1686 (figure)
- bending, metal-forming, 868, 893
- benzene, 12, 26
- benzene emission number (BEN), 185
- beverage bottle test, of hydrolytic stability, 1412, 1412 (figure)
- bias
 - in measurement processes, 1703–1704
 - monitoring, 1706–1707
- bio-accumulation factor (BAF), 1549–1550
- biochemical oxygen demand (BOD) test, 1545–1546
- biocides, 495
 - for pipeline corrosion control, 1454–1456, 1455 (figure), 1457 (table)
- biocompatibility, of hydrocarbon base oils, 318–319, 319 (table)
- bio-concentration factor (BCF), 1549–1550
- biocorrosion, biodeterioration and, 1244–1247, 1244 (figure), 1245 (figure), 1246 (figure), 1246 (table), 1247 (figure), 1248 (figure)
- biodegradability
 - environmental characteristics and, 1544–1549, 1545 (table), 1547 (table), 1549 (figure), 1550 (figure)
 - of EP agents, 461, 462 (table)
 - of hydraulic fluids, 676, 676 (figure)
 - of polyolesters and diesters, 516
 - of synthetic lubricants, 529, 529 (table)
- biodegradable lubricants, oxidation testing of, 1399–1400, 1400 (figure)
- biodeterioration. *See also* microbes
 - ASTM standards for, 1265–1266
 - biopolymers and, 1243
 - biosurfactants and, 1242–1243, 1243 (figure)
 - CE mapping for, 1259, 1260 (figure)
 - condition monitoring for, 1251
 - fuels and fuel systems, 1255–1258, 1256 (figure)
 - lubricants and lubricant systems, 1258–1259, 1258 (figure)
 - water-miscible metalworking fluids, 1252–1255, 1252 (figure), 1253 (figure), 1254 (figure)
 - correction strategies for
 - fuel systems, 1262–1264, 1263 (figure)
 - lubricant systems, 1264, 1264 (figure)
 - definition of, 1237
 - direct, 1242
 - of HFA and HFB fluids, 539–540
 - indirect, 1242–1243, 1243 (figure)
 - of lubricants, 1243
 - biocorrosion/MIC, 1244–1247, 1244 (figure), 1245 (figure), 1246 (figure), 1246 (table), 1247 (figure), 1248 (figure)
 - condition monitoring for, 1258–1259, 1258 (figure)
 - correction strategies for, 1264, 1264 (figure)
 - fouling, 1247–1251, 1248 (figure), 1249 (figure), 1250 (figure), 1251 (figure)
 - prevention strategies for, 1262, 1263 (figure)
 - monitoring procedures for, 1016–1017, 1017 (figure)
 - prevention strategies for
 - fuel systems, 1259–1262, 1261 (figure), 1261 (table)
 - lubricant systems, 1262, 1263 (figure)
 - processes of, 1016
 - root cause analysis of, 1259, 1260 (figure)
 - terms in, 1265
 - weak organic acids and, 1243
- biodiesel, 357
- biofilms, of microbes, 1240–1241, 1241 (figure)
- biofuels
 - LC and, 1110
 - microelemental analysis of, 1097, 1098 (table)
- biomass, fossil fuels and, 139–140
- biopolymers, 1243
- biosurfactants, 1242–1243, 1243 (figure)

biota-sediment accumulation factor (BSAF), 1549–1550
 black deposits, LPG and, 166–167
 “Blaugas,” 149
 blenders, 359
 blocking point, of petroleum waxes, 108, 109 (figure)
 block-on-ring test, 1683–1685, 1684 (figure), 1685 (figure)
 Blok's Critical Contact temperature model, 1592
 bobs and tapes, 1057
 boiling point, 26
 final, 1
 true, 347
 volatility and, 313–314, 314 (figure)
 boiling range
 of crude oil, 1, 3 (table)
 octane distribution through fuel, 194
 viscosity and, 312
 bomb combustion methods, in elemental analysis, 1088, 1091 (table)
 bomb oxidation test, 948–949, 949 (figure)
 bonded fuel, aviation fuel transportation and, 229
 boring operations, machining, 866
 boron nitride, 463, 464 (figure)
 boundary film formation, EP agents, 456–458, 456 (figure), 457 (figure), 458 (figure)
 boundary lubrication, 540, 871–872, 1599–1600, 1600 (figure)
 additives and, 443, 449, 452 (table), 1606, 1609–1612, 1609 (figure), 1609 (table), 1610 (figure), 1611 (figure), 1612 (table)
 antiwear agents and, 1612, 1612 (figure)
 EP agents and, 449, 452 (table), 1612–1613, 1613 (figure)
 friction modifiers and, 1606
 tribochemical wear, material surfaces and, 1606, 1607 (table)
 tribology TRL, oil types and, 1653–1654, 1654 (figure)
 Boyle's law, 683, 1318
 Brayton cycle, 1296–1297, 1297 (figure)
 brazing, 868–869
 British Standard (BS) viscometers, 1491
 broaching
 abrasive wear and, 1583, 1583 (figure)
 machining operations and, 866
 bronze corrosion, 468
 Brookfield viscometer, 747
 Broomwade 2050H Compressor Rig Test, 709, 709 (figure), 709 (table)
 BT-10 test, 1388
 btx recovery, in catalytic reforming, 12–13, 13 (figure)
 bulk material properties, wear and, 1574–1577
 bulk modulus, of base stocks, 352
 Bunsen coefficient, 712, 714
 buoyancy in air, of aerospace fuels, 1298–1299
 Bureau of Mines Correlation Index (BMCI), 334
 burnishing operations, machining, 866
 Burton, William Merriam, 333
 butadiene
 ASTM test methods and characterization of, 345–346
 peroxides in, 346
 production of, 342
 thermophysical properties of, 343 (table)
 butane, 145, 162. *See also* liquefied petroleum gas
 butane-butene mixtures, chlorides in, 346
i-butane, 336, 339
n-butane, 336, 339
 butane P-H diagram, 148 (figure)
 butene, thermophysical properties of, 343 (table)
 butylene, 342, 345

C

C_4 olefins
 ASTM test methods and characterization of, 345–346
 to finished product diagram, 335 (figure)
 thermal cracking for, 336, 339
 cadmium
 corrosion, aviation fuels and, 224
 test, of used oil, 33
 calcined coke, 1344–1346, 1346 (figure), 1346 (table), 1347 (table)
 calcium, in gas turbine fuel oils, 265 (table), 266
 calcium complex greases, 938, 940
 calcium fluoride (CaF_2), 463–464
 calcium soap greases, 938
 calcium sulfonate greases, 938–939, 941
 California Air Resources Board (CARB), 156, 183
 California Natural Gasoline Association, 151
 calorific values, of aerospace fuels, 1307–1308, 1308 (figure)
 Canadian Environmental Protection Act (CEPA), 184
 Canadian General Standards Board (CGSB), 145
 candelilla wax, 79, 80 (figure)
 Cannon-Fenske viscometers, 654
 carbon
 definition of, 365
 formation of, 366–367
 NMR spectroscopy quantitative analysis of, 1146–1147
 carbon anodes, for aluminum production, 1354
 carbon blacks, 1351–1353, 1352 (figure), 1353 (table)
 carbon cycle, 1238, 1238 (figure)
 carbon dioxide (CO_2)
 in crude oil, 1422
 partial pressure, pipeline corrosion and, 1437–1438
 carbon fibers, from petroleum pitch, 1353–1354, 1353 (table)
 carbonizable substances, of petroleum waxes, 104, 107 (figure)
 carbon materials, 1327
 ASTM standards for, 1355–1358
 carbon anodes for aluminum production, 1354
 carbon blacks, 1351–1353, 1352 (figure), 1353 (table)
 carbon fibers from petroleum pitch, 1353–1354, 1353 (table)
 graphite electrodes for electric-arc furnaces, 1354–1355
 carbon residue
 in compressor lubricants, 706
 in diesel fuel oils, 260
 in fuel oils, 1331 (table), 1332
 heat transfer fluids and, 967–968
 in lubricants, 1077–1078, 1077 (table)
 quenching and, 1009–1010
 carbonyls
 in C_4 olefins, 346
 IR spectroscopy and functionality of, 1125, 1125 (table)
 carbonyl sulfide, in propylene, 345
 carboxylate detergents, 421, 424 (figure)
 carboxylic acids
 detergent substrates and, 414–416, 416 (figure)
 environmentally acceptable ester-based hydraulic fluids and, 556–557, 557 (figure)
 oxidation and, 1364, 1368 (figure)
 carburetor deposits, 189
 carnauba wax, 79, 80 (figure)
 casinghead gasoline, 150
 cast iron chip test, for water-miscible metalworking fluids, 1413, 1413 (figure)
 catalytic reforming
 benzene concentration reduction in, 12
 btx recovery in, 12–13, 13 (figure)
 reactor configurations for, 10–11, 11 (figure)
 yield-octane relationship in, 12, 12 (figure)
 yields of, 12, 12 (table)

- catalytic two-stage liquefaction (CTSL) processing, 123–124, 124 (figure), 125 (table)
- Caterpillar Micro-Oxidation Test (CMOT), 1388, 1391 (figure)
- “cat” gasoline, 10
- cathodes, 1405
- cathodic reduction reactions, pipeline corrosion and, 1423
- cationic emulsifiers, 902–903, 903 (figure)
- cavitation
 - corrosion, 1585
 - definition of, 365
 - hydraulic fluids and, 661, 661 (figure)
 - wear, 1584, 1584 (figure)
- CE mapping, for biodeterioration, 1259, 1260 (figure)
- cementite, 978 (figure), 979
- central nervous system (CNS) effects, LPG exposure and, 172
- centrifugal compressors, rotary, 692, 692 (figure)
- centrifuges, for contamination removal, 923–924
- cetane index, 261–262, 262 (table)
- cetane number, 260–261
- CH-4. *See* engine oils, CH-4
- channel point FTM, for gear lubricants, 749
- Charles’s law, 683, 1318
- chemical analysis, of lubricating greases, 954–955
- chemical ionization (CI), 1152
- chemical methods, for asphaltene deposition prevention, 66
- chemical reactivity, load-carrying capacity compared to, 454, 455 (figure), 456
- chemisorption, 1606, 1609 (figure)
- Chevron catalyst technology, for mineral oil base stocks, 289–290
- China, direct coal liquefaction and, 124, 126 (figure), 126 (table)
- chlorides
 - alkylphenols and, 414, 415 (figure)
 - in butane-butene mixtures, 346
- chlorinated solvent elimination, in ASTM lubricant tests, 1081
- chlorine, 32
 - EP agents, 453, 458, 459 (figure)
 - in gear lubricants, 746
 - in turbine lubricating oils and hydraulic fluids, 629
- chord length, particle counting and, 1218, 1218 (table)
- chromatography, definition of, 1109. *See also* gas chromatography; liquid chromatography
- chromium acetylacetonate, antioxidants and, 386, 387 (figure)
- chromium test, of used oil, 33
- Chrysler Oxidation Test, 792
- CI-4/CI-4 PLUS. *See* engine oils, CI-4/CI-4 PLUS
- Cincinnati Milacron test, 1411–1412, 1412 (figure)
- Claus units, 25, 25 (figure)
- clay finishing, solvent extraction and, 35, 36 (figure)
- clay treatment vessels, 231
- Clean Air Act, 1963, 181
- Clean Air Act, 1970, 182
- Clean Air Act Amendments, 1977, 182
- Clean Air Act Amendments, 1990, 6, 183–184, 264
- clean-coke process, 117
- cleanliness
 - codes, particle counting and, 1220–1221, 1221 (table), 1232, 1232 (table)
 - of diesel fuel oils, 250–253, 251 (table), 252 (table)
 - of turbine lubricating oils and hydraulic fluids, 627–629
- Cleveland open cup (COC) method, 312, 743
- Closed Bottle Test, 1549
- cloud point, 7
 - of aqueous polymer quenchants, 1015, 1015 (figure)
 - definition of, 1521–1522
 - diesel fuel oils and, 248–249, 1523–1524, 1523 (figure), 1524 (figure)
 - freezing point of aviation fuels and, 1524–1525, 1525 (figure), 1526 (figure)
 - methods for determining, 1522–1523, 1522 (figure), 1522 (table)
 - of middle-distillate fuel oils, 1523
 - petroleum waxes and, 100–101, 102 (figure)
- CO₂ injection, asphaltene precipitation and, 60–61, 61 (figure)
- coal, structure of, 115, 116 (figure)
- coalescer blocking tendency (CBT) test, 710–711, 711 (table), 712 (figure)
- coalescers, for contamination removal, 924
- coal oil energy development (COED) process, 117
- coal tar pitch, 1333–1334. *See also* petroleum pitch
- coal-to-liquid conversion
 - carbon efficiency factors in, 138–140
 - direct coal liquefaction, solvent extraction and
 - asphaltene conversion pathways in, 126–127, 128 (figure)
 - catalytic conversion pathways in, 127, 128 (figure)
 - China and, 124, 126 (figure), 126 (table)
 - coal rank and, 126, 127 (figure)
 - Exxon donor solvent coal liquefaction process for, 119–120, 122, 123 (figure)
 - H-coal process for, 119, 121 (figure), 122 (figure)
 - Kohleol process for, 122, 123 (table)
 - light gas production, operating temperature and, 124, 126, 126 (figure)
 - LSE process for, 122
 - NEDO process for, 122, 124 (figure)
 - operation costs of, 129
 - plants for, 119, 120 (table)
 - product yields in, 119, 121 (figure)
 - SRC-I and SRC-II processes for, 119
 - temperature and reaction times in, 126, 127 (figure)
 - thermal pyrolysis pathway compared to, 128–129, 128 (figure), 129 (figure)
 - Wilsonville Pilot Plant, CTSL processing for, 123–124, 124 (figure), 125 (table)
 - environmental considerations in, 139–140
 - FTS and
 - cobalt catalyst in, 137, 137 (figure)
 - development of, 135–136
 - iron catalyst in, 137–138, 138 (figure)
 - operating plants for, 135, 135 (table)
 - reaction mechanism of, 136–138
 - ruthenium catalyst in, 136, 138, 139 (figure), 140 (figure)
 - indirect coal liquefaction and
 - methanol production and, 129–131, 130 (figure), 131 (figure)
 - MTG process for, 131–135
 - pyrolysis and
 - clean-coke process for, 117
 - COED process for, 117
 - current research on, 118–119
 - direct coal liquefaction pathway compared to, 128–129, 128 (figure), 129 (figure)
 - encoal process for, 118, 118 (figure)
 - Lurgi-Ruhrgas process for, 115–117
 - occidental process for, 118
 - reactions in, 115, 116 (figure)
 - Toscoal process for, 117, 117 (figure)
 - Union Carbide process for, 117–118
 - yield of volatile products in, 118, 119 (figure)
 - thermal efficiency factors in, 138
- cobalt, FTS and, 137, 137 (figure)
- CoBr test, 163, 164
- coefficient of friction, 108–109, 1565–1566, 1566 (figure)
- cogeneration, petroleum oil refining and, 25
- coker feedstocks, 1343–1344, 1344 (table), 1345 (figure)
- coking, delayed, 20–21, 20 (figure), 21 (table)
- coking value, of petroleum pitch, 1338–1339, 1339 (figure)

- cold-cranking simulator (CCS) viscosity, 315, 748, 759, 1530–1531, 1530 (figure)
- cold filter plugging point (CFPP), 1523–1524, 1524 (figure)
- Cold Filter Plugging Point (CFPP) test, 248–249
- cold flow properties, 1519. *See also* flow properties; low-temperature properties
- ASTM standards for, 1535–1536
- of ATFs, 1526–1527
- cloud point and
- definition of, 1521–1522
- diesel fuel oils and, 1523–1524, 1523 (figure), 1524 (figure)
- methods for determining, 1522–1523, 1522 (figure), 1522 (table)
- middle-distillate fuel oils and, 1523
- freezing point of aviation fuels and, 1524–1525, 1525 (figure), 1526 (figure)
- of gear oils, 1526–1527
- of hydraulic fluids, 1526–1527
- low-temperature pumpability of engine lubricants and, 1531–1535, 1531 (figure), 1532 (figure), 1533 (figure), 1534 (figure)
- of lubricants, 1525
- engine lubricants, 1528–1529, 1529 (table)
- low-temperature high-shear viscosity and, 1529–1531, 1529 (table), 1530 (figure), 1530 (table), 1531 (figure), 1531 (table)
- soot-containing, 1535
- turbine lubricants, 1526–1527, 1527 (figure)
- other standards for, 1537
- pour point and, 1520–1521, 1521 (figure)
- colloidal instability index (CII), 65, 65 (figure)
- color, of petroleum waxes, 104, 106 (figure)
- combustion
- aerospace fuels and
- emissions of, 1310–1311
- maximum temperature of, 1302, 1308
- autoignition and, 1283–1284
- cycle-to-cycle variation and, 1284–1285
- in diesel engines
- chamber development of, 1291–1294, 1292 (figure), 1293 (figure)
- fundamentals of, 1287–1290, 1288 (figure), 1289 (figure), 1290 (figure)
- dissociated products of, proportions of, 1322–1323, 1323 (table)
- EGR and, 1285, 1294
- energy release rate and, 1282
- flame propagation and, 1281–1283, 1281 (figure), 1282 (figure), 1283 (figure)
- laminar flame speed and, 1280
- regulated vehicle emissions and, 1285
- in SI engines
- chamber development of, 1283–1287, 1283 (figure), 1286 (figure), 1287 (figure)
- fundamentals of, 1279–1283, 1280 (figure), 1281 (figure), 1282 (figure)
- turbulence and, 1280–1281, 1281 (figure), 1285
- combustion chamber deposits (CCDs), 189–190
- compatibility. *See also* elastomer compatibility
- for compressor lubricants and seals, 716
- of corrosion inhibitors for pipeline corrosion chemical treatment, 1453–1454, 1454 (figure)
- filter bowl test, for compressor lubricants, 716
- of gear lubricants, 749
- of hydraulic fluids and seals, 666–667, 667 (table)
- lubricating greases and, 954
- material and paint, of HFA, HFB, HFC fluids, 546, 547 (table)
- paint test, for compressor lubricants, 716
- of turbine lubricating oils and hydraulic fluids, 629, 631–632, 631 (table)
- compound oils, 728, 729 (table)
- compressed natural gas (CNG), 431
- compressibility factor, 684
- compression, power requirement in, 685–687, 687 (table)
- compression ratio, ONR, 195
- compressor lubricants
- additives for, 698–700, 699 (table)
- ASTM tests for
- acid number, 706
- air release, 704
- antiwear agents, 708
- autoignition temperature, 704
- carbon residue, 706
- CBT test, 710–711, 711 (table), 712 (figure)
- compressor tests, 708–709, 709 (figure), 709 (table), 710 (figure), 710 (table), 711 (table)
- corrosion, 704
- demulsibility, 703–704
- evaporation, 705, 705 (figure)
- filter bowl compatibility test, 716
- flash and fire points, 704
- foaming tendency, 704
- gas solubility, 711–715, 713 (figure), 713 (table), 714 (table), 715 (figure), 716 (figure)
- heat transfer efficiency, 715–716
- hydrolytic stability, 704
- IR spectroscopy, 706–707, 706 (figure)
- kinematic viscosity, 701–702
- liquid heptane washing test, 708, 708 (figure)
- oxidation, 707, 707 (figure)
- paint compatibility test, 716
- pour point, 703
- precipitation number, 706
- seals compatibility, 716
- specific gravity, 702
- specific heat, 715–716
- standards, 717–718
- thermal conductivity, 715–716
- viscosity of gas/liquid mixtures under pressure, 715
- water content, 703
- base stocks of
- alkylbenzenes, 698
- categories of, 694, 694 (table)
- fluorinated, 697
- mineral oil, 694–695, 694 (table), 695 (figure)
- PAGs, 695–696, 696 (figure)
- PAOs, 696, 696 (figure), 697 (figure)
- phosphate esters, 695 (figure), 698
- polyolesters, 695 (figure), 696–697
- silicones, 697
- synthetic, 695
- classification of, 693 (table)
- gas solubility in, 324, 700, 700 (figure), 701 (figure), 702 (figure), 703 (figure), 711–715, 713 (figure), 713 (table), 714 (table), 715 (figure), 716 (figure)
- hydrocarbon base oils and, 324
- lubricant solubility in, 700–701, 703 (figure)
- lubrication requirements for, 701, 703 (table)
- performance demands of, 692–694
- purpose of, 683
- concentric cylinder viscometer, 1488, 1488 (figure), 1509, 1509 (figure)
- condition monitoring
- for biodeterioration, 1251
- fuels and fuel systems, 1255–1258, 1256 (figure)

- lubricants and lubricant systems, 1258–1259, 1258 (figure)
- water-miscible metalworking fluids, 1252–1255, 1252 (figure), 1253 (figure), 1254 (figure)
- IR spectroscopy and, 1133–1134, 1134 (figure), 1135 (figure)
- conductivity
 - of aqueous polymer quenchants, 1014, 1014 (figure)
 - of diesel fuel oils, 262, 263 (figure)
 - of gasoline, 203
- conductors, 1405
- cone and plate viscometer, 1488, 1488 (figure)
- cone penetration, lubricating grease consistency and, 943–944, 943 (figure), 944 (table)
- congealing point, petroleum waxes and, 98, 100
- consistency
 - definition of, 1486–1487
 - lubricating greases and, 943–944, 943 (figure), 944 (table)
- consistency stability, lubricating greases and, 944
- constant volume vane pump testing, 1691
- contact angle, of IL lubricants, 1041, 1042 (table)
- contamination
 - aviation fuels and
 - detection equipment for, 232–233
 - removal equipment for, 230–232, 230 (figure)
 - types of, 229–230, 230 (table)
 - in gasoline, 190
 - LPG and, 166–167
 - lubricating greases and, 953, 953 (figure)
 - metalworking fluids removal of, 923–925
 - in used oil, 30–31, 31 (table)
- continuous cooling transformation (CCT) diagrams, 979–980, 980 (figure)
- continuously variable transmission (CVT) fluids, 272, 322
- control charts, 1707–1708
- conventional oxidation catalyst (COC), 182
- conventional quenching oils, 1003
- conversion, detergents and, 423
- Cooperative Fuel Research (CFR) Committee, 180
- Co-ordination European Council (CEC) tests, 839, 841
 - for oxidation testing of gear oils, 1380–1382, 1382 (table), 1383 (figure), 1383 (table), 1384 (figure)
- copolymerization, of DVMs, 488
- copper corrosion
 - aviation fuels and, 223–224
 - chemistry of, 1406
 - of compressor lubricants, 704
 - corrosion inhibitors and, 468, 469 (figure)
 - in diesel fuel oils, 262–263
 - inhibitors, 189
 - chemistry of, 1407–1408, 1407 (figure)
 - lubricating greases and, 952, 952 (figure)
 - mechanism of, 468, 468 (figure)
 - test, 200
- copper ions, in oxidation, 1368, 1376 (figure)
- copper strip test, 743, 1408, 1409 (table), 1410 (figure), 1410 (table)
- Corporate Average Fuel Economy (CAFE) Standards, 431
- corrosion. *See also* copper corrosion; pipeline corrosion
 - acids and bases accelerating, 466–467
 - additives and, 371–372
 - ASTM tests for, 470
 - diesel fuel oils, 1408
 - engine oils, 1408, 1410
 - gear oils, 1410
 - HDDEOs, 1410
 - industrial lubricants, 1410–1413, 1411 (figure), 1412 (figure), 1413 (figure), 1414 (figure)
 - lubricants, 1408, 1409 (table), 1410 (figure), 1410 (table)
 - lubricating greases, 1409 (table), 1413–1414, 1414 (figure), 1415 (figure), 1415 (table)
 - standards, 1415–1416
 - aviation fuels and, 223–224
 - base stocks and, 353
 - bronze, 468
 - cadmium, 224
 - cavitation, 1585
 - of compressor lubricants, 704
 - costs associated with, 1405
 - damage from, 467
 - definition of, 365, 465
 - electrochemical, 466
 - in gear lubricants, 749
 - HFA and HFB fluids and, 540
 - HFC fluids and, 544
 - hydraulic fluid protection from, 664–666, 665 (figure), 666 (table)
 - hydrocarbon base oils and, 321, 321 (table)
 - iron, 467
 - of compressor lubricants, 704
 - lead, 470
 - in LPG, 166
 - lubricating greases and, 952, 952 (figure)
 - metal-removal fluids and protection from, 886
 - microbiologically influenced, 1244–1247, 1244 (figure), 1245 (figure), 1246 (figure), 1246 (table), 1247 (figure), 1248 (figure), 1454–1456
 - oxidation potentials and, 466, 466 (figure)
 - silver, 189, 200
 - steel, 224
 - turbine lubricating oils and hydraulic fluids and, 626–627
- corrosion coupons, weight loss measurements and, 1465–1466, 1466 (figure)
- corrosion inhibitors
 - acid neutralizers, 468
 - additives and, 470
 - aqueous polymer quenchants and, 1015–1016, 1015 (figure)
 - for automotive engine lubricants, 766
 - biodegradability of, 461, 462 (table)
 - chemistry of, 1407–1408, 1407 (figure)
 - for compressor lubricants, 698, 699 (table)
 - copper and, 468, 469 (figure)
 - detergents as, 427
 - for engine oils, 757
 - film formers, 468
 - for gear lubricants, 731
 - for hydraulic fluids, 666
 - lead and, 470
 - metallurgy in automotive equipment and, 467
 - metalworking and machining fluids and, 911, 912 (figure)
 - pipeline corrosion chemical treatment by
 - application methods of, 1452
 - classes of, 1450, 1451 (table)
 - operating conditions influencing, 1452–1453, 1453 (figure)
 - selection criteria for, 1452, 1452 (figure)
 - solubility, partitioning, and compatibility, 1453–1454, 1454 (figure)
 - structures of, 471 (figure)
 - surface activity of, 1406–1407, 1407 (figure)
 - for turbine lubricating oils and hydraulic fluids, 603–605, 605 (figure)
- corrosion rate (CR)
 - EIS for, 1468, 1469 (figure)
 - potentiodynamic anodic polarization and polarization resistance for, 1467–1468, 1467 (figure), 1468 (figure)

potentiostatic polarization for, 1468–1469, 1470 (figure)
 weight loss measurements for, 1465–1466, 1466 (figure)
 corrosion wear, 443, 888, 1584–1585, 1584 (figure), 1585 (figure)
 Council of European Union, 498, 500
 couplers, 495
 metalworking and machining fluids and, 903–904, 904 (figure)
 coupons, corrosion, 1465–1466, 1466 (figure)
 cranking torque, friction modifiers and, 441, 442 (figure)
 critical heat flux, quenching cooling curve analysis and, 1002, 1003 (table)
 critical nanoaggregate concentration (CNAC), 44
 critical pressure, 684, 684 (table)
 critical temperature, 684, 684 (table)
 crude oil
 aerospace fuels and, 1302–1303
 aromatics in, 281, 282 (figure)
 asphaltene chemical separation from, 67–68, 68 (figure), 69 (figure)
 asphaltene stability in, 39–40
 boiling ranges of, 1, 3 (table)
 classification of, 81, 81 (table)
 CO₂ in, 1422
 density of, 4
 GC analysis methods for, 1119
 H₂S in, 1422
 hydrocarbon composition in, 4, 280–281, 281 (figure), 1417, 1421–1422
 mercury in, 1096
 metals in, 4–5
 nitrogen in, 4
 O₂ in, 5, 1422
 preparation and separation of, 7–8, 8 (figure)
 quality and pricing of, 26
 refinery flow plan for, 1–2, 2 (figure)
 simulated distillation of, 1112–1113
 sulfur in, 4, 1422
 volatility ASTM standards for distillation of
 D2892, 1200–1201, 1201 (figure), 1202 (table)
 D5236, 1201–1203, 1203 (figure), 1204 (table)
 international methods compared to, 1203
 precision values, 1200, 1200 (table)
 water mixture with, pipeline corrosion and, 1417, 1418 (figure), 1420–1422, 1421 (table)
 waxy, 81–83, 82 (figure)
 crude oil gases, 1, 3 (table)
 crystalline structure, of petroleum coke, 1348–1349, 1349 (figure)
 crystal modifiers, 66
 cubic-plus-association (CPA) EOS model, 53
 cutting, definition of, 366
 cycle-to-cycle variation, combustion and, 1284–1285
 cyclic durability test, for gear lubricants, 748
 cyclo-alkanes, 281
 cyclohexane derivatives, 526
 cylindrical magnets, for contamination removal, 923–924

D

D02 test methods, in elemental analysis, 1088, 1089 (table), 1091 (table)
 Dalton's law, 684
 Damkohler number, 1281
 datum plates, 1056
 dead bottom samplers, 1061, 1061 (figure)
 deasphalted oil (DAO), 19–20, 20 (figure)
 de-asphalting, mineral oil base stocks and, 287, 293
 De Boer plot, 64, 65 (figure)
 debonding, biocorrosion and, 1246–1247, 1247 (figure), 1248 (figure)

deburring operations, machining, 867
 decomposition temperature, of IL lubricants, 1041, 1042 (table)
 decoupling, NMR spectroscopy and, 1140, 1141 (figure)
 defoamants. *See* foam inhibitors
 deformation
 friction due to, 1567
 tribology, Hertzian contact and, 1632–1635
 degasification, pipeline corrosion control and, 1445–1446, 1446 (figure)
 degree of overbasing, detergents and, 423
 dehydration, pipeline corrosion control and, 1446, 1447 (figure), 1448, 1448 (figure)
 de-icers, 188
 delamination wear, 1589–1590, 1590 (figure)
 delayed coking, 20–21, 20 (figure), 21 (table), 1340–1341, 1340 (figure), 1341 (table)
 Deming funnel experiment, 1707
 demulsibility
 of compressor lubricants, 703–704
 for gear lubricants, 747
 hydraulic fluids and, 660–661
 of industrial lubricants, 323
 turbine lubricating oils and hydraulic fluids and, 622–623
 demulsifiers, 470, 472, 473 (figure), 474, 661
 for gear lubricants, 731
 density
 of aerospace fuels, 1303
 of asphaltenes, 46
 of base stocks, 352
 of crude oil, 4
 of diesel fuel oils, 247
 of gasoline, 203–204
 of hydrocarbon base oils, 315
 of IL lubricants, 1038–1039, 1039 (table)
 LPG and, 155
 of petroleum coke, 1347–1348
 of petroleum pitch, 1339
 in static petroleum measurement, 1066–1067
 turbine lubricating oils and hydraulic fluids and, 618
 density test, of used oil, 31
 Department of Agriculture (USDA), 498, 499, 499 (figure)
 deposit formation
 dispersant control of, 390–391, 390 (figure), 391 (figure)
 lacquer and varnish, 367
 mechanism of, 366 (figure), 367, 367 (figure), 368 (figure), 369 (figure), 370–371
 precursors, 367–368, 369 (figure), 370 (figure)
 ring sticking and, 371
 sludge, 367
 soot and carbon, 366–367
 temperature and, 370, 370 (table)
 types of, 365–366
 deposit-modifying additives, 189–190, 363–366
 derived cetane number (DCN), 260–261
 desorption, environmental characteristics and, 1542
 desorption electrospray ionization (DESI), 1152
 detergents
 as antioxidants, 426–427, 427 (figure)
 asphaltene, 66
 for automotive engine lubricants, 768
 carboxylate, 421, 424 (figure)
 as corrosion inhibitors, 427
 dispersants compared to, 409–410, 426, 426 (figure)
 for engine oils, 757
 exhaust after-treatment systems and, 428, 429 (figure)
 film-forming agents and, 429–430, 429 (figure), 430 (figure)
 for gear lubricants, 730, 734 (table)

- hydraulic fluids and, 651
- micellar structure of basic, 425, 426 (figure)
- neutral and basic synthesis of, 417
 - carboxylate, 421, 424 (figure)
 - double decomposition reaction and, 419, 419 (figure)
 - idealized structures for, 419, 420 (figure)
 - novel overbased materials and, 421–422, 424 (figure)
 - phenate, 421, 422 (figure)
 - phosphonate, 421, 423 (figure)
 - process for, 419, 420 (figure), 421
 - promoters in, 418
 - salicylate, 421, 423 (figure)
 - sulfonate, 421, 422 (figure)
- parameters of
 - conversion, 423
 - degree of overbasing, 423
 - metal ratio, 422
 - percent sulfated ash, 422–423
 - soap content, 423
 - TBN, 423–425
- performance testing of, 425–429, 426 (figure), 427 (figure), 429 (figure)
- phenate, 421, 422 (figure), 428
- phosphonate, 421, 423 (figure), 428
- polar oxidation products of, 425, 426 (figure)
- port blocking, piston cleanliness and, 426, 426 (figure)
- salicylate, 421, 423 (figure), 428
- SAPS limits and, 428
- structure of, 410
- substrates
 - alkylphenols and, 413–414, 414 (figure), 415 (figure)
 - alkylphosphonic and alkylthiophosphonic acids and, 417, 417 (figure), 418 (figure)
 - alkylsalicylic acids and, 416, 417 (figure)
 - carboxylic acids and, 414–416, 416 (figure)
 - natural sulfonic acid, 412–413, 413 (figure)
 - nonacidic, 417, 418 (figure)
 - olefins in, 410–411, 410 (figure)
 - synthetic sulfonic acid, 411–412, 411 (figure), 412 (figure)
- sulfonate, 421, 422 (figure), 428
- types and uses of, 427–428
- detonation. *See* autoignition
- Deutsches Institut für Normung (DIN), 349
 - for biodegradable lubricants oxidation testing, 1399–1400, 1400 (figure)
 - for environmentally acceptable ester-based hydraulic fluids, 576–577
 - for friction and wear, 1693
 - for oxidation testing of turbine oils, 1379, 1380 (figure)
- dewatering, pipeline corrosion control and, 1446, 1447 (figure), 1448, 1448 (figure)
- dew point test, 163, 164, 1463, 1463 (figure)
- dielectric constant, gasoline and, 203–204
- diesel engines
 - combustion in
 - chamber development of, 1291–1294, 1292 (figure), 1293 (figure)
 - fundamentals of, 1287–1290, 1288 (figure), 1289 (figure), 1290 (figure)
 - corrosion ASTM tests for, 1408
 - direct injection, 1288, 1288 (figure)
 - flame structure in, 1289–1290, 1289 (figure)
 - fuel economy and, 431, 1291
 - improvements of, 761 (figure), 762–763, 762 (figure)
 - fuel injection splitting in, 1293–1294, 1293 (figure)
 - ignition delay in, 1288–1289, 1289 (figure)
 - indirect injection, 1288, 1288 (figure)
 - piston geometry in, 1292, 1292 (figure)
 - swirl generation in, 1292–1293
- diesel fuel oils
 - acid number and, 259
 - aromatics in, 256–257
 - ash in, 259–260
 - ASTM standards for, 266–269
 - carbon residue in, 260
 - cleanliness of, 250–253, 251 (table), 252 (table)
 - cloud point of, 248–249, 1523–1524, 1523 (figure), 1524 (figure)
 - conductivity of, 262, 263 (figure)
 - copper corrosion in, 262–263
 - demand for, 27
 - density of, 247
 - distillation of, 244
 - dyed, 264
 - energy content in, 257–258, 257 (table)
 - flash point of, 244–247, 247 (table)
 - ignition quality of, 260–262
 - jet, 216–217
 - low temperature operability of, 248–250, 249 (figure)
 - lubricity of, 255–256
 - pour point of, 249–250
 - quality of, 26
 - requirements for, 243 (table)
 - specifications of, 7, 7 (table), 239, 242 (table)
 - stability of, 253–255, 253 (figure), 255 (figure)
 - sulfur content in, 258–259, 259 (table), 264
 - viscosity of, 244, 263–264
 - volatility of, 244, 263
- diesel particulate filters (DPFs), 271
- diesters
 - application and performance characteristics of, 516–517
 - chemical characteristics of, 516
 - chemistry and manufacturing of, 513–515, 514 (figure)
 - physical properties of, 515–516
 - for turbines, 595–596, 596 (table), 597 (figure)
- differential scanning calorimeter (DSC), 314
- differential scanning calorimetry
 - petroleum waxes and, 92, 94, 96 (figure), 97–98, 97 (figure)
 - transition temperatures and, 103–104, 105 (figure)
- diffuse reflectance IR spectroscopy, 1130, 1130 (figure)
- diffusion, asphaltene, 46
- diffusion coating, solid lubricants and, 464
- diffusive wear, 888
- digital contact thermometers (DCTs), 1269, 1273 (figure), 1275–1277, 1276 (figure), 1276 (table), 1277 (figure), 1507
- dilauryl hydrogen phosphite (DLHP), 454, 455 (figure)
- diluents, for engine oils, 757
- dilution test, of used oil, 32
- dimethyl ether (DME), 153–154
- dip-cup viscometers, 1494 (figure)
- diphenylaminophenolics, antioxidants and, 386, 387 (figure)
- dipropylene glycol dehydration units, 1446, 1447 (figure)
- direct analysis in real time (DART), 1152
- direct biodeterioration, 1242
- direct coal liquefaction, solvent extraction and
 - asphaltene conversion pathways in, 126–127, 128 (figure)
 - catalytic conversion pathways in, 127, 128 (figure)
 - China and, 124, 126 (figure), 126 (table)
 - coal rank and, 126, 127 (figure)
 - Exxon donor solvent coal liquefaction process for, 119–120, 122, 123 (figure)
 - H-coal process for, 119, 121 (figure), 122 (figure)

- Kohleol process for, 122, 123 (table)
 light gas production, operating temperature and, 124, 126, 126 (figure)
 LSE process for, 122
 NEDO process for, 122, 124 (figure)
 operation costs of, 129
 plants for, 119, 120 (table)
 product yields in, 119, 121 (figure)
 SRC-I and SRC-II processes for, 119
 temperature and reaction times in, 126, 127 (figure)
 thermal pyrolysis pathway compared to, 128–129, 128 (figure), 129 (figure)
 Wilsonville Pilot Plant, CTSL processing for, 123–124, 124 (figure), 125 (table)
- direct imaging particle counting, 1226–1230, 1226 (figure), 1227 (figure)
- direct injection (DI) engines
 diesel, 1288, 1288 (figure)
 spark-ignition, 190, 1286–1287, 1287 (figure)
- dispersancy, 404
- dispersant polymers, 392, 401–402, 402 (figure), 403 (figure), 474–475
- dispersants
 amine, 392
 for automotive engine lubricants, 768
 definition of, 389
 deposit control by, 390–391, 390 (figure), 391 (figure)
 desirable properties of, 402–403
 dispersancy, 404
 seal performance, 406
 thermal and oxidation stability, 404–405
 viscosity, 405–406
- detergents compared to, 409–410, 426, 426 (figure)
 for engine oils, 757
- ester, 392, 398, 399 (figure)
- functions of, 389, 402–403
- for gear lubricants, 730, 734 (table)
- hydraulic fluids and, 651
- imidazoline, 398, 401 (figure)
- ionic, 398, 401, 401 (figure)
- Mannich, 392, 398, 399 (figure)
- metalworking and machining fluids and, 910, 911 (figure)
- performance testing of, 406–409, 408 (figure), 408 (table), 409 (table)
- phosphonic acid, 398, 399 (figure)
- polymeric, 391
 connecting group in synthesis of, 394–396, 394 (figure), 395 (figure), 396 (figure)
 hydrocarbon group in synthesis of, 392–394, 393 (figure)
 polar moieties in synthesis of, 396–401, 397 (figure), 399 (figure), 400 (figure), 401 (figure)
- structure of, 391–392, 391 (figure), 398, 400 (figure), 401 (figure)
- dispersant viscosity modifiers (DVMs), 392, 401–402, 402 (figure), 403 (figure)
 configurations of, 490–491
 grafting and copolymerization of, 488
 performance comparison of, 490, 491 (table)
 properties of, 488, 490
- dissociation constant, environmental characteristics and, 1542
- distillate fuel oils
 middle, cloud point of, 1523
 oxidation stability of, 1393, 1394 (figure), 1395–1396, 1395 (figure)
 storage stability of, 1393–1394, 1395 (figure)
 temperature stability of, 1394–1395
- distillation. *See also* crude oil, volatility ASTM standards for
 distillation of
 of diesel fuel oils, 244
 of fuel oils, 1331–1332, 1331 (table)
 GC and simulated, 1111–1113
 of heat transfer fluids, 969–970, 970 (figure)
 hydrotreating and, 34, 35 (figure)
 of mineral oil base stocks, 286–287
 vacuum, 286
 volatility ASTM standards for
 ASTM D86, 1172–1173, 1172 (figure), 1173 (figure), 1174 (table), 1175 (table), 1176 (table), 1177 (table), 1178 (table), 1180 (table)
 ASTM D850, 1173–1174, 1174 (table), 1176, 1178 (table), 1180 (table)
 ASTM D1078, 1174 (table), 1176–1178, 1179 (table), 1180 (table)
 ASTM D1160, 1179, 1181–1182, 1182 (figure), 1183 (table), 1184 (table), 1186 (table), 1187 (table), 1189 (table), 1190 (table), 1192 (table), 1193 (table)
 ASTM D7344, 1178–1179, 1180 (table)
 ASTM D7345, 1179, 1181 (table)
 importance of, 1171–1172
 international standards compared to, 1182, 1193 (table)
- distillation fractions, 1–2
- distortionless enhanced polarization transfer (DEPT) pulse sequences, 1141–1142, 1141 (figure), 1142 (figure)
- 2,6-ditertiarybutyl-4-methylphenol, 600, 600 (figure)
- dithiocarbamates, 447
- dithiocarbamic acid derivatives, synthesis of, 450 (figure)
- double bond equivalents (DBEs), 1158–1159, 1159 (figure)
- downhole heaters, 66
- Dowson equation, EHD lubrication and, 1600–1602
- drag reducer additive (DRA), 1120
- drawing, metal-forming, 868, 893 (table), 894 (table), 895 (table)
- Drayton agitation system, 998–999, 998 (figure)
- drilling operations, machining, 866
- driveability index, 197–198, 198 (figure)
- driveline lubricant additives, 358–359
- dropping point, lubricating grease heat resistance and, 946–947, 946 (figure)
- “dry” gas, 147
- dry machining, 889–890
- dyed diesel fuel, 264
- dyes, 495
 metalworking and machining fluids and, 914
- dynamic seals test, for gear lubricants, 749
- dynamic viscosity, 1486
- E**
- Eaton-Vickers 35VQ/25V vane pump test, 658–659
- eco-labeling, of lubricants, 499, 499 (figure), 500
- ecotoxicity assessments, 1558
- Edgar, Graham, 180
- elastic, definition of, 1487
- elastohydrodynamic (EHD) lubrication, 540, 1599–1600, 1600 (figure)
 Dowson equation and, 1600–1602
 film thickness and, 1600–1602, 1603 (figure)
 mixed-, 1603
 non-Newtonian and micro-, 1602–1603
- elastomer compatibility
 CI-4/CI-4 PLUS engine oils and, 831
 GF-5/SN and, 791
 for heat transfer fluid system, 971
 of hydrocarbon base oils, 318
 lubricating greases and, 953–954
 of turbine lubricating oils and hydraulic fluids, 631, 631 (table)

- electrical-conductance technique, for asphaltene precipitation
onset pressure, 50
- electrical conductivity, of base stocks, 353
- electric-arc furnaces, graphite electrodes for, 1354–1355
- electrochemical corrosion, 466
- electrochemical impedance spectroscopy (EIS), 1468, 1469 (figure)
- electrolytes, 1405
- electromagnetic radiation spectrum, 373 (figure)
- electronic control units (ECUs), 761
- electronic fuel injection (EFI) systems, 155
- electron ionization (EI), 1152
- electroplating, 869
- electrospray ionization (ESI), 1152, 1155–1156
- electrostatic stabilization, 390–391, 391 (figure)
- elemental analysis
AAS in, 1088, 1091 (table)
ASTM standards and tests for, 1099, 1099 (table), 1101–1104
bomb combustion methods in, 1088, 1091 (table)
D02 test methods in, 1088, 1089 (table), 1091 (table)
future developments in, 1101
GF-AAS in, 1088
ICP-AES in, 1088, 1091–1092, 1092 (table)
ICP-MS in, 1092–1093
IC technique in, 1093
international tests for, 1099, 1100 (table)
metals in petroleum products and, 1085, 1086 (table)
microelemental analysis methods
of ash and sulfated ash, 1096
of biofuels, 1097, 1098 (table)
of hydrogen, 1095–1096
of mercury in crude oil, 1096
of metals, 1096, 1097 (table)
NAA, 1093–1094
of nitrogen, 1096, 1096 (table)
precision of, 1094 (table)
of silicon, 1096
of sulfur, 1097, 1097 (table)
types of, 1093 (table)
XRF, 1094–1095, 1095 (table)
protocols for, 1085, 1086 (table)
quality control for, 1101
sample preparation in, 1085–1086, 1087 (table)
SRMs for, 1097–1098, 1099 (table)
wear metals in used oils and, 1086–1088, 1087 (table)
wet chemistry methods in, 1088, 1091 (table)
- elemental content, in gear lubricants, 747
- Elements of Chemistry* (Miller), 151–152
- emissions. *See* vehicle emissions
- emulsifiers, 470, 472, 473 (figure), 474, 474 (figure)
anionic, 902–903, 903 (figure)
cationic, 902–903, 903 (figure)
for gear lubricants, 731
HLB and, 901–902, 902 (figure)
metalworking fluid additives and, 900–903, 902 (figure), 902 (table)
micellar structure of, 882, 882 (figure)
nonionic, 902–903, 903 (figure)
- emulsion, 366, 470, 472, 474 (figure)
appearance of, 879, 879 (figure)
GF-5/SN and retention of, 791
hydrocarbon base oils and forming of, 320
in metalworking fluids, 877–879, 878 (figure), 878 (table), 879 (figure), 879 (table)
stability
of HFA and HFB fluids, 539
of metalworking fluids, 883
- encoal process, 118, 118 (figure)
- end film generation, Hertzian contact and, 1634–1635, 1634 (figure)
- energy content
of diesel fuel oils, 257–258, 257 (table)
of gasoline, 191
- energy-efficient technologies, 431, 432 (table)
- energy equation, 1325
- Energy Policy Act, 1992, 186
- Energy Policy Act, 2005, 186
- energy release rate, combustion and, 1282
- engine deposits, effects on ONR, 195
- engine design parameters, ONR, 194
- engine lubricants
cold flow properties of, 1528–1529, 1529 (table)
low-temperature pumpability of, 1531–1535, 1531 (figure), 1532 (figure), 1533 (figure), 1534 (figure)
- engine oil additives, 358, 757
- engine oils. *See also* heavy-duty diesel engine oils
ACEA system of, 754, 839, 841
API system of, 754–755
ASTM tests for, 758–759
oxidation testing, 1385–1387, 1386 (figure), 1387 (figure), 1389 (figure)
- CH-4, 797
bench tests, 798 (table)
Caterpillar 1K test, 800 (table)
Caterpillar 1N test, 800 (table)
Caterpillar 1P test, 799 (table)
Caterpillar 1R test, 800 (table)
Caterpillar C13 test, 801 (table)
Caterpillar Oil Aeration Test, 801 (table)
Cummins ISB, 801 (table)
Cummins ISM, 801 (table)
Cummins M11 300 h Extended Test, 801 (table)
Cummins M11 EGR, 801 (table)
Engine Oil Aeration Test, 803 (table)
engine tests, 799 (table)
HFRR tests, 799 (table)
HTC/T tests, 799 (table)
Mack T-8 (250 h), 802 (table)
Mack T-8E (300 h Extended Test), 802 (table)
Mack T-9, 802 (table)
Mack T-10, 802 (table)
Mitsubishi 4D34T, 803 (table)
OM 364 LA, 803 (table)
OM 441 LA, 803 (table)
OM 602 LA, 804 (table)
Sequence IIIIE, 803 (table)
Sequence IIIIF, 803 (table)
Sequence IIIIG, 803 (table)
- CI-4/CI-4 PLUS
Allison Graphite and Paper Friction Test, 830 (table)
API user language, 797
bench tests, 805 (table), 821 (table), 833
Caterpillar 1K test, 807 (table), 824 (table)
Caterpillar 1N test, 808 (table), 824 (table)
Caterpillar 1P test, 807 (table), 823 (table)
Caterpillar 1R test, 797, 807 (table), 823 (table), 831
Caterpillar 13 test, 825 (table)
Caterpillar C13 test, 808 (table)
Caterpillar Oil Aeration Test, 808 (table), 825 (table)
Caterpillar SEQ1220 test, 830 (table)
Caterpillar SEQFRRET test, 830 (table)
Cummins ISB test, 809 (table), 825 (table)
Cummins ISM test, 808 (table), 825 (table)
Cummins M11 300 h Extended Test, 809 (table), 825 (table)

- Cummins M11 EGR Test, 797, 809 (table), 825 (table)
 elastomer compatibility, 831
 Engine Oil Aeration Test, 811 (table), 828 (table)
 engine tests, 807 (table), 823 (table), 833
 HFRR test, 807 (table), 823 (table)
 HTCBT test, 807 (table), 823 (table)
 HTHS viscosity, 831
 introduction, 833
 Mack T-8E (300 h Extended Test), 809 (table),
 826 (table)
 Mack T-8 (250 h) Test, 809 (table), 826 (table)
 Mack T-9 Test, 809 (table), 826 (table)
 Mack T-10 Test, 797, 810 (table), 827 (table)
 Mack T-11/T-11A Test, 810 (table), 827 (table)
 Mack T-12 Test, 811 (table), 827 (table)
 Mack T-13 Test, 811 (table), 828 (table)
 MIL-PRF-2104J/MIL-PRF-2104K compared to,
 821 (table)
 Mitsubishi 4D34T, 811 (table), 828 (table)
 OM 364 LA, 812 (table), 829 (table)
 OM 441 LA, 812 (table), 829 (table)
 OM 602 LA, 812 (table), 829 (table)
 oxidation, 831
 Roller Follower Wear Test, 811 (table), 828 (table)
 Sequence IIIE, 811 (table), 828 (table)
 Sequence IIIF, 811 (table), 829 (table)
 Sequence IIIG, 812 (table), 829 (table)
 Volvo D12D460, 811 (table), 828 (table)
- CJ-4
 API user language, 834
 bench tests, 813 (table)
 Caterpillar 1K, 815 (table)
 Caterpillar 1P, 815 (table)
 Caterpillar 1R, 815 (table)
 Caterpillar C13, 816 (table), 834
 Caterpillar Oil Aeration Test, 816 (table)
 Cummins ISB, 817 (table), 834
 Cummins ISM, 816 (table), 834
 Cummins M11 300 h extended test, 817 (table)
 Cummins M11 EGR, 817 (table)
 drivers for development, 833–834
 early performance assessment, 835
 Engine Oil Aeration Test, 819 (table)
 fired-engine tests, 834–835
 HFRR test, 815 (table)
 HTCBT test, 815 (table)
 Mack T-8E (300 h Extended Test), 817 (table)
 Mack T-8 (250 h) Test, 817 (table)
 Mack T-9 Test, 817 (table)
 Mack T-10 Test, 818 (table)
 Mack T-11/T-11A Test, 818 (table)
 Mack T-12 Test, 818 (table), 835
 Mack T-13 Test, 819 (table)
 Mitsubishi 4D34T, 819 (table)
 OM 364 LA, 820 (table)
 OM 441 LA, 820 (table)
 OM 602 LA, 820 (table)
 Roller Follower Wear Test, 819 (table)
 Sequence IIIE, 819 (table)
 Sequence IIIF, 819 (table)
 Sequence IIIG, 820 (table)
 Volvo D12D460, 819 (table)
- CK-4, 837–838
 composition of
 additives, 358, 757
 base stocks, 755–757, 755 (table)
 formulation balance, 757–758
- corrosion ASTM tests for, 1408, 1410
 development of, 753–754
 drivers of quality, 321–322
 by duty cycle, 754
 elemental limits on, 361, 361 (table)
 engine design improvements and, 769–772
 FA-4, 837, 837 (figure)
 fuel economy and, 322
 diesel engine improvements, 761 (figure), 762–763,
 762 (figure)
 gasoline engine improvements, 760–762, 760 (figure)
- GF-4/SM
 aeration test, 779 (table)
 bench tests, 772–773, 773 (table), 774 (table), 775 (table)
 fired-engine tests, 772, 772 (table), 777 (table)
 GM aeration test, 780 (table)
 GM pre-ignition test, 780 (table)
 GM turbocharger deposits test, 780 (table)
 MB M111 fuel economy test, 779 (table)
 oil release test, 780 (table)
 Peugeot TU3M wear test, 779 (table)
 properties, 774 (table)
 Sequence IIIG, 777 (table)
 Sequence IIIGA, 777 (table)
 Sequence IVA, 778 (table)
 Sequence VG, 778 (table)
 Sequence VIB, 778 (table)
 Sequence VID, 779 (table)
 Sequence VIE, 779 (table)
 Sequence VIII, 779 (table)
 valve-train wear test, 780 (table)
- GF-5/SN
 aeration test, 789 (table)
 bench tests, 773, 782 (table), 783 (table), 787 (table),
 789 (table), 791
 elastomer compatibility, 791
 emulsion retention, 791
 fired-engine tests, 773, 785 (table)
 foam inhibitors, 791
 GM aeration test, 789 (table)
 GME fuel economy test, 790 (table)
 GM pre-ignition test, 789 (table)
 GM turbocharger deposits test, 790 (table)
 low-speed preignition prevention test, 788 (table)
 MB M111 black sludge test, 788 (table)
 MB M111 fuel economy test, 789 (table)
 MB M271 sludge test, 789 (table)
 oil release test, 790 (table)
 Peugeot TU3M wear test, 789 (table)
 Peugeot TU5JP-L4 test, 788 (table)
 properties, 782 (table)
 ROBO apparatus, 773, 791
 Sequence IIIG, 786 (table)
 Sequence IIIGA, 786 (table)
 Sequence IIIGB, 773
 Sequence IVA, 786 (table)
 Sequence VG, 786 (table)
 Sequence VIB, 787 (table)
 Sequence VID, 773, 787 (table)
 Sequence VIE, 787 (table)
 Sequence VIII, 788 (table)
 TEOST 33C, 773
 timing chain-wear test, 788 (table)
 valve-train wear test, 790 (table)
- GM dexos® specifications for, 791–792
 GM GEOS specifications for, 791
 heavy-duty, 272, 321

- hydraulic fluids and, 671
- ILSAC GF-6, 769–770
 - fired-engine tests, 795–796
 - GF-6A and GF-6B category split, 792–793
 - GMOD test, 793–795, 794 (table)
 - parts-depletion projections, 793
 - PC-11 split from, 792
 - replacement test development, 793
 - universal oils licensing, 793
- in-service, GC analysis methods for, 1118–1119
- LDD vehicles and, 796
- low and ultra-low, 847–848, 848 (table), 849 (figure)
- MIL-PRF-2104J/MIL-PRF-2104K
 - Allison Graphite and Paper Friction Test, 830 (table)
 - bench tests, 821 (table)
 - Caterpillar 1K test, 824 (table)
 - Caterpillar 1N test, 824 (table)
 - Caterpillar 1P test, 823 (table)
 - Caterpillar 1R test, 823 (table)
 - Caterpillar 13 test, 825 (table)
 - Caterpillar Oil Aeration Test, 825 (table)
 - Caterpillar SEQ1220 test, 830 (table)
 - Caterpillar SEQFRRET test, 830 (table)
 - CI-4 compared to, 821 (table)
 - Cummins ISB test, 825 (table)
 - Cummins ISM test, 825 (table)
 - Cummins M11 300 h Extended Test, 825 (table)
 - Cummins M11 EGR Test, 825 (table)
 - Engine Oil Aeration Test, 828 (table)
 - engine tests, 823 (table)
 - HFRR test, 823 (table)
 - HTCBT test, 823 (table)
 - intended use, 831–832
 - Mack T-8E (300 h Extended Test), 826 (table)
 - Mack T-8 (250 h) Test, 826 (table)
 - Mack T-9 Test, 826 (table)
 - Mack T-10 Test, 827 (table)
 - Mack T-11/T-11A Test, 827 (table)
 - Mack T-12 Test, 827 (table)
 - Mack T-13 Test, 828 (table)
 - Mitsubishi 4D34T, 828 (table)
 - OM 364 LA, 829 (table)
 - OM 441 LA, 829 (table)
 - OM 602 LA, 829 (table)
 - Roller Follower Wear Test, 828 (table)
 - SCPL, 832
 - Sequence IIIE, 828 (table)
 - Sequence IIIF, 829 (table)
 - Sequence IIIG, 829 (table)
 - Volvo D12D460, 828 (table)
- North American classification and specifications of, 759–760
- oxidation testing of
 - ABOT, 1388, 1390 (figure), 1390 (table)
 - ASTM tests, 1385–1387, 1386 (figure), 1387 (figure), 1389 (figure)
 - BT-10 test, 1388
 - CMOT, 1388, 1391 (figure)
- PC-10/CJ-4, 835
- PC-11, 835–837
 - viscosity of, 331 (table), 758, 759
- engine power loss, friction modifiers and, 440–441, 441 (figure)
- engine spark timing, ONR, 195
- enhanced oil recovery (EOR), 39, 40
- entraining velocity, tribology and, 1639–1640
- entrainment, 493
- environmental acceptability, of synthetic lubricants, 528–529, 529 (table), 548, 548 (table)
- environmental characteristics, of fuels and lubricants
 - abiotic degradation and, 1544
 - accumulation processes and, 1549–1550
 - adsorption and desorption and, 1542
 - ASTM standards for, 1560–1561
 - biodegradation and, 1544–1549, 1545 (table), 1547 (table), 1549 (figure), 1550 (figure)
 - chemical structure and, 1540, 1541 (table)
 - complex mixture toxicity and, 1555–1556
 - dissociation constant and, 1542
 - exposure and, 1551, 1554–1556
 - hazards and risk in, 1558
 - HLC and, 1541–1542
 - hydrolysis and, 1544
 - low solubility and, 1554–1555, 1554 (figure)
 - octanol-water partition coefficient and, 1540–1541
 - photolysis and, 1544
 - photooxidation and, 1544
 - standardized testing
 - methods of, 1551, 1551 (figure), 1552 (table)
 - rationale for, 1539–1540
 - toxicity tests, 1552 (table), 1556–1558, 1557 (figure)
 - terminology of, 1559–1560
 - transformation processes and, 1543–1544
 - transport processes and, 1543, 1543 (figure), 1543 (table)
 - vapor pressure and, 1541
 - volatility and, 1554
 - water solubility and, 1541, 1542 (figure)
- environmental compatibility, of metalworking and machining fluids, 922
- environmentally acceptable ester-based hydraulic fluids
 - alcohol bonds and, 555–556, 556 (figure)
 - ASTM standards for, 575–576
 - carboxylic acids and, 556–557, 557 (figure)
 - certification of, 574, 575 (figure)
 - classifications of, 675–676, 675 (table)
 - DIN standards for, 576–577
 - ecological tests for, 574, 574 (figure)
 - functional groups of, 555, 555 (figure)
 - functions and requirements of, 553–554, 554 (figure)
 - future developments for, 574–575
 - hydraulic aging test rigs for, 570–574, 571 (figure), 572 (figure), 573 (figure)
 - hydrolysis and, 558–560, 559 (figure), 560 (table)
 - hydrolytic stability of, 569–570, 570 (figure), 571 (figure)
 - ISO standards for, 576
 - low-temperature properties of, 564–566, 565 (figure)
 - lubrication and, 564, 564 (figure)
 - mineral oil mixtures with, 566
 - oxidation stability of, 560–561, 560 (figure), 561 (figure), 567–569, 568 (figure), 569 (figure)
 - resources and production of, 561–563, 562 (table), 563 (figure)
 - rheological properties of, 557–558, 558 (figure)
 - structure-performance considerations of, 561, 562 (table)
 - types of, 554–555, 554 (table)
 - verification of, 566–567, 567 (figure)
 - viscosity and, 564, 564 (figure)
- environmentally acceptable lubricants (EALs), 522, 529, 548, 1539
 - hydrocarbons as, 847
- environmentally assisted cracking (EAC), 1464–1465
- Environmental Protection Agency (EPA), 182, 499
 - EALs and, 522, 548
 - used oil criteria of, 922–923
 - used oil regulatory definition of, 297
 - VGP and, 522, 548, 548 (table)

- equations of state (EOS)
 of asphaltene phase behavior, 53–55, 54 (figure)
 for petroleum waxes, 88–89, 91–92, 91 (table), 93 (table), 94 (table), 95 (table)
- equipment calibration tests, 1707
- equivalent circle diameters, particle counting and, 1218, 1219 (table)
- Ernst angle, 1144
- erosion
 corrosion, 1430–1431, 1430 (figure)
 definition of, 366
 wear, 1584–1585, 1585 (figure)
- ester dispersants, 392, 398, 399 (figure)
- esterification, 513, 514 (figure), 515
- ester polymers
 comparison of, 491 (table)
 degradation-related viscosity loss and, 487–488, 490 (figure)
 mechanical shear and, 483
 shear-related viscosity loss and, 484–487, 486 (figure), 487 (figure), 488 (figure), 489 (figure)
 structures of commercially available, 484 (table)
 synthesis of, 481–484, 482 (figure), 483 (figure)
 thickening efficiency and, 484, 485 (figure)
- esters. *See also* environmentally acceptable ester-based hydraulic fluids
 benefits of, 843–844
 historical development of, 844, 844 (table)
- estolides, 847, 847 (table)
- ethane, 153. *See also* liquefied petroleum gas
 decomposition of, 336, 339
 ethylene from, 336
 from methane, 336
- ethanol
 gasoline blending with, 200
 history of, 185
 in propane, 163
- Ethanol Flex Fuel (E85), 186
- ethylene
 ASTM test methods and characterization of, 344
 from ethane, 336
 feedstock for, 334
 to finished product diagram, 334 (figure)
 historical production of, 333
 oligomerization of, 410–411
 production capacity for, global, 333, 338 (table)
 from propane, 336, 339
 thermophysical properties of, 343 (table)
- ethylene-propylene-diene monomer-derived copolymers (EPDMs), 478, 479
- ethylene-propylene rubbers (EPRs), 478, 479
- ethyl mercaptan (EtSH) odorants, 167, 169, 173
- European Automobile Manufacturers Association (ACEA), 353, 389
- evaporation
 of compressor lubricants, 705, 705 (figure)
 loss, lubricating grease heat resistance and, 947
- exhaust after-treatment systems, detergents and, 428, 429 (figure)
- exhaust gas recirculation (EGR), 355, 797, 1285, 1294
- expansion joints, for heat transfer fluid system, 972
- exposure, environmental characteristics and, 1551, 1554–1556
- extreme-pressure (EP) agents
 alkyl and aryl phosphate synthesis and, 448, 451 (figure)
 alkyl and aryl phosphite synthesis and, 448, 451 (figure)
 ASTM standards for, 1692–1693
 for automotive engine lubricants, 767–768
 automotive service ratings and, 443, 444 (figure)
 AWNs and, 452–453, 453 (figure), 453 (table)
- biodegradability of, 461, 462 (table)
 boundary film formation of, 456–458, 456 (figure), 457 (figure), 458 (figure)
 boundary lubrication and, 449, 452 (table), 1612–1613, 1613 (figure)
 chemical reactivity compared to load-carrying capacity and, 454, 455 (figure), 456
 chlorine, 453, 458, 459 (figure)
 common organophosphorus compounds as, 444, 445 (figure)
 for compressor lubricants, 698–699, 699 (table)
 conjunction temperature and protection requirements of, 449, 452 (figure)
 controlled wear of rough surfaces by, 458, 458 (figure)
 dithiocarbamic acid derivative synthesis and, 450 (figure)
 effectiveness of, 460, 461 (table)
 fatty acid and organic phosphate combined, 458, 459 (figure)
 film formation by, 444
 for gear lubricants, 729, 733 (table)
 hydraulic fluids and, 659
 load and, 453, 454 (figure)
 lubricating greases and, 950–952, 951 (figure)
 metalworking and machining fluids and, 905–910, 906 (figure), 907 (figure), 908 (figure), 909 (table), 910 (figure), 910 (table)
 olefin sulfurization and, 447–448, 448 (figure), 448 (table), 449 (figure), 450 (figure)
 oxidation of, for gear lubricants, 747
 passive, 909
 phosphorus content and, 454, 455 (figure)
 structures of, 443, 606 (figure), 906 (figure)
 sulfur, 458, 459 (figure), 908–909, 908 (figure), 909 (table)
 sulfurized products for greases and, 448, 448 (table)
 synergism of, 458, 459 (figure), 460–461, 460 (figure)
 thermal activation of, 1611, 1611 (figure)
 tribology terms of, 460, 461 (table)
 for turbine lubricating oils and hydraulic fluids, 605–608, 606 (figure), 607 (figure), 608 (figure)
 types of, 447–448
- extreme-pressure (EP) oils, 728, 729 (table)
- extrusion, metal-forming, 868
- Exxon donor solvent coal liquefaction process, 119–120, 122, 123 (figure)
- ## F
- falling viscometer, 1488–1489, 1489 (figure)
- FAME (fatty acid methyl ester), 357
- fatigue wear, 443, 1586, 1586 (figure), 1587 (figure)
- fatty acids, 414–416
 EP agent combining organic phosphate and, 458, 459 (figure)
- fatty acid test, of used oil, 32
- FCCU DO, 1340, 1343–1344
- Federal Test Procedure (FTP) emission bin standards, 185
- Feret diameters, particle counting and, 1218, 1218 (table)
- ferrite, 977, 978 (figure)
- ferrous corrosion inhibitors, 189
- fiber-reinforced polymers (FRPs), 1246–1247, 1248 (figure)
- filing operations, machining, 866
- filler, 1345
- film boiling (FB)
 factors influencing, 986, 987 (figure), 988, 988 (figure), 988 (table)
 shock, 988
- film-forming agents, 363–364, 468
 detergents and, 429–430, 429 (figure), 430 (figure)
 metalworking and machining fluids and, 904
- film-strength testing machines, 886–887, 886 (figure)

- film thickness
 - EHD lubrication and, 1600–1602, 1603 (figure)
 - of IL lubricants, 1041–1042
 - filterability, of hydraulic fluids, 663–664
 - filter bowl compatibility test, for compressor lubricants, 716
 - filter plugging, fouling and, 1247–1249, 1248 (figure), 1249 (figure), 1250 (figure)
 - filter-separators, 230–231, 230 (figure)
 - filtration, for contamination removal, 924
 - filtration technique, for asphaltene precipitation onset pressure, 49
 - final boiling point (FBP), 1
 - fire points
 - compressor lubricants and, 704
 - for gear lubricants, 743
 - quenching and, 1008
 - volatility and, 1195
 - fire resistance
 - hot surface tests for, 620–621
 - of hydraulic fluids, 545–546, 546 (table), 585, 671, 673–675, 673 (table), 674 (table)
 - spray ignition tests for, 620, 620 (figure), 621 (figure)
 - turbine lubricating oils and hydraulic fluids and, 620–622
 - wick tests for, 622, 622 (figure), 623 (figure)
 - fire safety, aerospace fuels and, 1311–1312
 - Fischer-Tropsch (F-T) process, 79–80, 80 (figure), 80 (table)
 - Fischer-Tropsch synthesis (FTS)
 - cobalt catalyst in, 137, 137 (figure)
 - development of, 135–136
 - iron catalyst in, 137–138, 138 (figure)
 - operating plants for, 135, 135 (table)
 - reaction mechanism of, 136–138
 - ruthenium catalyst in, 136, 138, 139 (figure), 140 (figure)
 - fish, in toxicity tests, 1556–1558, 1557 (figure)
 - Fives Cincinnati Thermal Stability Test, 650, 651 (table)
 - fixed bed hydrocracking, 22, 22 (table)
 - flame ionization detectors (FIDs), 154
 - flamelets in eddies, 1281, 1281 (figure)
 - flame stabilization, of aerospace fuels, 1309
 - flammability
 - of aerospace fuels, 1306
 - of aviation gasoline, 222–223, 223 (figure), 223 (table)
 - of gasoline, 202–203
 - of jet fuel, 222–223, 223 (figure), 223 (table)
 - LPG and, 170
 - volatility ASTM standards for
 - ASTM D56, 1194, 1196 (figure)
 - ASTM D92, 1194–1195, 1197 (figure)
 - ASTM D93, 1195–1196, 1198 (figure)
 - ASTM D1310, 1196
 - ASTM D3278, 1197, 1199 (figure)
 - ASTM D3828, 1197
 - ASTM D3941, 1197
 - ASTM D6450, 1198
 - ASTM D7094, 1198–1199
 - ASTM D7236, 1199
 - fire point and, 1195
 - flash point and, 1192–1194, 1194 (table), 1195 (table), 1196 (table)
 - international methods compared to, 1199–1200, 1200 (table)
 - flanges and fittings, for heat transfer fluid system, 971
 - flash point
 - compressor lubricants and, 704
 - diesel fuel oils and, 244–247, 247 (table)
 - of fuel oils, 1331, 1331 (table)
 - for gear lubricants, 743
 - heat transfer fluids and, 970
 - quenching and, 1008
 - used oil tests for, 32
 - volatility and, 312, 313 (figure), 314 (table), 1192–1194, 1194 (table), 1195 (table), 1196 (table)
 - flash temperature, wear and, 1592, 1593–1594, 1594 (figure), 1594 (table)
 - flexible fuel vehicles (FFVs), 186
 - flexicoking, 21
 - floating roof adjustment (FRA), 1067
 - flotation, for contamination removal, 925
 - flow loops, multiphase, 1456, 1458 (figure), 1459 (figure)
 - flow properties. *See also* cold flow properties
 - absolute viscosity of water and, 1505–1506, 1506 (table)
 - ASTM tests for, 1508–1511, 1509 (figure), 1510 (figure), 1511 (table), 1513–1515
 - historical measurement of, 1485
 - kinematic viscosity/temperature relationship and, 1497, 1498 (figure), 1499–1500, 1499 (figure), 1500 (table)
 - for lubricating greases, 944–946
 - nomenclature of, 1486–1487, 1486 (table)
 - of petroleum oil
 - kinematic viscosity and, 1489–1493, 1491 (table), 1492 (figure), 1492 (table), 1493 (figure), 1494 (figure)
 - kinematic viscosity history and, 1493–1496
 - Saybolt, short-capillary, and orifice viscometers for, 1496–1497
 - shear stability of polymer-containing oils and, 1511–1513, 1511 (figure), 1512 (figure)
 - standards for, 1515
 - VI and
 - calculation of, 1501, 1502 (table), 1503 (table), 1504, 1504 (table)
 - historical development of, 1501
 - pressure considerations for, 1504–1505, 1505 (figure)
 - uses of, 1500–1501
 - viscometer geometries for, 1487–1489, 1487 (figure), 1488 (figure), 1489 (figure), 1490 (table)
 - viscosity ASTM standards and, 1506–1508, 1506 (table), 1507 (figure), 1508 (table)
- flow protection, for heat transfer fluid system, 972
- fluid catalytic cracking, 1, 9–10, 9 (figure), 10 (table)
- fluid coking, 21, 1343, 1343 (figure)
- fluid friction, 871
- fluidity, definition of, 1486
- fluidized bed hydrocracking, 22, 22 (figure), 23 (table)
- fluid maintenance tests, for heat transfer fluids, 968–971
- fluid sampling, of heat transfer fluids, 969
- fluorescence correlation spectroscopy (FCS) technique, 45
- fluorescent indicator adsorption (FIA), 221, 306
- fluorinated base stocks, for compressor lubricants, 697
- foaming
 - aqueous polymer quenchants and, 1016
 - compressor lubricants and, 704
 - engine oils and, 759
 - gear lubricants and, 746
 - HFA and HFB fluids and, 540
 - HFC fluids and, 544
 - lubricants and, 1079
 - in metalworking fluids, 878–879
 - turbine lubricating oils and hydraulic fluids and, 619–620
- foam inhibitors, 492–494, 494 (figure)
 - for automotive engine lubricants, 769
 - for compressor lubricants, 699–700, 699 (table)
 - for engine oils, 757
 - for gear lubricants, 730, 748
 - GF-5/SN and, 791
 - hydraulic fluids and, 662, 662 (figure)

- metalworking and machining fluids and, 912–913, 913 (figure)
- for turbine lubricating oils and hydraulic fluids, 607–608, 608 (figure)
- Ford Mercon ABOT, 1388, 1390 (figure), 1390 (table)
- forging, metal-forming, 868
- formulators, 359
- fossil fuels, biomass and, 139–140
- fouling, biodeterioration and, 1247–1251, 1248 (figure), 1249 (figure), 1250 (figure), 1251 (figure)
- four-ball EP test, 747, 950–951, 951 (figure), 1683, 1683 (figure), 1684 (figure)
- four-ball tests, 1681, 1682 (figure)
- four-ball wear test, 654, 658, 658 (figure), 708, 746, 1682–1683, 1683 (figure)
- Fourier-transform ion cyclotron resonance (FT-ICR), 1152–1154, 1153 (figure)
- Fourier-transform ion cyclotron resonance mass spectrometry (FT-ICR-MS), 41
- Fourier-transform IR, 1127–1128, 1127 (figure), 1128 (figure)
- Fourier-transform nuclear magnetic resonance (FT-NMR), 1137–1138
- free water
 - aviation fuel quality control and, 232
 - definition of, 1066
 - static petroleum measurement and, 1058–1059
- freezing point, of aviation fuels, 1524–1525, 1525 (figure), 1526 (figure)
- fretting wear, 951, 1587–1588, 1587 (figure), 1588 (figure)
- friction. *See also* tribology test systems
 - adhesion and, 1567
 - ASTM standards for, 1691–1692
 - automotive engine lubricants reduction of, 841
 - additives, 848–849, 850 (figure), 851 (figure)
 - alternative base stocks, 842–846, 843 (figure), 844 (table), 845 (figure), 846 (figure)
 - estolides, 847, 847 (table)
 - hydrocarbons, 846–847, 847 (figure)
 - low and ultra-low engine oils, 847–848, 848 (table), 849 (figure)
 - thin-film coatings, 849, 850 (figure), 851 (figure), 852
 - tribological testing of Stribeck curves, 853, 854 (figure), 855 (figure)
 - uncoated steel, 852–853, 852 (figure)
 - coefficient of, 108–109, 1565–1566, 1566 (figure)
 - coefficient of kinetic, 108–109, 1565–1566, 1566 (figure)
 - definition of, 1565
 - deformation and, 1567
 - DIN standards for, 1693
 - fluid, 871
 - internal, 871
 - ISO standards for, 1693
 - kinetic, 871
 - lubrication and, 1565–1567, 1566 (figure), 1566 (table), 1567 (figure)
 - MFC, MFR and, 1616–1618, 1617 (figure), 1618 (table), 1619 (figure)
 - ploughing and, 1567, 1568 (figure)
 - solid, 871
 - true area of contact in, 1566–1567, 1566 (figure)
- friction modifiers, 430–432
 - adsorption and, 1611, 1611 (table)
 - ashless, 440
 - ATFs and, 434, 436 (figure), 442
 - for automotive engine lubricants, 766
 - boundary lubrication and, 1606
 - comparison of, 437–438, 440, 440 (figure), 441 (figure)
 - cranking torque and, 441, 442 (figure)
 - effect of, 433–434, 436 (figure)
 - for engine oils, 757
 - engine power loss and, 440–441, 441 (figure)
 - friction coefficients and film breakdown temperatures in, 437, 440 (table)
 - fuel economy and, 433, 435
 - for gear lubricants, 730
 - gear oils and, 442–443, 442 (table), 443 (figure)
 - lubrication as, 870–871
 - materials used for, 434–435
 - metal surfaces and, 436–437, 437 (figure), 438 (figure), 439 (figure)
 - metalworking and machining fluids and, 904–905, 904 (figure), 905 (figure)
 - molecular mass and coefficient of friction in, 437, 439 (figure)
 - organomolybdenum compounds as, 849
 - role of, 433, 435 (figure)
 - temperature and adsorption of, 437, 439 (figure)
- fuel cleanliness testing, 1215
- fuel economy
 - of alternative base stocks, 844–845, 845 (figure)
 - ASTM tests for, 432, 432 (table)
 - automotive engine design improvements for, 769–772
 - average car mileage and, 1978–2014, 431, 431 (figure)
 - diesel engines and, 431, 1291
 - improvements of, 761 (figure), 762–763, 762 (figure)
 - energy-efficient technologies and, 431, 432 (table)
 - engine oils and, 322
 - diesel engine improvements, 761 (figure), 762–763, 762 (figure)
 - gasoline engine improvements, 760–762, 760 (figure)
 - friction modifiers and, 433, 435
 - future trends in, 840 (figure)
 - lubricants and, 356
 - MB M111 test of, 779 (table), 789 (table)
 - resource conserving and, 431–432
 - shutdown time, start-up wear and, 432, 433 (figure)
 - standards for, 431
 - viscosity and, 432–433, 433 (figure), 434 (figure)
 - volatility and, 432, 434 (figure)
- fuel injection splitting, in diesel engines, 1293–1294, 1293 (figure)
- fuel injector deposits, 189
- fuel injector shear stability test (FISST), 1512, 1512 (figure)
- fuel oils. *See also* diesel fuel oils; environmental characteristics, of fuels and lubricants; fuel properties and test methods
 - API gravity of, 1328–1330
 - ASTM standards for, 1328, 1329 (table), 1355–1358
 - carbon residue in, 1331 (table), 1332
 - distillation of, 1331–1332, 1331 (table)
 - flash point of, 1331, 1331 (table)
 - grades of, 1327
 - heating value of, 1330, 1330 (figure)
 - instability and incompatibility of, 1333
 - oxidation stability of distillate, 1393, 1394 (figure), 1395–1396, 1395 (figure)
 - pour point of, 1331
 - requirements for, 240 (table)
 - specifications of, 7–8, 8 (table), 239, 239 (table), 1327–1328, 1328 (table), 1329 (table)
 - storage stability of distillate, 1393–1394, 1395 (figure)
 - sulfur in, 7–8, 1331 (table), 1332–1333
 - viscosity of, 1330–1331, 1331 (table)
- fuel properties and test methods, 242
 - acid number, 259
 - aromatics, 256–257
 - ash, 259–260
 - carbon residue, 260

cleanliness, 250–253, 251 (table), 252 (table)
 cloud point, 248–249
 conductivity, 262, 263 (figure)
 copper corrosion, 262–263
 density, 247
 distillation, 244
 energy content, 257–258, 257 (table)
 flash point, 244–247, 247 (table)
 ignition quality, 260–262
 low temperature operability, 248–250, 249 (figure)
 lubricity, 255–256
 pour point, 249–250
 stability, 253–255, 253 (figure), 255 (figure)
 sulfur, 258–259, 259 (table)
 viscosity, 244
 volatility, 244
 fuels and fuel systems condition monitoring, biodeterioration and, 1255–1258, 1256 (figure)
 fuses, aviation fuel quality control and, 231
 FZG test, 606–607, 607 (figure), 658, 658 (figure), 708
 for gear lubricants
 PITS, 749
 scuffing, 747–748
 rig, for tribology component test, 1689–1691, 1690 (figure), 1691 (figure)

G

galling, adhesive wear and, 1578–1579, 1582 (figure)
 galvanic corrosion, 1431, 1585
 gas chromatography (GC)
 ASTM standards for, 1120–1123
 analytical methods, 1113–1117
 crude oils, 1119
 hydrocarbon analysis, 1117–1118
 lubricants and in-service engine oils, 1118–1119
 simulated distillation methods, 1111–1113
 for butadiene, 345
 for butylene, 345
 drag reducer additive and, 1120
 future developments in, 1120
 historical development of, 1110–1111
 for hydrocarbon base oil analysis, 306
 LPG composition and, 155
 NMR spectroscopy compared to, 1137
 petroleum waxes composition by, 106–107
 for propylene, 344–345
 two-dimensional, 1155
 for volatility, 313
 gas chromatography and vacuum ultraviolet detection (GC-VUV), 1115
 gas chromatography-mass spectrometry (GC-MS), 1119–1120
 gas compression cycle, 684–687, 685 (figure), 686 (figure)
 gas compressors
 hypercompressors, 689–690
 reciprocating, 687–688, 688 (figure), 688 (table)
 rotary, 690–692, 690 (figure), 691 (figure), 692 (figure)
 types of, 687, 687 (figure)
 gas hydrates, 160–162
 gasification, 24
 gas laws, 683–684, 684 (table)
 gas-line antifreeze, 188
 gasoline. *See also* ASTM standards, D4814; methanol-to-gasoline process
 additives to, 188–190
 adiabatic flame temperature of, 202
 air-fuel ratio and stoichiometry of, 190–191
 alkyl lead compounds added to, 188

ASTM D4814 for, 196–202
 ASTM standards for, 204–206
 autoignition temperature of, 202
 aviation
 additives, 228, 228 (table)
 combustion and, 219–220
 contaminants in, 230, 230 (table)
 engines for, 212, 215
 flammability of, 222–223, 223 (figure), 223 (table)
 high aromatic content unleaded hydrocarbon, specifications for, 212, 213 (table)
 history of, 209, 212
 hydrocarbon unleaded, specifications for, 212, 212 (table)
 knock resistance, 220
 leaded, specifications for, 210 (table)
 in low temperature environment, 217
 manufacturing of, 225–226
 unleaded, specifications for, 211 (table)
 volatility of, 221
 water content in, 217, 218 (figure), 219
 casinghead, 150
 “cat,” 10
 combustion, 190–191
 composition of, 186–187
 conductivity of, 203
 density of, 203–204
 dielectric constant and, 203–204
 energy content of, 191
 ethanol blending with, 200
 flammability of, 202–203
 gum content in, 1390–1391, 1392 (figure)
 heat capacity, thermal conductivity, and heat of vaporization of, 203
 history of, 5–6, 6 (table)
 alkyl lead, 180–182
 Clean Air Act, 1963, 181
 Clean Air Act, 1970, 182
 Clean Air Act Amendments, 1977, 182
 Clean Air Act Amendments, 1990, 6, 183–184, 264
 ethanol, 185
 leaded gasoline, 179–180
 octane number ratings, 180–181, 181 (table)
 2004+ vehicle and fuel regulation, 184
 unleaded gasoline, 182
 vapor controls, 182–183
 vehicle emission standards, 181
 HoC of, 191, 202
 hydrocarbons in, 186–187, 187 (table)
 iron based organo-metallics in, 189
 MMT added to, 188
 MTG process yields and properties of, 132, 132 (table)
 octane number performance properties of
 AKI, 192–193, 193 (table)
 combustion and knock in engines, 191–192
 MON ASTM standards, 193, 193 (table)
 octane distribution through fuel boiling range, 194
 on-line analyzer octane rating, 194
 RON ASTM standards, 193–194, 193 (table)
 vehicle ONRs, 194–196
 oxidation stability of, 1392, 1392 (figure), 1393 (figure)
 oxidation testing of
 ASTM D381, 1390–1391, 1392 (figure)
 ASTM D525, 1391, 1392 (figure), 1393 (figure)
 ASTM D873, 1392–1393
 ASTM D2274, 1393, 1394 (figure), 1395 (figure)
 ASTM D3241, 1393
 ASTM D4625, 1393–1394, 1395 (figure)

- ASTM D6468, 1394–1395
- ASTM D7525, 1395
- ASTM D7545, 1396
- IP-467, 1396
- Rancimat test, 1396
- oxygenates added to, 5, 5 (table), 183–184, 187, 188, 188 (table)
- performance additives in, 189–190
- reformulated, 183–184
- refractive index of, 203–204
- specifications of, 6, 6 (table)
- static electricity and, 203
- trace constituents and contaminants in, 190
- unleaded, 182
- vehicle and fuel regulations, current, 184–186
- viscosity and lubricity of, 203
- gasoline direct injection (GDI) engines, 185
 - LSPI test for, 770–771, 771 (figure)
 - timing chain-wear test for, 771, 771 (figure)
- gasoline engines, fuel economy improvements of, 760–762, 760 (figure)
- gas-phase contaminants, pipeline corrosion control of, 1444–1445, 1445 (figure)
- Gas Processors Association (GPA), 150–152
 - olefin standards of, 349
- Gas Processor Suppliers Association (GPSA), 151
- gas solubility
 - in compressor lubricants, 324, 700, 700 (figure), 701 (figure), 702 (figure), 703 (figure), 711–715, 713 (figure), 713 (table), 714 (table), 715 (figure), 716 (figure)
 - of hydrocarbon base oils, 319, 319 (table)
 - in petroleum oil, 711–714, 713 (figure), 713 (table), 714 (table)
- gas-to-liquid (GTL) base stocks
 - benefits of, 293
 - oxidation stability of, 296, 297 (figure)
 - steps of, 293, 294 (figure), 295
 - viscosity of, 295–296, 296 (figure)
 - volatility of, 295, 296 (figure)
- gas turbine fuel oils. *See also* fuel properties and test methods
 - combustor air distribution in, 264, 265 (figure)
 - industrial compared to aviation, 264–265
 - PAGs and, 522
 - requirements for, 245 (table)
 - specifications of, 239, 242
 - trace metal limits in, 265–266, 265 (table)
- gas turbines, 582–583, 583 (figure)
 - aero-derivative, 585–586
 - heat input and removal for, 586, 588 (figure)
 - lubrication system for, 587 (figure)
- gated spin echo (GASPE) pulse sequences, 1142
- gauge hatches, 1056
- Gavrilov, Sergei, 333
- gear gam contact test, 1688, 1688 (figure)
- gear lubricants
 - additives for, 728
 - antiwear agents, 729–730, 733 (table)
 - chemically active, 731 (table)
 - chemically inert, 732 (table)
 - detergents, 730, 734 (table)
 - dispersants, 730, 734 (table)
 - EP agents, 729, 733 (table)
 - miscellaneous, 736 (table)
 - antioxidants for, 730–731, 735 (table)
 - API service designation for, 737–738, 737 (table), 738 (table), 739 (table)
 - ASTM tests for
 - acid number, 745
 - air release, 749
 - base number, 747
 - CCS viscosity, 748
 - channel point FTM, 749
 - chlorine, 746
 - compatibility, 749
 - copper strip tarnish test, 743
 - corrosion, 749
 - cyclic durability test, 748
 - demulsibility, 747
 - dynamic seals test, 749
 - elemental content, 747
 - flash and fire points, 743
 - foaming, 746
 - four-ball EP test, 747
 - four-ball wear test, 746
 - FZG test, PITS, 749
 - FZG test, scuffing, 747–748
 - gear scoring test, 749
 - GFC oxidation test, 748
 - gravity, 744
 - high temperature foam inhibition, 748
 - insolubles, 746
 - low-speed high torque hypoid test, 748
 - low-temperature properties, 747
 - nitrogen, 747
 - oxidation of EP oils, 747
 - phosphorus content, 746
 - pour point, 743
 - precipitation number, 742–743
 - rust inhibition, 746
 - seal compatibility, 748
 - shear stability, 749
 - standards, 750–751
 - storage stability, 749
 - sulfur, 746
 - synchronizer SSP 180 test, 748–749
 - thermal and oxidation stability, 748
 - Timken EP tester, 746–747
 - VI, 746
 - viscosity, 744
 - water content, 746
- automotive
 - historical development of, 732–733, 737 (table)
 - viscosity of, 332 (table)
- base stocks for, 731, 737 (table)
- compound oils, 728, 729 (table)
- corrosion inhibitors for, 731
- demulsifiers for, 731
- early, 721, 722 (table)
- emulsifiers for, 731
- EP oils, 728, 729 (table)
- foam inhibitors for, 730, 748
- friction modifiers for, 730
- function of, 721–722
- greases, 728, 729 (table)
- industrial, 741–742, 743 (table), 744 (table), 745 (table)
- MIL-PRF-2105E classification for, 739, 740 (table)
- OEM specifications for, 740–741, 742 (table)
- open gear compounds, 728, 729 (table)
- polymeric thickeners for, 730–731
- PPDs for, 730
- R&O oils, 728, 729 (table)
- SAE J306c viscosity classification for, 738, 740 (table)
- SAE J2360 classification for, 739–740, 740 (table), 741 (table)
- types of, 728, 729 (table)
- VI improvers for, 735 (table)

- gear oils, 322
 cold flow properties of, 1526–1527
 corrosion ASTM tests for, 1410
 friction modifiers and, 442–443, 442 (table), 443 (figure)
 oxidation testing of
 ASTM tests, 1379–1380, 1380 (figure), 1381 (figure),
 1382 (figure)
 CEC tests, 1382, 1382 (table), 1383 (figure), 1383 (table),
 1384 (figure)
 JIS-K2514, 1381, 1382 (table)
- gears
 failure modes of, 724–726, 724 (figure), 724 (table), 725 (figure),
 726 (figure)
 lubrication of, 723–724, 726–728, 726 (table), 727 (figure),
 727 (table), 728 (table)
 types of, 722–723, 723 (figure), 723 (table)
- gear scoring test, for gear lubricants, 749
- gel permeation chromatography (GPC), 392, 1016, 1016 (figure)
- General Motors (GM)
 aeration test, 780 (table), 789 (table)
 dexos[®] specifications, 791–792
 GEOS specifications, 791
 Oxidation and Deposits (GMOD) test, 792, 793–795, 794 (table)
 pre-ignition test, 780 (table), 789 (table)
 quenchometer test of, 1006, 1006 (figure), 1006 (table), 1010,
 1010 (figure)
 turbocharger deposits test, 780 (table), 790 (table)
- GF-4/SM. *See* engine oils, GF-4/SM
- GF-5/SN. *See* engine oils, GF-5/SN
- GFC oxidation test, for gear lubricants, 748
- glass capillary viscometers, 1495
- glass cell, for pipeline corrosion, 1460, 1462, 1462 (figure)
- glazing, definition of, 366
- Gledhill Shake Flask test, 1546
- gloss retention, of petroleum waxes, 107
- glycerol, 556, 556 (figure)
- glycerol monooleate (GMO) friction modifiers, 437–438, 440, 440
 (figure), 441 (figure)
- glycol, in HFC fluid composition, 541
- glycol/antifreeze content test, of used oil, 31
- glycol dehydration units, 1446, 1447 (figure)
- GME fuel economy test, 790 (table)
- goniometer, for pipeline corrosion, 1462–1463, 1462 (figure)
- gouging, abrasive wear and, 1583, 1583 (figure)
- GPA Midstream Association, 150
- GPSA Engineering Data Book*, 152
- grafting, of DVMs, 488
- graphite, 462–463, 463 (figure), 465
- graphite electrodes, for electric-arc furnaces, 1354–1355
- graphite furnace atomic absorption spectrometry (GF-AAS), 1088
- graphitic carbon, 1345
- graphitizable carbon, 1345
- graphitizable heat treatment, 1345
- gravimetric technique, for asphaltene precipitation onset pressure,
 48, 48 (figure)
- gravity
 API, 247, 261
 of fuel oils, 1328–1330
 static petroleum measurement and, 1066–1067
 for gear lubricants, 744
 specific
 of compressor lubricants, 702
 of heat transfer fluids, 968
 of hydrocarbon base oils, 315, 315 (table)
 quenching and, 1008
- greases. *See* lubricating greases
- green coke, 1345–1346, 1346 (figure), 1346 (table)
- greenhouse gases (GHGs), 271. *See also* vehicle emissions
- grinding
 abrasive wear and, 1583, 1583 (figure)
 machining operations and, 866
- grist, 1345
- Grossman hardenability, 983–985, 984 (figure), 984 (table), 985
 (figure), 985 (table)
- gross observed volume (GOV), 1066
- gross standard volume (GSV), 1066
- gum content, in gasoline, 1390–1391, 1392 (figure)
- ## H
- H1 grease production, 941
- halocarbons, LPG and, 167
- halogen test, of used oil, 32
- Handbook of Butane-Propane Gases*, 151, 152
- hardenability, of steel, 980–981, 980 (figure), 981 (figure),
 982 (table)
 measurement of, 982–985, 983 (figure), 984 (figure),
 984 (table), 985 (figure), 985 (table)
- hardening power, modified Segerberg, 1000–1001, 1001 (figure)
- hardness, 1575
 petroleum waxes and, 102–103, 104 (figure)
- H-coal process, 119, 121 (figure), 122 (figure)
- Health Canada, 499
- health effects, LPG exposure and, 171–172
- health issues, in aerospace fuels handling, 1315
- heat capacity
 of base stocks, 352
 of gasoline, 203
 of IL lubricants, 1041, 1042 (table)
- heating value, of fuel oils, 1330, 1330 (figure)
- heat-liberating chemicals, 66
- heat of combustion (HoC), 191, 202
 test methods for, 257–258, 257 (table)
- heat of fusion, of petroleum waxes, 97–98, 97 (figure), 98 (table)
- heat of vaporization, of gasoline, 203
- heat resistance, lubricating greases and, 946–948, 946 (figure),
 947 (figure), 948 (figure)
- heat transfer
 efficiency, compressor lubricants and, 715–716
 hydraulic fluids and, 645, 647 (table)
- heat transfer coefficient (HTC), 959–960, 1002, 1003 (table),
 1020, 1021
- heat transfer fluids
 acid number and, 969, 969 (figure)
 ASTM standards for, 972–974
 autoignition temperature of, 968
 carbon residue and, 967–968
 design and construction of systems for, 971–972
 distillation of, 969–970, 970 (figure)
 flash point and, 970
 fluid maintenance tests for, 968–971
 fluid sampling of, 969
 HTC and, 959–960
 insolubles in, 971
 ISO classification of, 959, 961 (table)
 metal content of, 968, 968 (table)
 mineral oil, composition of, 961–965, 962 (figure), 962 (table),
 963 (table), 964 (figure), 964 (table)
 oxidation stability of, 967
 pressure drop and, 961, 961 (table)
 properties of, 959, 960 (table), 965–968, 966 (table)
 pumpability of, 966–967
 rubber and, 968
 safety and, 971
 seals and, 968

- secondary coolants and, 959, 960 (table)
- specific gravity of, 968
- specific heat of, 968
- synthetic, composition of, 965
- thermal conductivity of, 968
- thermal stability of, 967
- viscosity of, 966, 970, 970 (table)
- water content in, 970–971
- heat-treatment, metalworking operations and, 869
- heavy-duty diesel engine oils (HDDEOs), 351
 - corrosion ASTM tests for, 1410
 - fired-engine test progression for, 796
 - lubricant development trends in, 354–355
- heavy-duty diesel (HDD) lubricants, 271
- heavy-duty engine oils (HDEOs), 272, 321, 754
- heavy straight run naphtha (HSR), 1, 3 (table)
- heavy vacuum gas oils (HVGs), 2, 3 (table)
- Henry's law, 711, 712
- Henry's law constant (HLC), 1541–1542
- heptane, 180–181, 181 (table)
- Hertzian contact, 1571, 1571 (figure)
 - end film generation and, 1634–1635, 1634 (figure)
 - line contact and, 1634
 - lubrication and, 1600–1605
 - point contact and, 1633
 - tribology, deformation and, 1632–1635
- heteroatom removal, 15–18
- heterocyclics, 281–282, 282 (figure)
- heteronuclear correlation (HETCOR) spectra, 1142, 1143 (figure)
- heteronuclear multiple-quantum correlation (HMQC) pulse sequences, 1142
- heteronuclear single quantum coherence (HSQC) pulse sequences, 1142
- HFA and HFB fluids
 - applications of, 537, 538 (table)
 - composition of, 535–537, 536 (table), 537 (table)
 - fire resistance of, 545–546, 546 (table), 673–674, 673 (table)
 - general features and chemistry of, 535
 - manufacturing of, 537
 - material and paint compatibility of, 546, 547 (table)
 - properties of, 537–540
 - pump derating and, 547–548, 547 (table)
 - pump performance testing of, 546, 546 (table)
- HFC fluids, 535
 - applications of, 542–543
 - composition of, 541–542, 541 (figure), 542 (table)
 - fire resistance of, 545–546, 546 (table), 673 (table), 674
 - general features of, 540–541
 - manufacturing of, 542
 - material and paint compatibility of, 546, 547 (table)
 - properties of, 543–545, 543 (table), 544 (figure), 545 (table)
 - pump derating and, 547–548, 547 (table)
 - pump performance testing of, 546, 546 (table)
- HFD fluids, 535
 - fire resistance of, 673 (table), 674–675
- HH fluids, 670, 671 (table)
- high-mobility multipurpose wheeled vehicle (HMMWV) simulation
 - hypoid gear mesh in, 1660–1662, 1660 (figure), 1661 (figure), 1662 (figure), 1663 (figure)
 - RIP concept oil and, 1662–1664, 1663 (figure), 1664 (figure)
- high oleic sunflower oil (HOSO), 561, 562 (table)
- high-performance liquid chromatography (HPLC), 306, 1110
- high-pressure differential scanning calorimetry (PDSC), 524, 524 (table)
- high-pressure microscope (HPM) technique, for asphaltene precipitation onset pressure, 49–50, 51 (figure)
- high-pressure oxygen turbopump (HPOTP), 1631
- high-strength low-alloy (HSLA) steel, 1440–1441, 1441 (figure), 1441 (table)
- high-temperature, high-shear (HTHS) viscosity, 272, 759, 1508–1511, 1509 (figure), 1510 (figure), 1511 (table)
 - CI-4/CI-4 PLUS engine oils and, 831
- high-temperature copper bearing test, for engine oils, 759
- high-velocity rig, for pipeline corrosion, 1460, 1461 (figure)
- high-viscosity polyalphaolefins (HiVis PAOs), 478
- Hildebrand solubility parameters, for hydrocarbon base oils, 316, 317 (figure), 317 (table)
- HL fluids, 671, 671 (table)
- HM fluids, 671, 671 (table)
- horizontal disk test, for steam turbine oils, 1412
- horizontal rotating cylinder (HRC) setups, for pipeline corrosion, 1459–1460, 1460 (figure)
- hot oiling, 66
- hot surface tests, for fire resistance, 620–621
- hot tack, of petroleum waxes, 110
- Houillon viscometers, 1495, 1496 (figure)
- HPHM and HPHV fluids, 671, 671 (table), 672 (table)
- humidity cabinet, rust inhibitors and, 1411, 1412 (figure)
- Humphrey, Robert, 333
- HV fluids, 671, 671 (table)
- hybrid-electric vehicles (HEVs), 431
- hydraulic aging test rigs, 570–574, 571 (figure), 572 (figure), 573 (figure)
- hydraulic environmental ester synthetic (HEES), 554, 554 (table), 675, 675 (table)
- hydraulic environmental polyalphaolefine and related products (HEPR), 554 (table), 555, 675 (table), 676, 676 (figure)
- hydraulic environmental polyglycoles (HEPG), 554–555, 554 (table), 675–676, 675 (table)
- hydraulic environmental triglyceride (HETG), 554, 554 (table), 675, 675 (table)
- hydraulic fluids. *See also* HFA and HFB fluids; HFC fluids; turbine lubricating oils and hydraulic fluids
 - aeration and, 661–662, 662 (table)
 - antioxidants and, 650–651, 651 (figure), 652 (figure)
 - antiwear agents and, 659
 - ASTM standards for, 676–678
 - ATFs and, 671
 - base stocks and, 647–648, 648 (table)
 - biodegradability of, 676, 676 (figure)
 - cavitation and, 661, 661 (figure)
 - cold flow properties of, 1526–1527
 - corrosion inhibitors, rust inhibitors, metal passivators for, 666
 - corrosion protection for, 664–666, 665 (figure), 666 (table)
 - demulsibility and, 660–661
 - detergents and dispersants and, 651
 - engine oils and, 671
 - environmentally acceptable ester-based
 - alcohol bonds and, 555–556, 556 (figure)
 - ASTM standards for, 575–576
 - carboxylic acids and, 556–557, 557 (figure)
 - certification of, 574, 575 (figure)
 - classifications of, 675–676, 675 (table)
 - DIN standards for, 576–577
 - ecological tests for, 574, 574 (figure)
 - functional groups of, 555, 555 (figure)
 - functions and requirements of, 553–554, 554 (figure)
 - future developments for, 574–575
 - hydraulic aging test rigs for, 570–574, 571 (figure), 572 (figure), 573 (figure)
 - hydrolysis and, 558–560, 559 (figure), 560 (table)
 - hydrolytic stability of, 569–570, 570 (figure), 571 (figure)
 - ISO standards for, 576

- low-temperature properties of, 564–566, 565 (figure)
- lubrication and, 564, 564 (figure)
- mineral oil mixtures with, 566
- oxidation stability of, 560–561, 560 (figure), 561 (figure), 567–569, 568 (figure), 569 (figure)
- resources and production of, 561–563, 562 (table), 563 (figure)
- rheological properties of, 557–558, 558 (figure)
- structure-performance considerations of, 561, 562 (table)
- types of, 554–555, 554 (table)
- viscosity and, 564, 564 (figure)
- EP agents and, 659
- fire resistance of, 545–546, 546 (table), 585, 671, 673–675, 673 (table), 674 (table)
- foam inhibitors and, 662, 662 (figure)
- heat transfer and, 645, 647 (table)
- hydrolytic stability and, 659–661
- ISO standards of, 678–679
- low-temperature properties of, 668–669, 668 (table)
- lubrication and, 645–646
- military specifications for, 679
- mineral oils for, 670–671, 671 (table), 672 (table)
- moisture analyzers and, 660
- oxidation stability of, 648–651, 648 (figure), 649 (figure), 649 (table)
- performance comparison of, 324, 324 (table)
- power transfer and, 645, 646 (figure)
- PPDs and, 669
- rheology of, 667–670
- seal compatibility with, 666–667, 667 (table)
- shear stability of, 667–668, 667 (figure)
- steady-state efficiency of, 669–670, 669 (figure)
- thermal stability of, 648–651, 650 (figure), 651 (table)
- torque losses and, 669–670, 670 (figure)
- tractor fluids and, 671
- trends in, 647
- VI improvers and, 668
- viscosity and, 652–654, 652 (figure), 653 (figure)
- water content and, 659–661
- wear protection for, 651–654, 652 (figure), 653 (figure), 654 (figure)
- hydraulic fuels
 - antiwear performance testing for, 654, 655 (table), 658–659, 658 (figure)
 - filterability of, 663–664
 - particulates in, 663–664
- hydride formation, 1435
- hydrocarbon base oils. *See also* base stocks
 - analysis of
 - GC for, 306
 - importance of, 305
 - IR spectroscopy for, 307
 - LC for, 306–307
 - MS for, 307, 308 (table)
 - NMR spectroscopy for, 307–308
 - objective of, 305–306
 - UV spectroscopy for, 307
 - wet analytical methods for, 308
 - API classification of
 - categories in, 273–274, 274 (figure), 274 (table)
 - by composition, 274–275, 275 (figure)
 - Group I, 275–276
 - Group II, 276
 - Group III, 276
 - Group IV, 276
 - Group V, 276–277
 - by physical properties, 275, 275 (table)
 - aromatic, 284, 286, 286 (table), 289, 290 (table)
 - ASTM standards for, 326 (table)
 - chemical properties of
 - corrosion, 321, 321 (table)
 - oxidation, 320, 320 (table)
 - sulfur and nitrogen effects, 320–321
 - compressor lubricants and, 324
 - global capacity for production of, 277–278, 277 (figure), 279 (figure)
 - GTL base stocks
 - benefits of, 293
 - oxidation stability of, 296, 297 (figure)
 - steps of, 293, 294 (figure), 295
 - viscosity of, 295–296, 296 (figure)
 - volatility of, 295, 296 (figure)
 - lubricant base stocks and, 283–284, 285 (table)
 - physical properties of, 302, 303 (table)
 - viscosity of, 302, 302 (table), 303 (figure)
 - market and demand for, 271–272, 279
 - drivers of, 302, 304–305, 304 (figure)
 - growth rate projections and, 305, 305 (figure)
 - metalworking fluids and, 325
 - mineral oil base stocks
 - Chevron catalyst technology for, 289–290
 - de-asphalting and, 287, 293
 - distillation of, 286–287
 - flow scheme for production of, 290, 292 (figure)
 - fluidity of, 291
 - hydrocracking and, 288–289, 292 (table), 293
 - hydrogen finishing and, 288
 - hydrotreating of, 291 (figure), 292 (table)
 - lubricating greases and, 324–325, 325 (table)
 - melting point and VI of, 292, 292 (figure)
 - solvent dewaxing and, 288–289, 293
 - solvent refining and, 287–288, 291 (figure)
 - structures and physical properties of, 289, 290 (table)
 - naphthenic, 284, 286, 286 (table), 289, 290 (table)
 - North American capacity for production of, 277–278, 277 (figure), 278 (table)
 - paraffinic, 284, 286, 286 (table), 289, 290 (table)
 - petroleum composition and, 279–282, 281 (figure), 282 (figure), 282 (table)
 - physical properties of
 - aromaticity, 316–318, 318 (figure)
 - biocompatibility, 318–319, 319 (table)
 - density, 315
 - elastomer compatibility, 318
 - emulsion-forming tendency, 320
 - gas solubility, 319, 319 (table)
 - low-temperature, 314–315
 - radiation stability, 320, 320 (table)
 - solvency, 315–316, 315 (table), 316 (figure), 316 (table), 317 (figure), 317 (table)
 - specific gravity, 315, 315 (table)
 - thermal stability, 319–320
 - viscosity, 309–312, 310 (figure), 311 (table), 312 (figure)
 - volatility, 312–314, 313 (figure), 314 (figure), 314 (table)
 - price trends for, 279, 280 (figure), 280 (table), 281 (table)
 - production method comparison of, 296, 298 (figure)
 - refinery processes of, 282–283, 283 (figure)
 - refrigeration lubricants and, 324
 - turbines and, 590, 591 (figure), 592 (table)
 - used oils and, 297–302
- “hydrocarbon pool,” 134
- hydrocarbons. *See also specific types*
 - for automotive engine lubricants wear and friction reduction, 846–847, 847 (figure)

- bond dissociation energies of, 374 (table)
 composition of, in crude oil, 4, 280–281, 281 (figure), 1417, 1421–1422
 as EALs, 847
 in gasoline, 186–187, 187 (table)
 GC analysis methods for, 1117–1118
 historical development in commercial production of, 333
 light
 high temperature vapor pressure for, 146 (figure)
 low temperature vapor pressure for, 147 (figure)
 novel, 847 (table)
 in polymeric dispersant synthesis, 392–394, 393 (figure)
 terminology of, 3–4
 hydrocracked base stocks, for turbines, 592–593, 593 (table), 594 (figure)
 hydrocracking, 15, 16 (table)
 fixed bed, 22, 22 (table)
 fluidized bed, 22, 22 (figure), 23 (table)
 mineral oil base stocks and, 288–289, 292 (table), 293
 hydrodynamic lubrication (HL), 540, 871, 872 (figure), 1599–1600, 1600 (figure)
 Petroff's law and, 1605–1606
 hydrofluoric acid (HF) alkylation, 14–15, 15 (figure), 15 (table)
 hydrogen
 classification of, in organic molecules, 1363–1364, 1365 (figure)
 damage, pipeline corrosion and, 1433–1435
 finishing, mineral oil base stocks and, 288
 microelemental analysis of, 1095–1096
 in petroleum fractions, 347
 production, 23–24
 hydrogen embrittlement (HE), 1433–1434
 hydrogen-induced cracking (HIC), 1434–1435
 hydrogen sulfide (H₂S)
 in crude oil, 1422
 LPG and, 166
 in pipeline corrosion, 1438–1439
 hydroisomerization, 291 (figure)
 hydrolysis
 environmental characteristics and, 1544
 environmentally acceptable ester-based hydraulic fluids and, 558–560, 559 (figure), 560 (table)
 hydrolytic stability
 beverage bottle test of, 1412, 1412 (figure)
 of compressor lubricants, 704
 of environmentally acceptable ester-based hydraulic fluids, 569–570, 570 (figure), 571 (figure)
 hydraulic fluids and, 659–661
 of polyolesters and diesters, 516
 of turbine lubricating oils and hydraulic fluids, 625, 625 (figure)
 hydroperoxides, 1363
 decomposition of
 alkyl phosphites and, 378–379
 mechanism of, 373, 375 (figure), 377 (figure)
 organic sulfides and, 373–374, 378, 378 (figure)
 phenol and, 377 (figure), 378–379
 ZDDPs and, 379, 379 (figure)
 oxidation rate and, 374 (figure)
 hydrophile-lipophile balance (HLB), 537, 537 (table)
 emulsifiers and, 901–902, 902 (figure)
 hydroprocessing
 options for, 16, 16 (table)
 terminology of, 15–16, 16 (table)
 unit design in, 16–17, 17 (figure)
 yields in, 18, 18 (table)
 hydrotreating, 2, 15, 16 (table)
 distillation and, 34, 35 (figure)
 of mineral oil base stocks, 291 (figure), 292 (table)
 solvent extraction and, 35, 36 (figure)
 hypercompressors, 689–690
 hyper-eutectoid steel, 1577, 1579 (figure)
 hyperoxide decomposition, 1364, 1365, 1367 (figure), 1370 (figure), 1371 (figure)
 hypo-eutectoid steel, 1577, 1579 (figure)
 hypoid gear mesh, in HMMWV simulation, 1660–1662, 1660 (figure), 1661 (figure), 1662 (figure), 1663 (figure)
- I**
- icing, in LPG systems, 161
 ideal gas law, 684
 IEC international standards, for turbine lubricating oils and hydraulic fluids, 640
 ILSAC GF-6. *See* engine oils, ILSAC GF-6
 imidazoline dispersants, 398, 401 (figure)
 improved oil recovery (IOR), 40
 Indiana Stirring Oxidation Test (ISOT), 707, 707 (figure)
 indirect biodeterioration, 1242–1243, 1243 (figure)
 indirect coal liquefaction
 methanol production and, 129–131, 130 (figure), 131 (figure)
 MTG process for, 131–135
 indirect injection (IDI) diesel engines, 1288, 1288 (figure)
 inductively coupled plasma-atomic emission spectrometry (ICP-AES), 1088, 1091–1092, 1092 (table)
 inductively coupled plasma-mass spectrometry (ICP-MS), 1092–1093
 industrial gas turbines, 264–265
 industrial gear lubricants, 741–742, 743 (table), 744 (table), 745 (table)
 industrial lubricant additives, 359
 industrial lubricants, 322–325, 323 (figure)
 corrosion ASTM tests for, 1410–1413, 1411 (figure), 1412 (figure), 1413 (figure), 1414 (figure)
 infrared (IR) spectroscopy
 absorbance in, 1126
 ATR and, 1130, 1130 (figure)
 carbonyl functionality and, 1125, 1125 (table)
 compressor lubricants and, 706–707, 706 (figure)
 condition monitoring and, 1133–1134, 1134 (figure), 1135 (figure)
 diffuse reflectance and, 1130, 1130 (figure)
 Fourier-transform, 1127–1128, 1127 (figure), 1128 (figure)
 for hydrocarbon base oil analysis, 307
 instrumentation for, 1127–1129, 1127 (figure), 1128 (figure), 1129 (table)
 near-, mid-, far-, 1126–1127, 1126 (figure)
 open-path gas measurements with, 1129
 oxidation and, 1133, 1134 (figure), 1135 (figure)
 qualitative analysis with, 1131, 1131 (figure)
 quantitative analysis with, 1131–1133
 for quenching, 1008, 1009 (figure)
 sampling methods in, 1129–1131, 1130 (figure)
 soot measurements and, 1133, 1134 (figure)
 surrogate mixtures calibrating, 1133
 transmittance in, 1126
 inhibitor content, determination of, 346
 innage measurement, 1057, 1063–1064
 inorganic/organic solids, metalworking and machining fluids and, 914–915
 insect waxes, 80

- insolubles
 in gear lubricants, 746
 in heat transfer fluids, 971
 in lubricants, 1078–1079
- Institute of Petroleum (IP), 1694
- Institut Francais du Patrole (IFP) process, 299
- insulation, for heat transfer fluid system, 971–972
- insulation fires, heat transfer fluid safety and, 971
- intake valve deposits (IVDs), 189
- interfacial tension (IFT), 39
- intergranular corrosion, 1431
- intergranular stress corrosion cracking (IGSCC), 1432
- interlaboratory (round-robin) exchange testing, 1707
- internal coating, for pipeline corrosion control, 1448–1449, 1450 (figure)
- internal friction, 871
- International Lubricants Standardization and Approval Committee (ILSAC), 353, 353 (figure). *See also* engine oils, ILSAC GF-6
- International Organization for Standardization (ISO), 349–350
 cleanliness codes of, 1220–1221, 1221 (table), 1232, 1232 (table)
 for environmentally acceptable ester-based hydraulic fluids, 576
 for friction and wear, 1693
 heat transfer fluids classification of, 959, 961 (table)
 hydraulic fluids standards of, 678–679
 lubricating grease standards of, 955, 955 (table), 956 (table)
 particle counting standards of, 1234–1235
 turbine lubricating oils and hydraulic fluid standards of, 640
- International Practical Temperature Scale (IPTS), 1507
- International Union of Pure and Applied Chemistry (IUPAC) scale, 1158
- invertebrates, in toxicity tests, 1556, 1557, 1557 (figure)
- ion chromatography (IC), 1093
- ionic dispersants, 398, 401, 401 (figure)
- ionic liquid (IL) lubricants
 additives and, 1047, 1048 (figure), 1048 (table)
 advantages and drawbacks of, 1037–1038, 1049
 historical development of, 1037
 lubrication mechanism of, 1044–1045
 nomenclature of, 1049
 nonmetal contact and, 1044, 1045 (figure)
 performance of, 1042–1045
 properties and impact factors of
 contact angle, 1041, 1042 (table)
 decomposition temperature and heat capacity, 1041, 1042 (table)
 density, 1038–1039, 1039 (table)
 film thickness of, 1041–1042
 molecular structures in, 1045–1046, 1046 (figure)
 refractive index, 1042, 1043 (table)
 surface tension of, 1041, 1041 (table)
 viscosity of, 1040–1041, 1040 (table), 1042, 1043 (table)
 in specific environments, 1046, 1047 (figure)
 steel-steel contacts and, 1043–1044, 1043 (figure)
 structure of, 1037, 1038 (figure)
- ion mobility MS, 1155
- IP-143 method, for asphaltene precipitation onset pressure, 50–51
- IP-280, for oxidation testing of turbine oils, 1373–1374, 1377 (figure), 1378 (figure)
- IP-306, for oxidation testing of turbine oils, 1374
- IP-467, for oxidation testing of gasoline, 1396
- IP 564/IP 565 standards, for particle counting, 1234
- Ircogel®, 421
- iron
 corrosion, 467
 of compressor lubricants, 704
 FTS and, 137–138, 138 (figure)
- iron based organo-metallics, in gasoline, 189
- iron carboxylate, antioxidants and, 373, 376 (figure)
- isobutane, autorefrigeration and, 162
- isomerization, 13, 14 (figure)
- isooctane, 180–181, 181 (table)
- isopropanol, in propane, 163
- isopropyl alcohol (IPA), 188
- isothermal operation, 684–685, 685 (figure)
- ## J
- jet fuel
 additives, 227–228, 227 (table)
 combustion and, 220–221, 220 (figure)
 contaminants in, 230
 diesel, 216–217
 engines for, 215–216, 216 (figure)
 flammability of, 222–223, 223 (figure), 223 (table)
 history of, 6, 212, 214 (table)
 in low temperature environment, 217, 218 (figure)
 manufacturing of, 226–227, 226 (table)
 product color of, 232
 specifications of, 6, 6 (table), 214 (table)
 viscosity and, 217, 218 (figure)
 visual appearance of, 232
 volatility of, 221–222, 222 (figure)
 water content in, 217, 218 (figure), 219
- JIS-K2514, 1381, 1382 (table)
- JIS K2519, 1693
- John Deere JDQ84A test, 659
- Jominy bar end-quench test, 982–983, 983 (figure)
- Joule-Thomson (JT) cooling, 162
- ## K
- Karl Fischer Reagent test, 660
- Karl Fischer titrations, 1076, 1076 (figure), 1076 (table)
- Kelvin thermodynamic temperature scale (KTTs), 1507
- Kendrick mass defect (KMD), 1158
- Kerogen, 40
- kerosine, 1–2, 3 (table). *See also* fuel properties and test methods requirements for, 246 (table) specifications of, 242, 245 (table)
- Kerr, A. N., 150
- Kerr, C. L., 150
- Kesternich Cabinet test, 1413, 1414 (figure)
- Kettering, Charles F., 180
- kinematic viscosity, 1486, 1486 (table). *See also* viscosity history of, 1493–1496 petroleum oil flow properties and, 1489–1493, 1491 (table), 1492 (figure), 1492 (table), 1493 (figure), 1494 (figure) temperature relationship to, 1497, 1498 (figure), 1499–1500, 1499 (figure), 1500 (table)
- kinetic friction, 871
- Kinetics Technology International (KTI) process, 299–300, 300 (figure)
- Kohleol process, 122, 123 (table)
- Kolmogorov length scales, 1281
- Komatsu HPV35+35 test, 659
- ## L
- lacquer, 366, 367
- Lambda ratio, 1569, 1569 (table)
 tribology and, 1640
 in WAM testing for micropitting and spalling, 1656–1658, 1657 (figure), 1658 (figure)
- laminar flame speed, combustion and, 1280
- lapping, abrasive wear and, 1583, 1583 (figure)

- laser desorption/ionization (LDI), 1152, 1157
laser technology, for asphaltene deposition prevention, 66, 66 (figure)
lauryl acid phosphate (LAP), 454, 455 (figure)
lead
 corrosion, 470
 in gas turbine fuel oils, 265 (table), 266
 test, of used oil, 33
leaded gasoline, history of, 179–180
lead oxide (PbO), 463
lead paint, definition of, 366
leakage
 heat transfer fluid safety and, 971
 lubricating grease heat resistance and, 948, 948 (figure)
lean burn technology, 763
Leidenfrost temperature, 985
Liedenfrost effect, 171
light-duty diesel (LDD) vehicles, 796
light-duty engine oils, 754
light extinction particle counting, 1221, 1222 (figure), 1223, 1223 (figure)
light hydrocarbons, 146 (figure), 147 (figure)
light-scattering technique, for asphaltene precipitation onset pressure, 48–49, 50 (figure)
light scatter particle counting, 1223–1226, 1224 (figure), 1225 (figure)
light straight run gasolines (LSRs), 1, 3 (table)
light-tight oil (LTO), 26
light vacuum gas oils (LVGOs), 2, 3 (table)
limited-additive suppliers, 359
linear reciprocity test, 1688–1689, 1688 (figure)
line contact, Hertzian contact and, 1634
liquefied petroleum gas (LPG)
 ASTM standards for, 145, 174–175
 DME and, 153–154
 history of, 152–153
 auto propane and, 169
 exposure to, 171–172
 flammability and, 170
 gas hydrates and, 160–162
 handling of, 170–171
 history of, 145
 industry, 146–149
 properties and thermodynamics, 151–152
 use, 149–151
icing in systems of, 161
injector systems, 169
odorization, 172–173
safety of, 170–173
sample cylinder approvals for, 171
specifications of
 composition, 155
 contaminants and, 166–167
 corrosion and, 166
 density and, 155
 H₂S and, 166
 history of ASTM standards for, 152–153
 NORM and, 167–168
 octane and, 155
 oil stain and, 165
 olefins and, 155–156
 propane dryness and, 158–165
 residual matter and, 165–166
 sampling, 154, 164, 348
 sulfur content and, 166
 vapor pressure and, 155–157
 volatility residue, weathering and, 157–158
 water content and, 158–165
 uses of, 173–174
 vapor removal and, 171
 volume correction factors and, 168–169
liquefied propane gas, 431
liquid chromatography (LC)
 ASTM standards for, 1109–1110, 1120–1123
 future developments in, 1120
 high-performance, 306
 for hydrocarbon base oil analysis, 306–307
liquid heptane washing test, 708, 708 (figure)
liquid-in-glass (LiG) thermometers, 1270–1271, 1270 (figure), 1271 (figure), 1507
liquid propane, 171
liquid solvent extraction (LSE) process, 122
Liščič-Petrofer probe
 HTC calculation with, 1020, 1021
 quenching cooling curve analysis with, 1019–1020, 1021 (figure), 1022, 1022 (figure), 1023 (figure), 1024 (figure)
 shape and schematic of, 1019, 1020 (figure)
lithium complex greases, 938, 940
lithium soap greases, 938
load
 capacity
 chemical reactivity compared to, 454, 455 (figure), 456
 testing, scuffing, 1651–1653, 1652 (figure), 1653 (figure)
 EP and, 453, 454 (figure)
 in tribology test systems, 1676
lobe compressors, rotary, 690–691, 690 (figure)
localized pipeline corrosion
 erosion corrosion, 1430–1431, 1430 (figure)
 galvanic corrosion, 1431
 intergranular corrosion, 1431
 pitting corrosion, 1428–1430, 1429 (figure)
long-chain chlorinated paraffins (LCCPs), 767–768, 907
long-chain surfactants, 766
low-speed high torque hypoid test, for gear lubricants, 748
low-speed preignition prevention test, 788 (table)
low-temperature flow test (LTFT), 248–249
low-temperature high-shear viscosity, lubricants and, 1529–1531, 1529 (table), 1530 (figure), 1530 (table), 1531 (figure), 1531 (table)
low-temperature penetration, lubricating grease consistency stability and, 944
low-temperature properties. *See also* cold flow properties
 of diesel fuel oils, 248–250, 249 (figure)
 of environmentally acceptable ester-based hydraulic fluids, 564–566, 565 (figure)
 for gear lubricants, 747
 of hydraulic fluids, 668–669, 668 (table)
 of hydrocarbon base oils, 314–315
 of polyolesters and diesters, 515
 turbine lubricating oils and hydraulic fluids and, 612, 616–617
low-temperature pumpability, of engine lubricants, 1531–1535, 1531 (figure), 1532 (figure), 1533 (figure), 1534 (figure)
LSPI test, 770–771, 771 (figure), 795–796
lube oil base stock production, 22–23
lubricant films, 873, 873 (figure)
lubricants. *See also* additives; automotive engine lubricants; environmental characteristics, of fuels and lubricants; gear lubricants; hydrocarbon base oils; ionic liquid (IL) lubricants; synthetic lubricants; turbine lubricating oils and hydraulic fluids
 additives and
 composition in, 363, 363 (figure), 363 (table)
 for engine and nonengine, 495, 496 (table)
 properties of, by application, 358 (table)
 samples of, 1069, 1071, 1072 (table)

- ASTM tests for, 1069, 1070 (table)
 - carbon residue, 1077–1078, 1077 (table)
 - chlorinated solvent elimination in, 1081
 - foaming, 1079
 - insolubles, 1078–1079
 - international methods, 1080–1081
 - other methods, 1080
 - proficiency testing programs, 1080
 - standards, 1081–1083
 - volatility, 1079–1080
- barrier-film, 898
- base stocks, 283–284, 285 (table)
 - physical properties of, 302, 303 (table)
 - viscosity of, 302, 302 (table), 303 (figure)
- biodegradable, oxidation testing of, 1399–1400, 1400 (figure)
- biodeterioration of, 1243
 - biocorrosion/MIC, 1244–1247, 1244 (figure), 1245 (figure), 1246 (figure), 1246 (table), 1247 (figure), 1248 (figure)
 - condition monitoring for, 1258–1259, 1258 (figure)
 - correction strategies for, 1264, 1264 (figure)
 - fouling, 1247–1251, 1248 (figure), 1249 (figure), 1250 (figure), 1251 (figure)
 - prevention strategies for, 1262, 1263 (figure)
- cold flow properties of, 1525
 - engine lubricants, 1528–1529, 1529 (table)
 - low-temperature high-shear viscosity and, 1529–1531, 1529 (table), 1530 (figure), 1530 (table), 1531 (figure), 1531 (table)
 - soot-containing, 1535
 - turbine lubricants, 1526–1527, 1527 (figure)
- composition of, 272, 273 (figure)
- consumption of, 272–273, 273 (figure)
- corrosion ASTM tests for, 1408, 1409 (table), 1410 (figure), 1410 (table)
- desirable properties of, 351–355
- development trends of
 - in HDDEOs, 354–355
 - in PCMOs, 353–354, 353 (figure), 355 (figure)
- eco-labeling of, 499, 499 (figure), 500
- engine
 - cold flow properties of, 1528–1529, 1529 (table)
 - low-temperature pumpability of, 1531–1535, 1531 (figure), 1532 (figure), 1533 (figure), 1534 (figure)
- environmentally acceptable, 522, 1539
- fuel economy and, 356
- GC analysis methods for, 1118–1119
- heavy-duty diesel, 271
- high-temperature degradation model of, 1365, 1369 (figure)
- history of, 351
- industrial, 322–325, 323 (figure)
 - corrosion ASTM tests for, 1410–1413, 1411 (figure), 1412 (figure), 1413 (figure), 1414 (figure)
- market and demand for, 271–272, 362–363
- microbes in, 1241–1242
- nonengine, 357–358
- oil drain intervals and, 356–357
- oxidation of
 - degradation of, 373, 376 (figure)
 - mechanisms of, 1363–1369
- oxidation testing of, 1396–1399, 1397 (figure), 1398 (figure)
- properties of, by application, 358 (table)
- quality rankings of, 1571–1572, 1572 (figure)
- slide-way, 898
- solid, 461–465, 463 (figure), 464 (figure), 464 (table), 465 (figure), 466 (table)
- solubility of, in compressor lubricants, 700–701, 703 (figure)
 - soot-containing, cold flow properties of, 1535
 - titration of
 - advantages of, 1071
 - potentiometric indication of, 1073–1077, 1074 (table), 1076 (figure), 1076 (table)
 - thermometric, 1081, 1081 (figure)
 - visual indication of, 1071, 1073, 1073 (figure), 1073 (table)
 - tribology test systems and, 1678
 - vehicle emission standards and, 355–356
 - viscosity and, 272, 354, 355 (figure)
- lubricating greases, 728, 729 (table)
 - ASTM tests for, 942
 - chemical analysis, 954–955
 - compatibility, 954
 - consistency, 943–944, 943 (figure), 944 (table)
 - consistency stability, 944
 - contamination, 953, 953 (figure)
 - corrosion, 952, 952 (figure)
 - discontinued standards, 955
 - elastomer compatibility, 953–954
 - EP agents and wear, 950–952, 951 (figure)
 - flow properties, 944–946
 - heat resistance, 946–948, 946 (figure), 947 (figure), 948 (figure)
 - ignition test, 955
 - oxidation stability, 948–950, 949 (figure), 950 (figure)
 - oxidation testing, 1382–1385, 1384 (figure), 1385 (figure), 1386 (figure)
 - standards, 957–958
 - static bleed test, 954
 - water content, 952–953, 953 (figure)
 - classification and specifications of, 942, 942 (table)
 - composition of
 - additives and, 939
 - base stocks and, 935–937, 936 (table)
 - thickeners and, 937–939, 937 (figure)
 - corrosion ASTM tests for, 1409 (table), 1413–1414, 1414 (figure), 1415 (figure), 1415 (table)
 - ISO standards for, 955, 955 (table), 956 (table)
 - manufacturing of, 939–941
 - mineral oil base stocks and, 324–325, 325 (table)
 - oxidation testing of, 1382–1385, 1384 (figure), 1385 (figure), 1386 (figure)
 - selection of, 939
 - structure of, 935, 936 (figure)
 - sulfurized products for, 448, 448 (table)
- lubrication. *See also* tribology test systems
 - ASTM standards for, 1621–1622
 - boundary, 540, 871–872, 1599–1600, 1600 (figure)
 - additives and, 443, 449, 452 (table), 1606, 1609–1612, 1609 (figure), 1609 (table), 1610 (figure), 1611 (figure), 1612 (table)
 - antiwear agents and, 1612, 1612 (figure)
 - EP agents and, 449, 452 (table), 1612–1613, 1613 (figure)
 - friction modifiers and, 1606
 - tribochemical wear, material surfaces and, 1606, 1607 (table)
 - tribology TRL, oil types and, 1653–1654, 1654 (figure)
 - bulk material properties and, 1574–1577, 1578 (table), 1579 (figure), 1579 (table)
 - compressor lubricant requirements for, 701, 703 (table)
 - elastohydrodynamic, 540, 1599–1600, 1600 (figure)
 - Dowson equation and, 1600–1602
 - film thickness and, 1600–1602, 1602 (table), 1603 (figure)
 - mixed-, 1603
 - non-Newtonian and micro-, 1602–1603

- environmentally acceptable ester-based hydraulic fluids and, 564, 564 (figure)
- friction and, 1565–1567, 1566 (figure), 1566 (table), 1567 (figure)
- as friction modifier, 870–871
- for gas turbines, 587 (figure)
- of gears, 723–724, 726–728, 726 (table), 727 (figure), 727 (table), 728 (table)
- Hertzian contact and, 1600–1605
- of HFA and HFB fluids, 540
- of HFC fluids, 544
- hydraulic fluids and, 645–646
- hydrodynamic, 540, 871, 872 (figure), 1599–1600, 1600 (figure)
- Petroff's law and, 1605–1606
- IL lubricant mechanism of, 1044–1045
- metalworking fluids and, 870–874, 871 (figure), 872 (figure), 873 (figure)
- nanoparticles in
- chemical composition of, 1615, 1615 (figure), 1615 (table)
 - importance of, 1613
 - metal oxides and, 1616, 1616 (table)
 - metals and, 1616, 1616 (table)
 - morphology of, 1618–1621, 1619 (figure), 1620 (figure), 1621 (table)
 - nanocomposites and, 1615–1616, 1616 (table)
 - rare earth compounds and, 1616–1618, 1617 (figure), 1617 (table), 1618 (figure), 1618 (table)
 - size of, 1618, 1619 (figure), 1619 (table)
 - sulfur and, 1615
 - summary of, 1614, 1614 (table)
- new surface structure and, 1574, 1576 (figure)
- regime, 873–874, 1599–1600, 1600 (figure)
- seizure in, 1595
- subsurface structure and, 1574, 1576 (figure), 1577 (figure), 1578 (figure)
- superficial tribology and structural elements of, 1635–1636, 1635 (figure), 1636 (figure)
- surface films and, 1574, 1574 (figure), 1575 (figure), 1576 (figure)
- surface roughness data analysis and, 1569–1573, 1570 (figure), 1570 (table), 1571 (figure), 1571 (table), 1572 (figure), 1573 (figure)
- turbine lubricating oils and hydraulic fluids and, 627, 627 (figure)
- wear surfaces and, 1567–1569, 1569 (figure), 1569 (table)
- worn surface structure and, 1573–1576
- lubricity**
- additives, 189
 - of aerospace fuels, 1312–1313
 - of aviation fuels, 225
 - of diesel fuel oils, 255–256
 - of gasoline, 203
 - PAGs and, 520–521
 - of synthetic lubricants, 527–528, 528 (table)
- Lurgi-Ruhr gas process, 115–117
- M**
- MacCoull equations, 1497, 1498 (figure), 1499–1500
- machining. *See also* metalworking and machining fluids
- definition of, 865
 - dry, 889–890
 - metal characteristics in, 888, 889 (table)
 - operations, 865–867
- macrocrystalline wax (paraffin wax), 85, 87–88, 97
- macroemulsions, metalworking and machining fluids, 880–881
- magnetic residues, LPG and, 166–167
- magnetic separators, for contamination removal, 923–924
- maltenes, 40
- manifold air temperature and pressure, ONR, 195
- Mannich dispersants, 392, 398, 399 (figure)
- manual piston cylinder (MPC) sampling, 154
- manufacturing process control, 1701–1702
- marine fuels, 242, 246 (table). *See also* fuel properties and test methods
- marine transport, for aviation fuels, 228–229
- marine vessels, static petroleum measurement and, 1065
- martempering quenching oils, 1004–1005, 1005 (figure), 1005 (table)
- martensite, 978 (figure), 979
- mass in air, 1067
- mass resolution, 1152
- mass spectrometry (MS)
- APCI and, 1152, 1156
 - APLI and, 1156–1157
 - APPI and, 1152, 1156
 - ESI and, 1152, 1155–1156
 - Fourier-transform ion cyclotron resonance, 41
 - FT-ICR, 1152–1154, 1153 (figure)
 - gas chromatography, 1119–1120
 - for hydrocarbon base oil analysis, 307, 308 (table)
 - inductively coupled plasma, 1092–1093
 - ion mobility, 1155
 - LDI and, 1152, 1157
 - MALDI and, 1152, 1157
 - Orbitrap, 1152, 1154
 - for petroleum oil
 - asphaltenes and, 1161–1162, 1162 (figure)
 - data analysis of, 1157–1160, 1157 (figure), 1158 (figure), 1159 (figure), 1160 (figure)
 - environmental monitoring and, 1162
 - sample preparation in, 1160–1161, 1161 (figure)
 - techniques of, 1152–1153
 - TOF, 1152–1154
- material and paint compatibility, of HFA, HFB, HFC fluids, 546, 547 (table)
- material safety data sheets (MSDSs), 919
- matrix-assisted laser desorption/ionization (MALDI), 1152, 1157
- maximum friction reduction (MFR), 1616–1618, 1617 (figure), 1618 (table), 1619 (figure)
- maximum wear reduction (MWR), 1616–1618, 1617 (figure), 1618 (table), 1619 (figure)
- MB M111 black sludge test, 788 (table)
- MB M111 fuel economy test, 779 (table), 789 (table)
- MB M271 sludge test, 789 (table)
- measurement processes
- ASTM standards for, 1709
 - bias in, 1703–1704
 - manufacturing process control, 1701–1702
 - precision in, 1702–1703, 1703 (figure)
 - product property conformance to specification, 1702
 - QA program for, 1704–1708
 - self-monitoring, 1702
- mechanical methods, for asphaltene deposition prevention, 65
- mechanical shear, ester polymers and, 483
- medium-chain chlorinated paraffins (MCCPs), 767–768, 907
- Meinken process, 299
- melting point
- of mineral oil base stocks, 292, 292 (figure)
 - petroleum waxes and, 98, 99 (figure), 100 (figure), 101 (figure), 101 (table)
- mercaptan odorants, 173
- mercury, in crude oil, 1096
- metabolism, microbial, 1237–1238, 1238 (figure)
- metal deactivators, 189
- as antioxidants, 382, 385 (figure), 1368, 1375 (figure)
 - for compressor lubricants, 698, 699 (table)

- metal-forming, 867–868
 - metalworking fluid classification and, 891–893, 893 (table), 894 (table), 895 (table), 896 (table)
 - composition of, 918 (table)
 - surface changes in, 872–873, 872 (figure)
- metallocenes, 411
- metal oxides, lubrication and, 1616, 1616 (table)
- metal passivators, 605, 605 (figure), 666
- metal-protecting fluids, 893
- metal ratio, of detergents, 422
- metal-removal, 865–867, 867 (figure)
 - metalworking fluid classification and, 885–891, 886 (figure), 887 (figure), 888 (table), 890 (table), 891 (table)
 - composition of, 917 (table)
- metal-rolling operations, 895 (table), 896 (table)
- metals
 - antioxidants and, 373, 375 (figure)
 - biocorrosion of, 1244–1245, 1244 (figure), 1245 (figure), 1246 (figure)
 - in crude oil, 4–5
 - in heat transfer fluids, 968, 968 (table)
 - lubrication and, 1616, 1616 (table)
 - microelemental analysis methods of, 1096, 1097 (table)
 - in petroleum coke, 1347
 - in petroleum products, 1085, 1086 (table)
 - test, of used oil, 33
 - transition, as oxidation promoters and inhibitors, 382, 384 (figure), 385, 385 (figure)
 - wear, in used oil, 1086–1088, 1087 (table)
- metal surfaces, friction modifiers and, 436–437, 437 (figure), 438 (figure), 439 (figure)
- metal-treating fluids, 893, 896–898, 897 (figure)
- metalworking and machining fluids
 - additives and, 901 (table)
 - alkalinity agents and, 911
 - antimicrobial agents and, 911–912, 913 (figure)
 - antimisting agents and, 911
 - antioxidants and, 913–914, 914 (figure)
 - corrosion inhibitors and, 911, 912 (figure)
 - couplers and, 903–904, 904 (figure)
 - dispersants and, 910, 911 (figure)
 - dyes and, 914
 - emulsifiers, 900–903, 902 (figure), 902 (table)
 - EP agents and, 905–910, 906 (figure), 907 (figure), 908 (figure), 909 (table), 910 (figure), 910 (table)
 - film formers and, 904
 - foam inhibitors and, 912–913, 913 (figure)
 - friction modifiers and, 904–905, 904 (figure), 905 (figure)
 - inorganic/organic solids and, 914–915
 - odor-control agents and, 914
 - ASTM standards for, 928–930
 - characteristics of, 884 (table)
 - classification of, 875 (figure), 876 (table)
 - barrier-film lubricants and, 898
 - base fluid-based, 875–879, 898–900, 899 (figure)
 - end use as basis of, 884–898
 - metal-forming and, 891–893, 893 (table), 894 (table), 895 (table), 896 (table), 918 (table)
 - metal-protecting fluids, 893
 - metal-removal and, 885–891, 886 (figure), 887 (figure), 888 (table), 890 (table), 891 (table), 917 (table)
 - metal-treating fluids, 893, 896–898, 897 (figure)
 - oil-based fluids, 876–877
 - semisynthetic fluids, 881–882
 - slide-way lubricants and, 898
 - soluble oils, 880–881
 - synthetic fluids, 882–883, 882 (figure)
 - water-based, 877–879, 878 (figure), 878 (table), 879 (figure), 879 (table)
 - concentration of, 870
 - emulsion stability of, 883
 - environmental compatibility of, 922
 - fluid blending and maintenance of, 916–917
 - foaming in, 878–879
 - formulations for, 915–916
 - hydrocarbon base oils and, 325
 - lubrication and, 870–874, 871 (figure), 872 (figure), 873 (figure)
 - market drivers and restraints of, 870
 - oxidation stability of, 884
 - recycling and disposal of
 - contaminant removal, 923–925
 - disposal methods, 925–926
 - metal cuttings disposal, 928
 - nonhazardous fluid disposal, 926–927, 927 (table), 928 (table)
 - reprocessing and reclamation, 923, 925, 925 (figure)
 - sludge disposal, 928
 - used oil criteria of EPA, 922–923
 - used oil disposal, 928
 - wastewater disposal, 927–928
 - safety of, 919
 - selection of, 869
 - solid dispersions and, 884
 - storage stability of, 883–884
 - tests of, 917–919, 919 (table), 920 (table), 921 (table)
 - toxicity of, 919, 922
 - viscosity and, 874–875, 874 (figure)
 - water-miscible
 - cast iron chip test for, 1413, 1413 (figure)
 - condition monitoring for biodeterioration and, 1252–1255, 1252 (figure), 1253 (figure), 1254 (figure)
 - water quality and, 900
- metalworking operations
 - heat-treatment and, 869
 - joining processes, 868–869
 - metal-forming, 867–868
 - metalworking fluid classification and, 891–893, 918 (table)
 - surface changes in, 872–873, 872 (figure)
 - metal-removal, 865–867, 867 (figure)
 - metalworking fluid classification and, 885–891, 917 (table)
- metering, of aviation fuels, 223
- methane
 - ethane from, 336
 - structure of, 1297, 1300 (figure)
- methanol
 - production of, indirect coal liquefaction and, 129–131, 130 (figure), 131 (figure)
 - in propane, phase behavior, 162–164, 163 (table), 164 (table)
 - in propylene, 345
- methanol-to-gasoline (MTG) process
 - block diagram of, 132 (figure)
 - discovery and development of, 131–132
 - dual-cycle mechanism of, 134–135, 135 (figure)
 - gasoline yields and properties in, 132, 132 (table)
 - reaction mechanism and steps in, 132, 133 (figure), 134, 134 (figure)
- methanol-to-olefin (MTO) process, 132, 133 (table), 135, 342, 342 (figure)
- methylcyclohexane, 132, 134
- methylcyclopentadienyl manganese tricarbonyl (MMT), 188
- methylene-bridged alkylphenols, 413, 414 (figure)
- methyl ethyl ketone (MEK), 83, 84 (figure)

- micellar solutions, metalworking and machining fluids, 882–883, 882 (figure)
- Michelson interferometer, 1127, 1127 (figure)
- microbes. *See also* biodeterioration
- biofilms of, 1240–1241, 1241 (figure)
 - definition of, 1237
 - in fuels and lubricants, 1241–1242
 - growth and proliferation of, 1238–1239, 1239 (figure)
 - metabolism of, 1237–1238, 1238 (figure)
 - persister cells and, 1241
 - physiochemical environments of, 1239–1240, 1240 (figure)
 - water and, 1240, 1240 (figure)
- microbiologically influenced corrosion (MIC), 1244–1247, 1244 (figure), 1245 (figure), 1246 (figure), 1246 (table), 1247 (figure), 1248 (figure), 1454–1456
- microcrystalline wax (microwax), 85, 97
- micro-EHD lubrication, 1602–1603
- microelemental analysis methods
- of ash and sulfated ash, 1096
 - of biofuels, 1097, 1098 (table)
 - of hydrogen, 1095–1096
 - of mercury in crude oil, 1096
 - of metals, 1096, 1097 (table)
 - NAA, 1093–1094
 - of nitrogen, 1096, 1096 (table)
 - precision of, 1094 (table)
 - of silicon, 1096
 - of sulfur, 1097, 1097 (table)
 - types of, 1093 (table)
 - XRF, 1094–1095, 1095 (table)
- microfiltration, for contamination removal, 924
- micronic filters, 231
- microorganisms, aviation fuel quality control and, 233
- micropitting, 724–725, 725 (figure)
- superficial tribology and, 1643, 1644 (figure)
 - tribology TRL and
 - low-cycle, 1654–1655, 1655 (figure)
 - spalling and, 1655–1656, 1656 (figure), 1657 (figure)
 - WAM testing for, 1656–1658, 1657 (figure), 1658 (figure), 1659 (figure)
- micro-scaffing, superficial tribology and, 1643, 1644 (figure)
- middle-distillate fuel oils, cloud point of, 1523
- Midgley, Thomas, Jr., 180
- mid-infrared spectroscopy (FTIR) test, 32
- Mie theory, light scatter particle counting and, 1225–1226, 1225 (figure)
- Miller, W. A., 151–152
- milling operations, machining, 866
- MIL-PRF-2104J/MIL-PRF-2104K. *See* engine oils, MIL-PRF-2104J/MIL-PRF-2104K
- MIL-PRF-2105E classification, for gear lubricants, 739, 740 (table)
- mineral oil base stocks
- of compressor lubricants, 694–695, 694 (table), 695 (figure)
 - de-asphalting and, 287, 293
 - distillation of, 286–287
 - flow scheme for production of, 290, 292 (figure)
 - fluidity of, 291
 - hydrocracking and, 288–289, 292 (table), 293
 - hydrogen finishing and, 288
 - hydrotreating of, 291 (figure), 292 (table)
 - lubricating greases and, 324–325, 325 (table)
 - melting point and VI of, 292, 292 (figure)
 - solvent dewaxing and, 288–289, 293
 - solvent refining and, 287–288, 291 (figure)
 - structures and physical properties of, 289, 290 (table)
- mineral oil heat transfer fluids, 961–965, 962 (figure), 962 (table), 963 (table), 964 (figure), 964 (table). *See also* heat transfer fluids
- mineral oils
- for aero-engines, 585
 - environmentally acceptable ester-based hydraulic fluids
 - mixing with, 566
 - for hydraulic fluids, 670–671, 671 (table), 672 (table)
- minimum bounding rectangle, particle counting and, 1218, 1218 (table)
- minimum friction coefficient (MFC), 1616–1618, 1617 (figure), 1618 (table), 1619 (figure)
- minirotary viscometer (MRV) test, 480
- mixed-EHD lubrication, 1603
- modified continuously closed cup (MCCCFP) tester, 246
- modified Ostwald viscometers, 1491 (table), 1492–1493, 1492 (figure), 1494 (figure)
- modulus, 1487
- moisture analyzers
- calibration of, 348
 - hydraulic fluids and, 660
 - pipeline corrosion, 1463–1464, 1463 (figure), 1464 (figure)
- molybdenum dialkyldithiocarbamate (MoDTC), 758, 849
- molybdenum disulfide (MoS₂), 463, 464 (figure), 465
- monitors, aviation fuel quality control and, 231
- motor octane number (MON), 1279
- Motor Octane Number (MON), 5, 181, 192–193, 193 (table)
- multi-additive suppliers, 359
- multilinear regression (MLR), 1131–1133
- multiphase flow loops, for pipeline corrosion, 1456, 1458 (figure), 1459 (figure)
- multiphase flow regime, pipeline corrosion and, 1435–1436, 1436 (figure)
- multiphase velocity, pipeline corrosion and, 1436, 1436 (figure)
- multiply-alkylated cyclopentanes (MACs), 525–526
- multispecimen test machine, 1687–1688, 1687 (figure)
- N**
- nanoaggregate concentration (NAC), 43
- nanocomposites, lubrication and, 1615–1616, 1616 (table)
- nanoparticles, in lubrication
- chemical composition of, 1615, 1615 (figure), 1615 (table)
 - importance of, 1613
 - metal oxides and, 1616, 1616 (table)
 - metals and, 1616, 1616 (table)
 - morphology of, 1618–1621, 1619 (figure), 1620 (figure), 1621 (table)
 - nanocomposites and, 1615–1616, 1616 (table)
 - rare earth compounds and, 1616–1618, 1617 (figure), 1617 (table), 1618 (figure), 1618 (table)
 - size of, 1618, 1619 (figure), 1619 (table)
 - sulfur and, 1615
 - summary of, 1614, 1614 (table)
- naphthenes, 281
- characteristics of, 3–4
 - composition of, 4
 - determination of, 347
- naphthenic acids, 416, 416 (figure)
- naphthenic hydrocarbon base oils, 284, 286, 286 (table), 289, 290 (table)
- naphthenic hydrocarbon fractions, 81
- National Highway Traffic Safety Administration (NHTSA), 431
- National Institute of Standards and Technology (NIST), 1097, 1099 (table)
- National Lubricating Grease Institute (NLGI), 357
- National Sanitation Foundation (NSF), 499
- natural gas liquids, volume correlation factors and, 168–169
- Natural Gasoline* (Oberfell and Alden), 151
- Natural Gasoline Association of America (NGAA), 150, 151
- naturally occurring radioactive materials (NORM), 167–168

- natural sulfonic acid substrates, 412–413, 413 (figure)
- needle coke, 1345, 1346 (figure)
- neopentylglycol, synthesis of, 563, 563 (figure)
- net standard volume (NSV), 1066
- neutron activation analysis (NAA), 1093–1094
- New Energy Development Organization (NEDO) process, 122, 124 (figure)
- new surface structure, wear and, 1574, 1576 (figure)
- Newtonian liquid, 1486
- nickel
 - in petroleum coke, 1347
 - test, of used oil, 33
- nitrogen
 - in crude oil, 4
 - in gear lubricants, 747
 - hydrocarbon base oils and, 320–321
 - microelemental analysis methods of, 1096, 1096 (table)
 - in radical scavengers, 1365, 1370 (figure)
- nitrogen oxide, 355
- NOACK evaporation tester, 705, 705 (figure)
- Noack volatility test, 313, 432, 434 (figure), 759
- “nonassociated” gas, 147
- nonengine lubricants, 357–358
- nonflow energy equation, 1325
- nonionic emulsifiers, 902–903, 903 (figure)
- nonlubricating process fluids, 977. *See also* quenching; steel
- non-Newtonian EHD lubrication, 1602–1603
- NO_x Clean Air Act, 182
- nuclear magnetic resonance (NMR) spectroscopy, 45
 - ASTM tests for, 1137–1138, 1138 (table), 1148
 - data collection methods for, 1140
 - data presentation in, 1146
 - data processing in, 1145–1146
 - decoupling and, 1140, 1141 (figure)
 - definition of, 1137
 - DEPT pulse sequences and, 1141–1142, 1141 (figure), 1142 (figure)
 - Fourier-Transform, 1137–1138
 - GASPE pulse sequences and, 1142
 - GC compared to, 1137
 - for hydrocarbon base oil analysis, 307–308
 - olefin analysis with, 1147–1148
 - process chemistry monitoring in, 1147
 - qualitative analysis of
 - one dimensional, 1140–1142, 1141 (figure), 1142 (figure)
 - two-dimensional, 1142, 1143 (figure)
 - quantitative analysis of, 1142–1144, 1143 (figure)
 - carbon types and, 1146–1147
 - with internal standard, 1144–1145, 1145 (figure)
 - without internal standard, 1144
 - sample preparation for, 1138, 1139 (figure), 1140, 1140 (table)
 - specialized applications of, 1148
-
- Oberfell, George G., 151
- occidental pyrolysis process, 118
- occupational exposure limits (OELs), 171–172
- Occupational Safety and Health Administration (OSHA), 919
- octane
 - distribution through fuel boiling range, 194
 - LPG and, 155
 - number ratings, history of, 180–181, 181 (table)
- octane number requirements (ONRs), 194–196
- octanol-water partition coefficient, environmental characteristics and, 1540–1541
- odor, of petroleum waxes, 105–106, 107 (table)
- odor-control agents, metalworking and machining fluids and, 914
- odorization, LPG, 172–173
- OEM specifications, for gear lubricants, 740–741, 742 (table)
- oil-based, metalworking and machining fluids, 876–877
- oil consumption, additives and, 371, 371 (figure)
- oil content, petroleum waxes and, 101
- oil drain intervals, lubricants and, 356–357
- oil-in-water emulsion, 472, 474 (figure)
 - in metalworking fluids, 877–879, 878 (figure), 878 (table), 879 (figure), 879 (table)
- oil release test
 - for GF-4/SM, 780 (table)
 - for GF-5/SN, 790 (table)
- oil separation, lubricating grease heat resistance and, 947–948, 947 (figure)
- oil-soluble dye, in gasoline, 189
- oil-soluble petroleum sulfonates, 1110
- oil stain, LPG and, 165
- oil thickening, 371, 476, 476 (figure)
- olefin-based polymers, 478–481, 479 (figure), 479 (table), 480 (table), 481 (figure)
- olefin copolymers (OCPs), 478–481, 479 (figure), 479 (table), 480 (table), 481 (figure)
- olefins, 280. *See also* C₄ olefins; ethylene; methanol-to-olefin process; propylene
 - ASTM test methods for, 349
 - C₄ olefins, 345–346
 - ethylene, 344
 - general, 346–348
 - propylene, 344–345
 - catalyst-based chemistry for, 342
 - characteristics of, 3–4
 - in detergent substrates, 410–411, 410 (figure)
 - DIN standards for, 349
 - feedstock outline for, 334, 336, 338 (table), 339 (table)
 - GPA standards for, 349
 - ISO standards for, 349–350
 - LPG and, 155–156
 - polymer sensitivity to, 333
 - process chemistry for, conventional, 336, 339
 - reduction of, 15–18, 26
 - steam cracking for, 333, 334 (figure), 335 (figure)
 - fractionation in, 340–341
 - process of, 339–340, 340 (figure)
 - pyrolysis in, 340
 - recovery in, 341
 - test sampling points in, 342, 343 (figure)
 - unit flow in, 341 (figure)
 - sulfurization of, 447–448, 448 (figure), 448 (table), 449 (figure), 450 (figure)
 - thermal cracking for production of, 336, 339
 - thermophysical properties of, 343 (table)
 - UOP standards for, 350
- open gear compounds, 728, 729 (table)
- open-path gas measurements, IR spectroscopy, 1129
- optical texture, of petroleum coke, 1348–1349, 1348 (table), 1349 (table)
- Orbitrap mass spectrometry, 1152, 1154
- organic acids, weak, 1243
- organic phosphate, EP agent combining fatty acid and, 458, 459 (figure)
- organoclay greases, 939, 941
- organo-metallics, iron based, in gasoline, 189
- organomolybdenum compounds, as friction modifiers, 849
- organophosphorus esters, applications of, 462 (table)
- orifice viscometers, 1496–1497
- oscillating motion test, 951
- oscillating roll/slide test, 1687, 1688 (figure)

- oscillating wear test, 951–952
- outage measurement, 1057, 1064–1065
- oxidant performance, aerospace fuels and, 1297, 1299 (table)
- oxidation
- acid formation and, 1364, 1368 (figure)
 - ASTM tests for, 601–603, 602 (figure), 603 (figure), 604 (figure), 604 (table), 649–650, 649 (figure), 649 (table)
 - base stock structures susceptible to, 1363, 1364 (figure)
 - carboxylic acids and, 1364, 1368 (figure)
 - CI-4/CI-4 PLUS engine oils and, 831
 - compressor lubricants and, 707, 707 (figure)
 - copper ions in, 1368, 1376 (figure)
 - of EP gear lubricants, 747
 - hydrocarbon base oil, 320, 320 (table)
 - hydroperoxide and rate of, 374 (figure)
 - hyperoxide decomposition and, 1364, 1365, 1367 (figure), 1370 (figure), 1371 (figure)
 - initiation stage of, 372–373, 372 (figure), 1364
 - IR spectroscopy and, 1133, 1134 (figure), 1135 (figure)
 - of lubricants
 - degradation and, 373, 376 (figure)
 - mechanisms of, 1363–1369
 - mechanism of, 372, 372 (figure), 1365 (figure)
 - polymer formation and, 1364, 1368 (figure)
 - propagation stage of, 373, 375 (figure), 376 (figure), 1364
 - termination stage of, 373, 1364
 - transition metals as promotor and inhibitor of, 382, 384 (figure), 385, 385 (figure), 1367–1368, 1375 (figure)
- oxidational wear, 1585, 1586 (figure)
- oxidation heat release, 1320–1322, 1321 (figure), 1321 (table)
- aerospace fuels and, 1302
- oxidation induction time (OIT), 1383–1384
- oxidation inhibitors. *See* antioxidants
- oxidation potentials, corrosion and, 466, 466 (figure)
- oxidation stability
- ASTM D4814 and, 201
 - of aviation fuels, 224–225, 1392–1393
 - of base stocks, 352
 - dispersants and, 404–405
 - of distillate fuel oils, 1393, 1394 (figure), 1395–1396, 1395 (figure)
 - of environmentally acceptable ester-based hydraulic fluids, 560–561, 560 (figure), 561 (figure), 567–569, 568 (figure), 569 (figure)
 - of gasoline, 1392, 1392 (figure), 1393 (figure)
 - for gear lubricants, 748
 - of GTL base stocks, 296, 297 (figure)
 - of heat transfer fluids, 967
 - of HFA and HFB fluids, 539
 - of HFC fluids, 543–544
 - of hydraulic fluids, 648–651, 648 (figure), 649 (figure), 649 (table)
 - of industrial lubricants, 323
 - lubricating greases and, 948–950, 949 (figure), 950 (figure)
 - of metalworking and machining fluids, 884
 - of PAOs, 524, 524 (table)
 - SI engines and, 1395
 - of synthetic lubricants, 526–527, 526 (figure), 527 (table)
 - test methods for, 253–254
 - of turbine lubricating oils and hydraulic fluids, 598, 599 (figure), 599 (table), 623–624, 624 (figure), 1373–1374, 1377 (figure), 1378 (figure)
- oxidation testing
- of antiwear, ASTM tests
 - ASTM D943, 1370–1372, 1376 (figure), 1376 (table)
 - ASTM D2272, 1372–1373, 1377 (figure)
 - ASTM D4310, 1372, 1376 (table)
 - of biodegradable lubricants, 1399–1400, 1400 (figure)
 - of engine oils
 - ABOT, 1388, 1390 (figure), 1390 (table)
 - ASTM tests, 1385–1387, 1386 (figure), 1387 (figure), 1389 (figure)
 - BT-10 test, 1388
 - CMOT, 1388, 1391 (figure)
 - of gasoline
 - ASTM D381, 1390–1391, 1392 (figure)
 - ASTM D525, 1391, 1392 (figure), 1393 (figure)
 - ASTM D873, 1392–1393
 - ASTM D2274, 1393, 1394 (figure), 1395 (figure)
 - ASTM D3241, 1393
 - ASTM D4625, 1393–1394, 1395 (figure)
 - ASTM D6468, 1394–1395
 - ASTM D7525, 1395
 - ASTM D7545, 1396
 - IP-467, 1396
 - Rancimat test, 1396
 - of gear oils
 - ASTM tests, 1379–1381, 1381 (figure), 1382 (figure)
 - CEC tests, 1382, 1382 (table), 1383 (figure), 1383 (table), 1384 (figure)
 - JIS-K2514, 1381, 1382 (table)
 - of lubricants, 1396–1399, 1397 (figure), 1398 (figure)
 - of lubricating greases, 1382–1385, 1384 (figure), 1385 (figure), 1386 (figure)
 - methods of, 1400–1401
 - purpose of, 1369–1370
 - of turbine oils
 - ASTM D2070, 1374–1376, 1378 (figure)
 - ASTM D4636, 1376–1377, 1379 (figure)
 - ASTM D5846, 1378–1379, 1380 (figure)
 - ASTM D6514, 1379
 - DIN 51352-2, 1379, 1380 (figure)
 - IP-280, 1373–1374, 1377 (figure), 1378 (figure)
 - IP-306, 1374
- oxygen (O₂)
- in crude oil, 5, 1422
 - in pipeline corrosion, 1439
- oxygenates
- in gasoline, 5, 5 (table), 183–184, 187, 188, 188 (table)
 - reduction of, 26
- P**
- paddle-type rotational viscometer, 1488, 1488 (figure)
- paint compatibility test, for compressor lubricants, 716
- panel coker test, 1396–1397, 1397 (figure)
- paraffinic hydrocarbon base oils, 284, 286, 286 (table), 289, 290 (table)
- paraffinic hydrocarbon fractions, 81
- paraffins, 187, 280
- characteristics of, 3–4
 - composition of, 4
 - determination of, 347
 - isomerization and, 13, 14 (figure)
- paraffin wax (macrocrystalline wax), 85, 87–88, 97
- Parker Hannifin T6H20C vane/piston test, 659
- partial least squares (PLS), 1131–1133
- partial oxidation (POX), 24
- particle counting
- APCs for, 1215, 1229
 - applications of, 1228, 1228 (table)
 - AS4059 standard for, 1235
 - ASTM tests for, 1233, 1235
 - benefits of, 1216, 1216 (table)
 - calibration and verification of, 1229–1230, 1230 (table)
 - chord length and, 1218, 1218 (table)
 - cleanliness codes and, 1220–1221, 1221 (table), 1232, 1232 (table)

- dimensioning and, 1217–1219, 1218 (table), 1219 (table)
- direct imaging, 1226–1230, 1226 (figure), 1227 (figure)
- equivalent circle diameters and, 1218, 1219 (table)
- Feret diameters and, 1218, 1218 (table)
- hardness and, 1217, 1217 (table)
- historical development of, 1216
- interferences in, 1230–1231
- IP 564/IP 565 standards for, 1234
- ISO standards for, 1234–1235
- light extinction for, 1221, 1222 (figure), 1223, 1223 (figure)
- light scatter, 1223–1226, 1224 (figure), 1225 (figure)
- minimum bounding rectangle and, 1218, 1218 (table)
- precision of, 1230, 1231 (table)
- purpose of, 1215–1216
- reporting results in, 1231–1232, 1232 (table)
- sampling and sample preparation for, 1228–1229
- shape and, 1217, 1217 (table)
 - characterization of, 1219, 1220 (table)
 - size and, 1217, 1217 (table)
 - sources and, 1216–1217
- particulates
 - control and removal of, 251
 - DPFs and, 271
 - in hydraulic fuels, 663–664
 - LPG and, 166–167
 - range codes for, 251, 251 (table)
- partitioning, of corrosion inhibitors for pipeline corrosion chemical treatment, 1453–1454, 1454 (figure)
- passenger car motor oils (PCMOs), 351
 - lubricant development trends in, 353–354, 353 (figure), 355 (figure)
- passive extreme-pressure (PEP) agents, 909
- PC-11, ILSAC GF-6 split from, 792
- PCB contamination test, of used oil, 32
- pearlite, 977, 978 (figure), 979
- Peng-Robinson (PR) EOS model, 53
- Peng-Robinson (PR) equation, 89, 91
- Penn State Micro-Oxidation (PSMO) test, 1384–1385
- Pensky-Martens closed cup tester, 244, 312
- pentaerythritol, 556, 556 (figure)
- percent sulfated ash, of detergents, 422–423
- Perfad[®] friction modifiers, 437–438, 440, 440 (figure), 441 (figure)
- perfluoroalkyl ethers (PFAEs), 525
- performance additives, in gasoline, 189–190
- performance package, additives in, 498
- permanent shear stability index (PSSI), 1512–1513
- peroxide number, of petroleum waxes, 105
- peroxides, in butadiene, 346
- persister cells, 1241
- perturbed-chain SAFT (PC-SAFT) EOS model, 54–55, 54 (figure)
- Peterson, Frank, 150–151
- Petroff's law, HL and, 1605–1606
- petroleum coke, 1327
 - ash in, 1346
 - ASTM standards for, 1355–1358
 - classification of, 1344–1345
 - crystalline structure of, 1348–1349, 1349 (figure)
 - density of, 1347–1348
 - feedstocks for, 1343–1344, 1344 (table), 1345 (figure)
 - microtexture formation and, 1342–1343, 1342 (figure), 1343 (figure), 1343 (table)
 - nickel, vanadium, other metals in, 1347
 - optical texture of, 1348–1349, 1348 (table), 1349 (table)
 - production processes of, 1340–1341, 1340 (figure), 1341 (figure), 1341 (table)
 - reactivity of, 1350
 - sulfur in, 1346
 - thermal expansion of, 1349–1350, 1349 (figure)
 - volatile matter in, 1345–1346, 1346 (table), 1347 (table)
- petroleum fractions, hydrogen in, 347
- petroleum gas, sulfur in, 346–347
- petroleum oil. *See also* crude oil; hydrocarbon base oils
 - alkylation and, 13–15, 15 (figure), 15 (table)
 - aromatic and olefin saturation reduction in, 15–18
 - asphaltenes studied for, 1151
 - MS for, 1161–1162, 1162 (figure)
 - capacity as percent of crude, 3 (table)
 - catalytic reforming and
 - benzene concentration reduction in, 12
 - btx recovery in, 12–13, 13 (figure)
 - reactor configurations for, 10–11, 11 (figure)
 - yield-octane relationship in, 12, 12 (figure)
 - yields of, 12, 12 (table)
 - cogeneration and, 25
 - composition of, 279–282, 281 (figure), 282 (figure), 282 (table)
 - costs and consumption of, in United States, 430–431, 430 (figure)
 - flow properties of
 - kinematic viscosity and, 1489–1493, 1491 (table), 1492 (figure), 1492 (table), 1493 (figure), 1494 (figure)
 - kinematic viscosity history and, 1493–1496
 - Saybolt, short-capillary, and orifice viscometers for, 1496–1497
 - fluid catalytic cracking and, 9–10, 9 (figure), 10 (table)
 - future options for refining of, 26–27
 - gas solubility in, 711–714, 713 (figure), 713 (table), 714 (table)
 - heteroatom removal and, 15–18
 - hydrogen production and, 23–24
 - isomerization and, 13, 14 (figure)
 - lube oil base stock production and, 22–23
 - molecular composition challenges with, 1151–1152
 - MS for
 - asphaltenes and, 1161–1162, 1162 (figure)
 - data analysis of, 1157–1160, 1157 (figure), 1158 (figure), 1159 (figure), 1160 (figure)
 - environmental monitoring and, 1162
 - sample preparation in, 1160–1161, 1161 (figure)
 - pollution control in refining of, 25
 - product blending and, 26
 - products of, 5–7
 - refinery flow plan for, 1–2, 2 (figure)
 - resid conversion and upgrading processes for
 - delayed coking, 20–21, 20 (figure), 21 (table)
 - fixed bed hydrocracking, 22, 22 (table)
 - fluid coking/flexicoking, 21
 - fluidized bed hydrocracking, 22, 22 (figure), 23 (table)
 - global installations of, 18, 18 (table)
 - solvent deasphalting, 19–20, 20 (figure)
 - visbreaking, 18–19, 19 (figure), 19 (table)
 - simulated distillation of, 1112
 - sulfur recovery and, 24–25, 24 (figure), 25 (figure)
 - TAN of, 1151
- petroleum pitch, 1327, 1340
 - ash in, 1339
 - ASTM standards for, 1355–1358
 - carbon fibers from, 1353–1354, 1353 (table)
 - coking value of, 1338–1339, 1339 (figure)
 - density of, 1339
 - production processes and applications of, 1331 (table), 1333–1334
 - softening point of, 1334–1335, 1335 (table)
 - solvent fractionation of, 1335–1338, 1336 (figure), 1336 (table), 1337 (table), 1338 (figure)
 - sulfur in, 1339
 - viscosity of, 1335

- petroleum waxes
 abrasion resistance of, 109–110
 additives and, 98
 ASTM standards for, 81, 81 (table), 110–112
 blocking point of, 108, 109 (figure)
 carbonizable substances of, 104, 107 (figure)
 cloud point and, 100–101, 102 (figure)
 coefficient of kinetic friction and, 108–109
 color of, 104, 106 (figure)
 composition of, 79–80, 85, 86 (table), 87, 87 (figure), 88 (table)
 by GC, 106–107
 congealing point and, 98, 100
 crystal structure of, 87–88, 89 (figure), 90 (figure), 90 (table)
 DSC and, 92, 94, 96 (figure), 97–98, 97 (figure)
 EOS for, 88–89, 91–92, 91 (table), 93 (table), 94 (table),
 95 (table)
 finishing process for, 85
 gloss retention of, 107
 hardness and, 102–103, 104 (figure)
 heat of fusion of, 97–98, 97 (figure), 98 (table)
 hot tack of, 110
 melting point and, 98, 99 (figure), 100 (figure), 101 (figure),
 101 (table)
 odor of, 105–106, 107 (table)
 oil content and, 101
 peroxide number of, 105
 physical properties of, 87, 88 (table)
 pour point and, 98
 refining and, 83, 83 (figure)
 solvent dewaxing process and, 83–85, 84 (figure), 85 (table)
 solvent solubility and, 102
 specular gloss of, 107, 108 (figure)
 surface wax of, 107–108
 total wax content of, 108
 transition temperatures, DSC and, 103–104, 105 (figure)
 types of, 85
 viscosity and, 102, 103 (figure)
 weight of wax applied during coating, 108
 Peugeot TU3M wear test, 779 (table), 789 (table)
 Peugeot TU5JP-L4 test, 788 (table)
- pH
 of aqueous polymer quenchant, 1014
 pipeline corrosion and, 1439, 1439 (figure)
- phenate detergents, 421, 422 (figure), 428
- phenol
 hindered, as antioxidant, 1366–1367, 1373 (figure), 1398
 hydroperoxide decomposition and, 377 (figure), 378–379
 radical scavengers and hindered, 379–380, 381 (figure),
 383 (figure)
- phenol connecting group, in polymeric dispersant synthesis,
 396, 396 (figure)
- phenothiazines, radical scavengers and, 381–382
- Phillips, Frank, 151
- phosphate esters, for compressor lubricants, 695 (figure), 698
- phosphonate detergents, 421, 423 (figure), 428
- phosphonic acid dispersants, 398, 399 (figure)
- phosphorus content
 ASTM D4814 and maximum, 201
 EP agents and, 454, 455 (figure)
 in gear lubricants, 746
 in hyperoxide decomposers, 1365, 1370 (figure)
- phosphorus test, of used oil, 33
- photolysis, environmental characteristics and, 1544
- photooxidation, environmental characteristics and, 1544
- photovoltaic thermal (PVT) cell, 48–50
- pH test, of used oil, 33
- physisorption, 1606, 1609 (figure)
- pigging, 1448, 1449 (figure)
- pin-and-vee block device testers, 1679–1680, 1680 (figure),
 1681 (figure)
- pin-on-disk testers, 1680–1681, 1681 (figure)
- pipe cleaning, for pipeline corrosion control, 1448–1449,
 1449 (figure), 1450 (figure)
- pipeline corrosion
 alloying composition in, 1442, 1442 (figure)
 anodic dissolution reactions and, 1424
 ASTM standards for, 1471
 biocides for control of, 1454–1456, 1455 (figure), 1457 (table)
 cathodic reduction reactions and, 1423
 chemical treatment by corrosion inhibitors for
 application methods of, 1452
 classes of, 1450, 1451 (table)
 operating conditions influencing, 1452–1453, 1453 (figure)
 selection criteria for, 1452, 1452 (figure)
 solubility, partitioning, and compatibility, 1453–1454,
 1454 (figure)
 CO₂ partial pressure and, 1437–1438
 corrosivity and CR determination in
 EIS for, 1468, 1469 (figure)
 potentiodynamic anodic polarization and polarization
 resistance for, 1467–1468, 1467 (figure), 1468 (figure)
 potentiostatic polarization for, 1468–1469, 1470 (figure)
 weight loss measurements for, 1465–1466, 1466 (figure)
- environmental control of
 degasification, 1445–1446, 1446 (figure)
 gas-phase contaminants, 1444–1445, 1445 (figure)
 water content and dehydration/dewatering, 1446,
 1447 (figure), 1448, 1448 (figure)
- experimental setups and devices for
 autoclaves, 1456, 1458–1459, 1459 (figure)
 glass cell, 1460, 1462, 1462 (figure)
 goniometer or tensiometer, 1462–1463, 1462 (figure)
 high-velocity rig, 1460, 1461 (figure)
 HRC setups, 1459–1460, 1460 (figure)
 moisture analyzers, 1463–1464, 1463 (figure), 1464 (figure)
 multiphase flow loops, 1456, 1458 (figure), 1459 (figure)
 SSRT, 1464–1465, 1464 (figure), 1465 (figure)
- H₂S in, 1438–1439
- HSLA steel and, 1440–1441, 1441 (figure), 1441 (table)
- hydrogen damage and, 1433–1435
- localized
 erosion corrosion, 1430–1431, 1430 (figure)
 galvanic corrosion, 1431
 intergranular corrosion, 1431
 pitting, 1428–1430, 1429 (figure)
- multiphase flow regime and, 1435–1436, 1436 (figure)
- multiphase velocity and, 1436, 1436 (figure)
- O₂ in, 1439
- oil chemistry and, 1422
- oil interference mechanisms in, 1426–1427, 1426 (table),
 1427 (figure)
- oil-water flow patterns and, 1417–1418, 1419 (figure),
 1420 (figure)
- oil-water mixture and, 1417, 1418 (figure), 1420–1422,
 1421 (table)
- pH and, 1439, 1439 (figure)
- pipe cleaning for control of, 1448–1449, 1449 (figure),
 1450 (figure)
- products of, 1425–1426, 1426 (figure)
- salinity in, 1436–1437, 1437 (figure), 1438 (figure)
- steel microstructure and, 1442–1443, 1443 (figure),
 1444 (figure), 1445 (figure), 1445 (table)
- stress corrosion cracking and, 1431–1433, 1431 (figure),
 1433 (figure)

- temperature and, 1439–1440, 1440 (figure)
- transport of species in, 1424–1425
- uniform, 1427–1428
- water phase wetting and, 1435
- wettability of metal surface in, 1418–1420, 1421 (figure)
- pipeline intervention gadget (PIG), 1448, 1449 (figure)
- pipelines, for aviation fuel transportation, 228
- pipeline samples, 1062
- piping, for heat transfer fluid system, 971
- piston cleanliness, detergents and, 426, 426 (figure)
- pitting, 366, 724, 724 (figure), 1586
- pitting pipeline corrosion, 1428–1430, 1429 (figure)
- plants, in toxicity tests, 1558
- plastic body, 1487
- plate-to-plate viscometer, 1488, 1488 (figure)
- platinum resistance thermometers (PRTs), 1271–1273, 1272 (figure), 1273 (figure), 1507
- ploughing, friction due to, 1567, 1568 (figure)
- Pneurop oxidation test, 1379, 1380 (figure)
- Podbielniak, Walter, 152
- point contact, Hertzian contact and, 1633
- polarization resistance, CR and, 1467–1468, 1467 (figure), 1468 (figure)
- polar moieties, in polymeric dispersant synthesis, 396–401, 397 (figure), 399 (figure), 400 (figure), 401 (figure)
- polishing wear, 366, 725, 725 (figure), 1577–1578, 1581 (figure)
 - superficial tribology and, 1643, 1643 (figure)
- pollution control, in petroleum oil refining, 25
- polyalkylene glycols (PAGs)
 - application and performance characteristics of, 520–522, 521 (figure)
 - benefits of, 843–844
 - chemical characteristics of, 519–520
 - chemistry and manufacturing of, 517–518, 517 (figure), 518 (figure)
 - for compressor lubricants, 695–696, 696 (figure)
 - historical development of, 846
 - lubricating greases and, 937
 - physical properties of, 518–519, 519 (table), 520 (table)
 - solubility reversal of, at high temperature, 897, 897 (figure)
 - for turbines, 593–595, 595 (table)
- polyalphaolefins (PAOs), 276, 321, 322, 478
 - chemical properties and performance characteristics of, 524, 524 (table)
 - chemistry and manufacturing of, 523, 523 (figure)
 - for compressor lubricants, 696, 696 (figure), 697 (figure)
 - history of, 522–523
 - lubricating greases and, 936–937
 - physical properties of, 523–524, 523 (table)
 - for turbines, 593, 595 (table)
- polycyclic aromatic hydrocarbons (PAHs), 45
- polydispersity index, 392
- polyglycols. *See* polyalkylene glycols
- polyisobutylene (PIB), 392–393, 393 (figure), 411, 478
- polymer-containing oils, shear stability of, 1511–1513, 1511 (figure), 1512 (figure)
- polymeric additives, 364, 474–475
- polymeric dispersants, 391
 - synthesis of
 - connecting group in, 394–396, 394 (figure), 395 (figure), 396 (figure)
 - hydrocarbon group in, 392–394, 393 (figure)
 - polar moieties in, 396–401, 397 (figure), 399 (figure), 400 (figure), 401 (figure)
- polymeric thickeners, for gear lubricants, 730–731
- polymers
 - aqueous, quenching and, 1006–1007, 1006 (figure)
 - appearance of, 1011–1012
 - cloud point of, 1015, 1015 (figure)
 - conductance of, 1014, 1014 (figure)
 - cooling curve analysis for, 1017, 1017 (figure), 1018 (figure)
 - corrosion inhibitors and, 1015–1016, 1015 (figure)
 - degradation analysis for, 1016, 1016 (figure)
 - foaming and, 1016
 - pH of, 1014
 - refractive index and, 1012, 1012 (figure), 1013 (figure)
 - viscosity of, 1012–1013, 1013 (figure)
 - water content and, 1014
- ester
 - degradation-related viscosity loss and, 487–488, 490 (figure)
 - mechanical shear and, 483
 - shear-related viscosity loss and, 484–487, 486 (figure), 487 (figure), 488 (figure), 489 (figure)
 - structures of commercially available, 484 (table)
 - synthesis of, 481–484, 482 (figure), 483 (figure)
 - thickening efficiency and, 484, 485 (figure)
- olefin-based, 478–481, 479 (figure), 479 (table), 480 (table), 481 (figure)
- olefins and sensitivity of, 333
- oxidation and formation of, 1364, 1368 (figure)
- SE, 392, 481, 484
- polymer solution theory, of asphaltene phase behavior, 52
- polymethacrylates (PMAs), 392, 476, 481–484, 483 (figure)
- polymethylmethacrylate (PMMA), 997–998
- polyolesters
 - application and performance characteristics of, 516–517
 - chemical characteristics of, 516
 - chemistry and manufacturing of, 513–515, 514 (figure)
 - for compressor lubricants, 695 (figure), 696–697
 - physical properties of, 515–516
 - for turbines, 595–596, 596 (table), 597 (figure)
- polyphenol ethers (PPEs), 525
- polytetrafluoroethylene (PTFE), 68, 464–465
- polyurea greases, 939, 941
- port blocking, detergents and, 426, 426 (figure)
- port-fuel injection (PFI), 760–761
- potentiodynamic anodic polarization, CR and, 1467–1468, 1467 (figure), 1468 (figure)
- potentiometry, for lubricant titration analysis, 1073–1077, 1074 (table), 1076 (figure), 1076 (table)
- potentiostatic polarization, for CR, 1468–1469, 1470 (figure)
- pour point, 7
 - of compressor lubricants, 703
 - definition of, 491
 - determination of, 1520–1521, 1521 (figure)
 - diesel fuel oils and, 249–250
 - of fuel oils, 1331
 - for gear lubricants, 743
 - historical development of, 1520
 - petroleum waxes and, 98
 - turbine lubricating oils and hydraulic fluids and, 612, 616–617
- pour point depressants (PPDs), 491–492, 492 (figure), 493 (figure)
 - for automotive engine lubricants, 768–769
 - for compressor lubricants, 699 (table), 700
 - for gear lubricants, 730
 - hydraulic fluids and, 669
- power law model, 1487
- powertrain systems, improving, 769
- power transfer, hydraulic fluids and, 645, 646 (figure)
- Prabhu-Ramesh correlation, quenching cooling curve analysis and, 1001–1002

precipitation number
 in compressor lubricants, 706
 in gear lubricants, 742–743
 quenching and, 1010

precision
 in measurement processes, 1702–1703, 1703 (figure)
 monitoring, 1704–1706

preformed soaps, 941

premature wear, 888

premium coke, 1345

pressure differential scanning calorimetry oxidation test, 949

pressure drop, heat transfer fluids and, 961, 961 (table)

pressure gauges, for heat transfer fluid system, 972

pressure-viscosity coefficient, 1603–1605, 1604 (figure), 1605 (figure), 1605 (table)
 tribology TRL and, 1645–1646, 1646 (figure), 1647 (figure)

principal components regression (PCR), 1131–1133

product property conformance to specification, 1702

proficiency testing programs (PTPs), 1080, 1098, 1099, 1099 (table)

prolonged worked penetration, lubricating grease consistency stability and, 944

propane, 145. *See also* liquefied petroleum gas
 auto, 169
 decomposition of, 339
 dryness of
 autorefrigeration and, 162
 determination of, 158–159
 dissolved water and, phase behavior of, 159–160, 159 (table), 160 (table)
 gas hydrates and, 160–162
 methanol and, phase behavior of, 162–164, 163 (table), 164 (table)
 water measurement and, 164–165
 water sources and, 164
 ethanol in, 163
 ethylene formation from, 336, 339
 isopropanol in, 163
 liquid, 171
 phase behavior of dissolved water in, 159–160, 159 (table), 160 (table)

propane-butane mix, 145. *See also* liquefied petroleum gas

propane hydrates, 160–161

propane P-H diagram, 148 (figure)

propylene, 333
 ASTM test methods and characterization of, 344–345
 to finished product diagram, 335 (figure)
 thermophysical properties of, 343 (table)

puffing, 1345

pumpability, of heat transfer fluids, 966–967

pump derating, HFA, HFB, HFC fluids and, 547–548, 547 (table)

pump-end ball bearing (PEBB), 1631

pump performance testing, 546, 546 (table)

pumps, for heat transfer fluid system, 972

PV curves, 684, 685 (figure)

pyrolysis
 clean-coke process for, 117
 COED process for, 117
 current research on, 118–119
 direct coal liquefaction pathway compared to, 128–129, 128 (figure), 129 (figure)
 encoal process for, 118, 118 (figure)
 Lurgi-Ruhrgas process for, 115–117
 occidental process for, 118
 in olefin steam cracking process, 340
 reactions in, 115, 116 (figure)
 Toscoal process for, 117, 117 (figure)
 Union Carbide process for, 117–118
 yield of volatile products in, 118, 119 (figure)

Q

quality assurance (QA), 1701, 1704–1708

quality control (QC), 1702, 1704–1708. *See also* aviation fuels, quality control for

quantitative structure activity relationships (QSARs), 1540, 1550

quenching, 869, 896. *See also* steel
 aqueous polymer, 1006–1007, 1006 (figure)
 appearance of, 1011–1012
 cloud point of, 1015, 1015 (figure)
 conductance of, 1014, 1014 (figure)
 cooling curve analysis for, 1017, 1017 (figure), 1018 (figure)
 corrosion inhibitors and, 1015–1016, 1015 (figure)
 degradation analysis for, 1016, 1016 (figure)
 foaming and, 1016
 pH of, 1014
 refractive index and, 1012, 1012 (figure), 1013 (figure)
 viscosity of, 1012–1013, 1013 (figure)
 water content and, 1014

ASTM tests for
 acid number, 1008
 aqueous polymer quenchants, 1011–1016
 ash content, 1010
 biodeterioration monitoring procedures, 1016–1017, 1017 (figure)
 carbon residue, 1009–1010
 cooling curve analysis, 1010–1011, 1011 (figure), 1017, 1017 (figure), 1018 (figure)
 flash point and fire point, 1008
 fluid biodeterioration processes, 1016
 GM quenchometer test, 1010, 1010 (figure)
 IR spectroscopy, 1008, 1009 (figure)
 precipitation number, 1010
 saponification number, 1008
 specific gravity, 1008
 standards, 1028–1029
 used quenching oil, 1010–1011
 viscosity, 1007–1008
 water content, 1008–1009, 1009 (figure)

bath maintenance for, 1007

cooling curve analysis of
 advanced, 1017–1020, 1020 (figure), 1021 (figure)
 agitation, 996–999, 997 (figure), 998 (figure), 998 (table)
 ASTM test for, 1010–1011, 1011 (figure)
 cooling time and rate parameters, 1000, 1000 (figure)
 data acquisition for, 991–992, 992 (figure)
 HTC and critical heat flux, 1002, 1003 (table), 1020, 1021
 with Lišič-Petrofer probe, 1019–1020, 1021 (figure), 1022, 1022 (figure), 1023 (figure), 1024 (figure)
 modified Segerberg hardening power, 1000–1001, 1001 (figure)
 polymer quenchants, 1017, 1017 (figure), 1018 (figure)
 Prabhu-Ramesh correlation, 1001–1002
 reference oils, 999, 999 (table)
 section size and probe shape, 995–996, 996 (figure)
 standard probes for, 992–993, 993 (table), 994 (figure), 994 (table)
 surface oxides and surface roughness, 993, 995, 995 (figure)
 with temperature gradient method, 1019, 1022

definition of, 977

fluid sampling and, 1007

fundamentals of
 acoustical measurements, 988–989, 989 (figure), 989 (table), 990 (figure)
 film boiling, factors influencing, 986, 987 (figure), 988, 988 (figure), 988 (table)
 rewetting impact on cooling behavior, 989, 990 (figure), 991, 991 (figure)

- shock film boiling, 988
- steel rewetting kinetics, 985–986, 986 (figure), 987 (figure)
- Grossman hardenability and, 983–985, 984 (figure), 984 (table), 985 (figure), 985 (table)
- hardenability of steel and, 980–981, 980 (figure), 981 (figure), 982 (table)
 - measurement of, 982–985, 983 (figure), 984 (figure), 984 (table), 985 (figure), 985 (table)
- Jominy bar end-quench test, 982–983, 983 (figure)
- oils
 - accelerated, 1003–1004
 - agitation influence on, 1024, 1024 (table)
 - classification of, 1003–1005, 1004 (table), 1005 (figure), 1005 (table)
 - classification of, by GM quenchometer test, 1006, 1006 (figure), 1006 (table)
 - conventional, 1003
 - martempering, 1004–1005, 1005 (figure), 1005 (table)
 - observation of, 1025
 - severity of, 1002, 1003 (figure)
 - temperature influence on, 1023, 1024 (table)
 - wettability of, 1003, 1003 (figure)
 - water for, 1025–1027, 1025 (figure), 1025 (table), 1026 (figure), 1027 (figure), 1028 (figure)
- quenchometer test, GM, 1006, 1006 (figure), 1006 (table), 1010, 1010 (figure)
- R**
- Rabinowitz abrasive wear model, 1582 (figure)
- radiation stability, of hydrocarbon base oils, 320, 320 (table)
- radical scavengers
 - antioxidants as, 1365, 1370 (figure)
 - arylamines and, 381, 382 (figure), 384 (figure), 386, 387 (figure)
 - hindered phenol and, 379–380, 381 (figure), 383 (figure)
 - phenothiazines and, 381–382
 - ZDDPs and, 379, 380 (figure)
- rail transport, for aviation fuels, 229
- rancidity control, metal-removal fluids and, 886
- Rancimat test, for gasoline oxidation testing, 1396
- range codes, for particulates, 251, 251 (table)
- rapeseed oil, 561, 562 (table)
- rapid small scale oxidation test (RSSOT), 1395
- rare earth compounds, lubrication and, 1616–1618, 1617 (figure), 1617 (table), 1618 (figure), 1618 (table)
- raw coke, 1345
- reaction temperature, maximum, 1323–1325, 1324 (table)
- Reavell VHP 15 Compressor Rig Test, 709, 710 (figure), 710 (table), 711 (table)
- reciprocating compressors, 687–688, 688 (figure), 688 (table)
- reclaiming oil, 29
- recycled oil, 29, 297. *See also* re-refining
- Redlich-Kwong (RK) equation, 89, 91
- reference gauge height, 1056–1057
- reference gauge point, 1056
- reference quenching oils, 999, 999 (table)
- reformulated gasoline, 183–184
- refractive index
 - aqueous polymer quenchants and, 1012, 1012 (figure), 1013 (figure)
 - of gasoline, 203–204
 - IL lubricants and, 1042, 1043 (table)
- refrigeration lubricants, hydrocarbon base oils and, 324
- Registration, Evaluation, and Authorization of Chemicals (REACH), 498, 500
- regular solution model, of asphaltene phase behavior, 53
- Reid vapor pressure (RVP), 222
- replacement thermometric devices (RTDs), 1507
- reprocessing oil, 29
- re-refining
 - definition of, 29
 - history of, 29–30
 - processes of, 33–35, 35 (figure), 36 (figure)
 - used oil for
 - assessment of, 30–31, 30 (table), 31 (table)
 - BERC process, 299
 - by-products of, 297–298
 - flow diagram for, 299 (figure)
 - IFP process, 299
 - KTI process, 299–300, 300 (figure)
 - Meinken process, 299
 - quality comparison of, 300, 301 (table)
 - testing of, 31–33, 33 (table)
 - uses of, 300, 302, 302 (figure)
- research octane number (RON), 5, 180, 192–194, 193 (table), 1279
- resid conversion and upgrading processes
 - delayed coking, 20–21, 20 (figure), 21 (table)
 - fixed bed hydrocracking, 22, 22 (table)
 - fluid coking/flexicoking, 21
 - fluidized bed hydrocracking, 22, 22 (figure), 23 (table)
 - global installations of, 18, 18 (table)
 - solvent deasphalting, 19–20, 20 (figure)
 - visbreaking, 18–19, 19 (figure), 19 (table)
- residual matter, LPG and, 165–166
- resin, soot interaction with, 390, 390 (figure)
- resistance temperature detectors (RTDs), 1507
 - PRTs, 1271–1273, 1272 (figure), 1273 (figure)
 - thermistors, 1273–1275, 1274 (figure)
 - thermocouples, 1274–1275, 1274 (figure)
- resonantly enhanced multiphoton ionization (REMPI), 1156
- resource conserving, fuel economy and, 431–432
- retail fuel systems, fouling and, 1250, 1250 (figure)
- reversed-phase HPLC (RP-HPLC), 306
- reverse-flow viscometers, 1491, 1493 (figure)
- Reynolds number, 1281
- rheology
 - definition of, 1486
 - of environmentally acceptable ester-based hydraulic fluids, 557–558, 558 (figure)
 - of hydraulic fluids, 667–670
- Riazi and Mansoori (RM) equation, 89, 91–92
- ring sticking, additives and, 371
- riveting, 869
- road transport, for aviation fuels, 229
- ROBO apparatus, 759, 773, 791
- rolling, metal-forming, 868
- rolling ball viscometer, 1488–1489, 1489 (figure)
- roll stability, lubricating grease consistency stability and, 944
- root cause analysis, of biodeterioration, 1259, 1260 (figure)
- rotary compressors, 690–692, 690 (figure), 691 (figure), 692 (figure)
- rotary pressure vessel oxidation test (RPVOT), 567, 568 (figure), 601, 602 (figure), 1373
- rotating bomb oxidation test (RBOT), 707
- round-robin (interlaboratory) exchange testing, 1707
- rubber
 - biocorrosion of, 1245–1246, 1246 (table)
 - heat transfer fluids and, 968
- run-in polishing (RIP), 1658–1660, 1659 (figure)
 - concept oil, in HMMWV simulation, 1662–1664, 1663 (figure), 1664 (figure)
- rust
 - definition of, 366
 - electrochemical nature of, 1405–1408, 1406 (figure)
 - lubricant basicity effect on, 468, 472 (figure)

mechanism of, 467, 467 (figure)
 turbine lubricating oils and hydraulic fluids and, 626–627
 rust and oxidation (R&O) oils, 728, 729 (table)
 rust inhibitors, 468, 469 (figure)
 ASTM tests for, 604–605
 for automotive engine lubricants, 766
 for compressor lubricants, 698, 699 (table)
 for engine oils, 757
 for gear lubricants, 746
 humidity cabinet and, 1411, 1412 (figure)
 for hydraulic fluids, 666
 lubricating greases and, 952
 mechanism of, 1407, 1407 (figure)
 mode of action of, 468, 469 (figure)
 structures of, 470 (figure)
 for turbine lubricating oils and hydraulic fluids, 603–605,
 605 (figure)
 ruthenium, FTS and, 136, 138, 139 (figure), 140 (figure)
 Ryder Gear Tester, 606, 610

S
 salicylate detergents, 421, 423 (figure), 428
 salinity, in pipeline corrosion, 1436–1437, 1437 (figure),
 1438 (figure)
 salt spray apparatus, 1410–1411, 1411 (figure)
 saponification, of esters, 558–560, 559 (figure)
 saponification number, quenching and, 1008
 saturate, aromatic, resin, and asphaltene (SARA) analysis, 48, 49
 Saybolt patent, 151
 Saybolt viscometers, 1494 (figure), 1496, 1497 (figure)
 scale wax, 85
 scanning-electron-microscopy (SEM), 43, 44 (figure)
 scanning-tunneling-microscopy (STM), 43
 scoring, definition of, 366
 scratching, definition of, 366
 screw compressors, rotary, 690–691, 690 (figure), 691 (figure)
 scuffing, 366, 725–726, 726 (figure)
 definition of, 1589
 examples of, 1589, 1589 (figure)
 FZG test of, gear lubricants and, 747–748
 load capacity testing, tribology TRL and, 1651–1653,
 1652 (figure), 1653 (figure)
 micro-, superficial tribology and, 1643, 1644 (figure)
 run-in polishing and, 1658–1660, 1659 (figure)
 spiral bevel gear threshold of, 1654, 1655 (figure),
 1656 (figure)
 superficial tribology and, 1644–1645, 1645 (figure)
 seals
 compressor lubricants compatibility with, 716
 gear lubricants compatibility with, 748
 heat transfer fluids and, 968
 hydraulic fuels compatibility with, 666–667, 667 (table)
 performance of, dispersants and, 406
 structures of, 494, 494 (figure)
 seal-swell agents, 495, 666–667
 sediment content, control and removal of, 250, 251
 sediment toxicity tests, 1558
 Segerberg hardening power, modified, 1000–1001, 1001 (figure)
 seizure, in lubrication, 1595
 selective catalytic reduction (SCR), 355
 self-monitoring, measurement process, 1702
 semisynthetic fluids, metalworking and machining fluids, 881–882
 servo-operated automated tank gauge, 1065
 settling tanks, for contamination removal, 923–924
 shale oil, 26
 shear rate, 1486
 viscosity and, 1508–1509, 1509 (figure)
 shear stability
 of engine oils, 759
 fuel injector test of, 1512, 1512 (figure)
 for gear lubricants, 749
 of hydraulic fluids, 667–668, 667 (figure)
 permanent index of, 1512–1513
 of polymer-containing oils, 1511–1513, 1511 (figure),
 1512 (figure)
 sonic test of, 626, 1511, 1511 (figure)
 of turbine lubricating oils and hydraulic fluids, 625–626
 shear strain, 1487
 shear stress, 1486
 shear thinning, 1487
 sheet metal forming test, 1688
 shock film boiling, 988
 short-capillary viscometers, 1496–1497
 short-chain chlorinated paraffins (SCCPs), 767–768, 907
 Shukhov, Vladimir, 333
 shutdown time, start-up wear and, 432, 433 (figure)
 silicon, microelemental analysis methods of, 1096
 silicones, 524–525
 for compressor lubricants, 697
 silicon test, of used oil, 33
 silver corrosion inhibitors, 189
 silver corrosion test, 200
 simulated distillation, GC and, 1111–1113
 single common powertrain lubricant (SCPL), 832
 Single Contact Model (SCM), 1650–1651, 1666–1669, 1667 (figure),
 1669 (figure)
 single particle optical sizing (SPOS) procedure, 1221, 1224,
 1224 (figure)
 skimmers, for contamination removal, 924
 slack wax, 85
 slide-way lubricants, 898
 sliding bottle test, 1688
 sliding velocity, tribology and, 1640
 slow strain rate test (SSRT), 1464–1465, 1464 (figure), 1465 (figure)
 sludge
 definition of, 366
 formation of, 366
 ZDDPs and formation of, 650, 650 (figure)
 small bearings, greases in, 949
 small scale closed cup tester, 244–245
 small-volume viscometers, 1492
 smearing, adhesive and polishing wear and, 1577–1578, 1581 (figure)
 smoke point, 221
 smoke tendency, of aerospace fuels, 1308–1309
 Snelling, Walter, 150
 soap content, detergents and, 423
 soaps, 418, 425, 426 (figure)
 Soave-Redlich-Kwong (SRK) equation, 89, 91–92
 Society of Automotive Engineers (SAE), 351
 J300 viscosity classification, 760
 J306c viscosity classification, 738, 740 (table)
 J2360 classification of, 739–740, 740 (table), 741 (table)
 turbine lubricating oils and hydraulic fluid standards of, 640
 sodium-plus-potassium, in gas turbine fuel oils, 265–266, 265 (table)
 softening point, 1487
 of petroleum pitch, 1334–1335, 1335 (table)
 soldering, 869
 solid dispersions, metalworking and machining fluids and, 884
 solid friction, 871
 solidification, of aerospace fuels, 1305
 solid lubricants
 boron nitride, 463, 464 (figure)
 CaF₂, 463–464
 definition of, 461

- diffusion coating and, 464
- frictional properties of, 463, 464 (table), 465, 466 (table)
- graphite, 462–463, 463 (figure), 465
- MoS₂, 463, 464 (figure), 465
- PbO, 463
- PTFE and, 464–465
- uses of, 461–462
- wear control with, 465, 465 (figure)
- solid models, of asphaltene phase behavior, 53
- solid particles, aviation fuel quality control and, 232
- solubility
 - asphaltenes and, 47
 - of corrosion inhibitors for pipeline corrosion chemical treatment, 1453–1454, 1454 (figure)
 - environmental characteristics and low, 1554–1555, 1554 (figure)
 - of gas in oil, 493
 - PAGs reversal of, at high temperature, 897, 897 (figure)
- soluble oils, metalworking and machining fluids, 880–881
- soluble organomolybdenum compounds, 766
- solvency, of hydrocarbon base oils, 315–316, 315 (table), 316 (figure), 316 (table), 317 (figure), 317 (table)
- solvent
 - asphaltene deposition prevention with, 66
 - deasphalting, 19–20, 20 (figure)
 - dewaxing process, 83–85, 84 (figure), 85 (table)
 - mineral oil base stocks and, 288–289, 293
 - extraction, hydrotreating, clay finishing and, 35, 36 (figure)
 - extraction, in direct coal liquefaction
 - asphaltene conversion pathways in, 126–127, 128 (figure)
 - catalytic conversion pathways in, 127, 128 (figure)
 - China and, 124, 126 (figure), 126 (table)
 - coal rank and, 126, 127 (figure)
 - Exxon donor solvent coal liquefaction process for, 119–120, 122, 123 (figure)
 - H-coal process for, 119, 121 (figure), 122 (figure)
 - Kohleol process for, 122, 123 (table)
 - light gas production, operating temperature and, 124, 126, 126 (figure)
 - LSE process for, 122
 - NEDO process for, 122, 124 (figure)
 - operation costs of, 129
 - plants for, 119, 120 (table)
 - product yields in, 119, 121 (figure)
 - SRC-I and SRC-II processes for, 119
 - temperature and reaction times in, 126, 127 (figure)
 - thermal pyrolysis pathway compared to, 128–129, 128 (figure), 129 (figure)
 - Wilsonville Pilot Plant, CTSL processing for, 123–124, 124 (figure), 125 (table)
 - fraction, of petroleum pitch, 1335–1338, 1336 (figure), 1336 (table), 1337 (table), 1338 (figure)
 - refining
 - mineral oil base stocks and, 287–288, 291 (figure)
 - turbine oil base stocks and, 590, 592 (figure), 593 (table)
 - solubility, petroleum waxes and, 102
 - washed and unwashed gum, 201
- Sommerfeld number, 1677
- sonic shear stability test, 626, 1511, 1511 (figure)
- soot
 - formation of, 366–367
 - IR spectroscopy and, 1133, 1134 (figure)
 - in lubricants, cold flow properties of, 1535
 - resin interaction with, 390, 390 (figure)
- “sour” gas, 147
- “space velocity,” 18
- spalling, 1586
- micropitting and, tribology TRL and, 1655–1656, 1656 (figure), 1657 (figure)
- WAM testing for, 1656–1658, 1657 (figure), 1658 (figure), 1659 (figure)
- spark-ignition direct injection (SIDI) engines, 190, 1286–1287, 1287 (figure)
- spark-ignition (SI) engines, 179, 190, 763
 - combustion in
 - chamber development of, 1283–1287, 1283 (figure), 1286 (figure), 1287 (figure)
 - fundamentals of, 1279–1283, 1280 (figure), 1281 (figure), 1282 (figure)
 - oxidation stability and, 1395
- specific gravity
 - of compressor lubricants, 702
 - of heat transfer fluids, 968
 - of hydrocarbon base oils, 315, 315 (table)
 - quenching and, 1008
- specific heat
 - of compressor lubricants, 715–716
 - of heat transfer fluids, 968
- specific impulse, of aerospace fuels, 1310, 1310 (table), 1311 (figure)
- specular gloss, of petroleum waxes, 107, 108 (figure)
- spinning, metal-forming, 893
- spiral bevel gear, scuffing threshold for, 1654, 1655 (figure), 1656 (figure)
- sponge coke removal, 21
- spontaneous ignitability, of aerospace fuels, 1299, 1306
- spot samples, 1061, 1061 (figure)
- spray flammability parameter (SFP), 545
- spray ignition tests, for fire resistance, 620, 620 (figure), 621 (figure)
- squeeze-type lubricant films, 873, 873 (figure)
- SRC-I and SRC-II processes, 119
- stabilization patent, 151
- stabilizers, 363–366
- Stabinger viscometers, 1495–1496
- standard platinum resistance thermometers (SPRTs), 1271, 1507–1508, 1508 (table)
- standard reference materials (SRMs), 1097–1098, 1099 (table)
- start-up wear, shutdown time and, 432, 433 (figure)
- static bleed test, for lubricating greases, 954
- static dissipator additives (SDAs), 1110
- static electricity
 - aviation fuels and, 225
 - gasoline and, 203
- static gases, thermodynamic properties and, 1318–1319
- static petroleum measurement
 - API standards for, 1055–1056
 - ASTM standards for, 1068
 - calculations in, 1065–1067
 - definition of, 1055
 - density or API gravity test for, 1066–1067
 - free water and, 1058–1059
- gauging operations in
 - innage measurement for, 1063–1064
 - marine vessels and, 1065
 - outage measurement for, 1064–1065
 - thermometers and, 1062–1063
- manual sampling in
 - pipeline samples, 1062
 - spot samples, 1061, 1061 (figure)
 - tools for, 1059–1060, 1060 (figure)
 - types of, 1060–1061, 1060 (figure)
- temperature measurement in, 1057–1059
- terminology of, 1056–1057
- statistical association fluid theory (SAFT) EOS model, 53–55, 54 (figure)

- steady-flow energy equation, 1325
- steady-state efficiency, of hydraulic fluids, 669–670, 669 (figure)
- steam cracking, for olefin production, 333, 334 (figure), 335 (figure)
- fractionation in, 340–341
 - process of, 339–340, 340 (figure)
 - pyrolysis in, 340
 - recovery in, 341
 - test sampling points in, 342, 343 (figure)
 - unit flow in, 341 (figure)
- steam reforming, 23–24
- steam turbine oils, horizontal disk test for, 1412
- steam turbines, 582
- control fluid system of, 586 (figure)
 - shaft driven lubrication system of, 585 (figure)
- steel
- alloying composition of, 1442, 1442 (figure)
 - CCT diagrams of, 979–980, 980 (figure)
 - corrosion, aviation fuels and, 224
 - hardenability of, 980–981, 980 (figure), 981 (figure), 982 (table)
 - measurement of, 982–985, 983 (figure), 984 (figure), 984 (table), 985 (figure), 985 (table)
 - high-strength low-alloy, 1440–1441, 1441 (figure), 1441 (table)
 - hyper-eutectoid and hypo-eutectoid, 1577, 1579 (figure)
 - IL lubricants and, 1043–1044, 1043 (figure)
 - microstructure of, 1442–1443, 1443 (figure), 1444 (figure), 1445 (figure), 1445 (table)
 - phase transformation of, 977, 978 (figure), 979
 - rewetting kinetics, 985–986, 986 (figure), 987 (figure)
 - TTT diagrams of, 979, 980 (figure)
 - uncoated, friction and wear reduction of, 852–853, 852 (figure)
- steric stabilization, 390, 390 (figure)
- stick/slip test, 1687
- stoichiometry, aerospace fuels and, 1302, 1306–1307
- storage stability
- of aerospace fuels, 1297–1298, 1313
 - of aviation fuels, 224–225
 - of distillate fuels, 1393–1394, 1395 (figure)
 - of gear lubricants, 749
 - low-temperature, 612, 616–617
 - of metalworking and machining fluids, 883–884
 - test methods for, 254–255
- straight oils, 876–877, 899
- strapping charts, 1056–1057
- stress corrosion cracking (SCC), 1431–1433, 1431 (figure), 1433 (figure)
- stress-oriented hydrogen-induced cracking (SOHIC), 1434–1435
- Stribeck curve, 1599, 1599 (figure), 1677
- tribological testing of, 853, 854 (figure), 855 (figure)
- Stribeck number, 652, 652 (figure), 653 (figure)
- styrene-ester (SE) polymers, 392, 481, 484
- submerged turbine pump (STP), 1260, 1261 (figure)
- subsurface structure, wear and, 1574, 1576 (figure), 1577 (figure), 1578 (figure)
- succinimide connecting group, in polymeric dispersant synthesis, 394, 394 (figure)
- sulfated ash
- microelemental analysis of, 1096
 - phosphorus, and sulfur (SAPS) limits, 356, 428
- sulfonate detergents, 421, 422 (figure), 428
- sulfonic acid substrates
- natural, 412–413, 413 (figure)
 - synthetic, 411–412, 411 (figure), 412 (figure)
- sulfur, 18
- active, 908
 - ASTM D4814 and maximum, 200–201
 - in crude oil, 4, 1422
 - in diesel fuel oils, 258–259, 259 (table), 264
 - EP agents, 458, 459 (figure), 908–909, 908 (figure), 909 (table)
 - in fuel oils, 7–8, 1331 (table), 1332–1333
 - in gear lubricants, 746
 - greases and, 448, 448 (table)
 - hydrocarbon base oils and, 320–321
 - in hyperoxide decomposers, 1365, 1370 (figure)
 - LPG and, 166
 - lubrication and, 1615
 - microelemental analysis methods of, 1097, 1097 (table)
 - olefins and, 447–448, 448 (figure), 448 (table), 449 (figure), 450 (figure)
 - in petroleum coke, 1346
 - in petroleum gas, 346–347
 - in petroleum pitch, 1339
 - reactive, 908
 - recovery, 24–25, 24 (figure), 25 (figure)
 - reduction of, 26
 - ZDDPs and, 909, 909 (table)
- sulfur-containing odorants, 169
- sulfurized fats, generic structures of, 449 (figure)
- supercritical fluid chromatography (SFC), 306, 1109
- surface conformity, 1570–1573
- surface energy, 1575
- surface forces apparatus (SFA), 55
- surface-free energy, 1575–1576
- surface oxides, quenching cooling curve analysis and, 993, 995, 995 (figure)
- surface roughness
- data analysis of, 1569–1573, 1570 (figure), 1570 (table), 1571 (figure), 1571 (table), 1572 (figure), 1573 (figure)
 - quenching cooling curve analysis and, 993, 995, 995 (figure)
 - standards for, 1622
 - wear surfaces and, 1567–1569, 1569 (figure), 1569 (table)
- surface stress, tribology and, 1636, 1636 (figure)
- surface tension
- of aerospace fuels, 1305–1306
 - of base stocks, 353
 - of IL lubricants, 1041, 1041 (table)
- surface-to-surface contact wear, 443
- surface wax, of petroleum waxes, 107–108
- surfactants
- aviation fuel quality control and, 232–233
 - HFA and HFB fluid composition and, 537, 537 (table)
- suspended-level kinematic viscometers, 1493 (figure)
- synchronizer SSP 180 test, for gear lubricants, 748–749
- synergism
- antioxidants and, 385–386, 386 (figure), 387 (figure)
 - of EP agents, 458, 459 (figure), 460–461, 460 (figure)
 - of turbine lubricating oils and hydraulic fluids and antioxidants, 600, 601 (table)
- synthetic fluids, metalworking and machining fluids, 882–883, 882 (figure)
- synthetic heat transfer fluids, 965. *See also* heat transfer fluids
- synthetic hydrocarbons. *See* butadiene; butylene; C₄ olefins; ethylene; olefins; propylene
- synthetic lubricants
- alkylated cyclopentanes, 525–526
 - ASTM standards for, 529–531
 - classes of, 513–514, 514 (figure)
 - cyclohexane derivatives, 526
 - environmental acceptability of, 528–529, 529 (table), 548, 548 (table)
 - HFA and HFB fluids
 - applications of, 537, 538 (table)
 - composition of, 535–537, 536 (table), 537 (table)
 - fire resistance of, 545–546, 546 (table)

- general features and chemistry of, 535
 - manufacturing of, 537
 - material and paint compatibility of, 546, 547 (table)
 - properties of, 537–540
 - pump derating and, 547–548, 547 (table)
 - pump performance testing of, 546, 546 (table)
 - HFC fluids, 535
 - applications of, 542–543
 - composition of, 541–542, 541 (figure)
 - fire resistance of, 545–546, 546 (table)
 - general features of, 540–541
 - manufacturing of, 542
 - material and paint compatibility of, 546, 547 (table)
 - properties of, 543–545, 543 (table), 544 (figure), 545 (table)
 - pump derating and, 547–548, 547 (table)
 - pump performance testing of, 546, 546 (table)
 - HFD fluids, 535
 - lubricity of, 527–528, 528 (table)
 - manufacturing technology of, 515
 - oxidation stability of, 526–527, 526 (figure), 527 (table)
 - PAGs
 - application and performance characteristics of, 520–522, 521 (figure)
 - chemical characteristics of, 519–520
 - chemistry and manufacturing of, 517–518, 517 (figure), 518 (figure)
 - physical properties of, 518–519, 519 (table), 520 (table)
 - PAOs
 - chemical properties and performance characteristics of, 524, 524 (table)
 - chemistry and manufacturing of, 523, 523 (figure)
 - history of, 522–523
 - physical properties of, 523–524, 523 (table)
 - PFAEs, 525
 - polyolesters and diesters
 - application and performance characteristics of, 516–517
 - chemical characteristics of, 516
 - chemistry and manufacturing of, 513–515, 514 (figure)
 - physical properties of, 515–516
 - PPEs, 525
 - raw materials of, 514–515
 - relative cost of, 529, 529 (table)
 - silicones, 524–525
 - synthetic sulfonic acid substrates, 411–412, 411 (figure), 412 (figure)
 - synthetic waxes, 79
 - system component fouling, 1249–1251, 1250 (figure), 1251 (figure)
- T**
- tag closed cup tester, 244
 - Tamura probe, 993
 - tapered bearing simulator (TBS), 1509–1510
 - tapered-plug viscometer (TPV), 1509
 - tapes and bobs, 1057
 - tapping torque test, 1686, 1686 (figure), 1687 (figure)
 - Taylor dispersion (TD) technique, 45
 - technology readiness level (TRL), tribology and, 1637–1639, 1638 (figure)
 - hypoid gear mesh in HMMWV simulation and, 1660–1662, 1660 (figure), 1661 (figure), 1662 (figure), 1663 (figure)
 - micropitting and, low-cycle, 1654–1655, 1655 (figure)
 - micropitting and spalling and, 1655–1656, 1656 (figure), 1657 (figure)
 - objectives and strategy of, 1658
 - oil types and boundary lubrication and, 1653–1654, 1654 (figure)
 - pressure-viscosity coefficient and, 1645–1646, 1646 (figure), 1647 (figure)
 - RIP concept oil in HMMWV simulation and, 1662–1664, 1663 (figure), 1664 (figure)
 - run-in polishing and, 1658–1660, 1659 (figure)
 - scuffing load capacity testing and, 1651–1653, 1652 (figure), 1653 (figure)
 - scuffing threshold for spiral bevel gear and, 1654, 1655 (figure), 1656 (figure)
 - traction coefficient, 1646–1650, 1647 (figure), 1648 (figure), 1648 (table), 1649 (figure), 1650 (figure)
 - traction modeling and, 1650–1651, 1651 (figure)
 - WAM testing for micropitting and spalling and, 1656–1658, 1657 (figure), 1658 (figure), 1659 (figure)
 - temperature, kinematic viscosity relationship to, 1497, 1498 (figure), 1499–1500, 1499 (figure), 1500 (table)
 - temperature gradient method, for quenching cooling curve analysis, 1019, 1022
 - temperature measurement
 - ASTM standards for, 1277–1278
 - devices for, 1269–1270
 - constant compared to controlled temperature and, 1275
 - immersion depth and, 1275–1276, 1276 (table)
 - thermal conduction and, 1275–1277, 1276 (table), 1277 (figure)
 - volume ratio and, 1275
 - historical development of, 1269, 1269 (table)
 - LiG thermometers for, 1270–1271, 1270 (figure), 1271 (figure)
 - RTDs for
 - PRTs, 1271–1273, 1272 (figure), 1273 (figure)
 - thermistors, 1273–1275, 1274 (figure)
 - thermocouples, 1274–1275, 1274 (figure)
 - temperature operating window (TOW), 652, 653 (figure)
 - temperature stability, of distillate fuel oils, 1394–1395
 - tempering, 869, 896–897, 897 (figure)
 - temporary viscosity loss (TVL), 480
 - Tensi agitation system, 996–999, 997 (figure)
 - tensiometer, for pipeline corrosion, 1462–1463, 1462 (figure)
 - terrestrial toxicity tests, 1558
 - tetraethyl lead (TEL), 155, 180
 - tetrahydronaphthalene, 1426–1427, 1427 (figure)
 - tetramethyl lead (TML), 180
 - thermal conductivity
 - of base stocks, 352
 - of compressor lubricants, 715–716
 - of gasoline, 203
 - of heat transfer fluids, 968
 - thermal cracking
 - invention of, 333
 - for olefin production, 336, 339
 - thermal expansion
 - of base stocks, 352
 - of petroleum coke, 1349–1350, 1349 (figure)
 - thermal measurement and analysis, tribology and, 1642, 1642 (figure)
 - thermal methods, for asphaltene deposition prevention, 66
 - thermal spraying, 869
 - thermal stability
 - of aerospace fuels, 1313–1314
 - antiwear agents and, 445, 447 (figure)
 - dispersants and, 404–405
 - for gear lubricants, 748
 - of heat transfer fluids, 967
 - of hydraulic fluids, 648–651, 650 (figure), 651 (table)
 - of hydrocarbon base oils, 319–320
 - of polyolesters and diesters, 516
 - test methods for, 253, 253 (figure)
 - of turbine lubricating oils and hydraulic fluids, 624–625, 1374–1376, 1378 (figure)

- thermal tars (TTs), 1343–1344
- thermistors, 1273–1275, 1274 (figure)
- thermocouples (TCs), 1274–1275, 1274 (figure), 1508
- thermodynamic colloidal model, of asphaltene phase behavior, 53
- thermodynamic micellization model, of asphaltene phase behavior, 55
- thermodynamic properties, static gases and, 1318–1319
- thermometric titration, 1081, 1081 (figure)
- thickeners
 - in HFC fluid composition, 541
 - lubricating greases and, 937–939, 937 (figure)
 - polymeric, for gear lubricants, 730–731
- thickening efficiency, ester polymers and, 484, 485 (figure)
- thin-film coatings, for automotive engine lubricants, 849, 850 (figure), 851 (figure), 852
- thixotropy, 1487
- threading operations, machining, 866
- 3M equation, 89, 91–92
- three-body abrasive wear, 1582, 1583 (figure)
- three-way catalyst (TWC), 763, 764
- thrust fit test, 465, 466 (table)
- thrust washer test, 1687
- tilting viscometers, 1493 (figure)
- time-of-flight (TOF) mass spectrometry, 1152–1154
- time resolved fluorescence depolarization (TRFD) technique, 45
- time-temperature-transformation (TTT) diagrams, 979, 980 (figure)
- timing chain-wear test, 771, 771 (figure), 788 (table), 796
- Timken EP tester
 - for gear lubricants, 746–747
 - for lubricating greases, 950
 - for tribology bench test, 1685–1686, 1685 (figure), 1686 (figure)
- titanium test, of used oil, 33
- titration, of lubricants
 - advantages of, 1071
 - potentiometric indication of, 1073–1077, 1074 (table), 1076 (figure), 1076 (table)
 - thermometric, 1081, 1081 (figure)
 - visual indication of, 1071, 1073, 1073 (figure), 1073 (table)
- toluene, 83
- tool wear, metal-removal fluids and, 888–891, 888 (table), 890 (table), 891 (table)
- torque
 - cranking, friction modifiers and, 441, 442 (figure)
 - losses, hydraulic fluids and, 669–670, 670 (figure)
 - low-speed high torque hypoid test, for gear lubricants, 748
 - lubricating grease flow properties and, 945–946
 - tapping test, 1686, 1686 (figure), 1687 (figure)
- Toscoal process, 117, 117 (figure)
- total acid number (TAN), 570, 572 (figure), 573 (figure). *See also*
 - acid number
 - of petroleum oil, 1151
- total base number (TBN)
 - detergents and, 423–425
 - engine oils and, 759
- total observed volume (TOV), 1066
- total wax content, of petroleum waxes, 108
- toxicity
 - acute test methods of, 1552 (table), 1556, 1557 (figure)
 - aquatic tests of, 1556
 - chronic test methods of, 1552 (table), 1556–1558
 - complex mixture, environmental characteristics and, 1555–1556
 - nonaquatic test methods of, 1558
- Toxic Substances Control Act (TSCA), 498, 499
- trace metals
 - in gas turbine fuel oils, 265–266, 265 (table)
 - in turbine lubricating oils and hydraulic fluids, 628–629
- traction coefficient, tribology TRL and, 1646–1650, 1647 (figure), 1648 (figure), 1648 (table), 1649 (figure), 1650 (figure)
- traction modeling, tribology TRL and, 1650–1651, 1651 (figure)
- tractor fluids, hydraulic fluids and, 671
- transformation processes, environmental characteristics and, 1543–1544
- transition metals, as oxidation promoters and inhibitors, 382, 384 (figure), 385, 385 (figure), 1367–1368, 1375 (figure)
- transmission-electron-microscopy (TEM), 43–44, 44 (figure)
- transmission fluids, 322
- transparency, metal-removal fluids and, 886–888, 886 (figure), 887 (figure)
- transport processes, environmental characteristics and, 1543, 1543 (figure), 1543 (table)
- trepanning operations, machining, 866
- triaryl phosphates, 597–598, 598 (table)
- tribochemical wear, 1585–1586
 - material surfaces and, 1606, 1607 (table)
- Tribological Aspect Number (TAN), 1678–1679
- tribology, 842
 - alternative base stocks and, 843
 - definition of, 1631
 - design and development of, 1631–1632, 1632 (figure)
 - Hertzian contact, deformation and, 1632–1635
 - history of, 1671–1672
 - parameters of, 1639 (figure)
 - entraining velocity, 1639–1640
 - Lambda ratio, 1640
 - normal load, 1640–1641
 - pressure distribution, 1640
 - sliding velocity, 1640
 - physics-based empirical modeling in, 1664–1668, 1666 (figure), 1668 (figure)
 - science and technology topics in, 1636–1637, 1637 (figure)
 - SCM and, 1666–1669, 1667 (figure), 1669 (figure)
 - Stribeck curve testing and, 853, 854 (figure), 855 (figure)
 - superficial
 - micropitting and, 1643, 1644 (figure)
 - micro-scuffing and, 1643, 1644 (figure)
 - polishing wear and, 1643, 1643 (figure)
 - scuffing and, 1644–1645, 1645 (figure)
 - structural elements of lubricated contact and, 1635–1636, 1635 (figure), 1636 (figure)
 - surface stress and, 1636, 1636 (figure)
 - thermal measurement and analysis and, 1642, 1642 (figure)
 - TRL in, 1637–1639, 1638 (figure)
 - hypoid gear mesh in HMMWV simulation and, 1660–1662, 1660 (figure), 1661 (figure), 1662 (figure), 1663 (figure)
 - micropitting and, low-cycle, 1654–1655, 1655 (figure)
 - micropitting and spalling and, 1655–1656, 1656 (figure), 1657 (figure)
 - objectives and strategy of, 1658
 - oil types and boundary lubrication and, 1653–1654, 1654 (figure)
 - pressure-viscosity coefficient and, 1645–1646, 1646 (figure), 1647 (figure)
 - RIP concept oil in HMMWV simulation and, 1662–1664, 1663 (figure), 1664 (figure)
 - run-in polishing and, 1658–1660, 1659 (figure)
 - scuffing load capacity testing and, 1651–1653, 1652 (figure), 1653 (figure)
 - scuffing threshold for spiral bevel gear and, 1654, 1655 (figure), 1656 (figure)

- traction coefficient, 1646–1650, 1647 (figure), 1648 (figure), 1648 (table), 1649 (figure), 1650 (figure)
- traction modeling and, 1650–1651, 1651 (figure)
- WAM testing for micropitting and spalling and, 1656–1658, 1657 (figure), 1658 (figure), 1659 (figure)
- WAM technology and, 1641–1642, 1641 (figure), 1646, 1646 (figure), 1648, 1648 (figure)
- tribology test systems
 - bench test
 - block-on-ring test machine for, 1683–1685, 1684 (figure), 1685 (figure)
 - designing, 1675
 - four-ball EP test device for, 1683, 1683 (figure), 1684 (figure)
 - four-ball test device for, 1681, 1682 (figure)
 - four-ball wear test device for, 1682–1683, 1683 (figure)
 - linear reciprocation test machine for, 1688–1689, 1688 (figure)
 - multispecimen test machine for, 1687–1688, 1687 (figure)
 - pin-and-vee block device for, 1679–1680, 1680 (figure), 1681 (figure)
 - pin-on-disk device for, 1680–1681, 1681 (figure)
 - selection of, 1673, 1678–1679
 - tapping torque test machine for, 1686, 1686 (figure), 1687 (figure)
 - Timken EP tester for, 1685–1686, 1685 (figure), 1686 (figure)
 - component test
 - constant volume vane pump testing, 1691
 - design of, 1675–1676
 - FZG gear rig for, 1689–1691, 1690 (figure), 1691 (figure)
 - designing fundamentals of, 1673–1674
 - duration in, 1678
 - load in, 1676
 - materials in, 1678
 - selection and designing of, 1674–1676
 - special atmospheres in, 1678
 - special testing in, 1678
 - speed in, 1677, 1677 (figure)
 - temperature in, 1676
 - terminology related to, 1695–1699
 - test lubricant in, 1678
 - types of, 1672–1673, 1672 (figure)
- trilauryl phosphate (TLPA), 454, 455 (figure)
- trilauryl phosphite (TLPI), 454, 455 (figure)
- trilauryl trithiophosphite (TLTTP), 454, 455 (figure)
- Trilene[®], 393
- trimethylolpropane, 555–556, 556 (figure)
- true boiling point, 347
- true value, 1704
- tunable diode laser absorption spectroscopy (TDLAS), 1464
- turbine entry temperature distribution, of aerospace fuels, 1310
- turbine lubricating oils and hydraulic fluids, 581–582
 - additives for, 598–603, 599 (figure), 599 (table)
 - analysis data of, 636
 - antioxidants and
 - ASTM tests for, 601–603, 602 (figure), 603 (figure), 604 (figure), 604 (table)
 - structures of, 598, 600, 600 (figure)
 - synergism of, 600, 601 (table)
 - antiwear agents for, 605–608, 606 (figure), 607 (figure), 608 (figure)
 - API standards for, 640
 - ASTM standards for, 601–603, 602 (figure), 603 (figure), 604 (figure), 604 (table), 637–639
 - base stocks for
 - diesters and polyolesters, 595–596, 596 (table), 597 (figure)
 - hydrocarbon oils, 590, 591 (figure), 592 (table)
 - hydrocracked/hydrotreated, 592–593, 593 (table), 594 (figure)
 - PAGs, 593–595, 595 (table)
 - PAOs, 593, 595 (table)
 - solvent-refined types, 590, 592 (figure), 593 (table)
 - triaryl phosphates, 597–598, 598 (table)
 - chlorine content in, 629
 - classification of, 608, 609 (table)
 - cleanliness of, 627–629
 - cold flow properties of, 1526–1527, 1527 (figure)
 - compatibility aspects of, 629, 631–632, 631 (table)
 - duty cycle of, 589
 - EP agents for, 605–608, 606 (figure), 607 (figure), 608 (figure)
 - federal standards for, 610 (table), 640
 - fire resistance of, 585
 - foam inhibitors for, 607–608, 608 (figure)
 - function of, 584
 - future trends of, 637
 - IEC standards for, 640
 - ISO standards for, 640
 - lubrication performance of, 627, 627 (figure)
 - maintenance of, 633, 634 (table), 636
 - military specifications for, 610–611, 612 (table), 640
 - operating environment for, 584–590, 589 (table)
 - oxidation testing
 - ASTM D2070, 1374–1376, 1378 (figure)
 - ASTM D4636, 1376–1377, 1379 (figure)
 - ASTM D5846, 1378–1379, 1380 (figure)
 - ASTM D6514, 1379
 - DIN 51352-2, 1379, 1380 (figure)
 - IP-280, 1373–1374, 1377 (figure), 1378 (figure)
 - IP-306, 1374
 - performance requirements for
 - acid number, 617, 618 (figure)
 - air release, 619–620
 - appearance, 612
 - comparison of, 611–612, 613 (table), 615 (table)
 - demulsibility, 622–623
 - density, 618
 - fire resistance, 620–622
 - foaming, 619–620
 - low-temperature storage stability, 612, 616–617
 - pour point, 612, 616–617
 - viscosity, 612, 615 (figure), 616 (figure)
 - water content, 617–618
 - water separability, 622–623
 - rust and corrosion behavior of, 626–627
 - rust and corrosion inhibitors for, 603–605, 605 (figure)
 - SAE standards for, 640
 - stability characteristics of
 - hydrolytic stability, 625, 625 (figure)
 - oxidation stability, 598, 599 (figure), 599 (table), 623–624, 624 (figure), 1373–1374, 1377 (figure), 1378 (figure)
 - shear stability, 625–626
 - thermal stability, 624–625, 1374–1376, 1378 (figure)
 - standards for, 608, 610–611, 610 (table), 611 (table), 612 (table), 637–640
 - system cleaning and flushing for, 636–637
 - thermal/oxidative stress and, 587
 - top-up rates of, 589
 - trace metals in, 628–629
 - volatility of, 629
 - volume resistivity of, 629, 630 (figure)
- turbine oil stability test (TOST), 601, 603 (figure), 649–650, 649 (figure), 649 (table), 707

- turbines
 cleaning and flushing of, 636–637
 gas, 582–583, 583 (figure)
 aero-derivative, 585–586
 heat input and removal for, 586, 588 (figure)
 lubrication system for, 587 (figure)
 steam, 582
 control fluid system of, 586 (figure)
 shaft driven lubrication system of, 585 (figure)
 water, 583–584
 wind, 584
- turbocharged, gasoline direct injection (TGDI) engines, 761–762
- turbulence, combustion and, 1280–1281, 1281 (figure), 1285
- turning operations, machining, 865–866
- two-body abrasive wear, 1583, 1583 (figure)
- U**
- ullage, 1057
- ultraviolet (UV) spectroscopy, for hydrocarbon base oils, 307
- uncoated steel, friction and wear reduction of, 852–853, 852 (figure)
- underground storage tanks (USTs), 1246–1247, 1248 (figure), 1260, 1261 (figure)
- uniform pipeline corrosion, 1427–1428
- Union Carbide process, 117–118
- unique point, 1319, 1319 (figure)
- unique process line, 1319–1320, 1320 (figure), 1320 (table)
- United Kingdom, LSE process, 122
- universal gas constant, 1318–1319
- universal oil products (UOP), 350
- unleaded gasoline, history of, 182
- unsaturated hydrocarbons. *See* olefins
- urea-dewaxing, 288
- used oil
 contamination in, 30–31, 31 (table)
 definition of, 29
 disposal of, 928
 EPA criteria of, 922–923
 EPA regulatory definition of, 297
 feedstock, 30
 history of, 29–30
 hydrocarbon base oils and, 297–302
 for re-refining
 assessment of, 30–31, 30 (table), 31 (table)
 BERC process, 299
 by-products of, 297–298
 flow diagram for, 299 (figure)
 IFP process, 299
 KTI process, 299–300, 300 (figure)
 Meinken process, 299
 quality comparison of, 300, 301 (table)
 testing of, 31–33, 33 (table)
 uses of, 300, 302, 302 (figure)
 wear metals in, 1086–1088, 1087 (table)
- V**
- vacuum distillation, 286
- vacuum distillation residua (VDR), 1340, 1343–1344
- vacuum resid, 2, 3 (table)
- valve-train wear test, 780 (table), 790 (table)
- vanadium
 in gas turbine fuel oils, 265 (table), 266
 in petroleum coke, 1347
 test, of used oil, 33
- van der Waals equation, 89
- vane compressors, rotary, 690–691, 691 (figure)
- vane-on-disk test, 1687, 1687 (figure)
- vane pump tests, 658–659
- van Krevelen diagrams, 1158–1160, 1160 (figure)
- vapor, LPG removal of, 171
- vapor control systems, history of, 182–183
- vapor-liquid ratio, 199 (figure)
- vapor lock temperature, 199–200
- vapor pressure
 ASTM D4814 for gasoline and, 198–200, 199 (figure)
 environmental characteristics and, 1541
 of HFC fluids, 543
 LPG and, 155–157
 volatility ASTM standards for
 ASTM D323, 1205–1206, 1207 (figure)
 ASTM D1267, 1210–1211, 1210 (figure)
 ASTM D2533, 1209–1210
 ASTM D4953, 1206–1207, 1207 (figure)
 ASTM D5188, 1209
 ASTM D5190, 1207, 1208 (figure)
 ASTM D5191, 1207–1208
 ASTM D5482, 1208–1209
 ASTM D6377, 1209
 ASTM D6378, 1209
 ASTM D7975, 1211
 importance of, 1204–1205
 international methods compared to, 1211, 1211 (table)
 precision values for, 1206 (table)
- vapor-pressure osmometry (VPO), 44–46
- variable-valve timing (VVT), 761
- varnish, formation of, 367
- vegetable waxes, 79, 80
- vehicle emissions
 aerospace fuels and combustion, 1310–1311
 automotive engine design improvements for, 769–772
 automotive engine lubricants and reduction of, 842, 842 (figure)
 combustion and regulated, 1285
 current standards for, 184–186
 Europe, United States, and Japan standards for, 762 (figure)
 future trends in, 840 (figure)
 history of standards for, 181
 lubricants and, 355–356
- vehicle (octane number requirements) ONRs, 194–196
- velocity
 entraining, tribology and, 1639–1640
 multiphase velocity, pipeline corrosion and, 1436, 1436 (figure)
 sliding, tribology and, 1640
- Verband Chemischer Ingenieure (VCI) classification system, 574, 574 (figure)
- vessel general permit (VGP), 522, 548, 548 (table), 1539
- visbreaking, 18–19, 19 (figure), 19 (table)
- viscoelastic materials, 1486
- viscometer geometries, 1487–1489, 1487 (figure), 1488 (figure), 1489 (figure), 1490 (table)
- viscometric technique, for asphaltene precipitation onset pressure, 50
- viscosity
 absolute, of water, 1505–1506, 1506 (table)
 of aerospace fuels, 1305
 antioxidants and, 385, 386 (figure)
 apparent, 1487
 lubricating grease flow properties and, 945
 of aqueous polymer quenchants, 1012–1013, 1013 (figure)
 asphaltene impact on, 46, 47 (figure)
 ASTM standards for, 1506–1508, 1506 (table), 1507 (figure), 1508 (table)
 of automotive gear lubricants, 332 (table), 770

- of base stocks, 352
 - boiling range and, 312
 - CCS, 315, 748, 1530–1531, 1530 (figure)
 - of compressor lubricants, 701–702
 - definition of, 309, 1486
 - of diesel fuel oils, 244, 263–264
 - dispersants and, 405–406
 - dynamic, 1486
 - of engine oils, 331 (table), 758, 759
 - environmentally acceptable ester-based hydraulic fluids and, 564, 564 (figure)
 - ester polymers and degradation loss of, 487–488, 490 (figure)
 - ester polymers and shear-related loss of, 484–487, 486 (figure), 487 (figure), 488 (figure), 489 (figure)
 - fuel economy and, 432–433, 433 (figure), 434 (figure)
 - of fuel oils, 1330–1331, 1331 (table)
 - of gas/liquid mixtures under pressure, 715
 - of gasoline, 203
 - of gear lubricants, 744
 - of GTL base stocks, 295–296, 296 (figure)
 - of heat transfer fluids, 966, 970, 970 (table)
 - of HFA and HFB fluids, 537–539
 - of HFC fluids, 543, 544 (figure)
 - HTHS, 272, 759, 831, 1508–1511, 1509 (figure), 1510 (figure), 1511 (table)
 - hydraulic fluids and, 652–654, 652 (figure), 653 (figure)
 - of hydrocarbon base oils, 309–312, 310 (figure), 311 (table), 312 (figure)
 - of IL lubricants, 1040–1041, 1040 (table), 1042, 1043 (table)
 - of industrial lubricants, 322–323
 - jet fuel and, 217, 218 (figure)
 - kinematic, 1486, 1486 (table)
 - history of, 1493–1496
 - petroleum oil flow properties and, 1489–1493, 1491 (table), 1492 (figure), 1492 (table), 1493 (figure), 1494 (figure)
 - temperature relationship to, 1497, 1498 (figure), 1499–1500, 1499 (figure), 1500 (table)
 - low-temperature high-shear, lubricants and, 1529–1531, 1529 (table), 1530 (figure), 1530 (table), 1531 (figure), 1531 (table)
 - lubricants and, 272, 354, 355 (figure)
 - metal-removal fluids and, 886–888, 886 (figure), 887 (figure)
 - metalworking fluids and, 874–875, 874 (figure)
 - of petroleum pitch, 1335
 - petroleum waxes and, 102, 103 (figure)
 - of polyolesters and diesters, 515
 - pressure and, 311–312, 311 (table), 312 (figure), 1603–1605, 1604 (figure), 1605 (figure), 1605 (table)
 - quenching and, 1007–1008
 - SAE J300 classification of, 760
 - SAE J306c classification of, 738, 740 (table)
 - SAW classification system of, 351
 - shear rate and, 1508–1509, 1509 (figure)
 - temperature impact on, 309–310, 310 (figure), 311 (table)
 - turbine lubricating oils and hydraulic fluids and, 612, 615 (figure), 616 (figure)
 - visualization of, 1487 (figure)
- viscosity gravity constant (VGC), 316, 317 (table), 318
- viscosity index (VI), 22
- calculation of, 1501, 1502 (table), 1503 (table), 1504, 1504 (table)
 - for gear lubricants, 746
 - historical development of, 1501
 - improvers, 476, 477 (figure), 478 (figure)
 - for automotive engine lubricants, 768
 - for engine oils, 757
 - for gear lubricants, 735 (table)
 - of hydraulic fluids and, 668
 - of mineral oil base stocks, 292, 292 (figure)
 - pressure considerations for, 1504–1505, 1505 (figure)
 - uses of, 1500–1501
- viscosity modifiers (VMs). *See also* dispersant viscosity modifiers
- classes of commercially available, 476
 - ester polymers, 481–488
 - olefin-based polymers, 478–481, 479 (figure), 479 (table), 480 (table), 481 (figure)
 - comparison of, 491 (table)
 - for compressor lubricants, 699 (table), 700
 - molecular weights of, 475
 - oil thickening and, 476, 476 (figure)
 - principle function of, 475
 - single-grade and multi-grade oils, 476, 477 (figure), 478 (figure)
 - temperature and, 475–476, 476 (figure)
- viscosity-temperature constant (VTC), 310
- visual inspection test, of used oil, 31
- volatile matter, in petroleum coke, 1345–1346, 1346 (table), 1347 (table)
- volatility
- of aerospace fuels, 1304–1305
 - ASTM D4814 for gasoline and, 197–200, 197 (figure), 197 (table)
 - ASTM standards for, 1212
 - of aviation gasoline, 221
 - of base stocks, 352
 - boiling point and, 313–314, 314 (figure)
 - crude oil distillation and, ASTM standards
 - ASTM D2892, 1200–1201, 1201 (figure), 1202 (table)
 - ASTM D5236, 1201–1203, 1203 (figure), 1204 (table)
 - international methods compared to, 1203
 - precision values, 1200, 1200 (table)
 - definition of, 312, 1171
 - of diesel fuel oils, 244, 263
 - distillation and, ASTM standards
 - ASTM D86, 1172–1173, 1172 (figure), 1173 (figure), 1174 (table), 1175 (table), 1176 (table), 1177 (table), 1178 (table), 1180 (table)
 - ASTM D850, 1173–1174, 1174 (table), 1176, 1178 (table), 1180 (table)
 - ASTM D1078, 1174 (table), 1176–1178, 1179 (table), 1180 (table)
 - ASTM D1160, 1179, 1181–1182, 1182 (figure), 1183 (table), 1184 (table), 1186 (table), 1187 (table), 1189 (table), 1190 (table), 1192 (table), 1193 (table)
 - ASTM D7344, 1178–1179, 1180 (table)
 - ASTM D7345, 1179, 1181 (table)
 - importance of, 1171–1172
 - international standards compared to, 1182, 1193 (table)
 - environmental characteristics and, 1554
 - fire point and, 1195
 - flammability and, ASTM standards
 - ASTM D56, 1194, 1196 (figure)
 - ASTM D92, 1194–1195, 1197 (figure)
 - ASTM D93, 1195–1196, 1198 (figure)
 - ASTM D1310, 1196
 - ASTM D3278, 1197, 1199 (figure)
 - ASTM D3828, 1197
 - ASTM D3941, 1197
 - ASTM D6450, 1198
 - ASTM D7094, 1198–1199
 - ASTM D7236, 1199
 - fire point and, 1195
 - flash point and, 1192–1194, 1194 (table), 1195 (table), 1196 (table)
 - international methods compared to, 1199–1200, 1200 (table)

flash point and, 312, 313 (figure), 314 (table), 1192–1194, 1194 (table), 1195 (table), 1196 (table)
 fuel economy and, 432, 434 (figure)
 GC assessment of, 313
 of GTL base stocks, 295, 296 (figure)
 of hydrocarbon base oils, 312–314, 313 (figure), 314 (figure), 314 (table)
 international standards for, 1213
 of jet fuel, 221–222, 222 (figure)
 lubricants and, 1079–1080
 Noack test for, 313, 759
 of polyolesters and diesters, 516
 of turbine lubricating oils and hydraulic fluids, 629
 vapor pressure and, ASTM standards
 ASTM D323, 1205–1206, 1207 (figure)
 ASTM D1267, 1210–1211, 1210 (figure)
 ASTM D2533, 1209–1210
 ASTM D4953, 1206–1207, 1207 (figure)
 ASTM D5188, 1209
 ASTM D5190, 1207, 1208 (figure)
 ASTM D5191, 1207–1208
 ASTM D5482, 1208–1209
 ASTM D6377, 1209
 ASTM D6378, 1209
 ASTM D7975, 1211
 importance of, 1204–1205
 international methods compared to, 1211, 1211 (table)
 precision values for, 1206 (table)
 summary of, 1205 (table)
 volatility residue, LPG and, 157–158
 volume correction factors (VCFs)
 definition of, 1066
 LPG and, 168–169
 volume resistivity, of turbine lubricating oils and hydraulic fluids, 629, 630 (figure)
 volumetric efficiency, 685, 686 (figure)

W

WAM (Wedeven Associates, Inc. machine) technology, 1641–1642, 1641 (figure), 1646, 1646 (figure), 1648, 1648 (figure)
 for micropitting and spalling, 1656–1658, 1657 (figure), 1658 (figure), 1659 (figure)
 waste oil, 29, 297
 water-absorbing cartridges, 231
 water-based, metalworking and machining fluids, 877–879, 878 (figure), 878 (table), 879 (figure), 879 (table)
 water content
 absolute viscosity of, 1505–1506, 1506 (table)
 aerospace fuels and, 1314–1315
 aqueous polymer quenchants and, 1014
 in aviation gasoline, 217, 218 (figure), 219
 of compressor lubricants, 703
 control and removal of, 250–251
 crude oil mixture with, pipeline corrosion and, 1417, 1418 (figure), 1420–1422, 1421 (table)
 dissolved in propane, phase behavior of, 159–160, 159 (table), 160 (table)
 in gear lubricants, 746
 in heat transfer fluids, 970–971
 in HFA and HFB fluid composition, 536
 in HFC fluid composition, 541
 hydraulic fluids and, 659–661
 in jet fuel, 217, 218 (figure), 219
 LPG and, 158–163
 measurement of, 164–165
 sources of, 164
 lubricating greases and, 952–953, 953 (figure)

metalworking fluids and quality of, 900
 microbes and, 1240, 1240 (figure)
 pipeline corrosion control and, 1446, 1447 (figure), 1448, 1448 (figure)
 for quenching, 1025–1027, 1025 (figure), 1025 (table), 1026 (figure), 1027 (figure), 1028 (figure)
 quenching tests and, 1008–1009, 1009 (figure)
 test of, used oil and, 31
 turbine lubricating oils and hydraulic fluids and, 617–618
 water hazard classification (WGK), 574, 574 (figure)
 water-in-oil emulsion, 472, 474 (figure)
 in metalworking fluids, 877–879, 878 (figure), 878 (table), 879 (figure), 879 (table)
 water-miscible metalworking fluids
 cast iron chip test for, 1413, 1413 (figure)
 condition monitoring for biodeterioration and, 1252–1255, 1252 (figure), 1253 (figure), 1254 (figure)
 water phase wetting, pipeline corrosion and, 1435
 water separability, 323
 turbine lubricating oils and hydraulic fluids and, 622–623
 water solubility, environmental characteristics and, 1541, 1542 (figure)
 water spray-off, lubricating greases and, 953, 953 (figure)
 water tolerance, ASTM D4814 and, 201–202
 water turbines, 583–584
 water washout, lubricating greases and, 952–953
 waxy crude oil, 81–83, 82 (figure)
 weak organic acids, 1243
 wear. *See also* antiwear agents; scuffing; tribology test systems
 abrasive, 443, 725, 725 (figure), 888, 1582–1583, 1583 (figure)
 additives and, 371–372
 adhesive, 443, 725, 888, 1577–1579, 1580 (figure), 1581 (figure), 1582, 1582 (figure)
 antioxidants and, 385, 386 (figure)
 Archard's constant, 1579, 1582, 1582 (table)
 ASTM standards for, 1691–1692
 automotive engine lubricants reduction of, 841
 additives, 848–849, 850 (figure), 851 (figure)
 alternative base stocks, 842–846, 843 (figure), 844 (table), 845 (figure), 846 (figure)
 estolides, 847, 847 (table)
 hydrocarbons, 846–847, 847 (figure)
 low and ultra-low engine oils, 847–848, 848 (table), 849 (figure)
 thin-film coatings, 849, 850 (figure), 851 (figure), 852
 tribological testing of Stribeck curves, 853, 854 (figure), 855 (figure)
 uncoated steel, 852–853, 852 (figure)
 bulk material properties and, 1574–1577, 1578 (table), 1579 (figure), 1579 (table)
 cavitation, 1584, 1584 (figure)
 cavitation corrosion and, 1585
 corrosion, 443, 888, 1584–1585, 1584 (figure), 1585 (figure)
 debris analysis, 1592, 1594 (figure)
 delamination, 1589–1590, 1590 (figure)
 diffusive, 888
 DIN standards for, 1693
 Engine Oil Aeration Test, 828 (table)
 EP agents and controlled, 458, 458 (figure)
 erosion, 1584–1585, 1585 (figure)
 fatigue, 443, 1585–1586, 1586 (figure), 1587 (figure)
 flash temperature and, 1592, 1593–1594, 1594 (figure), 1594 (table)
 fretting, 951, 1587–1588, 1587 (figure), 1588 (figure)
 hydraulic fluids protection from, 651–654, 652 (figure), 653 (figure), 654 (figure)

ISO standards for, 1693
 load and, 453, 454 (figure)
 lubricating greases and, 950–952, 951 (figure)
 maps, 1595–1599, 1596 (figure), 1597 (figure), 1598 (figure), 1599 (figure)
 MWR, 1616–1618, 1617 (figure), 1618 (table), 1619 (figure)
 new surface structure and, 1574, 1576 (figure)
 oxidational, 1585, 1586 (figure)
 Peugeot TU3M test of, 779 (table), 789 (table)
 polishing, 366, 725, 725 (figure), 1577–1578, 1581 (figure)
 superficial tribology and, 1643, 1643 (figure)
 premature, 888
 Roller Follower Wear Test, 811 (table), 819 (table), 828 (table)
 solid lubricants controlling, 465, 465 (figure)
 start-up, shutdown time and, 432, 433 (figure)
 structural elements of, 1573–1577, 1573 (figure)
 subsurface structure and, 1574, 1576 (figure), 1577 (figure), 1578 (figure)
 surface films reducing, 1574, 1574 (figure), 1575 (figure), 1576 (figure)
 surface-to-surface contact, 443
 testing, 1590–1592, 1591 (figure), 1592 (figure), 1593 (figure), 1594 (figure)
 timing chain-wear test, 771, 771 (figure), 788 (table), 796
 tool, metal-removal fluids and, 888–891, 888 (table), 890 (table), 891 (table)
 tribochemical, 1585–1586
 material surfaces and, 1606, 1607 (table)
 valve-train test of, 780 (table), 790 (table)
 wear material surfaces, 1606, 1607 (table)
 wear metals, in used oils, 1086–1088, 1087 (table)
 wear preventive characteristics test, of grease, 951
 wear surfaces, lubrication and, 1567–1569, 1569 (figure), 1569 (table)
 weathering, LPG and, 157–158
 wedge-type lubricant films, 873, 873 (figure)
 weight conversion factor (WCF), 1067
 weighted bottle and beaker samplers, 1059–1060, 1060 (figure)
 weight in air, 1067
 weight of wax applied during coating, of petroleum waxes, 108
 Weissenberg effect, 1487
 welding, 868
 wet analytical methods, for hydrocarbon base oils, 308
 wet battery cell, 1405–1406, 1406 (figure)
 wet chemistry methods, in elemental analysis, 1088, 1091 (table)

“wet” gas, 147
 wettability alteration, asphaltene deposition and, 63, 64 (figure)
 wettability of metal surface, in pipeline corrosion, 1418–1420, 1421 (figure)
 wheel-bearing grease life, 949–950, 950 (figure)
 wick tests, for fire resistance, 622, 622 (figure), 623 (figure)
 Wilsonville Pilot Plant, CTSL processing and, 123–124, 124 (figure), 125 (table)
 wind turbines, 584
 Wolf Strip Oxidation Test, 707
 worms, in toxicity tests, 1558
 worn surface structure, 1573–1577
 wrinkled laminar flame, 1281, 1281 (figure)

X

X-ray fluorescence spectrometry (XRF), 1094–1095, 1095 (table)
 X-ray small-angle scattering (SANS), 43

Y

yield stress
 definition of, 1487
 for engine oils, 759
 Young-Dupré equation, 1463
 y-strainers, for heat transfer fluid system, 972

Z

Zeldovich mechanism, 1291
 “Zeronize,” 842
 Ziegler-Natta catalysts, 411
 zinc dialkyldithiophosphates (ZDDPs), 757, 758
 as antiwear agents, 444–447, 446 (figure), 446 (table), 447 (figure), 849
 formation of, 729
 function of, 766–767
 hydroperoxide decomposition and, 379, 379 (figure)
 oxidation inhibition by, 1365–1366, 1372 (figure)
 radical scavengers and, 379, 380 (figure)
 sludge formation by, 650, 650 (figure)
 structure of, 446 (figure), 767 (figure)
 sulfur and, 909, 909 (table)
 for turbine lubricating oils and hydraulic fluids, 600, 600 (figure)
 zinc test, of used oil, 33
 Zisman plots, 1576