

Subject Index

A

ABAQUS, 243
 Accelerated aging, 513
 Accelerated tests, environmental degradation, 513
 Accept/reject criteria, 158
 Acoustic emission, 366
 Adequacy of standards, 324
 Aircraft, use of composite structures, 3
 Allowables, 3, 29, 210
 open hole compression, 273
 ASTM D 30, 324
 ASTM D 2344, 324
 ASTM D 3039, 324
 ASTM D 4255, 324
 ASTM D 5379, 324
 ASTM D 5448, 324
 ASTM standards, shear and tensile failure processes, 324

B

Bearing-bypass interaction, 293
 Bolted joints
 damage-tolerance design, 243
 fastener clearance and, 293
 stress analysis and failure prediction, 231
 Bonded joints
 propeller blades, 210
 tension pull-off and shear test methods, 398
 Braided materials, 210
 Buckling, 12, 72
 cylindrical shells, 529
 Building block structural qualification program, 131

C

Carbon/epoxy tape laminates, 273
 Carbon fiber, 12, 131
 predicting structural properties, 158
 Carbon fiber reinforced polymer, 366
 Carbon-fiber reinforced skin-stringer panels, 49
 Certification, 131
 cost reduction, 29
 Closed-cross-section laminates, 382
 Composite tailboom, 29
 Compression-after-impact strength, 72
 Compression-after-impact testing, 29
 Compression loading

 bolted joints, 293
 closed-cross-section laminates, 382
 Compression strength, open hole, 273
 Compression testing, compressive strength of
 production parts, 470
 Compressive strength, parts without compression
 testing, 470
 Constitutive model, 158
 Curved beams, 437
 Cylindrical shells, buckling, 529

D

Damage, environmental degradation, 513
 Damage assessment, 12
 Damage initiation prediction, 231
 Damage mechanics, 452
 Damage tolerance, 3
 design of bolted joints, 243
 three-stringer panel, 72
 Delamination
 flexbeam laminates, 188
 as threat to structural integrity, 3
 under multiaxial loading, 105
 Delamination growth, 12
 finite-element analysis, 345
 mechanisms, 49
 modeling, 49
 0°/45° interface, 311
 Delamination onset, 311
 Delamination toughness, friction effect, 334
 Design
 development testing, 3
 environmental degradation, 513
 Displacement spline approximation method, 231
 Double cantilever beam, 311
 Durability, 513

E

End notched flexure
 delamination growth, 345
 energy release rate, 334
 Energy release rates, 105
 end notched flexure tests, 334
 Environmental degradation, accelerated testing, 513
 Epoxy, 131

F

- Fail-safe testing, 131
- Failure, 452
 - interactive criteria, 413
 - open hole, 273
- Failure prediction, filled hole laminates, 231
- Fastener clearance, effect on bolted joint failure, 293
- Fatigue analysis, propeller blades, 210
- Fatigue delamination, $0^\circ/45^\circ$ interface, 311
- Fatigue tests, $0^\circ/45^\circ$ interface, 311
- Fiber bridging, 311
- Fiber misalignment, compressive strength and, 470
- Fiber-polymer composites, interactive failure theories, 413
- Filled hole laminates, stress analysis and failure prediction, 231
- Finite-element analysis
 - closed-cross-section laminates, 382
 - debonding under multiaxial loading, 105
 - end notched flexure tests, 334
 - fastener clearance, 293
- Finite-element modeling
 - delamination, 49
 - delamination growth, 345
 - flexbeam laminates, 188
 - open hole compression strength, 273
- Flexbeam laminates, ply waviness, 188
- Fractography, 49
- Fracture mechanics, 105
- Friction, effect on Mode II delamination toughness, 334
- Full-scale testing, 3

G

- Graphite-epoxy composite shells, 529
- Graphite/epoxy end notched flexure specimen, 345

H

- Hole size effect, 452
- Hole tolerance, 293

I

- Impact damage, 12
 - barely visible, 29
 - as threat to structural integrity, 3
- Impact resistance, 12
- Imperfections, initial, effects on buckling, 529
- In-plane/out-of-plane loading conditions, 105
- Integrally stiffened composite wing skins, 72
- Interactive failure theories, 413
- Interlaminar fracture, 345
 - toughness, 311

L

- Laminated composites, 437
- Laminated plate theory, 452

M

- Marcel defect, 158, 188
- Material properties, environmental degradation, 513
- Microcracking, 513
- Mode II delamination toughness, friction effect, 334
- Modified building block approach, 29
- Moisture, as threat to structural integrity, 3
- Moisture cycling, 513
- Moving mesh, 49
- Multiaxial straining, 452

N

- Nonlinear analysis, composite shells, 529
- Nonlinear constitutive law, 452

O

- Open hole compression strength, 273

P

- PDHOLEC, 273
- Ply waviness, 158
 - effect on fatigue life, 188
- Polyimides, 513
- Polymer matrix composites, 513
- Progressive damage, 273
- Propeller blade, structural qualification, 210
- Proprotor yoke, 131

Q

- Qualification of structures, 3
- Quasi-static tests, $0^\circ/45^\circ$ interface, 311

R

- RAH-66 Comanche, 131
- Reissner-Mindlin plate theory, 345
- Residual strength, 12
- Resin transfer molding, 210

S

- Sandwich element, 366
- Sandwich structures, 437
- Shear failure, ASTM standards, 324
- Shear test method, 398
- Single-piece structures, 437
- Skin/flange interface, 105
- Skin-stringer panels, delamination growth, 49
- Small mass impact, 12
- Spring-in, 437
- Stacking sequence effect, 231

Stiffness, ASTM standards. 324
 Stiffness loss, 452
 Strain energy dissipation, 452
 Strain energy release rates, under multiaxial loading, 105
 Strength, ASTM standards. 324
 Strength prediction, fastener clearance and, 293
 Stress analysis, 452
 three-dimensional, 231, 243
 Stress concentrations, 273
 Stringer panel, compression-after-impact strength, 72
 Structural failure, 49
 Structural properties, marcel defect effects, 158
 Structural qualification
 propeller blades, 210
 RAH-66 Comanche, 131
 Surface-effect ships, 366

T

Tailboom, composite, 29
 Tapered composite flexbeam laminates, ply waviness, 188
 Technology transition, 3
 Temperature, as threat to structural integrity, 3
 Tensile failure, ASTM standards, 324
 Tension pull-off, 398

Test methods, reinforced bonded T-joints, 398
 Thermal cycling, 513
 T-joints
 sandwich designs, 366
 textile reinforced bonded, 398
 3DBOLT, 243

U

U. S. Air Force, qualification of structures, 3

V

V-22, 131
 Virtual crack closure technique, 105, 334

W

Woven preforms, 398

Y

Yoke, composite, 131