

# Subject Index

## A

- Acoustic technique, 323
- Aluminum
  - annealed
    - stress response, 82–83
    - stress-strain hysteresis loops, 83–84
  - chemical composition, 82
  - strain-controlled cycling, 81
- 6061-T6 aluminum, 68
- Aluminum alloys
  - chemical composition, 340
  - crack extension and closure data, 349
  - crack-opening characteristics, 366
  - fracture surfaces, 302, 304
  - heat treatments, 341
  - mechanical properties, 342
  - threshold data, 344
  - underaged, fracture morphology, 351–353
- Artificial hole, 39
- ASTM, international role, 6–9
- ASTM E 647–83, 200, 245, 257
- ASTM E 739–80, 257

## B

- Bainitic 1Cr-Mo-V steel, tension-torsion test, 197
- Biaxial cyclic stress, Dugdale model, 238–246
- Biaxial fatigue, 120–134
  - analysis, 129–133
  - correction factors as function of aspect ratio, 129–130
  - correlation factors, 131
  - experimental observations, 128–129
  - facets along crack length, 125–126, 129
  - fracture surfaces, under pure torsion, 127, 129
  - procedure, 122–128
  - shear strain amplitudes, 131
  - strain intensity equations, 131
  - surface crack growth rates, 124, 128
  - tubular specimen, 121–122

- Biaxial stress, 194, 200, 233
  - dislocation substructure, 202, 205
  - elastic-plastic fracture mechanics parameters, 237–238
  - strain-based approaches, 235

## C

- Carbon steel, 142–143
- CCP specimen, Dugdale model extension, 241, 244–245
- Cell size, variation in size with cycles, 87–88
- Closure gage, pushrod, 163–164
- Complex loading, 214
- Compliance method, closure measurement, 362, 364
- Compression cycles, 337
- Compression overload experiments, fatigue threshold, 342–343
- Compressive stress, residual, ahead of crack tip, 161–162
- Constant-amplitude loading
  - crack-opening characteristics, 366
  - fatigue threshold, 342–345
  - stress history, surface acoustic wave, 327–328
- Copper, 39
  - foil specimen, 49, 56–57
  - polycrystal, 56
  - sheet specimen, 48, 56
  - single crystal
    - crack nucleation (*see* Crack nucleation)
    - dislocation structures, 40
    - screw dislocations, 17–25
- Crack
  - formation, environmental effects, 31–32
  - half length, 328
  - iron, 108–109
  - overload zone ahead of, 358
  - point loading, 241
  - size, acoustic measurement, 324–325
  - traversing overload zone, 361–363

- Crack branching, 308–309
- crack growth retardation, 161, 176
- overload tests
  - high baseline stress intensity factor levels, 177–178
  - low baseline stress intensity factor levels, 178, 180
  - simultaneous growth of branches, 309
- Crack closure (*see also* Sliding mode crack closure), 120, 157, 184, 233, 281, 323, 337–338, 357–375
  - concept, 360–361
  - development, 286–288
  - discontinuous, 172, 174
  - extent, prior to overload, 369–370
  - as function of stress intensity factor, 344–345, 347
  - influence of material, 369–372
  - measurement
    - compliance method, 362, 364
    - crack growth retardation, 163–164
    - notches, 284–285
  - mechanisms, 338–339
  - near-threshold, 177
  - number of cycles of delay as function of overload plastic zone size, 366–367
  - oxidation, 192
  - plane-stress zone, 361
  - plasticity-induced, 162
    - evidence for, 175–177
  - research needs, 374–375
  - responses of thick and thin, 167, 170
  - review, 360–366
  - short cracks, 372–373
  - stress range
    - short cracks, 240
    - change during fatigue loading, 189–190
  - transient, 167, 169–172
- Crack coalescence, steel, 314
- Crack depth
  - acoustic predictions, 325
  - effective, 137–138
  - reliability of concept, 148, 150
- Crack extension, as function of number of cycles following compression overloads, 345, 348
- Crack face displacement, 245, 255–256
- Crack flank, 178–179
  - displacement, 265–267
    - profiles, 278
    - response, coordinate system and notation for describing, 264–266
  - locking, 260
  - Mode I wedging behavior, 273
  - sliding response on first loading, 265, 267
  - slip, 260
- Crack front, irregular, crack growth retardation, 160–161
- Crack geometry, surface cracks, 128–130
- Crack growth (*see also* Biaxial fatigue; Elastic-plastic fracture mechanics parameters), 120, 214, 301, 312, 337, 357
  - antiplane shear mode, 219–221
  - before rearrest, 351
  - comparison of measured and calculated responses, 172–173
  - delayed retardation, 361–362
  - direction of maximum shear strain, 123, 128
  - directions, 120–121
  - early, environmental effect, 33–35
  - following single tensile overload, 367–368
  - grain size effect, 315
  - history effect, 358
  - Mode II (*see* Mode II crack growth)
  - near-threshold, 338
  - process, 306
  - recommencement, 338
  - resistance
    - alloy characteristics, 369
    - closure extent prior to overload, 369–370
    - cyclic fracture toughness, 371
    - yield strength, 369, 371
  - retardation, 157–180
    - after overload, 158
    - closure transient, 167, 169–172
    - crack branching, 161, 176–180
    - crack closure, measurements, 163–164
    - crack tip blunting, 159–160
    - crack tip strain hardening, 160
    - delayed retardation, 158
    - displacement gage, 163, 165
    - experiment, 163–164
    - flanks, 178–179
    - fractography, 167–169
    - irregular crack front, 160–161
    - mechanisms, 159–162
    - microcracking, 161
    - offset displacement, 164
    - plasticity-induced closure, 162, 175–177
    - residual compressive stress ahead of crack tip, 161–162
    - residual hump, 175–176
    - transient, 165–167
  - tensile, 362, 365
  - threshold condition, 297
  - torsional, 121

- Crack growth rate, 194
  - after single-peak overload, 358–359, 362, 365
  - comparison of Modes I and III, 222–223
  - correlations, 248–252
  - cyclic Mode III + static Mode I measurements, 225–227
  - dependence on cyclic plastic zone size, 246–247
  - ferritic steel, 372
  - function of crack length, Mode III, 219–221
  - function of effective stress intensity range, 345, 350
  - function of slip magnitude, 209
  - function of stress intensity factor, 200–201, 369–370
  - Mode III, 121, 226
    - versus plastic strain intensity, 222–223
  - nonproportional straining, 208–210
  - pure Mode I loading, 133
  - responses of thick and thin specimens, 165–166
  - retardation, following tensile overload, 357
  - secondary cracks, 129
  - sliding mode crack closure effect, 219
  - steady-state, variation with stress intensity factor, 342–343, 345, 347
  - striation spacing, 202
  - transient, ability of closure to account for, 172–174
  - true curve, 222–223
  - under variable-amplitude random-sequence load spectra, 359
  - variation with overload ratio, 358, 360
  - versus total strain, 132
- Crack initiation, 136
  - fatigue limits, 136
  - threshold condition, 287
- Crack length
  - effective, 271
  - facets formed along, 125–126, 129
  - function of number of flight, 373–374
  - intrinsic, 290
  - per intrusion, as function of the accumulated plastic shear strain, 33–34
  - threshold relation with stress amplitude, 292–293
  - versus J-integral, 318–319
- Crack mouth opening displacement, versus applied stress, 329–330
- Crack nucleation (*see also* Persistent slipbands), 26–37, 39
  - after fatigue, 57
  - cycles to failure, as function of oxygen pressure, 35–36
  - environment effect
    - early crack growth, 33–35
    - formation of PSBs, intrusions and cracks, 31
  - experimental details, 27–29
  - geometrical difference between intrusions and crack nuclei, 30–31
  - mechanism, 36–37
  - persistent slipbands, 47–48
  - pure iron, 98
  - secondary hardening in inert environments, 31–33
  - sites, 106
    - grain boundaries, 114
  - slipband cracks, 47, 54
  - statistical aspects, 116–117
  - transgranular crack, 45–46, 52
  - values of fit parameters, 36
- Crack opening
  - acoustic measurement, 325–326
  - microscopic measurement, 326–327
  - Mode I, proposed model, 227–228
  - SAW and SEM measurements, 328–330
  - stress, 323
    - intensity determination, 166
- Crack opening displacement, 233
  - applied tensile stress, 326
  - measurement, 188–189
  - precracked specimen, 190–192
- Crack path
  - deviation following single peak overload, 177–178
  - morphology, near-threshold growth, 345–346
  - relation to overload plastic zone, 178, 180
- Crack plane, 208–209
- Crack propagation, 26, 136, 157, 233
  - biaxial, 237–239
  - elastic-plastic fracture mechanics parameters, 246–248
  - life, relation with strain energy parameter, 320–321
  - Mode I, Paris law, 235–236
  - smooth specimen under constant stress amplitude, 189–190
  - threshold condition, 289
- Crack propagation rate
  - function of cyclic stress intensity, 217
  - relationships, 337
  - relation with J-integral range, 315–317
  - stress intensity range relation, 285–287
- Crack surface, interaction mechanisms, 272–274

- Crack tip
  - blunting, crack growth retardation, 159–160
  - closure, reduced crack propagation rate, 190–192
  - compliance measurements, 269–271
  - displacement, relationship with plastic strain intensity, 218
  - plasticity, EPFM analysis, 238–239
  - residual stresses ahead of, 161–162
  - slipband ahead of, 282
  - strain hardening, crack growth, retardation, 160
- Crack-tip clip gage
  - anvil geometry, 265
  - load-displacement traces, 272
  - Mode II crack growth, 262–263, 265
  - recording instrumentation, 265
- Cross-slip, 17, 25
  - role, 17–18
- Crystal orientation, 17
- CSS unlocking model, 276–278
- CTOD, formulas, 236–237
- Cyclic deformation
  - dynamic recovery during, 90–93
    - mechanism, 88–89, 91
    - structure breakdown resistance, 93
- Cyclic hardening, 19–21
  - copper single crystals, 19–20
  - edge dislocation dipole accumulation, 17
  - orientation effect of initial hardening rate, 20–21
- Cyclic loading, 194
  - out-of-phase, 195
- Cyclic strain
  - reduction, matrix effects, 78–79
  - within cell, 78
- Cyclic stress-strain behavior, 17, 83–86

## D

- Delayed retardation, 158
- Dipolar walls, within persistent slipbands, 41
- Discontinuous closure, 172, 174
- Dislocation
  - boundary sources, 89
  - density, 87, 89, 91, 207
  - generation rate, 93
- Dislocation cells, 207–208
  - arrangement, 208
- Dislocation microstructure, 17, 22–24
- Dislocation structures, 39–61, 194
  - after fatigue, 57
  - compatibility of macroscopic and microscopic observations, 49, 52, 54
  - extrusions and intrusions, 44
  - in grain apart from edge of hole, 59–60
  - material and test procedure, 56–58
  - observation by TEM, 51, 60
  - review of previous work, 42–49
  - successive observation by optical microscope, 50, 58
- Dislocation substructure, 202, 204–206
- Displacements, residual, 175–176
- Driving force, versus resistance, 290–291, 293
- Dugdale model
  - extended to CCP specimens, 241, 244–245
  - superposition of loads, 241–243
  - under biaxial cyclic stress, 238–246
  - under plane strain, 253–255
- Dynamic recovery, during cyclic deformation, 90–93

## E

- Edge crack, nonpropagation criterion, 287
- EGM model, 42, 47, 54
- Elastic-plastic fracture mechanics (*see also* Plastic zone size, cyclic), 122, 312
  - crack-tip plasticity, 238–239
  - parameters, 233–253
    - biaxial stress, 237–238
    - correlations, 258
    - crack propagation, 246–248
    - fatigue, 235–237
    - small-scale yielding, 237
    - statistical analysis, 257–258
- Elastic stress, maximum, 136
  - relation to notch root radius, 145–147, 149–150
- Elber gage, 163, 165
- Ellipticity ratio, surface cracks, 128–130
- Endurance limit, 184
- Engineering alloys, 301
  - characteristics contributing to resistance to crack growth, 369
  - chemical composition, 303
- Etch pit method, 98–99
  - grain orientation analysis, 100–105
  - patterns with different orientations, 101
- Exoelectron emission, 69, 71
- Experimentation, 9–13
- Experiments, types, 10
- Extrusion, 26, 44, 67–79
  - development, 67

experiment, 68–69  
 formation, stress-induced release of dis-  
 locations, 75–76  
 parabolic law, 74  
 periodic, 75  
 regular array, 71–73  
 specimen geometry, 68

## F

Fatigue limit, 136, 281  
 Fatigue test, iron, 105–106  
 Fatigue threshold, 337–354  
     compression overload experiments, 342–  
     343  
     concept, 338–341  
     constant-amplitude, 342–345  
     materials, 340–343  
     physical rationale, 338  
     significance, variable-amplitude loading,  
     338  
     tests, 341–343  
     uniqueness, 338  
     variable-amplitude, 345, 348–353  
 Ferritic steel, crack growth rate, 372  
 Foil specimen, preparation, 49, 56–57  
 Fractography, 194, 214, 301  
     crack growth retardation, 167–169  
 Fracture, 136  
     factory roof type, 228  
     fatigue limit, prediction, 137  
     lamellar, 226–228  
 Fracture mechanical characterization, Mode  
     III crack growth, 217–218  
 Fracture mechanics, 281  
 Fracture surface, 302  
     factory roof type, 219–220  
     fatigued in vacuum, 308  
     microstructure effect, 308  
     morphology  
         effect of single peak overload, 168–169  
         near-threshold growth, 345–346  
     under pure torsion, 127, 129  
     SEM, 202–203  
     specimens under tension-tension cycles,  
         302, 304  
     AISI 4340 steel, 219–220  
 Friction, 260  
 Frictional shear stress, 269

## G

Grain  
     containing persistent slipband, 77

diameter ratio, density distribution, 115,  
 117  
 dominating slip systems, 109–111  
 size, 281  
 surrounding cracks, 108–109  
 test area, 109–113  
 Grain boundary, 98  
     configuration, 111  
     interaction with persistent slipbands, 46–  
     47, 52, 54  
     possible fatigue crack nucleation sites, 114  
 Grain orientation analysis, 98  
     etch pit method, 100–105  
         circular arcs, 103  
         locus of stereographic projection, 102–  
         103  
     stereographic and orthogonal projec-  
     tions of vectors, 102–103  
     transformation equation, 101, 104

## H

Humberside Study, 7–8

## I

Inconel 718, 120  
 Intrusion, 26, 44  
     formation, 37  
         environmental effects, 31–32  
     geometrical difference from crack nuclei,  
         30–31  
 Iron  
     crack, 108–109  
         nucleation, 98  
     cross section observation, 113–116  
     etchants and etching conditions, 99  
     fatigue test, 105–106  
     grain  
         boundary configuration, 111  
         orientation analysis, 100–105  
         surrounding cracks, 108–109  
         test area, 109–113  
     heat treatment and mechanical proper-  
     ties, 105  
     microcrack, 107–109, 112  
     Schmid factor, 108–109, 111  
         frequency distribution, 116–117  
     S-N relation, 105–106  
 Iron-nickel alloy  
     crack branching, 309  
     fracture surfaces, 302, 304

**J**

- J-integral, 233, 312
  - applicability to short cracks, 318
  - life prediction approach, 319–321
  - limitations in representation of small-crack growth behavior, 315, 318
  - plane-strain situations, 248
  - prediction of crack growth initiation, 236
  - range, relation with crack propagation rate, 315–317
  - short crack growth, 315
  - versus crack length, 318–319

**L**

- Ladder structure, 39–40, 58, 60
  - formation from vein structures, 60
- Law-like relationship, 11
- Life, as function of peak normal strain, 196–197
- Life prediction, 312, 314
  - J-integral approach, 319–321
- Linear elastic fracture mechanics, 121, 136, 234
- Linear fracture mechanics, 136
- Linear notch mechanics, 136, 139–144
  - effectiveness for fatigue problems, 143–144
  - stress distribution,  $x$ -axis, 139
  - stress field
    - near root of notch, 140, 142
    - near tip of crack, 139–140
- Loading mode, fatigue threshold effect, 294–296
- Long crack growth, spectrum loading, 373–374

**M**

- Measurement, 9–13
- Microcrack, 184
  - crack growth retardation, 161
  - iron, 107–109, 112
- Micromilling, 27
- Microstructure, 337
  - effect on fracture surfaces, 308
- Misorientation measurements, 81, 84–87
- Mixed mode loading, 214
- Mode I crack growth
  - crack opening model, 227–228
  - crack propagation, Paris law, 235–236
  - rate, 133
- Mode II crack growth, 260–279
  - coplanar, 261

- crack-tip, compliance measurements, 269–271
- crack-tip clip gage, 262–263, 265
- cyclic unlocking and slip behavior, 267–269
- definitions, 263–265
- experiment, 261–263
- implications, 277, 279
- plastic replication technique, 262, 264
- specimen geometry, 263
- unlocking behavior
  - first loading, 265–266
  - modeling, 274–277
- wedging behavior of crack flanks, 273
- Mode III crack growth, 215, 219–221
  - fracture mechanical characterization, 217–218
  - fracture surface, 229
  - rate, 121, 266
  - versus plastic strain intensity, 222–223
- Mohr's circle, strain, combined loading, 130–131

**N**

- Nondestructive testing (*see also* Surface acoustic wave), 323
  - opening behavior of large cracks, 323
- Nonpropagating crack, 136, 184–193
  - crack opening displacement, measurement, 188–189
  - crack tip closure, 190–192
  - critical length, 186–187
  - material and experimental procedures, 185
  - micro-Vickers indentation marks, 185–186
  - opening and closing behavior with stress release annealing, 185–188
  - oxidation effect on closure, 192
  - slipband formation, 187–188
  - variation of length with stress amplitude, 293–294
- Nonproportional straining, 194–212
  - crack growth rate, 208–210
  - dislocation substructure, 202, 204–206
  - experiment, 198–202
  - hardening mechanisms, 206–208
  - microscopic examination, 202–206
  - specimen geometry, 200
  - tension-torsion test, 196–197
- Notch effects, 136–137
  - ordinary notches in fatigue, 145, 147–148
  - predicting method, 139

- shallow or extremely shallow notches in fatigue, 150–152
- unifying treatment, 152–153
- Notch fatigue, threshold models, 287, 289
- Notch geometry, fatigue threshold effect, 294–296
- Notch root
  - radius, 136–137, 160
  - states, 146
- Notch size, fatigue threshold effect, 295–296

## O

- Optical microscope, successive observation by, 50, 58
- Orthogonal projections, 102–103
- Overloads, 357
  - effect and *R*-ratio, 368
- Oxidation, 184
  - crack closure, 192

## P

- Paris law
  - equations, 257
  - Mode I crack propagation, 235–236
  - modified, 172
- Pearlitic steel, 184
  - chemical composition, 185
  - mechanical properties, 186
  - microstructural parameters, 186
  - micro-Vickers hardness, 188–189
  - surface microstructure, 185
- Persistent slipbands (*see also* Crack nucleation; Extrusion), 17, 39–40
  - appearance and disappearance, hysteresis loop, 43–44, 49
  - appearance at surface, 44, 52
  - crack nucleation at, 47–48
  - dipolar walls, 41
  - elongation rate, 76–77
  - exoelectron emission, 69, 71
  - fatigue cycle effect, 70
  - formation, 29
    - environmental effect, 31–32
  - grain containing, 77
  - growth, 75–76
  - importance, 67
  - interaction with grain boundaries, 46–47, 52, 54
  - ladder structures, 40, 42
    - formation mechanism, 48–49
  - matrix interface, 47
  - photoelectron microscope, 76

- plastic shear strain amplitude, 29
- plastic strain amplitude, 22–23
- profile, 29, 31
- protrusion height, 30, 32
- review of previous work, 42–44
- secondary hardening, 33
- strain concentration, 76–79
- surface profile, 42, 47
- three-dimensional model, 40, 43
- ultrahigh vacuum, 32
- volume fractions, 21–22
- Photoelectron microscopy, 67
  - persistent slipbands, 76
  - specimen geometry, 68
- Plane slip, 206–207
  - schematic representation, 207
- Plane strain, Dugdale model under, 253–255
- Plane-stress zone, 361
- Plastic deformation, 194
  - interlocking surface asperities, 273–274
- Plasticity-induced crack closure, crack growth retardation, 162
- Plastic replication technique, Mode II crack growth, 262, 264
- Plastic shear strain
  - accumulated, crack length as function of, 33–34
  - amplitude, persistent slipbands, 29
- Plastic strain
  - amplitude, persistent slipbands, 22–23
  - intensity, 217
    - relationship with crack tip displacement, 218
  - versus dissipated strain intensity, 224–225
  - versus Mode III crack growth rate, 222–223
- Plastic zone
  - length, 236
  - local forces, 227–228
  - overload, 361–363
  - radius, 217–218
- Plastic zone size, 136, 233
  - cyclic, 209–210, 241
    - crack growth rate dependence, 246–247
  - finite-width corrections, 244–245
  - formula, 210
  - overload, 370
    - forward, 160, 165, 167
    - number of cycles of delay as function of, 366–367
  - parameter, 236
  - relative, 141, 144

Plastic zone size—*Continued.*

- short cracks, 240
- stress intensity factor, 140
- Poisson ratio, effective, 125
- Polygonization, 91
- A533B pressure vessel steel, blunted cracks, 159
- Pushrod closure gage, 163–164

## R

- Rayleigh wave, stress components, 333
- Reflection coefficient
  - definition, 332–334
  - measurements, surface acoustic wave, 329–330
  - versus applied stress, 329–330
  - versus applied tensile stress, 325
  - versus normalized crack depth, 334
- Residual compressive stress, 184
- Residual stress (*see also* Linear notch mechanics)
  - quantitative measurements, 331
  - time-of-flight measurements, 331
- Rotating bending fatigue, 136–153
  - dimensions of notched specimens, 143
  - elliptical hole in tension, 138–139
  - notch effects
    - ordinary notches in fatigue, 145, 147–148
    - shallow or extremely shallow notches in fatigue, 150–152
  - relation between notch geometry and crack initiation limit, 144
  - reliability of effective crack depth concept, 148, 150
  - test procedures, 144–146
- R-ratio
  - effects, 367
  - high-baseline, 368
- Rubbing fracture surfaces, 215

## S

- Saturation shear stress, relation to dislocation density, 85
- Saturation stress, 21
- Scanning electron micrograph, persistent slipbands, 71–73
- Scattering geometry, generalized, 332
- Scattering theory, 332–335
- Schmid factor, 98, 108–109, 111

- frequency distribution, 116–117
- slip systems, 113
- Screw dislocations, 17–25
  - crystallographic characteristics of specimens, 18
  - cyclic hardening, 19–21
  - dislocation microstructures, 22–24
  - double slip crystals, 24
  - experimental parameters, 18
  - persistent slipbands, 17
  - saturation stress, 21
- Secondary crack, 301
  - association with striations, 302
  - crack growth rate, 129
- Secondary hardening, inert environment, 31–33
- Sectioning technique, 27
- Shallow notch, notch effects, 150–152
- Shear mode, 215, 260
- Shear strain, amplitudes, biaxial fatigue, 131
- Shear stress
  - distribution, 210
  - push dislocation through wall, 207
- BS 4360 50B sheet steel, 262
- Short crack, 235, 312–322
  - closure stress range, 240
  - experimental procedure, 313
  - growth
    - mechanics and mechanism, 314–319
    - rate, 321
- J-integral approach to life prediction, 319–321
- mechanism, 321
- notches, 281–297
  - crack closure development, 286–288
  - crack closure measurement, 284–285
  - crack propagation rate, stress intensity range relation, 285–286
  - driving force, versus resistance, 290–291, 293
  - effect of notch geometry and loading mode on fatigue thresholds, 294–296
  - fatigue testing and stress intensity factor, 283–284
  - limiting curve for nonpropagation of crack, 292–293
  - material and test specimen, 282–283
  - Tanaka-Nakai model (*see* Tanaka-Nakai model)
  - plastic zone size, 240
  - spectrum loading, 373
  - strength properties and crack growth behaviors, 313–314
  - tensile overloads, 372–373



- Sliding mode crack closure, 214–230, 263–264
  - cyclic Mode III + static Mode I crack growth measurements, 225–227
  - effect on crack growth rate, 219
  - experimental procedure, 216–217
  - fracture mechanical characterization, 217–218
  - literature review, 215–216
  - longitudinal elongations, 227
  - measuring procedure, 218–219
  - Mode III striations, 228–229
  - practical relevance of results, 229–230
  - quantitative characterization, 223–225
  - scientific relevance of results, 227–229
  - specimen diameter effect on influence, 224
  - true crack growth curve, 221–223
- Slip
  - decohesion, 301
  - static and reversed, 270–271
- Slipband, 301
  - ahead of crack tip, 282
  - associated with striations, 304–305
  - cracks, nucleation, 47, 54
  - formation, 187–188, 308
  - secondary crack produced between, 302, 304
- Slip systems, 108
  - dominating, 98, 109–111
  - frequency distribution of angles, 116–117
  - orthogonality, 98
  - Schmid factors, 113
- Small crack (*see also* Surface acoustic wave), 120
  - growth, 121, 323, 331
  - effect, 121–122
- Small-scale yielding, elastic-plastic fracture mechanics parameters, 237
- Spectrum loading, 373–374
- Stainless steel, 233
  - threshold data, 344
- AISI 316 stainless steel, 199, 238
- Static recovery, microstructural changes, 91
- Statistical analysis, elastic-plastic fracture mechanics parameters, 257–258
- Statistical distribution, 98
- Steel, 136, 157, 260
  - crack coalescence, 314
  - low-carbon, 281
  - mechanical properties, 283
  - low-strength, discontinuous closure, 174
- AISI 4340 steel
  - fracture mechanical characterization, 217–218
  - fracture surface, 219–220
  - properties, 217
- AISI C1018 steel
  - fracture mechanical characterization, 217–218
- Mode III
  - crack growth rate, 226
  - fracture surface, 229
  - properties
- Step-like fatigue crack, profile, 307
- Stepwise loading sequence, precracked specimen, 190
- Stereographic projection, 98, 102–103, 118–119
- Strain
  - concentration in slipband, 76–79
  - intensity equations, 131
  - Mohr's circle, 130–131
  - total, 195
  - von Mises criterion, 125
- Strain cycling, 81
  - types, 196
- Strain energy parameter, relation with crack propagation life, 320–321
- Strain hardening
  - crack tip, 160
  - exponent, 211
  - mechanisms
    - dislocation cells, 207–208
    - plane slip, 206–207
- Strain intensity factor
  - definition, 235–236
  - dissipated, versus plastic strain intensity, 224–225
- Strength reduction factor, 136
- Stress
  - amplitude
    - threshold relation with crack length, 292–293
    - variation of nonpropagating crack length, 293–294
  - applied, effective fraction, 287
  - average back, 209
  - components, surface acoustic wave, 333
- Stress concentration factor, 39, 136
- Stress cycles, cruciform specimens, 198
- Stress field
  - generated by crack or notch, 139–143
  - near root of notch, 140, 142
  - near tip of crack, 139–140
- Stress function, 254

Stress intensity factor, 136, 233, 290  
 against notch sharpness, 147–148  
 correction factor, 284  
 crack growth rate as function of, 369–370  
 cyclic, propagation rate and, 285–287  
 cyclic, propagation rate as function of, 217  
 effective, small cracks, 330–331  
 effective fraction, variation with crack length, 295–296  
 effective range, 293  
 fatigue testing, 283–284  
 high baseline levels, 177–178  
 implications, 354  
 low baseline levels, 178, 180  
 plastic zone size, 140  
 relation with nominal stress, 148, 150  
 threshold, 290  
   effective, 289  
   versus crack length, 294–295  
 variation following single compression overload, 345, 350

Stress ratio, 233

Stress release annealing, crack opening or closure behavior, 185–188

Stress state, 157

Stress-strain hysteresis loops, annealed aluminum, 83–84

Striation  
   appearances, 307–308  
   formation, 301–310  
     mechanism, 306  
     morphology, 304–306  
   secondary cracks associated with, 302  
   slipbands associated with, 304–305  
   spacing, 202

Strip yield zone, 238

Structural stability, 93–94

Substructural developments, 81–96  
   cyclic stress-strain behavior, 83–86  
   dislocation density, 87  
   dynamic recovery, during cyclic deformation, 90–93  
   experimental procedure, 82–83  
   mechanism of cyclic deformation, 88–89, 91  
   misorientation measurements, 84–87  
   structural stability, 93–94  
   substructure-stress relationship, 94–95

Substructure, as-extruded, 93–94

Surface acoustic wave, 323–332  
   constant-amplitude stress history, 327–328

  crack opening, microscopic measurement, 326–327  
   crack opening measurement, 325–326, 328–330  
   crack size measurement, 324–325  
   reflection coefficient measurements, 329–330  
   transducers, 323  
   variable-amplitude stress history, 327–329

Surface crack  
   crack geometry, 128–130  
   ellipticity ratio, 128–130  
   growth  
     cyclic loading, 130  
     rates, as function of surface crack length, 124, 128  
   semi-elliptical, 334

Surface roughening, 47

Surface states, 149–150  
   roots of extremely shallow notches, 151

## T

Tanaka-Nakai model, 287–290  
   evaluation, 290–294

Tensile overloads, short cracks, 372–373

Tensile stress, applied  
   COD versus, 326  
   reflection coefficient versus, 325

Tension-torsion test, nonproportional straining, 196–197

Threshold condition, 281

Tilt boundary, 88, 91

Time-of-flight measurements, residual stress, 331

Titanium alloys, fracture surfaces, 302, 304

Torsional loading, 214  
   cyclic, 229

Transgranular crack, nucleation, 45–46, 52

Transmission electron microscopy  
   dislocation structures, 39  
   observation, 51, 60  
   substructural developments, 83

T-stress, 241, 251

Twin cantilever gage, 163, 165

## U

Unlocking behavior  
   modeling  
     behavior, 276  
     comparison with experiment, 276–277  
     model description, 274–276

precrack on first loading, 275–276  
 precrack on unloading, 276–277  
 Unlocking response, first loading, 265–266

## V

Variable-amplitude loading, 157, 337, 357  
   fatigue threshold, 345, 348–353  
   significance, 338

Variable-amplitude stress history, surface  
   acoustic wave, 327–329  
 Vein structure, 39–40  
   ladder structure formation, 60  
 von Mises criterion, 125, 254

## Y

Yield strength, 369, 371