

# Subject Index

## A

Abrasive wear, 75-89  
   AP-orientation, 81-83  
   comparison of experimental and predicted rates, 87-88  
   crossover point, 83-85  
   materials, 76  
   minimum and maximum wear rates, 86  
   modified rule-of-mixtures, 87-89  
   N/AP woven composite, 85  
   N-orientation, 82-83  
   N/P woven composite, 84-85  
   P/AP woven composite, 83-84  
   P-orientation, 81-83  
   scanning electron microscopy, 79  
   sliding directions, 77-78  
   specimen area effect, 79-80  
   testing procedures, 78  
   two-dimensional woven fiber system, 82-86  
   unidirectional continuous fiber composite, 79-82  
   variation of properties with orientation, 82-83  
   wear equation, 78  
 Adhesive bonding, 31  
 Advanced Communications Technology Satellite, 31  
 Aluminum  
   honeycomb, 31  
   matrix, 261  
   mechanical properties, 263  
 Analysis of variance method, 137  
 Anderson-Darling test  
   *k*-sample, 136, 139-141  
   lognormality, 144-145  
   normality, 144  
   statistic, 141, 143-144  
   Weibullness, 143  
 Anisotropy, 224  
 ANOVA method, 145-147  
 ASTM D 638, 111, 113-114  
 ASTM D 648, 96  
 ASTM D 695, 99-101, 111, 113, 117, 132, 180  
 ASTM D 790, 35  
 ASTM D 792, 96  
 ASTM D 2290, 98  
 ASTM D 2344, 35, 104-105, 111, 113, 120  
 ASTM D 2584, 96  
 ASTM D 2585, 99

ASTM D 2586, 100-101  
 ASTM D 2719, 41  
 ASTM D 2734, 96  
 ASTM D 3039, 96, 111, 113, 132  
 ASTM D 3171, 96  
 ASTM D 3410, 100-103, 111, 113, 120, 181  
 ASTM D 3518, 104, 106, 108  
 ASTM D 3846, 104-108  
 ASTM D 4065, 96  
 ASTM D 4255, 104, 107-108  
 ASTM E 399, 46  
 Asymmetric four-point bend test fixture, 233-234  
   tab configurations used with, 233  
 Axial extensometer, 9  
 Axial modulus, 276-277

## B

*B* basis factors, 130, 132-134  
 Bending modulus, 39  
 Bismaleimide, 55  
 BMAS glass-ceramic matrices, 5  
 Boron/aluminum laminate, moire fringes, 268-269  
 Buckling study, torsion tubes, 212-216

## C

Carbon, 45  
 Celanese compression fixture, 101-102  
 Ceramic composites, 3  
 Characterization, 83  
   problems unique to composites, 94-95  
 Complementary shear, 228  
 Composite plaque, 46-47  
 Composite sandwich materials, 31-44  
   composite three-point bend tests, 35-36, 42  
   crippling failure, 36, 39  
   critical lengths, 39  
   failure mode, 43  
   flexural properties, 39-40  
   laminate strengths, 41  
   lap shear strength, 34  
   material properties, 33  
   material test matrix, 32, 34  
   materials and fabrication procedures, 32-33  
   picture-frame tests, 34-35, 41-42

Composite sandwich materials (*cont.*)  
 sandwich flexure tests, 35-36  
 sandwich structure tests, 43  
 shear properties, 42  
 shear stiffness, 43  
 tensile properties, 36, 38  
 tension specimens, 34, 37  
 Composite three-point bend tests, composite sandwich materials, 35-36, 42  
 Compression, 45, 93, 180  
   properties, short-fiber reinforced thermoplastics, 50  
 Compression stiffness, 183  
 Compression testing, 183  
   cylinders, 101  
   fiber reinforced composites, 99-103  
   statistical data reduction, 116-121, 124-125  
 Compressive strength, ultimate, 118, 124  
 Computer analysis, 31  
 Contact diameter, 169, 171  
 Contact pressure, versus impact force, 171-172  
 Crippling failure, 36, 39  
 Crossbeam shear specimen, 107  
 Crossover point, abrasive wear, 83-85  
 Cut depth, equivalent, 173-175

## D

Damage, 180  
   contours, Love's solution, hemispherical contact pressure, 169-170  
   depth  
     versus mean contact pressure, 169-170  
     prediction, 171  
     development, 276  
 Debonding energy, 228-229  
 Deflection, relationship with load, 37  
 Delamination, 197  
   depth  
     after loading, 174-177  
     comparison with equivalent cut depth, 175  
 Design allowables, 93, 96  
   factors/conditions affecting, 107-108  
   *see also* Statistical data reduction; Statistical methods, design allowables calculation  
 Double-rotating-disk testing device, 59  
 Double V-notch shear specimen, 105-106

## E

Effective stress-effective plastic strain curve, 274

Elastic moduli, 263  
 Elastic-plastic stress, 261-274  
   comparison of rectangular and radial mesh results, 268, 270  
   distribution ahead of slit tip, 268  
   experimental procedures, 262  
   fiber stress concentrations for layups containing 0° plies, 272  
   homogeneous materials, 267  
   material model, 268, 273-274  
   mesh description, 268-269  
   metal matrix composites, 267-272  
   specimens, materials, and preparations, 262  
   strain, front of slit tip, 264-267, 270-271  
 End caps test fixture, 99-101  
 Environmental effects, 16  
 Epoxy, 55  
   adhesive, lap shear strength, 34  
   final failure mode, 246  
 Erosion, 58  
 Erosion test chamber, 57  
 Extensometers, 9-11

## F

Failure mode, composite sandwich materials, 43  
 Failure stress, 263-264  
 Fatigue, 180  
 Fatigue testing, 276  
 Fiber reinforced composites, 93-109  
   characterization, 94-95  
   compression testing, 99-103  
   factors/conditions affecting design allowables, 107-108  
   hoop fiber stress, 99  
   in-plane shear testing, 106-107  
   interlaminar shear testing, 104-106  
   Morton Thiokol test fixture, 97-98  
   NOL ring split disk method, 98  
   physical property testing, 96  
   shear testing, 103-107  
   specimen fabrication and preparation, 95  
   tension testing, 96-99  
   transverse tension testing, 97-98  
 Filament-wound composites, 150, 208  
   membrane region, 152  
 Finite element analysis, 231  
   Iosipescu shear test, 247, 250-257  
   modeling, 238-239  
   isochromatic fringe patterns, 240-242  
   material properties used in, 239  
   meshes, 268-268  
   three dimensional, 261, 267-268  
 Flatwise tension, 197-198

Flexural properties, composite sandwich materials, 39-40  
 Flexural rigidity, 37, 39  
 Four-point ring twist testing, 106  
 Four-point shear test method, 104-105  
 Fracture energy, 224  
 Fracture modes, short-fiber reinforced thermoplastics, 50-51, 53  
 Fracture toughness, 45  
   short-fiber reinforced thermoplastics, 50, 52-53  
 Friction, 75  
 FTMS-406, 99-100

## G

Glass, 45  
 Glass/ceramic matrix composites, 3-14  
   materials and apparatus, 5-6  
   mechanical properties, 3-4  
   off-axis properties, 13  
   stress-strain curves, 10, 12-14  
   tension specimens and testing, 6-10  
   test method development, 4-5  
   unidirectional composite properties, 11  
 Glass/epoxy composites, 198-199  
   sand erosion, 60-62  
 Glass fiber composites, 55  
 Glass transition temperature, 96  
 Goodness-of-fit test, 138  
   lamina tests, 113  
 Graphite/bismaleimide, sand erosion, 62, 68  
 Graphite/epoxy composite, 16-30, 111, 150-178, 180, 197  
   clamped in cutting jig, 201  
   conditioning procedure, 17-18  
   failure modes, 191  
   first ligament failure, 165-167  
   hoop-fiber stress, 164  
   hygrothermal test conditions, 19  
   impact damage  
   delamination depths after loading, 174-177  
   equivalent cut depth, 173-174  
   predictions and radiographs, 169-173  
   impact tests, 153-155, 158-164  
   initial shear modulus 20, 251  
   in-plane shear properties, 27-29  
   longitudinal tensile properties, 25-27  
   material, 152-153  
   properties, 178  
   specimen preparation, 17-18  
   mixed amplitude cyclic loading, 189-190  
   penetrant-enhanced x-ray, 187, 189  
   photoelastic isochromatic fringe pattern, 236, 238-242

  post-failure appearance, 184-186  
   ratio of impact strength to undamaged strength versus impact force, 166-168  
   residual strengths, 155-156, 187-188  
   shear strength, 175-176  
   shear stress versus shear strain, 280-282  
   static compliance tests, 155, 157-158  
   statistical properties, 131  
   stiffness response, 187-188  
   strength tests, 155-156  
   impacted specimens, 165-169  
   undamaged specimens, 157, 164-165  
   stress-life, fully reversed cyclic loads, 185, 187  
   test procedure, 19  
   time-temperature-moisture master curves, 22-23, 25-29  
   time-temperature moisture shift factor, 27, 29  
   time-temperature shift factor, 23-25  
   transverse stress-strain curves, 20-21  
   transverse tensile properties, 20-25  
   X-radiographs, 281, 283  
   X-ray tests, 155  
 Graphite fiber composites, 31, 55  
 Graphite fiber/polyetheretherketone composites, 180  
   post-failure appearance, 184-186  
   residual strengths, 187-188  
   stiffness response, 187-188  
   *see also* Abrasive wear  
 Graphite/nylon, sand erosion, 72  
 Graphite/polyimide, sand erosion, 60-62, 67  
 Graphite/polyphenylene sulfide, sand erosion, 62, 69, 71

## H

Hertz law, 157, 163-164  
 High temperatures, 3  
 Hoop fiber stress, 99  
   graphite/epoxy composite, 164  
 Hybrid laminate, 127  
 Hygrothermal characterization, 16

## I

IITRI compression test fixture, 102  
 Impact damage, 150  
   graphite/epoxy composite  
   delamination depths after loading, 174-177  
   equivalent cut depth, 173-174  
   predictions and radiographs, 169-173  
 Impacted rings, mass and kinetic energies, 153-154

Impact force, versus contact pressure, 171-172

Impact tests

- force, 163
- graphite/epoxy composite, 153-155, 158-164
- impacter force versus energy, 162-163
- impacter mass effect, 160-161
- kinetic energy effect, 159-160
- maximum force, 158-159
- rebound velocity versus impacter mass, 161-162

In-plane shear, 208

- properties, graphite/epoxy composite, 27-29
- testing, fiber reinforced composites, 106-107
- torsion tubes, 216-222

In-plane shear modulus, 276-283

- evaluation of method, 280-281
- fixture description, 277-279
- jig and assembly of fixture, 278-279
- rail shear fixture, 278
- test procedure, 279-280

In-plane shear strain, 280

In-plane shear stress, variation, 250-251, 254

Interlaminar stresses, 197

Iosipescu shear test, 231-259

- final failure mode, 246
- finite element analysis, 247, 250-257
- finite-element modeling, 238-239
- fixture behavior during testing, 243-244, 246-247
- in-plane shear stress, 250-251, 254
- 45° isoclinic, 237
- loading fixtures, 233-235
- longitudinal stress, 250, 253, 256
- material properties, 247-249
- moiré interferometry, 238, 240, 243-245
- photoelastic measurements, 235-238
- photoelastic coating, 238-240
- shear stress
  - along notch flank, 250, 257-258
  - distribution between notches, 250, 259
- specimens, 105-106, 232-233
- stress ratio, 250, 259
- tab configurations used with AFBP fixture, 233
- testing and instrumentation, 235
- test matrix, 235-236
- transverse stress, 250, 252, 255

## K

Kevlar

- fiber composites, 55

machining, 95

Kevlar/epoxy

- sand erosion, 61, 64
- tubes, 210
  - buckled, 212-213
  - filament winding patterns, 211
  - in-plane shear behavior, 217, 220
  - shear stress-strain curve, 217-218, 221
  - shear stress versus tensile and compressive strain, 218, 222

Kolmogorov-Smirnov comparative tests, 112-115

*k*-sample Anderson-Darling test, 136, 139-141

## L

Lamina constants, graphite/epoxy composite, 178

Laminates

- strengths, composite sandwich materials, 41
- wrinkle-free and wrinkled, 164

Lamina tests, 111-126

- batch-to-batch variability, 113-114
- compression test results
  - fabric, 116-119
  - tape, 120-121, 124-125
- goodness-of-fit test, 113
- Kolmogorov-Smirnov comparative tests, 112-115
- matrix, 112-113
- pooling of data, 112-113
- short beam shear test results
  - fabric, 120-123
  - tape, 125-126
- tension test results
  - fabric, 114-116
  - tape, 120, 123-124

Laminate tests, 111, 126-130

- B* basis factors, 130, 132-134
- open-hole tension test specimen, 128
- rail shear test specimen, 129
- sandwich compression test specimen, 128
- single shear test specimen, 129
- test matrix, 127

Lap shear strength, epoxy adhesive, 34

Life, 180

Load, relationship with deflection, 37

Lognormal analysis procedure, 148

Lognormality, Anderson-Darling test, 144-145

Longitudinal extensometer, 9-10

Longitudinal stress, 250, 253, 256

Love's solution, 169

Low temperature, 45

## M

Material model, 268, 273-274  
Matrix cracking, 10  
Matrix materials, reinforced  
    graphite UD tape, sand erosion, 61-62, 65  
    graphite-woven fabric, sand erosion, 61-62, 66  
Maximum normed residual test, 138-139  
Mechanical properties, 31, 231  
    lamina, test matrix, 112-113  
Metal matrix composites, elastic-plastic stress, 267-272  
Metals testing, versus composites, 93-94  
Moire fringes, boron/aluminum laminate, 268-269  
Moire interferometry, Iosipescu shear test, 238, 240, 243-245  
Motor case, 150

## N

NBS compression test fixture, 102-103  
Nicalon/BMAS glass-ceramic, stress-strain curves, 12, 14  
Nicalon ceramic fibers, 5  
Nicalon/1723 glass, stress-strain curves, 12-13  
Nonparametric analysis procedure, 148-149  
Normal analysis procedure, 148  
Normality test  
    Anderson-Darling test, 144  
    multiple batches, 141  
Nylon, 55

## O

Observed significance level, 141-144  
Open-hole tension test specimen, 128  
Outlier, detection, 138-139

## P

PEEK. *See* Graphite/polyetheretherketone composites; Polyetheretherketone  
Photoelastic coating, Iosipescu shear test, 238-240  
Physical property testing, fiber reinforced composites, 96  
Picture frame testing, 106  
    composite sandwich materials, 34-35, 41-42  
Plate twist testing, 106  
Polyetheretherketone, 45, 55  
    brittle fracture bands, 53  
    compressive strength, 51

fracture toughness, 53  
tensile strength, 49  
unreinforced, abrasive wear, 85-86  
*see also* Graphite/polyetheretherketone composites

Polyetherimide, 45  
    compressive strength, 51  
    fracture toughness, 52  
    tensile strength, 48  
Polyethersulfone, 45  
    brittle fracture bands, 53  
    compressive strength, 51  
    fracture toughness, 52  
    tensile strength, 49  
Polyimide, 55  
Polymer matrix, 31  
Polyphenylene sulfide, 55  
    matrix, erosion resistance, 62-63, 70  
Pultruded rod, 224-230  
    data analysis, 227-229  
    diametral fracturing, 227-228  
    preparation, 225-227  
    torque-displacement curve, 225, 227  
Pultrusion process, 225

## Q

Quasi-static tension tests, 183

## R

Rail shear testing, 106, 276  
    fixture, 278  
    specimen, 129  
Release agents, 224  
Reserved cyclic loads, 180-192  
    anti-buckling fixture, 183-184  
    constant amplitude, 185, 187-189  
    mixed amplitude cyclic loading, 189-191  
    monotonic tests and specimen design, 183-185  
    specimen gripping configuration, 181-182  
    supporting equipment and procedures, 181-183  
    unsupported length effect, 184-185  
Residual strength, 150  
    tests, graphite/epoxy composite, 155-156  
Rocket motor case, 150  
Rule of mixtures, 75  
    modified, 87-89

## S

Sand erosion, 55-74  
    background, 55-56  
    materials, 60

- Sand erosion (*cont.*)  
 mechanisms, 56  
 rate versus particle impingement angles, 63, 73  
 resistance effects, different fibers, 61  
 test conditions, 59  
 test method, 56–59
- Sandwich compression test specimen, 128
- Sandwich flexure tests, composite sandwich materials, 35–36
- Sandwich structures, 31  
 tests, composite sandwich materials, 43
- S-glass/epoxy  
 shear stress-strain curve, 212–214  
 shear stress versus tensile and compressive strain, 214–215  
 tubes  
 buckling, 212, 217–218  
 failure modes, 215–216  
 in-plane shear behavior, 216, 219
- Shear, 93, 224  
 properties, composite sandwich materials, 42
- Shear modulus, 224, 227  
 initial, 250
- Shear stiffness, 37, 39  
 composite sandwich materials, 43
- Shear stress  
 along notch flank, 250, 257–258  
 distribution between notches, 250, 259  
 versus shear strain, 280–282  
 versus tensile and compressive strains, 214–215, 218, 222
- Shear stress-strain curve  
 Kevlar/epoxy tubes, 217–218, 221  
 S-glass/epoxy, 212–214
- Shear testing, 231, 276  
 fiber reinforced composites, 103–107
- Short beam shear testing, 104  
 statistical data reduction, 120–123, 125–126
- Short-fiber reinforced thermoplastics, 45–54  
 compression properties, 50  
 fracture modes, 50–51, 53  
 fracture toughness, 50, 52–53  
 L and T orientations, 47–49  
 materials, 46  
 specimens, 46–47  
 stress-strain curves, 48  
 tensile properties, 47–50  
 test methods, 47
- Silicon carbide, 261  
 abrasive wear, 80  
 mechanical properties, 263
- Single shear test specimen, 129
- Sliding directions, 77–78
- Space antenna, 31
- Standardization, 93
- Static compliance tests, graphite/epoxy composite, 155, 157–158
- Statistical data reduction, 111–134  
 graphite/epoxy, 131  
 laminate tests, 126–130  
*see also* Lamina tests
- Statistical methods, design allowables calculation, 136–149  
 ANOVA method, 145–147  
 between-batch variance, 146  
 computational procedure, 137–138  
 detecting outliers, 138–139  
 distribution identification, 142–145  
 goodness-of-fit tests, 138  
*k*-sample Anderson-Darling test, 139–141  
 lognormal analysis procedure, 148  
 maximum normed residual test, 138–139  
 nonparametric analysis procedure, 148–149  
 normal analysis procedure, 148  
 normality test, multiple batches, 141  
 observed significance level, 141–144  
 test for equality of variances, 141–142  
 two-parameter Weibull analysis procedure, 147
- Stiffness, 180, 208  
 degradation, 187–188, 276
- Strain gage, 182  
 configurations, 235  
 embedded, 17–18
- Strain rate  
 effects, 16  
 transverse modulus as function of, 22
- Strength, 180, 208
- Strength tests, graphite/epoxy composite  
 impacted specimens, 165–169  
 undamaged specimens, 157, 164–165
- Stress concentrations, 261
- Stress ratio, 250, 259
- Stress-strain curves  
 glass/ceramic matrix composites, 10, 12–14  
 short-fiber reinforced thermoplastics, 48  
 transverse, graphite/epoxy composite, 20–21
- ## T
- Tensile properties, short-fiber reinforced thermoplastics, 47–50
- Tensile strength  
 through-the-thickness strength specimen, 203  
 ultimate, 116, 123
- Tension, 45, 93

- Tension specimens, composite sandwich materials, 34, 37
  - Tension stiffness, 183
  - Tension testing
    - fiber reinforced composites, 96-99
    - statistical data reduction, 114-116, 120, 123-124
  - Testing facility, high temperature composites, 6
  - Test methods, 93, 180
  - Thermoplastics, 45; *see also* Sand erosion
  - Thermoset composites. *See* Sand erosion
  - Through-the-thickness strength specimen, 197-206
    - development, 198-199
    - failure surfaces, 204-205
    - fiber and loading directions, 202
    - final specimen configuration, 199-200
    - preparation and testing, 200-202
    - recommendations, 205-206
    - tensile strength, 203
    - test matrix, 202-203
  - Time-temperature-moisture master curves, 22-23, 25-29
  - Time-temperature moisture shift factor, 27, 29
  - Time-temperature shift factor, 23-25
  - Torque-displacement curve, pultruded rod, 225, 227
  - Torsion, 224
    - potential energy, 228
  - Torsion tubes, 208-223
    - analytical approach, 208-209
    - buckling study, 212-216
    - in-plane shear, 216-222
    - materials and preparation, 209-211
    - test procedure, 211-212
  - Transverse extensometer, 9
  - Transverse modulus, as function of strain rate, 22
  - Transverse shear, 228
  - Transverse stress, 250, 252, 255
  - Transverse tension testing, fiber reinforced composites, 97-98
  - Two-parameter Weibull analysis procedure, 147
- U-V**
- Unidirectional continuous fiber, 75
    - abrasive wear, 79-82
  - Variance, test for equality, 141-142
- W-Y**
- Weibull analysis, two-parameter, 147
  - Weibull distribution, 113, 142
  - Weibullness, Anderson-Darling test, 143
  - Width-tapered specimen geometry, 8-9
  - Woven fabrics, 75
  - Woven fiber system, two-dimensional, abrasive wear, 82-86
  - X-ray tests, graphite/epoxy composite, 155
  - Yielding, 261