

Subject Index

A

Abnormalities, manufacturing, titanium matrix composites, 315
 Acoustic emission, 278, 335, 376
 Acoustic impact technique, 376
 Acousto-ultrasonic techniques for nondestructive testing
 adhesively bonded joints, 335
 ceramic composites, 363
 Adhesively bonded joints, nondestructive testing, 335
 Advanced materials, fatigue crack propagation
 silicon nitride, 1
 Aerospace applications, titanium alloy, 48
 Alumina, reinforcement material for metal matrix composite, 134
 Aluminum coatings for space applications, 156
 Aluminum matrix, fatigue response, 32, 134
 Anisotropic constitutive relations, 178
 Anodized aluminum coatings, 156
 ASTM standards
 E 399, 109, 124(table)
 E 647-88a, 2, 109
 E 813, 109, 124(table)
 E 1150-87, 1
 Attenuation, nondestructive testing of adhesively bonded joints, 335
 Axial-bending interaction, elastoplastic concrete frames, 244
 Axial-torsional loading, cobalt-base superalloy, 204

B

Beryllium copper alloy, 109
 Bond strength prediction, adhesively bonded joints, 335
 Boron, reinforcement material for metal matrix composites, 134
 Bridging, 19, 64
 Bridging fibers, interface strength, 64
 Bulk matrix material vs Metal matrix composites, fatigue response, 32

C

Carbon fiber reinforced composites, 255
 Ceramic composites, nondestructive test evaluations, 363
 Ceramics, fatigue crack propagation, 1
 Cobalt base superalloy, deformation behavior, 204
 Composite dynamic response, nondestructive testing of adhesively bonded joints, 335
 Composite materials, production methods, 265, 301
 Conductors, 109
 Continuous fiber reinforcement
 metal matrix composites, 32
 Copper beryllium alloy, 109
 Copper-niobium microcomposite, 87
 Cost-effective manufacturing process, 301
 Crack bridging, intermetallic matrix composites, 64
 Crack closure, 48
 Crack growth behavior
 aluminum coatings, 156
 beryllium copper alloy, 109
 intermetallic matrix composites, 64
 metal matrix composites, 32
 titanium, 48
 Crack growth tests, 2, 109
 Crack propagation, 1
 Crack tip stress, 19
 Creep analysis for notches, 230
 Cryogenic testing, 109
 Cu-Nb microcomposite
 powder metallurgy processed, 87
 Cycle stress-strain response, 178
 Cyclic deformation, 204
 Cyclic fatigue, 19
 Cyclic loading
 crack propagation in silicon nitride, 1
 elastoplastic concrete frames, 244
 graphite epoxy composites, 301
 multiaxial stress-strain creep analysis, 230

D

Damage accumulation, fatigue crack growth behavior, 48

Damage mechanisms, fatigue behavior
 acoustic impact technique, 376
 adhesively bonded joints, 335
 ceramic composites, 363
 Cu-Nb microcomposite, 87
 fiber/matrix sliding, 64
 fiber-reinforced composites, 255
 graphite epoxy composites, 301
 intermetallic matrix composites, 64
 metal matrix composites, 32, 315
 nondestructive evaluation techniques, 315, 335, 363, 376
 orthotropic material, 178
 polymeric matrix composite materials, 265
 short fiber-reinforced styrene maleic anhydride, 278
 titanium matrix composites, 315

Defect characterization, 376

Deformation behavior, cobalt-base superalloy, 204

Design for space station thermal control, 156

Dynamic response of CFRP, 255

E

Effective fatigue driving force, 64
 Effective stress intensity, 48
 Elastoplastic concrete frames, 244
 Equivalent stress strain curve, 204

F

Failure analysis method, elastoplastic concrete frames, 244

Fatigue behavior
 adhesively bonded joints, 335
 ceramic composites, 363
 Cu-Nb microcomposite, 87
 fiber/matrix sliding, 64
 fiber-reinforced composites, 255
 graphite epoxy composites, 301
 intermetallic matrix composites, 64
 metal matrix composites, 32
 orthotropic material, 178
 polymeric matrix composite materials, 265
 pultrusion process variables, 301
 short fiber-reinforced styrene maleic anhydride, 278

Fatigue crack growth behavior
 aluminum coatings, 156
 aluminum matrix composite, 134
 Cu-Nb microcomposite, 87
 intermetallic matrix composites, 64
 silicon nitride, 19
 titanium alloy, 48

Fatigue crack propagation
 beryllium copper alloy, 109, 132(table)
 metal matrix composites, 32
 silicon nitride, 1, 19

Fatigue damage
 adhesively bonded joints, 335
 ceramic composites, 363
 fiber-reinforced composites, 255
 fiber-reinforced styrene maleic anhydride, 278
 orthotropic material, 178
 short fiber-reinforced styrene maleic anhydride, 278

Fatigue driving force, 64

Fatigue, fiber matrix interface, 255

Fatigue life predictions
 aluminum matrix composite, 134
 anodized aluminum coatings, 156
 orthotropic materials, 178
 polymeric matrix composite materials, 265

Fatigue model, 265, 278, 301

Fatigue response, metal matrix composites, 32

Fiber matrix interface, 225

Fiber pressure model, 64

Fiber pushout, 64

Fiber-reinforced composites, 255, 265

Fiber-reinforced styrene maleic anhydride, 278

Fiber reinforcement, metal matrix composites, 32

Fiber strength, 64

Fractography, beryllium copper alloy, 109,

Fracture behavior
 aluminum coatings, 156
 beryllium copper alloy, 109, 124(table), 132(table)
 creep analysis for notches, 230
 Cu-Nb microcomposite, 87

Frame, elastoplastic concrete, 244

Frequency response, 255

G

Gas turbine engines, titanium alloys, 48

Glass fiber-reinforced styrene maleic anhydride, 278

Graphite epoxy, 265, 301

Graphite fiber composite, 376

Graphite, reinforcement material for metal matrix composite, 134

H

High strength, high conductivity, Cu-Nb microcomposite, 87

High-temperature aerospace applications
 cobalt base superalloy, 204

intermetallic matrix composites, 64
 titanium alloy, 48
 Humidity
 effect on aluminum coatings in space station
 design, 156
 Hysteresis energy, 278

I

In-phase loading, 204
 IHPTET program (*See* Integrated High
 Performance)
 Integrated High Performance Turbine Engineer
 Technology (IHPTET) program, U.S. Air
 Force, 48
 Interfacial damage, 64, 255
 Interfacial shear stress, 64
 Intermetallic matrix composites, titanium alloy,
 48, 64
 Intensity factor, 19
 Internal stress, 32

L

Laminates, dynamic response of CFRP, 255
 Life prediction
 adhesively bonded joints, 335
 aluminum matrix composite, 134
 nondestructive testing, 335
 orthotropic material, 178
 polymeric matrix composite, 265
 short fiber reinforced styrene maleic anhydride,
 278
 silicon nitride, 1
 titanium, 49
 Loading conditions, 178, 204, 244
 Loss factor, graphite epoxy composites, 301
 Low cycle fatigue, 134, 139(table)
 Low earth orbit, 134

M

Magnesium, 134
 Manufacturing defects, 315
 Manufacturing processes, nondestructive testing
 adhesively bonded joints, 335
 ceramic composites, 363
 Manufacturing process, pultrusion, 301
 Materials testing, 376
 Mechanical behavior and properties
 aluminum matrix composite, 134
 beryllium copper alloy, 109, 113-117(tables),
 119(table)
 carbon fiber-reinforced composites, 255

cobalt-base superalloy, 204
 intermetallic matrix composites, 67(table),
 75(table)
 metal matrix composites, 32, 33-35(tables)
 orthotropic materials, 178, 189(tables)
 short glass fiber-reinforced thermoplastic
 materials, 278, 281(table), 283(table)
 titanium alloy, 48, 50(table)
 Metal matrix composites
 aluminum, 134
 fatigue response, 32
 manufacturing abnormalities, 315
 nondestructive evaluation techniques, 315,
 324(table), 329(table)
 reinforcement materials, 134
 titanium, 315
 Microcomposite, 87
 Modulus, fatigue loss, graphite epoxy composites,
 301, 308(table)
 Multiaxial fatigue damage models, 178
 Multiaxial stress strain, 230
 Multiaxiality, cobalt-base superalloy, 204

N

Near threshold crack growth behavior, 48
 Nondestructive evaluation testing
 acoustic impact technique, 376
 adhesively bonded joints, 335
 ceramic composites, 363
 graphite fiber composite, 376
 metal matrix composites, 315, 324(table),
 329(table)
 Notch tip stresses and strains, 230

O

Orthotropic material, 178
 Out of phase loading, 204

P

Particulate reinforcement, 134
 Phase lag, 255
 Polymeric matrix composite materials, 265
 Powder metallurgy processed microcomposites,
 87
 Pultrusion process, for producing composite
 materials, 301

R

Real time nondestructive testing, 363
 Regression, graphite epoxy composites, 301
 Residual stress, silicon nitride, 1

Response volume, graphite epoxy composites, 301
 Room temperature, fatigue crack growth rates, 134

S

Scanning electron microscopy, 1
 Secant modulus, 278
 Shear lag model, 64
 Shear stress, interfacial, 64
 Short glass fiber-reinforced composite, 278
 Silicon carbide, reinforcement for metal matrix composites, 134
 Silicon carbide fibers, fatigue response, 32
 Silicon nitride
 crack growth behavior, 19
 fatigue crack propagation, 1
 Space station design, humidity effect on
 aluminum coatings, 156
 Stiffness, as a damage analogue, 32, 255, 265
 Strength prediction, adhesively bonded joints, 335
 Strengthening, Cu-Nb microcomposite, 87
 Stress, aluminum coatings, 156
 Stress distribution, adhesively bonded joints, 335
 Stress intensity
 crack growth behavior, 19, 48
 fatigue crack propagation, 1
 Stress intensity range, 48
 Stress shielding effect, 19
 Stress strain, multiaxial, for notches, 230
 Stress strain curve, cobalt-base superalloy, 204
 Stress wave factor, 335
 Styrene maleic anhydride, 278
 Subcritical crack growth, silicon nitride, 1
 Surface cracks, silicon nitride, 19
 Surface film technique, 19

T

Temperature, elevated, cobalt-base superalloy, 204

Tensile behavior
 acoustic impact technique, 376
 adhesively bonded joints, 335
 ceramic composites, 363
 Cu-Nb microcomposites, 87
 graphite epoxy composites, 301
 metal matrix composites, 134, 138(table)
 polymeric matrix composite materials, 265
 pultrusion process variables, 301
 Tension compression loading, fatigue response, 32
 Testing (*See* Nondestructive evaluation)
 Textron fiber, fatigue response, 32
 Thermal control design for space station, 156
 Thermal fatigue, 156
 Thermal stability, metal matrix composites, 32
 Thermomechanical fatigue, 315
 Thermoplastic materials, 278
 Threshold stress intensity range, titanium alloys, 48
 Through the thickness cracks
 silicon nitride, 19
 Titanium, 134
 Titanium alloy, fatigue crack growth behavior, 48
 Titanium matrix composites, 315
 Titanium matrix, fatigue response, 32
 Turbine engines, gas, titanium alloys, 48
 Tyranno fiber (Ube, Japan), 32

U

Ultrasonics, nondestructive testing
 ceramic composites, 363
 titanium matrix composites, 315

V, W, X

Variable amplitude loading, 134, 148(table)
 Water exposure, effects on short fiber-reinforced
 styrene maleic anhydride, 278
 X-ray, titanium matrix composites, 315