MASONRY: OPPORTUNITIES FOR THE 21ST CENTURY

AUTHOR INDEX

A

Abell, Anne B., 23

B

Banfill, Philip F. G., 73
Bartos, Peter M. J., 73
Berman, Scott, 51
Brosnan, Denis A., 122

C

Chan, Lisa M., 155
Chevalier, Jean, 259
Chin, Ian R., 97
Cinnamon, Anthony D., 224

D

Day, Robert L., 285
Drage, Debera F., 51

F

Frederic, James C., Jr., 122

G

Galitz, Christopher L., 114
Gerns, Edward A., 155, 224
Godbey, Richard J., 61
Goyer, Martin, 259
Grimm, Clayford T., 241

H

Holser, Peter J., 186
Hughes, John J., 73

K

Klingner, Richard E., 186, 206
Küntz, Michel, 259

L

Lavallée, Paul, 259

M

Martirena, Fernando, 285
Melander, John M., 186
Mickley, Jana, 285
Middendorf, Bernhard, 285
Mujumdar, Vilas, 138

N

Nichols, John M., 23
Nordmeyer, D. Herbert, 36

P

Press, Philip J., 206

R

Riopelle, Pierre, 259

S

Sanders, John P., 122
Seaverson, Eric, 122
Sheehan, Michael S., 3
Sickels-Taves, Lauren B., 3
Swift, David S., 73

T

Tate, Michael J., 51
Thomas, Robert D., 138, 170, 206
Thompson, Jason J., 170
Thomson, Margaret L., 61, 88

W

Walloch, Craig T., 170, 206

Copyright©2002by ASTM International www.astm.org

SUBJECT INDEX

A

Absorption testing, 114
Acid rain, 51
Aging, 224
Agriculture waste, 285
Air barriers, 241
Analysis of variance, 206
Anomalous diffusion, 259
Ashes, 36, 285
Aspect ratio, 170
ASTM C 67, 97, 114, 122
ASTM C 109, 23
ASTM C 140, 138
ASTM C 206, 61
ASTM C 207, 23, 61
ASTM C 210, 61

ASTM C 216, 97
ASTM C 270, 23, 36
ASTM C 593, 88
ASTM C 595, 36
ASTM C 1157, 36
ASTM C 1329, 186, 206
ASTM C 1357, 186, 206
ASTM E 691, 186

B

Bias, 61, 114, 186, 206
Binders, 88
Bond strength, 206
Bond-wrench testing, 186, 206
Brick, 97, 114, 122
Building code, 241
Building materials, lime with pozzolanic mixture, 285

C

Calcination, 73
Capillary rise absorption test, 259
Cavity wall, 241
Cement-lime mortar, 51
Cladding systems, 155, 224
Clay, burnt, 285
Coatings, 97
Components of variance, 206
Compressive forces, 97
Compressive strength, 114, 138, 170
Concrete masonry unit, 138, 170
Condensation, interstitial, 241
Corrosion, 97
Coupon testing, 138
Crack sealing, 241
Cryogenic dilatometry, 122
Cryptoflorescence, 97

D

Dolomitic Type S hydrated lime, 51
Durability, 51, 97

E

Efflorescence, 51
Electron microscopy, 23
Emley plasticity, 61
Evaluation, 224
Exfiltration, 241

F

Facades, 224
Failure mechanisms, 224
Finishing hydrated lime, 61
Flexural bond strength, 206
Fly ash, 36
Freeze-thaw durability, 122

G

Glazed brick, 97
Grout, 170

H

Heat of hydration, 73
Height to thickness ratio, 138
Historic mortars, 3, 73
Historic stucco, 3
Hydrated lime, 23, 88
  plasticity, 61
Hydraulic lime, 88

I

Inductively coupled plasma-atomic emission spectroscopy, 51
Infiltration, 241
Inspection, 224
Insulation, 241
Inter-laboratory studies, 186, 206
IRA, 114

J

Joints, 241

L

Lateral anchors, 155

Length to thickness ratio, 138
Lime, 88
  in historic restorations, 3
Lime kiln, 73
Lime:sand mortar, 73

M

Magnesium hydroxide, 51
Masonry cement, high pozzolan, 36
Masonry conservation, 73
Masonry wall, 241, 285
Microstructure, 23
Moisture, 241
Morphology, 23
Mortar, 61, 170
Mortar cement, high pozzolan, 36
Mortars, 23, 206, 285
  high pozzolan, 36
  pozzolan-lime, 88

P

Plaster, 61
Plasticity, hydrated lime, 61
Porous building materials, 259
Pozzolan, 36, 88, 285
Precision, 61, 114, 186, 206
Predicted strength, 170
Prism strength, 170

Q

Quicklime, 73

R

Repeatability limit, 206
Reproducibility limit, 206
Residual expansion, 122
Restoration, 3
Rheology, 23

S

Sample size, 114
Sampling methods, 114
Sand, 23
Sealant, 241
Sealing tape, 241
Single wythe wall, 241
Skeletal frame buildings, 155
Solubility, 51
Sorptivity, 259
Spalling, 97
Specifications, historic mortars and stuccos, 3
Stack effect, 241
Standards, for historic structures, 3
Statistical variation, 114
Strength testing, 114
Stucco, 3, 61
Stucco cement, high pozzolan, 36
Sulfuric acid, 51

T

Tensile bond strength, 186, 206
Testing variables, 170, 206
Type S hydrated lime, 23, 51

V

Vapor retarder, 241
Veneer wall, 241
Vertical batch lime kiln, 73

W

Water absorption, 97, 259
Water content, 170
Workability, 23