

# Subject Index

## A

Acetate replica, for studying crack development, 227

Acoustic emission techniques, use of, to detect load corresponding to crack initiation, 644-660

Alternating-current potential drop technique  
for *J-R* curve testing, 367, 743  
for monitoring crack growth, 456, 460, 462, 465

Analysis and mechanisms  
assessing the dominant mechanism for size effect on CTOD values, 715-740  
boundary layer effects in cracked bodies, 775-788  
comparison of ductile crack growth resistance, 661-682  
dynamic crack propagation and branching under biaxial loading, 697-714  
dynamic *J-R* curve testing of a high strength steel, 741-774  
empirical surface crack solution for fatigue propagation analysis of notched components, 601-624  
extension of surface cracks during cyclic loading, 625-643  
minimum time criterion for crack instability in structural materials, 683-696  
predicted versus experimental stress for initiation of crack growth in specimens contain-

ing surface cracks, 644-660

stress intensity factors  
for circular ring, 559-572  
for circumferential surface cracks, 789-805  
weight functions of radial cracks, 573-600

Applications  
behavior of ductile iron and cast steel, 75-94  
fracture behavior of thick laminated composites, 124-135  
fracture mechanics to ship controllable pitch propeller crank ring, 5-21  
loading rate on dynamic fracture of reaction bonded silicon nitride, 95-107  
resistance curve approach to composite materials characterization, 108-123  
residual strength of boron/aluminum laminates, 136-152  
variable flaw shape analysis for reactor vessel under pressurized thermal shock loading, 41-58  
wide plate arrest test on weld joints of steel, 22-40

Arc bend geometries, 280-281

Arc bend specimens  
fracture testing with, 279-296  
aluminum tests, 291, 293  
steel tests, 289, 291

Arc support, 280

Arc-tension specimens,  $J_{Ic}$  testing using, 297-306

ASME Boiler and Pressure Vessel  
Code, 42, 52, 55

## ASTM

A 216: 78, 79

A 536: 78

A 710: 647, 660

E 8: 436, 544, 647

E 23: 437

E 399: 19, 77, 125, 131-132, 134,  
231, 258, 279, 289, 319, 354,  
356, 357, 364, 367, 381, 383,  
396, 420, 470, 646, 647, 695

E 616: 663

E 647: 236, 364

E 813: 18, 82, 86, 288, 297, 302,  
306, 365, 369, 372, 403, 410,  
424, 439, 442, 459, 460, 463,  
465, 467, 469, 470, 474, 475,  
486-487, 514, 515, 519, 544,  
646, 647, 663, 668, 742, 745,  
748-749, 769

ASTM A106 steel, 742

influence of partial unloadings  
range on *J-R* curves of, 364-  
378

*J* resistance curve analysis of, 435-  
453

ASTM A470 steel, 198, 200

ASTM A508 steel, 43

ASTM A533 steel, 43

ASTM A710 steel, 647

ASTM Subcommittee E24.06, 615

Automated photomicroscopic system  
(*see* Photomicroscopic sys-  
tem)

## B

Bauschinger effect, 206, 377

Bending, and application of fracture  
mechanics to ship controlla-  
ble pitch propeller crank ring,  
12-15, 37

## Biaxial loading

application of superposition prin-  
ciple to, 574, 582, 588, 594,  
599

dynamic crack propagation and  
branching under, 697-714

Bodner-Partom constitutive law, 266

Boron/aluminum laminates, resid-  
ual strength of, after fatigue  
loading, 136-152

## Boundary integral analysis

for solving stress-intensity factors,  
801

for solving tension loading, 59-60,  
65

Boundary layer effects, in cracked  
bodies, 775-788

Brittle fracture (*see also* Fracture be-  
havior; Fracture mechanics;  
Fracture toughness)

propagation of, 23

types of, 29-30

## C

Carbon-manganese steels, assessing  
size effects on CTOD values  
in ductile-to-brittle transition  
region, 715-740

Cast steel, fracture behavior of, 75-  
94

CCA test (*see* Compact crack arrest  
(CCA) test)

Center-cracked tension (M(T)), use  
of, in comparing fracture be-  
havior for laminate thickness,  
124-135

Ceramic failures, use of linear elastic  
fracture mechanics to ana-  
lyze, 96

Charpy impact test, 308

assessment of *J-R* curves obtained  
from precracked, 401-411

- correlation with HAZ-SCA test results and, 36-37
- differences between fracture mechanics tests and, in comparing fracture toughness of ductile iron and cast steel, 76-78, 79, 82, 83, 86, 88-89, 91-93
- relationship between HAZ-SCA results, 36-37
- use of, to determining strength and toughness requirements for the crank ring, 17-18
- Chord support, 280
- $C^*$  integral, and creep crack growth, 188-189, 192, 195, 200
- Circular ring, stress intensity factors for, with uniform array of radial cracks, 559-572
- Cladding, effect of, on toughness in reactor vessel steels, 49, 56
- Cleavage fracture, and weakest-link statistics, 715-740
- Closure phenomenon, 253-254
- Compact crack arrest (CCA) test, 34-35
  - correlation of, to SCA and wide plate tests, 38
- Compact tension (C(T)) specimens
  - for assessing  $J$ - $R$  curves, 401-411, 437, 439, 442-443, 445-446
  - automated photomicroscopic system study of, 231, 235, 237
  - for comparing fracture behavior for laminate thickness, 124-135
  - crack growth using the  $J$  integral in, 503, 511
  - fracture toughness testing of Zircaloy-2 pressure tube material, 379-400
  - $J_{Ic}$  testing of, 297, 300, 302
  - Mode II fracture testing of, 347-363
  - for testing effects of elastic unloadings on the  $J$  integral-resistance curves of ASTM A106 steel and 3-Ni steels, 364-378
  - for testing plastic energy dissipation, 544, 546, 548, 549, 550, 552-553
  - and viscoplastic fatigue, at elevated temperatures, 265, 268, 270, 274
- Composites
  - comparison of thick laminated graphite/epoxy, 124-135
  - resistance curve approach of characterization of, 108-122
- Cracked bodies, boundary layer effects in, 775-788
- Crack growth and propagation (*see also* Creep crack growth; Crack tip opening displacement; Fatigue crack growth and propagation; Radial cracks; Subcritical crack growth; Surface cracks)
  - and branching under biaxial loading, 697-714
  - comparison of predicted versus experimental stress for initiation of, in specimens with surface cracks, 644-660
  - computation of stable, using  $J$ -integral, 503-511
  - evaluation of environmental effect on, in high strength steel, with elastic-plastic fracture mechanics techniques, 512-541
  - influence of depth of, on resistance curves for three-point bend specimens in HY130, 454-484
  - minimum time criterion for instability, in structural materials, 683-696

- Crack growth and propagation (*cont.*)  
 in Mode II fracture specimens, 345-346  
 plastic energy dissipation as parameter to characterize, 542-555  
 in reaction-bonded silicon nitride, 95-107  
 in reactor vessel steels, 41-58  
 stress intensity factors for circular ring with uniform array of radial cracks, 559-572  
 in surface of circumferential plane of solid and hollow cylinders, 59-74  
 in Zircaloy-2, 384-386
- Crack tip constraint, 729
- Crack tip opening displacement (CTOD)  
 effect of depth on, 459, 460, 464, 469, 475-480  
 measurement of, during high-temperature fatigue, 253-264  
 size effects on values, in the ductile-to-brittle transition region, 715-740  
 and stress waves, 684, 690-693, 694  
 and testing weld joints of steel, 24-25, 27  
 fatigue, 25, 27  
 monotonic, 25, 27  
 and testing with ultrasonic method to determine, 415-434
- Crack tip parameter, 188-193, 194-198
- Creep crack growth, under non-steady-state conditions, 185-201
- Creep crack growth testing, 193-194
- Cryogenic use, application of stress intensity factor to fatigue strength analysis of welded Invar sheet for, 202-225
- C(T) (*see* Compact tension (C(T)) specimens)
- Cumulative damage model (*see* Linear cumulative damage model)
- Cumulative extension method, use of, to obtain resistance curves, 113-114
- Cyclic-dominated crack growth, 366
- Cyclic loading  
 elastic-plastic fracture resistance under, 417, 420, 422, 427  
 extension of surface cracks during, 625-643  
 and Mode II fatigue crack growth, 338-340, 342  
 and multiple fatigue cracks, 239, 241  
 and viscoplastic fatigue, 269-270  
 welded Invar steel under, 204, 212-213, 215-217, 220-221, 223-224
- Cyclic stress, in propeller crank rings, 6
- Cylinders  
 fracture testing with arc bend specimens made from, 279-295  
 growth behavior of surface cracks in circumferential plane of solid and hollow, 59-74
- ## D
- Data reduction, modified incremental polynomial method of, 236-237
- Deep compliance unloading, 374-375
- Deep elastic unloading, 367, 370-371
- Deformation theory model, 486
- Deformation plasticity theory formula, 747

- Deformation theory plasticity, 365
- Delamination, resistance curve approach to, 108-122
- Direct-current potential drop technique
  - for crack extension measurements, 437, 440, 441, 443, 445, 447, 527, 535
  - fracture toughness testing of Zircaloy-2, with, 379-400
  - for *J-R* curve testing, 366-368, 371-372, 375, 377, 743
- Direct fracture mechanics analysis, use of, in analyzing reactor vessel steels, 44
- $dJ/da$  analysis, 494-495
- $dJ/da$  theories
  - comparison of, with the *I* theory for
    - ductile tearing instability, 485-502
    - statement of, 489-491
- Drop tower *J-R* curve testing, 756, 759, 761, 765, 766
- Dual-gage procedure, for *J-R* curve testing, 367
- Ductile iron, fracture behavior of, 75-84
- Ductile fracture (*see also* Fracture behavior; Fracture mechanics; Fracture testing; Fracture toughness)
  - comparison of resistance in stainless steel, 661-682
  - computation of stable crack growth using *J*-integral, 503-511
  - evaluation of environmentally assisted cracking of high strength steel, 512-541
  - influence of crack depth on resistance curves for three-point bend specimens, 454-484
  - investigation of the *I* and  $dJ/da$ 
    - concepts for ductile tearing instability, 485-502
  - J*-resistance curve analysis, 435-453
    - plastic energy dissipation, 542-555
    - single-specimen determination of elastic-plastic fracture resistance by ultrasonic method, 415-434
- Ductile tearing instability
  - and crank ring material toughness, 17-18
  - investigation of the *I* and  $dJ/da$  concepts for, 485-502
- Ductile-to-brittle transition region, assessing size effects on CTOD values in, 715-740
- Dynamic crack arrest, in reaction-bonded silicon nitride, 96
- Dynamic finite element analysis (*see* Finite element analysis)
- Dynamic fracture (*see also* Fracture behavior; Fracture mechanics; Fracture testing; Fracture toughness)
  - behavior of ductile iron and cast steel, 75-94
  - effect of loading rate on, of reaction-bonded silicon nitride, 95-107
  - testing for toughness of 4340 steel, 307-328
- Dynamic loading (*see* Loading)
- Dynamic stress intensity factor (*see* Stress intensity factor)

## E

- Elastic compliance, 365
- Elastic compliance technique, for measuring crack extensions, 437, 441, 442, 443, 445
- Elastic-plastic analysis, use of, to measure stress in testing for

- fatigue strength of welded Invar sheet, 206-207, 212-213, 215-217, 220-221, 224-225
- Elastic-plastic fracture mechanics techniques, evaluating environmentally assisted cracking of high strength steel using, 512-541
- Elastic-plastic fracture resistance  $R$ -curve, 422, 424-426
- Elastic-plastic fracture resistance, single-specimen determination of, by ultrasonic method, 415-434
- Elastic-plastic materials, finite element studies of, 346
- Elastic unholdings, effects of, on the  $J_I$ - $R$  curves of ASTM A106 steel and 3-Ni steels, 364-378
- Electric potential monitoring, for studying crack development, 227
- Empirical surface crack solution, for fatigue propagation analysis of, 601-624
- Energy rate  $I$  balance method, 493-494
- Energy release rate  $I$ , 499-500  
effect of compliance on, 501
- Energy rate  $I$  theory  
comparison of, with the  $T$  or  $dJ/da$  theories for ductile tearing instability, 485-502  
statement of, 487-489
- ESSO test, use of, to evaluate brittle fracture arrest capability of steel materials, 27, 38
- surement during high-temperature, 253-264  
study of viscoplastic, in superalloys at elevated temperatures, 265-275
- Fatigue crack growth and propagation (*see also* Crack growth and propagation)  
automated photomicroscopic system for monitoring, 226-238  
interactive effects of frequency loading on, of Inconel 718, 169-184  
in propeller crank rings, 68  
empirical surface crack solution for, 601-624  
hold-time effects in elevated temperature, 155-168  
investigation of multiple, at notches, 239-252  
Mode II, 329-346
- Fatigue flaw growth analysis (*see also* Flaw shape growth analysis of surface cracks in circumferential plane of solid and hollow cylinders), 59-74
- Fatigue loading (*see also* Loading)  
residual strength of boron/aluminum laminates after, 136-152
- Fatigue propagation analysis, empirical surface crack solution for, 601-624
- Fatigue strength analysis, application of stress intensity factor, for welded Invar sheet for cryogenic use, 202-225
- FEM (*see* Finite element method)
- Fiber  
damage resulting from fatigue loading of boron/aluminum laminates, 139, 140, 144, 147  
effect of types of, on resistance to delamination growth, 116, 121

## F

Fatigue  
near-tip crack displacement mea-

Finite element analysis

- for analyzing stress intensity factors for radial cracks of unequal depth, 559-572
- for analyzing weight functions of radial cracks, 573-600
- for calculating stress-intensity factors for circumferential surface cracks in pipes and rods, 792-793, 803-804
- for elastic-plastic materials, 346
- for estimating magnitude of crank ring flange load, 9, 10-12
- for measuring stress in testing for fatigue strength of welded Invar sheet, 206-207
- for Mode II fracture toughness testing, 349, 351-354
- for reaction bonded silicon nitride, 98
- for solving tension and bending problems, 60, 65
- for viscoplastic fatigue in superalloys, 268

Flaw shape change analysis (*see also* Fatigue flaw growth analysis)

- control parameters for, 48-51
- method of, 43
  - determination of  $K_I$  for surface flaws, 43-48
  - determination of material properties, 43
  - results of, 52-55
  - sample calculations, 51

4340 steel (*see* High strength steel)

Fracture behavior

- of ductile iron and cast steel, 75-84
- effect of laminate thickness on, of laminated graphite/epoxy composites, 124-135

Fracture mechanics

- application of, to ship controllable

pitch propeller crank ring, 5-21

- extension of surface cracks during cyclic loading, 625-643
- and stress analysis of crack growth in specimens containing surface cracks, 644-660

Fracture testing (*see also* Fracture toughness)

- of arc-bend specimens, 279-296
- of compact Mode II fracture specimen, 347-363
- of ductile iron versus cast steel, 76, 77, 82, 86
- $J_{Ic}$  testing using arc-tension specimens, 297-306
- of  $J$ - $R$  curves obtained from pre-cracked Charpy specimens, 401-411
- of Mode II fatigue crack growth specimens, 329-346
- of partial unloadings range on the  $J_I$ - $R$  curves of ASTM A106 and 3-Ni steels, 364-378
- with the one-point-bend impact test, 307-328
- of Zircaloy-2 pressure tube material with radial hydrides using direct-current potential drop, 379-400

Fracture toughness (*see also* Fracture testing)

- in boron/aluminum laminates, 136-152
- in ductile iron versus cast steel, 75-94
- in Perspex, 347-363
- in reactor vessel steels, 43, 48-49, 56
- in resins, 108-109
- in stainless steel, 661-682
- in thick laminate composites, 124-135
- in weld joints of steel, 23, 24

Fracture toughness gradient in the base metal, 49

Frequency loading, interactive effects of, on fatigue crack growth in Inconel 718, 169-184

Frozen stress photoelasticity (*see* Photoelasticity)

## G

Graphite/epoxy composites, comparison of fracture toughness of, 124-135

Green's function, 574

## H

HAZ-SCA test

development of, 27, 29-30

effect of nickel content of base plate on results, 35-36

relationship between Charpy test results and, 36-37

results of, 30, 32, 34

High density moiré interferometry (*see* Moiré inteferometry)

High frequency loading (*see* Frequency loading)

High strength steel

ductile tearing instability in, 485-502

evaluation of environmentally assisted cracking of, using elastic-plastic fracture mechanics techniques, 512-541

fracture toughness of, 307-328

influence of crack depth on resistance curves for three-point bend specimens in, 454-484

*J-R* curve testing of, using the key curve and multispecimen techniques, 741-774

plastic energy dissipation as parameter to characterize crack growth in, 542-555

High temperature (*see* Temperature)

Hold-time effects, in elevated temperature fatigue crack propagation, 155-168

Homalite 100, dynamic crack propagation and branching under biaxial loading, 697-714

Hooke's law, 266

HY-130 high strength steel (*see* High strength steel)

Hydrogen embrittlement mechanism, and environmentally assisted cracking, 513, 531, 535

## I

*I* concept (*see* Energy rate *I* balance method; Energy release rate *I*; Energy rate *I* theory)

Immediate rate *J-R* curve testing, 754-756

Impact toughness testing, of high strength steel, 744, 749

Inconel 718

effects of hold times on fatigue crack growth rate of, 155-168

interactive effects of frequency loading on fatigue crack growth of, 169-184

near-tip crack displacement measurements during high-temperature fatigue in, 253-264

prediction of surface cracks in, 610-612, 619

Incremental extension method, for obtaining resistance curves, 112-113

Interference pressure, pin-loaded hole with, 590, 592

Interferometry (*see also* Moiré interferometry)



use of, to study near-tip crack displacement during high-temperature fatigue, 253-264  
 Invar, stress analysis of, 202-225  
 Irradiation damage, in reactor vessel steels, 43, 56

## J

### *J*-integral

for computing stable crack growth using, 503-511  
 for evaluating environmental cracking of high strength steel using, 512-541  
 for measuring fracture toughness under elastic-plastic conditions, 365

### *J-R* curves, 366-367

applicability of numerical smoothing to, 769  
 applicability of, to ship controllable pitch propeller crank ring, 15-16  
 assessment of, in precracked Charpy specimens, 401-411  
 for ASTM A106 steel 8-in.-diameter pipe and compact specimens, 435-453  
 in comparing ductile crack growth resistance in stainless steel, 661-682  
 influence of partial unloadings range on, of ASTM A106 and 3-Ni steels, 364-378  
 single-specimen determination of, 425-426  
 in testing of a high strength steel using the key curve and multispecimen techniques, 741-774

### *J<sub>1c</sub>*

and arc-tension specimens, 297-306

in comparing ductile iron and cast steel, 82, 89, 92-93  
*J<sub>1d</sub>*, in comparing ductile iron and cast steel, 82, 89

## K

### Key curve analysis

*J-R* curve testing of a high strength steel with, 747-748  
 load drop method as, 401-402

*K<sub>I</sub>* (see Stress intensity factor)

### *K<sub>Ic</sub>*

in characterizing unstable crack growth, 380, 383, 390, 385-396  
 in comparison of ductile iron and cast steel, 76, 89, 92-93  
 in determining fracture toughness, 364  
 in 4340 steel, 320  
 for fracture initiation toughness, 25  
 in precracked Charpy specimens, 404, 408

### *K<sub>Ia</sub>*

in comparison of ductile iron and cast steel, 82, 83, 86, 88-89, 93  
 in 4340 steel, 319-322  
 and reaction-bonded silicon nitrate, 96

## L

### Laminates

effect of thickness of, on fracture behavior of laminated graphite/epoxy composites, 124-135  
 residual strength of boron/aluminum, after fatigue loading, 136-152

Linear cumulative damage model, use of, to predict fatigue

- crack growth, 157-160, 165, 166-167
- Linear elastic fracture mechanics (LEFM)
  - in analyzing boundary layer effects in cracked bodies, 775, 785-788
  - in analyzing ceramic failures, 96
  - in characterizing fatigue fracture response, 365
  - in characterizing sustained load crack growth, 156
  - in determining fracture toughness, 127
  - in estimating  $n$ , 486
  - in predicting crack instability, 683-696
  - in studying crack growth, 227, 243, 512-513
  - in variable flaw shape analysis, 43, 56
- Load drop analysis, for measuring crack growth in Charpy specimens, 401-402, 405, 407, 409, 410-411
- Loading (*see also* Frequency loading)
  - dynamic, and quasi-static  $J$  analysis, 770-771
  - effect of rate of, on dynamic fracture of reaction-bonded silicon nitride, 95-107
- Low frequency loading (*see* Frequency loading)
- Low temperature (*see* Temperature)

## M

- Mann-Whitney test, 721-723
- Matrix damage, resulting from fatigue loading of boron/aluminum laminates, 147, 151
- Maximum tangential stress theory, 34, 346
- Merkle-Corten analysis, 298

Microhardness mapping, in comparing ductile iron and cast steel, 82, 91

Minimum time criterion, for crack instability in structural materials, 683-696

## Mode I

- delamination growth resistance of composites under, 108-123
- finite element analysis of, 349, 351, 354-357
- stress intensity studies of, 330-331, 346
- and the weight function concept, 573-600

## Mode II

- fatigue crack growth specimen development, 329-346
- fracture testing of, 347-363

Modified incremental polynomial method of data reduction, 236-237

Modified mapping collocation (MMC), accuracy of, in calculating stress intensity factors for shallow cracks, 570

Moiré interferometry (*see also* Interferometry)

- in analyzing boundary layer effects in cracked bodies, 775-779

Multi-degree-of-freedom model, for crack development, 241

Multiple unloading  $R$ -curve determination, 427-429

Multispecimen method for  $J$ - $R$  curve testing

- of ASTM A106 and 3-Ni steels, 365, 366, 369, 372-373, 377
- of a high strength steel with, 748-749

## N

Nickel-base superalloys (*see also* Inconel 718; Superalloys)

sustained load crack growth rates  
in, 156

Nodal-force method, use of, to calculate stress intensity factors, 791

Nodal release, and computation of stable crack growth using the  $J$  integral, 503-511

Non-steady-state conditions, creep crack growth under, 185-201

Notch constraint, 727, 729, 731

Numerical smoothing, applicability, of, to  $J$ - $R$  curve evaluation, 767, 769

## O

1D/2D flux effect, in reactor vessel steels, 50, 55, 56

One-point-bend impact test  
estimation of the duration  $T_0$ , 324-325  
estimation of the maximum amplitude  $K_I^{\max}$ , 325-327  
investigation and application of, 307-328

## P

Perspex (*see* Polymethyl methacrylate (PMMA))

Photoelasticity  
for analyzing boundary layer effects in cracked bodies, 775-788  
for examining Mode II specimens, 348, 349  
for studying high speed crack propagation, 697-714

Photomicroscopic system, use of automated, for monitoring the growth of fatigue cracks, 226-238

Pin-joint loading, application of su-

perposition principle to, 574, 588, 590

Pin-loaded hole with interference pressure, 590, 592

Pipe specimen fracture toughness test results, 446-447, 449-450, 452

Plastic energy dissipation, as parameter to characterize crack growth, 542-555

Plexiglas (*see* Polymethyl methacrylate (PMMA))

Polymethyl methacrylate (PMMA)  
fracture toughness of, 346, 347-363  
prediction of surface cracks in, 615-616

Pulse echo technique, 417

## Q

Quasi-static  $J$  analysis, application of, to dynamic loading, 770-771

Quasi-static  $J$ - $R$  curve testing, of a high strength steel, 749, 752, 754

## R

Radial cracks  
stress intensity factors for circular ring with uniform array of, 559-572  
weight functions of, 573-600

$R$ -curve-dominated crack growth, 366

Reaction-bonded silicon nitride (RBSN), effect of loading rate on dynamic fracture of, 95-107

Reactor vessels, application of variable flaw shape analysis to under pressurized thermal shock loading, 41-58

Recrystallization, 543

Residual life prediction, for subcomponent specimens, under complex loadings, 602-603, 612, 614-615, 620

#### Resins

fracture toughness in, 108-109  
resistance of, to delamination growth, 116, 121-122

#### Resistance curves, 108-123

cumulative extension method, 113-114  
for ductile tearing instability, 486-487, 488, 491, 497-501  
incremental extension method, 112-113  
influence of crack development on, for three-point bend specimens in HY130, 454-484  
influence of environment on, 117  
influence of fiber-resin combination on, 116  
influence of porosity on, 117, 119  
resistance for AS1/3501-6 laminate, 114, 116  
for T300/5208, 119  
for tough materials, 121

$RT_{NDT}$ , 48-49, 52-53, 55, 56

### S

Scanning electron microscope (SEM)  
for studying crack development, 227, 254

for studying fracture surfaces, 668, 672, 679

for studying microfracture, 322

for studying Mode II fatigue crack growth, 343

SE(B) specimen (*see* Three-point bend specimens)

Ship components (*see* Ship controllable pitch propeller crank ring)

Ship controllable pitch propeller crank ring, application of fracture mechanics to, 5-21

#### Short crack arrest (SCA) test

correlation of CCA test to, 38-39

development of, 27, 29-30

modification of, 37-38

results, 30, 32, 34

#### Single-specimen testing

of elastic-plastic fracture resistance by ultrasonic method, 415-434

of *J-R* curves

in ASTM A106 and 3-Ni steels, 367, 370-371, 377

in stainless steel, 663, 666

Size effects of crack tip opening displacement values in the ductile-to-brittle transition region, 715-740

#### Stainless steel (*see also* Cladding)

comparison of ductile crack growth resistance in, 661-682

Steel (*see* Carbon-manganese steel; Cast steel; High Strength steel; Stainless steel)

Strain gage measurements, use of, in estimating magnitude of crank ring flange load, 9-10

Stress analysis (*see* Stress intensity factor)

#### Stress intensity factor

and analyzing boundary layer effects in cracked bodies, 775-788

and analyzing ceramic failures, 96  
and analyzing fatigue strength of welded Invar sheet for cryogenic use, 202-225

for circular ring with radial cracks of unequal depth, 559-572

for circumferential surface cracks in pipes and rods under tension and bending loads, 789-805

and crack propagation and branching under biaxial loading, 697-714

- evaluation of, for radial cracks emanating from circular hole, 573-600
  - for initiation of crack growth in specimens containing surface cracks, 644-660
  - in reaction-bonded silicon nitrate, 96, 101-102
  - for reactor vessel steels, 42, 43-48
  - for surface cracks
    - in finite solids, 601-624
    - multiple at notches, 241-242
    - in solid and hollow cylinders, 59, 60, 65, 68, 70, 72
  - and use of one-point-bend impact test, 307-328
  - Stress intensity histories, and minimum time criterion for crack instability in structural materials, 683-696
  - Stress wave loading, and minimum time criterion for crack instability, 683-696
  - Structural materials, minimum time criterion for crack instability in, 683-696
  - Subcritical crack growth (*see also* Crack growth and propagation; Fatigue crack growth and propagation)
    - automated photomicroscopic system for monitoring crack growth, 226-227
    - creep crack growth under non-steady state conditions, 185-201
    - hold-time effects in elevated temperature fatigue crack propagation, 155-168
    - interactive effects of frequency loading in Inconel 718, 169-184
    - investigation of multiple fatigue cracks, 239-252
    - near-tip crack displacement measurements during high temperature fatigue, 253-264
    - stress intensity factors and fatigue strength analysis of welded Invar steel, 202-225
    - viscoplastic fatigue at elevated temperatures, 265-275
  - Superalloys (*see also* Inconel 718; Nickel-base superalloy)
    - viscoplastic fatigue in, at elevated temperatures, 265-275
  - Superposition principle
    - in analyzing stress intensity factors, 44, 602-603, 605, 620
    - and biaxial loading, 574, 582, 588, 594, 599
    - and pin-joint loading, 574, 588, 590, 594, 599
    - and weight function concept, 575, 576
  - Surface cracks (*see also* Crack growth and propagation; Fatigue crack growth and propagation)
    - comparison of predicted versus experimental stress for initiation of, in specimens with, 644-660
    - determination of, in reaction vessel steels, 43-48
    - empirical solution for fatigue propagation analysis of notched components, 601-624
    - extension of, during cyclic loading, 625-643
    - growth behavior of, in cylinders, 59-74
    - stress-intensity factors for, in pipes and rods, 789-805
- T**
- T* analysis, 496-497
  - Tearing instability theory, 742

Temperature (*see also* Cryogenic use)

effect of low on wide plate arrest test on steel weld joints, 22-40

effect of elevated, on viscoplastic fatigue in superalloys, 265-275

effect of, on near-tip crack displacement measurements during fatigue, 253-264

influence of, on creep crack growth behavior, 198

10% compliance unloading, 373

10% elastic unloading, 370

Tensile testing, of high strength steels, 743, 749

Tension loading, problem of, 59-60

Thermal shock loading, application of variable flaw shape analysis, to reactor vessel under pressurized, 41-58

Thick laminates (*see* Laminates)

3-Ni steel (*see* ASTM A106 steel)

Three-point bend (SE(B)) specimens in arc bend geometries, 280

in assessing  $J$ - $R$  curves, 401-411

in comparing fracture behavior for laminate thickness, 124-135

derivation of  $N_e$  for side-grooved, 482-483

derivation of  $N_p$ , 480-481

and influence of crack depth on resistance curves for, 454-484

$J_{Ic}$  testing using, 297

and stress intensity history, 309, 323

for testing plastic energy dissipation, 544, 547, 553

Time-dependent fracture mechanics (TDFM), 185

Titanium, multiple fatigue cracks in, 244-251

Toughness (*see* Fracture toughness)

## U

Ultrasonic method, single-specimen determination of elastic-plastic fracture resistance by, 415-434

Unloading effect, on the  $J$ - $R$  curve, 372-376

## V

Variable flaw shape analysis, application of, to reactor vessel under pressurized thermal shock loading, 41-58

Virtual crack extension (VCE) method

in determining  $K_I$  distribution of semi-elliptical cracks in a reactor vessel, 44-48

in evaluating weight functions of radial cracks, 573-600

Viscoplastic fatigue, in superalloys at elevated temperatures, 265-275

Void growth, 346

## W

Warm prestressing (WPS) effect, in reactor vessel steels, 49, 51, 53-54, 56

Waspaloy, multiple fatigue cracks in, 244-251

Weakest-link statistics, and cleavage fractures, 715-740

Weibull distribution, 720, 721, 723

Weight functions, of radial cracks, 573-600

Weight function technique, 620

in computing  $K_I$  for reactor vessel steels, 43-44

and stress intensity factors for surface cracks in finite solids, 602, 605-606, 620

Welded steel joints  
 fatigue strength analysis of, for  
 cryogenic use, 202-225  
 wide plate arrest test, for low-tem-  
 perature application, 22-40  
 Wide plate arrest test (SCA test)  
 correlation of CCA test to, 38

low temperature application on  
 steel weld joints, 22-40

## Z

Zircaloy-2 pressure tube material,  
 fracture toughness testing of,  
 379-400