

Subject Index

A

Aardelite aggregate, 27
 Absorption, initial rate
 of, 5, 85, 217, 324
 Aggregate
 C 144: 63
 gradation, 63
 lightweight, 27
 Air content, 85, 164
 ready-mixed mortar, 123
 Anchor systems, stone, 279
 ASTM standards
 C 67: 5
 C 90: 27, 339
 C 140: 339
 C 144: 63
 C 270: 108, 123, 164,
 194, 206, 339, 350
 C 476: 47, 206
 C 514: 85
 C 618: 27
 C 652: 263, 339
 C 780: 123, 147, 194
 C 902: 38
 C 1019: 47
 C 1072: 85, 235, 339, 350
 E 72: 235
 E 447: 339
 E 514: 299, 394
 E 518: 235
 Attenuation, 366

B

Barriers, sound
 attenuation, 366
 insertion loss, 366
 transmission loss, 366
 Bentonite, 108
 Blast resistant masonry, 413
 Bond
 C 1072: 85, 235, 339, 350
 strength, 85, 123, 217, 235
 wrench, 85, 217, 350
 Breathing, 324
 Brick
 C 652: 263, 339
 clay, 5, 85, 217
 hollow, 263
 paving, 38
 slip resistance, 38
 wall panels, 366

water penetration, 5, 85, 299
 Building code, blast resistant
 design incorporation, 413

C

Carbonation, 173
 Cavity walls, 173, 299, 394
 Cement (See Mortar)
 Chlorides, 173
 Coefficient of friction, 38
 Compressive strength, 47, 85,
 164, 206, 263, 403
 ready-mixed mortar, 123, 147
 shape effects on, 147, 194
 Concrete masonry units, 235,
 350, 403
 C 90: 27, 339
 masonry grout, 47
 Corrosion, reinforcing
 metal, 173, 324
 Cube compressive strength,
 147, 194, 206
 Cylinder compressive strength,
 147, 194, 206

D

Detonation, 413
 Differential movement, 309
 Drainage wall, 299
 Durability, 324

E

Earthquake resistance, masonry
 walls, 378
 Efflorescence, 324
 Explosion resistant design, 413
 Extended-life mortar, 123

F

Flashing, 394
 Flexural bond (See Bond)
 Flexural design, 403
 Fly ash
 C 618: 27
 Friction, coefficient of, 38

G

Grout, 403
 C 476: 47, 206
 C 1019: 47
 masonry, 47
 portland cement lime, 206
 physical properties, 47

I

Industry, masonry, practices,
 309, 324, 413
 Initial rate of absorption, 5,
 85, 217, 324

J

Japan and United States masonry
 programs, 378, 403

K

Kerfs, 279

L

Leakage, 299, 394
 Lime deposits, 324

M

Masonry (See also Mortar)
 brick
 C 652: 263, 339
 clay, 5, 85, 217
 hollow, 263
 paving, 38
 slip resistance, 38
 wall panels, 366
 water penetration, 5, 85,
 299
 cavity, 394
 clay, 235
 concrete units, 27, 47, 235,
 339, 350, 403
 construction, problems and
 cures, 309, 324
 design, blast-resistant, 413
 industry practices, 309, 324,
 413
 leakage, 299, 394
 nondestructive evaluation, 248
 mechanical properties, 248
 panels, 366
 prisms, 108, 123

brick, 217, 263, 339
 C 1072: 85, 339
 concrete masonry, 47, 217,
 339, 350, 403

E 447: 339

research programs, 339, 378,
 403

ultimate strength, 403, 413
 wall assemblies, 85, 108,
 173, 309, 339, 378

water penetration, 5, 85,
 123, 299

control, 309

E 514: 299, 394

Metal corrosion, in masonry, 173

Modelling, 413

Modulus of elasticity, 47, 206, 263

Moisture control (See Water
 penetration and Water control)

Moment capacity, 403

Montmorillonite, 108

Mortar, 47, 173

C 270: 108, 123, 164, 194,
 206, 339, 350

C 780: 123, 147, 194

conventional, 147, 164, 350

extended-life, 123

masonry cement, 63, 85,
 164, 194, 217, 350

plasticizers, 108

portland cement lime, 63, 164,
 194, 206, 235, 263, 350

ready-mixed, 123, 147, 194

N

Noise reduction, 366

Nondestructive evaluation, 248

P

Particle size distribution, 85

Paving brick

C 902: 38

Plasticizers, masonry mortar, 108

Portland cement (See Mortar)

Prisms, 108, 123

brick, 217, 263, 339

C 1072: 85, 339

concrete masonry, 47, 217,
 339, 350, 403

E 447: 339

Pull-outs, 279

R

Ready-mixed mortar, 123, 147, 194

S

Seismic resistance, concrete
 masonry walls, 378
 Slip resistance test, 38
 Spalling, 324
 Steel, 173
 Stone veneer, 279
 Strength tests
 E 72: 235
 Stress parameters, 403
 Striping, 324
 Suction, initial rate of (See
 Absorption, Initial rate of)

T

Tensile stress values, flexural, 235
 Tile, clay, sampling and testing
 C 67: 5
 Transverse tests, 350

U

Ultimate strength, 403, 413
 United States and Japan
 masonry programs, 378, 403

W

Walls
 air blast test, 413
 assemblies, 85, 108, 173,
 309, 339, 378
 drainage test, 394
 lateral load, 350
 masonry coupled, 378
 panels, 366
 ties, 173, 279
 veneer, 173, 279
 Water penetration, 5, 85, 123, 299
 control, 309
 E 514: 299, 394
 Water retention, 85, 123, 164
 Wire ties, 279
 Workability
 masonry, 108
 ready-mixed mortar, 123

Z

Zinc, 173